



US009297503B2

(12) **United States Patent**
Van De Ven et al.

(10) **Patent No.:** **US 9,297,503 B2**
(45) **Date of Patent:** **Mar. 29, 2016**

(54) **LIGHTING DEVICE AND LIGHTING METHOD**

(71) Applicant: **CREE, INC.**, Durham, NC (US)

(72) Inventors: **Antony Paul Van De Ven**, Hong Kong (CN); **Gerald H. Negley**, Durham, NC (US)

(73) Assignee: **Cree, Inc.**, Durham, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 158 days.

(21) Appl. No.: **14/252,855**

(22) Filed: **Apr. 15, 2014**

(65) **Prior Publication Data**

US 2014/0226326 A1 Aug. 14, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/354,510, filed on Jan. 20, 2012, now Pat. No. 8,733,968, which is a continuation of application No. 12/893,331, filed on Sep. 29, 2010, now Pat. No. 8,123,376, which is a
(Continued)

(51) **Int. Cl.**
F21K 99/00 (2010.01)
H05B 33/08 (2006.01)
F21Y 101/02 (2006.01)

(52) **U.S. Cl.**
CPC ... **F21K 9/56** (2013.01); **F21K 9/00** (2013.01);
H05B 33/0857 (2013.01); **F21Y 2101/02**
(2013.01); **Y10S 362/80** (2013.01)

(58) **Field of Classification Search**
CPC F21K 9/00; F21K 9/56; F21Y 2101/02;
H05B 33/0857; Y10S 362/80
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,805,937 A 4/1974 Hatanaka et al.
3,875,456 A 4/1975 Kano et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 1355936 A 6/2002
CN 1871714 A 11/2006
(Continued)

OTHER PUBLICATIONS

Japanese Office Action (and translation provided by foreign counsel) from a corresponding Japanese patent application bearing a mailing date of May 12, 2015, 37 pages.

(Continued)


Primary Examiner — Stephen F Husar

(74) *Attorney, Agent, or Firm* — Burr & Brown, PLLC

(57) **ABSTRACT**

A lighting device comprising first and second groups of solid state light emitters, which emit light having peak wavelength in ranges of from 430 nm to 480 nm, and first and second groups of lumiphors which emit light having dominant wavelength in the range of from 555 nm to 585 nm. In some embodiments, if current is supplied to a power line, a combination of (1) light exiting the lighting device which was emitted by the first group of emitters, and (2) light exiting the lighting device which was emitted by the first group of lumiphors would have a correlated color temperature which differs by at least 50 K from a correlated color temperature which would be emitted by a combination of (3) light exiting the lighting device which was emitted by the second group of emitters, and (4) light exiting the lighting device which was emitted by the second group of lumiphors.

25 Claims, 4 Drawing Sheets



Related U.S. Application Data

continuation of application No. 11/736,799, filed on Apr. 18, 2007, now Pat. No. 7,828,460.

- (60) Provisional application No. 60/793,518, filed on Apr. 20, 2006, provisional application No. 60/792,860, filed on Apr. 18, 2006.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,927,290	A	12/1975	Denley	6,703,173	B2	3/2004	Lu et al.
4,120,026	A	10/1978	Tsuchihashi et al.	6,712,486	B1	3/2004	Popovich et al.
4,325,146	A	4/1982	Lennington	6,737,801	B2	5/2004	Ragle
4,408,157	A	10/1983	Beaubien	6,744,194	B2	6/2004	Fukasawa et al.
4,420,398	A	12/1983	Castino	6,762,563	B2	7/2004	St-Germain
4,710,699	A	12/1987	Miyamoto	6,784,463	B2	8/2004	Camras et al.
4,772,885	A	9/1988	Uehara et al.	6,791,257	B1	9/2004	Sato et al.
5,087,883	A	2/1992	Hoffman	6,805,600	B2	10/2004	Wang et al.
5,166,815	A	11/1992	Elderfield	6,817,735	B2	11/2004	Shimizu et al.
5,264,997	A	11/1993	Hutchisson et al.	6,841,804	B1	1/2005	Chen et al.
5,407,799	A	4/1995	Studier	6,851,834	B2	2/2005	Leysath
5,410,519	A	4/1995	Hall et al.	6,880,954	B2	4/2005	Ollet et al.
5,477,436	A	12/1995	Betling et al.	6,882,101	B2	4/2005	Ragle
5,563,849	A	10/1996	Hall et al.	6,914,267	B2	7/2005	Fukasawa et al.
5,803,579	A	9/1998	Turnbull et al.	6,936,857	B2	8/2005	Doxsee et al.
5,851,063	A	12/1998	Doughty et al.	6,967,116	B2	11/2005	Negley
5,959,316	A	9/1999	Lowery	6,980,176	B2	12/2005	Matsumoto et al.
5,998,925	A	12/1999	Shimizu et al.	7,005,679	B2	2/2006	Tarsa et al.
6,066,861	A	5/2000	Hohn et al.	7,008,078	B2	3/2006	Shimizu et al.
6,069,440	A	5/2000	Shimizu et al.	7,009,343	B2	3/2006	Lim et al.
6,076,936	A	6/2000	George	7,014,336	B1	3/2006	Ducharme et al.
6,084,250	A	7/2000	Justel et al.	7,023,019	B2	4/2006	Maeda et al.
6,095,666	A	8/2000	Salam	7,026,756	B2	4/2006	Shimizu et al.
6,132,072	A	10/2000	Turnbull et al.	7,061,454	B2	6/2006	Sasuga et al.
6,153,971	A	11/2000	Shimizu et al.	7,066,623	B2	6/2006	Lee et al.
6,212,213	B1	4/2001	Weber et al.	7,071,616	B2	7/2006	Shimizu et al.
6,234,648	B1	5/2001	Borner et al.	7,083,302	B2	8/2006	Chen et al.
6,252,254	B1	6/2001	Soules	7,093,958	B2	8/2006	Coushaine
6,255,670	B1	7/2001	Srivastava et al.	7,095,056	B2	8/2006	Vitta et al.
6,278,135	B1	8/2001	Srivastava et al.	7,102,172	B2	9/2006	Lynch et al.
6,292,901	B1	9/2001	Lys et al.	7,116,308	B1	10/2006	Heeks et al.
6,294,800	B1	9/2001	Duggal et al.	7,118,262	B2	10/2006	Negley et al.
6,319,425	B1	11/2001	Tasaki et al.	7,125,143	B2	10/2006	Hacker
1,335,538	A1	1/2002	Prutchi et al.	7,126,274	B2	10/2006	Shimizu et al.
6,335,538	B1	1/2002	Prutchi et al.	7,135,644	B1	11/2006	Gilliland et al.
6,337,536	B1	1/2002	Matsubara et al.	7,135,664	B2	11/2006	Vornsand et al.
6,348,766	B1	2/2002	Ohishi et al.	7,144,121	B2	12/2006	Minano et al.
6,350,041	B1	2/2002	Tarsa et al.	7,164,231	B2	1/2007	Choi et al.
6,357,889	B1	3/2002	Duggal et al.	7,207,691	B2	4/2007	Lee et al.
6,394,621	B1	5/2002	Hanewinkel	7,213,940	B1	5/2007	Van De Ven et al.
6,429,583	B1	8/2002	Levinson et al.	7,215,074	B2	5/2007	Shimizu et al.
6,441,558	B1	8/2002	Muthu et al.	7,232,212	B2	6/2007	Iwase
6,480,299	B1	11/2002	Drakopoulos et al.	7,239,085	B2	7/2007	Kawamura
6,501,100	B1	12/2002	Srivastava et al.	7,250,715	B2	7/2007	Mueller et al.
6,504,179	B1	1/2003	Ellens et al.	7,255,457	B2	8/2007	Ducharme et al.
6,513,949	B1	2/2003	Marshall et al.	7,256,557	B2	8/2007	Lim
6,522,065	B1	2/2003	Srivastava et al.	7,322,732	B2	1/2008	Negley et al.
6,538,371	B1	3/2003	Duggal et al.	7,329,024	B2	2/2008	Lynch et al.
6,550,949	B1	4/2003	Bauer et al.	7,329,988	B2	2/2008	Shimizu et al.
6,552,495	B1	4/2003	Chang	7,358,954	B2	4/2008	Negley
6,577,073	B2	6/2003	Shimizu et al.	7,362,048	B2	4/2008	Shimizu et al.
6,578,986	B2	6/2003	Swaris et al.	7,365,485	B2	4/2008	Fukasawa et al.
6,592,810	B2	7/2003	Nishida et al.	7,387,405	B2	6/2008	Ducharme et al.
6,600,175	B1	7/2003	Baretz et al.	7,404,652	B2	7/2008	Ng et al.
6,600,324	B2	7/2003	St-Germain	7,422,504	B2	9/2008	Maeda et al.
6,603,258	B1	8/2003	Mueller-Mach et al.	7,453,195	B2	11/2008	Radkov
6,608,485	B2	8/2003	St-Germain	7,473,934	B2	1/2009	Nagai et al.
6,614,179	B1	9/2003	Shimizu et al.	7,474,044	B2	1/2009	Ge
6,616,862	B2	9/2003	Srivastava et al.	7,518,150	B2	4/2009	Aihara
6,624,350	B2	9/2003	Nixon et al.	7,531,960	B2	5/2009	Shimizu et al.
6,636,003	B2	10/2003	Rahm et al.	7,564,180	B2	7/2009	Brandes
6,642,666	B1	11/2003	St-Germain	7,569,987	B2	8/2009	Naitou
6,685,852	B2	2/2004	Setlur et al.	7,682,848	B2	3/2010	Shimizu et al.
6,686,691	B1	2/2004	Mueller et al.	7,828,460	B2	11/2010	Van De Ven et al.
6,692,136	B2	2/2004	Marshall et al.	7,855,092	B2	12/2010	Shimizu et al.
				7,901,959	B2	3/2011	Shimizu et al.
				7,915,631	B2	3/2011	Shimizu et al.
				7,918,581	B2	4/2011	Van De Ven et al.
				7,943,941	B2	5/2011	Shimizu et al.
				7,968,866	B2	6/2011	Shimizu et al.
				7,969,090	B2	6/2011	Shimizu et al.
				8,018,135	B2*	9/2011	Van De Ven H05B 33/086 313/498
				8,123,376	B2	2/2012	Van De Ven et al.
				8,148,177	B2	4/2012	Shimizu et al.
				8,309,375	B2	11/2012	Shimizu et al.
				8,513,875	B2*	8/2013	Van De Ven F21K 9/00 313/502
				8,610,147	B2	12/2013	Shimizu et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,679,866	B2	3/2014	Shimizu et al.						
8,685,762	B2	4/2014	Shimizu et al.						
8,733,968	B2 *	5/2014	Van De Ven	F21K 9/00	257/98			
8,754,428	B2	6/2014	Shimizu et al.						
2001/0002049	A1	5/2001	Reeh et al.						
2002/0006044	A1	1/2002	Harbers et al.						
2002/0048177	A1	4/2002	Rahm et al.						
2002/0070681	A1	6/2002	Shimizu et al.						
2002/0087532	A1	7/2002	Barritz et al.						
2002/0149576	A1	10/2002	Tanaka et al.						
2003/0026096	A1	2/2003	Ellens et al.						
2003/0030063	A1	2/2003	Sosniak et al.						
2003/0067773	A1	4/2003	Marshall et al.						
2003/0146411	A1	8/2003	Srivastava et al.						
2003/0222268	A1	12/2003	Yocom et al.						
2004/0000868	A1	1/2004	Shimizu et al.						
2004/0004437	A1	1/2004	Shimizu et al.						
2004/0046178	A1	3/2004	Sano						
2004/0090180	A1	5/2004	Shimizu et al.						
2004/0105261	A1	6/2004	Ducharme et al.						
2004/0105264	A1	6/2004	Spero						
2004/0212998	A1	10/2004	Mohacsi						
2004/0217364	A1	11/2004	Tarsa						
2004/0218387	A1	11/2004	Gerlach						
2004/0218388	A1	11/2004	Suzuki						
2004/0222435	A1	11/2004	Shimizu et al.						
2004/0239839	A1	12/2004	Hong						
2004/0264193	A1	12/2004	Okumura						
2004/0264212	A1	12/2004	Chung et al.						
2005/0007306	A1	1/2005	Iisaka et al.						
2005/0052378	A1	3/2005	Hacker						
2005/0082974	A1	4/2005	Fukasawa et al.						
2005/0093442	A1	5/2005	Setlur et al.						
2005/0117334	A1	6/2005	Lee et al.						
2005/0135094	A1	6/2005	Lee et al.						
2005/0190141	A1	9/2005	Roth et al.						
2005/0231976	A1	10/2005	Keuper et al.						
2005/0243556	A1	11/2005	Lynch						
2005/0251698	A1	11/2005	Lynch et al.						
2005/0259423	A1	11/2005	Heuser et al.						
2005/0274972	A1	12/2005	Roth et al.						
2005/0280357	A1	12/2005	Shimizu et al.						
2006/0012989	A1	1/2006	Lee						
2006/0022582	A1	2/2006	Radkov						
2006/0043879	A1	3/2006	Naitou						
2006/0060872	A1	3/2006	Edmond et al.						
2006/0067073	A1	3/2006	Ting						
2006/0105482	A1	5/2006	Alferink et al.						
2006/0113548	A1	6/2006	Chen et al.						
2006/0138435	A1	6/2006	Tarsa et al.						
2006/0138937	A1	6/2006	Ibbetson						
2006/0152140	A1	7/2006	Brandson						
2006/0152172	A9	7/2006	Mueller et al.						
2006/0180818	A1	8/2006	Nagai et al.						
2006/0181192	A1	8/2006	Radkov						
2006/0245184	A1	11/2006	Galli						
2007/0001188	A1	1/2007	Lee						
2007/0001994	A1	1/2007	Roth						
2007/0041220	A1	2/2007	Lynch						
2007/0051966	A1	3/2007	Higashi et al.						
2007/0090381	A1	4/2007	Otsuka et al.						
2007/0114914	A1	5/2007	Shimizu et al.						
2007/0137074	A1	6/2007	Van De Ven et al.						
2007/0139920	A1	6/2007	Van De Ven et al.						
2007/0139923	A1	6/2007	Negley						
2007/0159060	A1	7/2007	Shimizu et al.						
2007/0159091	A1	7/2007	Hirosaki et al.						
2007/0170447	A1	7/2007	Negley						
2007/0171145	A1	7/2007	Coleman et al.						
2007/0202623	A1	8/2007	Gao						
2007/0223219	A1	9/2007	Medendorp et al.						
2007/0236911	A1	10/2007	Negley						
2007/0247414	A1	10/2007	Robert						
2007/0247847	A1	10/2007	Villard						
2007/0262337	A1	11/2007	Villard						
2007/0263393	A1	11/2007	Van De Ven et al.						
2007/0267983	A1	11/2007	Van De Ven et al.						
2007/0274063	A1	11/2007	Negley						
2007/0274080	A1	11/2007	Negley et al.						
2007/0276606	A1	11/2007	Radkov						
2007/0278503	A1	12/2007	Van De Ven et al.						
2007/0278934	A1	12/2007	Van De Ven et al.						
2007/0278974	A1	12/2007	Van De Ven						
2007/0279440	A1	12/2007	Negley						
2007/0279903	A1	12/2007	Negley						
2007/0280624	A1	12/2007	Negley et al.						
2008/0084685	A1	4/2008	Van De Ven						
2008/0084700	A1	4/2008	Van De Ven						
2008/0084701	A1	4/2008	Van De Ven et al.						
2008/0088248	A1	4/2008	Myers						
2008/0089053	A1	4/2008	Negley						
2008/0106895	A1	5/2008	Van De Ven						
2008/0106907	A1	5/2008	Trott et al.						
2008/0112168	A1	5/2008	Pickard et al.						
2008/0112170	A1	5/2008	Trott et al.						
2008/0112183	A1	5/2008	Negley						
2008/0130265	A1	6/2008	Negley						
2008/0130285	A1	6/2008	Negley						
2008/0136313	A1	6/2008	Negley						
2008/0137347	A1	6/2008	Trott et al.						
2008/0138918	A1	6/2008	Shimizu et al.						
2008/0170396	A1	7/2008	Yuan et al.						
2008/0179602	A1	7/2008	Negley						
2008/0192462	A1	8/2008	Steedly et al.						
2008/0192493	A1	8/2008	Villard						
2008/0211416	A1	9/2008	Negley et al.						
2008/0231201	A1	9/2008	Higley et al.						
2008/0259589	A1	10/2008	Van De Ven et al.						
2008/0278928	A1	11/2008	Van De Ven et al.						
2008/0278940	A1	11/2008	Van De Ven et al.						
2008/0278950	A1	11/2008	Pickard et al.						
2008/0278952	A1	11/2008	Trott et al.						
2008/0304260	A1	12/2008	Van De Ven et al.						
2008/0304261	A1	12/2008	Van De Ven et al.						
2008/0304269	A1	12/2008	Pickard et al.						
2008/0309255	A1	12/2008	Myers et al.						
2008/0310154	A1	12/2008	Van De Ven et al.						
2009/0002986	A1	1/2009	Medendorp et al.						
2009/0161356	A1	6/2009	Negley						
2009/0184616	A1	7/2009	Van de Ven						
2009/0246895	A1	10/2009	You						
2009/0262515	A1	10/2009	Lee et al.						
2009/0315014	A1	12/2009	Shimizu et al.						
2009/0315015	A1	12/2009	Shimizu et al.						
2009/0316068	A1	12/2009	Shimizu et al.						
2010/0001258	A1	1/2010	Shimizu et al.						
2010/0006819	A1	1/2010	Shimizu et al.						
2010/0019224	A1	1/2010	Shimizu et al.						
2010/0019270	A1	1/2010	Shimizu et al.						
2010/0117516	A1	5/2010	Shimizu et al.						
2010/0264841	A1	10/2010	Shimizu et al.						
2010/0264842	A1	10/2010	Shimizu et al.						
2011/0053299	A1	3/2011	Shimieu et al.						
2011/0062864	A1	3/2011	Shimizu et al.						
2011/0297990	A1	12/2011	Shimizu et al.						
2014/0084323	A1	3/2014	Shimizu et al.						

FOREIGN PATENT DOCUMENTS

DE	3 916 875	12/1990
DE	3916875	12/1990
DE	10-335077	3/2005
DE	20 2005 001540 U1	5/2005
DE	10 2005 05936	9/2006
EP	0 838 866	4/1998
EP	0 971 421	1/2000
EP	1 024 399	8/2000
EP	1 081 771	3/2001
EP	1 160 883	12/2001
EP	1 193 772	4/2002
EP	1 367 655	7/2003
EP	1 367 655	12/2003
EP	1 380 876	1/2004

(56)

References Cited

FOREIGN PATENT DOCUMENTS

EP	1 462 711	12/2004
EP	1 566 848	8/2005
EP	1 571 715	9/2005
EP	1 760 795	1/2006
EP	1 837 386	9/2007
JP	04-159519	6/1992
JP	09-146089	6/1997
JP	10-163531	6/1998
JP	10-163535	6/1998
JP	2000-022222	1/2000
JP	2000-183408	6/2000
JP	2000-208815	7/2000
JP	2000-261039	9/2000
JP	2001-111114	4/2001
JP	2001-156331	6/2001
JP	2001-307506	11/2001
JP	2002-057376	2/2002
JP	2002-150821	5/2002
JP	2002-170999	6/2002
JP	2003-515956	5/2003
JP	2003-529889	10/2003
JP	2003-317979	11/2003
JP	2004-080046	3/2004
JP	2004-103443	4/2004
JP	2004 103443	4/2004
JP	2004-253309	9/2004
JP	2004-311791	11/2004
JP	2004-356116	12/2004
JP	2004-363055	12/2004
JP	2005-005482	1/2005
JP	2005-079500	3/2005
JP	2005-100800 A	4/2005
JP	2005-101296	4/2005
JP	2005-101296 A	4/2005
JP	2005-123484	5/2005
JP	2005-142311	6/2005
JP	2005-153606	6/2005
JP	2005-167177	6/2005
JP	2005-228979	8/2005
JP	2006-073656	3/2006
JP	2006-245443	9/2006
JP	2007-122950	5/2007
JP	2007-141737	6/2007
JP	2007-536729	12/2007
TW	546854	8/2003
TW	594828	6/2004
TW	1334231	3/2005
WO	98/43014	10/1998
WO	99/66483	12/1999
WO	00/34709	6/2000
WO	01/41215	6/2001
WO	01/43113	6/2001
WO	01/69692	9/2001
WO	03/056876	7/2003
WO	03/091771	11/2003
WO	2004/068909	8/2004
WO	2005/004202	1/2005
WO	2005/013365	2/2005
WO	2005/013365	10/2005
WO	2005/124877	12/2005
WO	2005/124877	12/2005
WO	WO 2005/124877	12/2005
WO	2006/028312	3/2006
WO	2007/061758	5/2007

OTHER PUBLICATIONS

White Light LED, Part Nos. NSPW300BS and NSPW312BS, High Brightness LEDs, Nov. 12, 1999, Publisher: Nichia Corporation.

Chhajed, S., *Influence of junction temperature on chromaticity and color-rendering properties of trichromatic white-light sources . . .*, Journal of Applied Physics, 2005, vol. 97pp. 1-8.

Color Kinetics Inc., Color Kinetics Support : White Papers & Presentations; available at <http://www.colorkinetics.com/support/>

whitepapers/, Solid State Lighting White Papers & Presentations, Feb. 22, 2006, pp. 1-4.

Color Kinetics Inc., *Color Quality of Intelligent Solid-State Light Systems*, Color Quality of Solid-State Light Sources, Mar. 2005, pp. 1-3.

Compound Semiconductors Online, "LED Lighting Fixtures, Inc. Sets World Record at 80 Lumens per Watt for Warm White", Compound Semiconductors Online, May 30, 2006, pp. 1.

Cree, Inc., "Cree® Xlamp® 7090 XR-E Series LED Binning and Labeling," Application Note: CLD-AP08.000, 7pp (2006).

CSA International, "Test Data Report," Project No. 1786317, Report No. 786317-1 (Apr. 2006).

DOE SSL CALiPer Report, "Product Test Reference: CALiPER 07-31 Downlight Lamp".

DOE SSL CALiPer Report, "Product Test Reference: CALiPER 07-47 Downlight Lamp".

Krames et al., *Lumileds Lighting, Light from Silicon Valley*, Progress and Future Direction of LED Technology, SSL Workshop, Nov. 13, 2003, Publisher: Lumileds Lighting Inc., pp. 1-21.

Narendran et al., "Solid State lighting: failure analysis of white LEDs," Journal of Crystal Growth, vol. 268, Issues 1-4, Aug. 2004, Abstract.

Narendran et al., *Color Rendering Properties of LED Light Sources*, 2002, pp. 1-8.

Nichia, White Light LED, Part Nos. NSPW300BS and NSPW312BS, High Brightness LEDs, Nov. 12, 1999, Publisher: Nichia Corporation.

Press Release from LED Lighting Fixtures dated Apr. 24, 2006 entitled "LED Lighting Fixtures, Inc. achieves unprecedented gain in light output from new luminaire".

Press Release from LED Lighting Fixtures dated Feb. 16, 2006 entitled "LED Lighting Fixtures, Inc. Announces Record Performance".

Press Release from LED Lighting Fixtures dated Feb. 7, 2007 entitled "LED Lighting Fixtures Announces its first LED-based Recessed Down Light".

Press Release from LED Lighting Fixtures dated Jan. 26, 2006 entitled "LED Lighting Fixtures Creates 750 Lumen Recessed Light and Uses Only 16 Watts of Power".

Press Release from LED Lighting Fixtures dated May 30, 2006 entitled "LED Lighting Fixtures, Inc. Sets World Record at 80 Lumens per Watt for Warm White Fixture".

Press Release from LED Lighting Fixtures dated Nov. 28, 2007 entitled "New Lamp from LED Lighting Fixtures Shatter World Record for Energy Efficiency".

Shimizu, "Development of High-Efficiency LED Downlight", First International Conference on White LEDs and Solid State Lighting, Nov. 30, 2007.

U.S. Department of Energy, "DOE Solid-State Lighting CALiPER Program, Summary of Results: Round 3 of Product Testing," Oct. 2007.

U.S. Department of Energy, "DOE Solid-State Lighting CALiPER Program, Summary of Results: Round 4 of Product Testing," Jan. 2008.

U.S. Department of Energy, "DOE Solid-State Lighting CALiPER Program, Summary of Results: Round 5 of Product Testing," May 2008.

Van De Ven et al., "Warm White Illumination with High CRI and High Efficacy by Combining 455 nm Excited Yellowish Phosphor LEDs and Red AlInGaP LEDs," First International Conference on White LEDs and Solid State Lighting, Nov. 30, 2007.

OptoLED Lighting Inc., *OptoLED Product Information*, 2009, Publisher: OptoLED GmbH website: accessed at <http://222.optoled.de/englisch/products/led.html>.

Permlight Inc., *Enbryten LED Product Information*, Feb. 2005, Publisher: Permlight Inc. website; accessed at <http://www.webarchive.org> displaying that www.permlight.com/products/LEDfixtures.asp was publicly available Jan. 2004.

(56)

References Cited

OTHER PUBLICATIONS

U.S. Appl. No. 61/075,513, filed Jun. 25, 2008, Roberts.
U.S. Appl. No. 61/037,365, filed Mar. 18, 2008, Van de Ven et al.
Van de Ven et al., "Warm White Illumination with High CRI and High Efficacy by Combining 455 nm Excited Yellowish Phosphor LEDs and Red AlInGaP LEDs," First International Conference on White LEDs and Solid State Lighting.
Cree® XLamp® 7090 XR-E Series LED Binning and Labeling.
U.S. Appl. No. 13/804,935, filed Mar. 14, 2013, Pickard et al.


Taiwan Office Action (and translation provided by foreign counsel) from a corresponding Taiwan patent application bearing a mailing date of Jul. 30, 2013.

Japanese Office Action (and translation provided by foreign counsel) from a corresponding Japanese patent application bearing a mailing date of Aug. 8, 2013.

Japanese Office Action (and translation provided by foreign counsel) from a corresponding Japanese patent application bearing a mailing date of Nov. 7, 2014, 6 pages.

* cited by examiner

Fig. 1






FIG. 2




FIG.3




FIG. 4




FIG. 5

1

LIGHTING DEVICE AND LIGHTING METHOD

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 13/354,510, filed on Jan. 20, 2012 (now U.S. Pat. No. 8,733,968), entitled "LIGHTING DEVICE AND LIGHTING METHOD" (inventors: Antony Paul van de Ven and Gerald H. Negley), the entirety of which is hereby incorporated by reference.

This application claims the benefit of U.S. patent application Ser. No. 12/893,331, filed on Sep. 29, 2010 (now U.S. Pat. No. 8,123,376), entitled "LIGHTING DEVICE AND LIGHTING METHOD" (inventors: Antony Paul van de Ven and Gerald H. Negley), the entirety of which is hereby incorporated by reference.

This application claims the benefit of U.S. patent application Ser. No. 11/736,799, filed on Apr. 18, 2007 (now U.S. Pat. No. 7,828,460), entitled "LIGHTING DEVICE AND LIGHTING METHOD" (inventors: Antony Paul van de Ven and Gerald H. Negley), the entirety of which is hereby incorporated by reference.

This application claims the benefit of U.S. Provisional Patent Application No. 60/792,860, filed on Apr. 18, 2006, entitled "LIGHTING DEVICE AND LIGHTING METHOD" (inventors: Gerald H. Negley and Antony Paul van de Ven), the entirety of which is hereby incorporated by reference.

This application claims the benefit of U.S. Provisional Patent Application No. 60/793,518, filed on Apr. 20, 2006, entitled "LIGHTING DEVICE AND LIGHTING METHOD" (inventors: Gerald H. Negley and Antony Paul van de Ven), the entirety of which is hereby incorporated by reference.

FIELD OF THE INVENTION

The present invention relates to a lighting device, in particular, a device which includes one or more solid state light emitters and one or more luminescent materials (e.g., one or more phosphors). The present invention is also directed to lighting methods.

BACKGROUND OF THE INVENTION

A large proportion (some estimates are as high as twenty-five percent) of the electricity generated in the United States each year goes to lighting. Accordingly, there is an ongoing need to provide lighting which is more energy-efficient. It is well-known that incandescent light bulbs are very energy-inefficient light sources—about ninety percent of the electricity they consume is released as heat rather than light. Fluorescent light bulbs are more efficient than incandescent light bulbs (by a factor of about 10) but are still less efficient as compared to solid state light emitters, such as light emitting diodes.

In addition, as compared to the normal lifetimes of solid state light emitters, incandescent light bulbs have relatively short lifetimes, i.e., typically about 750-1000 hours. In comparison, light emitting diodes, for example, typically have lifetimes between 50,000 and 70,000 hours. Fluorescent bulbs have longer lifetimes (e.g., 10,000-20,000 hours) than incandescent lights, but provide less favorable color reproduction.

2

Color reproduction is typically measured using the Color Rendering Index (CRI). CRI Ra is a relative measurement of how the color rendition of an illumination system compares to that of a reference illuminator (light source). For color temperatures below 5000 K, a blackbody radiator is used, and for color temperatures above 5000 K, a series of spectra defined by the CIE are used. CRI Ra is the average of the differences in the shift in surface color of an object when lit by a particular lamp, relative to the surface color of the object when illuminated by the reference light source. The CRI Ra equals 100 if the color coordinates of a set of test colors being illuminated by the illumination system are the same as the coordinates of the same test colors being irradiated by the reference radiator. Daylight has a high CRI (Ra being approximately 100), with incandescent bulbs also being relatively close (Ra greater than 95), and fluorescent lighting being less accurate (typical Ra of 70-80). Certain types of specialized lighting have very low CRI (e.g., mercury vapor or sodium lamps have Ra as low as about 40 or even lower). Sodium lights are used, e.g., to light highways—driver response time, however, significantly decreases with lower CRI values (for any given brightness, legibility decreases with lower CRI).

Another issue faced by conventional light fixtures is the need to periodically replace the lighting devices (e.g., light bulbs, etc.). Such issues are particularly pronounced where access is difficult (e.g., vaulted ceilings, bridges, high buildings, traffic tunnels) and/or where change-out costs are extremely high. The typical lifetime of conventional fixtures is about 20 years, corresponding to a light-producing device usage of at least about 44,000 hours (based on usage of 6 hours per day for 20 years). Light-producing device lifetime is typically much shorter, thus creating the need for periodic change-outs.

Accordingly, for these and other reasons, efforts have been ongoing to develop ways by which light emitting diodes can be used in place of incandescent lights, fluorescent lights and other light-generating devices in a wide variety of applications. In addition, where light emitting diodes are already being used, efforts are ongoing to provide light emitting diodes which are improved, e.g., with respect to energy efficiency, color rendering index (CRI Ra), contrast, efficacy (lm/W), and/or duration of service.

Light emitting diodes are well-known semiconductor devices that convert electrical current into light. A wide variety of light emitting diodes are used in increasingly diverse fields for an ever-expanding range of purposes.

More specifically, light emitting diodes are semiconductor devices that emit light (ultraviolet, visible, or infrared) when a potential difference is applied across a p-n junction structure. There are a number of well-known ways to make light emitting diodes and many associated structures, and the present invention can employ any such devices. By way of example, Chapters 12-14 of Sze, *Physics of Semiconductor Devices*, (2d Ed. 1981) and Chapter 7 of Sze, *Modern Semiconductor Device Physics* (1998) describe a variety of photonic devices, including light emitting diodes.

The commonly recognized and commercially available light emitting diode ("LED") that is sold (for example) in electronics stores typically represents a "packaged" device made up of a number of parts. These packaged devices typically include a semiconductor based light emitting diode such as (but not limited to) those described in U.S. Pat. Nos. 4,918,487; 5,631,190; and 5,912,477; various wire connections, and a package that encapsulates the light emitting diode.

As is well-known, a light emitting diode produces light by exciting electrons across the band gap between a conduction

band and a valence band of a semiconductor active (light-emitting) layer. The electron transition generates light at a wavelength that depends on the band gap. Thus, the color of the light (wavelength) emitted by a light emitting diode depends on the semiconductor materials of the active layers of the light emitting diode.

Although the development of light emitting diodes has in many ways revolutionized the lighting industry, some of the characteristics of light emitting diodes have presented challenges, some of which have not yet been fully met. For example, the emission spectrum of any particular light emitting diode is typically concentrated around a single wavelength (as dictated by the light emitting diode's composition and structure), which is desirable for some applications, but not desirable for others, (e.g., for providing lighting, such an emission spectrum provides a very low CRI).

Because light that is perceived as white is necessarily a blend of light of two or more colors (or wavelengths), no single light emitting diode junction has been developed that can produce white light. "White" light emitting diode lamps have been produced which have a light emitting diode pixel formed of respective red, green and blue light emitting diodes. Other "white" light emitting diodes have been produced which include (1) a light emitting diode which generates blue light and (2) a luminescent material (e.g., a phosphor) that emits yellow light in response to excitation by light emitted by the light emitting diode, whereby the blue light and the yellow light, when mixed, produce light that is perceived as white light.

In addition, the blending of primary colors to produce combinations of non-primary colors is generally well understood in this and other arts. In general, the 1931 CIE Chromaticity Diagram (an international standard for primary colors established in 1931), and the 1976 CIE Chromaticity Diagram (similar to the 1931 Diagram but modified such that similar distances on the Diagram represent similar perceived differences in color) provide useful reference for defining colors as weighted sums of primary colors.

Light emitting diodes can thus be used individually or in any combinations, optionally together with one or more luminescent material (e.g., phosphors or scintillators) and/or filters, to generate light of any desired perceived color (including white). Accordingly, the areas in which efforts are being made to replace existing light sources with light emitting diode light sources, e.g., to improve energy efficiency, color rendering index (CRI), efficacy (lm/W), and/or duration of service, are not limited to any particular color or color blends of light.

A wide variety of luminescent materials (also known as lumiphors or luminophoric media, e.g., as disclosed in U.S. Pat. No. 6,600,175, the entirety of which is hereby incorporated by reference) are well-known and available to persons of skill in the art. For example, a phosphor is a luminescent material that emits a responsive radiation (e.g., visible light) when excited by a source of exciting radiation. In many instances, the responsive radiation has a wavelength which is different from the wavelength of the exciting radiation. Other examples of luminescent materials include scintillators, day glow tapes and inks which glow in the visible spectrum upon illumination with ultraviolet light.

Luminescent materials can be categorized as being down-converting, i.e., a material which converts photons to a lower energy level (longer wavelength) or up-converting, i.e., a material which converts photons to a higher energy level (shorter wavelength).

Inclusion of luminescent materials in LED devices has been accomplished by adding the luminescent materials to a

clear or translucent encapsulant material (e.g., epoxy-based, silicone-based or glass-based material) as discussed above, for example by a blending or coating process.

For example, U.S. Pat. No. 6,963,166 (Yano '166) discloses that a conventional light emitting diode lamp includes a light emitting diode chip, a bullet-shaped transparent housing to cover the light emitting diode chip, leads to supply current to the light emitting diode chip, and a cup reflector for reflecting the emission of the light emitting diode chip in a uniform direction, in which the light emitting diode chip is encapsulated with a first resin portion, which is further encapsulated with a second resin portion. According to Yano '166, the first resin portion is obtained by filling the cup reflector with a resin material and curing it after the light emitting diode chip has been mounted onto the bottom of the cup reflector and then has had its cathode and anode electrodes electrically connected to the leads by way of wires. According to Yano '166, a phosphor is dispersed in the first resin portion so as to be excited with the light A that has been emitted from the light emitting diode chip, the excited phosphor produces fluorescence ("light B") that has a longer wavelength than the light A, a portion of the light A is transmitted through the first resin portion including the phosphor, and as a result, light C, as a mixture of the light A and light B, is used as illumination.

As noted above, "white LED lights" (i.e., lights which are perceived as being white or near-white) have been investigated as potential replacements for white incandescent lamps. A representative example of a white LED lamp includes a package of a blue light emitting diode chip, made of indium gallium nitride (InGaN) or gallium nitride (GaN), coated with a phosphor such as YAG. In such an LED lamp, the blue light emitting diode chip produces an emission with a wavelength of about 450 nm, and the phosphor produces yellow fluorescence with a peak wavelength of about 550 nm on receiving that emission. For instance, in some designs, white light emitting diodes are fabricated by forming a ceramic phosphor layer on the output surface of a blue light-emitting semiconductor light emitting diode. Part of the blue ray emitted from the light emitting diode chip passes through the phosphor, while part of the blue ray emitted from the light emitting diode chip is absorbed by the phosphor, which becomes excited and emits a yellow ray. The part of the blue light emitted by the light emitting diode which is transmitted through the phosphor is mixed with the yellow light emitted by the phosphor. The viewer perceives the mixture of blue and yellow light as white light.

As also noted above, in another type of LED lamp, a light emitting diode chip that emits an ultraviolet ray is combined with phosphor materials that produce red (R), green (G) and blue (B) light rays. In such an "RGB LED lamp", the ultraviolet ray that has been radiated from the light emitting diode chip excites the phosphor, causing the phosphor to emit red, green and blue light rays which, when mixed, are perceived by the human eye as white light. Consequently, white light can also be obtained as a mixture of these light rays.

Designs have been provided in which existing LED component packages and other electronics are assembled into a fixture. In such designs, a packaged LED is mounted to a circuit board or a heat sink directly, the circuit board is mounted to a heat sink, and the heat sink is mounted to the fixture housing along with required drive electronics. In many cases, additional optics (secondary to the package parts) are also necessary.

In substituting light emitting diodes for other light sources, e.g., incandescent light bulbs, packaged LEDs have been used with conventional light fixtures, for example, fixtures which include a hollow lens and a base plate attached to the lens, the

5

base plate having a conventional socket housing with one or more contacts which are electrically coupled to a power source. For example, LED light bulbs have been constructed which comprise an electrical circuit board, a plurality of packaged LEDs mounted to the circuit board, and a connection post attached to the circuit board and adapted to be connected to the socket housing of the light fixture, whereby the plurality of LEDs can be illuminated by the power source.

There is an ongoing need for ways to use solid state light emitters, e.g., light emitting diodes, to provide white light in a wider variety of applications, with greater energy efficiency, with improved color rendering index (CRI), with improved efficacy (lm/W), low cost and/or with longer duration of service.

BRIEF SUMMARY OF THE INVENTION

There exist "white" LED light sources which are relatively efficient but which have poor color rendering, typically having CRI Ra values of less than 75, and which are particularly deficient in the rendering of red colors and also to a significant extent deficient in green. This means that many things, including the typical human complexion, food items, labeling, painting, posters, signs, apparel, home decoration, plants, flowers, automobiles, etc. exhibit odd or wrong color as compared to being illuminated with an incandescent light or natural daylight. Typically, such white LEDs have a color temperature of approximately 5,000 K, which is generally not visually comfortable for general illumination, which however may be desirable for the illumination of commercial produce or advertising and printed materials.

Some so-called "warm white" LEDs have a more acceptable color temperature (typically 2700 to 3500 K) for indoor use, and, in some special cases, good CRI (in the case of a yellow and red phosphor mix, as high as Ra=95), but their efficiency is generally significantly less than that of the standard "cool white" LEDs.

Colored objects illuminated by RGB LED lamps sometimes do not appear in their true colors. For example, an object that reflects only yellow light, and thus that appears to be yellow when illuminated with white light, may appear desaturated and grayish when illuminated with light having an apparent yellow color, produced by the red and green LEDs of an RGB LED fixture. Such lamps, therefore, are considered not to provide excellent color rendition, particularly when illuminating various settings such as in general illumination and particularly with regard to natural scenes. In addition, currently available green LEDs are relatively inefficient, and thus limit the efficiency of such lamps.

Employing LEDs having a wide variety of hues would similarly necessitate use of LEDs having a variety of efficiencies, including some with low efficiency, thereby reducing the efficiency of such systems, and dramatically increase the complexity and cost of the circuitry to control the many different types of LEDs and maintain the color balance of the light.

There is therefore a need for a high efficiency white light source that combines the efficiency and long life of white LEDs (i.e., which avoids the use of relatively inefficient light sources) with an acceptable color temperature and good color rendering index, a wide gamut, and simple control circuitry.

In accordance with the present invention, it has unexpectedly been found that surprisingly high CRI can be obtained by combining light emitted from:

- a first group of light emitting diodes;
- a first group of lumiphors;
- a second group of light emitting diodes;

6

a second group of lumiphors; and
a third group of light emitting diodes;
wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point has a second correlated color temperature, the first correlated color temperature differs from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm.

By providing a lighting device in which, as mentioned above,

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature,

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature,

the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K),

it is readily possible, e.g., by adjusting the current supplied to one or more of the respective light emitting diodes, and/or by interrupting power supply to one or more of the respective light emitting diodes (and/or by adjusting the amount of excitation of one or more of the respective lumiphors, e.g., by adjusting the amount of light which contacts such lumiphor(s), and/or by preventing one or more of the lumiphors from being excited), to alter the first group-second group light, i.e., to control the x, y coordinates of the light which would be emitted if light emitted by the first group of light emitting

diodes, the first group of lumiphors, the second group of light emitting diodes and the second group of lumiphors were mixed in the absence of any other light, and therefor control the x, y coordinates of the light emitted by the lighting device.

Particularly high CRI can be obtained where, in addition, the light emitting diodes and the lumiphors are selected such that if each of the first group of light emitting diodes is illuminated, each of the first group of lumiphors is excited, each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes, the first group of lumiphors, the second group of light emitting diodes, and the second group of lumiphors would, in the absence of any additional light, have a first group mixed illumination having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line segment connecting a first point to a second point, the second line segment connecting the second point to a third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38.

In one aspect of the present invention, the light emitting diodes and the lumiphors are selected such that a mixture of light emitted from the first group of light emitting diodes, from the first group of lumiphors, from the second group of light emitting diodes, from the second group of lumiphors and from the third group of light emitting diodes would produce a first group-second group-third group mixed illumination having x, y coordinates on a 1931 CIE Chromaticity Diagram which define a point which is within twenty MacAdam ellipses of at least one point within the range of from about 2200K to about 4500K on the blackbody locus on a 1931 CIE Chromaticity Diagram.

In addition, it has unexpectedly been found that surprisingly high CRI can be obtained by combining light as described above, particularly where the light (2) referred to above (i.e., the light emitted from one or more lumiphors which emit light having a dominant wavelength in the range of from 555 to 585) is emitted from a broad spectrum light source, e.g., a yellow lumiphor.

Accordingly, in a first aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
 - a first group of lumiphors;
 - a second group of light emitting diodes;
 - a second group of lumiphors; and
 - a third group of light emitting diodes;
- wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited,

a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K).

In some embodiments according to this aspect of the present invention (and other aspects of the present invention), the device can include additional 430 nm to 480 nm light emitting diodes (i.e., light emitting diodes which, if illuminated, would emit light having a peak wavelength in the range of from about 430 nm to about 480 nm) which are not within either of the first and second group of light emitting diodes, and/or the device can include additional 555 nm to 585 nm lumiphors (i.e., lumiphors which, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm) which are not within either of the first or second groups of lumiphors, and/or the device can include additional 600 nm to 630 nm light emitting diodes (i.e., light emitting diodes which, if illuminated, would emit light having a dominant wavelength in the range of from about 600 nm to about 630 nm) which are not within the third group of light emitting diodes.

In some embodiments according to this aspect of the present invention (and other aspects of the present invention), the first and second groups of light emitting diodes together consist of all of the 430 nm to 480 nm light emitting diodes in the device, the first and second groups of lumiphors consist of all of the 555 nm to 585 nm lumiphors in the device, and the third group of light emitting diodes consists of all of the 600 nm to 630 nm light emitting diodes in the device.

According to a second aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
 - a first group of lumiphors;
 - a second group of light emitting diodes;
 - a second group of lumiphors; and
 - a third group of light emitting diodes;
- wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group

mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

if each of the light emitting diodes in the first and second groups of light emitting diodes is illuminated (e.g., by inserting into a standard 120 AC receptacle a power plug which is electrically connected to a power line which is directly or switchably electrically connected to the lighting device) and each of the lumiphors in the first and second groups of lumiphors is excited, a mixture of light emitted from the first and second groups of light emitting diodes and the first and second groups of lumiphors would, in the absence of any additional light, have a first group-second group mixed illumination having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line segment connecting a first point to a second point, the second line segment connecting the second point to a third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38.

In some embodiments according to this aspect of the present invention, the device can include additional 430 nm to 480 nm light emitting diodes which are not within either of the first and second groups of light emitting diodes, and/or the device can include additional 555 nm to 585 nm lumiphors which are not within either of the first and second groups of lumiphors, and/or the device can include additional 600 nm to 630 nm light emitting diodes which are not within the third group of light emitting diodes, including wherein if any of such additional 430 nm to 480 nm light emitting diodes and/or 555 nm to 585 nm lumiphors were illuminated or excited in addition to all of the light emitting diodes in the first and second groups of light emitting diodes and all of the lumiphors in the first and second groups of lumiphors, there would be produced combined light having x, y color coordinates which are not within the area on a 1931 CIE Chromaticity Diagram enclosed by the first, second, third, fourth and fifth line segments defined above.

In some embodiments according to this aspect of the present invention, the first and second groups of light emitting diodes consist of all of the 430 nm to 480 nm light emitting diodes in the device, the first and second groups of lumiphors consists of all of the 555 nm to 585 nm lumiphors in the device, and the third group of light emitting diodes consists of all of the 600 nm to 630 nm light emitting diodes in the device.

According to a third aspect of the present invention, there is provided a lighting device comprising:

a first group of light emitting diodes;
 a first group of lumiphors;
 a second group of light emitting diodes;
 a second group of lumiphors; and
 a third group of light emitting diodes;
 wherein:
 each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;
 each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and
 each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm; and
 if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

if each of the light emitting diodes in the first and second groups of light emitting diodes is illuminated, a mixture of light emitted from the first and second groups of light emitting diodes and the first and second groups of lumiphors would, in the absence of any additional light, have a first group-second group mixed illumination having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line segment connecting a first point to a second point, the second line segment connecting the second point to a third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38.

In some embodiments according to this aspect of the invention, at least some of the lumiphors in the first and/or the second group of lumiphors are excited by light emitted from the light emitting diodes in the first and/or the second group of light emitting diodes.

In some embodiments according to this aspect of the present invention, the lighting device can include additional 555 nm to 585 nm lumiphors which would not be excited by light emitted from any of the light emitting diodes in the first and/or the second group of light emitting diodes, even when

11

all of the light emitting diodes in the first and second groups of light emitting diodes are emitting light.

In some embodiments according to this aspect of the present invention, the lighting device can include additional 555 nm to 585 nm lumiphors (1) which would not be excited by light emitted from any of the light emitting diodes in the first and second groups of light emitting diodes and (2) which, if such additional 555 nm to 585 nm lumiphors were excited and all of the 430 to 480 nm light emitting diodes in the first and second groups of light emitting diodes were illuminated, the combined light would have x, y color coordinates which are not within the area on a 1931 CIE Chromaticity Diagram enclosed by the first, second, third, fourth and fifth line segments defined above.

According to a fourth aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
 - a first group of lumiphors;
 - a second group of light emitting diodes;
 - a second group of lumiphors; and
 - a third group of light emitting diodes;
- at least one power line directly or switchably electrically connected to the lighting device,

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

if power is supplied to at least one of the at least one power line (e.g., by inserting into a standard 120 AC receptacle a power plug which is electrically connected to the power line and, if necessary, closing one or more switch in the power line), a mixture of light would be emitted from the first and second groups of light emitting diodes and the first and second groups of lumiphors which, in the absence of any additional light, would have a first group-second group mixed illumination having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line seg-

12

ment connecting a first point to a second point, the second line segment connecting the second point to a third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38.

In some embodiments according to this aspect of the present invention, the lighting device can include one or more additional 430 nm to 480 nm light emitting diodes which are not connected to the at least one power line (but which might be connected to some other power line), and in which, if such additional 430 nm to 480 nm light emitting diode(s) were illuminated in addition to all of the 430 nm to 480 nm light emitting diodes connected to the at least one power line, the combined light emitted from all of the 430 nm to 480 nm light emitting diodes in the device and the 555 nm to 585 nm lumiphors in the device, in the absence of any additional light, would have x, y color coordinates which are not within the area on a 1931 CIE Chromaticity Diagram enclosed by the first, second, third, fourth and fifth line segments defined above.

According to a fifth aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
 - a first group of lumiphors;
 - a second group of light emitting diodes;
 - a second group of lumiphors; and
 - a third group of light emitting diodes;
- at least one power line directly or switchably electrically connected to the lighting device,

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

if power is supplied to each of the one or more power lines (e.g., by inserting into a standard 120 AC receptacle one or more power plugs which are electrically connected to one or more respective power lines), light would be emitted from the lighting device having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line segment connecting a first point to a second point, the second line segment connecting the second point to a third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38.

In some embodiments according to this aspect of the present invention, the lighting device can include additional 430 nm to 480 nm light emitting diodes which are not connected to any of the power lines (or are not connected to the power line) in the device, and in which, if such additional light emitting diodes were illuminated in addition to all of the light emitting diodes connected to the at least one power line, the combined light, in the absence of any additional light, would have x, y color coordinates which are not within the area on a 1931 CIE Chromaticity Diagram enclosed by the first, second, third, fourth and fifth line segments defined above.

According to a sixth aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
- a first group of lumiphors;
- a second group of light emitting diodes;
- a second group of lumiphors; and
- a third group of light emitting diodes;

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K

(in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K);

and wherein:

if (1) each of the light emitting diodes in the first and second groups of light emitting diodes is illuminated, (2) each of the lumiphors in the first and second groups of lumiphors is excited, and (3) each of the third group of light emitting diodes is illuminated, a mixture of light emitted from the first and second groups of light emitting diodes, from the first and second groups of lumiphors and from the third group of light emitting diodes would produce a first group-second group-third group mixed illumination having x, y coordinates on a 1931 CIE Chromaticity Diagram which define a point which is within 10 MacAdam ellipses (or within 20 MacAdam ellipses, or within 40 MacAdam ellipses) of at least one point within the range of from about 2200K to about 4500K on the blackbody locus on a 1931 CIE Chromaticity Diagram.

In some embodiments according to this aspect of the present invention, the device can include additional 430 nm to 480 nm light emitting diodes which are not within either of the first and second groups of light emitting diodes, and/or the device can include additional 555 nm to 585 nm lumiphors which are not within either of the first and second groups of lumiphors, and/or the device can include additional 600 nm to 630 nm light emitting diodes which are not within the third group of light emitting diodes, wherein if any combination of such additional light emitting diodes were illuminated in addition to all of the light emitting diodes in the first and second groups of light emitting diodes, all of the lumiphors in the first and second groups of lumiphors and all of the light emitting diodes in the third group of light emitting diodes, would produce combined light having x, y coordinates on a 1931 CIE Chromaticity Diagram which define a point which is not within 10 MacAdam ellipses (or not within 20 MacAdam ellipses, or not within 40 MacAdam ellipses, or not within 100 MacAdam ellipses) of any point within the range of from about 2200K to about 4500K on the blackbody locus on a 1931 CIE Chromaticity Diagram.

In some embodiments according to this aspect of the present invention, the first and second groups of light emitting diode consists of all of the 430 nm to 480 nm light emitting diodes in the device, the first and second groups of lumiphors consist of all of the 555 nm to 585 nm lumiphors in the device, and the third group of light emitting diodes consists of all of the 600 nm to 630 nm light emitting diodes in the device.

According to a seventh aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
- a first group of lumiphors;
- a second group of light emitting diodes;
- a second group of lumiphors; and
- a third group of light emitting diodes;

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm; and

15

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature,

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K);

and wherein:

if each of the light emitting diodes in the first and second groups of light emitting diodes is illuminated and each of the third group of light emitting diodes is illuminated, a mixture of light emitted from the first and second groups of light emitting diodes, light emitted from the first and second groups of lumiphors and light emitted from the third group of light emitting diodes would produce a first group-second group-third group mixed illumination having x, y coordinates on a 1931 CIE Chromaticity Diagram which define a point which is within 10 MacAdam ellipses (or within 20 MacAdam ellipses, or within 40 MacAdam ellipses) of at least one point within the range of from about 2200K to about 4500K on the blackbody locus on a 1931 CIE Chromaticity Diagram.

In some embodiments according to this aspect of the invention, at least some of the lumiphors in the first and/or the second group of lumiphors are excited by light emitted from one or more light emitting diodes in the first and/or the second group of light emitting diodes.

In some embodiments according to this aspect of the present invention, the lighting device might include additional lumiphors which would not be excited by light emitted from any of the light emitting diodes in the first or second groups of light emitting diodes, even when all of the light emitting diodes in the first and second groups of light emitting diodes are emitting light.

In some embodiments according to this aspect of the present invention, the lighting device can include additional lumiphors (1) which would not be excited by light emitted from any of the light emitting diodes in the first and second groups of light emitting diodes and (2) which, if such additional lumiphors were excited in addition to all of the light emitting diodes in the first and second groups of light emitting diodes and all of the light emitting diodes in the third group of light emitting diodes, would produce combined light having x, y coordinates on a 1931 CIE Chromaticity Diagram which define a point which is not within 10 MacAdam ellipses (or not within 100 MacAdam ellipses, or not within 40 MacAdam ellipses, or not within 20 MacAdam ellipses) of any point within the range of from about 2200K to about 4500K on the blackbody locus on a 1931 CIE Chromaticity Diagram.

According to an eighth aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
- a first group of lumiphors;

16

a second group of light emitting diodes;
 a second group of lumiphors; and
 a third group of light emitting diodes;
 at least one power line directly or switchably electrically connected to the lighting device,

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

if power is supplied to at least one of the at least one power line, a mixture of light emitted from the first and second groups of light emitting diodes, from the first and second groups of lumiphors and from the third group of light emitting diodes would produce a first group-second group-third group mixed illumination having x, y coordinates on a 1931 CIE Chromaticity Diagram which define a point which is within 10 MacAdam ellipses (or within 20 MacAdam ellipses, or within 40 MacAdam ellipses) of at least one point within the range of from about 2200K to about 4500K on the blackbody locus on a 1931 CIE Chromaticity Diagram.

In some embodiments according to this aspect of the present invention, the lighting device can include one or more additional 430 nm to 480 nm light emitting diodes, and/or one or more additional 600 nm to 630 nm light emitting diodes, which are not connected to the at least one power line (but which might be connected to some other power line), and in which, if such additional 430 nm to 480 nm light emitting diode(s) and/or such additional 600 nm to 630 nm light emitting diode(s) were illuminated in addition to all of the 430 nm to 480 nm light emitting diodes and all of the 600 nm to 630 nm light emitting diodes connected to the at least one power line, the combined light emitted, in the absence of any additional light, would have x, y coordinates on a 1931 CIE Chromaticity Diagram which define a point which is not within 10 MacAdam ellipses (or not within 100 MacAdam ellipses, or not within 40 MacAdam ellipses, or not within 20 MacAdam ellipses) of any point within the range of from

17

about 2200K to about 4500K on the blackbody locus on a 1931 CIE Chromaticity Diagram.

According to a ninth aspect of the present invention, there is provided a lighting device comprising:

a first group of light emitting diodes;

a first group of lumiphors;

a second group of light emitting diodes;

a second group of lumiphors; and

a third group of light emitting diodes;

at least one power line directly or switchably electrically connected to the lighting device,

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

if power is supplied to each of the at least one power line, a mixture of light emitted from the light emitting diodes in the first and second groups of light emitting diodes, from the lumiphors in the first and second groups of lumiphors and from the third group of light emitting diodes would produce a first group-second group-third group mixed illumination having x, y coordinates on a 1931 CIE Chromaticity Diagram which define a point which is within 10 MacAdam ellipses (or within 20 MacAdam ellipses, or within 40 MacAdam ellipses) of at least one point within the range of from about 2200K to about 4500K on the blackbody locus on a 1931 CIE Chromaticity Diagram.

In some embodiments according to this aspect of the present invention, the lighting device can include additional 430 nm to 480 nm light emitting diodes and/or additional 600 nm to 630 nm light emitting diodes which are not connected to any of the power lines (or are not connected to the power line) in the device, and in which, if any of such additional light emitting diodes were illuminated in addition to all of the light emitting diodes connected to the at least one power line, the combined light, in the absence of any additional light, would have x, y coordinates on a 1931 CIE Chromaticity Diagram which define a point which is not within 10 MacAdam

18

ellipses (or not within 100 MacAdam ellipses, or not within 40 MacAdam ellipses, or not within 20 MacAdam ellipses) of any point within the range of from about 2200K to about 4500K on the blackbody locus on a 1931 CIE Chromaticity Diagram.

According to a tenth aspect of the present invention, there is provided a lighting device comprising:

a first group of light emitting diodes;

a first group of lumiphors;

a second group of light emitting diodes;

a second group of lumiphors; and

a third group of light emitting diodes;

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

and wherein:

if each of the light emitting diodes in the first and second groups of light emitting diodes is illuminated and each of the lumiphors in the first and second groups of lumiphors is excited, a mixture of light emitted from the first and second groups of light emitting diodes and the first and second groups of lumiphors, in the absence of any other light, would have a first group-second group mixed illumination having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line segment connecting a first point to a second point, the second line segment connecting the second point to a third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38; and

if (1) each of the light emitting diodes in the first and second groups of light emitting diodes is illuminated, (2) each of the lumiphors in the first and second groups of lumiphors is excited, and (3) each of the third group of light emitting diodes is illuminated, a mixture of light emitted from the first and second groups of light emitting diodes, from the first and second groups of lumiphors and from the third group of light emitting diodes would produce a first group-second group-third group mixed illumination having x, y coordinates on a 1931 CIE Chromaticity Diagram which define a point which is within 10 MacAdam ellipses (or within 20 MacAdam ellipses, or within 40 MacAdam ellipses) of at least one point within the range of from about 2200K to about 4500K on the blackbody locus on a 1931 CIE Chromaticity Diagram.

In some embodiments according to this aspect of the present invention (and other aspects of the present invention), the device can include additional 430 nm to 480 nm light emitting diodes which are not within the first or the second group of light emitting diodes, and/or the device can include additional 555 nm to 585 nm lumiphors which are not within the first or the second group of lumiphors, and/or the device can include additional 600 nm to 630 nm light emitting diodes which are not within the third group of light emitting diodes.

In some embodiments according to this aspect of the present invention (and other aspects of the present invention), the first and second groups of light emitting diodes consist of all of the 430 nm to 480 nm light emitting diodes in the device, the first and second groups of lumiphors consist of all of the 555 nm to 585 nm lumiphors in the device, and the third group of light emitting diodes consists of all of the 600 nm to 630 nm light emitting diodes in the device.

According to an eleventh aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
- a first group of lumiphors;
- a second group of light emitting diodes;
- a second group of lumiphors; and
- a third group of light emitting diodes;

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm; each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color tempera-

ture, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K);

and wherein:

if each of the light emitting diodes in the first and second groups of light emitting diodes is illuminated and each of the lumiphors in the first and second groups of lumiphors is excited, a mixture of light emitted from the first and second groups of light emitting diodes and the first and second groups of lumiphors, in the absence of any other light, would have a first group-second group mixed illumination having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line segment connecting a first point to a second point, the second line segment connecting the second point to a third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38; and

if each of the light emitting diodes in the first and second groups of light emitting diodes is illuminated and each of the third group of light emitting diodes is illuminated, a mixture of light emitted from the first and second groups of light emitting diodes, light emitted from the first and second groups of lumiphors and light emitted from the third group of light emitting diodes would produce a first group-second group-third group mixed illumination having x, y coordinates on a 1931 CIE Chromaticity Diagram which define a point which is within 10 MacAdam ellipses (or within 20 MacAdam ellipses, or within 40 MacAdam ellipses) of at least one point within the range of from about 2200K to about 4500K on the blackbody locus on a 1931 CIE Chromaticity Diagram.

In some embodiments according to this aspect of the present invention (and other aspects of the present invention), the device can include additional 430 nm to 480 nm light emitting diodes which are not within the first group or the second group of light emitting diodes, and/or the device can include additional 555 nm to 585 nm lumiphors which are not within the first group or the second group of lumiphors, and/or the device can include additional 600 nm to 630 nm light emitting diodes which are not within the third group of light emitting diodes.

In some embodiments according to this aspect of the present invention (and other aspects of the present invention), the first and second groups of light emitting diodes consist of all of the 430 nm to 480 nm light emitting diodes in the device, the first and second groups of lumiphors consists of all of the 555 nm to 585 nm lumiphors in the device, and the third group of light emitting diodes consists of all of the 600 nm to 630 nm light emitting diodes in the device.

According to a twelfth aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
- a first group of lumiphors;
- a second group of light emitting diodes;
- a second group of lumiphors; and
- a third group of light emitting diodes;

21

at least one power line directly or switchably electrically connected to the lighting device,

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

if power is supplied to at least one of the at least one power line, a mixture of light emitted from the light emitting diodes in the first and second groups of light emitting diodes and the lumiphors in the first and second groups of lumiphors, in the absence of any other light, would have a first group-second group mixed illumination having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line segment connecting a first point to a second point, the second line segment connecting the second point to a third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38;

if power is supplied to at least one of the at least one power line, a mixture of light emitted from the light emitting diodes in the first and second groups of light emitting diodes, from the lumiphors in the first and second groups of lumiphors and from the third group of light emitting diodes would produce a first group-second group-third group mixed illumination having x, y coordinates on a 1931 CIE Chromaticity Diagram which define a point which is within 10 MacAdam ellipses (or within 20 MacAdam ellipses, or within 40 MacAdam ellipses) of at least one point within the range of from about 2200K to about 4500K on the blackbody locus on a 1931 CIE Chromaticity Diagram.

22

In some embodiments according to this aspect of the present invention (and other aspects of the present invention), the device can include additional 430 nm to 480 nm light emitting diodes which are not connected to the at least one power line, and/or the device can include additional 600 nm to 630 nm light emitting diodes which are not connected to the at least one power line.

In some embodiments according to this aspect of the present invention (and other aspects of the present invention), the first and second groups of light emitting diodes consist of all of the 430 nm to 480 nm light emitting diodes in the device, the first and second groups of lumiphors consist of all of the 555 nm to 585 nm lumiphors in the device, and the third group of light emitting diodes consists of all of the 600 nm to 630 nm light emitting diodes in the device.

According to a thirteenth aspect of the present invention, there is provided a lighting device comprising:

a first group of light emitting diodes;

a first group of lumiphors;

a second group of light emitting diodes;

a second group of lumiphors; and

a third group of light emitting diodes;

at least one power line directly or switchably electrically connected to the lighting device,

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

each of the third group of light emitting diodes, if illuminated, would emit light having a dominant wavelength in the range of from 600 nm to 630 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

if power is supplied to each of the at least one power line, a mixture of light emitted from the light emitting diodes in the first and second groups of light emitting diodes and the lumiphors in the first and second groups of lumiphors, in the absence of any other light, would have a first group-second group mixed illumination having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line segment connecting a first point to a second point, the second line segment connecting the second point to a

23

third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38; and if power is supplied to each of the at least one power line, a mixture of light emitted from the light emitting diodes in the first and second groups of light emitting diodes, from the lumiphors in the first and second groups of lumiphors and from the third group of light emitting diodes would produce a first group-second group-third group mixed illumination having x, y coordinates on a 1931 CIE Chromaticity Diagram which define a point which is within 10 MacAdam ellipses (or within 20 MacAdam ellipses, or within 40 MacAdam ellipses) of at least one point within the range of from about 2200K to about 4500K on the blackbody locus on a 1931 CIE Chromaticity Diagram.

In some embodiments according to this aspect of the present invention (and other aspects of the present invention), the device can include additional 430 nm to 480 nm light emitting diodes which are not connected to the at least one power line, and/or the device can include additional 600 nm to 630 nm light emitting diodes which are not connected to the at least one power line.

In some embodiments according to this aspect of the present invention (and other aspects of the present invention), the first and second groups of light emitting diodes consist of all of the 430 nm to 480 nm light emitting diodes in the device, the first and second groups of lumiphors consist of all of the 555 nm to 585 nm lumiphors in the device, and the third group of light emitting diodes consists of all of the 600 nm to 630 nm light emitting diodes in the device.

In accordance with the present invention, it has further been determined that an effective lighting device for use in generating light which can readily be mixed with light emitted from a 600 nm to 630 nm light emitting diode comprises:

- a first group of light emitting diodes;
- a first group of lumiphors;
- a second group of light emitting diodes;
- a second group of lumiphors; and

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have

24

a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

if each of the light emitting diodes in the first and second groups of light emitting diodes is illuminated and each of the lumiphors in the first and second groups of lumiphors is excited, a mixture of light emitted from the first and second groups of light emitting diodes and the first and second groups of lumiphors would, in the absence of any additional light, have a first group mixed illumination having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line segment connecting a first point to a second point, the second line segment connecting the second point to a third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38.

Accordingly, in a fourteenth aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
- a first group of lumiphors;
- a second group of light emitting diodes;
- a second group of lumiphors; and

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

if each of the light emitting diodes in the first and second groups of light emitting diodes is illuminated and each of the lumiphors in the first and second groups of lumiphors is excited, a mixture of light emitted from the first

25

and second groups of light emitting diodes and the first and second groups of lumiphors would, in the absence of any additional light, have a first group-second group mixed illumination having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line segment connecting a first point to a second point, the second line segment connecting the second point to a third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38.

In some embodiments according to this aspect of the present invention, the device can include additional 430 nm to 480 nm light emitting diodes which are not within the first group or the second group of light emitting diodes, and/or the device can include additional 555 nm to 585 nm lumiphors which are not within the first group or the second group of lumiphors, including wherein if any of such additional light emitting 430 nm to 480 nm diodes and/or 555 nm to 585 nm lumiphors were illuminated or excited in addition to all of the light emitting diodes in the first and second groups of light emitting diodes and all of the lumiphors in the first and second groups of lumiphors, there would be produced combined light having x, y color coordinates which are not within the area on a 1931 CIE Chromaticity Diagram enclosed by the first, second, third, fourth and fifth line segments defined above.

In some embodiments according to this aspect of the present invention, the first and second groups of light emitting diodes consist of all of the 430 nm to 480 nm light emitting diodes in the device, the first and second groups of lumiphors consist of all of the 555 nm to 585 nm lumiphors in the device, and the third group of light emitting diodes consists of all of the 600 nm to 630 nm light emitting diodes in the device.

According to a fifteenth aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
- a first group of lumiphors;
- a second group of light emitting diodes;
- a second group of lumiphors; and

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumi-

26

phors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

if each of the light emitting diodes in the first and second groups of light emitting diodes is illuminated, a mixture of light emitted from the first and second groups of light emitting diodes and the first and second groups of lumiphors would, in the absence of any additional light, have a first group-second group mixed illumination having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line segment connecting a first point to a second point, the second line segment connecting the second point to a third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38.

In some embodiments according to this aspect of the present invention, the device can include additional 430 nm to 480 nm light emitting diodes which are not within the first group or the second group of light emitting diodes, and/or the device can include additional 555 nm to 585 nm lumiphors which are not within the first group or the second group of lumiphors, including wherein if any of such additional light emitting diodes and/or lumiphors were illuminated or excited in addition to all of the light emitting diodes in the first and second groups of light emitting diodes and all of the lumiphors in the first and second groups of lumiphors, there would be produced combined light having x, y color coordinates which are not within the area on a 1931 CIE Chromaticity Diagram enclosed by the first, second, third, fourth and fifth line segments defined above.

According to a sixteenth aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
- a first group of lumiphors;
- a second group of light emitting diodes;
- a second group of lumiphors; and

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K).

In some embodiments according to this aspect of the present invention (and other aspects of the present invention), the device can include additional 430 nm to 480 nm light emitting diodes which are not within the first group or the second group of light emitting diodes, and/or the device can include additional 555 nm to 585 nm lumiphors which are not within the first group or the second group of lumiphors.

In some embodiments according to this aspect of the present invention (and other aspects of the present invention), the first and second groups of light emitting diodes consist of all of the 430 nm to 480 nm light emitting diodes in the device and the first and second groups of lumiphors consist of all of the 555 nm to 585 nm lumiphors in the device.

According to a seventeenth aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
- a first group of lumiphors;
- a second group of light emitting diodes;
- a second group of lumiphors; and

at least one power line directly or switchably electrically connected to the lighting device, wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

if power is supplied to at least one of the at least one power line, a mixture of light would be emitted from the first and second groups of light emitting diodes and the first and second groups of lumiphors which would, in the absence of any additional light, have a first group mixed

illumination having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line segment connecting a first point to a second point, the second line segment connecting the second point to a third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38.

In some embodiments according to this aspect of the present invention, the lighting device can include one or more additional 430 nm to 480 nm light emitting diodes which are not connected to the at least one power line (but which might be connected to some other power line), and in which, if such additional 430 nm to 480 nm light emitting diode(s) were illuminated in addition to all of the 430 nm to 480 nm light emitting diodes connected to the at least one power line, the combined light emitted from all of the 430 nm to 480 nm light emitting diodes in the device and the 555 nm to 585 nm lumiphors in the device, in the absence of any additional light, would have x, y color coordinates which are not within the area on a 1931 CIE Chromaticity Diagram enclosed by the first, second, third, fourth and fifth line segments defined above.

According to an eighteenth aspect of the present invention, there is provided a lighting device comprising:

- a first group of light emitting diodes;
- a first group of lumiphors;
- a second group of light emitting diodes;
- a second group of lumiphors; and

at least one power line directly or switchably electrically connected to the lighting device,

wherein:

each of the first group of light emitting diodes and each of the second group of light emitting diodes, if illuminated, would emit light having a peak wavelength in the range of from 430 nm to 480 nm;

each of the first group of lumiphors and each of the second group of lumiphors, if excited, would emit light having a dominant wavelength in the range of from about 555 nm to about 585 nm; and

if each of the first group of light emitting diodes is illuminated and each of the first group of lumiphors is excited, a mixture of light emitted from the first group of light emitting diodes and the first group of lumiphors would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

if each of the second group of light emitting diodes is illuminated and each of the second group of lumiphors is excited, a mixture of light emitted from the second group of light emitting diodes and the second group of lumiphors would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K); and

if power is supplied to each of the at least one power line, light would be emitted from the lighting device having x, y color coordinates which are within an area on a 1931 CIE Chromaticity Diagram enclosed by first, second, third, fourth and fifth line segments, the first line segment connecting a first point to a second point, the second line segment connecting the second point to a third point, the third line segment connecting the third point to a fourth point, the fourth line segment connecting the fourth point to a fifth point, and the fifth line segment connecting the fifth point to the first point, the first point having x, y coordinates of 0.32, 0.40, the second point having x, y coordinates of 0.36, 0.48, the third point having x, y coordinates of 0.43, 0.45, the fourth point having x, y coordinates of 0.42, 0.42, and the fifth point having x, y coordinates of 0.36, 0.38.

In some embodiments according to this aspect of the present invention, the lighting device can include additional 430 nm to 480 nm light emitting diodes which are not connected to any of the power lines (or are not connected to the power line) in the device, and in which, if such additional light emitting diodes were illuminated in addition to all of the light emitting diodes connected to the at least one power line, the combined light, in the absence of any additional light, would have x, y color coordinates which are not within the area on a 1931 CIE Chromaticity Diagram enclosed by the first, second, third, fourth and fifth line segments defined above.

According to a nineteenth aspect of the present invention, there is provided a method of lighting, comprising:

mixing light from a first group of at least one light emitting diode, light from a first group of at least one lumiphor, light from a second group of at least one light emitting diode, light from a second group of at least one lumiphor and light from a third group of at least one light emitting diode to form mixed light;

the light from each of the first group of at least one light emitting diode and the light from each of the second group of at least one light emitting diode having a peak wavelength in the range of from 430 nm to 480 nm;

the light from each of the first group of at least one lumiphor and the light from each of the second group of at least one lumiphor having a dominant wavelength in the range of from 555 nm to 585 nm;

the light from each of the third group of at least one light emitting diode having a dominant wavelength in the range of from 600 nm to 630 nm;

wherein:

the light from the first group of light emitting diodes and the light from the first group of lumiphors, if mixed in the absence of any other light, would have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

the light from the second group of light emitting diodes and the light from the second group of lumiphors, if mixed in the absence of any other light, would have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K).

According to a twentieth aspect of the present invention, there is provided a method of lighting, comprising:

mixing light from a first group of at least one light emitting diode, light from a first group of at least one lumiphor, light

from a second group of at least one light emitting diode and light from a second group of at least one lumiphor to form mixed light;

the light from each of the first group of at least one light emitting diode and the light from each of the second group of at least one light emitting diode having a peak wavelength in the range of from 430 nm to 480 nm;

the light from each of the first group of at least one lumiphor and the light from each of the second group of at least one lumiphor having a dominant wavelength in the range of from 555 nm to 585 nm;

wherein:

the light from the first group of light emitting diodes and the light from the first group of lumiphors, if mixed in the absence of any other light, would have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram, the first point having a first correlated color temperature;

the light from the second group of light emitting diodes and the light from the second group of lumiphors, if mixed in the absence of any other light, would have a second group mixed illumination corresponding to a second point on a 1931 CIE Chromaticity Diagram, the second point having a second correlated color temperature, the first correlated color temperature differing from the second correlated color temperature by at least 50 K (in some cases by at least 100 K; in some cases by at least 200 K; and in some cases by at least 500 K).

The light emitting diodes can be saturated or non-saturated. The term "saturated", as used herein, means having a purity of at least 85%, the term "purity" having a well-known meaning to persons skilled in the art, and procedures for calculating purity being well-known to those of skill in the art.

Aspects related to the present invention can be represented on either the 1931 CIE (Commission International de l'Eclairage) Chromaticity Diagram or the 1976 CIE Chromaticity Diagram. FIG. 1 shows the 1931 CIE Chromaticity Diagram. FIG. 2 shows the 1976 Chromaticity Diagram. FIG. 3 shows an enlarged portion of the 1976 Chromaticity Diagram, in order to show the blackbody locus in more detail. Persons of skill in the art are familiar with these diagrams, and these diagrams are readily available (e.g., by searching "CIE Chromaticity Diagram" on the internet).

The CIE Chromaticity Diagrams map out the human color perception in terms of two CIE parameters x and y (in the case of the 1931 diagram) or u' and v' (in the case of the 1976 diagram). For a technical description of CIE chromaticity diagrams, see, for example, "Encyclopedia of Physical Science and Technology", vol. 7, 230-231 (Robert A Meyers ed., 1987). The spectral colors are distributed around the edge of the outlined space, which includes all of the hues perceived by the human eye. The boundary line represents maximum saturation for the spectral colors. As noted above, the 1976 CIE Chromaticity Diagram is similar to the 1931 Diagram, except that the 1976 Diagram has been modified such that similar distances on the Diagram represent similar perceived differences in color.

In the 1931 Diagram, deviation from a point on the Diagram can be expressed either in terms of the coordinates or, alternatively, in order to give an indication as to the extent of the perceived difference in color, in terms of MacAdam ellipses. For example, a locus of points defined as being ten MacAdam ellipses from a specified hue defined by a particular set of coordinates on the 1931 Diagram consists of hues which would each be perceived as differing from the specified

hue to a common extent (and likewise for loci of points defined as being spaced from a particular hue by other quantities of MacAdam ellipses).

Since similar distances on the 1976 Diagram represent similar perceived differences in color, deviation from a point on the 1976 Diagram can be expressed in terms of the coordinates, u' and v' , e.g., distance from the point $=(\Delta u'^2 + \Delta v'^2)^{1/2}$, and the hues defined by a locus of points which are each a common distance from a specified hue consist of hues which would each be perceived as differing from the specified hue to a common extent.

The chromaticity coordinates and the CIE chromaticity diagrams illustrated in FIGS. 1-3 are explained in detail in a number of books and other publications, such as pages 98-107 of K. H. Butler, "Fluorescent Lamp Phosphors" (The Pennsylvania State University Press 1980) and pages 109-110 of G. Blasse et al., "Luminescent Materials" (Springer-Verlag 1994), both incorporated herein by reference.

The chromaticity coordinates (i.e., color points) that lie along the blackbody locus obey Planck's equation: $E(\lambda) = A \lambda^{-5} / (e^{B/\lambda} - 1)$, where E is the emission intensity, λ is the emission wavelength, T the color temperature of the blackbody and A and B are constants. Color coordinates that lie on or near the blackbody locus yield pleasing white light to a human observer. The 1976 CIE Diagram includes temperature listings along the blackbody locus. These temperature listings show the color path of a blackbody radiator that is caused to increase to such temperatures. As a heated object becomes incandescent, it first glows reddish, then yellowish, then white, and finally blueish. This occurs because the wavelength associated with the peak radiation of the blackbody radiator becomes progressively shorter with increased temperature, consistent with the Wien Displacement Law. Illuminants which produce light which is on or near the blackbody locus can thus be described in terms of their color temperature.

Also depicted on the 1976 CIE Diagram are designations A, B, C, D and E, which refer to light produced by several standard illuminants correspondingly identified as illuminants A, B, C, D and E, respectively.

CRI Ra is a modified average of the relative measurements of how the color rendition of an illumination system compares to that of a reference radiator when illuminating eight reference colors. The CRI Ra equals 100 if the color coordinates of a set of test colors being illuminated by the illumination system are the same as the coordinates of the same test colors being irradiated by the blackbody radiator.

The present invention may be more fully understood with reference to the accompanying drawings and the following detailed description of the invention.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

FIG. 1 shows the 1931 CIE Chromaticity Diagram.

FIG. 2 shows the 1976 Chromaticity Diagram.

FIG. 3 shows an enlarged portion of the 1976 Chromaticity Diagram, in order to show the blackbody locus in detail.

FIG. 4 is a schematic diagram of a representative example of a lighting device in accordance with the present invention.

FIG. 5 depicts a representative example of a packaged LED which can be used in the devices according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The expression "correlated color temperature" is used according to its well-known meaning to refer to the tempera-

ture of a blackbody that is, in a well-defined sense (i.e., can be readily and precisely determined by those skilled in the art), nearest in color.

The expression "directly or switchably electrically connected" means "directly electrically connected" or "switchably electrically connected."

A statement herein that two components in a device are "directly electrically connected," means that there are no components electrically between the components, the insertion of which materially affect the function or functions provided by the device. For example, two components can be referred to as being electrically connected, even though they may have a small resistor between them which does not materially affect the function or functions provided by the device (indeed, a wire connecting two components can be thought of as a small resistor); likewise, two components can be referred to as being electrically connected, even though they may have an additional electrical component between them which allows the device to perform an additional function, while not materially affecting the function or functions provided by a device which is identical except for not including the additional component; similarly, two components which are directly connected to each other, or which are directly connected to opposite ends of a wire or a trace on a circuit board, are electrically connected.

A statement herein that two components in a device are "switchably electrically connected" means that there is a switch located between the two components, the switch being selectively closed or opened, wherein if the switch is closed, the two components are directly electrically connected, and if the switch is open (i.e., during any time period that the switch is open), the two components are not electrically connected.

The expression "illuminated", as used herein when referring to a light emitting diode, means that at least some current is being supplied to the light emitting diode to cause the light emitting diode to emit at least some light. The expression "illuminated" encompasses situations where the light emitting diode emits light continuously or intermittently at a rate such that a human eye would perceive it as emitting light continuously, or where a plurality of light emitting diodes of the same color or different colors are emitting light intermittently and/or alternately (with or without overlap in "on" times) in such a way that a human eye would perceive them as emitting light continuously (and, in cases where different colors are emitted, as a mixture of those colors).

The expression "excited", as used herein when referring to a lumiphor, means that at least some electromagnetic radiation (e.g., visible light, UV light or infrared light) is contacting the lumiphor, causing the lumiphor to emit at least some light. The expression "excited" encompasses situations where the lumiphor emits light continuously or intermittently at a rate such that a human eye would perceive it as emitting light continuously, or where a plurality of lumiphors of the same color or different colors are emitting light intermittently and/or alternately (with or without overlap in "on" times) in such a way that a human eye would perceive them as emitting light continuously (and, in cases where different colors are emitted, as a mixture of those colors).

The light emitting diode (or light emitting diodes) used in the devices according to the present invention, and the lumiphor (or lumiphors) used in the devices according to the present invention, can be selected from among any light emitting diodes and lumiphors known to persons of skill in the art. Wide varieties of such light emitting diodes and lumiphors are readily obtainable and well known to those of skilled in the art, and any of them can be employed (e.g., AlInGaP for the 600 nm to 630 nm light emitting diodes).

Examples of types of such light emitting diodes include inorganic and organic light emitting diodes, a variety of each of which are well-known in the art.

The one or more luminescent materials can be any desired luminescent material. The one or more luminescent materials can be down-converting or up-converting, or can include a combination of both types. For example, the one or more luminescent materials can be selected from among phosphors, scintillators, day glow tapes, inks which glow in the visible spectrum upon illumination with ultraviolet light, etc. Additionally, the luminescent material may be embedded in a substantially transparent glass or metal oxide material.

The one or more luminescent materials can be provided in any desired form. For example, the luminescent element can be embedded in a resin (i.e., a polymeric matrix), such as a silicone material or an epoxy.

The one or more lumiphors can individually be any lumiphor, a wide variety of which, as noted above, are known to those skilled in the art. For example, the or each lumiphor can comprise (or can consist essentially of, or can consist of) one or more phosphor. The or each of the one or more lumiphors can, if desired, further comprise (or consist essentially of, or consist of) one or more highly transmissive (e.g., transparent or substantially transparent, or somewhat diffuse) binder, e.g., made of epoxy, silicone, glass or any other suitable material (for example, in any given lumiphor comprising one or more binder, one or more phosphor can be dispersed within the one or more binder). For example, the thicker the lumiphor, in general, the lower the weight percentage of the phosphor can be. Representative examples of the weight percentage of phosphor include from about 3.3 weight percent to about 4.7 weight percent, although, as indicated above, depending on the overall thickness of the lumiphor, the weight percentage of the phosphor could be generally any value, e.g., from 0.1 weight percent to 100 weight percent (e.g., a lumiphor formed by subjecting pure phosphor to a hot isostatic pressing procedure). In some situations, a weight percentage of about 20 weight percent is advantageous.

The or each of the one or more lumiphors can, independently, further comprise any of a number of well-known additives, e.g., diffusers, scatterers, tints, etc.

In some embodiments of the present invention, different power lines (i.e., any structure which can carry electrical energy to a light emitting diode) are electrically connected (directly or switchably) to light emitting diodes of the different groups, and the relative quantities of light emitting diodes connected to the respective power lines differ from one power line to the next, e.g., a first power line contains a first percentage of 430 nm to 480 nm light emitting diodes and a second power line contains a second percentage (different from the first percentage) of 430 nm to 480 nm light emitting diodes. As a representative example, first and second power lines each contain 100% 430 nm to 480 nm light emitting diodes, and a third power line contains 50% 430 nm to 480 nm light emitting diodes and 50% 600 nm to 630 nm light emitting diodes. By doing so, it is possible to easily adjust the relative intensities of the light of the respective wavelengths, and thereby effectively navigate within the CIE Diagram and/or compensate for other changes. For example, the intensity of red light can be increased, when necessary, in order to compensate for any reduction of the intensity of the light generated by the 600 nm to 630 nm light emitting diodes. Thus, for instance, in the representative example described above, by increasing the current supplied to the third power line, or by decreasing the current supplied to the first power line and/or second power line (and/or by interrupting the supply of power to the first power line or the second power line), the x, y

coordinates of the mixed light emitted from the lighting device can be appropriately adjusted.

Similarly, the color of the yellowish, yellowish-whitish or whitish light which is mixed with the reddish light (emitted by the 600 nm to 630 nm light emitting diodes) can be adjusted (between more yellowish and less yellowish) by providing power lines which have differing relative quantities of 430 nm to 480 nm light emitting diodes and 555 nm to 585 nm lumiphors, and then simply adjusting the current supplied to one or more of such power lines (and/or interrupting current supply to one or more of such power lines). As a representative example

a first power line contains 30% first group LED packages (each first group LED package including a 430 nm to 480 nm light emitting diode and a 555 nm to 585 nm lumiphor) and 70% second group LED packages (each second group LED package also including a 430 nm to 480 nm light emitting diode and a 555 nm to 585 nm lumiphor);

a second power line contains 70% first group LED packages (each first group LED package including a 430 nm to 480 nm light emitting diode and a 555 nm to 585 nm lumiphor) and 30% second group LED packages (each second group LED package also including a 430 nm to 480 nm light emitting diode and a 555 nm to 585 nm lumiphor); and

a third power line contains 30% first group LED packages (each first group LED package including a 430 nm to 480 nm light emitting diode and a 555 nm to 585 nm lumiphor), 30% second group LED packages (each second group LED package also including a 430 nm to 480 nm light emitting diode and a 555 nm to 585 nm lumiphor), and 40% 600 nm to 630 nm (third group) light emitting diodes,

wherein the first group LED packages are more yellowish than the second group LED packages.

By increasing the current applied to the first power line (and/or decreasing the current applied to the second power line), the x,y coordinates of the resulting mixed light will be closer to the 430 nm to 480 nm range; by increasing the current applied to the second power line (and/or decreasing the current applied to the first power line), the x,y coordinates of the resulting mixed light will be closer to the 555 nm to 585 nm range; by increasing the current applied to the third power line (and/or decreasing the current applied to the first and second power lines), the x,y coordinates of the resulting mixed light will be closer to the 600 nm to 630 nm range. In other words, by adjusting the respective current supplied to each of the respective power lines (and/or by interrupting current supplied to any of the power lines), it is possible to navigate within the CIE Diagram to achieve the desired mixed light hue (and/or to compensate for other factors which would otherwise cause the hue of the light to drift away from a desired point. Because it is possible to adjust the color coordinates in two dimensions, it is possible, for example, to move the mixed color point along a curved (or any other shape) path, in addition to or instead of a straight line path, e.g., to track the blackbody locus (or to remain within a maximum number of MacAdam ellipses from varying blackbody temperatures). For example, it is possible to easily alter the color temperature (or correlated color temperature) of the lighting device.

In some embodiments of the present invention, different power lines (i.e., any structure which can carry electrical energy to a light emitting diode) are electrically connected (directly or switchably) to light emitting diodes of the different groups, and the relative quantities of light emitting diodes

35

connected to the respective power lines differ from one power line to the next, e.g., a first power line contains a first percentage of 430 nm to 480 nm light emitting diodes and a second power line contains a second percentage (different from the first percentage) of 430 nm to 480 nm light emitting diodes. As a representative example, first and second power lines each contain 100% 430 nm to 480 nm light emitting diodes, and a third power line contains 50% 430 nm to 480 nm light emitting diodes and 50% 600 nm to 630 nm light emitting diodes. By doing so, it is possible to easily adjust the relative intensities of the light of the respective wavelengths, and thereby effectively navigate within the CIE Diagram and/or compensate for other changes. For example, the intensity of red light can be increased, when necessary, in order to compensate for any reduction of the intensity of the light generated by the 600 nm to 630 nm light emitting diodes. Thus, for instance, in the representative example described above, by increasing the current supplied to the third power line, or by decreasing the current supplied to the first power line and/or second power line (and/or by interrupting the supply of power to the first power line or the second power line), the x, y coordinates of the mixed light emitted from the lighting device can be appropriately adjusted.

In some embodiments of the present invention, there are further provided one or more current adjusters directly or switchably electrically connected to one or more of respective power lines which are electrically connected to light emitting diodes, whereby the current adjuster can be adjusted to adjust the current supplied to the respective light emitting diode(s).

In some embodiments of the present invention, there are further provided one or more switches electrically connected to one of respective power lines, whereby the switch selectively switches on and off current to the light emitting diode(s) on the respective power line.

In some embodiments of the present invention, one or more current adjusters and/or one or more switches automatically interrupt and/or adjust current passing through one or more respective power lines in response to a detected change in the output from the lighting device (e.g., an extent of deviation from the blackbody locus) or in accordance with a desired pattern (e.g., based on the time of day or night, such as altering the correlated color temperature of the combined emitted light).

In some embodiments of the present invention, there are further provided one or more thermistors which detect temperature and, as temperature changes, cause one or more current adjusters and/or one or more switches to automatically interrupt and/or adjust current passing through one or more respective power lines in order to compensate for such temperature change. In general, 600 nm to 630 nm light emitting diodes get dimmer as their temperature increases—in such embodiments, fluctuations in intensity caused by such temperature variation can be compensated for.

In some lighting devices according to the present invention, there are further included one or more circuitry components, e.g., drive electronics for supplying and controlling current passed through at least one of the one or more light emitting diodes in the lighting device. Persons of skill in the art are familiar with a wide variety of ways to supply and control the current passed through light emitting diodes, and any such ways can be employed in the devices of the present invention. For example, such circuitry can include at least one contact, at least one leadframe, at least one current regulator, at least one power control, at least one voltage control, at least one boost, at least one capacitor and/or at least one bridge rectifier, persons of skill in the art being familiar with such

36

components and being readily able to design appropriate circuitry to meet whatever current flow characteristics are desired.

The present invention further relates to an illuminated enclosure, comprising an enclosed space and at least one lighting device according to the present invention, wherein the lighting device illuminates at least a portion of the enclosure.

The present invention further relates to an illuminated surface, comprising a surface and at least one lighting device according to the present invention, wherein the lighting device illuminates at least a portion of the surface.

The present invention further relates to an illuminated area, comprising at least one area selected from among the group consisting of a structure, a swimming pool, a room, a warehouse, an indicator, a road, a vehicle, a road sign, a billboard, a ship, a boat, an aircraft, a stadium, a tree, a window, an LCD display, a cave or tunnel, and a lamppost having mounted therein or thereon at least one lighting device according to the present invention.

In addition, persons of skill in the art are familiar with a wide variety of mounting structures for many different types of lighting, and any such structures can be used according to the present invention. For example, FIG. 4 depicts a lighting device which includes a heat spreading element 11 (formed of a material with good heat conducting properties, e.g., aluminum), insulating regions 12 (which can be applied and/or formed in situ, e.g., by anodizing), a highly reflective surface 13 (which can be applied, e.g., MCPET, marketed by Furukawa of Japan, laminated aluminum or silver or formed in situ, e.g., by polishing), conductive traces 14, leadframes 15, packaged LED's 16, a reflective cone 17 and a diffusing element 18. The device depicted in FIG. 4 can further include an insulating element 28 below the conductive traces 14 to avoid unintended contact (e.g., a person receiving a shock) with the conductive traces. The device depicted in FIG. 4 can include any number of packaged LED's (e.g., up to 50 or 100 or more), and so the heat spreading element 11, as well as the insulating regions 12, reflective surface 13 and insulating element 28 can extend any necessary distance to the right or left, in the orientation shown in FIG. 4, as indicated by the fragmented structures (similarly, the sides of the reflective cone 17 can be located any distance to the right or left). Similarly, the diffusing element 18 can be located any desired distance from the LED's 16. The diffusing element 18 can be attached to the reflective cone 17, the insulating element 28, the heat spreading element 11, or any other desired structure in any suitable way, persons of skill in the art being familiar with and readily able to provide such attachment in a wide variety of ways. In this embodiment, and other embodiments, the heat spreading element 11 serves to spread out the heat, act as a heat sink, and/or dissipate the heat. Likewise, the reflective cone 17 functions as a heat sink. In addition, the reflective cone 17 can include ridges 19 to enhance its reflective properties.

FIG. 5 depicts a representative example of a packaged LED which can be used in the devices according to the present invention. Referring to FIG. 5, there is shown a lighting device 20 comprising a solid state light emitter 21 (in this case, a light emitting diode chip 21), a first electrode 22, a second electrode 23, an encapsulant region 24, a reflective element 26 in which the light emitting diode chip 21 is mounted and a lumiphor 27. A packaged LED which does not include any lumiphor (e.g., a 600 nm to 630 nm light emitting diode) can be constructed in a similar way but without the inclusion of a lumiphor 27. Persons of skill in the art are familiar with, and have ready access to, a wide variety of other

packaged and unpackaged LED structures, any of which can, if desired, be employed according to the present invention.

In some embodiments according to the present invention, one or more of the light emitting diodes can be included in a package together with one or more of the lumiphors, and the one or more lumiphor in the package can be spaced from the one or more light emitting diode in the package to achieve improved light extraction efficiency, as described in U.S. Patent Application No. 60/753,138, filed on Dec. 22, 2005, entitled "Lighting Device" (inventor: Gerald H. Negley), the entirety of which is hereby incorporated by reference.

In some embodiments according to the present invention, two or more lumiphors can be provided, two or more of the lumiphors being spaced from each other, as described in U.S. Patent Application No. 60/761,310, filed on Jan. 23, 2006, entitled "Shifting Spectral Content in LEDs by Spatially Separating Lumiphor Films" (inventors: Gerald H. Negley and Antony Van De Ven), the entirety of which is hereby incorporated by reference.

In some lighting devices according to the present invention, there are further included one or more power sources, e.g., one or more batteries and/or solar cells, and/or one or more standard AC power plugs (i.e., any of a wide variety of plugs which can be received in a standard AC power receptacle, e.g., any of the familiar types of three-pronged power plugs).

The lighting devices according to the present invention can comprise any desired number of LED's and lumiphors. For example, a lighting device according to the present invention can include 50 or more light emitting diodes, or can include 100 or more light emitting diodes, etc. In general, with current light emitting diodes, greater efficiency can be achieved by using a greater number of smaller light emitting diodes (e.g., 100 light emitting diodes each having a surface area of 0.1 mm² vs. 25 light emitting diodes each having a surface area of 0.4 mm² but otherwise being identical).

Analogously, light emitting diodes which operate at lower current densities are generally more efficient. Light emitting diodes which draw any particular current can be used according to the present invention. In one aspect of the present invention, light emitting diodes which each draw not more than 50 milliamps are employed.

Other embodiments may include fewer LEDs, as little as one each of blue and red, and such could be small chip LEDs or high power LEDs; and provided with sufficient heat sinking be operated at high currents. In the case of high power LEDs, operating up to 5A is possible.

The sources of visible light in the lighting devices of the present invention can be arranged, mounted and supplied with electricity in any desired manner, and can be mounted on any desired housing or fixture. Skilled artisans are familiar with a wide variety of arrangements, mounting schemes, power supplying apparatuses, housings and fixtures, and any such arrangements, schemes, apparatuses, housings and fixtures can be employed in connection with the present invention. The lighting devices of the present invention can be electrically connected (or selectively connected) to any desired power source, persons of skill in the art being familiar with a variety of such power sources.

Representative examples of arrangements of sources of visible light, schemes for mounting sources of visible light, apparatus for supplying electricity to sources of visible light, housings for sources of visible light, fixtures for sources of visible light and power supplies for sources of visible light, all of which are suitable for the lighting devices of the present invention, are described in U.S. Patent Application No. 60/752,753, filed on Dec. 21, 2005, entitled "Lighting

Device" (inventors: Gerald H. Negley, Antony Paul Ven de Ven and Neal Hunter), the entirety of which is hereby incorporated by reference.

The light emitting diodes and lumiphors can be arranged in any desired pattern. In some embodiments according to the present invention which include 600 nm to 630 nm (dominant wavelength) light emitting diodes as well as 430 nm to 480 nm (peak wavelength) light emitting diodes, some or all of the 600 are surrounded by five or six 430 nm to 480 nm light emitting diodes (some or all of which may or may not include 555 nm to 585 nm lumiphors), e.g., the 600 nm to 630 nm light emitting diodes and the 430 nm to 480 nm light emitting diodes are arranged in generally laterally arranged rows and spaced from one another substantially evenly, each row being laterally offset from the next adjacent (in a longitudinal direction) row by half the distance between laterally adjacent light emitting diodes, with, in most locations, two 430 nm to 480 nm light emitting diodes being located between each 600 nm to 630 nm light emitting diode and its nearest neighbor in the same row, and with the 600 nm to 630 nm light emitting diodes in each row being offset from the nearest 600 nm to 630 light emitting diode(s) in the next adjacent (in a longitudinal direction) row by one and a half times the distance between laterally spaced adjacent light emitting diodes. Alternatively or additionally, in some embodiments according to the present invention, some or all of the brighter light emitting diodes are placed closer to a center of the lighting device than the dimmer light emitting diodes. Generally, it is preferred that the location of the 430 nm to 480 nm (peak wavelength) light emitting diodes be arranged so that they are closer to the outside periphery of the fixture and that the 600 nm to 630 nm (dominant wavelength) light emitting diodes are arranged within the periphery of the fixture.

The devices according to the present invention can further comprise one or more long-life cooling device (e.g., a fan with an extremely high lifetime). Such long-life cooling device(s) can comprise piezoelectric or magnetorestrictive materials (e.g., MR, GMR, and/or HMR materials) that move air as a "Chinese fan". In cooling the devices according to the present invention, typically only enough air to break the boundary layer is required to induce temperature drops of 10 to 15 degrees C. Hence, in such cases, strong "breezes" or a large fluid flow rate (large CFM) are typically not required (thereby avoiding the need for conventional fans).

In some embodiments according to the present invention, any of the features, e.g., circuitry, as described in U.S. Patent Application No. 60/761,879, filed on Jan. 25, 2006, entitled "Lighting Device With Cooling" (inventors: Thomas Coleman, Gerald H. Negley and Antony Van De Ven), the entirety of which is hereby incorporated by reference, can be employed.

The devices according to the present invention can further comprise secondary optics to further change the projected nature of the emitted light. Such secondary optics are well-known to those skilled in the art, and so they do not need to be described in detail herein—any such secondary optics can, if desired, be employed.

The devices according to the present invention can further comprise sensors or charging devices or cameras, etc. For example, persons of skill in the art are familiar with, and have ready access to, devices which detect one or more occurrence (e.g., motion detectors, which detect motion of an object or person), and which, in response to such detection, trigger illumination of a light, activation of a security camera, etc. As a representative example, a device according to the present invention can include a lighting device according to the present invention and a motion sensor, and can be constructed

such that (1) while the light is illuminated, if the motion sensor detects movement, a security camera is activated to record visual data at or around the location of the detected motion, or (2) if the motion sensor detects movement, the light is illuminated to light the region near the location of the detected motion and the security camera is activated to record visual data at or around the location of the detected motion, etc.

For indoor residential illumination a color temperature of 2700 k to 3500 k is normally preferred; for indoor illumination of commercial indoor locations such as office spaces and in general illumination in tropical geographic latitudes, an indoor color temperature of 3500 to 5000 K is often desired; and for outdoor flood lighting of colorful scenes a color temperature approximating daylight 5000K (4500-6500K) is preferred.

Any two or more structural parts of the lighting devices described herein can be integrated. Any structural part of the lighting devices described herein can be provided in two or more parts (which can be held together, if necessary).

The invention claimed is:

1. A lighting device comprising:

a first group of solid state light emitters comprising at least one solid state light emitter;

a second group of solid state light emitters comprising at least one solid state light emitter;

at least first and second portions of luminescent material; and

at least a first power line and a second power line,

wherein:

if the first group of solid state light emitters is illuminated, a portion of light emitted from the first group of solid state light emitters would excite the first portion of luminescent material, and a mixture of light exiting the lighting device that was emitted from the first group of solid state light emitters and light exiting the lighting device that was emitted from the first portion of luminescent material would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram;

if the second group of solid state light emitters is illuminated, a portion of light emitted from the second group of solid state light emitters would excite the second portion of luminescent material, and a mixture of light exiting the lighting device that was emitted from the second group of solid state light emitters and light exiting the lighting device that was emitted from the second portion of luminescent material would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on the 1931 CIE Chromaticity Diagram,

a first ratio comprising a number of solid state light emitters on the first power line that are in the first group of solid state light emitters, divided by a number of solid state light emitters on the first power line that are in the second group of solid state light emitters,

a second ratio comprising a number of solid state light emitters on the second power line that are in the first group of solid state light emitters, divided by a number of solid state light emitters on the second power line that are in the second group of solid state light emitters, the first ratio differing from the second ratio.

2. A lighting device as recited in claim 1, wherein the first point on the 1931 CIE Chromaticity Diagram is spaced from the blackbody locus.

3. A lighting device as recited in claim 2, wherein the second point on the 1931 CIE Chromaticity Diagram is spaced from the blackbody locus.

4. A lighting device as recited in claim 3, wherein: the first point on the 1931 CIE Chromaticity Diagram is spaced from the blackbody locus in a first direction, and the second point on the 1931 CIE Chromaticity Diagram is spaced from the blackbody locus in a second direction, the second direction different from the first direction.

5. A lighting device as recited in claim 3, wherein: the first point on the 1931 CIE Chromaticity Diagram is above the blackbody locus, and the second point on the 1931 CIE Chromaticity Diagram is below the blackbody locus.

6. A lighting device as recited in claim 1, wherein: the lighting device further comprises at least a third group of solid state light emitters and at least a third portion of luminescent material, the third group of solid state light emitters comprising at least one solid state light emitter, and

if the third group of solid state light emitters is illuminated, a portion of light emitted from the third group of solid state light emitters would excite the third portion of luminescent material, and a mixture of light exiting the lighting device that was emitted from the third group of solid state light emitters and light exiting the lighting device that was emitted from the third portion of luminescent material would, in the absence of any additional light, have a third group mixed illumination corresponding to a third point on the 1931 CIE Chromaticity Diagram, the third point on a 1931 CIE Chromaticity Diagram differing from the first point on the 1931 CIE Chromaticity Diagram and from the second point on the 1931 CIE Chromaticity Diagram.

7. A lighting device as recited in claim 6, wherein the lighting device further comprises at least a third power line.

8. A lighting device as recited in claim 6, wherein: the lighting device further comprises a third power line, a third ratio comprises a number of solid state light emitters on the first power line that are in the first group of solid state light emitters, divided by a number of solid state light emitters on the first power line that are in the third group of solid state light emitters,

a fourth ratio comprises a number of solid state light emitters on the third power line that are in the first group of solid state light emitters, divided by a number of solid state light emitters on the third power line that are in the third group of solid state light emitters, and

the third ratio differs from the fourth ratio.

9. A lighting device as recited in claim 8, wherein the lighting device further comprises a fourth power line.

10. A lighting device as recited in claim 6, wherein: a third ratio comprises a number of solid state light emitters on the first power line that are in the first group of solid state light emitters, divided by a number of solid state light emitters on the first power line that are in the third group of solid state light emitters,

a fourth ratio comprises a number of solid state light emitters on the second power line that are in the first group of solid state light emitters, divided by a number of solid state light emitters on the second power line that are in the third group of solid state light emitters, and the third ratio differs from the fourth ratio.

11. A lighting device as recited in claim 1, wherein if the first group of solid state light emitters is illuminated, a mixture of light exiting the lighting device that was emitted from the first group of solid state light emitters and light exiting the

41

lighting device that was emitted from the first portion of luminescent material would, in the absence of any additional light, have a first group mixed illumination having a correlated color temperature that is:

- in the range of from about 2700 K to about 3500 K,
- in the range of from about 2200 K to about 4500 K,
- in the range of from about 3500 K to about 5000 K,
- in the range of from about 4500 K to about 6500 K, and/or about 5000 K.

12. A lighting device as recited in claim 1, wherein if all of the solid state light emitters in the lighting device are illuminated, a mixture of light exiting the lighting device would be white light.

13. A lighting device as recited in claim 1, wherein if all of the solid state light emitters in the lighting device are illuminated, a mixture of light exiting the lighting device would be non-white light.

14. A lighting device comprising:

- a first group of solid state light emitters comprising at least one solid state light emitter;
- a second group of solid state light emitters comprising at least one solid state light emitter; and
- at least first and second portions of luminescent material, wherein:

if the first group of solid state light emitters is illuminated, a portion of light emitted from the first group of solid state light emitters would excite the first portion of luminescent material, and a mixture of light exiting the lighting device that was emitted from the first group of solid state light emitters and light exiting the lighting device that was emitted from the first portion of luminescent material would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram;

if the second group of solid state light emitters is illuminated, a portion of light emitted from the second group of solid state light emitters would excite the second portion of luminescent material, and a mixture of light exiting the lighting device that was emitted from the second group of solid state light emitters and light exiting the lighting device that was emitted from the second portion of luminescent material would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on the 1931 CIE Chromaticity Diagram, the first point on the 1931 CIE Chromaticity Diagram is spaced from the blackbody locus, and the second point on the 1931 CIE Chromaticity Diagram is spaced from the blackbody locus.

15. A lighting device as recited in claim 14, wherein: the first point on the 1931 CIE Chromaticity Diagram is spaced from the blackbody locus in a first direction, and the second point on the 1931 CIE Chromaticity Diagram is spaced from the blackbody locus in a second direction, the second direction different from the first direction.

16. A lighting device as recited in claim 14, wherein: the first point on the 1931 CIE Chromaticity Diagram is above the blackbody locus, and the second point on the 1931 CIE Chromaticity Diagram is below the blackbody locus.

17. A lighting device as recited in claim 14, wherein: the lighting device further comprises at least a third group of solid state light emitters and at least a third portion of luminescent material, the third group of solid state light emitters comprising at least one solid state light emitter, and

42

if the third group of solid state light emitters is illuminated, a portion of light emitted from the third group of solid state light emitters would excite the third portion of luminescent material, and a mixture of light exiting the lighting device that was emitted from the third group of solid state light emitters and light exiting the lighting device that was emitted from the third portion of luminescent material would, in the absence of any additional light, have a third group mixed illumination corresponding to a third point on the 1931 CIE Chromaticity Diagram, the third point on a 1931 CIE Chromaticity Diagram differing from the first point on the 1931 CIE Chromaticity Diagram and from the second point on the 1931 CIE Chromaticity Diagram.

18. A lighting device as recited in claim 14, wherein if the first group of solid state light emitters is illuminated, a mixture of light exiting the lighting device that was emitted from the first group of solid state light emitters and light exiting the lighting device that was emitted from the first portion of luminescent material would, in the absence of any additional light, have a first group mixed illumination having a correlated color temperature that is:

- in the range of from about 2700 K to about 3500 K,
- in the range of from about 2200 K to about 4500 K,
- in the range of from about 3500 K to about 5000 K,
- in the range of from about 4500 K to about 6500 K, and/or about 5000 K.

19. A lighting device as recited in claim 14, wherein if all of the solid state light emitters in the lighting device are illuminated, a mixture of light exiting the lighting device would be white light.

20. A lighting device as recited in claim 14, wherein if all of the solid state light emitters in the lighting device are illuminated, a mixture of light exiting the lighting device would be non-white light.

21. A lighting device comprising:

- a first group of solid state light emitters comprising at least one solid state light emitter;
- a second group of solid state light emitters comprising at least one solid state light emitter; and
- at least first and second portions of luminescent material, wherein:

if the first group of solid state light emitters is illuminated, a portion of light emitted from the first group of solid state light emitters would excite the first portion of luminescent material, and a mixture of light exiting the lighting device that was emitted from the first group of solid state light emitters and light exiting the lighting device that was emitted from the first portion of luminescent material would, in the absence of any additional light, have a first group mixed illumination corresponding to a first point on a 1931 CIE Chromaticity Diagram;

if the second group of solid state light emitters is illuminated, a portion of light emitted from the second group of solid state light emitters would excite the second portion of luminescent material, and a mixture of light exiting the lighting device that was emitted from the second group of solid state light emitters and light exiting the lighting device that was emitted from the second portion of luminescent material would, in the absence of any additional light, have a second group mixed illumination corresponding to a second point on the 1931 CIE Chromaticity Diagram, the first point on the 1931 CIE Chromaticity Diagram is above the blackbody locus, and

the second point on the 1931 CIE Chromaticity Diagram is below the blackbody locus.

22. A lighting device as recited in claim 21, wherein: the lighting device further comprises at least a third group of solid state light emitters and at least a third portion of luminescent material, the third group of solid state light emitters comprising at least one solid state light emitter, and

if the third group of solid state light emitters is illuminated, a portion of light emitted from the third group of solid state light emitters would excite the third portion of luminescent material, and a mixture of light exiting the lighting device that was emitted from the third group of solid state light emitters and light exiting the lighting device that was emitted from the third portion of luminescent material would, in the absence of any additional light, have a third group mixed illumination corresponding to a third point on the 1931 CIE Chromaticity Diagram, the third point on a 1931 CIE Chromaticity Diagram differing from the first point on the 1931 CIE Chromaticity Diagram and from the second point on the 1931 CIE Chromaticity Diagram.

23. A lighting device as recited in claim 21, wherein if the first group of solid state light emitters is illuminated, a mixture of light exiting the lighting device that was emitted from the first group of solid state light emitters and light exiting the lighting device that was emitted from the first portion of luminescent material would, in the absence of any additional light, have a first group mixed illumination having a correlated color temperature that is:

- in the range of from about 2700 K to about 3500 K,
- in the range of from about 2200 K to about 4500 K,
- in the range of from about 3500 K to about 5000 K,
- in the range of from about 4500 K to about 6500 K, and/or about 5000 K.

24. A lighting device as recited in claim 21, wherein if all of the solid state light emitters in the lighting device are illuminated, a mixture of light exiting the lighting device would be white light.

25. A lighting device as recited in claim 21, wherein if all of the solid state light emitters in the lighting device are illuminated, a mixture of light exiting the lighting device would be non-white light.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,297,503 B2
APPLICATION NO. : 14/252855
DATED : March 29, 2016
INVENTOR(S) : Antony Paul Van De Ven et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:


Title Page, Other Publications, Page 4, Right Column

Please change: "CSA International, "Test Data Report," Project No. 1786317, Report No. 786317-1 (Apr. 2006)." to -- CSA International, "Test Data Report," Project No. 1786317, Report No. 1786317-1 (Apr. 2006). --

Title Page, Other Publications, Page 4, Right Column

Please change: "Krames et al., *Lumileds Lighting, Light from Silicon Valley*, Progress and Future Direction of LED Technology, SSL Workshop, Nov. 13, 2003, Publisher: Lumileds Lighting Inc., pp. 1-21." to -- Krames et al., *Lumileds Lighting, Light from Silicon Valley*, Progress and Future Direction of LED Technology, SSL Workshop, Nov. 13, 2003, Publisher: Lumileds Lighting Inc., pp. 1-21. --

Signed and Sealed this
Thirty-first Day of May, 2016



Michelle K. Lee
Director of the United States Patent and Trademark Office

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,297,503 B2
APPLICATION NO. : 14/252855
DATED : March 29, 2016
INVENTOR(S) : Antony Paul Van De Ven et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title Page, Item 56 Other Publications, Page 4, Right Column

Please change: "Narendran et al., "Solid State lighting: failure analysis of white LEDs,"
Journal of Crystal Growth, vol. 268, Issues 1-4, Aug. 2004, Abstract." to -- Narendran et al., "Solid
State lighting: failure analysis of white LEDs," Journal of Crystal Growth, vol. 268, Issues 1-4,
Aug. 2004, Abstract. --

Signed and Sealed this
Ninth Day of August, 2016



Michelle K. Lee
Director of the United States Patent and Trademark Office