



US009216504B2

(12) **United States Patent**
Zhang et al.

(10) **Patent No.:** **US 9,216,504 B2**

(45) **Date of Patent:** ***Dec. 22, 2015**

(54) **SPINDLE BEARING ARRANGEMENT FOR A POWER TOOL**

(71) Applicant: **Black & Decker Inc.**, Newark (DE)

(72) Inventors: **Qiang Zhang**, Lutherville, MD (US);
David C. Tomayko, Ellicott City, MD (US);
Sankarshan Murthy, Mountain View, CA (US);
James T. Rill, Hampstead, MD (US)

(73) Assignee: **BLACK & DECKER INC.**, Newark, DE (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/081,083**

(22) Filed: **Nov. 15, 2013**

(65) **Prior Publication Data**

US 2014/0069675 A1 Mar. 13, 2014

Related U.S. Application Data

(63) Continuation of application No. 12/729,867, filed on Mar. 23, 2010, now Pat. No. 8,584,770.

(51) **Int. Cl.**
B23Q 5/00 (2006.01)
E21B 3/00 (2006.01)
E21B 17/22 (2006.01)
E21B 19/16 (2006.01)
E21B 19/18 (2006.01)
B25F 5/00 (2006.01)
B23Q 5/04 (2006.01)

(52) **U.S. Cl.**
CPC .. **B25F 5/001** (2013.01); **B23Q 5/04** (2013.01)

(58) **Field of Classification Search**

CPC B25F 5/00; B23Q 5/04
USPC 173/5, 39-41, 140, 178; 474/53-54; 475/331

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,770,139 A * 11/1956 Shen et al. 74/18.1
2,868,039 A * 1/1959 Royal 475/165
3,195,702 A 7/1965 Alexander
3,207,237 A 9/1965 Wanner

(Continued)

FOREIGN PATENT DOCUMENTS

DE 1949415 A1 10/1970
DE 1652685 A1 12/1970

(Continued)


Primary Examiner — Robert Long

(74) *Attorney, Agent, or Firm* — Scott B. Markow

(57) **ABSTRACT**

A power tool that includes a housing, a motor, a pair of motor bearings, a transmission, an output spindle and front and rear spindle bearings. The motor is received in the housing and includes a stator and an output shaft that extends through the stator. The motor bearings support the output shaft for rotation relative to the housing and are disposed on opposite ends of the stator. The transmission is driven by the motor and includes an input pinion that is mounted to the output shaft for rotation therewith. The output spindle is driven by the transmission. The front spindle bearing is mounted to a front end of the output shaft radially between the housing and the output shaft. The rear spindle bearing is mounted to a rear end of the output spindle and a portion of the rear spindle bearing rotates with the output shaft.

20 Claims, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,584,695	A	6/1971	Turnbull		6,805,207	B2	10/2004	Hagan et al.
3,648,784	A	3/1972	Schoeps		6,811,509	B1	11/2004	Langenfeld et al.
3,710,873	A	1/1973	Allen		6,824,491	B2	11/2004	Chen
3,741,313	A	6/1973	States		6,834,730	B2	12/2004	Gass et al.
3,835,715	A *	9/1974	Howell	173/48	6,857,983	B2	2/2005	Milbourne et al.
3,895,546	A	7/1975	Yamaguchi et al.		6,887,176	B2	5/2005	Sasaki
3,901,631	A	8/1975	Wickham et al.		6,892,827	B2	5/2005	Toyama et al.
3,903,440	A *	9/1975	Paule et al.	310/50	6,938,526	B2	9/2005	Milbourne et al.
3,935,909	A	2/1976	Mabuchi et al.		6,966,391	B2	11/2005	Tang
4,065,811	A	12/1977	Pauty		6,976,545	B2	12/2005	Greitmann
4,154,308	A	5/1979	Goldsberry et al.		7,032,683	B2	4/2006	Hetcher et al.
4,227,680	A	10/1980	Hrescak		7,036,406	B2	5/2006	Milbourne et al.
4,428,438	A	1/1984	Holzer		7,048,075	B2	5/2006	Saito et al.
4,535,850	A	8/1985	Alexander		7,073,605	B2	7/2006	Saito et al.
4,547,687	A	10/1985	Arai		7,073,608	B2	7/2006	Droste
4,573,380	A	3/1986	Bald		7,086,483	B2	8/2006	Arimura et al.
4,631,012	A	12/1986	Eckman		7,093,668	B2	8/2006	Gass et al.
4,635,489	A	1/1987	Imamura et al.		7,101,300	B2	9/2006	Milbourne et al.
4,637,283	A *	1/1987	Bertram et al.	81/3.2	7,121,358	B2	10/2006	Gass et al.
4,763,031	A	8/1988	Wang		7,124,839	B2	10/2006	Furuta et al.
4,800,766	A	1/1989	Isozumi et al.		7,131,503	B2	11/2006	Furuta et al.
4,834,192	A	5/1989	Hansson		7,168,503	B1	1/2007	Teng
4,923,047	A	5/1990	Fink et al.		7,201,235	B2	4/2007	Umemura et al.
4,950,110	A	8/1990	Suzuki		7,207,393	B2	4/2007	Clark, Jr. et al.
4,986,369	A	1/1991	Fushiya et al.		7,213,659	B2	5/2007	Saito et al.
5,025,903	A	6/1991	Elligson		7,216,749	B2	5/2007	Droste
5,056,607	A	10/1991	Sanders		7,222,862	B2	5/2007	Buchholz et al.
5,080,180	A	1/1992	Hansson		7,223,195	B2	5/2007	Milbourne et al.
5,269,733	A *	12/1993	Anthony, III	475/331	7,225,884	B2	6/2007	Aeberhard
5,372,106	A	12/1994	Botterill		7,232,400	B2	6/2007	Hill
5,385,512	A	1/1995	Moolenaar et al.		7,249,638	B2	7/2007	Bodine et al.
5,447,205	A	9/1995	Thurler		7,249,695	B2	7/2007	Shew
5,457,860	A	10/1995	Miranda		7,306,049	B2	12/2007	Soika et al.
5,458,206	A	10/1995	Bourner et al.		7,308,948	B2	12/2007	Furuta
5,474,139	A	12/1995	Odendahl et al.		7,314,097	B2	1/2008	Jenner et al.
5,500,843	A *	3/1996	Ishii et al.	720/703	7,322,427	B2	1/2008	Shimma et al.
5,550,416	A	8/1996	Fanchang et al.		7,328,752	B2	2/2008	Gass et al.
5,551,927	A	9/1996	Enzmann et al.		7,331,408	B2	2/2008	Arich et al.
5,573,472	A *	11/1996	Ciulli	475/301	7,331,496	B2	2/2008	Britz et al.
5,624,000	A	4/1997	Miller		7,380,612	B2	6/2008	Furuta
5,673,758	A	10/1997	Sasaki et al.		7,380,613	B2	6/2008	Furuta
5,690,577	A	11/1997	Enzmann et al.		7,410,007	B2	8/2008	Chung et al.
5,706,902	A	1/1998	Eisenhardt		7,413,025	B2	8/2008	Provost
5,711,380	A	1/1998	Chen		7,416,031	B2	8/2008	Murakami et al.
5,715,894	A	2/1998	Maruyama et al.		7,419,013	B2	9/2008	Sainomoto et al.
5,730,232	A	3/1998	Mixer		7,455,121	B2	11/2008	Saito et al.
5,738,177	A	4/1998	Schell et al.		7,455,615	B2	11/2008	Chen
5,769,183	A *	6/1998	Richter et al.	187/249	7,494,437	B2	2/2009	Chen
5,782,593	A	7/1998	Klement		7,497,272	B2	3/2009	Strasser et al.
5,836,403	A	11/1998	Putney et al.		7,513,845	B2	4/2009	Ho
5,842,527	A	12/1998	Arakawa et al.		7,537,064	B2	5/2009	Milbourne et al.
5,868,208	A *	2/1999	Peisert et al.	173/178	7,547,265	B2	6/2009	Showalter
5,897,454	A	4/1999	Cannaliato		7,578,357	B2	8/2009	Schell
6,086,502	A	7/2000	Chung		7,708,085	B2	5/2010	DeCicco et al.
6,135,212	A	10/2000	Georgiou		7,794,355	B2	9/2010	Pusateri
6,142,242	A	11/2000	Okumura et al.		7,839,035	B2	11/2010	Hwaung
6,176,321	B1	1/2001	Arakawa et al.		7,845,460	B2 *	12/2010	Waibel et al. 180/444
6,196,076	B1 *	3/2001	Chung	74/22 A	7,896,097	B2	3/2011	Teng
6,196,330	B1	3/2001	Matthias et al.		7,980,324	B2	7/2011	Bixler et al.
6,223,833	B1	5/2001	Thurler et al.		8,118,702	B2	2/2012	Hansson
6,311,787	B1	11/2001	Berry et al.		8,636,081	B2 *	1/2014	Ludy et al. 173/128
6,401,572	B1	6/2002	Provost		8,820,430	B2 *	9/2014	Walker et al. 173/47
6,431,289	B1	8/2002	Potter et al.		2002/0094907	A1	7/2002	Elger
D462,594	S	9/2002	Flickinger		2003/0143042	A1	7/2003	Doyle et al.
6,457,535	B1	10/2002	Tanaka		2003/0146007	A1	8/2003	Greitmann
6,457,635	B1	10/2002	Scicluna		2004/0124727	A1	7/2004	Lau
RE37,905	E	11/2002	Bourner et al.		2004/0226969	A1	11/2004	Shew
6,500,087	B2	12/2002	Klinger et al.		2004/0245005	A1	12/2004	Toyama et al.
6,535,212	B1	3/2003	Goto et al.		2005/0028997	A1	2/2005	Hagan et al.
6,535,636	B1	3/2003	Savakis et al.		2005/0032604	A1	2/2005	Hill
6,550,546	B2	4/2003	Thurler et al.		2005/0061521	A1	3/2005	Saito et al.
6,676,557	B2	1/2004	Milbourne et al.		2005/0263303	A1	12/2005	Shimizu et al.
6,691,796	B1	2/2004	Wu		2005/0263304	A1	12/2005	Sainomoto et al.
6,733,414	B2 *	5/2004	Elger	475/331	2005/0263305	A1	12/2005	Shimizu et al.
6,796,921	B1	9/2004	Buck et al.		2005/0272548	A1	12/2005	Nagai et al.
					2006/0006614	A1	1/2006	Buchholz et al.
					2006/0021771	A1	2/2006	Milbourne et al.
					2006/0086514	A1	4/2006	Aeberhard
					2006/0090913	A1	5/2006	Furuta

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0213675 A1 9/2006 Whitmire et al.
 2006/0237205 A1 10/2006 Sia et al.
 2006/0254786 A1 11/2006 Murakami et al.
 2006/0254789 A1 11/2006 Murakami et al.
 2006/0266537 A1 11/2006 Izumisawa
 2007/0034394 A1 2/2007 Gass et al.
 2007/0056756 A1 3/2007 Chung et al.
 2007/0068692 A1 3/2007 Puzio
 2007/0068693 A1 3/2007 Whitmire et al.
 2007/0074883 A1 4/2007 Strasser et al.
 2007/0084614 A1 4/2007 Whitmire et al.
 2007/0129208 A1* 6/2007 Willmot et al. 475/339
 2007/0174645 A1 7/2007 Lin
 2007/0181319 A1 8/2007 Whitmine et al.
 2007/0201748 A1 8/2007 Bixler et al.
 2007/0205680 A1* 9/2007 Miyoshi et al. 310/90
 2007/0266545 A1 11/2007 Bodine et al.
 2008/0035360 A1 2/2008 Furuta
 2008/0041602 A1 2/2008 Furuta
 2008/0308286 A1 12/2008 Puzio
 2009/0098971 A1 4/2009 Ho et al.
 2009/0101376 A1 4/2009 Walker et al.
 2009/0151966 A1* 6/2009 Chen 173/48
 2010/0071923 A1 3/2010 Rudolph et al.
 2010/0072732 A1 3/2010 Offord
 2010/0163261 A1 7/2010 Tomayko et al.
 2010/0193207 A1* 8/2010 Mok et al. 173/48
 2010/0326687 A1* 12/2010 Roehm et al. 173/48
 2011/0023930 A1 2/2011 Konig et al.
 2011/0127059 A1* 6/2011 Limberg et al. 173/216
 2011/0188232 A1 8/2011 Friedman et al.
 2011/0284591 A1 11/2011 Guo
 2011/0303432 A1 12/2011 Stauffer et al.
 2012/0111594 A1* 5/2012 Herr 173/104
 2013/0048325 A1* 2/2013 Kuehne et al. 173/47

FOREIGN PATENT DOCUMENTS

DE 1941093 A1 4/1971
 DE 2557118 A1 6/1977
 DE 3329295 A1 2/1985
 DE 4038502 A1 6/1992
 DE 4328599 A1 3/1994
 DE 9404069 U1 6/1994
 DE 9406626 U1 6/1994
 DE 19954931 A1 6/2001
 DE 20209356 U1 10/2002
 DE 20304314 U1 7/2003
 DE 20305853 U1 9/2003
 DE 102004037072 B3 1/2006

EP 0394604 A2 10/1990
 EP 0404035 A2 12/1990
 EP 0808695 A2 11/1997
 EP 1 256 420 A2 11/2002
 EP 1621290 A1 2/2006
 EP 1652630 A2 5/2006
 EP 1707322 A1 10/2006
 EP 1815948 A2 8/2007
 EP 2168724 A1 3/2010
 GB 1574652 A 9/1980
 GB 2102718 A 2/1983
 GB 2274416 A 7/1994
 GB 2328635 A 3/1999
 GB 2334909 A 9/1999
 GB 2404891 A 2/2005
 JP 62173180 A 7/1987
 JP 62297007 A 12/1987
 JP 63123678 A 5/1988
 JP 2139182 A 5/1990
 JP 2284881 A 11/1990
 JP 3043164 A 2/1991
 JP 3168363 A 7/1991
 JP 6010844 A 1/1994
 JP 6023923 A 2/1994
 JP 6182674 A 7/1994
 JP 6210507 A 8/1994
 JP 6215085 A 8/1994
 JP 07040258 A 2/1995
 JP 7080711 A 3/1995
 JP 7328955 A 12/1995
 JP 9136273 A 5/1997
 JP 9239675 A 9/1997
 JP 10291173 A 11/1998
 JP 3655481 A 8/2000
 JP 2000233306 A 8/2000
 JP 2000246659 A 9/2000
 JP 2001009746 A 1/2001
 JP 2001088051 A 4/2001
 JP 2001088052 A 4/2001
 JP 2001105214 A 4/2001
 JP 2002059375 A 2/2002
 JP 2002178206 A 6/2002
 JP 2002224971 A 8/2002
 JP 2002273666 A 9/2002
 JP 2003071745 A 3/2003
 JP 2003220569 A 8/2003
 JP 2004130474 A 4/2004
 JP 2005052904 A 3/2005
 JP 2006123081 A 5/2006
 JP 2006175562 A 7/2006
 WO WO-9521039 A1 8/1995
 WO WO-2007135107 A1 11/2007

* cited by examiner




Fig-1




Fig-2




Fig-3




Fig-4




Fig-5




Fig-6

1

**SPINDLE BEARING ARRANGEMENT FOR A
POWER TOOL**CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 12/729,867 filed Mar. 23, 2010 (now U.S. Pat. No. 8,584,770), the entire disclosure of which is incorporated by reference as if fully set forth in detail herein.

FIELD

The present disclosure relates to a spindle bearing arrangement for a power tool.

BACKGROUND

U.S. Pat. No. 6,431,289 and U.S. patent application Ser. No. 12/610,762 disclose various rotary power tools having an output spindle, which is driven by a planetary-type tr, and a torque limiting clutch for selectively limiting an output torque of the rotary power tool. While such rotary power tools are satisfactory for their intended purposes, such rotary power tools are nonetheless susceptible to improvement.

SUMMARY

This section provides a general summary of the disclosure, and is not a comprehensive disclosure of its full scope or all of its features.

In one form, the teachings of the present disclosure provide a power tool having a motor, a housing, a transmission, an output spindle, a first bearing and a second bearing. The motor has an output shaft. The transmission is at least partly disposed in the housing and receives a rotary input from the output shaft. The transmission includes a planet carrier. The output spindle is driven by the transmission and includes a first end, which is supported for rotation about a spindle axis by the planet carrier, and a second end opposite the first end. The first bearing is disposed between the housing and the planet carrier and supports the planet carrier for rotation about the spindle axis. The second bearing is disposed between the housing and the output spindle and is configured to support the output spindle for rotation about the spindle axis at a location proximate the second end.

In another form, the teachings of the present disclosure provide a power tool with a motor, a housing, a transmission, an output spindle, a front bearing and a rear bearing. The motor has an output shaft. The transmission is disposed in the housing and receives a rotary input from the output shaft. The transmission includes an input planetary stage, which has an input planet carrier, and an output planetary stage. The output spindle is driven by the transmission and has a first end, which extends at least partly through the input planetary stage, and a second end opposite the first end. The front bearing is disposed between the output spindle and the housing to support the second end of the output spindle for rotation about the spindle axis. The rear bearing indirectly supports the first end of the output spindle in the housing for rotation about the spindle axis.

In still another form, the present disclosure provides a power tool that includes a motor, a housing, a transmission, an output spindle, a spindle lock and front and rear bearings. The motor has an output shaft. The transmission is disposed in the housing and receives a rotary input from the output shaft. The transmission includes an input planetary stage, which has an

2

input planet carrier, and an output planetary stage. The output spindle is driven by the transmission and is received through the output planetary stage such that the first end extends at least partly through the input planetary stage. The spindle lock is mounted on the output spindle between the first and second ends. The front and rear bearings, which are disposed on opposite sides of the spindle lock, support the output spindle relative to the housing for rotation about a spindle axis.

In yet another form, the present teachings provide a power tool that includes a housing, a motor, a pair of motor bearings, a transmission, an output spindle and front and rear spindle bearings. The motor is received in the housing and includes a stator and an output shaft that extends through the stator. The motor bearings support the output shaft for rotation relative to the housing and are disposed on opposite ends of the stator. The transmission is driven by the motor and includes an input pinion that is mounted to the output shaft for rotation therewith. The output spindle is driven by the transmission. The front spindle bearing is mounted to a front end of the output shaft radially between the housing and the output shaft. The rear spindle bearing is mounted to a rear end of the output spindle and a portion of the rear spindle bearing rotates with the output shaft.

In still another form, the present teachings provide a power tool that includes a housing, a motor received in the housing, a transmission driven by the motor, an output spindle driven by the transmission and front and rear spindle bearings. The transmission has an input pinion that is mounted to an output shaft of the motor for rotation therewith. The front spindle bearing is mounted to a front end of the output shaft radially between the housing and the output shaft. The rear spindle bearing is mounted to a rear end of the output spindle. The rear spindle bearing is supported by the output shaft.

In a further form, the present teachings provide a power tool that includes a housing, a motor received in the housing, a pair of motor bearings, a transmission driven by the motor, an output spindle driven by the transmission, and front and rear spindle bearings. The motor has a stator and an output shaft that extends through the stator. The motor bearings support the output shaft for rotation relative to the housing and are disposed on opposite ends of the stator. The transmission has an input pinion that is mounted to the output shaft for rotation therewith. The front spindle bearing is mounted to a front end of the output shaft radially between the housing and the output shaft. The rear spindle bearing is mounted to a rear end of the output spindle and is not directly mounted to the housing.

Further areas of applicability will become apparent from the description provided herein. The description and specific examples in this summary are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

DRAWINGS

The drawings described herein are for illustrative purposes only of selected embodiments and not all possible implementations, and are not intended to limit the scope of the present disclosure.

FIG. 1 is a side elevation view of an exemplary tool constructed in accordance with the teachings of the present disclosure;

FIG. 2 is an exploded perspective view of the tool of FIG. 1;

FIG. 3 is a longitudinal section view of a portion of the tool of FIG. 1; and

FIGS. 4 through 6 are section views of portions of five other tools constructed in accordance with the teachings of the present disclosure.

Corresponding reference numerals indicate corresponding parts throughout the several views of the drawings.

DETAILED DESCRIPTION

With reference to FIGS. 1 and 2 of the drawings, a power tool constructed in accordance with the teachings of the present disclosure is generally indicated by reference numeral 10. As those skilled in the art will appreciate, the power tool 10 may be either a corded (e.g., AC powered) or cordless (e.g., DC battery operated) device, such as a portable screwdriver, impact driver, drill/driver or hammer drill/drill. In the particular embodiment illustrated, the power tool 10 is a cordless screwdriver having a housing 12, a motor assembly 14, a transmission assembly 16, an output spindle 18, a spindle lock 20, a clutch mechanism 22, a chuck 24, a trigger assembly 26 and a battery pack 28. Those skilled in the art will understand that several of the components of power tool 10, such as the chuck 24, the trigger assembly 26 and the battery pack 28, are conventional in nature and need not be described in significant detail in this application. Reference may be made to a variety of publications for a more complete understanding of the operation of the conventional features of power tool 10. One example of such publications is commonly assigned U.S. Pat. No. 5,897,454 issued Apr. 27, 1999, the disclosure of which is hereby incorporated by reference as if fully set forth herein.

The housing 12 can include a pair of clam shell housing halves 40 only one shown in FIG. 2) that can cooperate to define a body 42, a handle 44 and a battery interface 46 that can be configured to receive the battery pack 28. The handle 44 can house the trigger assembly 26 in a conventional manner, while the body 42 can define a motor cavity 48 into which the motor assembly 14 can be received. The housing 12 can be configured with an exterior gear case housing (not shown) that can be coupled to a front side of the body 42 and configured to shroud or cover all or portions of the transmission assembly 16 and clutch mechanism 22. In the particular example provided, however, the clam shell housing halves 40 are configured to shroud or cover the transmission assembly 16 and the clutch mechanism 22.

With reference to FIGS. 2 and 3, the motor assembly 14 can comprise a motor 60 and an adapter plate 62. The motor 60 can be any type of motor, such as a DC electric motor, and can include an output shaft 64. The motor 60 can be received in the motor cavity 48 and can be electrically coupled to the trigger assembly 26 and the battery pack 28. The adapter plate 62 can be fixedly coupled to an end of the motor 60.

The transmission assembly 16 can comprise a transmission housing 80 and a transmission 82. The transmission housing 80 can be a hollow, generally tubular structure that is configured to house the transmission 82 and portions of the clutch mechanism 22. The transmission housing 80 can be received into the motor cavity 48 and can engage the clam shell housing halves 40 such that the transmission housing 80 is axially fixed and non-rotatably engaged to the housing 12. The transmission housing 80 can define a front bearing mount 90 and a central cavity 92 having a first shoulder 94, a second shoulder 96 and a third shoulder 98.

The transmission 82 can be a planetary-type transmission having an input planetary stage 110 and an output planetary stage 112 that can be received in the central cavity 92 of the transmission housing 80. It will be appreciated that although the particular transmission depicted and described herein is a

two-stage, single speed transmission, the teachings of the present disclosure have application to other types of transmissions, including those that are operable in more than one speed ratio and/or those that comprise fewer or more than two planetary stages (i.e., a single stage planetary transmission or a transmission having at least one planetary stage disposed between the input and output planetary stages 110 and 112). The input planetary stage 110 can comprise an input sun gear 120, a plurality of input planet gears 122, an input planet carrier 124 and an input ring gear 126, while the output planetary stage 112 can comprise an output sun gear 130, a plurality of output planet gears 132, an output planet carrier 134 and an output ring gear 136.

The input sun gear 120 can be mounted on the output shaft 64 of the motor 60 for rotation therewith. The input planet gears 122 can be meshingly engaged with the input sun gear 120 and the input ring gear 126. The input planet carrier 124 can comprise a carrier body 140 and a plurality of pins 142 that can be mounted to the carrier body 140. Each of the input planet gears 122 can be rotatably mounted on a respective one of the pins 142. The input ring gear 126 can be abutted against the first shoulder 94. The adapter plate 62 can be received in the central cavity 92 and non-rotatably coupled to the transmission housing 80 to thereby limit rearward axial movement of the input ring gear 126 relative to the transmission housing 80, as well as to inhibit rotation of the motor 60 relative to the transmission housing 80.

The output sun gear 130 can be coupled to the carrier body 140 of the input planet carrier 124 for rotation therewith. The output planet gears 132 can be meshingly engaged with the output sun gear 130 and the output ring gear 136. The output planet carrier 134 can comprise a carrier body 150 and a plurality of pins 152 that can be mounted to the carrier body 150. Each of the output planet gears 132 can be rotatably mounted on a respective one of the pins 152 of the output carrier 134. The output ring gear 136 can be abutted against the second shoulder 96 and non-rotatably engaged to the transmission housing 80. In the particular example provided, the output ring gear 136 includes a plurality of external teeth 160 that are engaged to internal teeth 162 formed on the interior of the transmission housing 80 proximate the second shoulder 96.

The output spindle 18 can be a unitarily formed shaft structure that can be received at least partially through the transmission 82. The output spindle 18 can comprise a rear end 170, a front end 172 and an anvil mount 174 that can be disposed between the rear and front ends 170 and 172. The rear end 170 can be generally cylindrically shaped and can extend fully or partly through the input planetary stage 110 where it can be supported for rotation by an element of the transmission 82. For example, the rear end 170 can extend through or into at least one of the output sun gear 130 and the carrier body 140 of the input planet carrier 124 such that the input planet carrier 124 supports the rear end 170 of the output spindle 18. The output shaft 64 of the motor 60 can be received in an appropriately sized aperture 180 in the rear end 170 of the output spindle 18.

A suitable rear bearing 190, such as a journal bearing or bushing, can be disposed between the transmission housing 80 and the carrier body 140 of the input planet carrier 124 to support the input planet carrier 124 for rotation about a spindle axis 200. It will be appreciated that the rear bearing 190, which can be disposed axially between the input ring gear 126 and the output ring gear 136, can indirectly support the rear end 170 of the output spindle 18 about the spindle axis 200.

5

A suitable front bearing **210**, such as a ball bearing, can be disposed in the front bearing mount **90** between the transmission housing **80** and the front end **172** of the output spindle **18**. The front end **172** can be configured to transmit rearwardly-directed thrust loads into the front bearing **210** so that they may be transmitted into the transmission housing **80**. One or more snap rings or other retaining devices can be employed to limit axial movement of the front bearing **210** on the front end **172** of the output spindle **18**.

The spindle lock **20** can comprise an outer collar **220**, a plurality of lock pins **222**, a plurality of projections **224**, which can be integrally formed with the carrier body **150** of the output planet carrier **134**, and an anvil **226**. The outer collar **220** can be an annular structure that can be received against the third shoulder **98** in the central cavity **92** and non-rotatably engaged to the transmission housing **80**. The lock pins **222** can extend longitudinally parallel to the spindle axis **200** between the projections **224** and an interior surface of the outer collar **220**. The anvil **226** can be mounted on the anvil mount **174** on the output spindle **18** such that the anvil **226** is coupled to the output spindle **18** for rotation therewith. The spindle lock **20** is configured to permit the output spindle **18** to rotatably driven by the transmission **82**, but to lock the output spindle **18** to the transmission housing **80** (to thereby inhibit rotation of the output spindle **18**) when the output spindle **18** is rotated manually.

The clutch mechanism **22** can include a clutch member **250**, one or more engagement assemblies **252** and an adjustment mechanism **254**. The clutch member **250** can be an annular structure that can be fixedly coupled to the input ring gear **126**. In the particular example provided, the clutch member **250** includes an arcuate clutch face **260** that is formed into an axially forward facing side of the input ring gear **126**. The outer diameter of the clutch member **250** is sized to rotate within the portion of the central cavity **92** that is proximate the first shoulder **94** in the transmission housing **80**. While the input ring gear **126** and the clutch member **250** have been illustrated as a one piece (i.e., unitarily formed) construction, those skilled in the art will understand that they may be constructed otherwise.

In the particular embodiment illustrated, the engagement assemblies **252** are disposed 180° apart from one another (only one is shown in FIG. 3 for clarity) and each engagement assembly **252** includes a pin member **270**, a follower spring **272** and a follower **274**. The pin member **270** includes a cylindrical body portion **280** having an outer diameter that is sized to slip-fit within an actuator aperture **284** that is formed through the transmission housing **80**. A first end of the pin member **270** can have an end that can be defined by a spherical radius and can be configured to engage the adjustment mechanism **254**.

The follower spring **272** can be a compression spring whose outside diameter is sized to slip fit within the actuator aperture **284**. The forward end of the follower spring **272** can contact the pin member **270**, while the opposite end of the follower spring **272** can contact the follower **274**. An end portion of the follower **274** can be cylindrical in shape and sized to slip fit within the inside diameter of the follower spring **272**. In this regard, the end portion of the follower **274** can act as a spring follower to prevent the follower spring **272** from bending over when it is compressed. The follower **274** can also include a cylindrically shaped body portion, which can be sized to slip fit within the actuator aperture **284**, and a tip portion that is configured to extend axially through the first shoulder **94** and engage the clutch face **260**. In the particular example illustrated, the tip portion is defined by a spherical radius.

6

The adjustment mechanism **254** can include a setting collar **322** can be shaped in the form of a generally hollow cylinder that is sized to fit and cover a front end of the housing **12**. The setting collar **322** can include an annular face into which an adjustment profile **330** is formed. The adjustment profile **330** can be tapered or stepped such that rotation of the setting collar **322** will cause corresponding axial movement of the pin member **270**, which operates to change the torque setting of the clutch mechanism **22** as a result of corresponding compression or extension of the follower spring **272**.

The setting collar **322** can include a contoured outer surface that can permit the user of the tool **10** to comfortably rotate both the setting collar **322** to set the adjustment profile **330** at a position corresponding to a desired torque setting of the clutch mechanism **22**.

During the operation of the tool **10**, an initial drive torque is transmitted by the output shaft **64** of the motor **60** to the input planetary stage **110**, causing the input planet gears **122** to rotate. Rotation of the input planet gears **122** creates a first intermediate torque that is applied against the input ring gear **126**. A clutch torque applied by the clutch mechanism **22** resists the first intermediate torque to thereby prevent the input ring gear **126** from rotating within the transmission housing **80** such that the first intermediate torque is applied to the input planet carrier **124** and the remainder of the transmission **82** so as to multiply the first intermediate torque in a predetermined manner according to the reduction ratio of the transmission **82**.

A portion of another power tool **10a** constructed in accordance with the teachings of the present disclosure is schematically illustrated in FIG. 4. In the example provided, the transmission **82a** includes an input planetary stage **110a**, an intermediate planetary stage **500**, and an output planetary stage **112a**. The output spindle **18a** extends through the transmission **82a** such that the rear end **170a** of the output spindle **18a** is received through or into at least one of an intermediate sun gear **504** (which is associated with the intermediate planetary stage **500**) and the carrier body **140a** of the input planet carrier **124a** such that the input planet carrier **124a** supports the rear end **170a** of the output spindle **18a**. The rear bearing **190a** can be disposed between the transmission housing **80a** and an element of the transmission **82a** located rearwardly of the final or output stage of the transmission **82a** (i.e., rearwardly of the output planetary stage **112a**). In the particular example provided, the rear bearing **190a** is disposed between the transmission housing **80a** and the carrier body **140a** of the input planet carrier **124a** to support the input planet carrier **124a** for rotation about the spindle axis **200a**. As with the previous example, the front bearing **210a** is received in a front bearing mount **90a** formed in a transmission housing **80a** and cooperates to align front end **172a** of the output spindle **18a** to the spindle axis **200a**.

In the particular example provided, the transmission **82a** is a two-speed, three-stage planetary-type transmission in which a ring gear **510** associated with the intermediate planetary stage **500** is movable between a first position (shown), in which the ring gear **510** is meshingly engaged to the planet gears **520** and a toothed exterior surface **522** of the planet carrier **524** of the intermediate planetary stage **500**, and a second position in which the ring gear **510** is translated axially rearwardly so as to non-rotatably engage the rear bearing **190a** and disengage the toothed exterior surface **522** of the planet carrier **524** of the intermediate planetary stage **500**. Moreover, the clutch mechanism **22a** is configured to resist rotation of the output ring gear **136a**.

A portion of another power tool **10b** constructed in accordance with the teachings of the present disclosure is sche-

matically illustrated in FIG. 5. This example is generally similar to that of FIGS. 1-3, except that a pair of motor bearings 600 support the output shaft 64b (relative to the housing 12b) on opposite sides of the motor 60b, the output spindle 18b extends into the input sun gear 120b, the output shaft 64b of the motor 60b does not extend into the rear end 170b of the output spindle 18b, and the rear bearing 190b is received between the input sun gear 120b and the rear end 170b of the output spindle 18b (rather than between the carrier body 140b of the input planet carrier 124b and the transmission housing 80b).

A portion of another power tool 10c constructed in accordance with the teachings of the present disclosure is schematically illustrated in FIG. 6. This example is generally similar to that of FIGS. 1-3, except that a pair of motor bearings 600 support the output shaft 64c (relative to the housing 12c) on opposite sides of the motor 64c and the rear bearing 190c is received between the output shaft 64c of the motor 60c and the rear end 170c of the output spindle 18c (rather than between the carrier body 140c of the input planet carrier 124c and the transmission housing 80c).

The foregoing description of the embodiments has been provided for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention. Individual elements or features of a particular embodiment are generally not limited to that particular embodiment, but, where applicable, are interchangeable and can be used in a selected embodiment, even if not specifically shown or described. The same may also be varied in many ways. Such variations are not to be regarded as a departure from the invention, and all such modifications are intended to be included within the scope of the invention.

What is claimed is:

1. A power tool comprising:
 - a housing;
 - a motor received in the housing, the motor having a stator and an output shaft that extends through the stator;
 - a pair of motor bearings supporting the output shaft for rotation relative to the housing about an axis, the motor bearings being disposed on opposite ends of the stator;
 - a transmission driven by the motor, the transmission having an input pinion that is mounted to the output shaft for rotation therewith;
 - an output spindle driven by the transmission for rotation about the axis;
 - a front spindle bearing mounted to a front end of the output spindle radially between the housing and the output spindle; and
 - a rear spindle bearing mounted to a rear end of the output spindle, wherein a portion of the rear spindle bearing engages and rotates with the output shaft.
2. The power tool of claim 1, wherein the output shaft extends through the input pinion.
3. The power tool of claim 2, wherein the rear spindle bearing is received in an aperture formed in the rear end of the output spindle.
4. The power tool of claim 1, wherein the rear spindle bearing is at least partly received in the input pinion.
5. The power tool of claim 1, wherein the rear spindle bearing is mounted on the input pinion.
6. The power tool of claim 1, wherein the front end of the output spindle has a first diameter, wherein the rear end of the output spindle has a second diameter, and wherein the first diameter is greater than the second diameter.
7. The power tool of claim 1, further comprising a clutch assembly that is configured to limit torque transmission through the transmission to the output spindle.

8. The power tool of claim 1, wherein the transmission is a multi-stage planetary transmission having an output stage with a planet carrier, and wherein the output spindle is coupled to the planet carrier for rotation therewith.

9. A power tool comprising:
 - a housing;
 - a motor received in the housing, the motor having an output shaft configured to rotate about an axis;
 - a transmission driven by the motor, the transmission having an input pinion that is mounted to the output shaft for rotation therewith;
 - an output spindle driven by the transmission for rotation about the axis;
 - a front spindle bearing mounted to a front end of the output shaft radially between the housing and the output spindle; and
 - a rear spindle bearing mounted to a rear end of the output spindle, wherein the rear spindle bearing engages and is supported by the output shaft.

10. The power tool of claim 9, wherein the rear spindle bearing is directly mounted to the rear output spindle.

11. The power tool of claim 9, wherein the output shaft extends through the input pinion.

12. The power tool of claim 9, wherein the rear spindle bearing is directly mounted to the input pinion.

13. The power tool of claim 12, wherein the rear spindle bearing is received in an aperture formed in the input pinion.

14. The power tool of claim 9, further comprising a clutch assembly that is configured to limit torque transmission through the transmission to the output spindle.

15. The power tool of claim 9, wherein the transmission is a multi-stage planetary transmission having an output stage with a planet carrier, and wherein the output spindle is coupled to the planet carrier for rotation therewith.

16. A power tool comprising:
 - a housing;
 - a motor received in the housing, the motor having a stator and an output shaft that extends through the stator;
 - a pair of motor bearings supporting the output shaft for rotation relative to the housing about an axis, the motor bearings being disposed on opposite ends of the stator;
 - a transmission driven by the motor, the transmission having an input pinion that is mounted to the output shaft for rotation therewith;
 - an output spindle driven by the transmission for rotation about the axis;
 - a front spindle bearing mounted to a front end of the output spindle radially between the housing and the output spindle; and
 - a rear spindle bearing mounted to a rear end of the output spindle, wherein the rear spindle bearing is not directly mounted to the housing and engages the output shaft.

17. The power tool of claim 16, wherein the rear spindle bearing is mounted to an element of the transmission such that the rear spindle bearing is disposed radially between the element of the transmission and the rear end of the output spindle.

18. The power tool of claim 17, wherein the element of the transmission is the input pinion.

19. The power tool of claim 16, wherein the output shaft extends through the input pinion.

20. The power tool of claim 16, wherein the rear spindle bearing is mounted to the output shaft such that the rear spindle bearing is disposed radially between the rear end of the output spindle and the output shaft.