



(12) **United States Patent**
Alamouti et al.

(10) **Patent No.:** **US 9,065,516 B2**
(45) **Date of Patent:** **Jun. 23, 2015**

(54) **LOW COMPLEXITY MAXIMUM LIKELIHOOD DETECTION OF CONCATENATED SPACE CODES FOR WIRELESS APPLICATIONS**

(71) Applicant: **AT&T Mobility II LLC**, Atlanta, GA (US)

(72) Inventors: **Siavash Alamouti**, Newbury Berkshire (GB); **Patrick Poon**, Hong Kong (HK); **Vahid Tarokh**, Cambridge, MA (US)

(73) Assignee: **AT&T Mobility II, LLC**, Atlanta, GA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/280,945**

(22) Filed: **May 19, 2014**

(65) **Prior Publication Data**

US 2014/0247896 A1 Sep. 4, 2014

Related U.S. Application Data

(60) Continuation of application No. 13/691,505, filed on Nov. 30, 2012, now Pat. No. 8,731,107, which is a continuation of application No. 12/650,007, filed on Dec. 30, 2009, now Pat. No. 8,351,545, which is a

(Continued)

(51) **Int. Cl.**
H04B 7/06 (2006.01)
H04L 5/12 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **H04B 7/0697** (2013.01); **H04L 1/0625** (2013.01); **H04B 7/0669** (2013.01);

(Continued)

(58) **Field of Classification Search**
CPC ... H04L 1/0054; H04L 1/0057; H04L 1/0059; H04L 1/006; H04L 1/0065; H04L 1/0618; H04L 1/0625; H04L 1/0631; H04L 25/03178; H04L 25/03331; H04B 7/0669; H03M 13/256
USPC 375/265, 267, 299, 341, 347, 295; 714/792, 795
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,633,107 A 1/1972 Brady
3,978,408 A 8/1976 Gupta et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2203903 5/1996
CA 2252664 11/1997

(Continued)

OTHER PUBLICATIONS

Alamouti et al., "Trellis-Coded Modulation and Transmit Diversity: Design Criteria and Performance Evaluation," 0-7803-5106-1/98, pp. 703-708, 1998 IEEE.


(Continued)

Primary Examiner — Betsy Deppe
(74) *Attorney, Agent, or Firm* — Abel Law Group, LLP

(57) **ABSTRACT**

Good transmission characteristics are achieved in the presence of fading with a transmitter that employs a trellis coder followed by a block coder. Correspondingly, the receiver comprises a Viterbi decoder followed by a block decoder. Advantageously, the block coder and decoder employ time-space diversity coding which, illustratively, employs two transmitter antennas and one receiver antenna.

10 Claims, 1 Drawing Sheet



Related U.S. Application Data

continuation of application No. 11/018,780, filed on Dec. 21, 2004, now Pat. No. 7,643,568, which is a continuation of application No. 10/334,343, filed on Dec. 30, 2002, now Pat. No. 6,853,688, which is a continuation of application No. 10/005,095, filed on Dec. 3, 2001, now Pat. No. 6,807,240, which is a division of application No. 09/167,422, filed on Oct. 5, 1998, now Pat. No. 6,501,803.

(60) Provisional application No. 60/063,794, filed on Oct. 31, 1997.

(51) **Int. Cl.**

H03M 13/03 (2006.01)
H04L 1/06 (2006.01)
H04L 1/00 (2006.01)
H04L 25/03 (2006.01)
H03M 13/25 (2006.01)
H04B 1/04 (2006.01)

(52) **U.S. Cl.**

CPC **H04L1/0054** (2013.01); **H04L 1/0057** (2013.01); **H04L 1/0059** (2013.01); **H04L 1/006** (2013.01); **H04L 1/0065** (2013.01); **H04L 1/0618** (2013.01); **H04L 1/0631** (2013.01); **H04L 25/03178** (2013.01); **H04L 25/03331** (2013.01); **H03M 13/256** (2013.01); **H04B 1/0475** (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,001,692	A	1/1977	Fenwick et al.	5,619,533	A	4/1997	Dent
4,099,121	A	7/1978	Fang	5,675,590	A	10/1997	Alamouti
4,281,411	A	7/1981	Bonn et al.	5,680,419	A	10/1997	Bottomley
4,369,516	A	1/1983	Byrns	5,781,845	A	7/1998	Dybdal et al.
4,567,464	A	1/1986	Siegel	5,787,131	A	7/1998	Bottomley
4,577,332	A	3/1986	Brenig	5,790,570	A	8/1998	Heegard et al.
4,675,880	A	6/1987	Davarian	5,790,598	A	8/1998	Moreland et al.
4,733,402	A	3/1988	Monsen	5,819,168	A	10/1998	Golden et al.
4,763,331	A	8/1988	Matsumoto	5,822,380	A	10/1998	Bottomley
4,953,183	A	8/1990	Bergmans et al.	5,838,728	A	11/1998	Alamouti et al.
5,022,053	A	6/1991	Chung et al.	5,838,742	A	11/1998	AbuDayya
5,029,185	A	7/1991	Wei	5,848,103	A	12/1998	Weerackody
5,088,113	A	2/1992	Wei	5,859,870	A	1/1999	Tsujimoto
5,101,501	A	3/1992	Gilhousen et al.	5,859,879	A	1/1999	Bolgiano et al.
5,109,390	A	4/1992	Gilhousen et al.	5,924,034	A	7/1999	Dupuy
5,127,025	A	6/1992	Okanoue	5,933,421	A	8/1999	Alamouti et al.
5,170,413	A	12/1992	Hess et al.	5,943,372	A	8/1999	Gans et al.
5,193,102	A	3/1993	Meidan et al.	5,949,833	A	9/1999	Weerackody
5,202,903	A	4/1993	Okanoue	5,960,039	A	9/1999	Martin et al.
5,283,780	A	2/1994	Schuchman et al.	5,991,273	A	11/1999	Abu-Dayya
5,305,353	A	4/1994	Weerackody	5,991,331	A	11/1999	Chennakeshu et al.
5,319,677	A	6/1994	Kim	5,999,826	A	12/1999	Whinnett
5,369,412	A	11/1994	Tsujimoto	6,031,474	A	2/2000	Kay et al.
5,396,518	A	3/1995	How	6,034,987	A	3/2000	Chennakeshu et al.
5,416,797	A	5/1995	Gilhousen et al.	6,038,263	A	3/2000	Kotzin et al.
5,418,798	A	5/1995	Wei	6,038,272	A	3/2000	Golden et al.
5,422,913	A	6/1995	Wilkinson	6,044,120	A	3/2000	Bar-David et al.
5,442,627	A	8/1995	Viterbi et al.	6,067,324	A	5/2000	Harrison
5,457,712	A	10/1995	Weerackody	6,081,566	A	6/2000	Molnar et al.
5,461,646	A	10/1995	Anvari	6,088,408	A	7/2000	Calderbank et al.
5,461,696	A	10/1995	Frank et al.	6,094,465	A	7/2000	Stein et al.
5,467,374	A	11/1995	Chennakeshu et al.	6,097,771	A	8/2000	Foschini
5,479,448	A	12/1995	Seshadri	6,101,399	A	8/2000	Raleigh et al.
5,481,572	A	1/1996	Skold et al.	6,115,427	A	9/2000	Calderbank
5,487,091	A	1/1996	Jasper et al.	6,128,355	A	10/2000	Backman et al.
5,499,272	A	3/1996	Bottomley	6,137,843	A	10/2000	Chennakeshu et al.
5,524,125	A	6/1996	Tsujimoto	6,144,711	A	11/2000	Raleigh et al.
5,530,725	A	6/1996	Koch	6,144,771	A	11/2000	Li et al.
5,553,102	A	9/1996	Jasper et al.	6,154,485	A	11/2000	Harrison
5,613,219	A	3/1997	Vogel et al.	6,173,005	B1	1/2001	Kotzin et al.
				6,178,196	B1	1/2001	Naguib et al.
				6,185,258	B1	2/2001	Alamouti et al.
				6,185,266	B1	2/2001	Kuchi et al.
				6,188,736	B1	2/2001	Lo et al.
				6,192,256	B1	2/2001	Whinnett
				6,298,082	B1	10/2001	Harrison
				6,304,581	B1	10/2001	Chen et al.
				6,317,411	B1	11/2001	Whinnett et al.
				6,317,466	B1	11/2001	Foschini et al.
				6,327,299	B1	12/2001	Meszko
				6,333,953	B1	12/2001	Bottomley et al.
				6,335,954	B1	1/2002	Bottomley et al.
				6,377,631	B1	4/2002	Raleigh
				6,377,812	B1	4/2002	Rashid-Farrokhi et al.
				6,393,074	B1	5/2002	Mandyam et al.
				6,411,257	B1	6/2002	Sorelius et al.
				6,411,612	B1	6/2002	Halford et al.
				RE37,802	E	7/2002	Fattouche et al.
				6,430,231	B1	8/2002	Calderbank
				6,452,981	B1	9/2002	Raleigh et al.
				6,470,043	B1	10/2002	Lo et al.
				6,501,803	B1 *	12/2002	Alamouti et al. 375/265
				6,542,556	B1	4/2003	Kuchi et al.
				6,549,585	B2	4/2003	Naguib et al.
				6,728,307	B1	4/2004	Derryberry et al.
				6,741,635	B2	5/2004	Lo et al.
				6,775,329	B2	8/2004	Alamouti et al.
				6,807,240	B2	10/2004	Alamouti et al.
				6,853,688	B2 *	2/2005	Alamouti et al. 375/265
				6,888,899	B2	5/2005	Raleigh et al.
				7,120,200	B2	10/2006	Alamouti et al.
				7,145,971	B2	12/2006	Raleigh et al.
				7,203,249	B2	4/2007	Raleigh et al.
				7,386,077	B2	6/2008	Alamouti et al.
				7,587,007	B2	9/2009	Alamouti et al.
				7,643,568	B2 *	1/2010	Alamouti et al. 375/267
				7,916,806	B2	3/2011	Alamouti et al.
				8,351,545	B2 *	1/2013	Alamouti et al. 375/299
				8,355,475	B2	1/2013	Alamouti et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,731,107	B2 *	5/2014	Alamouti et al.	375/299
8,767,874	B2	7/2014	Alamouti et al.	
2004/0157646	A1	8/2004	Raleigh et al.	
2005/0157810	A1	7/2005	Raleigh et al.	
2010/0091906	A1	4/2010	Raleigh et al.	
2011/0170635	A1	7/2011	Alamouti et al.	
2014/0314174	A1	10/2014	Alamouti et al.	

FOREIGN PATENT DOCUMENTS

CA	2302289	3/1998
CA	2276207	2/2003
DE	29824760 UI	6/2002
DE	29824761 UI	6/2002
DE	29824762 UI	6/2002
DE	29824763 UI	6/2002
DE	29824765 UI	6/2002
EP	0392723 A	10/1990
EP	0396101	11/1990
EP	0631399 A	12/1994
EP	0767546	4/1997
EP	1016228	7/2000
GB	2237706	5/1991
GB	2280575 A	2/1995
GB	2290010 A	12/1995
GB	2311445 A	9/1997
JP	63286027	11/1988
WO	WO 91/20142	12/1991
WO	WO 95/22214	8/1995
WO	WO 97/24849	7/1997
WO	WO 97/41670	11/1997
WO	WO 98/09385	3/1998
WO	WO 99/14871	3/1999
WO	WO 99/23766	5/1999
WO	WO 00/11806	3/2000
WO	WO 00/18056	3/2000
WO	WO 00/49780	8/2000
WO	WO 00/51265	8/2000
WO	WO 01/19013	3/2001
WO	WO 01/54305	7/2001
WO	WO 01/56218	8/2001
WO	WO 01/63826	8/2001
WO	WO 01/69814	9/2001

OTHER PUBLICATIONS

Alamouti, Siavash M., "A Simple Transmit Diversity Technique for Wireless Communications," *IEEE Journal on Select Areas in Communications*, Oct. 1998, pp. 1451-1458, vol. 16, No. 8, The Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.

Blanco, M.A. & Zdunek, K., "On the Optimization of Simple Switched Diversity Receivers," 1978 IEEE Conference on Communications and Power, Montreal, Canada, pp. 114-117, (1978).

Blanco, M.A. & Zdunek, K., "Performance and Optimization of Switched Diversity Systems for the Detection of Signals with Rayleigh Fading," *IEEE Transactions on Communications, Channels*, *IEEE Transactions on Vehicular Technology*, Nov. 1991, pp. 686-693, vol. 40, No. 4, The Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.

Calderbank, A. et al., "Space-Time Codes for Wireless Communications," 1997 IEEE, ISIT 1997, Jun. 29-Jul. 4, pp. 146, Ulm, Germany.

Cavers, James K., "An Analysis of Pilot Symbol Assisted Modulation for Rayleigh Fading Channels," *IEEE Transactions on Vehicular Technology*, Nov. 1991, pp. 686-693, vol. 40, No. 4, The Institute of Electrical and Electronics Engineers, Inc., New York, NY.

European Search Report and Written Opinion, mailed Mar. 12, 2010 in EP App. No. 06004662.0, 16 pages.

Foschini, G.J. and Gans, M.J., "On Limits of Wireless Communications in a Fading Environment when Using Multiple Antennas," *Wireless Personal Communications*, 1998, 6:311-335.

Foschini, G.J., "Layered Space-Time Architecture for Wireless Communication in a Fading Environment when Using Multi-Element Antennae", *Bell Technical Labs Journal*, pp. 41-59, (1996).

Hinderling, J. et al., "CDMA Mobile Station Modem ASIC," *IEEE 1992 Custom Integrated Circuits Conference* pp. 10.2.1-10.2.5, (1992).

Hiroike et al., "Combined Effects of Phase Sweeping Transmitter Diversity and Channel Coding," *IEEE Transactions on Vehicular Technology*, vol. 41, No. 2, May 1992, The Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.

Kerr, R. et al., "The CDMA Digital Cellular System: an ASIC Overview," *IEEE 1992 Custom Integrated Circuits Conference* pp. 10.1.1-10.1.7, (1992).

Naguib, A. F. et al., "Space-Time Coded Modulation for High Data Rate Wireless Communications," 1997 IEEE, pp. 102-109, 0-7803-4198-8/97, The Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.

Naguib, Ayman et al., "A Space-Time Coding Modem for High-Data-Rate Wireless Communications," *IEEE Journal on Selected Areas in Communications*, Oct. 1998, pp. 1459-1478, The Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.

Non-Final Office Action mailed Nov. 21, 2008 in U.S. Appl. No. 11/929,090, 14 pages.

Non-Final Office Action mailed Jun. 1, 2010 in U.S. Appl. No. 11/828,790, 11 pages.

Pickholtz, R.L. et al., "Theory of Spread Spectrum Communications—A Tutorial," *IEEE Transactions on Communications*, 30(5):855-884, (1982).

Sampei, S. et al., "Rayleigh Fading Compensation Method for 16QAM in Digital Land Mobile Radio Channels," *Proceeding of the 1989 IEEE Vehicular Technology Conference*, May 1989, pp. 640-646, The Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.

Seshadri, N. et al., "Advanced Techniques for Modulation, Error Correction, Channel Equalization and Diversity," *AT&T Tech. Journal* 47(4): 48-63, Jul. 1993.

Seshadri, N. et al., "Space-Time Codes for Wireless Communication: Code Construction," *IEEE 47th Vehicular Technology Conf.*, Phoenix, pp. 637-641, May 1997.

Seshadri, N. et al., "Two Signaling Schemes for Improving the Error Performance of FDD Transmission Systems Using Transmitter Antenna Diversity," *Proceeding of the 1993 IEEE Vehicular Technology Conference (VTC 43.sup.rd)*, May 1993, pp. 508-511, The Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.

Tarokh, V. et al., "Space Time Codes for High Data Rate Wireless Communication: Performance Criteria in the Presence of Channel Estimation Errors, Mobility, and Multiple Paths", *IEEE Transactions on Communications* 47(2):199-207, (1999).

Tarokh, V., et al. "Space-Time Codes for High Data Rate Wireless Communication: Performance Criteria," *IEEE International Conference on Communications*, Montreal, 1:299-303, Jun. 1997.

Tarokh, Vahid et al., "Combined Array Processing and Space-Time Coding," *IEEE Transactions on Information Theory*, May 1999, pp. 1121-1128, vol. 45, No. 4, The Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.

Tarokh, Vahid et al., "Space-Time Codes for High Data Rate Wireless Communication: Performance Criterion and Code Construction," *IEEE Transactions on Information Theory*, Mar. 1998, pp. 744-765, vol. 44, No. 2, The Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.

Ungerboeck, G., "Channel Coding with Multilevel/Phase Signals," *IEEE Transactions on Information Theory*, Jan. 1982, pp. 56-67, vol. IT-28, No. 1, The Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.

Weerackody, V., "Diversity for the Direct-Sequence Spread Spectrum System Using Multiple Transmit Antennas," *Proceedings of the IEEE International Conference on Communications*, May 23-26, 1993, Geneva, vol. 3, pp. 1775-1779.

Winters, J.H., "The Diversity Gain of Transmit Diversity in Wireless Systems with Rayleigh Fading," *Proceeding of the 1994 ICC/SUPERCOMM*, New Orleans, May 1994, vol. 2, pp. 1121-1125, The Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.

(56)

References Cited

OTHER PUBLICATIONS


Winters, J.H., Salz, J., Gitlin, R.D., "The Impact of Antenna Diversity on the Capacity of Wireless Communications Systems," IEEE Transactions on Communications, vol. 42, No. 2, Feb./Mar./Apr. 1994, pp. 1740-1751, IEEE Communications Society, New York, N.Y.
Wittneben, A. "A New Bandwidth Efficient Transmit Antenna Modulation Diversity Scheme for Linear Digital Modulation," Proceeding of the 1993 IEEE International Conference on Communications

(IICC '93), May 1993, pp. 1630-1634, The Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.

Wittneben, A. "Basestation modulation diversity for digital SIMULCAST," Proceeding of the 1991 IEEE Vehicular Technology Conference, May 1991, pp. 848-853, The Institute of Electrical and Electronics Engineers, Inc., New York, N.Y.

Non-Final Office action mailed Oct. 1, 2014 in U.S. Appl. No. 14/319,428, 12 pages.

* cited by examiner



**LOW COMPLEXITY MAXIMUM
LIKELIHOOD DETECTION OF
CONCATENATED SPACE CODES FOR
WIRELESS APPLICATIONS**

CROSS-REFERENCE TO RELATED
APPLICATION(S)

This application is a continuation of U.S. patent Ser. No. 13/691,505, filed Nov. 30, 2012 (now U.S. Pat. No. 8,731, 107), which is a continuation of U.S. patent application Ser. No. 12/650,007, filed Dec. 30, 2009 (now U.S. Pat. No. 8,351, 545), which is a continuation of Ser. No. 11/018,780, filed Dec. 21, 2004 (now U.S. Pat. No. 7,643,568), which is a continuation of U.S. patent application Ser. No. 10/334,343, filed Dec. 30, 2002 (now U.S. Pat. No. 6,853,688), which is a continuation of U.S. patent application Ser. No. 10/005,095, filed Dec. 3, 2001 (now U.S. Pat. No. 6,807,240), which is a divisional of U.S. patent application Ser. No. 09/167,422, filed Oct. 5, 1998 (now U.S. Pat. No. 6,501,803), which claims the benefit of U.S. Provisional Application No. 60/063,794, filed Oct. 31, 1997, all of which are incorporated herein by reference in their entirety.

BACKGROUND OF THE INVENTION

This invention relates to wireless communication and, more particularly, to techniques for effective wireless communication in the presence of fading and other degradations.

The most effective technique for mitigating multipath fading in a wireless radio channel is to cancel the effect of fading at the transmitter by controlling the transmitter's power. That is, if the channel conditions are known at the transmitter (on one side of the link), then the transmitter can pre-distort the signal to overcome the effect of the channel at the receiver (on the other side). However, there are two fundamental problems with this approach. The first problem is the transmitter's dynamic range. For the transmitter to overcome an x dB fade, it must increase its power by x dB which, in most cases, is not practical because of radiation power limitations, and the size and cost of amplifiers. The second problem is that the transmitter does not have any knowledge of the channel as seen by the receiver (except for time division duplex systems, where the transmitter receives power from a known other transmitter over the same channel). Therefore, if one wants to control a transmitter based on channel characteristics, channel information has to be sent from the receiver to the transmitter, which results in throughput degradation and added complexity to both the transmitter and the receiver.

Other effective techniques are time and frequency diversity. Using time interleaving together with coding can provide diversity improvement. The same holds for frequency hopping and spread spectrum. However, time interleaving results in unnecessarily large delays when the channel is slowly varying. Equivalently, frequency diversity techniques are ineffective when the coherence bandwidth of the channel is large (small delay spread).

It is well known that in most scattering environments antenna diversity is the most practical and effective technique for reducing the effect of multipath fading. The classical approach to antenna diversity is to use multiple antennas at the receiver and perform combining (or selection) to improve the quality of the received signal.

The major problem with using the receiver diversity approach in current wireless communication systems, such as IS-136 and GSM, is the cost, size and power consumption constraints of the receivers. For obvious reasons, small size,

weight and cost are paramount. The addition of multiple antennas and RF chains (or selection and switching circuits) in receivers is presently not feasible. As a result, diversity techniques have often been applied only to improve the up-link (receiver to base) transmission quality with multiple antennas (and receivers) at the base station. Since a base station often serves thousands of receivers, it is more economical to add equipment to base stations rather than the receivers.

Recently, some interesting approaches for transmitter diversity have been suggested. A delay diversity scheme was proposed by A. Wittneben in "Base Station Modulation Diversity for Digital SIMULCAST," Proceedings of the 1991 IEEE Vehicular Technology Conference (VTC 41st), pp. 848-853, May 1991, and in "A New Bandwidth Efficient Transmit Antenna Modulation Diversity Scheme For Linear Digital Modulation," in Proceedings of the 1993 IEEE International Conference on Communications (IICC '93), pp. 1630-1634, May 1993. The proposal is for a base station to transmit a sequence of symbols through one antenna, and the same sequence of symbols—but delayed—through another antenna.

U.S. Pat. No. 5,479,448, issued to Nambirajan Seshadri on Dec. 26, 1995, discloses a similar arrangement where a sequence of codes is transmitted through two antennas. The sequence of codes is routed through a cycling switch that directs each code to the various antennas, in succession. Since copies of the same symbol are transmitted through multiple antennas at different times, both space and time diversity are achieved. A maximum likelihood sequence estimator (MLSE) or a minimum mean squared error (MMSE) equalizer is then used to resolve multipath distortion and provide diversity gain. See also N. Seshadri, J. H. Winters, "Two Signaling Schemes for Improving the Error Performance of FDD Transmission Systems Using Transmitter Antenna Diversity," Proceedings of the 1993 IEEE Vehicular Technology Conference (VTC 43rd), pp. 508-511, May 1993; and J. H. Winters, "The Diversity Gain of Transmit Diversity in Wireless Systems with Rayleigh Fading," Proceedings of the 1994 ICC/SUPERCOMM, New Orleans, Vol. 2, pp. 1121-1125, May 1994.

Still another interesting approach is disclosed by Tarokh, Seshadri, Calderbank and Naguib in U.S. application Ser. No. 08/847,635, filed Apr. 25, 1997, now U.S. Pat. No. 6,115,427, (based on a provisional application filed Nov. 7, 1996), where symbols are encoded according to the antennas through which they are simultaneously transmitted, and are decoded using a maximum likelihood decoder. More specifically, the process at the transmitter handles the information in blocks of M_1 bits, where M_1 is a multiple of M_2 , i.e., $M_1 = k * M_2$. It converts each successive group of M_2 bits into information symbols (generating thereby k information symbols), encodes each sequence of k information symbols into n channel codes (developing thereby a group of n channel codes for each sequence of k information symbols), and applies each code of a group of codes to a different antenna.

Yet another approach is disclosed by Alamouti and Tarokh in U.S. application Ser. No. 09/074,224, filed May 5, 1998, now U.S. Pat. No. 6,185,258, and titled "Transmitter Diversity Technique for Wireless Communications" where symbols are encoded using only negations and conjugations, and transmitted in a manner that employs channel diversity.

Still another approach is disclosed by the last-mentioned inventors in a U.S. application filed Jul. 14, 1998, based on provisional 60/052,689 filed Jul. 17, 1997, titled "Combined Array Processing and Space-Time Coding," where symbols are divided into groups, where each group is transmitted over

a separate group of antennas and is encoded with a group code C that is a member of a product code.

SUMMARY

An advance in the art is realized with a transmitter that employs a trellis coder followed by a block coder. Correspondingly, the receiver comprises a Viterbi decoder followed by a block decoder. Advantageously, the block coder and decoder employ time-space diversity coding which, illustratively, employs two transmitter antennas and one receiver antenna.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 presents a block diagram of an embodiment in conformance with the principles of this invention.

DETAIL DESCRIPTION

FIG. 1 presents a block diagram of an arrangement comporting with the principles of this invention. It comprises a trellis code modulation (TCM) encoder 10 followed by a two-branch space block encoder 20. The output is applied to antenna circuitry 30, which feeds antenna 31, and antenna 32. FIG. 1 shows only two antennas, but this is merely illustrative. Arrangements can be had with a larger number of antennas, and it should be understood that the principles disclosed herein apply with equal advantage to such arrangements.

TCM encoder 10 generates complex numbers that represent constellation symbols, and block encoder 20 encodes (adjacent) pairs of symbols in the manner described in the aforementioned Ser. No. 09/074,224 application. That is, symbols s_0 and s_1 , forming a pair, are sent to antenna 31 and antenna 32, respectively, and in the following time period symbols $-s_1^*$ and s_0^* are sent to antennas 31 and 32, respectively. Thereafter, symbols s_2 and s_3 are sent to antenna 31 and 32, respectively, etc. Thus, encoder 20 creates channel diversity that results from signals traversing from the transmitter to the receiver at different times and over different channels.

The signals transmitted by antennas 31 and 32 are received by a receiver after traversing the airlink and suffering a multiplicative distortion and additive noise. Hence, the received signals at the two consecutive time intervals during which the signals s_0 , s_1 , $-s_1^*$, and s_0^* are sent correspond to:

$$r_0(t) = h_0 s_0 + h_1 s_1 + n_0, \tag{1}$$

and

$$r_1(t) = h_1 s_0^* - h_0 s_1^* + n_1, \tag{2}$$

where h_0 represents the channel from antenna 31, h_1 represents the channel from antenna 32, n_0 is the received noise at the first time interval, and n_1 is the received noise at the second time interval.

The receiver comprises a receive antenna 40, a two-branch space block combiner 50, and a Viterbi decoder 60. The receiver also includes a channel estimator; but since that is perfectly conventional and does not form a part of the invention, FIG. 1 does not explicitly show it. The following assumes that the receiver possesses \hat{h}_0 and \hat{h}_1 , which are estimates of h_0 and h_1 , respectively. Thus, the received signals at the first and second time intervals are combined in element 50 to form signals

$$\tilde{s}_0 = \hat{h}_0^* r_0 + \hat{h}_1 r_1^* \tag{3}$$

and

$$\tilde{s}_1 = \hat{h}_1^* r_0 - \hat{h}_0 r_1^*, \tag{4}$$

and those signals are applied to Viterbi decoder 60.

The Viterbi decoder builds the following metric for the hypothesized branch symbol s_1 corresponding to the first transmitted symbol s_0 :

$$M(s_0, s_1) = d^2 [\tilde{s}_0, (|\hat{h}_0|^2 + |\hat{h}_1|^2) s_1]. \tag{5}$$

Similarly, the Viterbi decoder builds the following metric for the hypothesized branch symbol s_i corresponding to the first transmitted symbol s_1 :

$$M(s_1, s_i) = d^2 [\tilde{s}_1, (|\hat{h}_0|^2 + |\hat{h}_1|^2) s_i]. \tag{6}$$

(Additional metrics are similarly constructed in arrangements that employ a larger number of antennas and a correspondingly larger constellation of signals transmitted at any one time.) If Trellis encoder 10 is a multiple TCM encoder, then the Viterbi decoder builds the following metric:

$$M[(s_0, s_1), (s_i, s_j)] = M(s_0, s_i) + M(s_1, s_j), \tag{7}$$

or equivalently,

$$M[(s_0, s_1), (s_i, s_j)] = d^2 (r_0 \hat{h}_0 s_i^* + \hat{h}_1 s_j) + d^2 (r_1 \hat{h}_1 s_i^* - \hat{h}_0 s_j^*). \tag{8}$$

The Viterbi decoder outputs estimates of the transmitted sequence of signals.

The above presented an illustrative embodiment. However, it should be understood that various modifications and alterations might be made by a skilled artisan without departing from the spirit and scope of this invention.

What is claimed is:

1. An apparatus comprising:
 - a trellis encoder that generates a first symbol and a second symbol;
 - a block encoder coupled to receive the first and second symbols and generate a block of symbols, the block of symbols including the first symbol, the second symbol, a complex conjugate of the first symbol and a negative complex conjugate of the second symbol; and
 - a first antenna and a second antenna coupled to the block encoder to transmit the block of symbols, the first symbol and the complex conjugate of the first symbol being transmitted with space diversity and with time diversity and the second symbol and the negative complex conjugate of the second symbol being transmitted with space diversity and with time diversity.
2. The apparatus as recited in claim 1 wherein the first symbol and the complex conjugate of the first symbol are transmitted during different time intervals and over different ones of the first and second antennas to achieve space diversity and time diversity and the negative complex conjugate of the second symbol and the second symbol are transmitted during different time intervals and over different ones of the first and second antennas to achieve space diversity and time diversity.
3. The apparatus as recited in claim 2 wherein the first and second symbols are transmitted during a first time interval and the complex conjugate of the first symbol and the negative complex conjugate of the second symbol are transmitted during a second time interval.
4. The apparatus as recited in claim 1 further comprising a receiver comprising:
 - a space block combiner configured to receive the transmitted block of symbols and supply output signals.
5. The apparatus as recited in claim 4 further comprising a Viterbi decoder coupled receive the output signals from the space block combiner.

5

6. A method comprising:
 trellis encoding received data to generate a first symbol and
 a second symbol;
 block encoding the first and second symbols to generate a
 block of symbols that includes the first and second symbols,
 a negative complex conjugate of the second symbol, and a complex
 conjugate of the first symbol; and
 transmitting the block of symbols by transmitting the first
 symbol and the complex conjugate of the first symbol at
 different times and over different channels and transmitting
 the second symbol and the negative complex conjugate of the
 second symbol at different times and over different channels.
 7. The method as recited in claim 6 further comprising:
 transmitting the first symbol and the complex conjugate of
 the first symbol at different times and over different
 channels and transmitting the second symbol and the
 negative complex conjugate of the second symbol at
 different times and over different channels by transmitting
 during a first time period the first symbol over a first
 antenna and the second symbol over a second antenna,
 and transmitting during a second time period the negative
 complex conjugate of the second symbol over the
 first antenna and the complex conjugate of the first sym-
 bol over the second antenna.

6

8. A receiver comprising:
 a space block combiner configured to receive a transmitted
 block of symbols and supply output signals, the trans-
 mitted block of symbols including a first symbol, a sec-
 ond symbol, a complex conjugate of the first symbol, and
 a negative complex conjugate of the second symbol; and
 a Viterbi decoder coupled receive the output signals from
 the space block combiner.
 9. The receiver as recited in claim 8 wherein the output
 signals of the space block combiner are $\tilde{s}_0 = \tilde{h}_0^* r_0 + \tilde{h}_1 r_1^*$, and
 $\tilde{s}_1 = \tilde{h}_1^* r_0 - \tilde{h}_0 r_1^*$, where \tilde{h}_0 is a channel estimate of a first
 channel from a first transmitting antenna to the receiver and
 \tilde{h}_1 is a channel estimate of a second channel from a second
 transmitting antenna to the receiver, and r_0 is a first signal
 received at a first time period and transmitted over the first
 and second channels and r_1 is a second signal received at a second
 time period and transmitted over the first and second chan-
 nels.
 10. The receiver as recited in claim 9 where, $r_0 = h_0 s_0 + h_1 s_1 +$
 n_0 and $r_1 = h_1 s_0^* - h_0 s_1^* + n_1$, where h_0 is the first channel, h_1 is
 the second channel, s_0 is the first symbol, s_1 is the second
 symbol, n_0 is received noise during the first time period, and
 n_1 is received noise during the second time period.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,065,516 B2
APPLICATION NO. : 14/280945
DATED : June 23, 2015
INVENTOR(S) : Siavash Alamouti et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

Column 4, in claim 5, line 67, please insert --to-- after “coupled”;


Column 6, in claim 8, line 7, please insert --to-- after “coupled”;

Column 6, in claim 9, line 10, please replace “ \tilde{h}_0^* ” with -- \tilde{h}_0^* -- and “ r_1^* ” with -- r_1^* --;

Column 6, in claim 9, line 11, please replace “ \tilde{h}_1^* ” with -- \tilde{h}_1^* -- and “ r_0^* ” with -- r_1^* --;

Column 6, in claim 10, line 20, please replace “ s_0^* ” with -- s_0^* -- and “ s_1^* ” with -- s_1^* --.

Signed and Sealed this
Twenty-fourth Day of November, 2015



Michelle K. Lee
Director of the United States Patent and Trademark Office