



(12) **United States Patent**
Klaban

(10) **Patent No.:** **US 9,270,824 B2**
(45) **Date of Patent:** ***Feb. 23, 2016**

(54) **EMERGENCY 9-1-1 PORTAL AND APPLICATION**

- (71) Applicant: **Thomas M. Klaban**, West Bloomfield, MI (US)
- (72) Inventor: **Thomas M. Klaban**, West Bloomfield, MI (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/828,175**
(22) Filed: **Aug. 17, 2015**

(65) **Prior Publication Data**
US 2015/0358461 A1 Dec. 10, 2015

Related U.S. Application Data
(63) Continuation of application No. 13/608,141, filed on Sep. 10, 2012, now Pat. No. 9,112,996.

(51) **Int. Cl.**
H04M 11/04 (2006.01)
H04M 3/51 (2006.01)
H04M 7/00 (2006.01)
H04W 4/22 (2009.01)
H04W 4/02 (2009.01)

(52) **U.S. Cl.**
CPC **H04M 3/5116** (2013.01); **H04M 7/0075** (2013.01); **H04M 11/04** (2013.01); **H04W 4/028** (2013.01); **H04W 4/22** (2013.01)

(58) **Field of Classification Search**
CPC combination set(s) only.
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,035,187	A *	3/2000	Franza	H04W 88/02	379/45
6,677,894	B2 *	1/2004	Sheynblat	G01S 5/0036	342/357.46
8,068,808	B2 *	11/2011	Smith	G08B 25/016	379/32.01
8,195,215	B2 *	6/2012	Marocchi	H04W 4/08	455/519
2004/0114611	A1 *	6/2004	O'Connell	H04Q 3/66	370/401
2007/0201664	A1 *	8/2007	Salafia	H04M 15/06	379/201.01
2012/0144305	A1 *	6/2012	Bekiares	H04N 21/422	715/733
2013/0077766	A1 *	3/2013	Keller	H04M 3/42365	379/45


* cited by examiner

Primary Examiner — Joseph J Nguyen
Assistant Examiner — Phung-Hoang J. Nguyen
(74) *Attorney, Agent, or Firm* — Fishman Stewart PLLC

(57) **ABSTRACT**

A computer aided prioritization (CAP) system may receive, from the emergency event reporter device, an emergency event including a priority selected from a set of event priorities and a type of event selected from a set of event types associated with the selected event priority; determine, based on the emergency event and without querying the emergency event reporter device for additional information, whether the emergency event indicates a higher priority emergency event to be handled by a computer aided dispatch (CAD) system or a lower priority emergency event to be handled automatically by a computer aided event module (CAEM); and selectively route the emergency event report to at least one of the CAD system and the CAEM according to the determination.

24 Claims, 13 Drawing Sheets






FIG. 1A




FIG. 2B




FIG. 1B




FIG. 2A




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

Priority	Type of Emergency	Time Received	Elapsed Time	Status	Handled by	Caller Name	Caller Phone#	Caller Address/Location	ACI (Automatic Caller Information) & Caller Text
	Medical	16:24:10	3:50	IN Progress Voice Only	Dispatcher (AMK)	Matt Hughes	947-236-5648	300 Big Beaver Rd Try MI	Allergies: Penicillin, Peanuts Medications: Eliquis (1 Capsule Daily) Medical Conditions: Asthma (Inhaler)
	Domestic Violence	16:25:20	2:40	IN Progress Text Only	Dispatcher (JKL)	Debra Jones	248-321-2654	4700 Greer Rd W Bloomfield MI	10/23/2011 Assault Victim assaulted with a deadly weapon by spouse
	Fire Alarm	16:27:30	0:30	IN Progress Text Only	Dispatcher (TMS)	Jason Harrison	248-553-5541	100 S Cass Lake Rd Waterford MI	
	Storm / Property Damage	16:20:20	7:40	ON Hold Text Only	Dispatcher (TMS)	Marcella Lopez (Spanish only)	734-563-5647	200 Woodward St Ypsilanti MI	Fallen Tree & No Electricity
	Vandalism	16:22:15	5:45	ON Hold Voice Only	Dispatcher (AMK)	Mandy Jackson	248-965-5544	1520 Main St Troy MI	N/A
	Stolen Vehicle	16:27:10	0:50	IN Progress Text Only		Alberto Rameriz	313-563-7456	2212 Burnside St Hamtramck MI	Secondary Vehicle (Motorcycle) 2007 Harley-Davidson Heritage (Red) Plate: JK321 (MI) Exp: 02/28/13 VIN: 4S3554812052581
	Accident	16:25:40	2:20	IN Progress Text Only		Jack Fuller	313-265-9654	North I75 near Exit 69A	Can be contacted Accident with Injuries Can be contacted
	Accident	16:26:00	2:00	IN Progress Text Only		Andrea Smith	248-563-9654	North I75 near Exit 69A	Several cars involved in major accident
	Drug Dealer	16:25:00	3:00	IN Progress Text Only		Anonymous	N/A	N/A	Drug Dealer Nickname Venom (acid/smack) Driving Black Mustang

1102

FIG. 11




FIG. 12

1

EMERGENCY 9-1-1 PORTAL AND APPLICATION**BACKGROUND**

In current caller to emergency dispatch systems (e.g., 9-1-1 dispatch), a dispatcher may ask a multitude of questions to the caller and record the answers. These questions may be directed to determining the caller's name, emergency and location based on the answers given by the caller. Only after collecting all of the necessary information can the dispatcher locate an appropriate nearest first responder to be dispatched to the location of the caller.

One potential cause for slow response time is an inability of the dispatcher to understand the caller. In the best case scenario, the caller is calling from the home address on a clear line with no background noise, and the first responder may be dispatched immediately. In most cases, the caller is somewhere other than their home address, calling from a noisy location, has trouble articulating his or her emergency and location, and the dispatcher has to somehow figure out who to send and where.

Lack of communication arising from language barriers, poor reception or a panic stricken caller who cannot speak or is screaming contributes to delays in response time. In some instances, these issues may cause a complete inability for the dispatcher to dispense a first responder altogether. In domestic violence cases or instances when a caller cannot speak, the situation may become even more desperate because the dispatcher cannot communicate with the caller, and unless an accurate address or global positioning system (GPS) coordinate is established, no first responder can be dispatched.

With the advent of functionality related to Phase II of the Federal Communications Commissions' E-911 initiative, a location of a caller may be determined by either triangulating the location based on multiple cellular phone towers; or in the case of a smartphone, by way of an exact GPS location determined by the smartphone device. This technology has improved response time, but in some cases several re-bids (i.e., requests for a location) are needed to obtain a useful caller location. In the case of triangulation in metropolitan areas, such location information is rarely accurate enough to locate a caller without his or her assistance.

One way for emergency dispatch systems to associate additional information with an emergency caller is by way of an automatic number identification (ANI)/automatic location identification (ALI) database. The ANI is a database of information configured to store name information and location information associated with telephone lines or telephone numbers. The ANI/ALI database may be used by emergency dispatch to retrieve the physical address and name associated with the telephone line from which a 9-1-1 call originated. This information may not be available for mobile phones that are designated as 9-1-1 only with no mobile plans, or throw away/disposable mobile phones. Also, such information may not be particularly useful to emergency dispatch systems for voice over internet protocol (VoIP) phones or mobile phones, as such devices may be utilized at a location far removed from the physical location on file in the ANI/ALI database. Moreover, the ANI/ALI database provides only limited information about the caller.

As a result, current emergency dispatch systems are fraught with delays, and in some cases, fail altogether because of communication or technical issues.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A illustrates an exemplary emergency event including an event type, an event priority, and event details.

2

FIG. 1B illustrates an exemplary system for implementing an emergency portal and dispatch system configured to handle emergency events.

FIG. 2A illustrates an exemplary data flow that may be performed by an emergency portal and dispatch system environment utilizing existing ANI/ALI functionality and configured to handle emergency events.

FIG. 2B illustrates an exemplary data flow that may be performed by an emergency portal and dispatch system environment utilizing IP technology and configured to handle emergency events.

FIG. 3 illustrates an exemplary user interface of an emergency priority dispatch application for selecting a priority for an emergency event.

FIG. 4 illustrates an exemplary user interface of an emergency priority dispatch application in night mode.

FIG. 5 illustrates an exemplary user interface of an emergency priority dispatch application for selecting an event type of a high priority emergency event.

FIG. 6 illustrates an exemplary user interface of an emergency priority dispatch application for selecting an event type of a medium priority emergency event.

FIG. 7 illustrates an exemplary user interface of an emergency priority dispatch application for selecting an event type of a low priority emergency event.

FIG. 8 illustrates an exemplary user interface of an emergency priority dispatch application for selecting an event type of a third-party priority emergency event.

FIG. 9 illustrates an exemplary user interface of an emergency priority dispatch application for selecting an event type of an anonymous priority emergency event.

FIG. 10 illustrates an exemplary user interface of an emergency priority dispatch application for communicating information with emergency dispatch.

FIG. 11 illustrates an exemplary user interface of a computer aided prioritization system.

FIG. 12 illustrates an exemplary process for receiving and processing an emergency event according to an identified event priority and type.

DETAILED DESCRIPTION

An emergency portal and dispatch system may improve the caller-to-emergency dispatch interaction by prioritizing incoming calls, providing additional caller information and creating a unified interface to bridge external emergency data with a computer aided dispatch (CAD) system at an emergency dispatch center. The emergency portal and dispatch system performs these objectives by shifting some of the responsibility onto the caller, business or reporting third-party to electronically provide a priority of the call, a type of emergency, and other pertinent information to the dispatch center so that the emergency dispatcher may dispatch an appropriate first responder in the fastest and most efficient manner possible.

With the emergency priority dispatch architecture, a caller may provide a priority and a type of emergency to dispatch as part of an emergency request or during the establishment of the emergency call, without the need to obtain additional queries for additional information from the dispatch center. This allows the dispatch center to automatically prioritize calls before an emergency dispatcher/call-taker gets involved. Instead of asking probing questions and waiting for answers, the dispatcher/call-taker may become more proactive with the caller by verifying the electronically received information and dispatching the proper first responder in the most expeditious manner. Moreover, the emergency portal

may allow low priority, third party and anonymous emergency requests to be processed without any emergency dispatcher involvement.

The emergency priority dispatch may include an emergency priority dispatch (EPD) application executed by a user's communications device. A user may launch the emergency priority dispatch application to begin reporting an emergency. The user may further select a type of connection icon to identify a type of communications session to have with dispatch, such as voice, texting or text-to-speech/speech-to-text. Selecting one of the communications options may trigger a request or may begin call initiation with dispatch. In some cases, the initial request to dispatch may include the priority and type of emergency information. In other cases while waiting for the connection to be established, which in the current centralized automatic message accounting (CAMA) environment may take from 5 to 10 seconds, the emergency priority dispatch application may prompt the caller for one or more of a priority and a type of emergency. If the caller selects a pre-defined type of emergency, the application may execute additional processes that are designed to help emergency dispatch more quickly dispatch the correct and closest first responder. These processes may include, for example, asking the caller questions designed to receive a simple yes/no response, or to asking the caller to select from a limited set options that clearly explain the type of information being requested.

While the caller is communicating with the emergency dispatcher, additional caller emergency information may be transmitted by the emergency priority dispatch application to dispatch. At application setup time, the caller may enter caller emergency information and set a permission level to determine what caller emergency information may be transmitted with what priority and type of emergency.

The emergency priority dispatch user interface may further assist the caller in texting and text-to-speech modes by providing short-cuts to common phrases used in emergency conversations that may be selected by the caller without the need to type in using a keyboard. These common phrases may be most helpful in the texting mode because they may clearly explain the emergency and avoid abbreviations that may be ambiguous.

Before or after a first responder is dispatched, the emergency dispatch may retrieve the additional caller emergency information from the emergency priority dispatch application and forward it to the first responder. Or, the additional caller information may be retrieved from a caller information server. Once the first responder arrives at a caller location, and in cases when an emergency dispatcher cannot relay additional caller data information electronically to the first responder, the first responder may be able to retrieve information from the EPD application directly. This also enhances the ability of the first responder to assist the caller, especially in a medical emergency if the caller becomes unavailable, such as after fainting or going into shock. The emergency portal and dispatch system may further provide pertinent personal, medical, handicap and location information to an emergency dispatcher, in order to expedite dispatching of appropriate first responders.

For third-party products that provide incident information, the emergency portal and dispatch system may provide a unified interface that allows prioritization and categorization of dispatch requests with the additional ability of providing and aggregating alarm location, contact information, telematics data, video feeds, pre-plans, photos and other relevant data to minimize emergency dispatcher involvement and cutting the time to dispatch the appropriate first responders.

While the emergency portal and dispatch system is discussed herein in relation to 9-1-1 service as implemented in the United States and Canada, the system is not so limited and is equally applicable to worldwide portal and caller-to-emergency dispatch connectivity and including, for example, 1-1-2 service available in Euro-Zone countries.

As a portion of shifting responsibility from dispatch to the caller, an emergency portal and dispatch system may define an event format for use by the dispatch system. FIG. 1A illustrates an exemplary emergency event **102**, including an event priority **104**, an event type **106**, and optionally, additional event details **108**. This event format may be used to allow emergency dispatch to quickly identify and classify incoming emergency events **102**.

The event priority **104** included in the emergency event **102** may include a priority selected from a set of event priorities. The set of event priorities may include one or more of: a high priority event indicative of a life-threatening event requiring urgent assistance, a medium priority event indicative of a non-life threatening event requiring urgent assistance, a low priority event indicative of a non-life threatening event not requiring urgent assistance, a third party priority event indicative of a report of information where a user of the emergency event reporter device is not involved, and an anonymous event priority indicative of a report of information where the user of the emergency event reporter device is not involved and wishes to remain anonymous.

The event type **106** included in the emergency event **102** may include a type of event selected from a set of event types associated with the selected event priority **104**. The set of event types may include one or more of: medical, accident, fire, child abduction, missing person, domestic violence, assault, robbery, hit & run, storm/property damage, vandalism, loud noise, gang activity, shots fired, riot, burglary, rape, stolen vehicle, stolen property, suspicious persons/activity, suspicious vehicle, observed drug deal, prostitution, among other exemplary types of emergency.

The emergency event **102** may further include additional event details **108**, such as any other information associated with the emergency event **102** that may be useful for dispatch to have. Moreover, the additional event details **108** may be supplemented by additional reporters of information to provide additional relevant information to dispatch.

FIG. 1B illustrates an exemplary system **100** for implementing an emergency portal and dispatch system configured to handle emergency events **102**. As shown, the system **100** includes a public safety answering point (PSAP) **110** in communication with a computer-aided dispatch (CAD) system **112** which is in turn in communication with caller priority dispatch (CPD) workstations **114**. The PSAP **110** may further be in communication with a plurality of reporters of information over a communications network **120**. These reporters of information may include a smartphone **116** having an emergency priority dispatch (EPD) application **118**, a phone device **122**, a burglar alarm **124**, a fire alarm **126**, a car alarm **128**, a medical alert device **130**, a telematics unit **132**, and a video feed **134**. In some instances, the system **100** may include an ANI/ALI system **136**. The system **100** may further include an automatic caller information (ACI) database **138** in communication with an ACI server **140**. The ACI server **140** may further provide an emergency caller information (ECI) web portal **142**. The system may also include a computer aided prioritization (CAP) system **144** in communication with the PSAP **110**, a computer aided event module (CAEM) **146**, the CAD system **112**, and the CPD workstation **114**. System **100** may take many different forms and include multiple and/or alternate components and facilities. While an

5

exemplary system **100** is shown in FIG. 1B, the exemplary components illustrated in FIG. 1B are not intended to be limiting. For example, some examples are implemented without ANI/ALI systems **136**. Indeed, additional or alternative components and/or implementations may be used.

As illustrated in FIG. 1B, system **100** may include a PSAP **110**. The PSAP **110** may include one or more devices responsible for receiving and handling emergency events **102**, such as requests for emergency services such as police, medical and fire. In some cases a PSAP **110** may be associated with a particular geographic area such that requests for emergency services may be routed to the appropriate PSAP **110** for the area. The PSAP **110** may include call distribution functionality, such as functionality configured to route the requests to the CAD system **112**.

The CAD system **112** may be configured to receive the emergency events **102** and to selectively forward the emergency events **102** to CPD workstations **114**. The CPD workstation **114** may be computing devices used by dispatcher personnel to receive and interact with callers and emergency event **102** information. The CAD system **112** may further be configured to maintain the status of responding resources in the field (e.g., ambulance locations) as well as the status of the various dispatch/call-taker operators and CPD workstations **114**. In many cases, the CAD system **112** may be located in a relatively centralized public-safety call center, while in other cases portions of the CAD system **112**, such CPD workstations **114**, may be located with mobile field personnel.

The smartphone **116** may be implemented as a combination of hardware and software, and may include one or more software applications or processes for causing one or more computer processors to perform the operations of the smartphone **116** described herein. Smartphones **116** may include any cellular or mobile phone that are programmable, and includes, but is not limited to phones running the iOS operating systems distributed by Apple Inc. of Cupertino, Calif., the BlackBerry OS distributed by Research In Motion of Waterloo, Canada, the Android operating system developed by the Open Handset Alliance, and Microsoft Windows® operating system developed by Microsoft Inc. of Redmond, Wash.

One such application installed on the smartphone **116** may be the EPD application **118**. The smartphone **116** may be configured to execute the EPD application **118** to perform operations in relation to emergency dispatch, such as providing emergency events **102** to the PSAP **110**. Further aspects of the EPD application **118** are discussed in detail below with respect to FIGS. 3-10.

The communications network **120** may provide communications services, such as packet-switched network services (e.g., Internet access and/or VoIP communication services) and/or circuit-switched services (e.g., plain old telephone service (POTS) and/or integrated services digital network (ISDN) services) to various communications devices. Communication devices include, but are not limited to smartphones **116** or other phone devices **122** such as cell phones, VoIP phones, and public switched telephone network (PSTN) phones configured to communicate over the POTS. Communications devices may also include tablet computers, laptop computers, desktop computers or any device other that may provide a communication session over a connection between the PSAP **110** and one or more of a caller, a business, and a third-party emergency product provider.

The communications network **120** may include any combination of wired or wireless forms of communication. For example, the communications network **120** may include cable, optical fibers, cellular towers, etc. In some cases, the

6

communications network **120** may support the use of the CAMA telephone protocol for emergency requests sent to the PSAP **110** such as emergency 9-1-1 calls. Other communication protocols that may be utilized over the communications network **120** may include, but are not limited to, dial-up networking, teletype data transmission, internet protocol (IP) and short message service (SMS)/multimedia messaging service (MMS) messaging, among others.

When utilizing a phone device **122** that lacks an ability to provide emergency events **102**, such as a voice-only plain old telephone system telephone, the system **100** may provide compatibility by allowing a dispatcher/call-taker utilizing a CPD workstation **114** to manually enter the event priority **104** and emergency type **106** to facilitate entry of the emergency event **102** into the system **100**.

In addition to smartphones **116** and phone devices **122**, additional reporters may provide information to dispatch. For example, burglar alarms **124** may provide information regarding break-ins at building locations, fire alarms **126** may provide information regarding fires at building locations, car alarms **128** may provide information regarding auto thefts or break-ins, medical alert device **130** may provide information regarding health emergencies of monitored users, telematics unit **132** may provide information regarding vehicle crashes and history, and video feeds **134** may provide video information relating to past or in-progress incidents. To facilitate the handling of emergencies, these additional reporters of information may provide emergency events **102** including event priority **104**, event type **106**, and optionally further event details **108**.

In some examples, an ANI/ALI system **136** may be included in the system **100** as a reporter of supplemental information for received emergency events **102**. For example, the ANI/ALI system **136** may be configured to accept requests for physical address and name information associated with a phone number, perform queries of an ANI/ALI database for the requested information, and respond to the requests by returning the requested name and physical location on file in the ANI/ALI database.

The ACI database **138** may further be included in the system **100** as an additional reporter of supplemental information, and may be configured to store additional information regarding users of the PSAP **110**. Initially (or at least prior to the reporting of an emergency), a user may pre-register to have certain predetermined information available to the PSAP **110**. For example, the predetermined information may include personal information, location information, medical information, physical/mental handicap information, special needs information, language information, special circumstances information, and emergency contact information, as some examples. Moreover, the user may identify predetermined information as being releasable based on the event type **106** of the emergency. For example, medical information may only be released to the PSAP **110** for medical emergencies of the user, and next-of-kin information may only be released upon death.

Personal information may include, but is not limited to: name, phone number, age, sex, race, height, weight, eye color, hair color, date-of-birth, photo, primary/secondary language, and e-mail address. Location information may include, but is not limited to: physical address, latitude/longitude of address, type of address, type of structure, photo of structure, number of stories, type of utilities, alarms, video cameras, nearest fire hydrant, gated community, nearest cross streets and/or land marks. Medical information may include, but is not limited to: blood type, medical conditions such as diabetes, HIV, food or drug allergies, prior heart attack or any other relevant

medical conditions; primary-care physician name, phone number, pager number, e-mail address and preferred hospital. Special-needs and mental/physical handicap information may include, but is not limited to: hearing impaired, visually impaired, mentally impaired, loss of limbs, eye sight, special needs child, physically impaired or young child. Language information may include, but is not limited to: a primary/national language of the system **100**, an indication of a secondary language of the system **100**, a primary language of a caller, a secondary language of a caller and a flag that indicates whether or not the caller is able to communicate in the primary language of the primary/national language of the system **100**. Special circumstances information may include, but is not limited to: dog on premises, confined to bed, confined to wheel chair, elderly person living alone or any other special circumstances that would help the first responder in an emergency situation. Emergency contact information may include, but is not limited to: name, address, phone number, relationship to caller and e-mail address, in what circumstance the emergency contacts will be notified, and what method of notification will be used (e.g., text-to-speech, phone call, SMS Text Message or e-mail).

The ACI server **140** may be configured to receive requests for the predetermined information from dispatch, and may selectively retrieve and provide the predetermined information responsive to the requests. The ACI server **140** may further support an ECI web portal **142** configured to allow the users to add, edit, remove, and otherwise update the predetermined information and conditions for its release. The ECI web portal **142** may provide secure access to allow callers to add or edit stored caller information including, but not limited to: personal, medical, handicap and mental information, as well as location, contact, vehicle and system information. A caller may use the ECI web portal **142** to enter or change their information as well as information regarding their family members including, but not limited to, spouse, significant other, child, parent, other relative, or acquaintance. Other than the authorized callers, access to the stored caller information may be highly secure and limited to personnell with the security clearances. In some cases, a high security firewall may be used to protect the integrity of the data and to ensure its distribution only to authorized PSAP **110** locations.

The CAP system **144** may be configured to receive an emergency event **102** including an event priority **104** selected from a set of event priorities **104** and an event type **106** selected from a set of event types **106** associated with the selected event priority **104**. The CAP system **144** may further be configured to determine, based on the emergency event **102**, whether the emergency event **102** indicates a higher priority emergency event **102** to be handled by a dispatcher/call-taker (e.g., by the CAD system **112**) or a lower priority emergency event **102** to be handled automatically (e.g., by the CAEM **146** discussed in more detail below). This determination may be made by the CAP system **144** without querying the emergency event reporter device for additional information. Based on the determination, the CAP system **144** may further be configured to selectively route the higher-priority emergency event **102** reports to the CAD system **112** and the lower-priority event reports to the CAEM **146**.

The CAEM **146** may be configured to automatically handle lower-priority emergency event **102**. For example, the CAEM **146** may be configured to return a message to the user indicating that the emergency event **102** was received and will be processed. The CAEM **146** may also be configured to request additional information from the reporter of the emergency event **102**. As some examples, the CAEM **146** may be configured to provide pre-formatted phrases to the caller that are

designed to receive a simple yes/no response, or to ask the caller to select from a limited set of options that clearly explain the type of information being requested.

The CAP system **144** may be further configured to supplement information included in the emergency event **102** according to a predetermined rule for including additional information. As some examples, the predetermined rule for including additional information in the emergency event **102** may include one or more of: (i) a rule making pre-entered emergency information available based on at least one of the selected event priority **104** and the event type **106** of the emergency event **102**; (ii) a rule including telematics data in emergency event **102** reports for events including a vehicle; (iii) a rule including health information in emergency event **102** reports for events requiring medical attention; (iv) a rule including additional contact information in the emergency event **102** reports for events requiring notification of emergency contacts; (v) a rule including floor-plan information for emergency event **102** reports requiring access to a building; (vi) a rule including picture or video information for emergency event **102** reports for which picture or video information is available; and (vii) a rule including vehicle information for emergency events **102** that involve vehicles. If the conditions of one or more of these rules are triggered based on the fields of the emergency event **102**, the CAP system **144** may be configured to retrieve the additional information from one or more of the ANI/ALI system **136** and the ACI server **140**.

Moreover, additional reporters may provide information to dispatch. The unified third-party interface **148** of the CAP system **144** may be configured to receive such information in a uniform manner. For example, one or more of the burglar alarms **124**, fire alarms **126**, car alarms **128**, medical alert device **130**, telematics units **132**, and video feeds **134** may provide information to the CAEM **146** for the predetermined rules by way of the unified third-party interface **148** of the CAP system **144**. Exemplary supplemental information to be received via the third-party interface **148** may include: type of alarm or emergency, emergency contacts, business name, business location, hazardous material information, sprinkler information, telematics, video feeds, photos, architectural drawings, pre-plans/evacuation information, etc. and any other information that will enable the emergency dispatcher to expedite dispatching the appropriate first responders. Moreover, the third-party interface **148** may also be configured to receive emergency events **102** from various event reporters, the received emergency events **102** including an event priority **104** and an event type **106**, similar to as discussed above with respect to caller-reported incidents.

The CAP system **144** may further be configured to present the selected event priority **104**, event type **106**, event details **108** and any additional supplemental information to a dispatcher/call-taker associated with the CAD system **112** before, or while a communications session is established between a dispatcher/call-taker of the CAD system **112** and the reporting device (e.g., the smartphone **116** executing the EPD application **118**).

As a more specific example, the CAP system **144** may be configured to receive an emergency event **102** from a smartphone **116** executed an EPD application **118**. The EPD application **118** may connect to the CAP system **144** utilizing a data connection and may provide a unique identifier associated with the network device (e.g. phone number, serial number etc.) to the CAP system **144**. The EPD application **118** may substantially simultaneously connect to the PSAP **110** utilizing a voice and/or data connection (depending on the capabilities of the PSAP **110**), and may pass the unique networked computing device identifier from the PSAP **110** to the

CAP system 144. The unique networked computing device identifier passed by the PSAP 110 to the CAP system 144 may then be associated with the networked computing device identifier passed to the CAP system 144 directly, in order to allow the CAP system 144 to make a positive identification of the event reporter. Once a positive identification has been made, the CAP system 144 may be configured to transmit the emergency event 102 and appropriate personal, medical, physical/mental handicap, contact, location and vehicle information to the CPD workstation 114 or to the CAEM 146 for processing.

With respect to the reporting of emergency events 102 by third-party event reporters, such as burglar alarms 124, fire alarms 126, car alarms 128, medical alert devices 130, telematics units 132 and video feeds 134, a communications session may be established with the CAP system 144 over which an emergency event 102 may be provided. The emergency event 102 may include information such as a unique identifier associated with the third party device (e.g. serial number, account number etc.), an event priority 104 and an emergency type 106. The CAP system 144 may be configured to route the emergency event 102 along with any additional event details 108 (e.g., location, contact, pre-plan, video, personal, medical, physical/mental handicap, or vehicle information) to the appropriate CPD workstation 114 or to the CAEM 146 for processing.

FIG. 2A illustrates an exemplary data flow 200-A that may be performed by an emergency portal and dispatch system 100 environment utilizing existing ANI/ALI functionality and configured to handle emergency events 102. The data flow 200-A may be performed by various devices, such as by the CAP system 144 in communication with an ANI/ALI system 136 and one or more event reporters over a communications network 120. The exemplary data flow 200-A may be performed in systems 100 in which ACI functionality is integrated into an existing PSAP 110 system utilizing ANI/ALI information.

The exemplary data flow 200-A may begin with an emergency event 102 being generated by an event reporter. Exemplary event reporters may include any of the reporters discussed above, such as a smartphone 116 executing an EPD application 118, a phone device 122, a burglar alarm 124, a fire alarm 126, a car alarm 128, a medical alert device 130, a telematics unit 132, or a video feed 134. The emergency event 102 may include an event priority 104 and an event type 106, as discussed above.

The CAP system 144 may receive the emergency event 102 from the event reporter. In some examples, the emergency event 102 may be received by the CAP system 144 over the communications network 120 via the PSAP 110. In other examples, the emergency event 102 may be received by the CAP system 144 via a third-party interface 148.

Upon receipt of the event, the CAP system 144 may be configured to request ANI/ALI information from the ANI/ALI system 136 according to the received emergency event 102. For example, based on an identifier included in the emergency event 102 such as a phone number of the caller, the CAP system 144 may request the ANI/ALI system 136 to query an ANI/ALI database for the physical address and name associated with the caller from which the emergency event originated. The CAP system 144 may further be configured to receive the requested ANI/ALI information. For example, responsive to the request, the ANI/ALI system 136 may provide the requested information, and may return the requested name and physical location on file in the ANI/ALI database. The CAP system 144 may be configured to supplement the information of the emergency event 102 according to the

received ANI/ALI information. This additional information may be incorporated into the emergency event 102 as additional event details 108.

The CAP system 144 may be further configured to supplement the information of the emergency event 102 according to a predetermined rule keyed to at least a portion of the information received from the ANI/ALI system 136 and additional information in the emergency event 102. As an example, the CAP system 144 may identify based on the event type 106 of the emergency event 102 that the emergency event 102 indicates a medical emergency for an identified user. Accordingly, the CAP system 144 may invoke a rule making pre-entered emergency information for the user available based on at least one of the selected event priority 104 and the event type 106 of the emergency event 102. The pre-entered emergency information may have been previously entered by the user by way of the ECI web portal 142.

Continuing with the medical emergency event 102 example, the CAP system 144 may request certain predetermined medical information from the ACI database 138 that is intended to be provided to the CAD system 112 in the case of a medical emergency. The ACI database 138 may respond to the request with the requested information. The CAP system 144 may then incorporate the supplemental information into the emergency event 102 as additional event details 108, and may forward the supplemented emergency event 102 to the CAD system 112 for further processing (or to the CAEM 146 for a lower-priority emergency event 102).

FIG. 2B illustrates an exemplary data flow 200-B that may be performed by an emergency portal and dispatch system 100 environment utilizing IP technology and configured to handle emergency events 102. Similar to the exemplary data flow 200-A, the exemplary data flow 200-B may also be performed by various devices, such as by the CAP system 144 in communication with one or more event reporters over a communications network 120.

Similar to the exemplary data flow 200-A, the exemplary data flow 200-B may begin with an emergency event 102 being generated by an event reporter. Upon receipt of the emergency event 102, the CAP system 144 may be configured to determine whether any ACI information related to the emergency event 102 was received. For example, an emergency event 102 may be received from a smartphone 116 executing an EPD application 118, where the event requires supplementation according to any applicable rules. In other examples, an emergency event 102 may be received where the EPD application 118 has already supplemented the emergency event 102 with locally-stored additional event details 108. In such an instance, further supplementation of the emergency event 102 may be unnecessary. In some examples, regardless of whether the emergency event 102 was supplemented by the reporting event reporter, the CAP system 144 may determine to supplement the event according to the ACI database 138.

If the CAP system 144 determines to supplement the information of the emergency event 102, may be configured to supplement information included in the emergency event 102 according to a predetermined rule for including additional information based on the information of the emergency event 102 directly, without requiring the use of an ANI/ALI system.

For instance, the CAP system 144 may query the ACI database 138 for information based on one or more of an identifier of the caller associated with the emergency event 102 (e.g., an IP address from which the emergency event was received 102, a caller name, login ID, or other handle included in the emergency event 102, etc.), an event priority 104 of the event, and an event type 106 of the event. The ACI

database 138 may provide the requested information back to the CAP system 144, and the CAP system 144 may incorporate the supplemental information into the emergency event 102 as additional event details 108. The CAP system 144 may then forward the supplemented emergency event 102 to the CAD system 112 for further processing (or to the CAEM 146 for a lower-priority emergency event 102).

FIG. 3 illustrates an exemplary user interface 302 of an EPD application 118 for selecting an event priority 104 for an emergency event 102. The user interface 302 may be provided, for example, by a smartphone 116 executing the EPD application 118.

As illustrated, the user interface 302 may include priority controls 304 configured to allow a user to select a relevant event priority 104. The user interface 302 may accordingly receive a user selection of the event priority 104 upon a user selection of one of the priority controls 304. For example, the user interface 302 may include priority controls 304 for the selection of high priority, medium priority, low priority, third-party report priority, and anonymous priority event priorities 104.

A high priority event priority 104 may identify a life-threatening event needing an immediate response. Exemplary high priority event types 106 may include medical emergencies, immediate physical dangers such as domestic violence, fires or any other life threatening event.

A medium priority event priority 104 may identify a non-life threatening even still requiring a fast response. Exemplary medium priority event types 106 may include hit & run, vandalism, an accident with no obvious injuries, a storm/property damage with no obvious injuries, an unarmed robbery in progress, etc.

A low event priority 104 may identify a non-life threatening event not requiring an immediate response. Exemplary low priority event types 106 may include filing a police report after the fact for a burglary not in progress, a minor accident, minor storm or property damage, vandalism, stolen vehicle or property, etc.

A third-party event priority 104 may identify an event where the caller is not physically involved, but wants dispatch to be aware of the situation. Exemplary third-party event types 106 may include the reporting of a car accident where the caller is not physically involved, the reporting of a suspicious person/activity or vehicle, the reporting of a drug dealer or deal in progress, or the reporting of prostitution or shooting in an area.

An anonymous event priority 104 is similar to a third-party event priority 104, except the identity of the reporter may be kept confidential from dispatch. The anonymous option encourages callers to report suspicious activity without the fear of being found out. This may be a useful priority 104 in certain situations, such as for children in school who see event types 106 such as bullying, illegal activity such as consuming alcohol or selling drugs, or for any person who wants to report a crime or other illegal activity without identifying themselves. This information may then be distributed to neighborhood watch groups as well as to law enforcement.

The user interface 302 may also include a bypass control 306 configured to allow the user to connect with dispatch directly without specifying the event priority 104, a home control 308 configured to allow the user to return to a home page of the EPD application 118, a day/night control 310 configured to toggle the background of the EPD application 118 for better day or night visibility.

Texting communication may be established between the EPD application 118 and dispatch upon selection of a texting control 312 from the EPD application 118. More specifically,

the EPD application 118 may be configured to cause the smartphone 116 to send and receive text messages with the CAP system 144. The CAP system 144 in turn may pass the text messages between the smartphone 116 and a CPD workstation 114 of a dispatcher communicating with the user of the EPD application 118. Accordingly, the text messages may be displayed to the dispatcher/call-taker. In some cases, the dispatcher/call-taker may further utilize pre-formatted messages, such as questions designed to receive a simple yes/no response, or asking the caller to select from a limited set of options that clearly explain the type of information being requested. These pre-formatted messages may be set up through the CAP system 144 and stored on the ACI server 140 or in the ACI database 138.

Voice communication may be established between the EPD application 118 and dispatch upon selection of a voice control 314 from the EPD application 118. To facilitate the voice communication, the PSAP 110 may receive a voice call initiated by the EPD application 118 of the smartphone 116. The PSAP 110 may accordingly route the received voice call to an appropriate dispatcher/call taker or CPD workstation 114. In voice mode, the CPD workstation 114 may be used by the dispatcher/call-taker to enter an event priority 104 and an event type 106 to be passed to the CAP system 144.

FIG. 4 illustrates an exemplary user interface 402 of an EPD application 118 in night mode. The user interface 402 may be displayed, for example, upon selecting the day/night control 310 configured to toggle the background of the EPD application 118. The user interface 402 in this instance may be an exemplary night mode version of the user interface 302 discussed above. The night mode may display the same information as the day mode, but may do so with a dark background rather than a light background. The dark background may be more readable in a dark environment, and may also allow a user to report an emergency event 102 without throwing a large amount of light and being spotted.

FIG. 5 illustrates an exemplary user interface 502 of an EPD application 118 for selecting an event type 106 of a high priority emergency event 102. Similar to the user interface 302, the user interface 502 may include a home control 308 configured to allow the user to return to a home page of the EPD application 118, a day/night control 310 configured to toggle the background of the EPD application 118 for better day or night visibility, a texting control 312 configured to access texting functionality, and a voice control 314 configured to access voice functionality.

Moreover, similar to the user interface 402, the user interface 502 may also include priority controls 304 for the selection of high priority, medium priority, low priority, third-party report priority, and anonymous priority emergency events 102. In the illustrated example, a high priority event type 106 was selected (e.g., from the user interface 302). The user interface 502 may further include an indication that the high priority event type 106 was selected, for example, by highlighting the priority control 304 associated with a high priority event type 106.

Additionally, the user interface 502 may include type controls 504 for the selection of different event types 106 of emergency events 102. The available event types 106 may be those event types 106 associated with the selected event priority 104. For example, upon receiving a selection of a high priority event priority 104, the user interface 502 may provide type controls 504 for a set of high priority event types 106, such as a medical emergency, an accident, a fire, a child abduction, a missing person, a domestic violence incident, an assault, a robbery, and another emergency to be specified by a user. The user interface 502 may be configured to allow a

13

user to select the type control **504** associated with the event type **106** for the emergency event **102** being reported.

Upon selection of the event priority **104** and event type **106** (and potentially after receiving a user confirmation) the EPD application **118** may cause the smartphone **116** to submit the emergency event **102** to the CAP system **144**.

FIG. 6 illustrates an exemplary user interface **602** of an EPD application **118** for selecting an event type **106** of a medium priority emergency event **102**. For example, upon receiving a selection of a medium priority event priority **104**, the user interface **602** may provide type controls **504** for a set of medium priority event types **106**, such as a hit & run accident, an accident, a storm or property damage, vandalism, a loud noise complaint, gang/shots fired/riots, an assault, a robbery, or another emergency to be specified by a user. The user interface **602** may be configured to allow a user to select the type control **504** associated with the event type **106** for the emergency event **102** being reported.

FIG. 7 illustrates an exemplary user interface **702** of an EPD application **118** for selecting an event type **106** of a low priority emergency event **102**. For example, upon receiving a selection of a low priority event priority **104**, the user interface **702** may provide type controls **504** for a set of low priority event types **106**, such as a burglary after the fact, an accident after the fact, a storm or property damage, a rape or assault after the fact, vandalism after the fact, a previous incident of domestic violence, a stolen vehicle, stolen property, or another type of report of an incident after the fact. The user interface **702** may be configured to allow a user to select the type control **504** associated with the event type **106** for the emergency event **102** being reported.

FIG. 8 illustrates an exemplary user interface **802** of an EPD application **118** for selecting an event type **106** of a third-party priority emergency event **102**. For example, upon receiving a selection of a third party event priority **104**, the user interface **802** may provide type controls **504** for a set of third-party priority event types **106**, such as a report of a suspicious person, a report of a suspicious vehicle, a report of a probable drug dealer, a report of an accident in which the third-party is not involved, a report of an assault in which the third-party is not involved, a report of probably prostitution, a report of a robbery in which the third-party is not involved, a report of a fire observed by the third-party, and a report of probable gang or riot activity. The user interface **802** may be configured to allow a user to select the type control **504** associated with the event type **106** for the emergency event **102** being reported.

FIG. 9 illustrates an exemplary user interface **902** of an EPD application **118** for selecting an event type **106** of an anonymous priority emergency event **102**. The user interface **902** may include similar options to those for the third-party priority emergency event **102**, except that the identity of the reporter may be kept confidential for an anonymous priority event type **106**.

FIG. 10 illustrates an exemplary user interface **1002** of an EPD application **118** for communicating information with emergency dispatch. The user interface **1002** may be provided by the EPD application **118** upon providing an emergency event **102** based on a selection of an event priority **104** and an event type **106**. The user interface **1002** may include summary information **1004** relating to the emergency event **102** and caller information **1006** related to the caller reporting the emergency event.

The user interface **1002** may further allow for the display of dialog **1008** between the EPD application **118** and dispatch related to the emergency event **102** being reported. An exemplary dialog **1008** is illustrated in the user interface **1002**,

14

including updates from dispatch to the EPD application **118** indicating the status of dispatch in responding to the emergency event **102** being reported.

In some cases, the EPD application **118**, CAP system **144** and CPD workstation **114** may establish a texting environment that allows the dispatcher/call-taker to communicate with the caller. This environment may be displayed in the dialog **1008** portion of the user interface **1002**. The texting environment may provide pre-formatted phrases by way of the dialog **1008** portion of the user interface **1002** that are designed to receive a simple yes/no response, or to ask the caller to select from options that clearly explain the type of information needed in order to dispatch a first responder. The EPD application **118** may further provide controls in the user interface **1002** to allow for the reception of responses from the caller, such as yes and no buttons to receive yes or no responses, or option controls in response to multiple choice questions from dispatch. These provided controls may allow for the caller to respond to questions from dispatch while minimizing keystrokes. The dialogue between the dispatcher/call-taker and the caller may be electronically transferred to the CAD system **112** and may be associated with the emergency event **102**.

FIG. 11 illustrates an exemplary user interface **1102** of a CAP system **144**. The user interface **1102** of the CAP system **144** may include be configured to present a listing of the emergency events **102** being handled by the CAP system **144**. The user interface **1102** of the CAP system **144** may be configured to show the status of external connections or communications session with event reporters, which may include, but are not limited to, smartphones **116** having an EPD application **118**, phone devices **122**, burglar alarms **124**, fire alarms **126**, car alarms **128**, medical alert devices **130**, telematics units **132**, and video feeds **134**. Each communications session may be displayed on the user interface **1102** until its status is changed to completed by a dispatcher/call-taker. In some examples, the status of connections being handled by the CAEM **146** may automatically be set to complete by the CAEM **146** upon completion of handling the connection. Changing the status to complete may cause the connection to be dropped from the display.

For example, the user interface **1102** of the CAP system **144** may be configured to display pertinent information such as the event priority **104** of the emergency events **102**, the event type **106** of the emergency events **102**, and the event details **108** of the emergency event **102**.

The user interface **1102** of the CAP system **144** may be further configured to display additional information related to the handling of the event, such as a time at which the emergency event **102** was received, an elapsed time the caller has been connected, a status indicative of whether the call has been handled and, if so, how (e.g., whether the caller is currently on hold or is communication with dispatch according to voice or text messaging), and whether the emergency event **102** is being handled by a dispatcher/call-taker or automatically by the CAEM **146**.

The user interface **1102** of the CAP system **144** may be further configured to display additional information about the emergency event **102**, such as a name of the caller (e.g., retrieved according to the ANI/ALI system **136** or a predetermined information supplemented according to a rule), a phone number of the caller, an address or location of the caller (e.g., retrieved according to ALI or GPS), as well as supplementary details of the emergency event **102**, such as additional caller information retrieved from an ACI database **138** in communication with an ACI server **140**.

15

The user interface **1102** may accordingly be used to provide an overall status of the emergency events **102** being handled by the CAD system **112**. The combination of the user interface **1102** of the CAP system and the CAD system **112** may enable dispatch centers to respond to emergency requests in the most expeditious manner. For example, the user interface **1102** may allow a dispatcher to identify a set of multiple reported emergencies that all relate to a single underlying incident based on the displayed information. Accordingly the user interface **1102** information of the CAP system may reduce response time and increase the operational efficiency of each dispatch center.

FIG. 12 illustrates an exemplary process **1200** for receiving and processing an emergency event **102** according to an identified event priority **104** and event type **106**. The process **1200** may be performed by various devices, such as by the CAP system **144** in communication with one or more event reporters over a communications network **120**.

In block **1205**, the CAP system **144** receives an emergency event **102**. The emergency event may include an event priority **104** and an event type **106**. The event reporter may include reporters such as a smartphone **116** executing an EPD application **118**, and may be generated by user interaction with a user interface of the EPD application **118** such as described above. The event reporter may also include a phone device **122**, a burglar alarm **124**, a fire alarm **126**, a car alarm **128**, a medical alert device **130**, a telematics unit **132**, or a video feed **134**. In some cases, the emergency event **102** may be generated automatically based on the emergency event **102** being detected by the event reporter, such as the fire alarm **126** detecting a fire and sending an emergency event **102** with an event priority **104** of high and an event type **106** of fire emergency. In some cases, while waiting for a connection to be established between the event reporter and the CAP system **144** (such as via CAMA), the EPD application **118** may prompt the caller for one or more of event priority **104** and event type **106** to include in the emergency event **102**.

In block **1210**, the CAP system **144** supplements the emergency event **102** information. For example, the supplementation of the emergency event **102** may be performed according to one or more of the data flows **200-A** and **200-B** discussed in detail above with respect to FIGS. 2A and 2B.

In block **1215**, the CAP system **144** identifies the event priority **104** and the event type **106** of the emergency event **102**. This identification may be performed without querying the event reporter for additional event priority **104** and event type **106** information. Rather, the event priority **104** and the event type **106** information may be identified from the emergency event **102**.

In block **1220**, the CAP system **144** determines based on the emergency event **102**, whether the emergency event **102** indicates a higher event priority **104** emergency event **102** to be handled by the CAD system **112** or a lower priority emergency event **102** to be handled automatically by the CAEM **146**. If the emergency event **102** is determined to be of a higher event priority **104**, control passes to block **1225**. Otherwise, control passes to block **1235**.

In block **1225**, the CAP system **144** routes the emergency event **102** to the CAD system **112** for processing. Accordingly, the CAD system **112** may be configured to handle higher-priority emergency event **102** by way of a dispatcher/call-taker at the CAD system **112**.

In block **1230**, the CAP system **144** provides the emergency event **102** information to the dispatcher/call-taker. For example, the CAD system **112** may establish a communications session between a dispatcher/call-taker of the CAD system **112** and the reporting device (e.g., the smartphone **116**

16

executing the EPD application **118**), and may facilitate handling of the emergency event **102** via the dispatcher/call-taker. Rather than having to retrieve the event priority **104** and event type **106** from the caller, the dispatcher/call-taker may instead have the easier task of confirming the information already provided by the emergency event **102**, and of receiving any additional information from the caller.

In block **1235** the CAP system **144** routes the emergency event **102** to the CAEM **146** for processing. Accordingly, the CAEM **146** may be configured to automatically handle lower-priority emergency event **102**, without requiring the use of a dispatcher/call-taker at the CAD system **112**.

In block **1240**, the CAEM **146** automatically responds to the emergency event **102**. For example, the CAEM **146** may be configured to return a message to the user indicating that the emergency event **102** was received and will be processed. The CAEM **146** may also be configured to request additional information from the reporter of the emergency event **102**.

In block **1245**, the CAP system **144** updates the dispatch user interface. For example, emergency event **102** information in a display such as the user interface **1102** may be updated with the current status of the emergency event **102** being handled. After block **1245** the process **1200** ends.

With regard to the processes, systems, methods, heuristics, etc. described herein, it should be understood that, although the steps of such processes, etc. have been described as occurring according to a certain ordered sequence, such processes could be practiced with the described steps performed in an order other than the order described herein. It further should be understood that certain steps could be performed simultaneously, that other steps could be added, or that certain steps described herein could be omitted. In other words, the descriptions of processes herein are provided for the purpose of illustrating certain embodiments, and should in no way be construed so as to limit the claims.

In general, computing systems and/or devices, such as smartphone **116**, may employ any of a number of computer operating systems, including, but by no means limited to, versions and/or varieties of the Microsoft Windows® operating system, the Unix operating system (e.g., the Solaris® operating system distributed by Oracle Corporation of Redwood Shores, Calif.), the AIX UNIX operating system distributed by International Business Machines of Armonk, N.Y., the Linux operating system, the Mac OS X and iOS operating systems distributed by Apple Inc. of Cupertino, Calif., the BlackBerry OS distributed by Research In Motion of Waterloo, Canada, and the Android operating system developed by the Open Handset Alliance.

Computing devices such as smartphone **116** generally include computer-executable instructions, where the instructions may be executable by one or more computing devices such as those listed above. Computer-executable instructions may be compiled or interpreted from computer programs created using a variety of programming languages and/or technologies, including, without limitation, and either alone or in combination, Java™, C, C++, Visual Basic, JavaScript, Perl, etc. In general, a processor or microprocessor receives instructions, e.g., from a memory, a computer-readable medium, etc., and executes these instructions, thereby performing one or more processes, including one or more of the processes described herein. Such instructions and other data may be stored and transmitted using a variety of computer-readable media.

A computer-readable medium (also referred to as a processor-readable medium) includes any non-transitory (e.g., tangible) medium that participates in providing data (e.g., instructions) that may be read by a computer (e.g., by a

processor of a computer). Such a medium may take many forms, including, but not limited to, non-volatile media and volatile media. Non-volatile media may include, for example, optical or magnetic disks and other persistent memory. Volatile media may include, for example, dynamic random access memory (DRAM), which typically constitutes a main memory. Such instructions may be transmitted by one or more transmission media, including coaxial cables, copper wire and fiber optics, including the wires that comprise a system bus coupled to a processor of a computer. Common forms of computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, any other magnetic medium, a CD-ROM, DVD, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, a RAM, a PROM, an EPROM, a FLASH-EEPROM, any other memory chip or cartridge, or any other medium from which a computer can read.

Databases, data repositories or other data stores described herein may include various kinds of mechanisms for storing, accessing, and retrieving various kinds of data, including a hierarchical database, a set of files in a file system, an application database in a proprietary format, a relational database management system (RDBMS), etc. Each such data store is generally included within a computing device employing a computer operating system such as one of those mentioned above, and are accessed via a network in any one or more of a variety of manners. A file system may be accessible from a computer operating system, and may include files stored in various formats. An RDBMS generally employs the Structured Query Language (SQL) in addition to a language for creating, storing, editing, and executing stored procedures, such as the PL/SQL language mentioned above.

In some examples, system elements may be implemented as computer-readable instructions (e.g., software) on one or more computing devices (e.g., servers, personal computers, etc.), stored on computer readable media associated therewith (e.g., disks, memories, etc.). A computer program product may comprise such instructions stored on computer readable media for carrying out the functions described herein. The EPD application **118** may be one such computer program product. In some example, the EPD application **118** may be provided as software that when executed by the processor provides the operations described herein. Alternatively, the EPD application **118** may be provided as hardware or firmware, or combinations of software, hardware and/or firmware.

Accordingly, it is to be understood that the above description is intended to be illustrative and not restrictive. Many embodiments and applications other than the examples provided would be apparent upon reading the above description. The scope should be determined, not with reference to the above description, but should instead be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. It is anticipated and intended that future developments will occur in the technologies discussed herein, and that the disclosed systems and methods will be incorporated into such future embodiments. In sum, it should be understood that the application is capable of modification and variation.

All terms used in the claims are intended to be given their broadest reasonable constructions and their ordinary meanings as understood by those knowledgeable in the technologies described herein unless an explicit indication to the contrary is made herein. In particular, use of the singular articles such as "a," "the," "said," etc. should be read to recite one or more of the indicated elements unless a claim recites an explicit limitation to the contrary.

The Abstract of the Disclosure is provided to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in various embodiments for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed embodiments require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed embodiment. Thus the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separately claimed subject matter.

What is claimed is:

1. A system, comprising:

a computer aided prioritization (CAP) system in communication with a computer aided dispatch (CAD) system, a computer aided event module (CAEM), and an emergency event reporter device, the CAP system configured to:

receive, from the emergency event reporter device, an emergency event including a priority selected from a set of event priorities;

determine, based on the emergency event and without querying the emergency event reporter device for additional information, whether the emergency event indicates a higher priority emergency event to be handled by the CAD system or a lower priority emergency event to be handled automatically by the CAEM; and

selectively route the emergency event report to at least one of the computer aided dispatch (CAD) system and the computer aided event module (CAEM) according to the determination, wherein the computer aided prioritization (CAP) system further configured to:

receive an indication that the emergency event reporter device has changed location; and

identify an updated location reporter of the emergency event reporter device responsive to the indication that the emergency event reporter device has changed location.

2. The system of claim 1, the emergency event including a type of event selected from a set of event types associated with the selected event priority, the computer aided prioritization (CAP) system further configured to supplement information included in the emergency event according to a predetermined rule for including additional information based at least in part on the type of event.

3. The system of claim 2, the computer aided prioritization (CAP) system further configured to present the selected event priority, the type of event, and the additional information to the dispatcher associated with the computer aided dispatch (CAD) system before a communications session is established between a dispatcher of the CAD system and the emergency event reporter device.

4. The system of claim 2, the predetermined rule for including additional information in the emergency event report including at least one of:

(i) a rule making pre-entered emergency information available based on at least one of the selected event priority and the type of event;

(ii) a rule including telematics data in the emergency event report for events including a vehicle;

(iii) a rule including health information in the emergency event report for events requiring medical attention;

19

- (iv) a rule including additional contact information in the emergency event report for events requiring notification of emergency contacts;
- (v) a rule including floor-plan information for events requiring access to a building;
- (vi) a rule including picture or video information for events for which picture or video information is available; and
- (vii) a rule including vehicle information for events that involve vehicles.

5. The system of claim 4, the computer aided prioritization (CAP) system further configured to store the pre-entered emergency information on at least one of the emergency event reporter devices and a remote database in communication with the computer aided prioritization (CAP) system.

6. The system of claim 1, the computer aided prioritization (CAP) system further configured to:

present information associated with a plurality of emergency event reports in a graphical user interface, each event being identified at least according to the selected event priority and the type of event; and

indicate in the graphical user interface which events are being handled by a dispatcher associated with the CAP system, and which events are being handled by the computer aided event module (CAEM).

7. The system of claim 1, the computer aided prioritization (CAP) system further configured to receive at least one of automatic number identification (ANI) and automatic location information (ALI).

8. The system of claim 7, the computer aided prioritization (CAP) system further configured to supplement information included in the event report with additional information identified as associated with the event report based on at least one of the automatic number identification (ANI) and the automatic location information (ALI).

9. The system of claim 7, the computer aided prioritization (CAP) system further configured to present the selected event priority and the type of event to a dispatcher associated with the computer aided dispatch (CAD) system accompanied by at least one of the automatic number identification (ANI) and the automatic location information (ALI).

10. The system of claim 1, the computer aided prioritization (CAP) system further configured to:

determine whether additional information was included in the emergency event as submitted;

if the additional information was included in the emergency event, route the emergency event without additional supplementation; and

if the additional information was not included in the emergency event, supplement the information in the emergency event.

11. The system of claim 1, the set of event priorities including at least two of a high priority event indicative of a life-threatening event requiring urgent assistance, a medium priority event indicative of a non-life threatening event requiring urgent assistance, and a low priority event indicative of a non-life threatening event not requiring urgent assistance.

12. The system of claim 1, the set of event priorities including at least one of a third party priority event indicative of a report of information where a user of the emergency event reporter device is not involved, and an anonymous event priority indicative of a report of information where the user of the emergency event reporter device is not involved and wishes to remain anonymous.

13. The system of claim 1, the computer aided prioritization (CAP) system further configured to:

20

determine whether the emergency event reporter device is configured to support textual communication with a dispatcher associated with the emergency dispatch system; and

enable textual communication with the dispatcher associated with the computer aided dispatch (CAD) system according to the determination.

14. The system of claim 1, further comprising a third-party event interface in communication with the CAP system, wherein the emergency event is submitted via the third-party interface.

15. A method, comprising:

receiving, by a computer aided prioritization (CAP) system from an emergency event reporter device, an emergency event including a priority selected from a set of event priorities, the CAP system in communication with a computer aided dispatch (CAD) system, a computer aided event module (CAEM), and the emergency event reporter device;

determining, based on the emergency event and without querying the emergency event reporter device for additional information, whether the emergency event indicates a higher priority emergency event to be handled by the CAD system or a lower priority emergency event to be handled automatically by the CAEM; and

selectively routing the emergency event report to at least one of the computer aided dispatch (CAD) system and the computer aided event module (CAEM) according to the determination, wherein the computer aided prioritization (CAP) system further configured to:

receive an indication that the emergency event reporter device has changed location; and

identify an updated location reporter of the emergency event reporter device responsive to the indication that the emergency event reporter device has changed location.

16. The method of claim 15, the emergency event including a type of event selected from a set of event types associated with the selected event priority, and further comprising supplementing information included in the emergency event by the computer aided prioritization (CAP) system according to a predetermined rule for including additional information based at least in part on the type of event.

17. The method of claim 16, further comprising presenting, by the computer aided prioritization (CAP) system, the selected event priority, the type of event, and the additional information to the dispatcher associated with the computer aided dispatch (CAD) system before a communications session is established between a dispatcher of the computer aided dispatch (CAD) system and the emergency event reporter device.

18. The method of claim 16, the predetermined rule for including additional information in the emergency event report including at least one of:

(i) a rule making pre-entered emergency information available based on at least one of the selected event priority and the type of event;

(ii) a rule including telematics data in the emergency event report for events including a vehicle;

(iii) a rule including health information in the emergency event report for events requiring medical attention;

(iv) a rule including additional contact information in the emergency event report for events requiring notification of emergency contacts;

(v) a rule including floor-plan information for events requiring access to a building;

21

(vi) a rule including picture or video information for events for which picture or video information is available; and
(vii) a rule including vehicle information for events that involve vehicles.

19. The method of claim 15, further comprising:
presenting information associated with a plurality of emergency event reports in a graphical user interface, each event being identified at least according to the selected event priority and the type of event; and
indicating in the graphical user interface which events are being handled by a dispatcher associated with the computer aided prioritization (CAP) system, and which events are being handled by the computer aided event module (CAEM).

20. The method of claim 15, further comprising storing pre-entered emergency information on at least one of the emergency event reporter devices and a remote database in communication with the computer aided prioritization (CAP) system.

21. The method of claim 15, further comprising:
receiving at least one of automatic number identification (ANI) and automatic location information (ALI); and
supplementing information included in the event report with the additional information identified as associated with the event report based on at least one of the ANI and the ALI.

22. The method of claim 15, the set of event priorities including at least two of a high priority event indicative of a life-threatening event requiring urgent assistance, a medium priority event indicative of a non-life threatening event requiring urgent assistance, and a low priority event indicative of a non-life threatening event not requiring urgent assistance.

23. The method of claim 15, the set of event priorities including at least one of a third party priority event indicative of a report of information where a user of the emergency event reporter device is not involved, and an anonymous event

22

priority indicative of a report of information where the user of the emergency event reporter device is not involved and wishes to remain anonymous.

24. A non-transitory computer readable medium storing an application software program, the application being executable to provide operations comprising:

receiving, by a computer aided prioritization (CAP) system from an emergency event reporter device, an emergency event including a priority selected from a set of event priorities and a type of event selected from a set of event types associated with the selected event priority, the CAP system in communication with a computer aided dispatch (CAD) system, a computer aided event module (CAEM), and the emergency event reporter device;

supplementing information included in the emergency event by the CAP system according to a predetermined rule for including additional information based at least in part on the type of event;

determining, based on the emergency event and without querying the emergency event reporter device for additional information, whether the emergency event indicates a higher priority emergency event to be handled by the CAD system or a lower priority emergency event to be handled automatically by the CAEM; and

selectively routing the emergency event report to at least one of the computer aided dispatch (CAD) system and the computer aided event module (CAEM) according to the determination, wherein the computer aided prioritization (CAP) system further configured to:

receive an indication that the emergency event reporter device has changed location; and

identify an updated location reporter of the emergency event reporter device responsive to the indication that the emergency event reporter device has changed location.

* * * * *