US009082046B2

(12) **United States Patent**
Matraszek et al.

(10) **Patent No.: US 9,082,046 B2**
(45) **Date of Patent: Jul. 14, 2015**

(54) **METHOD FOR CREATING AND USING AFFECTIVE INFORMATION IN A DIGITAL IMAGING SYSTEM**

(71) Applicant: **Intellectual Ventures Fund 83 LLC**, Las Vegas, NV (US)

(72) Inventors: **Tomasz A. Matraszek**, Rochester, NY (US); **Elena A. Fedorovskaya**, Pittsford, NY (US); **Serguei Endrikhovski**, Sammamish, WA (US); **Kenneth A. Parulski**, Rochester, NY (US)

(73) Assignee: **Intellectual Ventures Fund 83 LLC**, Las Vegas, NV (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/087,186**

(22) Filed: **Nov. 22, 2013**

(65) **Prior Publication Data**

US 2014/0086498 A1 Mar. 27, 2014

Related U.S. Application Data

(60) Continuation of application No. 13/476,597, filed on May 21, 2012, now Pat. No. 8,630,496, which is a continuation of application No. 13/227,287, filed on Sep. 7, 2011, now Pat. No. 8,184,916, which is a continuation of application No. 12/541,224, filed on Aug. 14, 2009, now Pat. No. 8,036,467, which is a division of application No. 11/456,620, filed on Jul. 11, 2006, now Pat. No. 7,620,270, which is a continuation of application No. 10/036,113, filed on Dec. 26, 2001, now abandoned.

(51) **Int. Cl.**

G06K 9/62	(2006.01)
G06F 17/30	(2006.01)
G06T 5/00	(2006.01)

(52) **U.S. Cl.**
CPC ***G06K 9/6267*** (2013.01); ***G06F 17/30265*** (2013.01); ***G06T 5/00*** (2013.01)

(58) **Field of Classification Search**
USPC 382/224
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,019,975	A	5/1991	Mukai	
5,550,646	A	8/1996	Hassan et al.	
5,666,215	A	9/1997	Fredlund et al.	
5,731,844	A *	3/1998	Rauch et al.	725/40
5,760,917	A	6/1998	Sheridan	
5,802,220	A	9/1998	Black et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

EP	0 604 755	7/1994
JP	10-143680	5/1998

OTHER PUBLICATIONS

"Colorimetry for HDTV" by LeRoy DeMarsh, IEEE Transactions on Consumer Electronics, vol. 37, No. 1, Feb. 1991, pp. 1-6.

(Continued)

Primary Examiner — Gregory F Cunningham

(57) **ABSTRACT**

An image file for storing a still digital image and metadata related to the still digital image, the image file including digital image data representing the still digital image, and metadata that categorizes the still digital image as an important digital image, wherein the categorization uses a range of levels and the range of levels includes at least three different integer values.

24 Claims, 10 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

5,832,464	A	11/1998	Houvener et al.	
6,004,061	A	12/1999	Manico et al.	
6,154,772	A	11/2000	Dunn et al.	
6,182,133	B1	1/2001	Horvitz	
6,241,668	B1	6/2001	Herzog	
H0001997	H *	10/2001	Fleischer	702/5
6,462,778	B1	10/2002	Abram et al.	
6,629,104	B1	9/2003	Parulski et al.	
6,721,952	B1	4/2004	Guedalia et al.	
7,028,253	B1	4/2006	Lieberman et al.	
7,454,090	B2	11/2008	Wilcock et al.	
8,014,027	B1	9/2011	Kulkarni et al.	
2001/0022621	A1	9/2001	Squibbs	
2001/0041020	A1	11/2001	Shaffer et al.	
2001/0046330	A1	11/2001	Shaffer et al.	
2002/0008762	A1	1/2002	Takemoto	
2002/0013161	A1	1/2002	Schaeffer et al.	
2002/0049738	A1	4/2002	Epstein	
2002/0055955	A1	5/2002	Lloyd-Jones et al.	
2002/0097894	A1	7/2002	Staas et al.	
2003/0009469	A1	1/2003	Platt et al.	
2004/0246526	A1	12/2004	Ishigami et al.	
2005/0083352	A1	4/2005	Higgins	
2005/0149572	A1	7/2005	Kanai et al.	
2007/0150389	A1	6/2007	Aamodt et al.	
2007/0268378	A1	11/2007	Hsu	
2008/0094515	A1	4/2008	Gutta et al.	
2009/0067506	A1	3/2009	Doser	
2011/0214144	A1	9/2011	Girouard et al.	

OTHER PUBLICATIONS

"Digital Color Management" Encoding Solutions by Edward J. Giorgianni et al., pp. 61-69, 83-97 and 474-478, 1998.
"Digital Still Camera Image File Format Standard (Exchangeable image file format for digital still cameras: Exif)", Version 2.1, Jun. 12, 1998, 172 pages.
"Digital Video and HDTV Algorithms and Interfaces" by Charles Poynton, pp. 81-86 and 257-280, 2003.
"Emotion Recognition in Human-Computer Interaction", by R. Cowie et al., IEEE Signal Processing Magazine, vol. 18, No. 1, Jan. 2001, pp. 32-80.
"Facial Expression Recognition using a Dynamic Model and Motion Energy", by Irfan Essa et al. MIT Media Laboratory Perceptual Computing Section Technical Report No. 307, pp. 1-8. 1995.
"FotoFile: A Consumer Multimedia Organization and Retrieval System", by Allan Kuchinsky et al., Hewlett Packard Laboratories, 1501 Page Mill Road.about. Palo Alto, CA 94304 USA. 1999, 8 pages.
"Looking at Pictures: Affective, facial, visceral, and behavorial reactions", by Peter J. Lang et al, Psychophysiology, 30 (1993), 261-273.
"The Reproduction of Colour in Photography, Printing and Television", by Dr. R. W. G. Hunt, 1981 (8 pages, Title page and Table of Contents).
"The Sentic Mouse: Developing a tool for Measuring Emotional Valence", by Dana Kirsch, May 1997, 46 pages.
Communication from the European Patent Office on EP 02 080339.1, dated Jun. 27, 2006.
Dillon et al, Aroused and Immersed: The Psychophysiology of Presence, Goldsmiths College, University of London, 2000, 6 pages.
Final Office Action on U.S. Appl. No. 12/211,141, mailed Aug. 6, 2012.
Final Rejection on U.S. Appl. No. 12/541,224, mailed Dec. 10, 2010.
International Preliminary Report on Patentability for PCT/US2009/003793, issued Jan. 11, 2011.
International Search Report and Written Opinion for PCT/US2009/003793, mailed Oct. 1, 2009.
Matthew Anderson et al: "Proposal for a Standard Default Color Space for the Internet-SRGB", Final Program and Proceedings of the IS&T/SID Color Imaging Conference: Color Science, Systems, and Applications, XX, XX, Nov. 19, 1996, pp. 238-246.
Non-Final Office Action on U.S. Appl. No. 11/456,620, mailed Mar. 4, 2009.
Non-Final Office Action on U.S. Appl. No. 12/211,141, mailed Mar. 5, 2012.
Non-Final Office Action on U.S. Appl. No. 12/211,141, mailed May 17, 2013.
Non-Final Office Action on U.S. Appl. No. 12/541,224, mailed Jul. 26, 2010.
Non-Final Office Action on U.S. Appl. No. 13/476,597, mailed Jun. 14, 2013.
Non-Final Office Action on U.S. Appl. No. 12/541,233, mailed Mar. 19, 2010.
Notice of Allowance on U.S. Appl. No. 11/456,620, mailed Jul. 23, 2009.
Notice of Allowance on U.S. Appl. No. 12/211,141, mailed Sep. 19, 2013.
Notice of Allowance on U.S. Appl. No. 12/541,224, mailed Jun. 10, 2011.
Notice of Allowance on U.S. Appl. No. 12/541,233, mailed Oct. 29, 2010.
Notice of Allowance on U.S. Appl. No. 13/227,287, mailed Feb. 6, 2012.
Notice of Allowance on U.S. Appl. No. 13/476,597, mailed Mar. 21, 2013.
Notice of Allowance on U.S. Appl. No. 13/476,597, mailed Sep. 13, 2013.
R. W. Picard et al., Affective Intelligence—The Missing Link?, BT Technology Journal, vol. 14, No. 4, Oct. 1997.
R. W. Picard et al., Affective Wearables, IEEE Comput. Soc., Oct. 13, 1997, pp. 90-97.
R. W. Picard et al., Modeling User Subjectivity in Image Libraries, Proceedings Internation Conference on Image Processing, vol. 2, 1996, pp. 777-780.
R. W. Picard et al., Toward Machine Emotional Intelligence: Analysis of Affective Physiological State, IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 23 No. 10, Oct. 2001, pp. 1175-1191.
R. W. Picard, Affective Computing, Online, 1995.
R. W. Picard, Building HAL: Computers That Sense, Recognize, and Respond to Human Emotion, Proceedings of the SPIE—The International Society for Optical Engineering, vol. 4299, 2001, pp. 518-523.
Rob Roy, DVD From Hollywood Video Rentals, SSBN 0-7928-3366-X, Metro Goldwyn Mayer (MGM) @ 1995.
Search Report for EP application 02080339.1, dated Nov. 5, 2008.
"Smile, You're on Yahoo! Photos" Mar. 28, 2000 Release Detail, 1 page.
Final Office Action on U.S. Appl. No. 14/138,504, mailed Aug. 4, 2014.
Notice of Allowance on U.S. Appl. No. 14/138,504, mailed Oct. 14, 2014.
Non-Final Office Action on U.S. Appl. No. 14/138,504, mailed Mar. 19, 2014.

* cited by examiner


10
4
14
MONITOR
30
INTERNET SERVICE PROVIDER
22
MODEM
12
2
18
20
KEYBOARD
16
SCANNER
28
CD READER
26
24

FIG. 1


USER OPENS NEW SET OF DIGITAL IMAGE
110
APPLICATION IS LAUNCHED
112
USER ENTERS PERSONAL ID & PASSWORD
114
AUTOMATIC AFFECTIVE TAGGING ?
118
NO
YES
DISPLAY SELECTION OF POSSIBLE AFFECTIVE SIGNALS
120
USER SELECTS DESIRED AFFECTIVE SIGNALS
122
THUMBNAIL DISPLAY OF IMAGES
140
USER MANUALLY SELECTS IMAGES AND ENTERS AFFECTIVE INFORMATION
142
RETRIEVE FIRST IMAGE OF THE IMAGE SET
124
IMAGE IS DISPLAYED ON THE MONITOR
126
AUTOMATICALLY RECORD AFFECTIVE SIGNALS (E.G. VIEWING TIME, FACIAL EXPRESSION, PHYSIOLOGY)
128
USER CLICKS TO MOVE TO THE NEXT IMAGE
130
LAST IMAGE ?
132
NO
YES
RETRIEVE NEXT IMAGE
134
ANALYZE AFFECTIVE SIGNALS AND CREATE AFFECTIVE INFORMATION
136
PERSONAL AFFECTIVE TAGS ARE ASSOCIATED WITH IMAGES
146
PERSONAL AFFECTIVE TAGS USED TO RETRIEVE OR PRINT IMAGES
148

FIG. 2

THESE SIGNALS ARE GOING TO BE RECORDED FOR DETERMINING YOUR PSYCHOLOGICAL REACTION TO IMAGES

- [V] VIEWING TIME
- [V] FACIAL EXPRESSION / HEAD MOVEMENTS
- [V] PHYSIOLOGY
- [ ] AUDIO
- [ ] GAZE TRACKING
- [ ] TOUCH PRESSURE

FIG. 3A

THESE SIGNALS ARE GOING TO BE RECORDED FOR DETERMINING YOUR PSYCHOLOGICAL REACTION TO IMAGES

- [V] VIEWING TIME
- [V] FACIAL EXPRESSION / HEAD MOVEMENTS
- [V] PHYSIOLOGY
  - V HEART RATE
  - V GSR
  - V TEMPERATURE
  - EEG
- [ ] AUDIO
- [ ] GAZE TRACKING
- [ ] TOUCH PRESSURE

FIG. 3B

Personal Affective Tag field - PAT
Personal Identification field – PID_1
Affective Record Start field – BEGIN_RECORD_1
Date field – DATE
Location field – LOCATION
Affect field – AFFECT
Viewing time field – VIEWING_TIME
Physiology GSR field – GSR_SIGNAL
Physiology Temperature field – TEMP_SIGNAL
Ambient Temperature – AMBIENT_TEMP_SIGNAL
Physiology Heart Rate field – HR_SIGNAL
Face Expression field – FACE_EXPRESSION_DATA
Affective Record Start field – BEGIN_RECORD_2
Date field - DATE
Location field – LOCATION
Affect field – AFFECT
Viewing time field – VIEWING_TIME
Physiology GSR field – GSR_SIGNAL
Physiology Temperature field – TEMP_SIGNAL
Physiology Heart Rate field – HR_SIGNAL
Physiology EEG field – EEG_SIGNAL
Face Expression field – FACE_EXPRESSION_DATA
Gaze tracking field – GAZE_TRACKING_DATA
Behavior Record Start field – BEGIN_RECORD_3
Number of times viewed field – VIEWING_COUNTER
Number of times printed field – PRINTING_COUNTER
Number of times sent in e-mail field – E_MAIL_COUNTER

FIG. 4A

Personal Affective Tag 1
Personal Identification = User 1
Date = Aug 1, 2000
Importance = 8.....
Personal Affective Tag 2
Personal Identification = User 2
Date = July 4, 2001
Importance = 4.....
Personal Affective Tag 3
Personal Identification = User 1
Date = Oct 8, 2001
Importance = -5.....

FIG. 4B


Capture device make / model
Capture date
Capture lens settings
.....
Personal Affective Tag 1
Personal Identification
Affective Record
Optional Affective signal
.....
Optional Behavior Record
.....
Personal Affective Tag n
Personal Identification
Affective Record
Optional Affective signal
.....
Optional Behavior Record
IMAGE DATA
Capture Device Metadata
Affective Metadata
Image Metadata

FIG. 4C


USER INITIATES IMAGE RETRIEVAL AND UTILIZATION PROCESS
149
THUMBNAIL DISPLAY OF IMAGES, ORDERED ACCORDING TO "IMPORTANCE" RATING
150
CHANGE
152
YES
NO
MANUAL VERIFICATION
154
SELECTION OF SERVICES AND APPLICATIONS
156
CREATE ALBUM PAGES
158
UPLOAD IMAGES TO INTERNET PHOTO SYSTEM
160
SEND FAVORITES
162
CREATE PICTURE MAP
164
ADD TAGGED IMAGE SET TO COLLECTION
166
DONE
170
YES
NO
END
172

FIG. 5


USER SPECIFIES NUMBER OF ALBUM PAGES AND SELECTS IMAGES FOR EACH PAGE
305
SYSTEM CREATES AUTOMATICALLY ALBUM PAGES USING SELECTED IMAGES
310
312
CHANGE ?
NO
YES
314
USER CHANGES NUMBER OF PAGES
318
USER CHANGES LAYOUT OF SELECTED PAGE
322
USER SELECTS DIFFERENT IMAGES FOR SELECTED PAGE
USER CHANGES NUMBER OF IMAGES ON SELECTED PAGE
316
USER CHANGES IMAGES SIZE
320
324
YES
CHANGE ?
NO
326
YES
DESKTOP PRINTING
NO
330
USER PRINTS ALBUM PAGES LOCALLY
328
USER PRINTS ALBUM PAGES THROUGH SERVICE PROVIDER
END
332

FIG. 6


P2
P3
P1
P5
P4

FIG. 7A


P5
P4
P3
P6
P2
P1
P7
VACATION IN ARIZONA. SUMMER 2001

FIG. 7B


37
PDAs
30A
10A
HOME COMPUTOR
32
MODEM
10B
34
INTERNET SERVICE PROVIDER
39
10C
COMPUTERS/ ROUTERS
10D
ELECTRONIC PICTURE FRAME DEVICES
RETAIL KIOSKS
38
36
CHANNEL
30C
30B
40
SERVICE PROVIDER
BILL ISSUING
48
46
44
42
BILLING SYSTEM
ELECTRONIC DATABASE
INTERNET SERVER
52
PRODUCTION CONTROLLER
70
SHIPPING SYSTEM
72
54
56
SHIPPING LABEL PRINTER
HARD COPY PRINTER
ALBUM PAGES
SHIPPING LABEL
74
PRINTS
50

FIG. 8


CUSTOMER LOGS ONTO PHOTO SERVICE PROVIDE
510
CUSTOMER ENTERS PERSONAL ID & PASSWORD
512
CUSTOMER SELECTS WHOSE FAVORITES TO VIEW
514
CUSTOMER BROWSES AND SELECTS EVENT OR EVENTS FROM TAGGED COLLECTION OF IMAGES
516
THUMNAIL DISPLAY OF FAVORITES
518
520
CHANGE
YES
NO
522
CUSTOMER SELECTS FAVORITES
524
CUSTOMER SELECTS PRODUCT AND DESIGNEE
526
532
SELECT ALBUM PAGES
SELECT CALENDAR
SELECT MONTAGE POSTER
SELECT PICTURE MAP
528
530
540
NO
DONE
YES
542
USE PERSONAL AFFECTIVE INFORMATION TO FEATURE MOST FAVORITE IMAGES
PRODUCE AND SHIP PHOTO PRODUCT, BILL CUSTOMER
546

FIG. 9

METHOD FOR CREATING AND USING AFFECTIVE INFORMATION IN A DIGITAL IMAGING SYSTEM

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

This application is a Continuation of U.S. application Ser. No. 13/476,597, filed May 21, 2012, which is a Continuation of U.S. application Ser. No. 13/227,287, filed Sep. 7, 2011 (now U.S. Pat. No. 8,184,916), which is a Continuation of U.S. application Ser. No. 12/541,224, filed Aug. 14, 2009 (now U.S. Pat. No. 8,036,467), which is a Divisional of U.S. application Ser. No. 11/456,620, filed Jul. 11, 2006 (now U.S. Pat. No. 7,620,270), which is a Continuation of U.S. application Ser. No. 10/036,113, filed Dec. 26, 2001, all of which are incorporated herein by reference in their entirety.

FIELD

The present disclosure relates to systems that retrieve digital images and, more particularly, to systems that retrieve digital images based upon affective information.

BACKGROUND

Digital images, from digital cameras or scanned photographic film, can be viewed, stored, retrieved, and printed using a home computer, or can be uploaded to a web site for viewing, as described in commonly assigned U.S. Pat. No. 5,666,215 to Fredlund et al., the disclosure of which is incorporated herein by reference. Using a web browser, a group of these digital images can be viewed and selected for printing, for example using the Kodak Photonet Service. The user can select the size of each print to be produced, and the quantity of prints to be made from each image.

Images can be organized into categories according to the people, places, subjects or events depicted, as described in a paper entitled "FotoFile: A Consumer Multimedia Organization and Retrieval System" by Kuchinsky et al. This paper describes metadata attributes that are used to describe certain images, including a "favorite" attribute that is used to indicate the "best" images in a user's collection. However, in this paper, the "favorite" attribute can only be used to help retrieve one user's images on their own PC, since there is nothing in the "favorite" attribute to designate which user has indicated that this is a "favorite" image. If the PC is used by more that one user, the FotoFile system is unable to distinguish which user labeled the image as a "favorite". Furthermore, the favorite attribute is stored in a database separate from the digital image files. Therefore, when the digital image files are used on a different system, for example when the images are transferred via a CD-R or other media, or are uploaded to an on-line photo service provider, the favorite attribute information is no longer available.

Various types of metadata related to images have been standardized. For example, the International Organization for Standardization (ISO) group ISO/IEC JTC1/SC29/WG11, "Coding of Moving Pictures and Audio", has developed an"MPEG-7 Requirements Document" V.8, No. N2727, March 1999, which defines various types of metadata that can be stored with moving images. Also, the Digital Imaging Group (DIG) has developed the DIG35 metadata standard. However, neither of these specifications defines metadata, which indicates that an image is a favorite image for a particular user.

Album pages can be produced from digital images by arranging numerous images on the same page, as described in commonly assigned U.S. Pat. No. 6,004,061 to Manico et al., the disclosure of which is incorporated herein by reference. These album pages can be customized in terms of the size and arrangement of images on the page, the size and finish of the album pages, and the background color or patterns used. The method of organizing digital images on an album page is described in U.S. patent application Ser. No. 09/559,478, filed Apr. 27, 2000 by Simon, the disclosure of which is incorporated herein by reference. However, this method does not enable a user's favorite images to be automatically featured, for example by making them larger or more prominent, unless the user manually intervenes and manually adjusts their images.

SUMMARY

It is an object of the present disclosure to make use of affective information related to a user's reaction to an image to classify such image based upon such reaction.

This object is achieved by an image file for storing a still digital image and metadata related to the still digital image, the image file comprising:

a) digital image data representing the still digital image; and

b) metadata that categorizes the still digital image as an important digital image, wherein the categorization uses a range of levels and the range of levels includes at least three different integer values.

It is an advantage of the present invention to make use of affective information to classify a user's reaction to digital images.

It is an additional advantage of the present invention that a user's reaction can be manually input by the user, using a mouse, keypad, or speech recognition, or can be automatically determined by one or more determining how long a given image was viewed by the user, by the user's facial expression or gaze, or by measuring the user's physiology.

It is a further advantage of the present invention that affective information is associated with a user identifier which defines which user's reaction is provided by the affective information.

It is a further advantage of the present invention to associate affective information for multiple users with the same digital image.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** depicts a block diagram of a home computer system for creating affective information;

FIG. **2** is a flow diagram showing an embodiment of a system for creating affective information;

FIG. **3**A and FIG. **3**B depict a user interface for selecting signal recordings for creating affective information;

FIG. **4**A is an example of a personal affective tag for a single user;

FIG. **4**B is an example of affective metadata for multiple users with multiple personal affective tags;

FIG. **4**C depicts an image file including affective metadata;

FIG. **5** is a flow diagram of a typical method for using affective information in a digital imaging system;

FIG. **6** depicts a flow diagram for creating album pages;

FIG. **7**A depicts a customized album page produced using affective information;

FIG. **7**B depicts a picture map produced using affective information;

FIG. **8** depicts a block diagram of a networked digital system that uses affective information; and

FIG. **9** depicts a flow diagram for creating customized photo-products using a service provider for a designee.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present disclosure defines methods for determining affective information related to images, for storing affective information and user identifiers in association with digital images, and for using the affective information and user identifiers in retrieving digital images and in producing hardcopy output, such as album pages. The present invention associates the emotional reactions of different people to the same images. When used with networked photosystems, this enables people to share and to use images in more personal ways. By storing affective information and user identifiers in a standard manner, it is possible to automatically create imaging products, such as album pages, which have been personalized using the affective information for a particular user.

Affective information is defined in this patent as information that relates to the feelings or emotions of a person toward images. This information usually describes or represents a person's subjective reaction to a given image. The image could be a still image, or a moving image such as a video clip. Affective information can indicate the level of importance a user associates with an image, such as whether the image is a "favorite". For example, a user may take dozens of photographs during an event, such as a wedding or Christmas celebration. Out of these many images, there a normally a few that the user feels are special favorites. Affective information can also include emotional categories, such as fear, anger, happiness, etc.

A simple example of affective information is a "tag" or "flag", associated with an image, which indicates whether or not the image has been identified as a "favorite" or "important" image for the user. The absence of such a tag indicates that the image has not been identified as a favorite or important image for the user. Such tag represents a binary categorization, classifying images into "favorite" and "normal" categories. In another example, favorite images are categorized into a range of levels. For example, images can be classified between a range of −10 to +10, where 0 is used for an unclassified image, +10 is used for the "most favorite" image or images, and −10 is used for the "least favorite" image or images.

The present invention recognizes that different users have different emotional reactions to the same image. Therefore, to be useful, affective information relating to images must be associated with a particular user. This can be done by providing a user identifier along with the affective information. The user identifier can be any type of information that enables a particular user to be identified. The user identifier can be a personal identification code such as a globally unique ID (GUID), user number, social security number, or the like. The user identifier can also be a complete legal name, a nickname, a computer user name, or the like. The user identifier can alternatively include information such as a facial image or description, fingerprint image or description, retina scan, or the like.

The present invention recognizes that a user's emotional reaction to a particular image can change over time. For example, a user may have a favorite photo of one of their adult children and their spouse, taken at a family gathering. Sometime later, the couple may divorce. At this later time, the image is no longer the same type of favorite photo, providing the user with happy memories. Instead, it may now be a "disliked" photo, which makes the user sad or angry. Therefore, in some embodiments of the present invention, a date or time period is associated with the affective information. In addition, affective information for the same user, provided at different dates or time periods, can be associated with the image. This history of a user's reaction to a given image also enables analysis of changes in person's reaction that can be used for therapeutic, diagnosis or retrospective purposes.

Affective information can be manually entered by a user, for example using a mouse, keyboard, or voice recognition, or can be collected automatically.

The following are examples of methods for automatically collecting affective information:

the viewing time of the image, since a longer viewing time normally indicates that this is an important image;

other behavioral/usage information related to the usage of this image, such as how many times the image was printed or sent to others via e-mail;

the facial expression of the user, which can be captured automatically by a video camera as the user views the image;

body gestures recorded by a video camera as the user views the image;

the user's eye movements, such as the gaze path of the user while viewing the image;

the user's voice, recorded while viewing the image;

the pressure of the user's hand on the input device (e.g. joystick or mouse) recorded while viewing the image; and

the user's biometric or physiological responses recorded as the user views the image. These can be any combination of signals, including EMG, temperature, GSR, heart rate, brain waves EEG, brain-imaging signals, etc.

The following are examples of methods for a user to manually provide affective information:

- having the user "click" a mouse on an icon representing a "favorite image" tag;
- having the user type in a keyword, or select a keyword from a group of keywords, describing a subjective reaction (e.g. funny, sad, etc.) to an image; and
- having the user annotate the image with a voice recording (e.g. with phrases like "This is my favorite image").

Affective information is typically determined, either manually or automatically, as a user views images in their home, for example on their home computer. Affective tagging is defined as the process of determining affective information, and storing the affective information in association with the images. When the affective information is stored in association with a user identifier, it is known as "personal affective information". The affective information and user identifier are types of image "metadata", which is a term used for any information relating to an image. Examples of other types of image metadata include image capture time, capture device, capture location, date of capture, image capture parameters, image editing history, etc.

The personal affective information can be associated with a digital image by storing the personal affective information within the image file, for example using a TIFF IFD within an Exif image file. Alternatively, the personal affective information can be stored in a separate database. In some embodiments, this information is stored along with security and access permissions information, to prevent unauthorized access to the information.

Referring to FIG. **1**, there is illustrated a desktop computer system made in accordance with the present invention for providing personal affective information, associating it with image(s) as image metadata, and storing the images and the associated personal affective information. The personal

affective information is then used to provide improved image retrieval, and to provide customized photoproducts.

The system depicted in FIG. **1** includes a home computer **10** (with associated peripherals) located at the user location (e.g. their home). It is understood that a system such as a game console, dedicated Internet appliance, set top box, or retail kiosk may be substituted for the home computer system **10**. The home computer **10** is connected through a modem **22** or other communications interface to a communication service provider, such as an Internet service provider **30**. The home computer **10** includes a CPU motherboard **12**, a display monitor **14**, and a hard drive storage device **20** that can store high resolution image files such as digital still or digital motion images and associated metadata. The metadata includes personal affective information as well as other metadata, for example audio information associated with particular images.

The home computer includes various image input peripherals, including a scanner **28**, a CD reader **26**, and a digital camera **24**. The scanner **28** is used to scan prints or film and produce digital images. The CD reader **26** is used to input digital images from a CD-R disc, such as a Kodak PictureCD (not shown). The user can also download images from a Service Provider using the modem **22**. The home computer **10** can also connect to a local printer (not shown), such as an inkjet printer, to allow images to be printed at the user's home.

The digital camera **24** can be a digital still camera such as the Kodak DC 4800 digital camera manufactured by Eastman Kodak Company, Rochester N.Y. Alternatively, the digital camera **24** can be a digital motion camera such as the Kodak MC3 portable multimedia device, which records motion and sound video files, in addition to still images. The digital camera **24** connects to the home computer **10** via a cable employing a common interface, such as the well-known Universal Serial Bus (USB) interface or the IEEE 1394 interface. Alternatively, digital camera **24** can connect to the home computer **10** using a wireless interface, such as the well-known Bluetooth interface or the IEEE Standard 802.15 interface. Alternatively, the images can be transferred from the digital camera **24** to the home computer **10** using a removable memory card, such as a CompactFlash card and a card reader (not shown).

In order to provide affective information, the home computer **10** is connected to a keyboard **16** and a pointing device **18**, such as a mouse or trackball. In a preferred embodiment, the pointing device **18** also includes sensors that can detect the user's physiological signals, including the GSR (Galvanic Skin Response), hand temperature and heart rate. The sensors also detect ambient temperature.

The home computer **10** is optionally connected to video camera **4**. The video camera captures video images of the face of the user **2**, and stores this video information on the hard drive storage **20**. The video camera **4** can be, for example, a DV325 tethered camera sold by Eastman Kodak Company. The camera connects to the home computer **10** via a cable employing a common interface, such as the Universal Serial Bus (USB) interface.

The home computer **10** is provided with appropriate software for creating and using personalized affective information in accordance with the present invention. This software is typically stored on hard drive **20**, and provided using a CD-ROM disc (not shown) which can be read by CD reader **26**, or can be provided on a floppy disk (not shown) which is loaded into the home computer **10** via a floppy disk drive (not shown). Alternatively, this software can be downloaded from the Internet via modem **22**.

The home computer **10** is connected to a network, such as the Internet, as shown in FIG. **8**. As depicted in FIG. **8**, many different home computers **10**A, **10**B, **10**C, and **10**D are connected to the Internet by various Internet service providers (ISPs) **30**A, **30**B, and **30**C. The ISPs provide a connection to a service provider **40**. The ISP **30**A-C includes banks of modems **32**, one of which is connected to communicate with the modem **22** of the user's computer **10**. The modem **32**, in turn, communicates with computers/routers **34** in order to provide a connection to the channel **36** using equipment and techniques well known to those skilled in the art.

The service provider **40** is connected to the channel **36**, such as the Internet, by a network server **42**, such as an Internet server, which is comprised of one or more computers and associated peripherals. The service provider **40** also includes an electronic database **44**. The electronic database **44** provides information describing numerous image bearing product options, including different print sizes, different output formats such as mugs and t-shirts, and printing a group of digital images onto album pages. The electronic database **44** can be contained on the same computer as the network server **42**, or can utilize a separate computer, or can be distributed over several computers at the same physical site, or at different sites.

As shown in FIG. **8**, the electronic database **44** is connected to production controller **52**. The production controller **52** controls one or more color hardcopy printers **54**, which can produce album pages **56** or separate hardcopy prints **58**, which are examples of photoproducts. The production controller **52** can optionally be connected to a transfer printer (not shown) for producing transfer prints that can be used to produce t-shirts, coffee mugs, etc. incorporating one or more images uploaded by the user. The production controller **52** also controls a shipping system **70**, which controls a shipping label printer **72** to produce a shipping label **74**. The shipping label **74** is attached to a shipping container (e.g., a cardboard box containing packing material) that contains and protects the photoproducts during shipment (e.g., via air express mail, ground carrier, etc.) to the customer or the customer's designee.

On a regular basis (e.g. monthly) or alternatively whenever a photoproduct is purchased by the user, the electronic database **44** communicates with a billing system **46** to verify that the payment identifier (e.g., credit card or debit card number) provided by the customer is valid, and to debit the account for any purchases made, or for any monthly service fees for providing services to the user, such as for storing user images and associated personal affective information. As shown in block **48**, the bill is issued. The customer's account that is debited can, of course, be located at a remote financial institution.

The service provider **40** is located at a second location, typically in another city, remote from the user's computer **10**. The various portions of the service provider **40** can be located in a single building or complex of adjacent buildings, or can be geographically dispersed over several sites in different cities or even different continents. For example, the electronic database **44** and the album production controller **52** can be provided by computers located in different cities and interconnected via a suitable digital communications network, such as the Internet. Furthermore, the electronic database **44** can itself be distributed over several computers in several different locations.

The electronic database **44** also provides long-term storage of the uploaded images and associated personal affective information. In this embodiment, stored images are accessible (e.g. viewable) via the Internet by authorized users, as

described, for example, in commonly assigned U.S. Pat. No. 5,760,917 to Sheridan, the disclosure of which is herein incorporated by reference.

The electronic database **44** includes information describing different features of the albums and other photoproducts that can be selected and customized by the customer at the remote location, using the customer's computer **10**. The electronic database **44** also includes information describing photoproduct options, for example album features such as providing various background colors or textures, page numbers, page captions, image captions, etc. The album pages can be bound in a cover, or can include holes to permit the pages to be inserted into a standard binder, such as a three-ring binder. These album feature options can be demonstrated via software programs, for example, JAVA applets, MPEG or QuickTime movies, or Shockwave files, which depict the functionality of features that the customer can choose.

In addition to home computers **10**A-**10**D, other types of devices can be used to provide or access images via channel **36**. These devices include Wireless PDA devices **37**, retail kiosks **38**, and electronic picture frame devices **39**, all of which can be used to retrieve images and associated affective information from database **44** through channel **36** via one of the ISPs **30**A-C.

Referring to FIG. **2**, there is shown a flow diagram illustrating embodiments of the present invention, implemented in the system described in relation to FIG. **1** and FIG. **8**. This embodiment includes both automatic and manual determination of affective information.

In block **110**, a user opens a new set of images by inserting the CD-ROM into the CD reader **26** of the home computer **10**. In a preferred embodiment, the CD-ROM also includes the software application that implements the method of FIG. **2**. In this case, the software is automatically installed as part of block **112**, if necessary, so that it can be used by CPU motherboard **12**.

In block **112**, the application which implements the method of the present invention is launched automatically, when the images are viewed for the first time by a user. Alternatively, the user can start the application manually and load a new set of images from the digital camera **24**, the scanner **28**, or from other image sources including the Internet.

In block **114**, the user enters their personal ID and password. Alternatively, this step can be provided automatically by the operating system of the home computer **10** when the user "logs on" to the computer. In an alternative embodiment, the video camera **4** is used in conjunction with face recognition software to automatically determine the user, and provide an appropriate user identifier, such as their name or personal identification code.

In block **118**, the home computer **10** asks the user whether the user wants to manually provide affective information, or instead have the system automatically provide affective tagging while the user views the images.

In block **120**, if the user selects automatic affective tagging, the home computer **10** provides a selection of signals that can be recorded in order to determine the user's emotional reaction as they view images. An example of a screen displayed on monitor **14** to enable this user selection is shown in FIG. **3**A. Three signals are marked as defaults: viewing time per image, the facial expression recorded by the video camera **4**, and physiological signals detected through sensors in pointing device **18**. Depending on the hardware configuration, other signals may be listed in the selection.

In block **122**, the user selects which signals are to be recorded in order to determine the affective information. In FIG. **3**B, there is shown an example of signals selected by the user, including viewing time, facial expression, and physiology. The physiological signals selected by the user include heart rate, hand temperature, and galvanic skin response (GSR).

In block **124**, the home computer **10** retrieves the first image from the CD-ROM (or other image source) and in block **126**, the home computer **10** displays the image on the monitor **14**.

In block **128**, the home computer **10** automatically records the signals that the user selected in block **122** (e.g. the viewing time, a video of the user's face, and physiological signals).

In block **130**, the user clicks the pointing device **18** to indicate that they want to move to the next image. Alternatively, the user can provide some other form of input, such as hitting a key on the keyboard **16**, providing an audio command which is input by a microphone (not shown), providing a gesture captured by video camera **4**, or using other input devices.

In block **132**, the home computer **10** determines if this is the last image of the image set.

In block **134**, if this is not the last image, the home computer **10** retrieves the next image of the image set and repeats blocks **126** through **132**.

In block **136**, if this is the last image, the home computer **10** analyzes the recorded affective signals in order to create affective information and creates affective tag. This step includes determining the degree of emotional importance of each image of the set, for the user **2**. In a preferred embodiment, the home computer **10** estimates the emotional positive importance of each image of the set based on the user's facial expression (e.g. smiling), viewing time, and skin conductance.

The home computer **10** can detect the facial expression recorded by the video camera **4** using well known facial expression detection algorithms. An example of one such algorithm is "Facial Expression Recognition using a Dynamic Model and Motion Energy" by Irfan A. Essa and Alex Pentland published in the Proceedings of the ICCV 95, Cambridge, Mass., June 1995. A detected smile is a positive facial expression.

In block **128**, the facial expression of the user **2** was recorded as the user viewed the set of images. Frames of the video signal from the video camera **4** are then processed using facial expression recognition software, and classified into at least two categories: positive and not positive. The positive category is assigned when the smile is detected on the user's face. The not positive category is assigned if a smile has not been detected on the user's face. Alternatively, the facial expression may be more classified into a broader range of categories, such as happiness, sadness, despair, disgust, love, etc. and further classified using a range of values for these categories, such as for example strongly positive, somewhat positive, neutral and somewhat negative, and strongly negative. As a result of facial recognition, images in the positive category are then considered to be a user's favorite images, while images in the not positive category are not considered to be the user's favorite images.

The longer the image viewing time, the higher probability of positive image importance for that particular image. In blocks **126**-**134**, the user views images, one at a time, on the monitor **14** and proceeds to the next image by clicking the mouse button. The time interval between two consecutive images is determined by a home computer **10** and recorded as an affective signal. The paper entitled "Looking at pictures: Affective, facial, visceral, and behavioral reactions", *Psychophysiology,* 30, pp. 261-273, 1993, by P. J. Lang, M. K. Greenwald, M. M. Bradley, and A. O. Hamm, reports that on

average, viewing time linearly correlates with the degree of the interest or attention an image elicits in an observer. This paper compares the viewing time with the degree of the interest for third party pictures. In the present invention, the viewing time information is assessed for one or more users, for first party images.

The relationship between viewing time and user interest is used by the home computer **10**, which interprets the viewing time as an indication of the user's interest toward an image, or as a degree of importance of the image. The relative degree of interest for a specific image is determined as the viewing time for this specific image divided (or normalized) by the maximum viewing time among all images of the set. This relative degree of interest is used by the home computer **10** to rank the images in the set in a systematic and continuous manner, as "important" or "favorite" images. The most favorite images are those that have higher relative degrees of interest for a specified user.

To ensure that the viewing time is not improperly judged as a result of user distraction, the video camera **4** can be used to ensure that the user **2** is directing their gaze towards the monitor **14**, and is not distracted by other tasks, or has even left the room.

Skin conductance is a magnitude of the electrical conductance of the skin that is measured as a response to viewing the image. This signal is recorded using a biometric sensor. A computer mouse that is able to detect and record skin conductance has been developed by IBM Corp. Skin conductance or galvanic skin response reflects a degree of interest toward the picture as described in a paper entitled "Looking at pictures: Affective, facial, visceral, and behavioral reactions", *Psychophysiology,* 30, pp. 261-273, 1993, by P. J. Lang, M. K. Greenwald, M. M. Bradley, and A. O. Hamm. The skin conductance changes depending on the arousal the image elicits in the viewer: the higher the skin conductance, the higher the arousal or excitement, and vice versa: the lower the skin conductance, the lower the arousal. Therefore, the measure of the amplitude of the skin conductance response which is the difference between skin conductance before an image onset and the extremum of the skin conductance developed within a few seconds after an image onset, can be used to determine the user's interest or attention to a certain image.

Based on the skin conductance recorded using the pointing device **18**, every image of the set is assigned a degree of interest. The value is a function of the magnitude of the skin conductance for the particular image, divided by the maximum skin conductance response recorded for the image set. The images in the set can be ranked as favorite images by using these values. The lower relative skin conductance, the more "favorite" the image is.

The three affective signals can be further combined to obtain an integral measure of positive interest. For every image in the set, the relative degrees of interest are obtained based on the viewing time (degree of interest via viewing time, DItime) and the skin conductance response (degree of interest via skin conductance response, DIskin_response) as described above. If an image was classified as positive based on the assessment of facial expression, the image is assigned a value of 1 for positive response (PR). If an image was classified as not positive, a value of 0 is assigned for positive response. Then a measure of positive interest (e.g. importance or "favoriteness") can be computed for every image using an appropriate function. One such function is a sum of all three measures:

$$\text{Positive Interest}=\text{DItime}+\text{DIskin_response}+\text{PR}.$$

Other appropriate functions include a weighted sum of these three measures, where the weights are determined based on the standard deviation within each of the normalized (divided by the maximum value) signals over the image set. In this case, the higher the standard deviation within the signal, the higher the weight of the contribution for the signal into the measure of positive interest. Consequently, the lower the standard deviation of a given signal, the lower the weight of the contribution for the corresponding signal into the measure of positive interest. The reason for this dependency stems from the assumption that a standard deviation of a particular measure reflects a degree of differentiation between the images along a given measure. This implies that the signal with the highest standard deviation has more differentiation power, and therefor is more important to consider while determining an integral measure of positive interest.

In block **140**, if the user selected manual affective tagging in block **118**, the images in the image set are displayed on the monitor **14** as small thumbnail images. In block **142**, the user manually selects images, which are favorites, and enters manually affective information (e.g. degree of positive importance/favorite) for the selected images. This may be done using the methods described in commonly assigned U.S. Pat. No. 6,629,104, the disclosure of which is incorporated herein by reference.

In block **146**, the affective information from block **136** or **142** is used to provide personal affective tags, which are associated with the corresponding images of the image set. The association can be accomplished by including the personal affective tags within each image file of the set or by providing the personal affective tags in a separate database, along with a name or pointer to the corresponding image associated with each tag. The database can be stored on hard drive **20**. The personal affective tag includes a user identifier, as described earlier in relation to block **114**.

An illustrative example of a personal affective tag is shown in FIG. **4**A. FIG. **4**A depicts a file data structure of a personal affective tag for a single user, which includes a personal identification field, two affective records captured at two different times, and one behavior record.

The personal affective tag field identifies the data structure in the file as containing personal affective tag data. A personal identification code is stored in the personal identification field. This field identifies the user, whose affective information is stored in this personal affective tag.

The affective records stores affective information directly related to a user's reaction to an image. This includes the date and the place the affective information was collected. The first affective record stores affective information captured at a first time and location specified in the first Location field and Time field, and the second affective record stores affective information captured at a second time and location specified in the second Location field and Time field. The affect field in the affective record stores the subjective reaction(s) determined when the image was viewed by the user identified by personal identification code stored in the personal identification field. In the simple embodiment, the affect field can store an "importance" or "favorite" ranking ranging from −10 to 10, where 10 means the most favorite and −10 means the least favorite. Alternatively, the affect field can include basic emotion (e.g. happy) with a corresponding ranking that quantifies the intensity of the detected emotion. The affect determination can be the result of automatic detection or a manual entry by the user, as described earlier in relation to FIG. **2**.

The minimum required information contained in a personal affective tag consists of the personal identification code stored in the corresponding field, and at least one subjective

reaction (affect) stored in the affect field. Other optional fields shown in FIG. **4**A include the time the affective information was collected, stored in the Time field. The personal affective tag can also contain other affective data related to the affective signals selected by the user in step **122**. These fields can include the viewing time field, physiology temperature field, physiology heart rate field, physiology EEG field, face expression field, the gaze tracking field, and the touch pressure field.

The behavior record stores information related to the usage of the image, including the number of times the image was viewed by the user, the number of times the image was printed by the user, and the number of times the image was sent by e-mail by the user.

Referring to FIG. **4**B, there is shown an example data structure of affective metadata for a single image, which provides personal affective information for multiple users. Personal affective tag **1** indicates that on Aug. 1, 2000, a first user (user **1**) provided affective information (either manually or automatically) which gave the associated image an importance rating of 8 (on a −10 to 10 scale). Personal affective tag **2** indicates that on Jul. 4, 2001, a different user (user **2**) provided affective information, which gave the same associated image an importance rating of 4. Personal affective tag **3** indicates that on Oct. 8, 2001, the first user (user **1**) provided affective information, which now gave the same associated image an importance rating of −5.

Referring to FIG. **4**C, there is shown an example of an image file, which contains image metadata and image data. The image file can be a JPEG image files, such as an Exif/JPEG file, a TIFF file, a JPEG 2000 image file, or can utilize many other image file formats. The image metadata includes well known capture device metadata. This capture device metadata can include the make of the digital capture device that provided the image, for example the make of the digital camera. It can also include the image capture date and capture device settings, such as the camera lens focal length, f-number, etc. In accordance with a preferred embodiment of the present invention, the image metadata includes one or more personal affective tags. Each personal affective tag includes a user identifier stored in a personal identification field, and at least one Affective Record, such as an importance rating. A single image file can include a plurality of affective tags for a plurality of different users.

In block **148** of FIG. **2**, the personal affective tags are used to retrieve or print images. Referring to FIG. **5**, there is shown a flow diagram of an exemplary embodiment of the present invention of a retrieval system on the home computer **10**. In this embodiment, the personal affective information is used to assist in the image retrieval process, and is used to improve the process of providing photoproducts, such as album pages, which utilize the set of images described earlier in relation to block **110**. It will be understood that the image retrieval can be done immediately after the personal affective information is created, or at a later time. It will also be understood that prior to image retrieval, other users may have provided affective information for the same set of images, so that each image has associated affective information for a plurality of users. If the image retrieval is done at a later time, the user is asked to enter their personal ID and password, as described earlier in relation to block **112**. This is done so that the appropriate user identifier can be used to retrieve the appropriate personal affective information for the user.

In block **149** of FIG. **5**, the retrieval user initiates the image retrieval and utilization process, by selecting, using the pointing device **18**, an appropriate menu item (such as a menu item named "retrieve images") displayed on monitor **14**.

In block **150**, the home computer **10** provides a thumbnail display of the set of images on the monitor **14**. The thumbnails are ordered according to "importance" rating of the images for the particular user. The higher rated images are displayed first, and the lowest rated images are displayed last. The rating can also be displayed alongside each associated image. As a result, the user's personal affective information is used to determine the order of presentation of the retrieved images.

In block **152**, the user is asked if they want to change the ratings. If the user responses in the affirmative, in block **154** the user can manually adjust the rating. The home computer **10** stores new personal affective information for the user, for each image whose rating is manually adjusted.

In block **156**, the user selects one or more services and applications of interest. These can include creating customized album pages (block **158**), uploading images or album pages to the service provider **40** for printing (block **160**), sending favorite images by e-mail (block **162**), creating a picture map (block **164**), and adding the image set (including the associated personal affective tags) to a user's collection on the local hard drive **20**, or on a remote server (step **166**), for sharing with family and friends via the Internet.

In block **170**, the user is asked if they are done, or if they want to select additional services or products. In block **172**, the process ends.

FIG. **6** is a flow diagram of an exemplary embodiment of the present invention of a system for creating album pages that uses affective information. Affective information can be used by the system to create album pages in the following ways:

to retrieve favorite images to be included on album pages;

to position most favorite images in the center of the page;

to resize most favorite images to be bigger than other images on the page; and

to change the background surround the most favorite images to emphasize their importance (e.g. providing a bold framing feature).

The flow diagram in FIG. **6** describes in more detail the process of creating album pages, which is block **158** in FIG. **5**. In block **305** of FIG. **6**, the user specifies the number of album pages, and selects images for each album page. In an alternative embodiment, the system can automatically select images for each page by using the capture date information, stored in image metadata, and the number of pages specified by the user, to group the images on pages according to the date.

In block **310**, the system automatically creates the specified number of album pages from the selected images. In a preferred embodiment of the present invention, the images are automatically organized into album pages using emphasis images, as described in commonly assigned U.S. patent application Ser. No. 09/559,478, filed Apr. 27, 2000 by Simon, the disclosure of which is incorporated herein by reference. In the present invention, the most favorite images are automatically identified as emphasis images. As described in the Simon et al. patent, the emphasis image is located in the center of the page and is larger than other images on the page. This method of emphasizing the most important images can be repeated for each album page, to create specified number of album pages.

After the album pages are automatically arranged, in block **310**, the user is asked whether they want to modify the arrangement, in block **312**. The user can then change the number of pages (block **314**), the number of images on a selected page (block **316**), the layout of the selected page (block **318**), and the size of images on the page (block **320**). The user can also select different images to include on the

pages (block **322**). When the user is satisfied with the appearance of the album pages (block **324**), then user then decides (block **326**) whether to print the album pages locally (block **330**) or to instead order printed album pages from the service provider **40** (block **328**). The album pages can be produced using the methods described in commonly assigned U.S. Pat. No. 6,004,061 to Manico et al., the disclosure of which is herein incorporated by reference. The process ends at block **332**.

Referring to FIG. **7**A, there is shown an example of a created album page. Five images (P**1**-P**5**) are formatted and put on the album page by the home computer **10**, or by the service provider **40**. When the system automatically creates an album page, the most favorite image is featured. This can be done by positioning this most favorite image in the center of the page (image P**1**). This can also be done by formatting the most favorite image (P**1**) so that this image is larger in size than the other images on the page. This can also be done by providing a background frame, or another type of background surround, that draws attention to this particular image. In addition, image attributes of the most favorite image can be modified to emphasize its importance. For example, this image can be processed to increase its sharpness, color saturation, etc.

The most favorite image is automatically selected from the set of images assigned for the album page, based on the personal affective information associated with images for the particular user. If a second user, having different personal affective information, were to request an album page including the same set of images, it is likely that a different image would be featured, since a different image is likely to be the most favorite image for that second user. Thus, album page layout is automatically customized for the particular user, based on the personal affective information for that user.

Referring to FIG. **7**B, there is shown an example of a picture map created in block **166** of FIG. **5**. In this example, seven images (P**1**-P**7**) are formatted and put on the picture map. In one exemplary embodiment, the system can automatically select an appropriate map based on geographic location information stored as metadata associated with the images. Such metadata can be created automatically at capture time (e.g. by the digital cameras with GPS-Global Positioning System) or manually by the user. For each different location specified by the metadata, the system selects the most favorite image captured in that location and places it in the proper place on the map. The most favorite images are automatically selected by the system based on the personal affective information associated with the images. In FIG. **7**B, seven locations have been identified, and the seven most favorite images (P**1**-P**7**) corresponding to these locations have been selected and placed on the map.

Referring to FIG. **9**, there is shown a flow diagram of an exemplary embodiment of the present invention of using affective information to create customized photoproducts through a communications network, such as the Internet. In the present invention, customized photoproducts, such as album pages, are created based on personal affective information associated with the images.

In block **510**, the customer logs onto a web site provided by the photo service provider **40** (FIG. **8**). In general, the customer may not be the same person as the user who created the affective information in FIG. **2**. For example, this is the case when one family member creates personalized photoproducts for other family members or friends using their favorite images.

In block **512**, the customer enters their personal ID and password, as described earlier in relation to block **114** of FIG. **2**.

In block **514**, the customer selects whose favorite images they want to browse. The customer can choose to browse through their favorites, and/or through favorite images provide by their family members or friends. To browse through other people's favorite images, the customer must have access permission, as described in commonly assigned U.S. Pat. No. 5,760,917 to Sheridan, referenced earlier. These access permissions are created when images are uploaded and stored by a user in database **44**.

In block **516**, the customer browses through favorites by date and/or event and selects images of interest (e.g. by clicking on images to be selected). In block **518**, thumbnails of all selected images are displayed. In block **520** and **522**, the customer can modify their selection of images.

In block **524**, the customer selects one or more desired products, and the designee who is to receive the product. If the user has access permission for the designee, the service provider can automatically determine the user identifier for the designee, so that personal affective information for the designee can be used to customize the photoproduct to be order and shipped to that designee, for example as a gift.

Using the customer selected images, different customized photoproducts can be created. In block **526**, album pages can be selected. In block **528**, a customized calendar including customer selected images can be selected. In block **530**, a montage poster can be selected. This is a large poster containing a creative background and many different images. In block **532**, the customer can choose to create a picture map. In block **540**, the customer decides whether they are done selecting photoproducts, or want to select additional photoproducts.

In block **542**, the personal affective information for the designee is used to feature the most favorite images, as the photoproduct is organized. As described earlier in reference to FIG. **5**, when album pages, calendars, or montage posters are created, the personal affective information is used to select one or more particularly favorite images to be featured. These featured images are printed larger than the others are, and in more prominent locations in the photoproduct.

In block **546**, the photoproduct is produced and shipped to the customer's designee, and the customer is billed by the service provider.

A computer program product can include one or more storage medium, for example; magnetic storage media such as magnetic disk (such as a floppy disk) or magnetic tape; optical storage media such as optical disk, optical tape, or machine readable bar code; solid-state electronic storage devices such as random access memory (RAM), or read-only memory (ROM); or any other physical device or media employed to store a computer program having instructions for practicing a method according to the present invention.

The invention has been described in detail with particular reference to certain preferred embodiments thereof, but it will be understood that variations and modifications can be effected within the spirit and scope of the invention.

PARTS LIST

2 user
4 video camera
10A-D home computer systems
12 CPU motherboard
14 monitor
16 keyboard

18 pointing device with physiology sensors
20 hard drive
22 modem
24 digital camera
26 CD reader
28 scanner
30A-C Internet service provider
32 modems
34 computers/routers
36 channel
37 PDAs
38 retail kiosks
39 electronic picture frame device
40 service provider
42 Internet server
44 electronic database
46 billing system
48 bill issuing
52 production controller
54 hardcopy printers
56 album pages
70 shipping system
72 shipping label printer
74 shipping label
110 block
112 block
114 block
118 block
120 block
122 block
124 block
126 block
128 block
130 block
132 block
134 block
136 block
140 block
142 block
146 block
148 block
149 block
150 block
152 block
154 block
156 block
158 block
160 block
162 block
164 block
166 block
170 block
172 block
305 block
310 block
312 block
314 block
316 block
318 block
320 block
322 block
324 block
326 block
328 block
330 block
332 block
510 block
512 block
514 block
516 block
518 block
520 block
522 block
524 block
526 block
528 block
530 block
532 block
540 block
542 block
546 block

What is claimed is:

1. A method comprising:

receiving, by a computing device, a first digital image set including digital images having associated importance ratings for a user;

modifying, by the computing device, image attributes of one or more digital images in the first digital image set to enhance or change a viewed image for the one or more digital images; and

providing, by the computing device, the digital images from the first digital image set in order of the associated importance ratings, including the one or more digital images in the first digital image set having modified image attributes.

2. The method of claim **1**, wherein the importance ratings are each based on rating metadata associated with the digital images in the first digital image set.

3. The method of claim **2**, further comprising providing access to the digital images in the first digital image set.

4. The method of claim **2**, further comprising determining the rating metadata based on number of views of a particular digital image in the first digital image set.

5. The method of claim **2**, further comprising determining the rating metadata based on a viewing time of the user viewing a particular digital image in the first digital image set.

6. The method of claim **2**, further comprising determining the rating metadata based on a facial expression of the user viewing a particular digital image in the first digital image set.

7. The method of claim **1**, wherein the provided digital images include a thumbnail image.

8. A system comprising:

a processing system configured to:

receive a first digital image set including digital images having associated importance ratings for a user;

modify image attributes of one or more digital images in the first digital image set to enhance or change a viewed image for the one or more digital images; and

provide the first digital image set in order of the associated importance ratings, including the one or more digital images in the first digital image set having modified image attributes.

9. The system of claim **8**, wherein the importance ratings are each based on rating metadata associated with one or more digital images in the first digital image set.

10. The system of claim **9**, wherein the processing system is further configured to provide access to the digital images in the first digital image set.

11. The system of claim **9**, wherein the processing system is further configured to determine the rating metadata based on number of views of a particular digital image in the first digital image set.

12. The system of claim **9**, wherein the processing system is further configured to determine the rating metadata based

on a viewing time of the user viewing a particular digital image in the first digital image set.

13. The system of claim **8**, wherein the provided digital images include a thumbnail image.

14. A non-transitory computer readable medium having instructions stored thereon, the instructions comprising:

instructions to receive a first digital image set including digital images having associated importance ratings for a user;

instructions to modify image attributes of one or more digital images in the first digital image set to enhance or change a viewed image for the one or more digital images; and

instructions to provide the digital images from the first digital image set in order of the associated importance ratings, including the one or more digital images in the first digital image set having modified image attributes.

15. The computer readable medium of claim **14**, wherein the importance ratings are each based on rating metadata associated with one or more digital images in the first digital image set.

16. The computer readable medium of claim **15**, further comprising instructions to provide access to the digital images in the digital image set including the provided digital image.

17. The computer readable medium of claim **15**, further comprising instructions to determine the rating metadata based on number of views of a particular digital image in the first digital image set.

18. The computer readable medium of claim **15**, further comprising instructions to determine the rating metadata based on a viewing time of the user viewing a particular digital image in the first digital image set.

19. The computer readable medium of claim **15**, further comprising instructions to determine the rating metadata based on a facial expression of the user viewing a particular digital image in the first digital image set.

20. The method of claim **1**, further comprising maintaining a profile of the user, wherein the profile comprises a history of the importance ratings corresponding to the digital images of the first digital image set.

21. The method of claim **20**, wherein each importance rating associated with a digital image has an associated date or time period, and wherein the history of the importance ratings is based on each associated date or time period.

22. The method of claim **1**, wherein each importance rating associated with a digital image comprises a categorization of the associated digital image, and wherein the categorization designates the associated digital image as a favorite image or a normal image.

23. The method of claim **2**, wherein the rating metadata is determined based on a biometric or physiological response of the user viewing a particular digital image in the first digital image set.

24. The method of claim **23**, wherein the biometric or physiological response is based on at least one of an electromyography reading of the user, a temperature of the user, a galvanic skin response of the user, a heart rate of the user, an electroencephalography reading of the user, and a brain-imaging signal of the user.

* * * * *