



US009113953B2

(12) **United States Patent**
Smith

(10) **Patent No.:** **US 9,113,953 B2**

(45) **Date of Patent:** **Aug. 25, 2015**

(54) **TWO-MODE TROCAR ASSEMBLY**

(75) Inventor: **Robert C. Smith**, Middletown, CT (US)

(73) Assignee: **Covidien LP**, Mansfield, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 419 days.

(21) Appl. No.: **11/821,344**

(22) Filed: **Jun. 22, 2007**

(65) **Prior Publication Data**

US 2008/0009894 A1 Jan. 10, 2008

(51) **Int. Cl.**
A61B 17/34 (2006.01)

(52) **U.S. Cl.**
CPC **A61B 17/3496** (2013.01); **A61B 17/3417** (2013.01)

(58) **Field of Classification Search**
CPC A61B 17/3417; A61B 17/3496
USPC 606/185
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,535,773 A 8/1985 Yoon
4,601,710 A 7/1986 Moll

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 604 197 A2 12/1993
EP 0 617 924 A2 2/1994

(Continued)

OTHER PUBLICATIONS

European Search Report for corresponding EP 07252535 date of mailing is Feb. 26, 2009 (3 pages).


Primary Examiner — Kathleen Holwerda

Assistant Examiner — Sarah Simpson

(57) **ABSTRACT**

An obturator assembly for penetrating tissue and being at least partially positionable within a cannula assembly includes an obturator housing, an obturator shaft connected to the obturator housing and defining a longitudinal axis, a penetrating member adjacent the distal end of the obturator shaft and an obturator shield mounted about the obturator shaft and having a distal shield nose. The obturator shield is adapted for longitudinal movement between an extended position where the penetration member is substantially enclosed within the shield nose and a retracted position where the penetrating member is at least partially exposed from the shield nose. A manually manipulative member is mounted to the obturator housing and is adapted for rotational movement about the longitudinal axis and relative to the obturator housing between an initial position corresponding to a first mode of operation where the obturator shield is secured in the extended position and the shield nose is used to penetrate tissue, and a release position corresponding to a second mode of operation operatively releasing the obturator shield to permit the obturator shield to move to the retracted position thereof to expose the penetrating member for penetrating the tissue. The obturator assembly may further include a latch member disposed within the obturator housing. The preferred latch member is in operative engagement with the obturator shield to secure the obturator shield in the extended position thereof. The latch member is actuatable to release the obturator shield when the obturator housing is mated with the cannula assembly to thereby permit movement of the obturator shield toward the retracted position provided the manually manipulative member is in the release position. The obturator assembly further includes a release member which is mounted to the obturator housing and operatively coupled with the latch member. The release member is positioned to engage the cannula assembly upon mating of the obturator housing and the cannula assembly to thereby displace the release member and cause actuation of the latch member.

17 Claims, 11 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,654,030 A 3/1987 Moll et al.
 4,902,280 A 2/1990 Lander
 4,931,042 A 6/1990 Holmes et al.
 5,030,206 A 7/1991 Lander
 5,066,288 A 11/1991 Deniega et al.
 5,104,382 A 4/1992 Brinkerhoff et al.
 5,114,407 A 5/1992 Burbank
 5,116,353 A 5/1992 Green
 5,152,754 A 10/1992 Plyley et al.
 5,158,552 A 10/1992 Borgia et al.
 5,215,526 A 6/1993 Deniega et al.
 5,226,426 A 7/1993 Yoon
 5,246,425 A 9/1993 Hunsberger et al.
 5,248,298 A 9/1993 Bedi et al.
 5,263,937 A 11/1993 Shipp
 5,275,583 A 1/1994 Crainich
 5,290,243 A 3/1994 Chodorow et al.
 5,295,993 A 3/1994 Green
 5,312,354 A 5/1994 Allen et al.
 5,314,417 A 5/1994 Stephens et al.
 5,318,580 A 6/1994 Gresl, Jr.
 5,318,585 A 6/1994 Guy et al.
 5,338,305 A 8/1994 Plyley et al.
 5,346,459 A 9/1994 Allen
 5,350,393 A * 9/1994 Yoon 606/185
 5,356,421 A 10/1994 Castro
 5,364,365 A 11/1994 Wortrich
 5,364,372 A 11/1994 Danks et al.
 5,370,625 A 12/1994 Shichman
 5,387,197 A 2/1995 Smith et al.
 5,399,167 A 3/1995 Deniega
 5,411,515 A 5/1995 Haber et al.
 5,417,705 A 5/1995 Haber et al.
 5,431,635 A 7/1995 Yoon
 5,437,643 A 8/1995 Transue
 5,441,513 A 8/1995 Roth

5,462,532 A 10/1995 Gresl
 5,474,539 A 12/1995 Costa et al.
 5,486,190 A 1/1996 Green
 5,522,833 A 6/1996 Stephens et al.
 5,527,335 A 6/1996 Bolduc et al.
 5,538,509 A 7/1996 Dunlap et al.
 5,549,564 A 8/1996 Yoon
 5,578,053 A 11/1996 Yoon
 5,591,190 A 1/1997 Yoon
 5,626,598 A 5/1997 Roth
 5,645,556 A 7/1997 Yoon
 5,645,557 A 7/1997 Yoon
 5,669,885 A 9/1997 Smith
 5,674,237 A 10/1997 Ott
 5,676,156 A 10/1997 Yoon
 5,697,947 A 12/1997 Wolf et al.
 5,772,660 A 6/1998 Young et al.
 5,827,315 A 10/1998 Yoon
 5,851,216 A 12/1998 Allen
 5,860,996 A 1/1999 Urban et al.
 5,868,773 A 2/1999 Danks et al.
 5,904,699 A * 5/1999 Schwemberger et al. 606/185
 5,980,493 A 11/1999 Smith et al.
 5,984,941 A 11/1999 Wilson et al.
 6,017,356 A 1/2000 Frederick et al.
 6,036,711 A 3/2000 Mozdierz et al.
 6,063,099 A * 5/2000 Danks et al. 606/185
 6,099,544 A 8/2000 Wolf et al.
 6,238,407 B1 5/2001 Wolf et al.
 6,319,266 B1 * 11/2001 Stellan et al. 606/185
 2005/0119685 A1 * 6/2005 Smith 606/198

FOREIGN PATENT DOCUMENTS

EP 0769279 4/1997
 WO WO94/04206 3/1994
 WO WO 94/22508 3/1994
 WO WO 02/11605 2/2002

* cited by examiner




FIG. 2

FIG. 1




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 16




FIG. 9

FIG. 8




FIG. 10






FIG. 11






FIG. 17

FIG. 18




FIG. 19

TWO-MODE TROCAR ASSEMBLY

BACKGROUND

1. Technical Field

This application claims the benefit of U.S. Provisional Patent Application No. 60/819,244 filed Jul. 6, 2006, the entire disclosure of which is incorporated by referenced herein.

2. Background of the Related Art

Minimally invasive procedures are continually increasing in number and variation. Forming a relatively small diameter temporary pathway to the surgical site is a key feature of most minimally invasive surgical procedures. The most common method of providing such a pathway is by inserting a trocar assembly through the skin. In many procedures, the trocar assembly is inserted into an insufflated body cavity of a patient. In such procedures, the trocar assemblies with seal mechanisms are utilized to provide the necessary pathway to the surgical site while minimizing leakage of insufflation gases.

Trocar assemblies typically include an obturator which is removably inserted through a cannula. The obturator may include a safety shield which protects against unintentional puncturing by the sharpened tip of the obturator. The safety shield includes a mechanism which controls the relative movement and locking of the safety shield. Examples of safety shield mechanisms are disclosed in commonly assigned U.S. Pat. No. 6,319,266 to Stelson et al., and commonly assigned U.S. application Ser. No. 11/171,052, filed Jun. 30, 2005, the entire contents of each disclosure being incorporated herein by reference.

SUMMARY

Accordingly, the present disclosure is directed to further improvements in obturator assemblies. In one preferred embodiment, an obturator assembly for penetrating tissue and being at least partially positionable within a cannula assembly includes an obturator housing, an obturator shaft connected to the obturator housing and defining a longitudinal axis, a penetrating member adjacent the distal end of the obturator shaft and an obturator shield mounted about the obturator shaft and having a distal shield nose. The obturator shield is adapted for longitudinal movement between an extended position where the penetration member is substantially enclosed within the shield nose and a retracted position where the penetrating member is at least partially exposed from the shield nose. A manually manipulative member is mounted to the obturator housing and is adapted for rotational movement about the longitudinal axis and relative to the obturator housing between an initial position corresponding to a first mode of operation where the obturator shield is secured in the extended position and the shield nose is used to penetrate tissue, and a release position corresponding to a second mode of operation operatively releasing the obturator shield to permit the obturator shield to move to the retracted position thereof to expose the penetrating member for penetrating the tissue. The obturator assembly may further include a latch member disposed within the obturator housing. The preferred latch member is in operative engagement with the obturator shield to secure the obturator shield in the extended position thereof. The latch member is actuatable to release the obturator shield when the obturator housing is properly mated with the cannula assembly to thereby permit movement of the obturator shield toward the retracted position provided the manually manipulative member is in the

release position. The obturator assembly further includes a release member which is mounted to the obturator housing and operatively coupled with the latch member. The release member is positioned to engage the cannula assembly upon mating of the obturator housing and the cannula assembly to thereby displace the release member and cause actuation of the latch member.

An indicator member may be operatively connected to the obturator shield. The indicator member is adapted for longitudinal movement with the obturator shield to provide visual confirmation to the operator of the positioning of the obturator shield. The manually manipulative member may be in operative engagement with the indicator member when in the initial position of the manually manipulative member to secure the obturator shield in the extended position and is operatively disengaged from the indicator member when in the release position of the manually manipulative member to permit movement of the obturator shield to the retracted position. An indicator collar may be disposed within the obturator housing and mounted to the obturator shield. The indicator collar has the indicator member mounted thereto and is adapted for longitudinal movement with the obturator shield.

Stop means may be associated with the obturator housing for confirming positioning of the manually manipulative member at the initial position and the release position. Alternatively, a control member may be mounted in fixed relation to the obturator housing and operatively associated with the manually manipulative member. One of the control member and the manually manipulative member includes a groove and the other of the control member and the manually manipulative member includes a pin. The pin traverses the groove during rotation of the manually manipulative member between the initial and release position thereof whereby terminating ends of the groove correspond to the initial and release position of the manually manipulative member.

The penetrating member is preferably an obturator blade connected to the obturator shaft. The obturator shield may be normally biased toward the extended position.

In another preferred embodiment, an obturator assembly for penetrating tissue and being at least partially positionable within a cannula assembly includes an obturator housing defining a longitudinal axis, an obturator shaft connected to the obturator housing, a penetrating member adjacent the distal end of the obturator shaft and an obturator shield mounted about the penetrating member and having a shield nose adapted to penetrate tissue. The obturator shield is adapted for longitudinal movement between an extended position where the shield nose substantially encloses the penetrating member and a retracted position to at least partially expose the penetrating member. A latch member is disposed within the obturator housing and in operative engagement with the obturator shield to secure the obturator shield in the extended position thereof. The latch member is actuatable to release the obturator shield to permit movement of the obturator shield toward the retracted position thereof. A manually manipulative member is mounted to the obturator housing and adapted to be selectively moved by the operator relative to the obturator housing between an initial position corresponding to a first mode of operation securing the obturator shield in the extended position whereby the shield nose is utilized to pass through tissue, and a release position corresponding to a second mode of operation operatively releasing the obturator shield to permit the obturator shield to move to the retracted position thereof provided the latch member is actuated to expose the penetrating member to permit the penetrating member to engage and pass through the tissue. The manually

3

manipulative member may be adapted for rotational movement relative to the obturator housing to move between the initial position and the release position. A release member may be mounted to the obturator housing and operatively coupled with the latch member. The release member is positioned to engage the cannula assembly upon mating of the obturator housing and the cannula assembly to thereby displace the release member and cause actuation of the latch member. An indicator member may be operatively connected to the obturator shield. The indicator member is adapted for longitudinal movement with the obturator shield and for providing visual confirmation to the operator of the positioning of the obturator shield. The manually manipulative member is in operative engagement with the indicator member when in the initial position of the manually manipulative member to secure the obturator shield in the extended position, and is operatively disengaged from the indicator member when in the release position of the manually manipulative member to permit movement of the obturator shield to the retracted position provided the latch member is actuated.

In another preferred embodiment, a trocar assembly includes a cannula including a cannula housing and a cannula sleeve extending from the cannula housing and an obturator assembly at least partially positionable within the cannula. The obturator assembly includes an obturator housing, an obturator shaft connected to the obturator housing, an obturator blade connected to the obturator shaft and an obturator shield coaxially mounted about the obturator blade. The obturator shield is adapted for longitudinal movement between a first position substantially enclosing the obturator blade and a second position to at least partially expose the obturator blade. A manually manipulative member is mounted to the obturator housing and is adapted to be selectively moved by the operator relative to the obturator housing between an initial position corresponding to a first mode of operation where a generally blunt leading end of the obturator shield is used to penetrate tissue, and a release position corresponding to a second mode of operation operatively releasing the obturator shield to permit the obturator shield to move to the retracted position thereof to at least partially expose the obturator blade for piercing through tissue. A latch member is disposed within the obturator housing and in operative engagement with the obturator shield to secure the obturator shield in the extended position thereof. The latch member is actuable to release the obturator shield upon approximating the obturator housing and the cannula housing. The manually manipulative member may be adapted for rotational movement relative to the obturator housing to move between the initial position and the release position.

Methods of use of the obturator assembly are also disclosed.

BRIEF DESCRIPTION OF THE DRAWINGS

Preferred embodiments of the present disclosure are described hereinbelow with references to the drawings, wherein:

Preferred embodiments of the present disclosure are described hereinbelow with references to the drawings, wherein:

FIG. 1 is a perspective view of the trocar assembly in accordance with the present disclosure, illustrating the cannula assembly and the obturator assembly;

FIG. 2 is a perspective view of the trocar assembly illustrating the obturator assembly assembled within the cannula assembly;

4

FIG. 3 is a perspective view with parts separated of the obturator assembly;

FIG. 4 is a perspective view of the obturator housing of the obturator assembly;

FIG. 5 is a second perspective view of the obturator housing of the obturator assembly;

FIG. 6 is a side cross-sectional view of the obturator housing of the obturator assembly illustrating the activator member in an initial position corresponding to a first mode of operation of the obturator assembly;

FIGS. 7-8 are perspective views of the obturator housing with the housing cover removed;

FIG. 9 is an enlarged perspective view of the control member of the obturator housing;

FIGS. 10-11 are additional perspective views of the obturator housing with the housing cover removed;

FIG. 12 is a side cross-sectional view of the obturator assembly illustrating the latch member in an unactuated position;

FIG. 13 is an enlarged isolated view of the indicated area of detail of FIG. 12 illustrating the relationship of the components of the latch member in the unactuated position;

FIG. 14 is a side cross-sectional view of the trocar assembly illustrating the obturator assembly mounted relative to the cannula assembly and the latch member in an actuated position;

FIG. 15 is an enlarged isolated view of the indicated area of detail of FIG. 14 illustrating the relationship of the components of the latch member in the actuated position;

FIG. 16 is a side cross-sectional view of the obturator housing illustrating the activator member in a release position corresponding to a second mode of operation of the obturator assembly;

FIG. 17 is a side cross-sectional view similar to the view of FIG. 14 illustrating the obturator shield of the obturator assembly in a retracted position to expose the obturator blade;

FIG. 18 is an enlarged isolated view of the indicated area of detail of FIG. 17; and

FIG. 19 is a side cross-sectional view illustrating proximal movement of the indicator collar during movement of the obturator shield to the retracted position.

DETAIL DESCRIPTION OF PREFERRED EMBODIMENTS

Referring now in detail to the drawing figures, in which like references numerals identify similar or identical elements, there is illustrated, in FIGS. 1 and 2, a trocar assembly constructed in accordance with a preferred embodiment of the present disclosure, and designated generally by reference numeral 10. Trocar assembly 10 is particularly adapted for use in minimally invasive surgical procedures such as endoscopic or laparoscopic procedures. Generally, trocar assembly 10 includes two principal subassemblies, namely, obturator assembly 100 and cannula assembly 1000.

Cannula assembly 1000 may be any cannula assembly suitable for use in a laparoscopic surgical procedure. In one preferred embodiment, cannula assembly 1000 includes cannula housing 1002 and cannula sleeve 1004 extending from the cannula housing 1002. Either or both cannula housing 1002 and cannula sleeve 1004 may be opaque or transparent in part or in whole and are fabricated from biocompatible metal or polymeric material. Cannula assembly 1000 may include an internal seal such as a duck-bill valve or other zero closure valve adapted to close in the absence of a surgical instrument to prevent passage of insufflation gases through the cannula assembly 1000.

5

Trocar assembly **10** may also include a seal assembly **2000** which is preferably releasably mounted to cannula housing **1002**. Means for releasably connecting seal assembly **2000** to cannula housing **1002** may include a bayonet coupling, threaded connection, latch, friction fit, tongue and groove arrangements, snap-fit, etc. Seal assembly **2000** includes seal housing **2002** and at least one internal seal which is adapted to form a fluid tight seal about an instrument inserted through the seal assembly **2000**. One suitable seal may be the fabric seal disclosed in commonly assigned U.S. Pat. No. 6,702,787 to Racenet et al., the entire contents of which are incorporated herein by reference. The seal disclosed in the Racenet '787 patent may be a flat septum seal having a first layer of resilient material and a second fabric layer juxtaposed relative to the first layer. Further details of the seal may be ascertained by reference to the '787 patent. Seal assembly **2000** may or may not be a component of cannula assembly **1000**. For example, the seal assembly may be a separate, removable assembly. In the alternative, the seal assembly may comprise an integral part of the cannula assembly **1000** and not be removable.

With reference now to FIG. 3, in conjunction with FIGS. 1-2, obturator assembly **100** includes obturator housing **102**, obturator shaft **104** defining obturator axis "x" and extending distally from the housing **102** and obturator shield **106** coaxially mounted about the obturator shaft **104**. In general, in a first preferred mode of operation, obturator shield **106** defines a distal shield nose **206** which may be used to enter, penetrate or pass, etc. through tissue through a blunt or dissection entry. Alternatively, in a second mode of operation, obturator shield **106** is permitted to retract in a proximal longitudinal direction to expose the cutting blade disposed at the distal end of the obturator shaft **104**. The details of operation and the configuration of shield nose **206** and the cutting blade will be discussed hereinbelow.

Referring now to FIGS. 3-5, obturator housing **102** includes housing base **108** and housing cover **110**. Once the appropriate components are positioned therewithin (as described below), housing base **108** may be attached to housing cover **110** by engaging mating surfaces, for example, by resilient depending latches **112** of cover **110** interlocking with correspondingly dimensioned latch openings **114** of housing base **108**. Preferably, to uniformly connect base **108** and cover **110**, at least three corresponding latches **112** and openings **114** are spaced evenly around the circumference of the cover **110** and the base **108**, respectively. Preferably, obturator housing **102** is configured and dimensioned to functionally cooperate with cannulas that range in size, e.g., from about 5 mm to about 15 mm in diameter.

Referring now to FIGS. 4-7, in conjunction with FIG. 3, obturator housing **102** further includes dial or activator member **116** and control member **118** both of which are housed within the obturator housing **102**. Activator member **116** defines activator disk **120** and activator collar **122** extending distally from the activator disk **120**. Activator disk **120** defines raised tab **124** which is contoured for manual engagement by the fingers of the operator. Raised tab **124** extends beyond opening **126** of housing cover **110**. Raised tab **124** further includes indicia in the form of recessed arrow **128** which identifies the status or position of activator member **116**. Activator collar **122** includes axial slot **130** and axial rib **132** (FIG. 7) in diametrical opposed relation to the axial slot **130**. Activator member **116** is adapted for limited rotational movement as depicted by directional arrow "a" about longitudinal axis "x" between initial and release positions to respectively secure and release obturator shield **106** (FIG. 4). The initial position of activator member **116** corresponds to the first mode of operation of obturator assembly **100** where obturator

6

shield **106** is prevented from retracting and the distal shield nose **206** is used to pass through tissue. FIG. 6 illustrates the initial position of activator member **116**. The release position corresponds to the second mode of operation of obturator assembly **100** where obturator shield **106** is permitted to retract and the cutting blade is used to pierce through tissue.

With reference to FIGS. 6-9, in conjunction with FIG. 3, control member **118** is fixed within obturator housing **102**. Control member **118** includes control disk **134** and limiting collar **136** extending from the proximal side or face of control disk **134**. Control disk **134** includes a plurality of alternating tabs **138** and recesses **140** disposed along the outer periphery of the control disk **134**. Tabs **138** are received within corresponding internal recesses **140** (FIG. 6) defined in the inner wall of housing cover **110** to secure control member **118** within obturator housing **102**. Control member **118** also includes secondary aperture **142** which is radially or laterally spaced from longitudinal axis "x". Control disk **134** further includes cylindrical shaft mount **144** and spring mount **146** both of which extend from the distal face of the control disk **134**. As best depicted in FIG. 6, shaft mount **144** is generally aligned with longitudinal axis "x" and includes bifurcated tabs **148** and central channel **150**. Spring mount **146** is laterally or radially spaced from the longitudinal axis "x".

With reference to FIG. 7, limiting collar **136** of control member **118** is dimensioned to receive activator collar **122** of activator member **116** in the assembled condition of the components, and to permit the activator collar **122** to rotate within the limiting collar **136**. Limiting collar **136** defines recessed groove **152** which extends about 1/2 the perimeter of the limiting collar **136**. Axial rib **132** of activator member **116** traverses recessed groove **152** of control member **118** during rotation of the activator member **116** between the initial and release positions. As best depicted in FIG. 3, recessed groove **152** defines abutment walls **154**, **156** at each end of the recessed groove **152**. Abutment walls **154**, **156** serve as stop (s) to ensure and/or confirm placement of activator member **116** in the initial or release position. Specifically, abutment walls **154**, **156** serve as a tactile indicator that activator member **116** has been moved to either the initial or release position.

Referring now to FIGS. 3, 6, and 7, obturator housing **100** further includes indicator collar **158**. In one preferred arrangement, indicator collar **158** defines internal channel **160** and has distal collar extension **162**. Collar extension **162** includes inner tabs **164** on its inner surface. Indicator collar **158** further includes transverse arm **166** extending radially outwardly from indicator collar **158** and shield position indicator, such as indicator flag **168**. Transverse arm **166** includes axial pin **170** which depends in a proximal direction from the arm **166**. Axial pin **170** is in general axial alignment with secondary aperture **142** of control member **118** and traverses the secondary aperture **142** during proximal movement of the indicator collar **158**. Indicator flag **168** is visible from the exterior of obturator housing **102** as it extends through groove **172** of housing cover **110** (see FIGS. 3 and 4). Preferably, indicator flag **168** is colored to contrast sharply with the surrounding housing components. For example, indicator flag **168** may be red if the surrounding housing components are white or light colored. As best depicted in FIG. 7, indicator collar **158** further includes collar ledge **174** and a pair of posts **176** formed below the ledge **174** and extending radially outwardly from the ledge **174**.

As best depicted in FIG. 6, indicator collar **158** is spring biased in the distal direction by coil spring **178**. In particular, coil spring **178** is received within internal channel **160** of indicator collar **158** and engages internal shelf **160s** of the

indicator collar **158**. The proximal end of coil spring **178** is coaxially positioned about spring mount **144** depending from the distal face of control member **118**.

Referring now to FIGS. **10-13**, in conjunction with FIG. **3**, obturator assembly **100** includes a latching mechanism disposed within obturator housing **102** to prevent proximal movement of obturator shield **106** until such time as the obturator assembly **100** is properly mounted to cannula assembly **1000** and the surgeon is prepared to begin trocar entry. Latching mechanism includes latch member **180**, and release member such as slider **182**. Latch member **180** has two vertical legs **184** connected by web **186**. A pair of biasing posts **188** extends outwardly, one for each side of latch member **180**. Collar ledge **174** of indicator collar **158** is engaged and secured by web **186** of latch member **180** when in an unactuated position of the latch member **180** as depicted in FIGS. **10-13**. In the unactuated position of latch member **180** of indicator collar **158**, the indicator collar **158** and thus obturator shield **106** is retained in a first extended position. Latch member **180** is preferably molded as part of housing base **108** in cantilever fashion. However, latch member **180** may be formed as a separate element and secured to base **108** by suitable known techniques.

Slider **182** includes slider post **190** disposed at its lower end, arming button **192** extending distally from the distal face of slider **182** and a pair of slider legs **194** which terminate in crooks **196**. Crooks **196** defined in slider legs **194** are configured and dimensioned to engage posts **188** of latch member **180**, as shown in FIGS. **10** and **11**. Slider **182** is distally biased by slider spring **198** which is maintained in axial alignment by slider post **190** of slider **182**. The proximal end of slider spring **198** bears against the inner surface of control member **118** and is maintained in position between slider post **190** and spring mount **146** of the control member **118**. (See FIGS. **12** and **13**). The distal biasing of slider **182** causes arming button **192** to project through opening **108a** formed in housing base **108**. The lower end or transverse leg **200** of slider **182** resides with mounting posts **202** of housing base **108** (FIG. **3**).

Referring now to FIGS. **3** and **12-13**, obturator shield **106** has shield linkage **204** operatively connected thereto and along with the obturator shield **106** defines an outer member of obturator assembly **100**. In one preferred embodiment, shield linkage **204** is connected to obturator shield **106** through an arrangement including diametrical tabs **208** extending from the distal end of shield linkage **204**, which are received within corresponding openings **210** of obturator shield **106** in snap relation therewith. Other means for connecting the components of obturator shield **106** are also envisioned including snap fit arrangements, adhesives, welding tongue and groove arrangements, etc. In other embodiments, obturator shield **106** and shield linkage **204** are a single component. In the assembled condition, shield linkage **204** extends within housing base **108** and is at least partially received within collar extension **162**. Shield linkage **204** includes a pair of diametrically opposed outer grooves **212** which receive inner tabs **164** of collar extension **162** to operatively connect shield extension **204** and indicator collar **158**. Thus, by virtue of connection of indicator collar **158** with shield linkage **204**, obturator shield **106** and shield nose **206** are adapted for reciprocal axial movement along axis "x" and relative to obturator housing **102** and obturator shaft **104** concurrently with corresponding movement of the indicator collar **158**.

With reference again to FIGS. **1** and **2**, shield nose **206** may be tapered, conical or frusto-conical in configuration, and is adapted to pass through tissue and may be capable of cutting or piercing through tissue. In one preferred embodiment,

shield nose **206** has an irregular shaped with rounded tip **214**. In particular, shield nose **206** is generally tapered in configuration defining a complex curved arrangement. As best depicted in FIG. **2**, in a first profile of shield nose **206**, the shield nose **206** includes opposed concave surfaces **216**. In a second profile (viewed at a 90° offset), shield nose **206** defines convex surfaces **218**. This alternating concave and convex arrangement provides a substantially reduced profile (in cross-section) compared to conventional conically shaped obturators thereby providing an enhanced ability to penetrate or pass through tissue layers. Various radii of curvature are contemplated. Rounded tip **214**, by its arcuate configuration, minimizes the potential of undesired or unintended piercing of tissue. Alternatively, it is envisioned that rounded tip **214** may be more pointed to also pierce tissue if desired. This particular configuration of shield nose **206** is disclosed in commonly assigned U.S. patent application Ser. No. 11/103,892, filed Apr. 12, 2005, the contents of which are incorporated in its entirety by reference herein. Shield nose **206** also defines knife slot **220**.

With reference to FIGS. **3**, **6** and **13**, the components of obturator shaft **104** now will be discussed. Obturator shaft **104** includes obturator rod **222** and blade **224** mounted to the obturator rod **222**. Obturator rod **222** defines proximal end **226** which passes through opening **160** of indicator collar **158** and is received within shaft mount **144** of control member **118**. Proximal end **226** of obturator rod **222** includes circumferential recess **228** which receives bifurcated tabs **148** of shaft mount **144** of control member **118** in snap relation therewith. In this manner, obturator rod **104** is fixed to obturator housing **102**.

With reference now to FIG. **12**, in conjunction with FIG. **3**, the distal end of obturator rod **222** defines obturator knife slot **230** having locking projection **232**. Knife blade **224** may be secured within knife slot **230** by reception of locking projection **232** within knife aperture **234**. Conventional means including adhesives, cements, etc. are also envisioned. Knife blade **224** is preferably a flat or thin blade and fabricated from stainless steel by a suitable process, e.g., by stamping or metal injection molding and includes opposed cutting edges **236** which extend to penetrating tip **238**. Knife blade **224** is accommodated within knife slot **220** of shield nose **206**.

With reference now to FIGS. **14-15**, a method of use and operation of trocar assembly **10** will be discussed. Obturator assembly **100** has two modes of operation. In the first mode of operation, obturator shield **106** is locked in its distal position and nose shield **206** is applied against the tissue to penetrate or pass through the tissue through a blunt or dissecting entry. In the second mode, nose shield **206** and obturator shield **106** are permitted to retract to expose knife blade **224** to contact and penetrate the tissue. Activator member **116** controls operation of obturator assembly **100** between the two modes.

Initially, obturator assembly **100** is inserted within cannula assembly **1000** and advanced to where obturator housing **102** is approximated with seal housing **2002** of the seal assembly **2000**. Seal assembly **2000** may comprise a separate part or may be a component of cannula assembly **1000**. Seal housing **2002** and housing base **108** of obturator housing **102** may be appropriately dimensioned to form a friction fit or may be coupled to each other by conventional means including bayonet coupling, tongue-groove, etc. With obturator housing **102** and seal housing **2002** approximated, arming button **192** of slider **182** engages proximal surface **2004** of seal housing **2002** and is forced upwardly (depicted by directional arrow "u") from the position depicted in FIG. **13** to the position depicted in FIGS. **14-15**. During this movement, slider **182** pivots or angulates whereby legs **194** of the slider **182** push

latch member **180** in a radial outward direction (depicted by directional arrow “z”) such that web portion **186** of latch member **180** is out of axial alignment with ledge **174** of indicator collar **158**. In this position, indicator collar **158**, obturator shield **106** and shield nose **206** are free to axially move provided activator member **116** is in the second mode of operation. With obturator assembly **100** mated with cannula assembly **2000**, the surgeon decides whether a blunt bladeless entry or a piercing blade entry is required to access the surgical site. This decision may be predicated on whether or not an initial entry opening has been made within the tissue, and, if so, thereby requiring a bladeless entry into the tissue corresponding to the first mode of operation of obturator assembly **100**. If a bladeless or blunt entry is selected, the surgeon will position activator member **116** in the initial position of FIG. 6. In this position, activator collar **122** is positioned over axial pin **170** of indicator collar **158** and thus prevents proximal retracting movement of the indicator collar **158** and obturator shield **106**. Visual confirmation of the positioning of activator collar **122** in the initial position is provided by indicator arrow **128** of raised tab **124**. In one preferred embodiment, the initial position of activator collar **122** corresponds to recessed arrow **128** being arranged in diametrical opposed relation to indicator flag **168** as shown in FIG. 6. The surgeon then applies shield nose **206** to the tissue and exerts a distal force on the assembly **10**. Shield nose **206** passes through tissue, e.g., by a blunt dissecting action, to access the underlying surgical site, e.g., the abdominal cavity. Obturator assembly **100** may be removed from cannula assembly **1000** and surgery may be performed with instruments introduced within cannula assembly **1000**.

If a bladed entry is required corresponding to the second mode of operation, activator member **116** is selectively moved from the initial position of FIG. 6 to the release position of FIG. 16 by rotating the activator member **116** about longitudinal axis “x” such that recessed arrow **128** of the activator member **116** is aligned with indicator flag **168** thereby providing visual confirmation of the positioning of activator member **116**. Engagement of axial rib **122** of activator member **116** with wall **156** (FIG. 3) of control member **118** also provides tactile confirmation of the positioning of activator member **116** in the release position. In the release position, axial slot **130** of activator collar **122** is in general alignment with axial pin **170** of indicator collar **158**.

With reference now to FIGS. 17-19, the surgeon begins to insert trocar assembly **10** through the body wall of the patient. Shield nose **206** contacts the tissue “t” and is driven upwardly to cause the shield nose **206**, obturator shield **106**, and indicator collar **158** to move proximally (depicted by directional arrow “v”) against the bias of coil spring **178**. As discussed hereinabove, obturator assembly **100** must be properly mated with seal assembly **2000** such that the latching mechanism is activated to permit retraction of obturator shield **106**. During the proximal movement of indicator collar **158**, axial pin **170** of the indicator collar **158** traverses secondary aperture **142** of control member **118** and traverses axial slot **130** of activator member **116**. (FIG. 19) Such movement exposes obturator blade **224** to incise the tissue. This armed condition of obturator assembly **100** is visually verified by the proximal location of indicator flag **168** of indicator collar **158**. In addition, proximal movement of indicator collar **158** causes posts **176** of the indicator collar **158** to ride along outer surfaces **194a** of legs **194** of slider **182** to thereby move the slider **182** at least radially inwardly and upwardly (as shown by the directional arrows “r” and “v”, respectively) in a general aligned position relative to the obturator axis “x” and disengaged from latch member **180**. (i.e., crooks **196** of slider legs **194** disengage

posts **188** of latch member **180**). With obturator blade **224** exposed, the surgeon may apply a distally-directed force to obturator assembly **100** to cause penetration through the tissue.

Once knife blade **224** and shield nose **206** pass through the body wall of the patient, indicator collar **158**, obturator shield **106** and the shield nose **206** move distally under the influence of coil spring **178** whereby the shield nose **206** covers blade **224** as shown in FIG. 14. The obturator assembly **100** may be removed from cannula assembly **1000** and surgery is performed with instruments inserted through cannula assembly **1000**. It is noted that upon removal of obturator assembly **100**, ledge **174** of indicator collar **158** moves into engagement with web portion **186** of latch member **180**. Concurrently with this movement, slider **182**, which is aligned relative to axis “x” as discussed hereinabove, is driven distally under the influence of coil spring **198**. In the respective positions of indicator collar **158** and slider **182** depicted in FIG. 13, collar ledge **174** of indicator collar **158** securely engages web **186** of latch member **180** to secure shield nose **206** in its extended position. This feature ensures that the removed obturator assembly **100** will not be armed.

Except where noted otherwise, the materials utilized in the components of the presently disclosed trocar assembly generally include materials such as, for example, ABS, polycarbonate, stainless steel, titanium and any other suitable biocompatible metals and/or polymeric materials. A preferred ABS material is CYCOLAC which is available from General Electric. A preferred polycarbonate material is also available from General Electric under the trademark LEXAN. An alternative polycarbonate material which may be utilized is CALIBRE polycarbonate available from Dow Chemical Company. The polycarbonate materials may be partially glass filled for added strength.

Although the illustrative embodiments of the present disclosure have been described herein with reference to the accompanying drawings, it is to be understood that the disclosure is not limited to those precise embodiments, and that various other changes and modifications may be effected therein by one skilled in the art without departing from the scope or spirit of the disclosure.

What is claimed is:

1. An obturator assembly for penetrating tissue and being at least partially positionable within a cannula assembly, which comprises:
 - an obturator housing;
 - an obturator shaft connected to the obturator housing and defining a longitudinal axis, and proximal and distal ends;
 - a penetrating member adjacent the distal end of the obturator shaft;
 - an obturator shield mounted about the obturator shaft and having a distal shield nose, the obturator shield being adapted for longitudinal movement between a fully extended position where the penetrating member is substantially enclosed within the distal shield nose and a fully retracted position where the penetrating member is at least partially exposed from the distal shield nose; and
 - a manually manipulative member mounted to the obturator housing and adapted for rotational movement about the longitudinal axis and relative to the obturator housing between an initial position corresponding to a first mode of operation where the obturator shield is secured in the fully extended position and the distal shield nose is used to penetrate tissue, and a release position corresponding to a second mode of operation operatively releasing the obturator shield to permit the obturator shield to move

11

repeatedly from the fully extended position to the fully retracted position and back to the fully extended position, the obturator shield moving independent of the manually manipulative member when in the second mode of operation.

2. The obturator assembly according to claim 1 further including a latch member disposed within the obturator housing, the latch member in operative engagement with the obturator shield to secure the obturator shield in the fully extended position thereof, the latch member being actuatable to release the obturator shield to thereby permit movement of the obturator shield toward the fully retracted position provided the manually manipulative member is in the release position thereof.

3. The obturator assembly according to claim 2 further comprising a release member mounted to the obturator housing and operatively coupled with the latch member, the release member positioned to engage the cannula assembly upon mating of the obturator housing and the cannula assembly to thereby displace the release member and cause actuation of the latch member.

4. The obturator assembly according to claim 1 including an indicator member operatively connected to the obturator shield, the indicator member being adapted for longitudinal movement with the obturator shield and for providing visual confirmation to the operator of the positioning of the obturator shield.

5. The obturator assembly according to claim 4 wherein the manually manipulative member is in operative engagement with the indicator member when in the initial position of the manually manipulative member to secure the obturator shield in the fully extended position and being operatively disengaged from the indicator member when in the release position of the manually manipulative member to permit movement of the obturator shield to the fully retracted position.

6. The obturator assembly according to claim 5 including an indicator collar disposed within the obturator housing and mounted to the obturator shield, the indicator collar having the indicator member mounted thereto and being adapted for longitudinal movement with the obturator shield.

7. The obturator assembly according to claim 1 including stop means associated with the obturator housing for confirming positioning of the manually manipulative member at the initial position and the release position.

8. The obturator assembly according to claim 1 including a control member mounted in fixed relation to the obturator housing and operatively associated with the manually manipulative member, one of the control member and the manually manipulative member including a groove and the other of the control member and the manually manipulative member including a pin, the pin traversing the groove during rotation of the manually manipulative member between the initial and release position thereof whereby terminating ends of the groove correspond to the initial and release position of the manually manipulative member.

9. The obturator assembly according to claim 1 wherein the penetrating member is an obturator blade connected to the obturator shaft.

10. The obturator assembly according to claim 1 wherein the obturator shield is normally biased toward the fully extended position.

11. An obturator assembly for penetrating tissue at least partially within a cannula assembly, comprising:
an obturator housing;

12

an obturator shaft extending distally from the obturator housing and defining a longitudinal axis, the obturator shaft including a proximal end and a distal end;

a penetrating member adjacent the distal end of the obturator shaft;

an obturator shield mounted about the obturator shaft and having a distal shield nose, the obturator shield being adapted for longitudinal movement between an extended position where the penetrating member is substantially enclosed within the distal shield nose and a fully retracted position where the penetrating member is at least partially exposed from the distal shield nose; and a manually manipulative member mounted to the obturator housing and adapted for movement about the longitudinal axis and relative to the obturator housing between an initial position corresponding to a first mode of operation where the obturator shield is secured in the extended position, and a release position corresponding to a second mode of operation where the obturator shield is repeatedly moveable relative to the manually manipulative member between the extended position and the fully retracted position.

12. The obturator assembly according to claim 11, further comprising a latch member disposed within the obturator housing, the latch member in operative engagement with the obturator shield to secure the obturator shield in the extended position thereof, the latch member being actuatable to release the obturator shield to thereby permit movement of the obturator shield toward the fully retracted position provided the manually manipulative member is in the release position thereof.

13. The obturator assembly according to claim 11, further comprising stop means associated with the obturator housing for confirming positioning of the manually manipulative member at the initial position and the release position.

14. The obturator assembly according to claim 11, further comprising a control member mounted in fixed relation to the obturator housing and operatively associated with the manually manipulative member, one of the control member or the manually manipulative member including a groove and the other of the control member or the manually manipulative member including a pin, wherein the manipulative member is rotatable about the longitudinal axis, and wherein the pin traverses the groove during rotation of the manually manipulative member between the initial position and the release position thereof whereby terminating ends of the groove correspond to the initial position and the release position of the manually manipulative member.

15. The obturator assembly according to claim 11, wherein the penetrating member is an obturator blade connected to the obturator shaft.

16. The obturator assembly according to claim 11, wherein the obturator shield is normally biased toward the extended position.

17. The obturator assembly according to claim 11, wherein in the first mode of operation, the obturator shield is secured in a fully extended position, and wherein in the second mode of operation, the obturator shield is repeatedly moveable relative to the obturator shield between the fully extended position and the fully retracted position.