



US009303657B2

(12) **United States Patent**
Chou

(10) **Patent No.:** **US 9,303,657 B2**
(45) **Date of Patent:** **Apr. 5, 2016**

(54) **FAN AND MOTOR BEARING HEAT DISSIPATION STRUCTURE THEREOF**

(71) Applicant: **ASIA VITAL COMPONENTS CO., LTD.**, New Taipei (TW)

(72) Inventor: **Chu-Hsien Chou**, New Taipei (TW)

(73) Assignee: **ASIA VITAL COMPONENTS CO., LTD.**, New Taipei (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 679 days.

(21) Appl. No.: **13/723,098**

(22) Filed: **Dec. 20, 2012**

(65) **Prior Publication Data**

US 2014/0178184 A1 Jun. 26, 2014

(51) **Int. Cl.**

- F04D 29/056** (2006.01)
- F04D 29/58** (2006.01)
- F04D 25/06** (2006.01)
- F04D 25/08** (2006.01)
- F04D 29/046** (2006.01)
- F04D 29/057** (2006.01)
- H02K 5/167** (2006.01)
- H02K 9/22** (2006.01)

(52) **U.S. Cl.**

CPC **F04D 29/5806** (2013.01); **F04D 25/062** (2013.01); **F04D 25/064** (2013.01); **F04D 25/08** (2013.01); **F04D 29/046** (2013.01); **F04D 29/057** (2013.01); **F04D 29/584** (2013.01); **H02K 5/1677** (2013.01); **H02K 9/22** (2013.01); **F05D 2240/50** (2013.01)

(58) **Field of Classification Search**

CPC . F04D 25/062; F04D 25/064; F04D 25/0646; F04D 25/08; F04D 29/046; F04D 29/049; F04D 29/58; F05D 2240/50; H02K 9/22
USPC 384/476; 361/695
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,246,140	B1 *	6/2001	Hong	H02K 1/187 310/40 MM
7,364,403	B2 *	4/2008	Wu	F04D 29/063 384/114
7,567,003	B2 *	7/2009	Hong	F04D 29/056 310/67 R
2007/0286725	A1 *	12/2007	Su	F04D 29/601 415/213.1
2008/0063527	A1 *	3/2008	Yeh	F04D 29/646 416/174


* cited by examiner

Primary Examiner — Ninh H Nguyen

(57) **ABSTRACT**

A motor bearing heat dissipation structure includes a metal base, a heat conducting element connected to the metal base and including a wall portion and an extended portion, and a plastic bearing cup located around an outer side of the wall portion of the heat conducting element and fixed to the metal base. The plastic bearing cup internally defines a bearing receiving hole. The extended portion is horizontally extended from an upper end of the wall portion toward a center of the bearing receiving hole. A bearing is received in the bearing receiving hole and seated on the extended portion, so that heat produced by the bearing when it rotates along with a rotary shaft of a motor is transferred from the extended portion of the heat conducting element to the metal base for dissipation. A fan using such motor bearing heat dissipation structure is also disclosed.

20 Claims, 10 Drawing Sheets






Fig. 1A




Fig. 1B




Fig. 1C




Fig. 2A




Fig. 2B




Fig. 2C




Fig. 2D

20




Fig. 3B

20




Fig. 4

20




Fig. 5

1

FAN AND MOTOR BEARING HEAT DISSIPATION STRUCTURE THEREOF

FIELD OF THE INVENTION

The present invention relates to a heat dissipation structure, and more particularly, to a motor bearing heat dissipation structure; and the present invention also relates to a fan having such motor bearing heat dissipation structure.

BACKGROUND OF THE INVENTION

Many conventional inventions have disclosed different manners of holding a bearing in a bearing cup. For example, a prior art discloses a motor fixing structure for a fan having a metal bearing cup. The fan includes a frame, a circuit board arranged on the frame, a stator assembly mounted on the frame, and a rotor assembly located around an outer side of the stator assembly. The frame is provided at a central area with a support seat, on which a bearing cup is provided. The bearing cup includes a connection sleeve portion and a hollow tube portion. The connection sleeve portion is provided on an outer wall surface with a plurality of receiving sections. The stator assembly is fixedly provided on a bottom with a lower winding frame, which defines a central through hole. A plurality of latching sections is provided on an inner wall surface of the central through hole for correspondingly engaging with the receiving sections on the bearing cup. In this manner, the stator assembly is stably fitted via the lower winding frame to the bearing cup on the support seat without the risk of loosening or separating from the bearing cup due to any external force or being used over a long time, so as to ensure normal operation of the fan.

Furthermore, a prior art discloses a motor fixing structure for a fan having a non-metal bearing cup. The fan includes a frame, a circuit board arranged on the frame, a stator assembly mounted on the frame, and a rotor assembly located around an outer side of the stator assembly. The frame is provided at a central area with a support seat, on which a bearing cup is provided. The bearing cup includes a connection sleeve portion and a hollow tube portion. The connection sleeve portion is provided on an outer wall surface with a plurality of receiving sections, and the hollow tube portion is provided on an outer wall surface with a plurality of ribs. The stator assembly is fixedly provided on a bottom with a lower winding frame, which defines a central through hole. A plurality of latching sections is provided on an inner wall surface of the central through hole for correspondingly engaging with the receiving sections on the bearing cup. In this manner, the stator assembly is stably fitted via the lower winding frame to the bearing cup on the support seat without the risk of loosening or separating from the bearing cup due to any external force or being used over a long time, so as to ensure normal operation of the fan.

Furthermore, a prior art discloses a fan bearing cup structure. The fan includes a frame, a motor unit and a blade unit. The frame is provided at a central area with a support seat, on which a bearing cup is provided, and the bearing cup is provided on an outer wall surface at proper positions with a plurality of latching units. The motor unit has a central opening fitted around an outer side of the bearing cup. The opening is formed on an inner edge thereof with a plurality of recesses, to which the latching units are correspondingly locked. The blade unit includes a fan hub, a rotary shaft, a plurality of blades, and a magnetic member. The rotary shaft is centered in the fan hub and fitted in the bearing cup, and the magnetic member is mounted to an inner wall of the fan hub corre-

2

sponding to the motor unit. In this manner, the motor unit can be stably held to the bearing cup without the risk of becoming loosened therefrom to sway or displace laterally while rotating or to move upward and separate from the bearing cup.

Furthermore, a prior art discloses a motor, which includes a shaft tube, a stator seat, and a rotor structure. The shaft tube is provided at an upper end with at least one first receiving section. The stator seat has an inner bushing, and an opening defined at a center of the inner bushing. Via the opening, the stator seat is fitted around the shaft tube. At least one second receiving section is provided on a peripheral edge of the opening at the center of the inner bushing of the stator seat corresponding to the first receiving section on the shaft tube and is welded thereto. The rotor structure includes a rotary shaft axially received in the shaft tube.

In the above-mentioned techniques, the bearings are held in place generally by plastic injection molding or metal press fit. In the case of metal press fit, while the metal bearing cup has relatively high heat conductivity and the bearing received therein can have better heat dissipation efficiency to effectively lower the bearing temperature, a higher manufacturing cost is required. On the other hand, in the case of plastic injection molding, while a lower manufacturing cost is possible, the plastic bearing cup could not transfer the heat produced by the bearing during rotation thereof, so that the bearing has relatively higher temperature because the produced heat thereof could not be easily dissipated from the plastic bearing cup.

It is therefore very important to work out a way for forming a fan at reduced manufacturing cost while enabling efficient removal of heat from the bearing.

SUMMARY OF THE INVENTION

A primary object of the present invention is to provide a fan motor structure, in which a plastic bearing cup encloses a heat conducting element therein and holds the same to a metal base, so as to help in the dissipation of heat produced by a bearing in the plastic bearing cup during motor operation.

Another object of the present invention is to provide a heat conducting element having a wall portion fixedly connected to a metal base and enclosed in a plastic bearing cup, which is also fixed to the metal base.

A further object of the present invention is to provide a plastic bearing cup having an inner wall surface to define a bearing receiving hole therein, a heat conducting element having a wall portion and an extended portion horizontally extended from an upper end of the wall portion beyond the inner wall of the plastic bearing cup toward a center thereof, and a bearing received in the bearing receiving hole and seated on the extended portion of the heat conducting element, so that heat produced by the bearing during rotation thereof is transferred via the extended portion of the heat conducting element to the metal base for dissipation.

A still further object of the present invention is to provide a heat conducting element, which transfers heat produced by a bearing received in a plastic bearing cup to a metal base having a large surface area, so as to enable quick dissipation of heat produced by the bearing during rotation thereof.

A still further object of the present invention is to provide a plastic bearing cup having an inner wall surface to define a bearing receiving hole therein, and a heat conducting element enclosed in the plastic bearing cup and fixedly connected to a metal base; the heat conducting element has an extended portion horizontally extended beyond the inner wall of the plastic bearing cup toward a center thereof, so that a bearing received in the plastic bearing cup is seated on the extended

3

portion. Further, the extended portion of the heat conducting element has a free end extended into and engaged with an annular retaining groove formed around an end of a rotary shaft extended through the bearing, so that the rotary shaft is held to the bearing and the heat produced by the bearing when the same rotates along with the rotary shaft can be transferred to the metal base for dissipation.

To achieve the above and other objects, the present invention provides a motor bearing heat dissipation structure applicable to a bearing having a bottom surface. The motor bearing heat dissipation structure includes a metal base; a heat conducting element, and a plastic bearing cup. The heat conducting element has a wall portion fixedly connected at a lower end to the metal base and an extended portion horizontally formed on an upper end of the wall portion, and the extended portion has a free end and a top surface. The plastic bearing cup includes a lower portion, which encloses the wall portion of the heat conducting element therein and is fixed to the metal base. The plastic bearing cup upward extends from the lower portion and has an upper end located higher than the wall portion. The plastic bearing cup also has an inner wall surface to internally define a bearing receiving hole, which extends from the upper end of the plastic bearing cup into the lower portion thereof. The extended portion of the heat conducting element is extended from the upper end of the wall portion to horizontally radially inward project beyond the inner wall surface of the plastic bearing cup toward a center thereof, so that both the free end and the top surface of the extended portion are located in the bearing receiving hole. The bearing is accommodated in the bearing receiving hole and seated on the extended portion with the bottom surface of the bearing being in contact with the top surface of the extended portion.

According to an embodiment of the present invention, the wall portion of the heat conducting element is configured as a hollow cylinder and is substantially perpendicular to the metal base; and the extended portion of the heat conducting element is horizontally extended from the upper end of the wall portion toward a center of the hollow cylinder.

According to another embodiment of the present invention, the metal base is provided with a through hole, which is located below the heat conducting element and the plastic bearing cup; and a space is defined in the heat conducting element between an underside of the extended portion and an inner side of the wall portion to communicate with the bearing receiving hole and the through hole on the metal base. And, the through hole of the metal base and the space in the heat conducting element a sealing element is correspondingly closed by a sealing element.

According to an embodiment of the present invention, the bearing includes an inner cylindrical portion and an outer cylindrical portion, which together define the bottom surface of the bearing between them, and the free end of the extended portion of the heat conducting element is located at a position corresponding to the inner cylindrical portion.

According to another embodiment of the present invention, the free end of the extended portion of the heat conducting element is located at a position slightly radially inward protruded beyond the inner cylindrical portion to engage with an annular retaining groove formed on a rotary shaft that is received in the inner cylindrical portion.

In the present invention, there is further included a metal bottom plate, on which a first opening is provided; and the metal base is located in the first opening and connected to the metal bottom plate via a plurality of connection arms. The connection arms respectively have an end connected to an outer periphery of the metal base and another opposite end

4

connected to an inner periphery of the first opening, so as to support the metal base in the first opening. The metal bottom plate includes a frame portion extended along an outer edge thereof, such that a second opening is formed on one side of the metal bottom plate between two ends of the frame portion.

According to the present invention, the heat conducting element and the metal bottom plate are made of gold, silver, copper, aluminum or iron, or any combination thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

The structure and the technical means adopted by the present invention to achieve the above and other objects can be best understood by referring to the following detailed description of the preferred embodiments and the accompanying drawings, wherein

FIG. 1A is an exploded perspective view of a motor bearing heat dissipation structure according to a first preferred embodiment of the present invention, in which a heat conducting element is included;

FIG. 1B is a sectional view of FIG. 1A;

FIG. 1C is an assembled view of FIG. 1B;

FIG. 2A is a perspective view showing a motor bearing heat dissipation structure according to a second embodiment of the present invention, which has a differently configured heat conducting element;

FIG. 2B is a perspective view showing a motor bearing heat dissipation structure according to a third embodiment of the present invention, which has another differently-configured heat conducting element;

FIG. 2C is a perspective view showing the manner in which the heat conducting element in FIG. 2A is enclosed in a plastic bearing cup;

FIG. 2D is an enlarged view of the circled area of FIG. 2C;

FIG. 3A is an exploded sectional view of a first embodiment of a fan according to the present invention, which uses the motor bearing heat dissipation structure as shown in FIGS. 1A, 2A and 2B;

FIG. 3B is an assembled view of FIG. 3A;

FIG. 4 is an assembled view showing a second embodiment of the fan according to the present invention, which includes a rotary shaft without using any retaining element; and

FIG. 5 is another assembled view showing a third embodiment of the fan according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will now be described with some preferred embodiments thereof and with reference to the accompanying drawings. For the purpose of easy to understand, elements that are the same in the preferred embodiments are denoted by the same reference numerals.

Please refer to FIG. 1A that is an exploded perspective view of a motor bearing heat dissipation structure according to a first preferred embodiment of the present invention; and to FIGS. 1B and 1C that are exploded and assembled sectional views, respectively, of the motor bearing heat dissipation structure shown in FIG. 1A. As shown, the motor bearing heat dissipation structure of FIG. 1A includes a metal base **11**, a plastic bearing cup **12**, and a heat conducting element **13**. The metal base **11** has a centered through hole **111** formed thereon. The heat conducting element **13** includes a wall portion **131** and an extended portion **132** horizontally formed on an upper end of the wall portion **131**. The wall portion **131** is substantially perpendicular to the metal base **11** and is fixedly connected at a lower end **1311** to the metal base **11**,

5

such that the wall portion **131** is located around an outer side of the centered through hole **111**.

In an embodiment, the lower end **1311** of the wall portion **131** is welded to the metal base **11**. In another embodiment, the metal base **11** is provided with insertion slots or insertion holes, into which the lower end **1311** of the wall portion **131** is correspondingly inserted to connect the heat conducting element **13** to the metal base **11**. In a further embodiment, the wall portion **131** and the metal base **11** are correspondingly provided with fixing holes, through which fastening elements can be extended to lock or connect the heat conducting element **13** to the metal base **11**. In a still further embodiment, the wall portion **131** is enclosed in the plastic bearing cup **12** and therefore held to the metal base **11**.

While the heat conducting element **13** illustrated in the first preferred embodiment of the present invention has a round configuration, it is not limited thereto and can be differently shaped to have, for example, a square, an oblong, a hexagonal, or an octagonal configuration.

The plastic bearing cup **12** includes a lower portion enclosing the wall portion **131** of the heat conducting element **13** therein and being fixed to the metal base **11**. The plastic bearing cup **12** upward extends from the lower portion **121** and has an upper end **122** located higher than the wall portion **131**. The plastic bearing cup **12** has an inner wall surface **123** and internally defines a bearing receiving hole **124**, which extends from the upper end **122** into the lower portion **121**. In an embodiment, the plastic bearing cup **12** is injection molded to enclose an outer wall surface of the wall portion **131** and fixedly connect to the metal base **11**.

The extended portion **132** of the heat conducting element **13** has a free end **1321** and a top surface **1322**. The top surface **1322** is extended between the free end **1321** and the upper end of the wall portion **131** to horizontally radially project beyond the inner wall surface **123** toward a center of the plastic bearing cup **12**, so that both the free end **1321** and the top surface **1322** are located in the bearing receiving hole **124**. A space **134** is defined between an underside of the extended portion **132** and an inner side of the wall portion **131** to communicate with the bearing receiving hole **124** and the centered through hole **111**. The centered through hole **111** can be sealed by a corresponding sealing element **14**. According to an embodiment of the present invention, the sealing element **14** is a cap closed onto the centered through hole **111** from a lower side of the metal base **11**. According to another embodiment, the plastic bearing cup **12** can be formed on the metal base **11** around the centered through hole **111** by upward injection molding a plastic material from the lower side of the metal base **11** via the centered through hole **111**, so as to seal the centered through hole **111** at the same time.

Alternatively, according to a further embodiment, the metal base **11** can be a flat base without a centered through hole. In this case, the sealing element **14** is omitted.

A bearing **16** is received in the bearing receiving hole **124** of the plastic bearing cup **12**. The bearing **16** includes an inner cylindrical portion **161** and an outer cylindrical portion **162**, which together define a bottom surface **163** of the bearing **16** between them. The inner cylindrical portion **161** internally defines a central bore **164**, into which a rotary shaft **223** can be inserted (see FIGS. 3A, 3B, 4 and 5). The bearing **16** accommodated in the bearing receiving hole **124** is seated on the extended portion **132** with the bottom surface **163** being in contact with the top surface **1322**. In an embodiment, the free end **1321** of the extended portion **132** is located at a position corresponding to the inner cylindrical portion **161** or between the inner cylindrical portion **161** and the outer cylindrical portion **162**. In another embodiment, the free end **1321** is

6

slightly radially protruded into the central bore **164** defined by the inner cylindrical portion **161** to engage with an annular retaining groove formed on the rotary shaft **223** inserted in the central bore **164**, as will be described in more details later.

In FIG. 1, there is also shown a metal bottom plate **17**, on which a first opening **171** is provided. The metal base **11** is located in the first opening **171** and connected to the metal bottom plate **17** via a plurality of connection arms **118**. More specifically, the connection arms **118** respectively have an end connected to an outer periphery of the metal base **11** and another opposite end connected to an inner periphery of the first opening **171**, so as to support the metal base **11** in the first opening **171**. The metal bottom plate **17** includes a frame portion **172** extended along an outer edge thereof, such that a second opening **173** is formed on one side of the metal bottom plate **17** between two ends of the frame portion **172**.

In some embodiments, the metal base **11**, the heat conducting element **13**, and the metal bottom plate **17** can be made of any one of gold, silver, copper, aluminum, and iron, or any combination thereof.

In the first preferred embodiment shown in FIGS. 1A to 1C, the heat conducting element **13** is illustrated as having a round wall portion **131** forming a hollow cylinder, and an extended portion **132** horizontally extended toward a center of the hollow cylinder. However, in a motor bearing heat dissipation structure according to a second embodiment of the present invention, a differently configured heat conducting element **13a** as shown in FIG. 2A is included. FIG. 2C shows the manner in which the heat conducting element **13a** is enclosed in a correspondingly shaped plastic bearing cup **12a**, and FIG. 2D is an enlarged view of the circled area of FIG. 2C. As can be seen in FIG. 2A, the heat conducting element **13a** includes a wall portion **131a** and an extended portion **132a** similar to the wall portion **131** and the extended portion **132**, and defines a space **134a** therein. However, the wall portion **131a** is provided with a plurality of circumferentially spaced slots **135a**, which do not cut through a lower end **1311a** of the wall portion **131a** but are respectively extended from the wall portion **131a** to the extended portion **132a**. The plastic bearing cup **12a** has a lower portion **121a** partially radially inward extended through the slots **135a** into the space **134a** above the centered through hole **111**, and the lower portion **121a** of the plastic bearing cup **12a** also forms a sealing end **125a** to close the centered through hole **111** and a lower open side of the space **134a**. Further, a motor bearing heat dissipation structure according to a third embodiment of the present invention includes another differently configured heat conducting element **13b** as shown in FIG. 2B. The heat conducting element **13b** includes a wall portion **131b** and an extended portion **132b** similar to the wall portion **131a** and the extended portion **132a**. However, the wall portion **131b** is provided with a plurality of circumferentially spaced slots **135b**, which cut through a lower end **1311b** of the wall portion **131b** and are respectively extended from the wall portion **131b** to the extended portion **132b**, so that the heat conducting element **13b** is actually formed from a plurality of segments.

The present invention also provides a fan **20** using the motor bearing heat dissipation structure according to the present invention. FIGS. 3A and 3B are exploded and assembled sectional views, respectively, of a first embodiment of the fan **20**, which includes, in addition to the above-described motor bearing heat dissipation structure, a stator assembly **21** and a rotor assembly **22**. Since the motor bearing heat dissipation structure has been described in details above, it is not repeatedly discussed below.

The stator assembly 21 is fitted on around an outer side of the plastic bearing cup 12, and includes a plurality of silicon steel plates, insulation frames and windings, as well as a circuit board.

The rotor assembly 22 includes a fan hub 221 and a plurality of fan blades 222 circumferentially spaced on an outer side of the fan hub 221. The fan hub 221 is internally provided at a center with a rearward extended rotary shaft 223, which extends through the central bore 164 of the bearing 16. An end of the rotary shaft 223 that extends through the bearing 16 is provided with an annular retaining groove 2231 for a retaining ring 24 to set therein. The retaining ring 24 set in the annular retaining groove 2231 is upward pressed against the underside of the extended portion 132 to prevent the rotary shaft 223 from separating from the bearing 16. A magnetic element 224 is arranged on around an inner wall surface of the fan hub 221 corresponding to the stator assembly 21. The rotor assembly 22 can be an axial fan blade assembly or a centrifugal fan blade assembly.

A pad 25 can be provided on a top of the sealing element 14, so that the end of the rotary shaft 223 extended through the bearing 16 is pressed against the pad 25.

A top cover 26 having a third opening 261 is correspondingly closed onto the frame portion 172 of the metal bottom plate 17, so that a receiving space 27 is defined between the top cover 26, the metal bottom plate 17 and the frame portion 172. The third opening 261 and the first and second openings 171, 172 (see FIG. 1A) are communicable with the receiving space 27.

When the stator assembly 21 is supplied with an amount of current and becomes excited, it drives the rotor assembly 22 to rotate. At this point, the inner cylinder 161 of the bearing 16 rotates along with the rotary shaft 223. Heat produced by the bearing 16 when the inner cylinder 161 rotates is transferred to the metal base 11 and the metal bottom plate 17 via the extended portion 132 of the heat conducting element 13 to achieve the effect of heat dissipation, so as to protect the bearing 16 against damage due to overheating.

FIG. 4 is an assembled sectional view of a second embodiment of the fan 20, in which an end of a rotary shaft 223a thereof extended through the bearing 16 and the heat conducting element 13 is not provided with any annular groove, so that the retaining ring 24 in the first embodiment is omitted from the second embodiment.

FIG. 5 is an assembled sectional view of a third embodiment of the fan 20, in which the extended portion 132 of the heat conducting element 13 has a free end 1321c slightly radially inward extended beyond the inner cylinder 161 to engage with the annular retaining groove 2231 provided on the rotary shaft 231. Therefore, the heat conducting element 13 in the third embodiment of the fan 20 not only helps in dissipating heat from the bearing 16, but also functions like a retaining ring to prevent the rotary shaft 223 from separating from the bearing 16.

The present invention has been described with some preferred embodiments thereof and it is understood that many changes and modifications in the described embodiments can be carried out without departing from the scope and the spirit of the invention that is intended to be limited only by the appended claims.

What is claimed is:

1. A motor bearing heat dissipation structure being applied to a bearing having a bottom surface, comprising:
 - a metal base provided with a through hole;
 - a heat conducting element including a wall portion fixedly connected at a lower end to the metal base and an

extended portion horizontally formed on an upper end of the wall portion; and the extended portion having a free end and a top surface; and

- a plastic bearing cup including a lower portion, which encloses the wall portion of the heat conducting element therein and is fixed to the metal base; the plastic bearing cup upward extending from the lower portion and having an upper end located higher than the wall portion; the plastic bearing cup having an inner wall surface and internally defining a bearing receiving hole, which extends from the upper end of the plastic bearing cup into the lower portion thereof;

wherein the extended portion of the heat conducting element is extended from the upper end of the wall portion to horizontally radially inward project beyond the inner wall surface of the plastic bearing cup toward a center thereof, so that both the free end and the top surface of the extended portion are located in the bearing receiving hole; and the bearing being accommodated in the bearing receiving hole and seated on the extended portion with the bottom surface of the bearing being in contact with the top surface of the extended portion;

wherein the through hole of the metal base is located below the heat conducting element and the plastic bearing cup, and a space defined in the heat conducting element between an underside of the extended portion and an inner side of the wall portion to communicate with the bearing receiving hole in the plastic bearing cup and the through hole of the metal base.

2. The motor bearing heat dissipation structure as claimed in claim 1, wherein the wall portion is configured as a hollow cylinder.

3. The motor bearing heat dissipation structure as claimed in claim 2, wherein the extended portion of the heat conducting element is horizontally extended from the upper end of the wall portion toward a center of the hollow cylinder.

4. The motor bearing heat dissipation structure as claimed in claim 1, wherein a space is defined in the heat conducting element between an underside of the extended portion and an inner side of the wall portion to communicate with the bearing receiving hole in the plastic bearing cup and the through hole on the metal base.

5. The motor bearing heat dissipation structure as claimed in claim 4, further comprising a sealing element being correspondingly closed onto the through hole of the metal base to seal the through hole and a lower open side of the space in the heat conducting element.

6. The motor bearing heat dissipation structure as claimed in claim 4, wherein the wall portion of the heat conducting element is provided with a plurality of circumferentially spaced slots respectively extending from the wall portion to the extended portion; wherein the slots can be configured to cut through or not to cut through a lower end of the wall portion.

7. The motor bearing heat dissipation structure as claimed in claim 6, wherein the lower portion of the plastic bearing cup is partially radially inward extended through the slots into the space in the heat conducting element above the through hole of the metal base, and also forms a sealing end to close the through hole and the space.

8. The motor bearing heat dissipation structure as claimed in claim 1, wherein the wall portion of the heat conducting element is substantially perpendicular to the metal base.

9. The motor bearing heat dissipation structure as claimed in claim 1, wherein the bearing includes an inner cylindrical portion and an outer cylindrical portion, which together define the bottom surface of the bearing between them.

10. The motor bearing heat dissipation structure as claimed in claim 9, wherein the free end of the extended portion of the heat conducting element is located at a position corresponding to the inner cylindrical portion or between the inner cylindrical portion and the outer cylindrical portion.

11. The motor bearing heat dissipation structure as claimed in claim 9, wherein the free end of the extended portion of the heat conducting element is located at a position slightly radially inward protruded beyond the inner cylindrical portion to engage with an annular retaining groove formed on a rotary shaft that is received in the inner cylindrical portion.

12. The motor bearing heat dissipation structure as claimed in claim 1, further comprising a metal bottom plate, on which a first opening is provided; the metal base being located in the first opening and connected to the metal bottom plate via a plurality of connection arms; the connection arms respectively having an end connected to an outer periphery of the metal base and another opposite end connected to an inner periphery of the first opening, so as to support the metal base in the first opening.

13. The motor bearing heat dissipation structure as claimed in claim 12, wherein the metal bottom plate includes a frame portion extended along an outer edge thereof, such that a second opening is formed on one side of the metal bottom plate between two ends of the frame portion.

14. The motor bearing heat dissipation structure as claimed in claim 12, wherein the metal bottom plate is made of a material selected from the group consisting of gold, silver, copper, aluminum, and iron, and any combination thereof.

15. The motor bearing heat dissipation structure as claimed in claim 1, wherein the metal base and the heat conducting element are made of a material selected from the group consisting of gold, silver, copper, aluminum, and iron, and any combination thereof.

- 16. A fan, comprising:
 - a metal base provided with a through hole;
 - a heat conducting element including a wall portion fixedly connected at a lower end to the metal base and an extended portion horizontally formed on an upper end of the wall portion; and the extended portion having a free end and a top surface;
 - a plastic bearing cup including a lower portion, which encloses the wall portion of the heat conducting element therein and is fixed to the metal base; the plastic bearing cup upward extending from the lower portion and hav-

- ing an upper end located higher than the wall portion; the plastic bearing cup having an inner wall surface and internally defining a bearing receiving hole, which extends from the upper end of the plastic bearing cup into the lower portion thereof;
- a stator assembly being fitted on around an outer side of the plastic bearing cup;
- a bearing being received in the bearing receiving hole of the plastic bearing cup, and having a central bore and a bottom surface;
- a rotor assembly being correspondingly located around the stator assembly and including a rotary shaft, which extends through the central bore of the bearing;
- wherein the extended portion of the heat conducting element is extended from the upper end of the wall portion to horizontally radially inward project beyond the inner wall surface of the plastic bearing cup toward a center thereof, so that both the free end and the top surface of the extended portion are located in the bearing receiving hole; and
- wherein the bearing is seated on the extended portion with the bottom surface thereof being in contact with the top surface of the extended portion;
- wherein the through hole of the metal base is located below the heat conducting element and the plastic bearing cup, and a space defined in the heat conducting element between an underside of the extended portion and an inner side of the wall portion to communicate with the bearing receiving hole in the plastic bearing cup and the through hole of the metal base.
- 17. The fan as claimed in claim 16, wherein an end of the rotary shaft that is extended through the bearing is provided with an annular retaining groove.
- 18. The fan as claimed in claim 17, wherein the free end of the extended portion of the heat conducting element is extended into and engaged with the annular retaining groove formed on the rotary shaft.
- 19. The fan as claimed in claim 17, further comprising a retaining ring set in the annular retaining groove.
- 20. The fan as claimed in claim 16, wherein the free end of the extended portion of the heat conducting element is extended to a position corresponding to the inner cylindrical portion or between the inner cylindrical portion and the outer cylindrical portion.

* * * * *