



US009114857B2

(12) **United States Patent**
Miller et al.

(10) **Patent No.:** **US 9,114,857 B2**
(45) **Date of Patent:** **Aug. 25, 2015**

(54) **EASY-UP SWIM HANDLES**

(76) Inventors: **Rodger E. Miller**, Chesapeake Beach, MD (US); **Carol E. Cook**, Chesapeake Beach, MD (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/137,601**

(22) Filed: **Aug. 29, 2011**

(65) **Prior Publication Data**

US 2012/0048174 A1 Mar. 1, 2012

Related U.S. Application Data

(60) Provisional application No. 61/377,508, filed on Aug. 27, 2010, provisional application No. 61/457,586, filed on Apr. 25, 2011.

(51) **Int. Cl.**
B63B 17/00 (2006.01)
B63B 27/14 (2006.01)

(52) **U.S. Cl.**
CPC **B63B 27/146** (2013.01)

(58) **Field of Classification Search**
USPC 114/362, 364, 218
IPC B63B 27/14, 27/146
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,669,733	A *	2/1954	Picker	114/362
4,672,909	A *	6/1987	Sweetsir	114/218
5,813,504	A *	9/1998	Iny et al.	190/116
7,444,954	B1 *	11/2008	Resta	114/362
2008/0087211	A1 *	4/2008	Sutherland et al.	114/364
2008/0314310	A1 *	12/2008	Little et al.	114/364

* cited by examiner


Primary Examiner — Stephen Avila

(74) *Attorney, Agent, or Firm* — William H. Holt

(57) **ABSTRACT**

Various designs and arrangements of preferably tubular handle members are detachably mounted upon the swim platform of a boat for aiding swimmers to enter and/or exit from the water. In one embodiment the handles have an end, or ends, thereof slidably mountable within a tubular portion of a socket member that is preferably secured in a counter-sunk fashion in the swim platform. In a further embodiment handles are provided with an end lug for detachably mounting the handle to a mounting plate. When not in use, the handle members are slidably detached from the mounting members thereby providing an unencumbered surface on the swim platform.

13 Claims, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 12




FIG. 11

1

EASY-UP SWIM HANDLES

RELATED APPLICATIONS

Provisional Application 61/377,508 filed Aug. 27, 2010 ⁵
and Provisional application 61/457,586 filed Apr. 25, 2011.

BACKGROUND OF THE INVENTION

Pleasure crafts, in the nature of small power boats and/or ¹⁰
sail boats, have been provided with a swim platform for
accommodating swimmers for entering and exiting the water
while the craft is anchored or free floating. The swim platform
is usually at the stern of the craft, but it may also be located
along a side or front thereof. A number of devices have been ¹⁵
designed in the form of a ladder, or the like, and proposed for
attachment to the swim platform and may be extendable into
the water and below the surface thereof for assisting in enter-
ing or, primarily, for exiting the water and climbing upon the
swim platform.

Generally speaking, such devices fall short of providing a
reasonably safe means for prevention of slips and falls on the
wet surface of the swim platform which can result in severe
injury.

SUMMARY OF THE INVENTION

The present invention provides several forms and styles of
handles which are designed for being securely affixed upon
conventional swim platforms and readily detached therefrom ²⁵
for storage and the like thereby resulting in an unobstructed
surface on the swim platform when the handles are not in use.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a typical swim platform
which, for simplicity, is shown unattached to a boat and
includes a pair of U-shaped handles mounted thereon adjac- ³⁰
ent to the stern portion and showing the ends of the handles
assembled upon the swim platform.

FIG. 2 is a perspective view of a swim platform similar to
the showing in FIG. 1 and showing a pair of generally
P-shaped handles, each having one end thereof mounted near
the marginal portion of the swim platform.

FIG. 3 is a perspective view similar to FIGS. 1 and 2 ³⁵
showing an embodiment of the invention wherein a combi-
nation of a U-shaped handle and a P-shaped handle provide a
modified arrangement of handles for assisting a swimmer to
exit from the water and gain access to the swim platform and
the boat.

FIG. 4 illustrates a U-shaped handle and an accompanying
flanged socket member that is used for providing a mounting,
or securing member, to which an end of the handle is readily
insertable into and detachable therefrom.

FIG. 5 illustrates the socket member having one end of the
handle being slidably received therein.

FIG. 6 illustrates a flanged socket member located in an
upside down position for showing a drain hole in the bottom
surface thereof for allowing water to escape from the interior
volume of the socket member.

FIG. 7 is a side view of the flanged socket member showing
the hollow interior thereof and a plurality of holes for receiv-
ing bolts to secure the socket member to the swim platform as
shown in FIGS. 1-3.

FIG. 8 shows a socket member in an upright position prior ⁶⁵
to being counter-sunk below a surface of the swim platforms
of FIGS. 1-3.

2

FIG. 9 is a fragmentary view, partly in section of a modified
design of a P-shaped handle and shows one end thereof being
slidably mounted within a socket member that is counter-
sunk within a swim platform and secured thereto by a plural-
ity of threaded nuts and bolts which cooperate with a lower-
most support ring for securely clamping the socket member to
the swim platform.

FIG. 10 illustrates a modified arrangement of a flanged
socket member having exterior screw threads formed on a
tubular portion adjacent a lower portion thereof for cooper-
ating with internal screw threads formed on the interior cylin-
drical surface of a support ring surrounding and reinforcing
the lower portion of the socket member.

FIG. 11 illustrates a further embodiment wherein a secur-
ing member, or plate member, includes a varied size slot for
receiving and securing a lug portion of a handle.

FIG. 12 illustrates handle members that are provided with
a securing lug for use with the plate member of FIG. 11.

DESCRIPTION OF PREFERRED
EMBODIMENTS

FIG. 1 shows a swim platform 10 which, in a known man-
ner, is to be attached unto the stern of a power boat or sail boat
(not shown). Such platforms are known in the prior art and are
useful for aiding swimmers to enter the water and return to the
boat safely. An example of a similar swim platform is shown
in U.S. Pat. No. 4,907,673. The top surface of the platform 10 ²⁵
is usually in a wet and somewhat slippery condition; this can
readily lead to slips and falls with consequent injury.

In order to preclude or minimize injury to swimmers, and/
or boatmen, a pair of tubular, U-shaped handles 12 and 14 are
shown in FIG. 1 as being placed parallel to each other in a
vertical, upstanding, spaced relation and have their ends
mounted in a series of securing or socket members 16 that are
recessed within and secured to the swim platform 10. Handles
12 and 14 are located adjacent an edge of the platform 10 in a
position that they can be readily grasped by a swimmer who
wishes to exit the water and climb upon the swim platform 10 ³⁰
of the boat. It is known in the prior art to provide a ladder or
an arrangement of steps that can be secured to a swim plat-
form, or to the boat, but such devices are not part of the
present invention.

It is to be understood that the ends of handles 12 and 14 are
not fixedly secured to the securing or socket members 16.
Rather, as will be later explained in more detail, the ends of
handles 12 and 14 are slidably received in the sockets 16 and
are easily removed therefrom to allow for safe storage upon ³⁵
the boat, thus leaving the top surface of swim platform 10 in
a smooth and unencumbered condition.

FIG. 2 shows a pair of generally P-shaped handles 20 and
22 arranged in parallel fashion upon swim platform 10 and
having their lower ends slidably mounted within socket mem-
bers 16 in a like manner to the arrangement in FIG. 1. The
embodiment of FIG. 2 reduces the number of necessary
socket members 16 to only two, rather than four as shown in
FIG. 1. Of course, costs involved in recessing the socket
members 16 into the swim platform are also halved.

FIG. 3 illustrates a further modification of the invention
wherein a single U-shaped handle 14 is used in combination
with a single P-shaped handle 22. This arrangement allows
for handle 22 to be rotatable toward and away from the
U-shaped handle 14 which is stable, and non-rotatable,
because the lower two ends are located within a pair of socket
members 16. This arrangement allows a person standing upon

3

swim platform **10** to hold onto U-shaped handle **14** to aid and assist a swimmer holding onto P-shaped handle **22** while exiting the water.

FIG. **4** shows a U-shaped handle **22** and a socket member **16** separated from each other.

FIG. **5** shows a U-shaped handle **22** having a socket member **16** slidably mounted upon one end of handle **22**.

FIGS. **6**, **7** and **8** are perspective views showing details of a socket member **16** which is preferably formed of stainless steel but which may be constructed from other metals or plastics and preferably is provided with a protective coating such as a wear resistant epoxy, or the like. Socket member **16** is comprised of a hollow, cylindrical, tubular stem **30** having a flange portion **32** integral therewith, such as by being welded or swaged thereto, or formed integral by a stamping operation, or molded from metal or plastic. Flange **32** may be provided with a plurality of holes **34** to accommodate either bolts or screws for attaching socket member **16** to the upper surface of swim platform **10**. As is best shown in FIG. **6**, socket member **16** is shown in an upside down position to show a closed end **35** which provides strength to the tubular stem **30**, limits travel of the lower end of the handles **12**, **14**, **20** and **22**, and includes a drain hole **36** passing through closed end **35** for allowing water to drain from tubular stem **30**.

FIG. **9** illustrates a modified handle design wherein a generally P-shaped handle **40** includes a vertical leg **42** for being slidably and rotatably located in socket member **16** and a reversely turned arm **44** having a free end located closely adjacent to vertical leg **42** for forming a substantially closed loop for handle **40**. Leg **42** is shown as being shorter in length than the arms shown in FIGS. **1-5** thereby providing a lower profile.

FIG. **9** also shows details of the manner in which socket member **16** is mounted within swim platform **10**. It is seen that a plurality of threaded fasteners, such as bolts **50**, are counter-sunk within flange **32** and pass through holes **34** (see FIGS. **6-8**) for providing a smooth upper surface and are secured at their lower end by threaded nuts **52**. It is preferred that a reinforcing plate member **64** is provided for effectively clamping the socket member **16** to the swim platform **10**.

FIG. **10** shows a modified socket member **116**, partly in section, to be located within and secured to the swim platform **10** for receiving a lower end of the various, previously described handles. As shown, socket member **116** includes a depending, hollow stem **130**, a closed end **135** having a drain hole **136** therethrough, and an upper flange member **132**. Stem **130** includes a threaded portion **150** at a lowermost, outer portion thereof for cooperating with internal threads **152** provided within a reinforcing plate member **154**. Threading plate member **154** onto stem **130** effectively secures socket member to the swim platform **10** without a requirement for the nuts and bolt required by the socket member **16**.

FIGS. **11** and **12** show a modified form of the invention wherein U-shaped railings or handles **160** cooperate with individual mounting or securing members in the form of plate members **162** that can be secured to the swim platform **10** of FIG. **1** by a plurality of bolt members **164**. The railings or handles **160** are shown in FIG. **12** as having generally enlarged knobs, or lugs, **166** which are adapted to be inserted into enlarged openings **168** of the plate members **162** and then slid into narrow openings **170** such that the lugs **166** releasably secure the handles **160** to the plate members **162**. While U-shaped handles **160** are shown in FIG. **12** as each having a pair of lugs **166**, it is to be understood that only a single lug may be used. Likewise, P-shaped handles similar to handles

4

20 and **22** in FIG. **3** can be used and provided with only a single lug **166** for being secured to a plate member **162**.

Various modifications to the foregoing described elements of the invention may become obvious to those skilled in the respective art without departing from the spirit and scope of the invention as defined by the appended claims.

We claim:

1. Apparatus for being attached to a swim platform of a boat, said apparatus being comprised of at least one handle member for aiding an individual to enter and exit from the water and to climb aboard said boat, and having at least one mounting member for each said handle member, each said mounting member having means for securing it to said swim platform and including an opening for slidably and releasably receiving an end of said handle member, said end of said handle member being readily insertable into said mounting member for ease of mounting said handle member and being readily, slidably, removed from said mounting member by simply lifting said handle member from said mounting member without the need of removing fasteners for placing said handle member in storage, whereby said swim platform has an unobstructed surface when said handle member is not in use; said mounting member being comprised of a cup-shaped member having a tubular portion providing said opening for slidably receiving said end of said handle member, said mounting member including an outwardly extending flange member at one end thereof for securing said mounting member to said swim platform; said flange containing a plurality of openings for receiving threaded fasteners for securing said mounting member to said swim platform; said flange member being counter-sunk into the surface of said swim platform for providing an unobstructed surface; said apparatus further including a pair of handle members, wherein one handle member is U-shaped and a second handle member is P-shaped, and said U-shaped member includes a pair of end portions which are attachable to said swim platform for precluding rotation thereof.

2. Apparatus as defined in claim **1** wherein said cup-shaped member includes a closed end for providing strength to said tubular portion, and an opening in said closed end for providing an outlet for allowing water to drain therefrom.

3. Apparatus as defined in claim **1** wherein said tubular portion contains exterior screw threads thereon, and said apparatus further includes an internally threaded support ring for securing said cup-shaped member to said swim platform.

4. Apparatus as defined in claim **1** wherein said mounting member is comprised of a plate member including a varied sized slot, and said handle having a lug portion on at least one end thereof for slidably fitting within said varied sized slot for detachably mounting said handle upon said plate member.

5. Apparatus as defined in claim **1** wherein said handle member is U-shaped, and each end thereof is mounted within a cup-shaped member for precluding rotation of said U-shaped handle.

6. Apparatus as defined in claim **1** wherein said handle member is P-shaped, and one end thereof is mounted within a cup-shaped member for allowing rotation of said handle member therein.

7. Apparatus for being attached to a swim platform of a boat, said apparatus being comprised of at least one handle member for aiding an individual to enter and exit from the water and to climb aboard said boat, and having at least one mounting member for each said handle member, each said mounting member having means for securing it to said swim platform and including an opening for slidably and releasably receiving an end of said handle member, said end of said handle member being slidably insertable into said mounting

5

member for ease of mounting said handle member and being readily, slidably, removable from said mounting member by simply lifting said handle member from said mounting member without the need of removing fasteners for placing said handle member in storage, whereby said swim platform has an unobstructed surface when said handle member is not in use; said mounting member being comprised of a cup-shaped member having a tubular portion providing said opening for slidably receiving said end of said handle member, said mounting member including an outwardly extending flange member at one end thereof for securing said mounting member to said swim platform.

8. Apparatus as defined in claim 7 wherein said flange contains a plurality of openings for receiving threaded fasteners for securing said mounting member to said swim platform; said flange member being counter-sunk into the surface of said swim platform for providing an unobstructed surface.

9. Apparatus as defined in claim 7 wherein said cup-shaped member includes a closed end for providing strength to said

6

tubular portion, and an opening in said closed end for providing an outlet for allowing water to drain therefrom.

10. Apparatus as defined in claim 7 wherein said tubular portion contains exterior screw threads thereon, and said apparatus further includes an internally threaded support ring for securing said cup-shaped member to said swim platform.

11. Apparatus as defined in claim 7 wherein said mounting member is comprised of a plate member including a varied sized slot, and said handle having a lug portion on at least one end thereof for slidably fitting within said varied sized slot for detachably mounting said handle upon said plate member.

12. Apparatus as defined in claim 7 wherein said handle member is U-shaped, and each end thereof is mounted within a cup-shaped member for precluding rotation of said U-shaped handle.

13. Apparatus as defined in claim 7 wherein said handle member is P-shaped, and one end thereof is mounted within a cup-shaped member for allowing rotation of said handle member therein.

* * * * *