

(12) **United States Patent**  
**Schmid**

(10) **Patent No.:** **US 9,061,457 B2**  
(45) **Date of Patent:** **Jun. 23, 2015**

(54) **STRIPPER SLEEVE**

USPC ..... 425/441, DIG. 58  
See application file for complete search history.

(75) Inventor: **Markus Schmid**, Dietmanns (AT)

(73) Assignee: **Husky Injection Molding Systems Ltd.**, Bolton, Ontario (CA)

(56) **References Cited**

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

U.S. PATENT DOCUMENTS

(21) Appl. No.: **14/237,233**

(22) PCT Filed: **Jul. 25, 2012**

(86) PCT No.: **PCT/CA2012/050500**

§ 371 (c)(1),  
(2), (4) Date: **Feb. 5, 2014**

4,526,282	A *	7/1985	Dutt et al.	215/252
4,793,499	A	12/1988	Dubach et al.	
4,881,892	A	11/1989	Webster et al.	
5,086,938	A *	2/1992	Aichinger	215/252
5,230,856	A *	7/1993	Schellenbach	264/328.1
5,240,719	A *	8/1993	Hedgewick	425/556
5,281,385	A *	1/1994	Julian	264/318
5,833,912	A *	11/1998	Schweigert et al.	264/318
6,413,075	B1 *	7/2002	Koch et al.	425/526
6,450,797	B1	9/2002	Joseph	
7,128,865	B2 *	10/2006	Martin	264/318
7,429,170	B2 *	9/2008	Rote et al.	425/350
7,510,677	B2	3/2009	Miller et al.	
2012/0135102	A1 *	5/2012	Glaesener	425/556
2012/0251656	A1 *	10/2012	Wang et al.	425/556

(87) PCT Pub. No.: **WO2013/029167**

PCT Pub. Date: **Mar. 7, 2013**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2014/0178521 A1 Jun. 26, 2014

PCT International Search Report; Cuerrier, Pierre; 3 pages; Aug. 20, 2012.

**Related U.S. Application Data**

\* cited by examiner

(60) Provisional application No. 61/528,803, filed on Aug. 30, 2011.

*Primary Examiner* — Yogendra Gupta  
*Assistant Examiner* — Emmanuel S Luk

(51) **Int. Cl.**  
*B29C 45/44* (2006.01)  
*B29C 33/44* (2006.01)  
*B29L 31/56* (2006.01)  
*B29C 45/40* (2006.01)


(57) **ABSTRACT**

(52) **U.S. Cl.**  
CPC ..... *B29C 45/4407* (2013.01); *B29C 33/444* (2013.01); *B29L 2031/565* (2013.01); *B29C 2045/4078* (2013.01)

There is provided a molding stack (102). The molding stack (102) comprises a stripper sleeve (122) that is movable to contact a molded article (114) after the molding thereof; the stripper sleeve (122) having a first surface (204) and a second surface (206) for simultaneously contacting a side and an underside surface, respectively, of the molded article (114) during the stripping of the molded article (114).

(58) **Field of Classification Search**  
CPC ..... B29C 45/4407; B29C 2045/4407; B29C 2045/4078; B29C 33/444; B29L 2031/565

**2 Claims, 2 Drawing Sheets**







FIG. 1



**FIG. 2**

1

## STRIPPER SLEEVE

## TECHNICAL FIELD

The non-limiting embodiments disclosed herein generally relate to the structure and operation of a molding apparatus, and more particularly to a stripper sleeve.

## BACKGROUND

Molding is a process by virtue of which a molded article can be formed from molding material by using a molding system. Various molded articles can be formed by using the molding process, such as an injection molding process. One example of a molded article that can be formed, for example, from polypropylene (PP material) is a closure suitable for capping, in use, a beverage container, such as, a container for still water or a carbonated drink.

A typical molding system includes inter alia an injection unit, a clamp assembly and a mold assembly. The injection unit can be of a reciprocating screw type or of a two-stage type. Within the reciprocating screw type injection unit, raw material (such as PP, PET or the like) is fed through a hopper, which in turn feeds an inlet end of a plasticizing screw. The plasticizing screw is encapsulated in a barrel, which is heated by barrel heaters. Helical flights of the screw convey the raw material along an operational axis of the screw. Typically, a root diameter of the screw is progressively increased along the operational axis of the screw in a direction away from the inlet end.

As the raw material is being conveyed along the screw, it is sheared between the flights of the screw, the screw root and the inner surface of the barrel. The raw material is also subjected to some heat emitted by the barrel heaters and conducted through the barrel. As the shear level increases in line with the increasing root diameter, the raw material, gradually, turns into substantially homogenous melt. When a desired amount of the melt is accumulated in a space at discharge end of the screw (which is an opposite extreme of the screw vis-à-vis the inlet end), the screw stops its rotation. The screw is then forced forward (in a direction away from the inlet end thereof), forcing the desired amount of the melt into one or more molding cavities. Accordingly, it can be said that the screw performs two functions in the reciprocating type injection unit, namely (i) plasticizing of the raw material into a substantially homogeneous melt and (ii) injecting the substantially homogeneous melt into one or more molding cavities.

U.S. Pat. No. 6,450,797 issued to Joseph on Sep. 17, 2002 teaches a molding apparatus that has a pair of slide inserts which are laterally movable into and out of engagement with the other mold components. The lateral movement of the slide inserts is provided by a slide mechanism having a driving rack, a pair of drive pinions at either end of the driving rack, two pairs of driven racks and a plurality of slides connected to the driven racks. The driven racks of each pair are parallel and spaced from one another, engaging opposite sides of a pinion and thereby being driven in opposite directions by rotation of the pinion. The molding apparatus is more compact than conventional devices having slide inserts, eliminates the use of slide retainers, eliminates obstructions between the mold plates when the plates are separated, and can cycle faster than conventional devices.

U.S. Pat. No. 7,510,677 issued to Miller, et al. on Mar. 31, 2009 discloses an injection molding method and apparatus for ejecting a molded plastic article from a mold. A lifting structure and/or step is provided with a lifting portion which

2

is configured to contact substantially one half of an end of the molded plastic article along a line substantially perpendicular to the lifting direction. Since the molded plastic article is lifted by its end, the article does not have to be solidified at its interior, thus allowing earlier removal of the article from the mold, reducing cycle time. A tapered surface forms an acute angle with respect to the lifting portion to form a tight seal with the mold, preventing leakage. Preferably, the neck ring engages only an outer circumferential portion of the molded plastic article during a majority of a mold opening stroke.

U.S. Pat. No. 4,881,892 issued to Webster, et al. on Nov. 21, 1989 teaches a mold for forming a plastic closure includes a first mold part defining a female cavity and a second mold part defining a male mold cavity surface, with the second mold part including a core having a knock-out pin reciprocated therein and surrounded by a fixed sleeve which cooperate to define a tamper evident band on the cavity for the closure. Vents are provided for venting the lower edge of the cavity during the ejection-molding process. Also, the knock-out pin has a lubricant pocket formed on the peripheral surface thereof.

## SUMMARY

According to a first broad aspect of the present invention, there is provided a molding stack. The molding stack comprises a stripper sleeve that is movable to contact a molded article after the molding thereof; the stripper sleeve having a first surface and a second surface for simultaneously contacting a side and an underside surface, respectively, of the molded article during the stripping of the molded article.

According to a second broad aspect of the present invention, there is provided a stripper sleeve for use in the molding stack, the stripper sleeve being configured to be movable to contact a closure after the molding thereof, the stripper sleeve comprising: a pocket having a first surface and a second surface for simultaneously contacting a side and an underside surface, respectively, of the closure during the stripping of the closure.

These and other aspects and features will now become apparent to those skilled in the art upon review of the following description of specific non-limiting embodiments in conjunction with the accompanying drawings.

## DETAILED DESCRIPTION OF THE DRAWINGS

The detailed description of illustrative (non-limiting) embodiments will be more fully appreciated when taken in conjunction with the accompanying drawings, in which:

FIG. 1 depicts a schematic representation of a cross-section of a portion of a molding stack, taken along operational axis thereof, the molding stack being implemented in accordance with various non-limiting embodiments of the present invention.

FIG. 2 depicts a portion of the molding stack of FIG. 1 in greater detail.

The drawings are not necessarily to scale and may be illustrated by phantom lines, diagrammatic representations and fragmentary views. In certain instances, details that are not necessary for an understanding of the embodiments or that render other details difficult to perceive may have been omitted.

## DETAILED DESCRIPTION OF THE NON-LIMITING EMBODIMENT(S)

FIG. 1 depicts a schematic representation of a cross-section of a portion of a molding stack 102, taken along operational

axis thereof, the molding stack **102** being implemented in accordance with various non-limiting embodiments of the present invention. The molding stack **102** can be part of a mold (not depicted) that is positionable within a clamp (not depicted) of an injection molding machine (not depicted). It is noted that the implementation of the mold, the clamp and the injection molding machine can be typical to that of prior art implementations and, as such, will not be described here at any length. It is also noted that embodiments of present invention can be used within various implementations of the mold, such as, an injection mold, an injection-compression mold, a compression mold, a transfer-molding mold and the like (as well, as the associated machines).

The molding stack **102** includes a core assembly **104** and a cavity assembly **106**. Starting with the cavity assembly **106**, the cavity assembly **106** comprises a gate insert **108** and a cavity insert **110**. The general purpose for the gate insert **108** is to receive, in use, a nozzle of a hot runner (both not depicted) and for providing a path for molten material into a molding cavity **112**. The cavity insert **110** defines a portion of the molding cavity **112** and, more specifically, an outside wall of a top panel and a side skirt of a molded article **114**, which molded article **114** is defined within the molding cavity **112**. Within this illustration, molded article **114** comprises a closure **114** of a types suitable for capping a beverage container and the like. The cavity insert **110** also comprises cooling channels through which an appropriate coolant media (such as water and the like) can be circulated during appropriate portions of the molding cycle.

The core assembly **104** comprises a first inner core **116**, a second inner core **118**, an outer core **120**, a stripper sleeve **122** and a pair of split inserts **124**. Since the general function of the components of the core assembly **104** is known to those of ordinary skill in the art, only a brief description thereof will be presented here.

The purpose of the first inner core **116** is to define an inner portion of the top panel of the closure **114**. In the specific embodiment of the present invention, the first inner core comprises a first inner core portion **126** and a second inner core portion **128**. In a specific example provided herewith, the first inner core portion **126** and the second inner core portion **128** can be made of different materials, such as materials with different thermal conductivity, materials with different wear resistance and the like. In a specific embodiment, the first inner core portion **126** and the second inner core portion **128** can be made of different materials to improve heat dissipation between portions thereof. In a specific non-limiting embodiment of the present invention, the first inner core portion **126** can be made of stainless steel (DIN: 1.4528) and the second inner core portion **128** can be made of AMPCOLOY 940.

In alternative embodiments of the present invention, the first inner core **116** can be made up of more than two portions or be of unitary structure. It is noted that the first inner core **116** is configured, under motive of an actuator (not depicted) to move in an axial direction, i.e. left and right as viewed in FIG. 1. The first inner core **116** comprises an inner cooling channel (not separately numbered) through which an appropriate coolant media (such as water and the like) can be circulated during appropriate portions of the molding cycle.

The purpose of the second inner core **118** is to define a portion of the top panel (not separately numbered) of the closure **114**. The second inner core **118** also defines a portion of a plug seal (not separately numbered), which plug seal depends from the top panel of the closure **114**. The second inner core **118** is stationary, within the depicted embodiments of the present invention.

The purpose of the outer core **120** is to define (i) another portion of the plug seal and the top panel of the closure **114** (including the centering ring thereof), (ii) an inner portion of a skirt (not separately numbered) of the closure **114** (including features of a thread finish) and (iii) a bottom-most portion of a tamper evident band of the closure **114**. Within the specific embodiment illustrated herein, the outer core **120** comprises a first outer core portion **130** and a second outer core portion **132**. In a specific example provided herewith, the first outer core portion **130** and the second outer core portion **132** can be made of different materials, such as materials with different thermal conductivity, materials with different wear resistance and the like. In a specific embodiment, the first outer core portion **130** and the second outer core portion **132** can be made of different materials to improve heat dissipation between portions thereof. In a specific non-limiting embodiment of the present invention, the first outer core portion **130** can be made of stainless steel (DIN: 1.2767) and the second outer core portion **132** can be made of AMPCOLOY 940.

In alternative embodiments of the present invention, the outer core **120** can be made up of more than two portions or be of unitary structure. As such, within embodiments of the present invention, the first outer core portion **130** is configured to define the bottom-most portion of the closure **114** and a portion of the inner portion of the skirt. The second outer core portion **132** is configured to define the portion of the plug seal, another portion of the inner portion of the skirt and the portion of the top panel of the closure **114**. It is noted that the outer core **120** is configured, under motive of an actuator (not depicted) to move in an axial direction, i.e. left and right as viewed in FIG. 1.

The purpose of the pair of split inserts **124** is to define a portion of the outer portion of the skirt of the closure **114**, including but not limited to a tamper evident band and bridges connecting the tamper evident band to the remainder of the skirt of the closure **114**. The pair of split inserts **124** are configured, under motive of an actuator (not depicted) to move in a traverse direction, i.e. up and down as viewed in FIG. 1.

The purpose of the stripper sleeve **122** is to assist in stripping the closure **114** off the molding stack **102**, as will be described in detail momentarily. The stripper sleeve **122** is configured, under a motive of an actuator (not depicted) to move in an axial direction, i.e. left and right as viewed in FIG. 1. More specifically, the stripper sleeve **122** is configured to move between a “retracted configuration” depicted in FIG. 1 and an “extended configuration”, which is not depicted, but which is generally located axially towards right, as viewed in FIG. 1.

According to embodiments of the present invention and is best seen in FIG. 2, which FIG. 2 depicts a portion of the molding stack **102** in greater detail. The stripper sleeve **122** comprises a pocket **202**. The pocket **202** is defined by a first axial wall **204** and a second traverse wall **206**. In use, during the part ejection function, the stripper sleeve **122** is extended, under the motive of an actuator (not depicted) towards the extended configuration, in which extended configuration the stripper sleeve **122** engages the bottom-most portion of the closure **114**. More specifically, the pocket **202** engages the bottom-most portion of the closure **114**. Even more specifically and in accordance with embodiments of the present invention, the second traverse wall **206** engages the underside of the bottom-most portion of the tamper evident band of the closure **114** and, effectively, pushes it to the right, as viewed in FIG. 1, with further movement of the stripper sleeve **122**. At the same time, the first axial wall **204** engages a side portion of the taper evident band. Even more specifically, the first

axial wall **204** provides a stopper (i.e. a physical stop) which delimits the extent of radial travel of the tamper evident band, which radial travel occurs as the closure **114** is stripped off the molding stack **102** and, especially, as portions of the closure **114** clear portions of the outer core **120** (such as portions of the first outer core portion **130**). For the avoidance of doubt, the term “radial travel” means travel in a direction that is traverse to the axis of the molding stack **102**.

It is noted that even though in the specific embodiment being depicted herein, the first axial wall **204** and the second traverse wall **206** are inter-disposed at a **90** degree angle therebetween, this does not need to be so in every embodiment of the present invention. As such, it should be expressly understood that in alternative embodiments of the present invention, the first axial wall **204** and the second traverse wall **206** can be inter-disposed at a different angle therebetween.

Accordingly, it can be said that the stripper sleeve **122** is movable to contact a molded article **114** after the molded article **114** has been molded or, in other words, the stripper sleeve **122** does not define any portion of the molding cavity **112** during molding of the molded article **114**. It can be further said that the stripper sleeve **122** comprises a first surface (i.e. the first axial wall **204**) and a second surface (i.e. the second traverse wall **206**), which first and second surfaces engage simultaneously, during stripping of the molded article **114**, a side surface and an underside of the molded article **114** (and more specifically, the underside and the side portion of the bottom-most portion of the closure **114**, i.e. the tamper evident band of the closure **114**).

To this end, the depth of the pocket **202**, or more specifically the distance between an edge **208** and the first axial wall **204** is such as (i) to allow the portion of the closure **114** to deflect in the direction “A” to clear certain features of the outer core **120** (i.e. the first outer core portion **130**), and (ii) to prevent significant damage attributable to “over-deflection” of the portion of the closure **114** in the direction “A”, typically associated with prior art executions of the molding stack **102**. The extent of “allowable” travel for the portion of the closure **114** is shown in FIG. 2 as “B”.

Having described the structure of the non-limiting embodiments of the molding stack **102**, a brief description of the operational sequence thereof, in the context of part ejection, will be presented herein.

#### Mold Closed, Molding and Cooling

The molding process starts with urging the molding stack **102** into a mold closed position, as is depicted in FIG. 1. The molding stack **102** is actuated into and maintained in the mold closed configuration by a clamp arrangement (not depicted) under sufficient clamp tonnage (i.e. tonnage sufficient to withstand injection pressure of the molding material). More specifically, the core assembly **104** and the cavity assembly **106** are urged in the mold closed configuration, whereby the molding cavity **112** is defined and is available for acceptance of the molding material.

Then, in the mold closed configuration, molding material is injected, under pressure, into the molding cavity **112** via an orifice (not separately numbered) in the gate insert **108**. The molding material is then allowed to cool down and, typically, as the molding material solidifies and cools down it shrinks. As such, in some embodiments of the present invention, a packing function is executed, whereby extra molding material is injected into the molding cavity **112** to compensate for the molding material shrinkage.

The molding material is allowed to cool down to a temperature whereby it is safe to eject the molded article **114** without significant structural damage thereto.

#### Molded Article Ejection

At this point, where the molding material has sufficiently cooled down and the molded article **114** has sufficiently solidified for safe ejection thereof, the process of molded article ejection commences.

First, clamp tonnage is released. Next, a core plate (not depicted) accommodating the core assembly **104** is urged away from a cavity plate (not depicted) accommodating the cavity assembly **106** or vice versa, the cavity plate can be urged away from the core plate. Since the molded article **114** tends to shrink as it cools down and due to the number of undercuts associated with the closure **114**, the closure **114** tends to stay associated with the core assembly **104**.

Once the closure **114** has sufficiently cleared the portion of the molding cavity **112** associated with the cavity insert **110**, the split inserts **124**, under control of the appropriate actuator (not depicted) are urged transversely away from the outer core **120**, thus releasing the undercuts of the tamper evident band of the closure **114**.

Next, under the motive of the appropriate actuator (not depicted), the stripper sleeve **122** is actuated into the extended configuration, whereby the pocket **202** engages the bottom-most portion of the closure **114**.

Next, the first inner core **116**, the outer core **120** and the stripper sleeve **122** move in unison to effectively release the plug seal of the closure **114** from in-between the second inner core **118** and the outer core **120** (recalling that within these embodiments of the present invention, the second inner core **118** is stationary).

Once the plug seal of the closure **114** is released, the outer core **120** becomes immobile (for example, by means of actuator stopping it or by means of a physical stop), and the first inner core **116** and the stripper sleeve **122** continue to move. In some embodiments of the present invention, the first inner core **116** and the stripper sleeve **122** continue to move in unison until the closure **114** is stripped off the first inner core **116**. In other embodiments, the first inner core **116** can, at some point, become immobile (for example, by means of actuator stopping it or by means of a physical stop), and the stripper sleeve **122** completing the stripping action.

Effectively, at this point, the closure **114** is released (or stripped off) the molding stack **102**.

It is noted that a specific technical advantage associated with embodiments of the present invention includes, alleviation of certain defects associated with the closure **114** with the prior art solutions and, specifically, defects attributable to over-stretching of the tamper evident band of the closure **114** during stripping thereof.

It is noted that the foregoing has outlined some of the more pertinent non-limiting embodiments. These non-limiting embodiments may be used for many applications. Thus, although the description is made for particular arrangements and methods, the intent and concept of these non-limiting embodiments may be suitable and applicable to other arrangements and applications. It will be clear to those skilled in the art that modifications to the disclosed non-limiting embodiments can be effected. The described non-limiting embodiments ought to be construed to be merely illustrative of some of the more prominent features and applications thereof. Other beneficial results can be realized by applying these non-limiting embodiments in a different manner or modifying them in ways known to those familiar with the art. This includes the mixing and matching of features, elements and/or functions between various non-limiting embodiments is expressly contemplated herein, unless described otherwise, above.

What is claimed is:

1. A molding stack, comprising:  
 a stripper sleeve that is movable to contact a molded article after the molding thereof;  
 the stripper sleeve having a first surface and a second surface for simultaneously contacting a side and an underside surface, respectively, of the molded article during the stripping of the molded article;  
 wherein the stripper sleeve comprises a pocket, which pocket defines the first surface and the second surface;  
 wherein the first surface comprises a first axial wall, the first axial wall being configured to engage the side portion of a tamper evident band of a closure;  
 wherein the first axial wall provides a stopper, which delimits an extent of radial travel of the tamper evident band of the closure during stripping thereof;  
 wherein the pocket is associated with a depth, which depth represents a distance between an edge of the second surface where it meets an inner surface of the stripper sleeve and the first axial wall, whereby the depth is selected such as (i) to allow the portion of the tamper evident band of the closure to deflect in a direction to clear a feature of the molding stack, and (ii) to prevent significant damage attributable to “over-deflection” of the portion of the tamper evident band of the closure in the direction;  
 wherein the depth of the pocket is selected to accommodate an allowable travel path for the portion of the tamper evident band of the closure;  
 the second surface comprises a second traverse wall, said second traverse wall being configured to engage a bottom-most portion of a tamper evident band of the closure.

2. A stripper sleeve for use in the molding stack, the stripper sleeve being configured to be movable to contact a closure after the molding thereof, the stripper sleeve comprising:  
 a pocket having a first surface and a second surface for simultaneously contacting a side and an underside surface, respectively, of the closure during the stripping of the closure;  
 wherein the first surface comprises a first axial wall, the first axial wall being configured to engage the side portion of a tamper evident band of the closure;  
 wherein the first axial wall provides a stopper, which delimits an extent of radial travel of the tamper evident band of the closure during stripping thereof;  
 wherein the pocket is associated with a depth, which depth represents a distance between an edge of the second surface where it meets an inner surface of the stripper sleeve and the first axial wall, whereby the depth is selected such as (i) to allow the portion of the tamper evident band of the closure to deflect in a direction to clear a feature of the molding stack, and (ii) to prevent significant damage attributable to “over-deflection” of the portion of the tamper evident band of the closure in the direction;  
 wherein the depth of the pocket is selected to accommodate an allowable travel path for the portion of the tamper evident band of the closure;  
 wherein the second surface comprises a second traverse wall, said second traverse wall being configured to engage a bottom-most portion of a tamper evident band of the closure.

\* \* \* \* \*