



US009175463B1

(12) **United States Patent**  
**Stivers**

(10) **Patent No.:** **US 9,175,463 B1**  
(45) **Date of Patent:** **Nov. 3, 2015**

(54) **METHODS FOR MODULAR CATCH BASINS**

(71) Applicant: **Guy Alan Stivers**, Tustin, CA (US)

(72) Inventor: **Guy Alan Stivers**, Tustin, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 302 days.

(21) Appl. No.: **13/831,889**

(22) Filed: **Mar. 15, 2013**

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 13/764,738, filed on Feb. 11, 2013.

(60) Provisional application No. 61/696,163, filed on Sep. 1, 2012.

(51) **Int. Cl.**

**E05F 5/04** (2006.01)  
**C02F 3/04** (2006.01)  
**E03F 5/04** (2006.01)  
**C02F 103/00** (2006.01)

(52) **U.S. Cl.**

CPC ..... **E03F 5/0404** (2013.01); **C02F 3/04** (2013.01); **C02F 2103/001** (2013.01)

(58) **Field of Classification Search**

CPC ..... **E03F 5/0404**; **C02F 3/04**; **C02F 2103/001**  
USPC ..... **210/602**, **615**, **616**, **617**, **150**, **151**, **163**,  
**210/164**, **165**, **170.03**

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,013,559 A \* 3/1977 Johnson ..... 210/151  
4,419,232 A 12/1983 Arntyr et al.

5,030,343 A 7/1991 Urriola  
5,037,541 A 8/1991 Ruey-Jang et al.  
5,269,094 A 12/1993 Wolverton et al.  
5,322,629 A 6/1994 Stewart  
5,372,714 A 12/1994 Logue, Jr.  
5,511,904 A 4/1996 Van Egmond  
5,618,428 A 4/1997 Oslund  
5,707,527 A 1/1998 Knutson et al.  
5,720,574 A 2/1998 Barella  
5,788,409 A 8/1998 Johnson  
5,810,510 A 9/1998 Urriola  
6,149,803 A \* 11/2000 DiLoreto et al. .... 210/164  
6,241,882 B1 6/2001 Allard  
6,277,274 B1 8/2001 Coffman  
6,334,953 B1 1/2002 Singleton  
6,527,477 B1 3/2003 Allard  
6,551,023 B2 4/2003 Allard  
6,562,233 B1 \* 5/2003 Schilling et al. .... 210/164  
6,641,335 B1 11/2003 Allard  
6,648,549 B1 11/2003 Urriola

(Continued)

**FOREIGN PATENT DOCUMENTS**

WO WO2009030896 3/2009

**OTHER PUBLICATIONS**

“Shaping the Future of Water Quality”, Cudo Water Storage System advertising brochure, Santa Rosa, CA 95407.

(Continued)


*Primary Examiner* — Fred Prince

(74) *Attorney, Agent, or Firm* — Alford Law Group, Inc.; Vy Vu

(57) **ABSTRACT**

Various embodiments of a modular catch basin for implementation in a high performance bioswale are disclosed. The modular catch basin containing bio-media in bio-media filters to treat urban run-off. Method of installing and maintaining the modular catch basin are also disclosed.

**18 Claims, 36 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

6,733,209	B2	5/2004	Allard	
6,779,946	B1	8/2004	Urriola et al.	
6,869,528	B2	3/2005	Pank	
6,872,029	B2	3/2005	Allard et al.	
6,875,350	B2	4/2005	Allard	
6,905,599	B2	6/2005	Allard	
6,976,808	B2	12/2005	Allard	
6,986,621	B2	1/2006	Allard	
7,014,782	B2	3/2006	D'Emidio et al.	
7,040,838	B2	5/2006	Allard et al.	
7,056,058	B2	6/2006	Urriola et al.	
7,165,913	B2	1/2007	Allard et al.	
7,182,874	B2	2/2007	Allard et al.	
D539,923	S	4/2007	Urriola	
D539,924	S	4/2007	Urriola	
D555,809	S	11/2007	Urriola	
7,374,364	B2	5/2008	Allard et al.	
D571,023	S	6/2008	Urriola	
D596,698	S	7/2009	Urriola	
D596,699	S	7/2009	Urriola	
7,686,540	B2	3/2010	Urriola	
7,897,047	B2	3/2011	Wanielista	
7,985,335	B2	7/2011	Allard	
2002/0113025	A1*	8/2002	Gauldin et al.	210/767
2004/0011731	A1*	1/2004	Sanguinetti	210/483
2004/0173522	A1	9/2004	Allard	
2005/0109693	A1	5/2005	Allard	
2005/0184007	A1	8/2005	Allard et al.	
2006/0060523	A1*	3/2006	Kerns	210/602
2006/0078387	A1	4/2006	Allard et al.	
2006/0133897	A1	6/2006	Allard et al.	
2007/0199869	A1*	8/2007	Al-Assfour	210/164
2007/0274784	A1	11/2007	Allard et al.	

2008/0056625	A1	3/2008	Stanton et al.	
2008/0073277	A1	3/2008	Paoluccio et al.	
2008/0251448	A1	10/2008	Kent	
2008/0251470	A1	10/2008	Kent	
2009/0101553	A1*	4/2009	Lucas	210/164
2009/0250405	A1	10/2009	Allard	
2009/0279953	A1	11/2009	Allard et al.	
2009/0305379	A1*	12/2009	Johnson et al.	435/170
2010/0200480	A1	8/2010	Kania et al.	
2010/0206790	A1*	8/2010	Holtz	210/150
2011/0011780	A1	1/2011	Izumo	
2011/0094153	A1	4/2011	Urriola	
2011/0147303	A1	6/2011	Allard	
2011/0278237	A1*	11/2011	McInnis	210/767
2011/0284442	A1	11/2011	Williams	
2012/0031854	A1	2/2012	Allard	
2012/0091057	A1*	4/2012	Kent et al.	210/602
2012/0132581	A1	5/2012	Williams et al.	
2012/0145612	A1*	6/2012	McInnis et al.	210/163
2012/0152827	A1	6/2012	Allard	
2013/0001158	A1	1/2013	Condon et al.	
2013/0299435	A1	11/2013	Coffman et al.	
2014/0138307	A1	5/2014	Coffman et al.	

OTHER PUBLICATIONS

“Cudo General Field Installation Guide” Cudo Water Storage System manual. rev 11-12, Santa Rosa, CA 95407.

“The Stormwater Opportunity”, Douglass Allard, Jon McDonald, Vivian Volz, the construction specifier, Nov. 2010.

Norris, Clare A.; U.S. Appl. No. 13/831,859; Office Action mailed May 4, 2015; 28 pages.

Prince Jr., Freddie Gary; U.S. Appl. No. 14/017,224; Office Action mailed Jun. 18, 2015 11 pages.

\* cited by examiner








FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 9B

205

105




FIG. 9A

205




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15












FIG. 16












FIG. 18B




FIG. 19B




FIG. 18C




FIG. 19C




FIG. 20A







FIG. 20B



**FIG. 20C**



**FIG. 20D**







FIG. 22A



**FIG. 22B**




FIG. 22C




FIG. 23A



FIG. 24A




FIG. 23B




FIG. 24B




FIG. 25A



FIG. 26A




FIG. 25B










FIG. 26B






FIG. 30




FIG. 31




FIG. 32





FIG. 32A



**FIG. 33**




FIG. 34

FIG. 36A




FIG. 35








FIG. 36






*FIG. 38*





*FIG. 39A*




*FIG. 39B*



*FIG. 40*





**METHODS FOR MODULAR CATCH BASINS****CROSS REFERENCE TO RELATED APPLICATIONS**

This non-provisional United States (U.S.) patent application claims the benefit of and is a continuation-in-part of U.S. patent application Ser. No. 13/764,738 filed on Feb. 11, 2013 by inventor Guy Alan Stivers, entitled SYSTEM AND METHOD FOR A MODULAR HIGH PERFORMANCE BIOS WALE. This non-provisional United States (U.S.) patent application further claims the benefit of U.S. Provisional Patent Application No. 61/696,163 entitled MODULAR HIGH PERFORMANCE BIOSWALE AND WATER TREATMENT SYSTEM AND METHOD filed on Sep. 1, 2012 by inventor Guy Alan Stivers et al., which is incorporated herein by reference as another example of a high performance bioswale with modular catch basins.

**TECHNICAL FIELD OF THE INVENTION**

The embodiments of the invention generally relate to catch basins for capturing and treating water.

**COPYRIGHT & TRADEMARK NOTICE**

A portion of the disclosure of this patent application may contain material that is subject to copyright protection. The owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyrights whatsoever.

Certain marks referenced herein may be common law or registered trademarks of third parties affiliated or unaffiliated with the applicant or the assignee. Use of these marks is by way of example and should not be construed as descriptive or to limit the scope of this invention to material associated only with such marks.

**BACKGROUND OF THE INVENTION**

Current methods that utilize an on site bioswale technique are highly inefficient and tend to rapidly become ineffective due to deferred maintenance and other issues. To illustrate this point, it is helpful to understand how a typical bioswale functions in order to treat contaminated water.

During a storm event, rain falls on urban development that is composed of approximately 70% impermeable surfaces (paving, roads, buildings, etc.) and 30% permeable surfaces (grasses, shrubs, and landscapes in general). These surfaces, especially the impermeable ones, are heavily laden with contaminants such as hydrocarbons, metals, bacteria, nitrogen, phosphorous nutrients, silt, debris, herbicides, insecticides, and pesticides. Currently, rain washes these surfaces directly into municipal stormwater management systems where it ends up fouling waterways and oceans. One method of removing these various contaminants is to channel the contaminated water into a landscaped structure commonly known as a bioswale.

With more urban development has come more regulation. In the past 20 years, laws have been passed requiring that runoff from paved areas drain into adjacent landscape bioswales where it is mitigated by soil and plant biology, allowing some of it to infiltrate soils and most of it to drain to municipal stormwater management systems. A typical bioswale is a vegetated depression in the landscape that channelizes stormwater for filtration of contaminants prior to drain-

age into the municipal stormwater system. This setup poses some serious problems however, as discussed below.

The typical bioswale requires an extraordinary amount of maintenance to maintain its effectiveness at removing contaminants from stormwater. Over the course of many rain-falls, the bioswale fills with heavily polluted silts that cause the bioswale's biological system, primarily soil biology and vegetation, to fail. To adequately maintain the bioswale, it is required that the polluted silts be removed from the bioswale once or twice per year. This is a very expensive and labor intensive process, and usually consists of removing the top 1"-2" of soil and vegetation from the entire length of the bioswale. It may also be necessary to modify the irrigation system. Other issues related to this burdensome process include soil preparation, revegetation, and disposal of polluted debris. In other words, the bioswale has to be rebuilt periodically to maintain its effectiveness. Few bioswales are maintained to this level. However, stormwater quality legislation requires that many current and future bioswales be adequately maintained for effectiveness. Thus there is a need in the art for a high performance modular bioswale system for treatment of runoff water that is highly effective yet relatively easy to construct and maintain. It is to these ends that the embodiments of the invention have been developed.

**SUMMARY OF THE INVENTION**

The embodiments of the invention are summarized by the claims that follow below. Insofar as a summary is required, the embodiments of the invention may be generally described as a modular catch basin for filtering storm water or urban run-off. The modular catch basin and surrounding high performance bioswale uses pond liners instead of pipes so there is less clogging. The pond liner is easily maintained and captures surface flow more readily than pipes or other means currently in use.

The modular catch basin is novel in that it uses a gravity flow filtration system versus forcing water through a filter. No expensive, high maintenance, high energy cost pumps are needed for filtering. Pumps may be used to pump water from the cisterns for irrigation. The use of a solar pump is possible.

The modular catch basin system uses one or more bio-media filters to filter the storm water. Run-off is channeled by pond liners towards the modular catch basin, where the run-off falls through the one or more bio-media filters. The bio-media filters are uniquely adapted to exchange gases with the environment. Air is needed for biology to remove pollutants. Trap gas must be vented and exchanged for oxygen. Methane, a common organic gas, must be released as it is toxic to grass plant and other biology used in the bio-media filter.

The modular catch basin is also ingeniously constructed to be installed and maintained by landscape professionals with minimal use of civil engineers.

**BRIEF DESCRIPTION OF THE DRAWINGS**

Elements in the Figures may not be drawn to scale in order to enhance their clarity and improve understanding of these elements and embodiments of the invention. Furthermore, elements that are known to be common and well understood to those in the industry may not be depicted in order to provide a less obstructed view of the various embodiments of the invention.

FIG. 1 is a top plan view of a preferred embodiment of a high performance bioswale system, depicting its primary components including a forebay and a primary detention basin.

## 3

FIG. 2A is a longitudinal cross sectional view of a high performance bioswale system.

FIG. 2B is a magnified view of a drainage pipe depicted in FIG. 2A.

FIG. 3 is a longitudinal cross section view of an embodiment for a primary detention basin, representing a water reuse system comprised of a water reuse pipe and an irrigation pump.

FIG. 4 is a side cross section view depicting an embodiment for a primary detention basin, with a water reuse pipe, and the preferred embodiment of an upper catch basin.

FIG. 5 is a side cross section view primarily depicting a water testing device, which may be used to test the effectiveness of a high performance bioswale system.

FIG. 6 is a side cross section view of an embodiment of a forebay depicting water flow through its primary components.

FIG. 7 is an exploded view an exemplary embodiment of a catch basin located in a primary detention basin.

FIG. 8 is a longitudinal cross section view of another embodiment of a high performance bioswale system depicting potential alternative lower basins.

FIG. 9A is a side cross sectional view of a forebay depicted in FIG. 8.

FIG. 9B is a side cross sectional view of a primary detention basin depicted in FIG. 8.

FIG. 10 is an alternative embodiment of a high performance bioswale system representing a top plan view of a singular stormwater treatment basin sans forebay.

FIG. 11 is a longitudinal cross section view of a stormwater treatment basin, which depicts a preferred embodiment for simultaneous pretreatment and primary treatment of water.

FIG. 12 is a side cross section view of FIG. 11 depicting water flow entering a high performance bioswale system, being treated, and exiting via an outflow pipe.

FIG. 13 is a top plan view depicting an alternative embodiment of an "L" shaped high performance bioswale system.

FIG. 14 is a top plan view of an alternative embodiment of a high performance bioswale system depicting a larger forebay and primary detention basin for a larger site.

FIG. 15 is a top plan view of an alternative embodiment of a high performance bioswale system depicting the modular and flexible nature of the system.

FIG. 16 is a longitudinal cross section view of an alternative embodiment of a high performance bioswale demonstrating the modular nature of the system and its components.

FIG. 17A is an exploded view of an embodiment of a modular catch basin, depicting its primary components including a plurality of bio-media filters, a filter housing, a filtration housing, and a cistern container.

FIG. 17B is a perspective view of upper and lower hollow support structures.

FIG. 17C is a magnified perspective view of the complementary legs of two hollow support structures.

FIG. 17D is a perspective view of upper and lower hollow support structures joined to form a filtration housing.

FIG. 17E is a magnified perspective view of the leg (with a peg end) of a hollow support structure above a complementary mounting corner receptacle.

FIG. 17F is a magnified perspective view of the leg (with a receptacle end) of a hollow support structure above a complementary mounting corner peg.

FIG. 17G is a magnified perspective view of a snap in mounting corner above the corner of a grate.

FIG. 18A is a system diagram of a catch basin embodiment containing two bio-media filter.

## 4

FIG. 18B is a side view of an exemplary filtration housing stacked above an exemplary cistern container 1707.

FIG. 18C is a magnified side view of the corner of an exemplary filtration housing depicting the fastening prongs of the top grate.

FIG. 19A is a system diagram of a catch basin embodiment containing three bio-media filter.

FIG. 19B is a side view of an exemplary filtration housing stacked above an exemplary cistern container, the first bio-media filter containing optional vegetation.

FIG. 19C is a magnified side view of the corner of an exemplary filtration housing depicting the fastening prongs of the top grate.

FIGS. 20A-20D illustrate the modularity of the modular catch basin with various heights and widths of hollow modular cube structural housing.

FIG. 21A is a perspective view of an open bio-media filter.

FIG. 21B is a plan view of an open bio-media filter.

FIG. 21C is a side view of a bio-media filter with optional vegetation.

FIGS. 22A-22C are side cross section views of embodiments of bio-media filter inserted into the perforated hollow cylinder within a catch basin.

FIGS. 23A-23B are side and plan views of a side grate inserts for sides of a hollow modular cube structural housing full.

FIGS. 24A-24B are side and plan views of side wall inserts for a hollow support structure half-unit.

FIGS. 25A-25B are side and plan views of a connector ring for connecting hollow support structure units together.

FIGS. 26A-26B are side and plan views of a support grate insertable into an opening of the connector ring of FIGS. 25A-25B.

FIGS. 27A-27B are side and plan view of a bottom grate for the modular catch basin.

FIGS. 28A-28B are side and plan views of a top grate mountable to the perforated hollow cylinder of the forebay catch basins.

FIGS. 29A-29B are side and plan views of another embodiment of a top grate mountable to the perforated hollow cylinder and the hollow modular cube structural housing of the detention catch basins.

FIG. 30 is a plan view of an exemplary high performance bioswale depicting a drainage channel, forebay, and primary drainage bay (PDB) with catch basins equipped with drain down grommets.

FIG. 31 is a plan view of an exemplary catch basin depicted with drain down grommets.

FIG. 32 is a magnified side view of the top corner an exemplary filtration housing with drain down grommets.

FIG. 32A is a magnified side view of a drain down grommet coupled to a water impermeable material, such as a pond liner.

FIG. 33 is side view of an exemplary catch basin depicting the fluid flow through the drain down grommets.

FIG. 34 is side view of an embodiment of the invention depicting an exemplary catch basin without a filtration housing.

FIG. 35 is side view of an exemplary catch basin with drainage shoulders.

FIG. 36 is a plan view of an exemplary connector ring with perforations.

FIG. 36A is a plan view of an exemplary connector ring with perforations wrapped in a filter fabric.

FIG. 37 is side view of an exemplary bioswale.

FIG. 38 is a plan view of an exemplary unitary bottom grate.

5

FIGS. 39A-39B are top and cross section views of an exemplary unitary connector ring.

FIG. 40 is a plan view of an exemplary unitary top grate.

FIG. 41-42 are side views of exemplary catch basins depicting the modular nature of embodiments of the invention.

FIG. 43 is a cross section view of an exemplary catch basin depicting with emphasis on the excavation.

#### DETAILED DESCRIPTION

In the following discussion that addresses a number of embodiments and applications of the embodiments of the invention, reference is made to the accompanying drawings that form a part hereof, where depictions are made, by way of illustration, of specific embodiments in which the invention may be practiced. It is to be understood that other embodiments may be utilized and changes may be made without departing from the scope thereof.

FIG. 1 illustrates an exemplary embodiment depicting a top-plan view of the high performance bioswale system 100 (note however, that "system 100" generally refers to all embodiments). FIG. 2 illustrates a longitudinal cross section of FIG. 1. FIG. 1 and FIG. 2 will be discussed extensively with one another for ease of transmitting the scope of the system 100 to the reader. System 100 is modular in nature, and can be adjusted and sized to varying dimensions and settings as will be explained in further detail throughout these descriptions and various embodiments.

#### Water Inflow to System

System 100 may be situated near a paved area 101, such as a driveway, an asphaltic concrete parking lot, or other similar type of area. Adjacent the paved area 101 is a curb 102, such as a concrete curb, separating the paved area 101 from a landscaped/planting area. Integrated with the curb 102 is a drainage channel 103, such as a concrete drainage channel, that may already exist on curb 102, or that may be constructed into curb 102 and located proximate to system 100. Typically, water runoff, also termed as urban runoff or stormwater runoff, from rain or other urban sources, will flow down around paved area 101 and down along curb 102 and into drainage channel 103. For ease of clarification, the water from paved area 101 will hereinafter be referred to as urban runoff. An example of the typical water flow from urban runoff is illustrated with the various arrow indicators in FIG. 1 with respect to paved area 101, curb 102 and drainage channel 103.

Once urban runoff flows through drainage channel 103, it will flow into pond-lined channel 104. Pond-lined channel 104 collects and fluidly conveys urban runoff from drainage channel 103 to forebay 105. Pond-lined channel 104 also collects and fluidly conveys landscape runoff (which may be stormwater, grey water, etc. but for ease of reference will be referred to simply as landscape runoff) to forebay 105, such as from a preexisting landscape swale 106. Pond-lined channel 104 may be formed with a pond liner material as well as a non-woven geotextile underlayment material for purposes of securing a watertight barrier. In one embodiment, pond-lined channel 104 may be formed with a pond liner of a 45-mil Ethylene Propylene Diene Monomer ("EPDM") material without limiting the scope of the system 100. After urban runoff flows into drainage channel 103, pond-lined channel 104 directs urban runoff to forebay 105. Pond-lined channel 104 also directs landscape runoff to forebay 105.

Pond-lined channel 104 is able to move large volumes of surface water with ease allowing for fast waterflow rates. Further, pond-lined channel 104 alleviates the need to use other mechanisms for directing runoff to a bioswale, such as

6

pipng mechanisms that are often used in the industry. The use of piping requires labor-intensive installation as well as frequent maintenance for clogging issues, and can only withstand a certain amount of water flow rate and volume.

Pond-lined channel 104 may be covered with decorative rock 204. The primary function of decorative rock 204 is to serve as a ballast to provide form. Decorative rock 204 also serves to provide water displacement so that runoff may flow evenly into the catch basins of forebay 105. A tertiary function of decorative rock 204 is to provide an initial silt and large debris filtration layer to increase the overall effectiveness of the water flow to system 100. Finally, decorative rock 204 also has aesthetic appeal with the surrounding environment and may be easily manipulated by landscape personnel who may service system 100 on a periodic basis.

Once urban and landscape runoff (hereinafter referred to simply as runoff, unless otherwise indicated) has passed onto pond-lined channel 104, its flow is directed to forebay 105 of system 100, which serves to give runoff a pretreatment. In so constructing forebay 105 of system 100, forebay excavation 107A area may first be excavated with a backhoe, for example. This area is adapted to receive forebay 105 components and acts as a surrounding enclosure. The forebay excavation 107A area is then lined with a filter fabric in order to reduce siltation and maintain water holding capacity. The filter fabric enclosure also assists in prolonging the life and use of forebay 105. Sand base 202, may thereafter be installed, leveled and enclosed in filter fabric to keep sand from migrating in excess into surrounding soils. Sand base 202 serves to maintain a generally level base for the components of forebay 105. Once laid, the other components of forebay 105 may be installed, including lower detention basin 205 and the catch basins and other components, which are depicted in FIG. 1 as circles within squares in both forebay 105 and primary detention basin ("PDB") 111. The excess space of 107A may then be backfilled with gravel 201, which may be 1.5" in size and serve as a natural filtering element and water containment of system 100. Pond-lined channel 104 may thereafter be placed and topped with decorative rock 204.

Once in place, forebay 105 acts as an entry point for runoff via guidance by pond-lined channel 104. Forebay excavation 107A may act more specifically as an entry point for landscape runoff that may not be channeled by pond-lined channel 104. As depicted in FIG. 1, this is one reason pond-lined channel does not extend to the outer edges of forebay excavation 107A. However, this should not be considered as a limitation and may be modified for other purposes, as will be discussed below. For this purpose, however, landscape runoff is generally considered as pretreated water and does not require the level of treatment as that required by urban runoff, thus it is not an absolute requirement that it flow through the catch basins of forebay 105.

Runoff that is directed to the catch basins of forebay 105 will first pass over pond-lined area of forebay 105 which may be covered with a layer of decorative rock 204. Decorative rock 204 however, serves many purposes beyond the aesthetic. Decorative rock 204 may be 5" in depth and serve to capture additional silt and larger debris from water entering forebay 105. Large debris is also separated from the fine silts, metals, hydrocarbons, nutrients and contaminants in the runoff which may be directed toward the forebay 105 catch basins for sequestering. Decorative rock 204 also may act to assist in displacing stormwater evenly into the cylinders of forebay 105 catch basins. Additionally, decorative rock 204 covers drain down grommets (not depicted in FIG. 1, see FIG. 20A for example, but located near the outside edges of each

catch basin) as well as any irrigation lateral lines and emitters that may be present. It may also be used as mulch surrounding grass plants **213**.

After passing through decorative rock **204**, runoff will then flow toward forebay **105** catch basins. In an exemplary embodiment of system **100**, forebay **105** may contain three catch basins for urban runoff and one catch basin for landscape runoff. Each of the catch basins is placed next to each other in a row in the direction of water flow, and is situated generally parallel to the length of the bioswale area. The catch basins serve to receive runoff directed from drainage channel **103** and landscape swale **106**. One reason for the separate catch basins in forebay **105** is that different contaminants may be found in the landscape as compared to urban surfaces such as parking lots and streets, where roughly 75% of contaminants may be washed toward system **100** during the first 15 minutes of a storm. Furthermore, these catch basins may be elevated approximately one inch from pond-lined channel **104** as to allow for even distribution of runoff into the catch basins.

In an exemplary embodiment of system **100**, each catch basin of forebay **105** may include a CUDO® cube. A CUDO® cube may have dimensions of 24" cubed with circular openings that are 18" diameter on each of its six sides. The catch basins (or CUDO® cubes) are enveloped with a filter fabric that may be permeable in nature. In another embodiment, the catch basins may be fully or partially wrapped in an impermeable pond liner.

Each catch basin of forebay **105** contains cylinders (discussed in further detail in FIG. 7) that may be placed through the top of a modular cube structural housing and extend through one or more cubes to a bottom grate. In the exemplary embodiment, each cylinder is elevated approximately one inch above pond-lined channel **104** so that runoff displaced by decorative rock **204** may be evenly distributed throughout forebay **105** before entering each of forebay's **105** catch basins. Each cylinder may also be topped with a perforated cap (a top grate) so that runoff may drain through and larger debris separated out before runoff enters the inner area of the cylinders of the catch basins. These cylinders may contain a certain number of bio-media filters **208**. Thus, once runoff passes through the perforated cap and into the inner portion of the catch basin cylinder, it will flow onto bio-media filters **208**. Bio-media filter **208** may contain a particular bio-media that is suited for the particular purpose of the location of system **100**, but primarily to sequester contaminants and give a level of treatment to runoff entering forebay **105**. In the exemplary embodiment, forebay **105** catch basin may contain two vertically stacked bio-media filters **208**.

Depending on the bio-media filter **208** permeability design and bio-media type, runoff may filtrate therethrough and contaminants may be sequestered in the media allowing a cleaner level of water (pretreated runoff) to pass down through the bottom of bio-media filters **208** of the catch basins and into a lower cistern-like device labeled here as lower detention basin **205**. In the depicted embodiment of the system **100**, detention basin **205** may also be comprised of a CUDO® cube with dimensions of 24" cubed and circular openings that are 18" diameter on each of its six sides. Depending on the needs of the location, however, other devices may be used as for lower detention basin **205** with varying dimensions such as height, or composed of varying materials. Detention basin **205** may have perforated plastic side grates, and can be wrapped in a filter fabric, which allows for pretreated runoff to move in or out of detention basin **205**. Use of a filter fabric around basins **205** also allows for pretreated runoff to safely

infiltrate into native soil **209**, as represented by the numerous downward pointing arrows depicted in FIG. 2.

Finally, forebay **105** may serve to receive, mitigate and regulate approximately 80 gallons of runoff per minute. Other variations and sizes of forebay **105** may be employed for larger capacities and volumes of water depending on logistics and the location involved. Furthermore, the modular aspect of forebay **105** and its inner components allow for easy accessibility as well as ease of maintenance should bio-media filters **208** need to be cleaned, removed, replaced or silt need to be removed from lower detention basin **205**.

When forebay **105** fills with pretreated runoff, the pretreated runoff surface level rises to an elevation allowing it to flow via drainage pipe **112** to PDB **111**. Drainage pipe **112** may be situated just below the surface of pond-lined weir **109**—a part of pond-lined channel **104**. In the exemplary embodiment, drainage pipe **112** may be comprised of a perforated pipe situated near the two upper corners of forebay **105** closest to PDB **111**, and may be connected to two non-perforated pipes situated parallel to one another extending in the direction from forebay **105** to PDB **111**, see FIG. 1. Pretreated runoff may enter drainage pipe **112** on either end of the perforated pipe section or through any of the perforations where it may thereafter be channeled to either of the two non-perforated pipes that are perpendicularly connected to the main entry perforated pipe and are sloped at an angle of not less than 2% leading to PDB **111**. Pretreated runoff will exit drainage pipe **112** onto pond-lined channel **104** of PDB **111**, see FIGS. 2 and 2A.

Drainage pipe **112** serves as the primary component that moves pretreated runoff from forebay **105** to PDB **111**. In the event that drainage pipe **112** fails to serve its function (for example becomes blocked), after pretreated runoff fills forebay **105** it will be channeled to PDB **111** via pond-lined weir **109**. In the event that pond-lined weir **109** fails to serve its function, pretreated runoff will nevertheless be guided towards PDB **111** as it is down slope from forebay **105**, and in the exemplary embodiment, will be situated within a pre-existing swale. For purposes of clarity, however, discussion of the FIGS. hereinafter will only refer to pretreated runoff moving via drainage pipe **112** into PDB **111** area.

Below drainage pipe **112** and pond-lined weir **109** is a soil area between forebay **105** and PDB **111**, which may be 4' in width. This will typically be undisturbed native soil **209**, but may be used for re-routing existing utility lines or installing irrigation lines to facilitate the surrounding landscape. See e.g. **206**.

#### Primary Detention Basin

In so constructing PDB **111** of system **100**, PDB excavation **107B** area may first be excavated as with forebay **105**. The entire PDB **107B** area is then lined with a filter fabric. Sand base **202** is then installed, leveled and enclosed in filter fabric. Once laid, the other components of PDB **111** may be installed, including lower detention basin **205** and the PDB catch basins. The excess void of **107B** may then be backfilled with gravel **201**, Pond-lined channel **104** may thereafter be placed and secured tightly around each of PDB **111**'s catch basins and then topped with decorative rock **204**, which serves the same purposes as described above with reference to forebay **105**.

In an exemplary embodiment, PDB **111** may be comprised of fourteen (14) catch basins, which are lined up in rows of seven (7) and are substantially parallel to each other and the length of system **100**. These catch basins are similar to those found in forebay **105**, but have notable differences as will be discussed below.

When pretreated runoff from forebay **105** flows through drainage pipe **112** into the PDB **111** area, the cylinder inside each of the fourteen catch basins of PDB **111** is elevated approximately one-inch above the pond-lined channel **104**, in accordance with the method used in forebay **105**. The elevated cylinders allow for pretreated runoff traveling from drainage pipe **112** to become more evenly distributed throughout PDB **111** before entering each of PDB's **111** catch basins.

The catch basins of PDB **111** contain different contents for purposes of serving as the primary water filtration treatment and may vary depending on the needs of system **100** and the particular location involved. PDB's **111** catch basins also each have a cylinder that may contain three bio-media filters stacked vertically upon one another.

The top bio-media filter **208** is designed to allow for a grass plant **213** to be planted therein so that its roots may grow down through the top of bio-media filter **208** into the middle and bottom of bio-media filters **208**. This also allows for maximum biological effectiveness for grass plant **213** growth. Grass plants **213** serve as an additional biological component to filtrate contaminants and contaminates from pretreated runoff. In an exemplary embodiment, use of grass plants **213** in PDB's **111** catch basins may be particularly effective as they have a relatively high "root to shoot" ratio, which provides for substantially more biological activity than shrubs. In particular, grass plants **213** are desirable for use in PDB **111** as their biological properties include being a natural accumulator that can sequester metals as well as metabolize nutrients, hydrocarbons, inorganic materials, and bacteria. Grass plants **213** are also desirable for use in PDB **111** since they are durable, reliable, easy to maintain, and highly tolerant to the effects of various urban conditions. One species of a grass plant **213** that may be used is the vetiver species, which is known as a hyperaccumulator with phytoremediation properties.

Middle and lower bio-media filters **208** may contain a combination of water "polishing" agents such as sandy loam soil (directed to metals sequestration), bio-char (directed to enhance sorption of nutrients), and water purifiers (such as chlorinated tablets for irrigation). Other combinations of bio-media may be utilized in the bio-media filters without deviating from the scope of the embodiments of the invention.

Pretreated runoff filtrates down through each bio-media filter **208** of PDB's catch basins and percolates into lower detention basin **205** as depicted by the various arrows in FIG. **2**. Once in lower detention basin **205**, water may be considered fully treated. PDB's **111** detention basin **205** may also be comprised of CUDO® cubes, have perforated plastic side-walls and be wrapped in filter fabric, which allows for treated water to move in or out of detention basin **205**. Use of a filter fabric around detention basin **205** also allows for drainage to infiltrate into native soil **209**. In other embodiments, a non-permeable pond-liner may be used to contain treated water in basins **205**, as will be discussed below. The embodiment employing a non-permeable pond-liner may be useful when treated runoff or other water is used for reuse water. Furthermore, any particular device may be used as a lower basin that may have varying dimensions or properties, and the scope should not be limited to CUDO® cubes. Atlantis® crates may serve the same purpose. They are made of a hardened plastic, have six sides that are completely permeable, are structurally sound, and may just as easily be wrapped in a filter fabric or impermeable pond liner to either detain or retain treated water:

Where filter fabric is wrapped around detention basin **205**, however, treated runoff may then pass through the filter fab-

ric, infiltrate into native soil **209**, and thereafter into an aquifer. If the water flow is voluminous in nature and the treated water level in PDB's **111** lower detention basin **205** rises toward the height of detention basin **205**, it may then be directed into outflow pipe **207**. Outflow pipe **207** may convey treated water into a city stormwater drainage system, for example.

Outflow pipe **207** may be positioned at one end detention basin **205** on the opposite end from where runoff primarily enters system **100**. Outflow pipe **207** may also be positioned toward the upper level of detention basin **205** where it is desirous that most treated water eventually percolate into native soil **209**. In the event there is a high volume of water accumulating in detention basin **205**, outflow pipe **207** serves to act as a secondary drainage system. The inlet portion of outflow pipe **207** runs from detention basin **205** through gravel **201** area and into native soil **209**. Outflow pipe **207** may be positioned at a slope with a minimum 0.5% grade allowing for adequate water outflow.

The portion of outflow pipe **207** that runs through the gravel **201** area may contain perforations along its length and may be wrapped with a filter fabric to reduce clogging. The perforations in outflow pipe **207** allow for it to receive drainage from gravel **201** area as well as any overflow from detention basin **205**. Outflow pipe **207** may be sized to fit the amount of water volume processed in system **100**. For example, outflow pipe **207** may generally be between 4"-6" in diameter.

#### Reuse Pipe

Another aspect of system **100** includes a water reuse pipe **117**, which is a dedicated pipe line used to convey water from other locations directly to PDB **111** for cleaning and reuse. Other water sources may include general runoff, air conditioning condensation from surrounding structures, wash-down water, harvested roof rainwater, and grey water from sinks and showers. For ease of reference, water channeled to PDB **111** via water reuse pipe **117** will be deemed reuse water, however, this term is not to limit the scope of the function of water reuse pipe **117**. In the exemplary embodiment, this water may be reused after treatment, but this is not necessary.

As shown in FIG. **1**, water reuse pipe **117** may be installed as running down the length of one row of PDB's **111** catch basins. The portion of water reuse pipe **117** running down the length of PDB **111** is perforated so that water can be deposited down into the upper catch basin portions of PDB **111** for treatment. Each of PDB's **111** catch basins containing water reuse pipe **117** may be covered with a non-perforated cap **403** so that only water from water reuse pipe **117** is directed to those particular catch basins. Additionally, the water reuse pipe **117** may be aligned by the side or between rows of PDB **111** catch basin cylinders. In the latter regard, the integration of runoff and reuse water may provide for maximum efficiency and maintenance of system **100**.

FIG. **3** is a longitudinal cross section of a particular embodiment depicting water reuse pipe **117** and its preferred components: lower retention basin **302** and irrigation pump **118**. As noted above, reuse water is conveyed via water reuse pipe **117** to PDB **111**, where the water percolates through the initial catch basins and bio-media of PDB **111** down into lower retention basin **302**. In this embodiment however, the initial catch basins of PDB **111** would only contain two bio-media filters **208** such as to allow adequate room for water reuse pipe **117**.

Lower retention basin **302** may be composed, for example, of CUDO® cubes collectively wrapped in an impermeable pond-liner **404**, which allows for treated reuse water to be pumped out by irrigation pump **118**. Irrigation pump **118** may

11

operate as a result of conventional power sources or from solar-powered sources. Irrigation pump **118** may be fitted into one end of PDB's **111** lower retention basin **302** and catch basins so that treated reuse water may be pumped via irrigation mainline **301** to the surrounding landscape, to the grasses planted in the top bio-media bio-media filter **208** of PDB **111**, or elsewhere for other uses. Irrigation mainline **301** is the main water line running to the drip, bubbler and hose irrigation systems and may also supply pressurized wash-down water. Irrigation mainline **301** runs out from irrigation pump **118** through gravel **201** and into native soil **209**. Irrigation pump **118** is also provided with a potable water source to ensure that irrigation to surrounding landscape and grasses can occur when reuse water is in short supply.

The catch basin that contains the components of irrigation pump **118** does not contain bio-media filters **208** that are found in the other catch basins of PDB **111** so as to allow adequate room for irrigation pump's **118** components. Furthermore, the impermeable pond-liner allows for surrounding sand, silt and other grit, which would otherwise foul the pump and lateral lines and emitters, to be segregated from system **100**. Depending on components used, retention basin **302** may hold 17" of treated reuse water (or approximately 42 gallons per basin). When retention basin **302** fills to excess capacity, as is exemplified by water level line **303**, outflow pipe **207** may serve to direct treated reuse water to a city stormwater system.

It should be noted, however, that FIG. 3 depicts an ideal configuration for actually reusing water. This embodiment may be modified such that reuse water conveyed to PDB **111** via reuse pipe **117**, is allowed to infiltrate into native soil **209** or be conveyed to a city storm drainage system via outflow pipe **207** rather than actually be reused. Irrigation pump **118** in either scenario would then be unnecessary.

FIG. 4 illustrates a cross-section and partial view of PDB **111** area, including water reuse pipe **117** as well as the surrounding environmental elements of PDB **111**, and depicts how water reuse pipe **117** may be positioned within the cylinder area of a catch basin. In this view, water reuse pipe **117** is situated within the cylinder of a catch basin through a cylinder opening **402** that accommodates the size of water reuse pipe **117**. Cylinder opening **402** may be 8" in diameter and is located on each side of cylinder so that water reuse pipe **117** may run therethrough. As noted earlier, water reuse pipe **117** may be a flexible and perforated pipe, 4" in diameter. In this view, water reuse pipe **117** is placed over a set of two bio-media filters **208** that may contain a combination of filtering materials targeted to the particular area system **100** is located. Reuse water flows out of the perforated openings in water reuse pipe **117** onto bio-media filters **208** for filtration treatment.

Water reuse pipe **117** may be removed from the row of cylinders in the event that it needs to be cleaned or maintained or when bio-media filters **208** located beneath need to be replaced. Installment of water reuse pipe **117** may require one attachment proximate the area where water reuse pipe **117** enters the first catch basin in the row of catch basins (not shown).

A non-perforated cap **403** may be used to cover cylinder so that water reuse pipe **117** is sequestered from other water sources, however, in another embodiment, the non-perforated cap **403** may be perforated to allow additional water flow into the cylinder.

Surrounding each cylinder is pond-lined channel **104** and decorative rock **204** that is placed around the top area of PDB **111**. As explained above pond-lined channel **104** and decorative rock **204** help for water flowing into PDB **111** to gen-

12

erally drain evenly into cylinders. The cylinders themselves further effectuate this goal by being positioned slightly above the level of pond-lined channel **104** (about one inch).

Pond-lined channel **104** and protective rock layer **204** in PDB **111** also serve to capture silt and other debris not previously filtered out in forebay **105**. Additionally, pond-lined channel **104** serves as a cleaning base when the components for forebay **105** and PDB **111** are removed for cleaning. The components of forebay **105** and PDB **111** can be rinsed down onto pond-lined channel **104**. The residue rinsed onto pond-lined channel **104** can then be rinsed into lower retention basin **302** and left to dry before being vacuumed out. This allows for easy, effective and efficient maintenance of system **100** that may coincide with particular wet and dry seasons.

As mentioned earlier, a non-woven underlayment material is layered beneath pond-lined channel **104**. Under pond-lined channel **104** may be a pea gravel base **405**, or other such material or structure which may be from 2" to 6" in depth to help support the slope of pond-lined channel **104** that helps to direct water to catch basins. Adjacent to the pea gravel base **405** is the surrounding swale grade **406** area. Drainage from the surrounding landscape flows down around swale grade **406** and into the excavation areas **107B** and **107A** (as previously discussed above). Landscape runoff taking this route bypasses pond-lined channel **104**, but as noted, this runoff is considered pretreated. Landscape runoff is further treated by entering system **100** through filter fabric and gravel **201** area, and by the time it leaves system **100**, it is considered fully treated. Furthermore, most water entering system **100** will enter via other primary avenues, i.e. drainage channel **103** and landscape swale **106**.

FIG. 5 illustrates an alternate cross-section view of PDB **111**, including a cross-section view of catch basins with a set of three bio-media filters with grass plant **213** planted at the top as well as the surrounding components of PDB **111** discussed above in FIG. 4. Depicted in this view is water testing device **501** that is situated in lower detention basin **205** (but could also be placed in lower retention basin **302**, for example) and that allows for the collection of water quality samples. Testing the quality of water that has filtrated down through bio-media filters **208** enables a user or maintenance personnel to determine whether the bio-media is still effective or needs replacement.

In this view, the water testing device **501** is placed in lower detention basin **205**. However, water testing device **501** may be placed in any part of lower detention basin **205** beneath initial catch basins for purposes of testing bio-media filters' **208** effectiveness over time. In one embodiment, water testing device **501** may be a container, such as a bucket, used to collect water samples. However, this should not be construed as limiting the scope of the system **100**.

FIG. 6 illustrates a cross-section view of forebay **105**, including a catch basin and the manner in which runoff may flow into said catch basin. As discussed above in FIG. 1, urban runoff may flow from paved area **101**, such as a street, down along curb **102** and into drainage channel **103**. The urban runoff is then directed to system **100** via pond-lined channel **104**. An example of the water flow is generally indicated by the series of arrows. Also depicted is perforated cap **601** to receive runoff, silt, and finer debris. Larger debris that cannot pass through the perforation diameter is held in decorative rock **204** situated upon pond-lined channel **104**.

FIG. 7 depicts an exploded view of the primary components comprising PDB **111**. FIG. 7 also depicts most of the same components that are used in forebay **105**. The upper unit may be a catch basin as represented by **701A**. The lower unit may be part of a lower detention or retention basin as repre-

sented by 701B after water filtrates through 701A and its components. 701A and 701B may be connected by optional connector ring 702, wherein an additional grate or similar device may be located, upon which bio-media filters 208 may rest. Inside catch basin 701A is a perforated cylinder 703, which would contain bio-media filters 208 and grass plant 213.

Basin 701A may contain perforated cylinder 703, which is fitted within the inner space of basin 701A. The perforated surface of cylinder 703 allows for air circulation throughout basins 701A and 701B as well as gas exchange between the biological elements of bio-media filters 208 including grass plant 213. Cylinder 703 may contain three bio-media filters 208 within it. Bio-media filters 208 fit snugly around the entire circumference of cylinder 703 so that water entering basin 701A interacts and filters through the bio-media of bio-media filters 208. As explained earlier, bio-media filters 208 may contain a mixture of bio-media targeted for specific types of primary filtration and cleaning depending on geographical factors. Cylinder 703 may be 18" in diameter and 24" in length and constructed of a PVC pipe or a rubberized laminated material. In an exemplary embodiment, forebay 105 cylinders 703 may have twenty-four 3/4inch diameter openings that are equally spaced throughout cylinder 703. PDB 111 cylinders 703 (which typically would contain an additional bio-media filter) may have forty 3/4inch diameter openings also equally spaced throughout cylinder 703. The holes serve the purpose of allowing bio-media filters 208 a means to breathe, which is beneficial for the optimal functioning of system 100 as a whole.

Each filter portion may be fabricated of a permeable plastic material, and contain a particular type of bio-media. Depending on the bioswale, runoff flow rate, and other specified factors, the bio-media may be targeted with a specified mixture of design soil, including known proprietary bio-media that may be licensed or sold. For example, a design soil may contain a specified mixture of organic and inorganic minerals that target and sequester contaminants such as metals, hydrocarbons, bacteria, and organic and inorganic nutrients. The type of bio-media as well as permeability of the filter material may be customized accordingly.

In the exemplary embodiment, bio-media filters 208 may be generally comprised of a permeable woven plastic that is generally 18 inches in diameter and 8 inches in depth. The bottom center of bio-media filter 208 may contain a 6 inch diameter circular opening, which is covered with a pliable mesh material. The pliable mesh material that covers the bottom opening of bio-media filter 208 allows for grass plant 213 to easily grow its roots down from the top bio-media filter 208 to the bottom bio-media filter 208. The bottom bio-media filter 208 may contain a permeable woven plastic insert that covers the bottom opening in order to prevent bio-media material from falling out or from the roots of grass plant 213 from growing down into basin 701B. The permeable plastic insert may also be used in the center bio-media filter 208 if it is desired, for example, to prevent the roots of grass plant 213 from growing into the bottom bio-media filter 208 or to segregate filtration material from entering the bio-media filter 208 below it.

Each bio-media filter 208 may contain one or more reinforcing lifting straps. Each lifting strap may be 1.5" wide and extend approximately 8" above the bio-media filter 208. The lifting straps allow a user or other maintenance crews to more easily install and remove bio-media filters 208 when needed. Other dimensions and sizes may be used for lifting straps without limiting the scope of the embodiments of the invention. The lifting straps may be further reinforced to bio-media

filter 208 by attaching a portion of the lifting straps around the top and bottom portions of bio-media filter 208. The lifting straps may be attached to bio-media filter 208 by being sewn in around the opposite sides of bio-media filter 208.

Around the upper circumferential edge of bio-media filter 208 is a pliable plastic 3/4inch mesh material which extends approximately 6 inches upwards in length and has a drawstring mechanism integrated with its upper most portions. When a user desires to secure the bio-media contents in bio-media filter 208, the drawstring mechanism can be tightened down over the top area of bio-media filter 208. As mentioned earlier, the top bio-media filter 208 holds grass plant 213. In one embodiment, when the drawstring mechanism is tightened down around the bio-media it can only be tightened to a certain extent leaving a generally circular opening of approximately 6" in diameter, which also serves to provide some space for grass plant 213. Rock mulch may be placed on top of the pliable mesh material and around grass plant 213.

The drawstring mechanism also provides a user with easy access to the bio-media in bio-media filter 208 when replacement of its contents is desired. The drawstring mechanism also allows a user to easily open bio-media filter 208 as well as move the rock mulch aside when opening bio-media filter 208. If desired, a user (such as a landscape laborer or maintenance crew member) may remove bio-media filter 208 out of cylinder 703 by its lifting straps in the event the entire unit requires replacement or cleaning. The contents of bio-media filter 208 may be sent to a composting center for recycling and later reuse in a landscaped area.

FIG. 8 illustrates an alternative embodiment of system 100, which includes the use of water storage crates in lower detention basin 205 when system 100 is installed in an excavated area of less than approximately 4'-9' feet in depth. Atlantis® detention crates may be used, however, this is not to limit the scope of system 100. In this embodiment, water storage crates comprise lower detention basin 205 and are placed beneath the catch basins in forebay 105 and PDB 111. The crates may be placed in a staggered manner beneath the catch basins. However, other configurations and placements may be applied in constructing lower detention basin 205 without deviating from the scope of system 100.

At the top of one or more of the water storage crates of lower detention basin 205 are ports 802. Port 802 is an opening located at the top of lower detention basin 205 that may be approximately 6.5" in diameter. In the embodiment illustrated in FIG. 8, there are four ports 802 spaced along lower detention basin 205 in PDB 111, as well as two ports 802 located in lower detention basin 205 in forebay 105.

FIG. 9 illustrates cross sections of the alternative embodiment of system 100 depicted in FIG. 8. FIG. 9A is a representation of forebay 105 with an alternative lower detention basin underneath initial catch basin. As described above, the initial catch basin where runoff would first flow through may be comprised of the preferred embodiments described in FIG. 7 including specified bio-media filters 208 that are suitable for the particular location and purpose of system 100. Water would thereafter filtrate from the bottom of the filters of the catch basin and into lower detention basin 205.

In FIG. 9B, water passing from forebay 105 into the PDB 111 via drainage pipe 112, or other means, would flow through the components of PDB 111 catch basins as described above. After flowing through said catch basin, as represented by the arrows showing the gravity induced flow, the treated water would then percolate into lower detention basin 205, where it would fill and thereafter drain into the city stormwater system via outflow pipe 207.

15

## Stormwater Treatment Basin

FIG. 10 illustrates an embodiment such as for certain parts of the watershed where infiltration into the ground is not desirable, limited, or not permitted. This embodiment may be termed a stormwater treatment basin 1001 (“STB”) where runoff is treated and enters the city’s stormwater system. In this particular embodiment, forebay 105 as described above is foregone, however, its function is implemented into STB 1001. This may be done where space is limited, for example. It should also be noted that pond-lined channel extends beyond the edges of STB excavation 1002 to force greater amounts of landscape runoff to be given pre and primary treatment in system 1001. In most other respects, STB 1001 functions similarly to system 100 described above as runoff is still channeled into STP 1001 via drainage channel 103, landscape swale 106, and pond-lined channel 104. It also goes through pretreatment and primary treatment phases while passing through particular catch basins, but rather than these processes being separated in space and time, they are efficiently combined.

In FIG. 11, runoff would be directed from drainage channel 103 and landscape swale 106 onto pond-lined channel 104 and through decorative rock 204 all as discussed above and for similar purposes. It would then be channeled to the 1" elevated pre and primary treatment cylinders 1101, which could be comprised of, for example, CUDO® cubes, or some similar variation. The top portion of the pre and primary treatment cylinders 1101 would be comprised of a perforated cap 601, such as to serve as an additional filter for large debris and as platform on which to place decorative rock 204. Runoff would be evenly distributed to each pre and primary treatment cylinder 1101. The initial 6" of each pre and primary treatment cylinder 1101 would serve as a silt detention basin 1101A. Water would thereafter percolate into a pretreatment filter 1101B, which, for example, could be 8" deep and comprised of activated carbon. The water would then percolate into the primary treatment filter 1101C, which, for example, could be 12" deep and comprised of a particular bio-media depending on the needs of the particular site.

After pre and primary treatment, by force of gravity, the treated water would then percolate into a lower detention basin 205, which could be comprised of small Atlantis® crates similar to those as mentioned above. These crates’ function would be analogous to that of the lower detention basins 205 comprised of CUDO® cubes described above. These crates could also be wrapped with an impermeable pond liner 404 to ensure water does not flow into the ground. FIG. 11, however represents an alternative depiction in that rather than lower detention basin 205 being fully wrapped in pond liner 404, pond liner 404 is extended across the entire bottom of STB excavation 1002 directly above sand base 202. This allows for water to move freely between the void created by the crates. This embodiment also allows for lateral moving water from native soil 209 to be captured all four sides of STB excavation 1002. Once lateral moving water enters gravel 201 area from native soil 209, it will drain downward and be captured within pond liner 404 to be efficiently removed from the area. The arrows in the outflow pipe 207 represent the flow of water from STB 1001 of this particular embodiment to the city storm drainage system, for example, and not into the ground.

FIG. 12 depicts a side cross-section view of FIG. 11. In this depiction the slope of the swale can be easily seen, as well as the extended pond-lined channel 104, which helps to efficiently direct runoff to STP 1001 to pre and primary treatment cylinders 1101. As discussed above pre and primary treatment cylinders 1101 have silt detention basin 1101A, pre-

16

treatment filter 1101B, and primary treatment filter 1101C. Treated water then settles into the lower detention basin 205 where it is able to flow out of STP 1001 via outflow pipe 207. Other Embodiments

FIG. 13 depicts an alternative embodiment of system 100. This depiction represents the modular capability of system 100 to meet the needs of any particular site that would, for example, necessitate an “L” shaped high performance bio-swale. This embodiment is not to limit the scope of system 100, but may be useful to install near the corner of a building, or where real estate space is scarce. The modular nature of system 100 may also allow for it to be installed so as to fit within existing island planters in a parking lot. For this particular use, FIG. 13 depicts runoff entering system 100 from a preexisting landscape swale 106 area and/or drainage channel 103 into forebay 105. As described in detail above, runoff would be given a pretreatment in the forebay 105 area. It would then be directed to the PDB 111 primarily via drainage pipe 112 for a primary treatment.

As shown in FIG. 13, PDB 111 need not be constructed in such a way that its components are installed in a straight line. The modular nature of the system allows for the various components to be placed around corners and even negotiate 90 degree turns where, for example, CUDO® cubes are used. It is furthermore contemplated that system 100 would be able to accommodate any degree of turn, including 180 degrees and/or 360 degrees. Regardless of the variation of turn angle, system 100 still serves the same general purpose of treating runoff. After primary treatment in PDB 111, treated runoff could then infiltrate into the native soil, or be directed away from system 100 via outflow pipe 207.

Additionally, the embodiment depicted in FIG. 13, may be equipped for other uses. Water reuse pipe 117 may be installed to direct reuse water to system 100. Lower detention basin 205 may consist of double or triple stacked pond lined CUDO® cubes to maximize retention in order to reuse treated water. Moreover, in the event that space is truly at a premium, forebay 105 may be dropped and a system similar to that described in FIG. 12 may be installed allowing for pre and primary treatment to occur rather simultaneously. These variations flesh out the numerous capabilities and possibilities of system 100.

FIG. 14 depicts an alternative embodiment of system 100 that again represents the modular nature of the system that may be installed according to the needs of the particular site. As represented here, an alternative configuration of forebay 105 depicts horizontally and vertically aligned initial catch basins within forebay excavation 107A area, designed to allow for a multitude of landscape and paving drainage sources entering system 100 from various directions. PDB 111 also represents an alternate configuration where an additional row of catch basins and requisite lower components is installed, i.e. lower detention basin 205, which may be wrapped in any variation of material to achieve the desired purpose, such as to retain, detain, test, or otherwise make alternate uses of treated water.

Furthermore, each modular component of PDB 111 may be used for an alternate purpose. For example, one catch basin and its lower components, or a group of catch basins and its lower components—such as a square group of four or one horizontal row—may be used solely to retain water for reuse, while the rest of the system may be designed to treat runoff in order to safely drain to the city’s stormwater drainage system.

FIG. 15 depicts an embodiment of system 100 that includes two separate PDBs, 111 which represent the modular nature of system 100. However, this is not to limit the scope of system 100, as a multitude of PDBs 111, and/or forebays 105

may be necessary to properly accommodate the needs of the particular location, such as for stormwater volume and site restrictions. In addition, by adding PDBs **111**, and adjusting corresponding pond-lined weirs **109** and drainage pipes **112**, system **100** can be aligned with preexisting or proposed bioswales and may become a part of the landscape both functionally and aesthetically. This embodiment may also be modified in accordance with any of the other FIGS. discussed throughout this specification.

FIG. **16** depicts an embodiment of system **100** with one forebay **105** and one continuous PDB **111** with multiple groups of catch basins situated within PDB **111**. FIG. **16** also depicts a variation in the configuration of lower detention basin **205** in both forebay **105** and PDB **111**. As depicted, lower detention basin **205** in forebay **105** may be comprised of four CUDO® cubes upon which rest three initial catch basins. This demonstrates the modular nature of the system, in particular when it would be desirable to create a larger void for lower detention basin **205**. This same concept of variation on lower detention basin **205** is also applicable to PDB **111** as depicted in FIG. **16**.

Furthermore, it is not necessary to have a contiguous row of catch basins in PDB **111**. System **100** can function effectively by using pond-lined weirs **109** to direct pretreated runoff to separate groups of catch basins. In the preferred embodiment, pretreated runoff may flow from forebay **105** to the first group of catch basins in PDB **111** where the water may be treated at such a rate that inflow into the catch basin and its components would exceed outflow into lower detention basin **205**. As such, the pretreated runoff level would rise and flow over pond-lined weir **109** to the subsequent group of catch basins where a similar process may take place, until the pretreated runoff entered into the final group of catch basins. Top existing grade **1601** depicts an existing downward slope at 2% which may help to facilitate the process of channeling water from one group of catch basins to the next and eventually through the entirety of system **100**. Similarly, terrace **1602** depicts an alternative method of construction for PDB excavation **107B**, which also helps to facilitate the overall downward slope of system **100** in order to achieve the desired result of properly channeling water through and out of system **100**. Terrace **1602** also may serve to allow for lower detention basin **205** to rest upon a level base, which may further allow for the system to optimally function.

FIG. **17A** is an exploded perspective view of a modular catch basin **1700** in accordance with an embodiment of the invention. The primary elements of the modular catch basin **1700** may include cistern container **1707**, filtration housing **1705**, hollow cylindrical filter sock housing **1703**, and bio-media filter **1708**. Elements of the modular catch basin **1700** are described in detail herein including descriptions of sub-elements and combination of elements.

An excavation lined with filter fabric or liner **1704D** is generally excavated to house the modular catch basin. Liner **1704D** may be an impermeable liner such as a pond liner if the bioswale is to hold water for irrigation. Cistern container **1707** generally forms the base unit of the modular catch basin **1700**. The cistern container **1707** ideally may be placed upon a bed of sand to provide stability and also some amount of protection for the modular catch basin **1700** components. Cistern container **1707** is adapted to aggregate and, in some embodiments, store filtered water from a high performance bioswale. To funnel runoff or storm water into the modular catch basin **1700** for treatment, a water impermeable liner **1704A**, **1704B** may be placed over a top grate **1701**. As discussed above, the treated water may be reused in irrigation,

routed to a municipal storm water facility for further treatment, or allowed to permeate into the surrounding soil.

Another use of a cistern container **1707** is as a sampling unit. For example, a water testing device **1709** such as a bucket or other container may be placed inside a cistern container **1707**. Water collected in the bucket **1709** is readily accessible for sampling, testing, and reporting on the quality of the water. Such testing may be periodically conducted to determine the overall “health” of the bioswale system. Depending on the test results, bio-media or filter media replacement, vegetation replacement, or the addition of more modular catch basins **1700** may be warranted. Due to the importance and repeated nature of the sampling, it may be advantageous that access to the cistern container **1707** is quickly and easily accomplished so that maintenance can be accomplished economically by one maintenance worker.

Referring to FIG. **17A**, the exemplary cistern container **1707** is formed of a hollow support structure half-unit mounted on a bottom grate **1711**. Atop the bottom grate **1711** may be placed a sampling bucket **1709** also referred to as a water testing device or sampling device.

In FIG. **17A** the cistern container **1707** is depicted as a half-unit but it should be noted that one or more hollow support structure full units may be used to form the cistern container **1707**. The amount of water to be stored, the depth limit of the excavation, and width of the bioswale may all be factors when considering the quantity of half-units to stack atop each other to form the cistern container **1707**. For example, if the filtered run-off water to be collected in the cistern containers **1707** are to be used for irrigation, two or more hollow support structure full units may be used because of the need to collect and store more water. On the other hand, if the depth of the bioswale excavation is limited by pipes, subterranean rock formations, or other obstructions then a hollow support structure half-unit may be used instead. Similarly, a hollow support structure half-unit may be used if excavation depth is limited but the width of the bioswale is not as constrained. Likewise, city and state regulations may require expensive civil engineers to excavate beyond a certain depth. Thus it may be preferable to excavate a shallower basin and use a shallower cistern container **1707**.

In FIG. **17A**, a sampling bucket **1709** is placed on a bottom grate **1711**. The sampling bucket **1709** may be optional depending on the type of cistern container **1707** needed. In some embodiments of a high performance bioswale, a plurality of cistern containers **1707** may be placed adjacent to each other. In such a configuration, typically only one of the plurality of cistern containers **1707** would include a sampling bucket.

Each side of the cistern container **1707** may include removable sidewalls or side grates **1706**. In FIG. **17A** the four removable side grates **1706** (of the cistern container **1707**) are half sized to fit the hollow support structure half-unit. Removable side grates **1706** are designed to keep sand, silt, and gravel out of the cistern container **1707**. Filter fabric may be wrapped around the entire modular catch basin system to help keep sand and finer particulates from sifting down into the cistern container **1707**. The filter fabric, the hollow support structure, and side grates **1706** allow water (and air) to enter and exit the cistern container **1707**, yet keeps out sand, gravel and silt.

Covering the top of the cistern container **1707** is a connector ring **1702**. A connector ring **1702** generally includes a removable support grate **1702A** to rapidly access the cistern container **1707** and the sampling bucket **1709** contained therein. The connector ring **1702** may be fastened to the cistern container **1707** at the perimeter of the ring connector.

The center of the connector ring **1702** may include a removable support grate **1702A**. Once attached to the connector ring **1702**, the support grate **1702A** serves to support a filter sock housing **1703**. In FIG. 17A the support grate **1702A** is depicted as being circular shaped, however other shapes may also serve the same support function.

Atop the cistern container **1707** and resting on the connector ring **1702** is a filtration housing **1705**. The exemplary filtration housing **1705** depicted in FIG. 17A is comprised of two hollow support structure half-units coupled to each other by their leg portions. The modular nature of the hollow support structure allows for more half-units to be added depending on the height of the filter sock housing **1703** to be housed.

As the name implies the filtration housing **1705** houses the bio-media filters **1708** and filter sock housing **1703**. The bio-media filter **1708** may be further divided into sub-components; a bio-media filter sock or handbag and bio-media or filter media. The filtration housing **1705** supports and protects the bio-media filters **1708** and filter sock housing **1703**, providing stability and a barrier against side or shear forces on the filter sock housing **1703**. Full circle side grates **1706** may also be attached to the filtration housing **1705** to prevent sand, gravel and silt intruding into the filtration housing **1705**.

In one embodiment of the invention, as illustrated in FIG. 17A, the filter sock housing **1703** is a hollow cylinder open at both ends. The sides of the cylinder **1703** may be perforated with holes or openings. The perforations may aid gas exchange of the bio-media filters **1708** and aeration of the vegetation **1713**. Although vegetation **1713** is depicted as a leaf bearing plant, it should be noted that grass plants are preferable due to their higher root to shoot ratio, durability, and ability to sequester metals. The perforated cylinder **1703** is adapted to hold a plurality of bio-media filters **1708** in a stacked configuration. The perforated cylinder **1703** is sized to fit the bio-media filter **1708** such that the latter can be removed easily but without allowing excessive water to run down between the sides of the cylinder and the bio-media filter **1708**. The height of the perforated cylinder **1703** may depend on the quantity of bio-media filters **1708** the perforated cylinder **1703** will hold. The height dimension of the perforated cylinder **1703** may also need to account for the one inch (1") preferred clearance from the top of the modular catch basin **1700** to the pond liner. As mentioned above, the one inch (1") elevation from the pond-lined channel **104** allows for even distribution of run-off into the modular catch basins **1700**.

Inside each perforated cylinder **1703** may be one or more bio-media filter **1708**. The bio-media filter **1708** are designed to contain a filter media such as sandy loam, bio-char, lava rock, perlite, sand, and activated carbon or additives such as chlorinated tablets. The filter media may also be a bio-media such as proprietary designer soil. A designer soil may contain a specified mixture of organic and inorganic minerals that target and sequester contaminants such as metals, hydrocarbons, bacteria, and organic and inorganic nutrients. Other combinations of organic and inorganic filter media may be utilized without deviating from the scope of the invention. A sealing disk **1712** may be placed at the bottom of the lowest bio-media filter **1708N** to prevent root growth from entering the cistern container **1707**. The bio-media filter **1708** is adapted to allow easy maintenance, removal, and replacement of the filter media. Each bio-media filter **1708** may be individually lifted out of the perforated cylinder **1703** and replaced by a minimal amount of personnel with a minimal amount of training.

In some embodiments of the invention, cistern container **1707** and filtration housing **1705** are both formed of hollow

support structure half-units. While hollow support structure units are preferred for reasons that will be made apparent by the rest of the specification, other types of a containers or plastic crates may suffice. Rigid plastic crates or boxes may be substituted in place of the cistern container **1707** and filtration housing **1705** with positive results.

Refer now to FIG. 17B-17D for an in-depth look at the hollow support structure halves. Generally any material that can be molded or cast can be used to fabricate each hollow support structure half-unit used in the cistern container **1707** and filtration housing **1705**. Materials may include but are not limited to plastics such as injection-molded polymer, polypropylene, high density polyethylene (HDPE), low-density polyethylene (LDPE).

The hollow structure of each hollow support structure half-unit allows air to circulate through the modular units to avoid anaerobic conditions and to facilitate grass plant growth within the top bio-media filter **1708A**. For filtration to function properly there has to be an exchange of gases (aerobic conditions) so the biology, bacteria, and grass roots in the bio-media thrive and filter pollutants. Anaerobic conditions may also promote methane gas buildup in the cistern container **1707** as organic matter decomposes in the modular catch basin. Furthermore, gas exchange allows the cistern container **1707** to dry so that silt collected therein can be readily vacuumed out.

Referring now to FIG. 17B, a hollow support structure half-unit is depicted stacked atop another hollow support structure half-unit such that the legs of each half-unit are joined at the ends. As can be seen in FIG. 17B-17D, between each leg **1715** of the hollow support structures is a semi-circle or arch. When coupled together the two circle semi-circle create an opening into the center portion of the joined hollow support structure full unit. As shown in FIG. 17C, the legs **1715** are coupled together by complementary peg **1716** and hole element **1717** formed into each leg. In FIG. 17C the peg **1716** is formed on the upper leg and the hole **1717** in the lower leg, however the position of peg **1716** and hole **1717** may be reversed as shown in FIG. 17B (the two legs on the left side). The peg **1716** may include drainage slit **1719** to transfer water from the top half-unit to the bottom half-unit. Water inside the bottom half-unit may exit through drain holes **1714** formed in the hollow support structure.

Each hollow support structure half-unit may have a plurality of drain holes **1714** on an inside surface to allow water to flow out of the hollow spaces and into the inner portion of the hollow support structure. The upper half-unit typically has plugs positioned within its drain holes **1714** so that the water may drain down inside of the hollow structure through a side filter media **1723** (e.g., sand), a filter fabric, the hollow legs, and out through the drain holes **1714** in the lower half-unit.

In FIG. 17D, the upper and lower half-units are coupled to form a hollow support structure full unit. In one embodiment, the hollow support structure full unit measure approximately two feet by two feet (2"x2"), thus forming a cube; however other shapes such as a rectangle, polygon, or cylinder may be substituted without taking away from the inventive concept. The top portion of the upper hollow support structure half-unit may comprise a circular opening sized to fit the perforated cylinder **1703**. The circular opening is adapted to receive and support the perforated cylinder **1703**.

The lower hollow support structure half-unit may include drain holes **1714** to drain the sand filtered residual run-off water. Silt **1718** may form at the bottom of the lower half-unit after continuous use. This silt may be left to dry and vacuumed out or otherwise removed during maintenance of the high performance bioswale.

## 21

Previously, a means of attaching the upper and lower half-units of a filtration housing 1705 was disclosed. A similar method of using pegs 1716 and complementary holes 1717 may be used to fasten the legs 1715 of a hollow support structure to the corners of a bottom grate 1711. For example, in FIG. 17E a leg 1715 with a peg extension 1716 may be mated to a corner connector 1720 with a complementary hole 1717. In a similar but reversed situation illustrated in 17F, a leg 1715 with a hole 1717 is mated to a corner unit 1720 with a complementary peg 1716. The corner connectors 1720 may be molded as a unitary part of the top and bottom grate 1711 or may be added as needed. For example, in FIG. 17G, a snap-in corner unit 1721 may be snapped in place and fastened with a lock-tie 1722 or other fastening device. Snap-in corner units 1721 allow modification of existing catch basin grates with additional cistern containers 1707 or filtration housings 1705.

FIG. 18A is a system diagram of a modular catch basin embodiment 1800 which may be used in the forebay of a high performance bioswale. The modular catch basin 1800 illustrated in 18A share similar elements with the system described in FIG. 17A with some notable additions and differences. The modular catch basin 1800 of FIG. 18A, includes a sealing ring 1725. The modular catch basin 1800 also uses cistern container 1807 comprising a hollow support structure full-unit instead of a half-unit. This modular catch basin 1800 also includes a perforated cylinder 1803 that is not perforated along a portion of its length. Although the system diagrams 1800 and 1900 attempts to illustrate each component in its correct relative position, it should be noted that some components may fit through other components, thus their order is variable.

It is preferable to leave the upper portion of the perforated cylinder 1803 free of perforation when no vegetation 1713 is planted in the top bio-media filter 1708A. As mentioned previously, the perforations in the perforated cylinder 1803 aid in gas exchange and aeration. In this embodiment, vegetation 1713 is not present; therefore the perforations are not needed in the upper portion of the perforated cylinder 1803. The modular catch basin 1800 illustrated in FIG. 18A may be more suited for use in the forebay of a high performance bioswale system. The forebay pretreats and regulates the stormwater. Once the forebay fills up with pretreated stormwater, the water flows into the primary detention basin (PDB) where it receives a primary treatment.

Sealing ring 1725 is designed to prevent run-off water from bypassing the bio-media filter 1708 and flowing unimpeded through the gap between the bio-media filter 1708 and the inner wall of the perforated cylinder 1703. The sealing ring 1725 blocks the gap and forces run-off water to percolate through the bio-media. The sealing rings 1725 in FIG. 18A are shown separated from the bio-media filter 1708. This exemplary sealing ring 1725 may be a foam strip applied between the bio-media filter 1708 and the inner wall of the perforated cylinder 1703.

Sealing ring 1725 may also be attached to the bio-media filter 1708 via a series of loops sewn around the circumference of the bio-media filter 1708. The sealing ring 1725 may be threaded through the loops much like a belt through the belt loops of a pair of pants. When the bio-media filter 1708 is filled with a filter media and placed in the perforated cylinder 1703, the sealing ring 1725 presses against the perforated cylinder 1703 to prevent leakage.

The use of two hollow support structure half units as the cistern container 1807 may necessitate the use of a riser 1810. The purpose of the riser 1810 is to adjust the elevation of the sampling bucket 1709. It may be preferable for the top of the

## 22

sampling bucket 1709 to be approximately four (4) inches above the waterline high level. The riser 1810 may be formed of a water resistant material strong enough to resist the weight of a filled bucket 1709 of water over a lengthy period of time. Furthermore, the riser 1810 may be adapted to removeably secure the sampling bucket 1709 to prevent it from sliding or tipping. For example, the riser 1810 may include a shallow depression in which the bottom of the sampling bucket 1709 may rest.

FIG. 19A illustrates another embodiment of a modular catch basin 1900. The modular catch basin system 1900 of FIG. 19A includes three bio-media filters 1708 in contrast to the two found in FIG. 18A. The use of a variable number of bio-media filter 1708 allow the modular catch basin 1900 to be specifically tailored to the particular types of pollutants found in the local run-off water. For example, in a three bio-med filter system, three types of filter media, such as pre-treatment, primary treatment, and polishing treatment, may be tailored to the type of pollutants found. In this specific embodiment, vegetation 1713 is illustrated as part of the modular catch basin 1900. This particular system shown in FIG. 19A may be more suited to use in a primary detention basin ("PDB"). The forebay removes larger debris from the run-off and regulates the flow of water whereas the PDB "polishes" the stormwater for reuse, infiltration or release. Vegetation 1713 is preferably used only in the PDB.

FIGS. 18B and 19B illustrate cross section side views of the modular catch basin 1800 and 1900, respectively as they would appear when assembled. Connector rings 1702 are shown connecting the cistern container 1707 to the filtration housing 1705. The connector rings 1702 are held in place by rows of parallel ridges adapted to lock onto the bottom of the filtration housing 1705 and top of the cistern container 1707. Filter fabric 1813 may be wrapped around the entire modular catch basin system. The filter fabric 1813, the hollow support structure, and side grates 1706 allow water (and air) to enter and exit the modular catch basin, yet keeps out sand, gravel and silt.

At the top of the modular catch basin covering the filtration housing 1705 is a top grate 1701 and a top grate cap 1701A. In FIG. 18B a top grate 1701 and a top grate cap 1701A are illustrated attached to and covering the filtration housing 1705. In FIG. 19B only the top grate 1701 is illustrated covering the filtration housing 1705. The top grate cap 1701A was removed to accommodate vegetation 1713. The top grate 1701 and top grate cap 1701A removeably attach to the filtration housing 1705 in a similar manner as the connector ring 1702. More details on the means of attachment may be seen in the magnified cross section views (FIGS. 18C and 19C).

The attachment of a top grate 1701 and top grate cap 1701A to the filtration housing 1705 is shown in more detail in FIG. 18C. Two parallel ridges 1810 running along the perimeter of the top grate cap 1701A are adapted to lock onto the top of the perforated cylinder 1703 and a flange 1815 of the top grate 1701. An edge of pond liner 1704B may also be locked between the two parallel ridges 1810. Specifically, the wall of the perforated cylinder 1703, the flange 1815, and the edge of the pond liner 1704B fit tightly between the twin ridges 1810 of the top grate cap 1701A. Although the circular ridges are illustrated as prong like structures, keep in mind that FIG. 18C is a cross section side view and thus the prongs are merely a slice of continuous parallel circular ridges 1810. Pond liner 1704B is also ballasted by decorative rocks (not shown) to keep the pond liner in place.

In FIG. 19C, a cutout side view of a top grate 1701, with the top grate cap 1701A removed, is illustrated. In this illustration, the top grate 1701 attaches to the walls of the filtration

housing **1705**. Like the top grate cap **1701A**, the top grate **1701**, also attaches by means of parallel ridges locking onto the walls of the filtration housing **1705**. Specifically, the outer prong **1920**, at the perimeter of the top grate **1701**, locks onto the straight peripheral wall of the filtration housing **1705** and the inner prong **1925** locks onto the circular wall of the opening in the center of the filtration housing **1705**. In FIG. **19C**, the top grate cap **1701A** has been removed to allow vegetation to grow from the top bio-media filter. The edge of pond liner **1704A** is not trapped by top grate cap **1701A**; however the pond liner **1704A** is tightly fitted around the circular flange **1815** in the top grate **1701** and is also ballasted by decorative rocks to prevent excessive movement.

Once the primary components of a modular catch basin **2000** are assembled, they may be placed in a high performance bioswale to treat urban run-off. FIGS. **20A-20D** illustrate cross section side views of assembled exemplary modular catch basins. The modular catch basins depicted in FIGS. **20A-20D** are similar in most respects. To avoid repetition, only FIG. **20A** will be described in detail.

In FIG. **20A**, the exemplary catch basin system **2000** includes a cistern container **1707** and a filtration housing **1705**. A hollow support structure half-unit, with sampling bucket **1709** therein, comprise the cistern container **1707**. Above the cistern container **1707** is the filtration housing **1705**, comprising a hollow support structure full-unit containing three bio-media filters **1708**. The top bio-media filter **1708A** is potted with vegetation **1713**. Pond liner **1704A** forms the bottom of the bioswale and is slightly sloped towards the opening of the modular catch basin to channel run-off **2020** into the catch basin. The slope in the pond liner **1704A** may be accomplished by placing curbs or bases of pea gravel or landscape foam **2025** such as geofoam to elevate the pond liner **1704A** at the sides of the forebay or primary detention basin.

Decorative rocks **2004** may be placed atop the pond liner to provide an aesthetic touch. Decorative rocks **2004** may aid in ballasting the pond liner **1704A** and may also filter out large debris before they reach the top grate **1701** of the catch basin. Decorative rocks **2004** also displaces the storm water so that water flows into the perforated cylinders **1703** evenly and provide ultra violet radiation (UV) protection to the pond liner **1704A** underneath, preventing deterioration. The top of the modular catch basins are preferably elevated approximately one inch (1") above the pond liner **1704A** to evenly distribute run-off water **2020** to all the catch basins in the bay. Directional arrows **2015** in FIG. **20A** represent the direction of the water flow as the run-off **2020** percolates through the bio-media filter **1708** towards the cistern container **1707**.

The various embodiments of the modular catch basins described herein share a fundamental advantage over many of the bioswale filtration systems currently in use. Rather than using piping that is prone to clogging and has relatively low flow volume, the high performance bioswale uses pond liners to channel the run-off towards the modular catch basins.

From there, the run-off water percolates by gravity action through the bio-media filters **1708** and is collected in the cistern container **1707**. The modular catch basins are easy to install and easy to maintain. The current invention, improves on prior art filtration systems with a less costly, more reliable, and more eco-friendly method and apparatus of filtering storm water run-off.

The modular advantage of the exemplary catch basin systems is exemplified in FIGS. **20A-20D**. Various configurations of modular catch basin are illustrated showing the ease with which the bioswales can be scaled to accommodate project size by adding and subtracting modular catch basins.

As shown in FIGS. **20C-20D**, two and three modular catch basins may be placed side by side, increasing the volume of run-off treated per unit of time.

#### Bio-Media Filters

One of the objectives of the modular catch basin system is to provide a bioswale that can be easily maintained without the use of heavy equipment or intensive labor. One of the many novel improvements that allow the modular catch basin **1700** to meet this objective is the addition of the bio-media filter **1708**. The bio-media filter **1708** allows one maintenance worker to service a bioswale rapidly and efficiently with minimal training.

Vegetation **1713** may be grown in a bio-media filter **1708** composed of approximately 50% organics (primarily composted greenwaste), the remaining 50% is sandy loam. The bio-media (full of microscopic flora and fauna) and grass roots break down the bacteria, organic nutrients, hydrocarbons and the metals (primarily zinc and copper) are sequestered in the sandy loam.

When the bio-media has reached its capacity to mitigate pollutants it is removed and replaced (by an on-site landscape maintenance contractor) with fresh bio-media filter **1708** and grasses as needed. The used bio-media filter **1708** including the grasses may be added to the site's existing greenwaste and taken to a local greenwaste composting facility where it is diluted and processed into a nutrient rich compost to be used in the landscape. Plants require micro elements such as zinc and copper, making the greenwaste valuable compost. The invention captures urban pollutants, processes it, and reuses it in the landscape—a "cradle to cradle" solution. The old bio-media filter **1708** may be recycled and reused by filling them with new filter media. The old filter media contained therein may be sent to a composting center for recycling and later reuse in a landscaped area.

Various views of an exemplary bio-media filter **1708** are illustrated in FIGS. **21A-21C**. In general bio-media filter **1708** is a flexible cylindrical filter hand bag or sock made of a permeable material preferably resistant to degradation from soil and water. The cylindrical body of water permeable material having a ring shaped bottom with a bottom opening **2130** and a circular-shaped edge opposite the ring shaped bottom. The permeable material allowing filtration from bag to bag thru the bio-media.

A drawstring **2115** may be threaded through the top of the bag to cinch the bag closed as needed. The upper section of the bio-media filter may be made of a mesh material. When cinched the mesh material is at the top of the bag and allows more water to flow through the top of the bio-media filter **1708**. Two sturdy lifting straps **2110** may be woven into the sides of the bag. A portion of the titling straps **2110** may be attached to the bottom of the bio-media filter **1708** to provide extra reinforcement. Threaded through loops **2120** around the circumference of the sock may be one or more sealing rings **2125**. A mesh disk **2105** may be inserted into the bio-media filter **1708** to cover an opening **2130** in the bottom of the bio-media filter **1708**.

The bottom of the sock may have an opening **2130** or cut-out to allow root growth through the opening. Preferably this opening is smaller than the diameter of the bio-media filter **1708**. In FIG. **21B** the opening **2130** is depicted as a circular hole covered by a mesh material **2105**. The mesh material **2105** may be sewn into the bottom of the sock. Alternately, the mesh material **2105** may be made larger than the opening **2130** and placed inside the sock to cover the opening **2130**. The mesh disk **2105** allows root growth but prevents the bio-media from escaping the bio-media filter

**1708.** Vegetation **1713** may be placed inside the bio-media filter **1708A** as shown in FIG. **21C**.

The bio-media filter **1708** is uniquely adapted to encourage vegetation growth. Besides having a stream of nutrient rich run-off water flowing through, the bottom opening **2130** in the bio-media filter **1708** also allows the root system to grow from the upper sock to the lower sock. As depicted in FIG. **22A**, the roots **2215** grow virtually unimpeded through the openings in the socks below the vegetation **1713**. For healthier growth, vegetation **1713** may be "potted" in a nutrient rich area of potting soil **2220** or the like within the bio-media **2225**. A larger root system **2215** will generally treat more water by accumulating and sequestering more pollutants and metals. A permeable plastic insert or sealing disk **1712** may be placed over opening **2130** in the bottom sock to prevent the root system **2215** from growing out of the perforated cylinder **1703**. The sealing disk **1712** will also keep the bio-media **2225** from exiting the last bottommost bio-media filter **1708**.

FIGS. **22B-22C** illustrate cross section views of exemplary bio-media filter **1708** with different types of sealing rings **1725** attached. The diameter of a bio-media filter **1708** is preferably slightly smaller than the perforated cylinder **1703**. However due to manufacturing tolerances and the type of filter media **2225** used, a small gap may be present between the bio-media filter **1708** and the inner wall of the perforated cylinder **1703**. Water tends to flow down the path of least resistance thus a gap may permit water to flow unfiltered down into the cistern container **1707**. The sealing rings **1725** may prevent water from flowing between the sock and the cylinder wall, bypassing the bio-media filters **1708**. The sealing rings **1725** are adapted to substantially fill the gap, thus forcing the water to flow through the filter media **2225**. The sealing ring **1725** depicted in FIG. **22B** may be a foam strip or tubing separate from the bio-media filter **1708**. For example, once the bio-media filter **1708** is placed into the perforated cylinder **1703** and the drawstring **2115** has been cinched closed, a sealing ring **1725** may be wedged into the gap between the sock and the inner wall of the perforated cylinder **1703**. The sealing ring **1725** may prevent unfiltered run-off water from flowing down the gap and into the cistern container **1707**.

In FIG. **22C**, an alternative embodiment of the sealing ring **2125** is illustrated. In this embodiment, the sealing ring **2125** is attached to the bio-media filter **1708** through a series of loops **2120** sewn into the perimeter of the sock. The unitary sealing ring **2125** depicted may be easier to use and thus preferred. Other means of attaching a sealing ring **2125** to the sock should be obvious to one skilled in the art and is within the scope of the invention.

FIGS. **23A-29B** illustrate various exemplary side grates **1706**, connector rings **1702**, support grate **1702A**, top grates **1701**, and bottom grates **1711** are shown in cross section and plan views. The various structures depicted may be formed of a similar material as the hollow support structure, e.g. injection-molded polymer, polypropylene, high density polyethylene (HDPE), low-density polyethylene (LDPE).

Side grates **1706** are shown in FIGS. **23A-24B**. The side grates **1706** of FIG. **23A-23B** are full circle side grates **1706** adapted for use with the hollow support structure full units. The side grates **1706** of FIG. **24A-24B** are half circle side grates **1706** adapted for use with the hollow support structure half units. The side grates **1706** are preferably formed of radially spaced ribs interspersed with circular ribs in a web-like lattice. The spaces in between the ribs may be hollow allowing the passage of both air and water. A side grate **1706** flange may surround the rib structure. When the side grates

**1706** are placed over the openings in the hollow support structure, the flange may overlap the side of the hollow support structure, to keep the side grates **1706** in place.

FIGS. **25A-25B** illustrate an exemplary connector ring **1702**. The connector ring **1702** connects the cistern container **1707** with the filtration housing **1705**. The center of the connector ring **1702** has a circular opening to accommodate a support grate **1702A**. Radially spaced ribs also provide structural support to the connector ring **1702**, and like the grates and side grates, the spacing between the ribs are hollow. Parallel ridge fasteners formed on the connector ring **1702** may be used to secure the cistern container **1707** to the filtration housing **1705**.

An exemplary support grate **1702A** is illustrated in FIGS. **26A-26B**. The support grate **1702A** may be formed of radially spaced ribs interspersed with circular ribs much like the side grates **1706**. The support grate **1702A** may fasten to the inner set of upward facing parallel ridge fasteners on the connector ring **1702** or alternatively the support grate **1702A** may rest on flanges protruding from the inner opening in connector ring **1702**. The support grate **1702A** supports the perforated cylinder **1703** and bio-media filter **1708** over the cistern container **1707**.

Drain Down Grommets

In FIG. **30** an exemplary high performance bioswale is illustrated. Forebay **3005**, weir section **3022**, and primary detention basin (PDB) **3011** are covered by separate pond liners overlapping at dashed lines A and B. Forebay liner **3020** overlaps weir liner **3022** at dashed line A. Weir liner **3022** overlaps primary detention basin liner **3024** at dashed line B. The individual pond liners **3020**, **3022**, and **3024** are glued together at the overlap. The order of overlap, forebay to weir to PDB is important to prevent water from flowing under the liner.

As mentioned in the previous sections, the modular catch basin **1700** is elevated approximately one inch (1") above the pond liner. This elevation allows for the even distribution of the run-off water to all the modular catch basins **1700** in a forebay **105** or primary detention basin **111**. However, a residual one inch (1") of water may be left behind because of the elevation.

This residual water may stagnate in the forebay **3005** and primary detention basin **3011** if left untreated. By law, standing pools of water are not permitted because of disease carrying vectors. Thus a method of draining this residual water is needed. Referring to FIG. **30-31**, a plurality of drain down grommets **3015** may be adapted to remove and filter the residual run-off water trapped in forebay **3005** and primary detention basin **3011**.

Referring now to FIG. **31-33**, in order to filter the residual run-off **3220**, one or more drain down grommets **3015** are provided in the pond liner **1704A**, **1704B** above top grate **1701** and the hollow support structure of the filtration housing **1705**. The drain down grommets **3015** drains the residual water through the hollow space in the legs and side of the hollow support structure. A filter fabric **3225** is placed in the bottom of one or more legs to retain a filter media. The filter media **3223**, for example sand, is placed on top of the filter fabric **3225** in the hollow spaces of the hollow support structure to filter the residual run-off **3220**. Residual run-off draining through the drain down grommet **3015** is filtered through the sand **3223** and filter fabric **3225** and exits a drain hole **1714** in the lower half-unit.

FIG. **32A** is a magnified side view of a drain down grommet **3015** coupled to a water impermeable material, such as a pond liner **1704A**, **1704B**. The grommet **3015** includes a drainage channel **3210** passes through the middle of the

grommet. Run-off water passes through the grommet **3015** and pond liner **1704A**, **1704B** before entering the hollow walls of the support structure of the filtration housing **1705**. FIG. **33**, illustrates the flow of residual run-off through the filter media **3223** in the hollow support structure as represented by arrows **3315**.

The solid wall support structures illustrated in FIG. **17A** may require some modification of the flow path. Instead of flowing through filter media in the hollow walls of the filtration housing **1705**, the grommets **3015** drain down directly onto filter media over filter fabric between the four solid walls and the perforated cylinder **1703**. Filter fabric **3225** may also be placed over the connector ring **1702** and support grate **1702A** to prevent sand and other particulates from migrating into the cistern container **1707**.

#### Self-Supporting Filter Sock Housing

Although previous disclosed embodiments have included a hollow support structure for the filtration housing **1705**, the modular catch basin **3400** may operate without the use of a hollow support structure. In FIG. **34-35**, a perforated hollow cylinder **3403** connected to cistern container **1707** operates without the support of a hollow support structure. Run-off is still channeled into and through bio-media filter **1708** and into cistern container **1707** as before. However, without a hollow support structure, residual run-off does not have drainage path through the hollow support structure. Instead, hollow cylinder **3403** is adapted with support shoulder **3510** to channel the residual water from the drain down grommet **3015** into the support shoulder **3510** and from there into the perforated hollow cylinder **3403** and bio-media filter **1708**. Support shoulders **3510** are hollow ledges fluidly connected to hollow cylinder **3403**. The support shoulder **3510** provides a base on which to attach the top grate **1701**. Drain down grommet **3015** mounted on the pond liner **1704B** above top grate **1701** drain into the support shoulder **3510** fluidly connected to the hollow cylinder **3403**. From the hollow cylinder **3403**, the residual run-off joins the flow path of normal run-off and is filtered into cistern container **1707**. Filter fabric **3325** is wrapped around the cistern container **1707** to prevent sand from migrating into the cistern container **1707**.

Connector ring **3602** of FIG. **36** is adapted for use with the hollow support structure-less modular catch basin. The center of the connector ring **3602** has a circular opening to accommodate a support grate **1702A**. Radially spaced ribs also provide structural support to the connector ring **3602**, but unlike connector ring **1702**, sheeting cover the spaces between the ribs and the sheeting is perforated by perforations **3615**. Connector ring **3602** may be used to secure the cistern container **1707** to the perforated cylinder **3403**. In FIG. **36A** the exemplary connector ring with perforations **3602** is wrapped in a filter fabric **3225** to prevent sand from entering the cistern container **1707**.

In previous disclosed embodiments, the grates and connector rings have been illustrated as being squares. FIGS. **37-40** disclose unitary grates and connector rings for assembling modular catch basin which are connected together. In FIG. **37** unitary top grate **3701**, unitary connector ring **3702**, and unitary bottom grate **3711** are all of one-piece design. Similarly, FIGS. **41-42** discloses joined filtration housings **4105** and joined cistern container **4107**. The unitary grates and joined containers may allow for more precise placement of units next to each other thus allowing more even distribution of run-off to each modular catch basin.

#### Method of Maintaining a Modular Catch Basin

The typical prior art bioswale requires an extraordinary amount of maintenance to maintain its effectiveness at removing contaminants from run-off. Over the course of

many rainfalls, the typical prior art bioswale fills with heavily polluted silt that cause the bioswale's primary filtration means; soil biology and vegetation, to fail. To adequately maintain a bioswale, the polluted silt needs to be removed by removing the top 1"-2" of soil and vegetation. The bioswale may need to be rebuilt. Few existing bioswales are well maintained due to the prohibitive cost. A significant percentage of existing bioswales lay unattended and are virtually useless for removing run-off contaminants. Thus there is a need for a high performance modular bioswale system that is highly effective yet relatively easy to construct and maintain. The following method of maintaining a modular catch basin was developed to meet this need.

The method disclosed herein for maintaining the modular catch basin may be performed at relatively low cost by a single maintenance worker. No costly training or heavy machinery is required to maintain the high performance bioswale at peak operating efficiency for dozens of years. Momentarily refer back to FIGS. **19A**, **20A**, and **21A** for illustrations of the method of installation.

To install a modular catch basin, a maintenance worker first removes decorative rocks **2004** that may be obstructing top grate **1701**. Next the maintenance worker removes the top grate **1701** of the modular catch basin to reveal a first bio-media filter **1708A** mounted within a hollow perforated circular cylinder **1703**;

By reaching down into the hollow perforated circular cylinder **1703**, the maintenance worker may grasp and pull up on a pair of lifting straps **2110** at the top used bio-media filter **1708** to remove it from the hollow perforated circular cylinder **1703** and the catch basin. Once the top bio-media filter **1708A** is removed, the lower used bio-media filter(s) **1708** can be removed in a similar manner.

If water quality testing needs to be done, a support grate **1702A** underneath the hollow perforated circular cylinder **1703** may be removed to reveal a water sampling device **1709**. The maintenance worker may test water captured by the water sampling device **1709** to determine if the first and second bio-media filter **1708** require replacement. Excessive silt may accumulate at the bottom of the filtration housing **1705** or cistern container **1707**. During summer months or other dry spells the silt may be left to dry and vacuumed out of the catch basin. Some light washing of the hollow support structure may also be done after the silt has been removed.

The decorative rock and pond liner will collect debris and silt. The debris may be removed and the silt washed down into the lower cisterns through an opened catch basin. During the summer months (June-September) the cisterns may dry. Late September the dried silt is ideally vacuumed out of the cisterns

The maintenance worker may replace the used bio-media filter **1708A** with new ones by first replacing the support grate **1702A** and then grabbing a pair of lifting straps **2110** of a first new bio-media filter **1708** and lowering the first new bio-media filter **1708** into the hollow perforated circular cylinder **1703**. To ensure that run-off water does not bypass the bio-media filter **1708**, the maintenance worker may need to adjust a first sealing ring **2125** to seal between an edge of the first new bio-media filter **1708** and an inner surface of the hollow perforated circular cylinder **1703**.

Placement of more bio-media filters **1708** and adjusting their sealing rings **2125** may be repeated as needed depending on the type of bioswale being maintained. Once all the bio-media filters **1708** are in place, the top grate **1701** of the modular catch basin is reinstalled to cover over the new bio-media filter **1708**.

Vegetation **1713** may be grown in a bio-media filter **1708** composed of approximately 50% organics (primarily composted greenwaste), the remaining 50% is sandy loam. The bio-media (full of microscopic flora and fauna) and grass roots break down the bacteria, organic nutrients, hydrocarbons and the metals (primarily zinc and copper) are sequestered in the sandy loam.

When the bio-media has reached its capacity to mitigate pollutants it is removed and replaced (by an on-site landscape maintenance contractor) with fresh bio-media filter **1708** and grasses as needed. The used bio-media filter **1708** including the grasses may be added to the site's existing greenwaste and taken to a local greenwaste composting facility where it is diluted and processed into a nutrient rich compost to be used in the landscape. Plants require micro elements such as zinc and copper, making the greenwaste valuable compost. The invention captures urban pollutants, processes it and reuse it in the landscape—a “cradle to cradle” solution. The old bio-media filter **1708** may be recycled and reused by filling them with new filter media **2225**. The old filter media **2225** contained therein may be sent to a composting center for recycling and later reuse in a landscaped area.

#### Method of Installing a Modular Catch Basin

Typical prior art bioswales in use today are often expensive to install. Large excavations are required to house the bioswales and some may even require a concrete housing surrounding the bioswale. The high performance bioswale and modular catch basin disclosed herein require less area, thus leaving a smaller footprint on the environment. Furthermore, instead of costly concrete basins, the high performance bioswales and modular catch basin systems use pond liners to channel run-off and form treatment basins instead of concrete. The following method of installing a modular catch basin allows a high performance bioswale to be scaled to fit the project need. Momentarily refer back to FIGS. **17D**, **19A**, and **20A** for illustrations of the method of installation.

There are generally two excavations that receive the invention. Both excavations are sized according to need. The size of the watershed, soil percolation and volume of stormwater are all factors that are considered when determining the size of the excavation. The first excavation is a forebay **105** where stormwater is pre-treated and volumes regulated. After the forebay treatment, stormwater flows into the primary detention basin **111** where it receives a primary filtration or “polishing” treatment. Treated water is captured in the lower cistern container **1707** where it then allowed to infiltrate existing soils into the aquifer; be reused (pumped) as irrigation water in the landscape, and or allowed to drain into the existing municipal stormwater drainage system.

Soil must first be excavated to create a first excavation for a water treatment system. The area of soil excavated may be less than needed relative to typical prior art bioswale systems, due to the efficiency of the modular catch basin. Once the excavation is completed, the excavation may be lined with a fabric or impermeable lining **1704D**. For high performance bioswales that reuse the treated water for irrigation, an impermeable liner holds the water until needed. A fabric or permeable liner can be used in high performance bioswale systems that allow the treated water to permeate back into the soil.

A first hollow support structure is then placed into said first excavation to function as a cistern container **1707**. Sand may be used to support and level the cistern container to the proper elevation.

A second hollow support structure can be coupled to the first hollow support structure to function as a filter container **1705**. A filter fabric **3225** may be inserted into at least one hollow leg **1715** of the second hollow support structure to

filter residual run-off from the drain down grommets. At least one hollow leg **1715** of the second hollow support structure may also be filled with a with filter material **1723** such as sand, for a final drain down of the residual run-off water **3220**.

Next, a first perforated cylinder **1703** is installed into said second hollow support structure. Then, at least one bio-media filter **1708** is placed into said first perforated cylinder **1703**. The at least one bio-media filter **1708** comprising a proportion of at least one filtrating substance, e.g. sandy loam, bio-char.

Once the bio-media filter(s) **1708** are in place, the second hollow support structure is capped with a top grate **1701** and an impermeable liner **1704B** is overlaid around the first perforated cylinder **1703** over the top grate **1701**. Drain down grommets **3015** in the impermeable liner **1704B** are aligned to the hollow leg **1715** with filter material **1723** inside. Decorative rocks **2004** may be installed to ballast portions of said impermeable liner **1704B** and hold it in place.

The above method of installation may be repeated as needed to scale the high performance bioswale system to fit the project size. Different combinations of cistern container **1707** and filtration housings **1705** may be used to fit the filtration requirements as well as space availability.

Embodiments of modular catch basins for high performance bioswales have been described. The foregoing description of the various exemplary embodiments of the invention has been presented for the purposes of illustration and disclosure. It is not intended to be exhaustive or to limit the embodiments of invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching. It is intended that the scope of the embodiments of the invention not be limited by this detailed description, but construed by the claims and the equivalents to the claims that follow below.

#### What is claimed is:

1. A method of maintaining a modular catch basin for water reclamation, the method comprising:
  - removing a top grate cap of the modular catch basin to reveal a first bio-media filter mounted within a hollow perforated circular cylinder;
  - reaching down into the hollow perforated circular cylinder to grasp and pull up on a pair of lifting straps of the top used bio-media filter to remove it from the hollow perforated circular cylinder and the catch basin;
  - reaching down into the hollow perforated circular cylinder to grasp and pull up on a pair of lifting straps of a lower used bio-media filter to remove it from the hollow perforated circular cylinder and the catch basin;
  - grabbing a pair of lifting straps of a first new bio-media filter and lowering the first new bio-media filter into the hollow perforated circular cylinder;
  - grabbing a pair of lifting straps of a second new bio-media filter and lowering the second new bio-media filter into the hollow perforated circular cylinder; and
  - reinstalling the top grate cap of the modular catch basin to cover over at least the second new bio-media filter.
2. The method of maintaining a modular catch basin of claim 1, further comprising:
  - prior to the grabbing and the reinstalling, removing a support grate to reveal a water sampling device; and
  - testing water captured by the water sampling device to determine that the first and second bio-media filter require replacement.

31

3. The method of maintaining a modular catch basin of claim 1, further comprising:  
 prior to the grabbing the pair of lifting straps of the second new bio-media filter,  
 adjusting a first sealing ring to seal between an edge of the first new bio-media filter and an inner surface of the hollow perforated circular cylinder. 5
4. The method of maintaining a modular catch basin of claim 1, further comprising:  
 prior to the grabbing and the reinstalling,  
 reaching down into the hollow perforated circular cylinder to grasp and pull up on a pair of lifting straps of another lower used bio-media filter to remove it from the hollow perforated circular cylinder and the catch basin; and 15  
 grabbing a pair of lifting straps of a third new bio-media filter and lowering the third new bio-media filter into the hollow perforated circular cylinder.
5. The method of maintaining a modular catch basin of claim 4, further comprising:  
 prior to the grabbing of the pair of lifting straps of the second new bio-media filter,  
 adjusting a first sealing ring to seal between an edge of the first new bio-media filter and an inner surface of the hollow perforated circular cylinder; and 25  
 prior to the grabbing of the pair of lifting straps of the third new bio-media filter,  
 adjusting a second sealing ring to seal between an edge of the second new bio-media filter and the inner surface of the hollow perforated circular cylinder. 30
6. The method of maintaining a modular catch basin of claim 1, further comprising:  
 un-cinching a cinch of each used bio-media filter;  
 emptying used filter media from the used bio-media filter to expose a flexible filter hand bag; and 35  
 recycling the used filter media.
7. The method of maintaining a modular catch basin of claim 6, further comprising:  
 reusing the flexible filter hand bag by filling it with new filter media and cinching a cinch around the filter media of each flexible filter hand bag to form a bio-media filter. 40
8. The method of maintaining a modular catch basin of claim 1, further comprising:  
 prior to the grabbing and the reinstalling,  
 vacuuming out silt in a lower support structure below the perforated cylinder. 45
9. The method of maintaining a modular catch basin of claim 8, further comprising:  
 prior to the grabbing and the reinstalling,  
 washing out an upper support structure and the lower support structure. 50
10. The method of maintaining a modular catch basin of claim 1, further comprising:  
 prior to the removing of the top grate,  
 removing rocks over the top grate. 55
11. A method of installing a modular catch basin for a water treatment system, the method comprising:  
 excavating soil to create a first excavation for a water treatment system;  
 lining said first excavation with a first fabric to barricade the soil from said first excavation;  
 installing a first hollow support structure into said first excavation, the first hollow support structure providing a cistern;  
 coupling a second hollow support structure to the first hollow support structure in said first excavation; 65

32

- installing a first perforated cylinder into said second hollow support structure;  
 installing at least one bio-media filter into said first perforated cylinder, the at least one bio-media filter comprising a proportion of at least one filtrating substance;  
 capping said second hollow support structure with a top grate;  
 overlaying an impermeable liner around an opening of the first perforated cylinder; and  
 installing a rock ballast atop portions of said impermeable liner to hold it in place.
12. The method of claim 11, further comprising:  
 plugging one or more drain holes in a top half of the second hollow support structure.
13. The method of claim 11, further comprising:  
 inserting a filter fabric into at least one hollow leg of the second hollow support structure; and  
 filling at least one hollow leg of the second hollow support structure with a side filter media for a final drain down of residual water on the impermeable liner.
14. The method of claim 13, further comprising:  
 aligning at least one drain down grommet in the impermeable liner over the side filter media in the at least one hollow leg of the second hollow support structure.
15. The method of claim 11, wherein  
 the second hollow support structure has four solid walls coupled together; and  
 the method further comprises  
 installing a filter fabric over a connector ring between the first and second hollow support structures;  
 pouring a side filter media onto the filter fabric between the four solid walls of the second hollow support structure and the perforated cylinder; and  
 aligning at least one down drain grommet in an impermeable liner over the side filter media between the second hollow support structure and the perforated cylinder.
16. The method of claim 11, the method further comprises  
 pouring sand onto the first fabric under the first hollow support structure;  
 applying a first filter fabric over the sand under the first hollow support structure;  
 wrapping a second filter fabric around the first and second hollow support structures to deter sand, gravel, and silt from entering a cistern of the first hollow support structure;  
 pouring a side filter material between the second filter fabric wrapped around the first and second hollow support structures and walls of the excavation to press the filter fabric against walls of the second hollow support structure;  
 applying a third filter fabric onto the side filter material between the first filter fabric and walls of the excavation to separate sand from gravel and reduce migration of sand into the gravel;  
 placing geofoam on the third filter fabric near the walls of the excavation to provide a stable elevated platform for edges of the impermeable liner to direct water into the catch basin;  
 applying pea-gravel on the third filter fabric under the pond liner backfilling around the geofoam to support the pond liner and stabilizes the position of the geofoam;  
 overlaying an underlinement onto the pea-gravel under the water impermeable liner between edges of the excavation and a cylinder of the catch basin, wherein the underlinement barricades the water impermeable liner from pea-gravel to avoid wear from sharp edges; and

33

wherein said rock ballast are smooth decorative rocks placed onto the water impermeable liner to shade the liner from sunlight, displace water to flow evenly into the catch basin, and catch silt and debris from entering the catch basin.

17. A method of installing a modular catch basin for a water treatment system, the method comprising:

excavating soil to create a first excavation for a water treatment system;

providing a sand base in the bottom of the first excavation;

installing at least one hollow support structure on top of the sand base in the first excavation;

backfilling gravel in the first excavation around the at least one hollow support structure;

overlaying a filter fabric over the at least one hollow support structure;

coupling at least one hollow perforated cylinder to the first hollow support structure;

backfilling sand in the first excavation around the at least one hollow perforated cylinder;

5

10

15

20

34

installing at least one bio-media filter into the at least one hollow perforated cylinder, the at least one bio-media filter comprising a proportion of at least one filtrating substance;

placing opposing spaced apart geofoam bases onto the top of the sand around the at least one hollow perforated cylinder;

overlaying an impermeable liner over the opposing spaced apart geofoam bases around at least one top circular edge of the at least one hollow perforated cylinder;

capping the at least one hollow perforated cylinder with at least one top grate cap; and

installing a rock ballast onto portions of the impermeable liner to hold it in place.

18. The method of claim 17, wherein the impermeable liner has at least one drain down grommet; and

the method further comprises

prior to the capping and the installing of the rock ballast,

aligning the at least one drain down grommet in the impermeable liner over the sand backfilled around the

at least one hollow perforated cylinder.

\* \* \* \* \*