



US009457768B2

(12) **United States Patent**
Tolentino et al.

(10) **Patent No.:** **US 9,457,768 B2**
(45) **Date of Patent:** **Oct. 4, 2016**

(54) **VORTEX DAMPING WIPER BLADE**

2,550,094 A 4/1951 Smulski
2,589,339 A 3/1952 Carson
2,616,112 A 11/1952 Smulski
2,643,411 A 6/1953 Nesson
2,658,223 A 11/1953 Enochian

(75) Inventors: **Vambi Raymundo Tolentino**, Coconut Creek, FL (US); **Robert Peter Peers**, Boca Raton, FL (US)

(Continued)

(73) Assignee: **Pylon Manufacturing Corp.**, Deerfield Beach, FL (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

AR 206463 7/1976
AU 409933 2/1971

(Continued)

(21) Appl. No.: **13/453,601**

OTHER PUBLICATIONS

(22) Filed: **Apr. 23, 2012**

International Search Report mailed Oct. 19, 2012 for PCT/US2012/048843 filed Jul. 30, 2012.

(65) **Prior Publication Data**

(Continued)

US 2012/0266405 A1 Oct. 25, 2012

Related U.S. Application Data

(60) Provisional application No. 61/477,908, filed on Apr. 21, 2011.

Primary Examiner — Michael Jennings

(74) *Attorney, Agent, or Firm* — Cozen O'Connor

(51) **Int. Cl.**
B60S 1/38 (2006.01)

(57) **ABSTRACT**

(52) **U.S. Cl.**
CPC **B60S 1/3863** (2013.01); **B60S 1/3848** (2013.01); **B60S 1/3806** (2013.01); **B60S 1/3808** (2013.01); **B60S 1/3867** (2013.01); **B60S 2001/3843** (2013.01)

A windshield wiper blade cover and a wiper blade having same. The windshield wiper blade cover being capable of being disposed on the top side of a beam of a wiper blade, and comprising two longitudinal sides, two outer ends and a top surface, where the top surface of the cover has a base portion having a height and a raised portion having a height, the height of the raised portion is greater than the height of the base portion, and the height of the raised portion gradually decreases as the raised portion approaches the outer ends of the cover. The wiper blade comprising a cover as described above, a beam having two ends, two longitudinal sides, a top side and a bottom side, a central bridge disposed on the top side of the beam, a wiper strip disposed on the bottom side of the beam, and the cover disposed on the top side of the beam.

(58) **Field of Classification Search**
CPC B60S 1/3806; B60S 1/3808; B60S 1/381; B60S 1/3863; B60S 1/3848; B60S 1/3867
USPC 15/250.201, 250.361, 250.32, 250.43, 15/250.44


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D56,762 S 12/1920 Minier
2,310,751 A 2/1943 Scinta

20 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,799,887	A	7/1957	Nemic	D282,718	S	2/1986	Fireman
2,801,436	A	8/1957	Scinta	4,570,284	A	2/1986	Verton
2,814,820	A	12/1957	Elliot et al.	4,587,686	A	5/1986	Thompson
2,890,472	A	6/1959	Olson	4,590,638	A	5/1986	Beneteau
2,932,843	A	4/1960	Zaiger et al.	D286,499	S	11/1986	Moreno
2,937,393	A	5/1960	Brueder	D287,709	S	1/1987	Mower et al.
2,946,078	A	7/1960	Deibel et al.	4,670,934	A	6/1987	Epple et al.
3,029,460	A	4/1962	Hoyler	D295,020	S	4/1988	Franchi
3,037,233	A	6/1962	Peras et al.	4,741,071	A	5/1988	Bauer et al.
3,056,991	A	10/1962	Smithers	D296,317	S	6/1988	Mower et al.
3,082,464	A	3/1963	Smithers	4,766,636	A	8/1988	Shinpo
3,088,155	A	5/1963	Smithers	D298,116	S	10/1988	Sussich
3,089,174	A	5/1963	Bignon	4,782,547	A	11/1988	Mohnach
3,104,412	A	9/1963	Hinder	D298,926	S	12/1988	Rusnak
3,116,510	A	1/1964	Oishei et al.	4,807,326	A	2/1989	Arai et al.
3,132,367	A	5/1964	Wise	D301,329	S	5/1989	Cavicchioli
3,139,644	A	7/1964	Smith	4,852,206	A	8/1989	Fisher
3,147,506	A	9/1964	Williams	D304,709	S	11/1989	Sussich
3,147,507	A	9/1964	Glynn	D307,408	S	4/1990	Mower et al.
3,192,551	A	7/1965	Appel	D308,352	S	6/1990	Bradley
3,234,578	A	2/1966	Golub et al.	D308,660	S	6/1990	Fisher
3,296,647	A	1/1967	Gumbleton	D308,845	S	6/1990	Charet et al.
3,317,945	A	5/1967	Ludwig	D310,193	S	8/1990	Charet
3,317,946	A	5/1967	Anderson	4,971,472	A	11/1990	Pethers
3,350,738	A	11/1967	Anderson	4,976,001	A	12/1990	Wright
D211,570	S	7/1968	Tomlin	4,984,325	A	1/1991	Arai et al.
3,405,421	A	10/1968	Tomlin	4,989,290	A	2/1991	Hoshino
3,418,679	A	12/1968	Barth et al.	5,042,106	A	8/1991	Maubray
3,480,986	A	12/1969	Forster	5,056,183	A	10/1991	Haney, III
3,588,941	A	6/1971	Schlesinger	5,062,176	A	11/1991	Unterborn et al.
3,588,942	A	6/1971	Schlesinger	D322,053	S	12/1991	Bradley
3,618,155	A	11/1971	Mower	D322,772	S	12/1991	Leu et al.
3,665,544	A	5/1972	Sakamoto	D322,952	S	1/1992	Wu
3,673,631	A	7/1972	Yamadai et al.	5,082,078	A	1/1992	Umeda et al.
3,685,086	A	8/1972	Frohlich	D323,637	S	2/1992	Dipple
3,751,754	A	8/1973	Quinlan et al.	D324,014	S	2/1992	Ruminer
3,757,377	A	9/1973	Hayhurst	5,084,933	A	2/1992	Buechele
3,780,395	A	12/1973	Quinlan et al.	5,086,534	A	2/1992	Journee
3,857,741	A	12/1974	Hultgren et al.	D324,359	S	3/1992	Chen
3,862,465	A	1/1975	Ito	D324,667	S	3/1992	Williams
3,872,537	A	3/1975	Bianchi	5,093,954	A	3/1992	Kuzuno
3,879,793	A	4/1975	Schlegel	D327,461	S	6/1992	Nelson
3,881,213	A	5/1975	Tilli	5,123,140	A	6/1992	Raymond
3,881,214	A	5/1975	Palu	D327,667	S	7/1992	Mar
D236,337	S	8/1975	Deibel	D328,061	S	7/1992	Su
3,942,212	A	3/1976	Steger et al.	5,138,739	A	8/1992	Maubray
D240,809	S	8/1976	Deibel	D329,034	S	9/1992	Charet et al.
3,995,347	A	12/1976	Kohler	D329,997	S	10/1992	Leu
4,007,511	A	2/1977	Deibel	D330,181	S	10/1992	Charet et al.
4,009,504	A	3/1977	Arman	D330,691	S	11/1992	Leu
4,028,770	A	6/1977	Appel	D330,696	S	11/1992	Alain
4,047,480	A	9/1977	Vassiliou	D331,036	S	11/1992	Isley
4,063,328	A	12/1977	Arman	D331,037	S	11/1992	Hsi
D248,388	S	7/1978	Hughes	D331,212	S	11/1992	Poteet
4,102,003	A	7/1978	Hancu	D331,556	S	12/1992	Ismert
4,127,912	A	12/1978	Deibel et al.	5,168,596	A	12/1992	Maubray
4,127,916	A	12/1978	Van den Berg et al.	5,170,527	A	12/1992	Lyon, II
D253,040	S	10/1979	Fournier et al.	D332,593	S	1/1993	Gerardiello et al.
D253,167	S	10/1979	Fournier et al.	5,179,761	A	1/1993	Buechele et al.
D257,339	S	10/1980	Ellinwood	5,182,831	A	2/1993	Knight
4,308,635	A	1/1982	Maiocco	D334,161	S	3/1993	Wu et al.
4,309,790	A	1/1982	Bauer et al.	D334,549	S	4/1993	Esquibel
4,339,839	A	7/1982	Knights	5,206,969	A	5/1993	Patterson et al.
4,342,126	A	8/1982	Neefeldt	D336,739	S	6/1993	Wu et al.
4,343,063	A	8/1982	Batt	5,218,735	A	6/1993	Maubray
D267,939	S	2/1983	Duvoux	5,228,167	A	7/1993	Yang
D267,940	S	2/1983	Duvoux	5,233,721	A	8/1993	Yang
D268,020	S	2/1983	Duvoux	D341,561	S	11/1993	Heckman et al.
4,400,845	A	8/1983	Noguchi et al.	5,257,436	A	11/1993	Yang
4,422,207	A	12/1983	Maiocco et al.	D342,225	S	12/1993	Heckman et al.
4,438,543	A	3/1984	Noguchi et al.	5,276,937	A	1/1994	Lan
4,464,808	A	8/1984	Berry	5,283,925	A	2/1994	Maubray
4,547,925	A	10/1985	Blackborow et al.	D345,329	S	3/1994	Kanellis et al.
4,561,143	A	12/1985	Beneteau	D345,330	S	3/1994	Yang
D282,243	S	1/1986	Mason	D345,537	S	3/1994	Bianco et al.
				D345,538	S	3/1994	Bianco et al.
				5,307,536	A	5/1994	Lescher
				5,311,636	A	5/1994	Lee
				5,312,177	A	5/1994	Coulter

(56)

References Cited

U.S. PATENT DOCUMENTS

D347,610	S	6/1994	Charet et al.	6,158,078	A	12/2000	Kotlarski
5,319,826	A	6/1994	Mower	6,161,248	A	12/2000	Merkel et al.
5,325,564	A	7/1994	Swanepoel	6,192,546	B1	2/2001	Kotlarski
D349,877	S	8/1994	Oyama	6,202,251	B1	3/2001	Kotlarski
5,333,351	A	8/1994	Sato	D442,537	S	5/2001	Kim
D350,723	S	9/1994	Longazel	6,226,829	B1	5/2001	Kotlarski
5,349,716	A	9/1994	Millar	D443,245	S	6/2001	Kim
D353,354	S	12/1994	Oyama	D443,582	S	6/2001	De Block
5,372,449	A	12/1994	Bauer et al.	D443,854	S	6/2001	De Block
5,383,248	A	1/1995	Ho	D444,760	S	7/2001	Houssat et al.
5,383,249	A	1/1995	Yang	D445,754	S	7/2001	Benoit
5,392,489	A	2/1995	Mohnach	6,266,843	B1	7/2001	Doman et al.
D357,626	S	4/1995	Snow et al.	6,279,191	B1	8/2001	Kotlarski et al.
5,408,719	A	4/1995	DeRees et al.	D448,295	S	9/2001	Mozes
5,412,177	A	5/1995	Clark	6,286,176	B1	9/2001	Westermann et al.
5,454,135	A	10/1995	Okuya et al.	6,292,974	B1	9/2001	Merkel et al.
5,463,790	A	11/1995	Chiou et al.	6,295,690	B1	10/2001	Merkel et al.
D365,079	S	12/1995	Abbott et al.	6,301,742	B1	10/2001	Kota
5,485,650	A	1/1996	Swanepoel	6,305,066	B1	10/2001	De Paolo et al.
5,487,205	A	1/1996	Scherch et al.	6,308,373	B1	10/2001	Merkel et al.
5,497,528	A	3/1996	Wu	6,327,738	B1	12/2001	Lewis
5,509,166	A	4/1996	Wagner et al.	6,332,236	B1	12/2001	Ku
D370,199	S	5/1996	Kim	6,336,243	B1*	1/2002	Charng 15/250.201
D370,653	S	6/1996	Kim	D453,316	S	2/2002	Watanabe
D370,654	S	6/1996	Kim	6,363,569	B1	4/2002	Kotlarski
D372,217	S	7/1996	Abbott et al.	6,367,117	B1	4/2002	Sahara et al.
5,564,157	A	10/1996	Kushida et al.	D457,479	S	5/2002	De Block et al.
5,566,419	A	10/1996	Zhou	6,393,654	B2	5/2002	Nacamuli
D375,289	S	11/1996	Waselewski et al.	6,397,428	B2	6/2002	Kotlarski
5,577,292	A	11/1996	Blachetta et al.	D462,044	S	8/2002	Gfatter et al.
D376,792	S	12/1996	Chodkiewicz	6,427,282	B1	8/2002	Kotlarski
5,593,125	A	1/1997	Storz et al.	6,434,780	B1	8/2002	Kotlarski
D377,754	S	2/1997	Abbott et al.	6,449,797	B1	9/2002	De Block
D379,613	S	6/1997	Chen	6,453,505	B1	9/2002	Terai
D382,848	S	8/1997	Chen	D464,012	S	10/2002	Hussaini et al.
5,661,870	A	9/1997	Eustache et al.	D464,600	S	10/2002	Chen
D389,449	S	1/1998	Hussaini	6,499,181	B1	12/2002	Kotlarski
D390,823	S	2/1998	Baranowski et al.	D469,731	S	2/2003	Geer
D392,612	S	3/1998	Jonasson et al.	6,516,491	B2	2/2003	Merkel et al.
5,732,437	A	3/1998	Jonasson et al.	6,523,218	B1	2/2003	Kotlarski
D393,619	S	4/1998	Jeffer et al.	6,530,111	B1	3/2003	Kotlarski
D395,271	S	6/1998	Kim	D472,510	S	4/2003	Lin
D395,864	S	7/1998	Stahlhut et al.	D473,180	S	4/2003	Sun
D395,865	S	7/1998	Powell et al.	6,550,096	B1	4/2003	Stewart et al.
D396,840	S	8/1998	Vita	6,553,607	B1	4/2003	De Block
5,836,110	A	11/1998	Buening	D474,143	S	5/2003	Ho
D402,953	S	12/1998	Kim	6,564,441	B2	5/2003	Ibe et al.
D404,354	S	1/1999	Witek et al.	6,581,237	B1	6/2003	Kotlarski
D406,094	S	2/1999	Lai	6,606,759	B1	8/2003	Hoshino
D406,257	S	3/1999	Lee	6,609,267	B1	8/2003	Journee et al.
5,875,672	A	3/1999	Fourie et al.	6,611,988	B1	9/2003	De Block
5,885,023	A	3/1999	Witek et al.	6,619,094	B2	9/2003	Juhl
5,899,334	A	5/1999	Domerchie et al.	6,622,540	B2	9/2003	Jones et al.
D411,161	S	6/1999	Wooten	6,625,842	B1	9/2003	De Block
D411,504	S	6/1999	Hsu	6,632,738	B2	10/2003	Sone
5,907,885	A	6/1999	Tilli et al.	6,634,056	B1	10/2003	De Block
5,920,947	A	7/1999	Varner	6,640,380	B2	11/2003	Rosenstein et al.
D414,456	S	9/1999	Hussaini et al.	6,643,889	B1	11/2003	Kotlarski
5,970,569	A	10/1999	Merkel et al.	6,651,292	B2	11/2003	Komerska
5,970,570	A	10/1999	Groninger	6,665,904	B1	12/2003	Kerchaert
D417,180	S	11/1999	Shih	6,668,419	B1	12/2003	Kotlarski
D418,103	S	12/1999	Don	6,675,433	B1	1/2004	Stewart et al.
D418,474	S	1/2000	Witek et al.	6,675,434	B1	1/2004	Wilhelm et al.
D419,950	S	2/2000	Spector	6,681,440	B2	1/2004	Zimmer et al.
6,055,697	A	5/2000	Wollenschlaeger	D487,047	S	2/2004	Kim
6,063,216	A	5/2000	Damm et al.	6,687,948	B2	2/2004	Kotlarski
D427,134	S	6/2000	Lee	6,718,594	B1	4/2004	Kotlarski
6,088,872	A	7/2000	Schmid et al.	D490,763	S	6/2004	Kim
D430,097	S	8/2000	Breesch et al.	D494,125	S	8/2004	Leu
6,101,665	A	8/2000	Sahara et al.	D494,527	S	8/2004	Hsu
D431,223	S	9/2000	Breesch et al.	D494,528	S	8/2004	Chiang
6,119,301	A	9/2000	Nakatsukasa et al.	6,785,931	B2	9/2004	Lee et al.
D431,520	S	10/2000	Breesch et al.	6,789,289	B2	9/2004	Roodt
D432,072	S	10/2000	Breesch et al.	6,792,644	B2	9/2004	Roodt
D434,715	S	12/2000	Wang	6,796,000	B2	9/2004	Varner
				6,806,452	B2	10/2004	Bos et al.
				6,810,555	B2	11/2004	Ritt
				6,810,556	B1	11/2004	Kotlarski
				6,813,803	B2	11/2004	Leutsch

(56)

References Cited

U.S. PATENT DOCUMENTS

6,813,923	B2	11/2004	Jones et al.	7,461,429	B2	12/2008	Huang
6,820,302	B2	11/2004	Zimmer	7,464,433	B2	12/2008	Thomar et al.
6,820,303	B2	11/2004	Zimmer et al.	D584,160	S	1/2009	Zimmermann
6,820,304	B1	11/2004	Gossez et al.	7,472,451	B2	1/2009	Hara et al.
D499,962	S	12/2004	Lee et al.	D586,663	S	2/2009	Tidqvist
D500,728	S	1/2005	Leu	D586,716	S	2/2009	Radfar
6,836,924	B2	1/2005	Egan-Walter	D586,717	S	2/2009	Depondt
6,836,925	B1	1/2005	Swanepoel	D587,186	S	2/2009	Herinckx et al.
6,836,926	B1	1/2005	De Block	7,484,264	B2	2/2009	Kraemer et al.
6,836,927	B2	1/2005	De Block et al.	7,493,672	B2	2/2009	Op't Roodt
D501,819	S	2/2005	Hsu	D588,933	S	3/2009	Bonzagni et al.
6,857,160	B2	2/2005	Weiler et al.	7,506,401	B2	3/2009	Park
6,859,971	B2	3/2005	Siklosi	7,509,704	B2	3/2009	Bauer et al.
6,874,195	B2	4/2005	Kotlarski	7,523,519	B2	4/2009	Egner-Walter et al.
6,883,966	B2	4/2005	Zimmer	7,523,520	B2	4/2009	Breesch
6,886,213	B2	5/2005	Merkel et al.	7,523,522	B2	4/2009	Herring et al.
6,904,639	B2	6/2005	Dietrich et al.	7,526,832	B2	5/2009	Matsumoto et al.
6,910,243	B1	6/2005	Zimmer	7,527,151	B2	5/2009	Park
6,910,244	B2	6/2005	De Block et al.	D593,480	S	6/2009	Kim
D508,226	S	8/2005	Lin	7,543,353	B2	6/2009	Ko
D508,888	S	8/2005	Carroll	7,552,502	B2	6/2009	Kagawa et al.
6,944,905	B2	9/2005	De Block et al.	D596,102	S	7/2009	Kim
6,946,810	B2	9/2005	Kohlrausch	7,559,110	B1	7/2009	Kotlarski et al.
6,951,043	B1	10/2005	Fehrsen	D601,077	S	9/2009	Kim
D511,735	S	11/2005	Aoyama et al.	7,581,280	B2	9/2009	Op't Roodt et al.
6,964,079	B2	11/2005	Zimmer	7,581,887	B2	9/2009	Zimmer
6,964,080	B2	11/2005	Knauf	7,596,479	B2	9/2009	Weiler et al.
6,966,096	B2	11/2005	Baseotto et al.	7,603,741	B2	10/2009	Verelst et al.
D512,362	S	12/2005	Breesch et al.	7,603,742	B2*	10/2009	Nakano et al. 15/250.201
6,973,698	B1	12/2005	Kotlarski	7,607,194	B2	10/2009	Weber et al.
6,978,512	B2	12/2005	Dietrich et al.	7,614,499	B2	11/2009	Mueller
7,007,339	B2	3/2006	Weiler et al.	7,621,016	B2	11/2009	Verelst et al.
7,024,722	B2	4/2006	Neubauer et al.	7,628,560	B2	12/2009	Westermann et al.
7,036,181	B2	5/2006	Zimmer	7,636,980	B2	12/2009	Nakano
D522,380	S	6/2006	Dibnah et al.	D608,717	S	1/2010	Aglassinger
7,055,207	B2	6/2006	Coughlin	D610,518	S	2/2010	Aglassinger
7,055,208	B2	6/2006	Merkel et al.	D610,519	S	2/2010	Aglassinger
7,076,829	B2	7/2006	Ritt	D610,520	S	2/2010	Aglassinger
D527,336	S	8/2006	Van Baelen	D611,809	S	3/2010	Borgerson et al.
7,093,317	B1	8/2006	Zimmer	7,669,276	B2	3/2010	Verelst et al.
7,134,163	B2	11/2006	Varner	7,687,565	B2	3/2010	Geilenkirchen
7,137,167	B2	11/2006	Torii et al.	7,690,073	B2	4/2010	Marmoy et al.
7,143,463	B2	12/2006	Baseotto et al.	7,699,169	B2	4/2010	Lewis
7,150,065	B2	12/2006	Zimmer	D615,918	S	5/2010	Kim
7,150,066	B1	12/2006	Huang	7,707,680	B2	5/2010	Hawighorst et al.
7,150,795	B2	12/2006	Javaruski et al.	7,716,780	B2	5/2010	Scholl et al.
7,166,979	B2	1/2007	Zimmer	7,743,457	B2	6/2010	Metz
7,171,718	B2	2/2007	Moein et al.	7,748,076	B2	7/2010	Weiler et al.
D538,218	S	3/2007	Elwell et al.	D621,322	S	8/2010	Lee et al.
7,196,440	B2	3/2007	Lamprecht	7,780,214	B2	8/2010	Kraus et al.
7,228,588	B2	6/2007	Kraemer et al.	7,788,761	B2	9/2010	Weiler et al.
D546,669	S	7/2007	Sheppard et al.	7,793,382	B2	9/2010	Van De Rovaart
D547,713	S	7/2007	Goeller	7,797,787	B2	9/2010	Wilms et al.
D549,152	S	8/2007	Goeller	7,805,800	B2	10/2010	Wilms et al.
7,256,565	B2	8/2007	Merkel et al.	7,810,206	B2	10/2010	Weiler et al.
7,257,856	B2	8/2007	Zimmer	7,814,611	B2	10/2010	Heinrich et al.
7,258,233	B2	8/2007	Lee	7,823,953	B2	11/2010	Haas
7,272,890	B2	9/2007	Zimmer et al.	7,832,045	B2	11/2010	Weiler et al.
D552,486	S	10/2007	Herring et al.	7,832,047	B2	11/2010	Herinckx et al.
7,281,294	B2	10/2007	Wilms et al.	7,836,542	B2	11/2010	Dietrich et al.
7,293,321	B2	11/2007	Breesch	7,849,553	B2	12/2010	Weiler et al.
7,299,520	B2	11/2007	Huang	7,886,401	B2	2/2011	Weber et al.
7,316,047	B2	1/2008	Thienard	7,891,043	B2	2/2011	Kraus et al.
7,316,048	B2	1/2008	Yamane et al.	7,891,044	B2	2/2011	Fink et al.
7,337,900	B2	3/2008	Reiber et al.	7,895,702	B2	3/2011	Tisch et al.
7,353,562	B2	4/2008	Huang	7,895,703	B2	3/2011	Ina et al.
D569,327	S	5/2008	Lin	7,898,141	B2	3/2011	Hurst et al.
D569,328	S	5/2008	Lin	7,899,596	B2	3/2011	Zimmer
7,370,385	B2	5/2008	Chiang	7,908,703	B2	3/2011	Van Bealen
D573,457	S	7/2008	Park	7,908,704	B2	3/2011	Kraemer
7,398,577	B2	7/2008	Genet	7,921,504	B1	4/2011	Chiang
D577,324	S	9/2008	McCray	7,926,659	B2	4/2011	Kim
D579,849	S	11/2008	Garrastacho et al.	7,930,796	B2	4/2011	Weiler et al.
7,451,520	B2	11/2008	Weiler et al.	D637,132	S	5/2011	Kim
D582,765	S	12/2008	Gustafson et al.	7,937,798	B2	5/2011	Fink et al.
				7,941,891	B2	5/2011	Breesch
				7,941,892	B2	5/2011	Kraus et al.
				7,945,985	B2	5/2011	Stubner
				7,945,987	B2	5/2011	Verelst et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,950,717 B2	5/2011	Metz	2006/0117515 A1	6/2006	Fink et al.	
7,962,787 B2	6/2011	Camilleri et al.	2006/0130263 A1	6/2006	Coughlin	
7,966,689 B2	6/2011	Rovaart et al.	2006/0156529 A1	7/2006	Thomar et al.	
7,971,312 B2	7/2011	Crabee et al.	2006/0179597 A1*	8/2006	Hoshino et al.	15/250.43
7,975,849 B2	7/2011	Kim	2006/0218740 A1	10/2006	Coughlin	
7,989,955 B2	8/2011	Yagi	2006/0230571 A1	10/2006	Son	
7,996,953 B2	8/2011	Braun et al.	2006/0248675 A1	11/2006	Vacher et al.	
D644,925 S	9/2011	Jaworski	2006/0282972 A1*	12/2006	Huang	15/250.201
8,020,246 B2	9/2011	Bauer et al.	2007/0017056 A1	1/2007	Cooke et al.	
8,020,248 B2	9/2011	Hasegawa	2007/0067939 A1	3/2007	Huang	
8,020,249 B2	9/2011	Masuda et al.	2007/0067941 A1	3/2007	Huang	
8,026,645 B2	9/2011	Stubner et al.	2007/0089257 A1	4/2007	Harita et al.	
8,042,690 B2	10/2011	Lewis	2007/0186366 A1	8/2007	Alley	
D647,795 S	11/2011	Eaton et al.	2007/0220698 A1	9/2007	Huang	
8,051,526 B2	11/2011	Summerville et al.	2007/0226940 A1	10/2007	Thienard	
8,060,976 B2	11/2011	Mayer et al.	2007/0226941 A1	10/2007	Kraemer et al.	
8,069,528 B2	12/2011	Verelst et al.	2007/0234501 A1	10/2007	Ho et al.	
8,076,807 B2	12/2011	Bohn et al.	2007/0266517 A1*	11/2007	Kim et al.	15/250.29
D651,509 S	1/2012	Methe et al.	2008/0083082 A1	4/2008	Rovaart et al.	
8,096,013 B2	1/2012	Eschenbrenner et al.	2008/0098554 A1*	5/2008	Cho	15/250.32
8,099,823 B2	1/2012	Kraemer et al.	2008/0196192 A1	8/2008	Yao	
8,104,134 B2	1/2012	Ritt	2008/0222830 A1	9/2008	Chiang	
8,104,136 B2	1/2012	Carangelo	2008/0263805 A1	10/2008	Sebring	
8,117,710 B2	2/2012	Kraus et al.	2008/0289133 A1	11/2008	Kim	
8,125,111 B2	2/2012	Bohn et al.	2009/0007364 A1	1/2009	Jarasson et al.	
8,141,198 B2	3/2012	Wilms et al.	2009/0013492 A1	1/2009	Henin	
8,148,467 B2	4/2012	Pieters et al.	2009/0064440 A1	3/2009	Boland	
8,151,656 B2	4/2012	Nicgorski, II	2009/0158545 A1	6/2009	Grasso et al.	
D658,494 S	5/2012	Raimer et al.	2009/0172910 A1	7/2009	De Block et al.	
8,181,308 B2*	5/2012	Kwon et al.	2009/0178226 A1	7/2009	Lee et al.	
8,186,002 B2	5/2012	Kinnaert et al.	2010/0005608 A1	1/2010	Chien	
8,191,200 B2	6/2012	Kim	2010/0005609 A1	1/2010	Kim	
8,261,403 B2	9/2012	Ehde	2010/0024151 A1	2/2010	Ku	
8,261,405 B2	9/2012	Kim et al.	2010/0050360 A1	3/2010	Chiang	
8,272,096 B2	9/2012	Wilms et al.	2010/0050361 A1	3/2010	Chang et al.	
8,381,348 B2	2/2013	Egner-Walter et al.	2010/0064468 A1	3/2010	Kang	
8,413,291 B2*	2/2013	Wu	2010/0083454 A1	4/2010	Op't Roodt et al.	
8,434,621 B2	5/2013	Hun et al.	2010/0083454 A1	4/2010	Op't Roodt et al.	
D684,862 S	6/2013	DiFranza	2010/0205763 A1	8/2010	Ku	
8,474,088 B2	7/2013	Wu	2010/0212101 A1	8/2010	Thienard et al.	
8,490,239 B2	7/2013	Ehde	2010/0236008 A1	9/2010	Yang et al.	
8,505,724 B2	8/2013	Bult et al.	2010/0236675 A1	9/2010	Schneider	
8,510,897 B2	8/2013	Ku	2010/0242204 A1*	9/2010	Chien	15/250.201
8,510,898 B2	8/2013	Ku	2010/0281645 A1	11/2010	Kim et al.	
8,544,137 B2	10/2013	Thienard	2011/0047742 A1	3/2011	Kim et al.	
8,555,456 B2	10/2013	Ehde	2011/0072607 A1	3/2011	Van Baelen et al.	
D692,750 S	11/2013	Ehde et al.	2011/0113582 A1	5/2011	Kruse et al.	
8,613,357 B2	12/2013	Putnam	2011/0113583 A1	5/2011	Shanmugham et al.	
D702,619 S	4/2014	Kim	2011/0162161 A1	7/2011	Amado	
D704,620 S	5/2014	Kim	2011/0192511 A1	8/2011	Marrone	
2001/0013236 A1	8/2001	Weyerstall et al.	2011/0219563 A1	9/2011	Guastella et al.	
2002/0043092 A1	4/2002	Jones et al.	2011/0277264 A1	11/2011	Ehde	
2002/0112306 A1	8/2002	Komerska	2011/0277266 A1	11/2011	Umeno	
2003/0014828 A1	1/2003	Edner-Walter et al.	2012/0027206 A1	2/2012	Suzuki et al.	
2003/0028990 A1	2/2003	Zimmer	2012/0047673 A1	3/2012	Depondt	
2003/0033683 A1	2/2003	Kotlarski	2012/0054976 A1	3/2012	Yang et al.	
2003/0159229 A1	8/2003	Weiler et al.	2012/0060316 A1	3/2012	Avasiloaie et al.	
2003/0209049 A1	11/2003	Jones et al.	2012/0102669 A1	5/2012	Lee et al.	
2003/0221276 A1	12/2003	Siklosi	2012/0144615 A1	6/2012	Song et al.	
2003/0229961 A1	12/2003	Barnett	2012/0159733 A1	6/2012	Kwon	
2004/0010882 A1	1/2004	Breesch	2012/0180245 A1	7/2012	Ku	
2004/0025280 A1	2/2004	Krickau et al.	2012/0180246 A1	7/2012	Ku	
2004/0025281 A1	2/2004	Baseotto et al.	2012/0279008 A1	11/2012	Depondt	
2004/0098821 A1	5/2004	Kraemer et al.	2012/0311808 A1	12/2012	Yang et al.	
2004/0159994 A1	8/2004	Lenzen et al.	2012/0317740 A1	12/2012	Yang et al.	
2004/0211021 A1	10/2004	Weber et al.	2013/0067675 A1	3/2013	Chien	
2004/0244137 A1	12/2004	Poton	2013/0104334 A1	5/2013	Depondt	
2004/0250369 A1*	12/2004	Matsumoto et al.	2013/0152326 A1	6/2013	Oslizlo et al.	
2005/0005387 A1	1/2005	Kinoshita et al.	2013/0152330 A1	6/2013	Kim et al.	
2005/0011033 A1	1/2005	Thomar et al.	2013/0167316 A1	7/2013	Egner-Walter et al.	
2005/0039292 A1	2/2005	Boland	2013/0192016 A1	8/2013	Kim et al.	
2005/0166349 A1	8/2005	Nakano et al.	2013/0247323 A1	9/2013	Geubel et al.	
2005/0177970 A1	8/2005	Scholl et al.	2013/0255026 A1	10/2013	Depondt	
2006/0010636 A1	1/2006	Vacher	2013/0263400 A1	10/2013	Duesterhoeft et al.	
2006/0112511 A1	6/2006	Op't Roodt et al.	2013/0333145 A1	12/2013	Depondt	
			2013/0333146 A1	12/2013	Depondt	

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0026348 A1 1/2014 Schaeuble
 2014/0026349 A1 1/2014 Schaeuble

FOREIGN PATENT DOCUMENTS

AU 410701 2/1971
 AU 649730 6/1994
 AU 729371 7/2001
 AU 741730 12/2001
 AU 762557 6/2003
 AU 770944 3/2004
 AU 2003257828 3/2004
 AU 780818 4/2005
 AU 2006100618 8/2006
 AU 2006241297 6/2007
 AU 2006203445 10/2007
 AU 2008100641 8/2008
 AU 2009238193 10/2009
 AU 2009324257 8/2010
 BR 8304484 4/1984
 BR 8604381 5/1987
 BR 8707390 11/1988
 BR 8903473 3/1990
 BR 8907154 2/1991
 BR 9005080 8/1991
 BR 9105809 8/1992
 BR 9200129 10/1992
 BR 0006164 4/2001
 BR 0007263 10/2001
 BR 0106665 4/2002
 BR 0106667 4/2002
 BR 0306135 10/2004
 BR PI0411532 8/2006
 BR PI0506158 10/2006
 BR PI0007263 1/2009
 BR PI0519259 1/2009
 BR 0006917 8/2009
 BR PI0606903 8/2009
 BR PI0901324 4/2010
 BR PI0006963 9/2010
 BR PI0706762 4/2011
 BR PI1000961 6/2011
 BR PI0621265 12/2011
 CA 954258 9/1974
 CA 966609 4/1975
 CA 1038117 9/1978
 CA 1075414 4/1980
 CA 1124462 6/1982
 CA 1184712 4/1985
 CA 1257059 7/1989
 CA 1263803 12/1989
 CA 2027227 4/1991
 CA 1289308 9/1991
 CA 2037400 2/1992
 CA 2093956 4/1992
 CA 2079846 7/1993
 CA 2118874 9/1994
 CA 2156345 2/1996
 CA 2174030 5/1997
 CA 2260175 1/1998
 CA 2220462 7/1998
 CA 2243143 1/1999
 CA 2344888 4/2000
 CA 2414099 1/2002
 CA 2472914 8/2003
 CA 2487799 12/2003
 CA 2515071 8/2004
 CA 2242776 7/2005
 CA 2553977 9/2005
 CA 2514372 1/2006
 CA 2574330 2/2006
 CA 2523315 4/2006
 CA 2541641 4/2006
 CA 2522729 6/2006
 CA 2598104 9/2006

CA 2550409 11/2006
 CA 2568561 5/2007
 CA 2569175 5/2007
 CA 2569176 5/2007
 CA 2569977 6/2007
 CA 2560155 9/2007
 CA 2645821 10/2007
 CA 2649474 11/2007
 CA 2649760 11/2007
 CA 2651069 11/2007
 CA 2590443 4/2008
 CA 2631513 5/2008
 CA 2574242 7/2008
 CA 2617013 11/2008
 CA 2628517 4/2009
 CA 2671767 1/2010
 CA 2500891 5/2011
 CA 2789431 8/2011
 CA 2809243 3/2012
 CA 2809292 3/2012
 CA 2809947 3/2012
 CA 2835703 11/2012
 CA 2843527 1/2013
 CA 2843637 2/2013
 CA 2843644 2/2013
 CA 2797693 5/2013
 CA 2799267 6/2013
 CA 2740384 7/2013
 CN 101983148 3/2011
 CN 202593459 12/2012
 CN 102963337 3/2013
 CN 102991462 3/2013
 CN 102991466 3/2013
 CN 103101514 5/2013
 CN 103101516 5/2013
 CN 103108782 5/2013
 CN 103183008 7/2013
 CN 103183009 7/2013
 CN 103223923 7/2013
 CN 103228498 7/2013
 DE 2309063 8/1974
 DE 2311293 9/1974
 DE 2353368 5/1975
 DE 3222864 12/1983
 DE 3919050 A1 12/1990
 DE 19650929 6/1998
 DE 19734843 2/1999
 DE 19745460 4/1999
 DE 19814609 10/1999
 DE 10054287 5/2002
 DE 10228494 A1 1/2004
 DE 10320930 11/2004
 DE 102004019157 11/2005
 DE 102004061088 6/2006
 DE 102005019389 11/2006
 DE 102006057024 6/2008
 DE 102007030169 1/2009
 DE 102007051549 4/2009
 DE 102008042516 5/2009
 DE 102008001045 10/2009
 DE 102008021457 11/2009
 DE 102008002447 12/2009
 DE 102008049269 4/2010
 DE 102008049270 4/2010
 DE 102009000483 4/2010
 DE 102009001025 8/2010
 DE 102010012983 2/2011
 DE 102009029469 3/2011
 DE 102009029470 3/2011
 DE 102009048212 4/2011
 DE 102010016348 4/2011
 DE 102010003269 9/2011
 DE 202011005213 9/2011
 DE 202011100429 9/2011
 DE 102010003645 10/2011
 DE 102010028102 10/2011
 DE 102010029107 11/2011
 DE 102010030880 1/2012
 DE 102010039526 2/2012

(56)

References Cited

FOREIGN PATENT DOCUMENTS

EP	0594451	4/1994	EP	2146877	1/2010
EP	0633170	1/1995	EP	2230140	9/2010
EP	0683703	11/1995	EP	2236366	10/2010
EP	0695246	2/1996	EP	2253520	11/2010
EP	0749378	12/1996	EP	2258592	12/2010
EP	0757636	2/1997	EP	1559623	1/2011
EP	0760761	3/1997	EP	2321160	5/2011
EP	0777594	6/1997	EP	2338747	6/2011
EP	0792704	9/1997	EP	2426017	3/2012
EP	0810936	12/1997	FR	2736025	A1 1/1997
EP	0828638	3/1998	FR	2738201	A1 3/1997
EP	0841229	5/1998	FR	2747976	10/1997
EP	0847346	6/1998	FR	2879987	6/2006
EP	0847347	6/1998	FR	2957877	9/2011
EP	0853561	7/1998	GB	1395918	5/1975
EP	0853563	7/1998	GB	1405579	9/1975
EP	0853565	7/1998	GB	2188672	10/1987
EP	0914269	5/1999	GB	2220844	A 1/1990
EP	0926028	6/1999	GB	2324237	10/1998
EP	0930991	7/1999	GB	2348118	A 9/2000
EP	0935546	8/1999	HK	1110560	5/2010
EP	0943511	9/1999	HK	1105928	8/2010
EP	1022202	7/2000	HK	1108573	10/2011
EP	1037778	9/2000	HK	1110561	7/2012
EP	0783998	10/2000	JP	60092136	A 5/1985
EP	1056628	12/2000	JP	2008037388	A 2/2008
EP	1098795	5/2001	KR	10-089115	2/2009
EP	1098796	5/2001	MX	169141	6/1993
EP	1109706	6/2001	MX	9708272	8/1998
EP	1119475	8/2001	MX	9708273	8/1998
EP	1119476	8/2001	MX	PA03010189	3/2004
EP	1178907	2/2002	MX	PA03010190	3/2004
EP	1197406	4/2002	MX	PA05002760	6/2005
EP	1243489	9/2002	MX	PA05002988	6/2005
EP	1247707	10/2002	MX	PA05008266	9/2005
EP	1257445	11/2002	MX	PA05005581	11/2005
EP	1289804	3/2003	MX	PA06008594	8/2006
EP	1289806	3/2003	MX	2007007828	7/2007
EP	1294596	3/2003	MX	2007007829	7/2007
EP	1337420	8/2003	MX	2008012325	10/2008
EP	1412235	4/2004	MX	2008013480	10/2008
EP	1017514	6/2004	MX	2008013814	12/2008
EP	1425204	6/2004	MX	2008014163	2/2009
EP	1448414	8/2004	MX	2009013050	1/2010
EP	1462327	9/2004	MX	2009013051	1/2010
EP	1485279	12/2004	MX	2010009333	10/2010
EP	1494901	1/2005	MX	2011000597	3/2011
EP	1494902	1/2005	MX	2011000598	3/2011
EP	1501710	2/2005	MX	2011003242	4/2011
EP	1519862	4/2005	MX	2011003243	4/2011
EP	1547883	6/2005	MX	2011003911	9/2011
EP	1612113	1/2006	MX	2012002314	6/2012
EP	1312522	4/2006	MX	2013002710	5/2013
EP	1666319	6/2006	MX	2013006881	7/2013
EP	1719673	11/2006	MY	122308	4/2006
EP	1733939	12/2006	MY	122563	4/2006
EP	1740424	1/2007	MY	128028	1/2007
EP	1744940	1/2007	MY	128970	3/2007
EP	1753646	2/2007	PT	1800978	5/2011
EP	1758772	3/2007	PT	1800977	1/2012
EP	1769987	4/2007	RU	2238198	10/2004
EP	1792794	6/2007	RU	2251500	5/2005
EP	1799518	6/2007	RU	2260527	9/2005
EP	1800977	6/2007	RU	2260528	9/2005
EP	1800978	6/2007	RU	2268176	1/2006
EP	1846274	10/2007	RU	2271287	3/2006
EP	1849666	A1 10/2007	RU	2293034	2/2007
EP	2015971	1/2009	RU	2294291	2/2007
EP	2050638	4/2009	RU	2007127898	1/2009
EP	2079617	7/2009	RU	80415	2/2009
EP	2109557	10/2009	RU	2346834	2/2009
EP	2113432	11/2009	RU	2369500	10/2009
EP	2127969	12/2009	RU	2381120	2/2010
EP	2134576	12/2009	RU	2394706	7/2010
EP	2143603	1/2010	RU	105237	6/2011
			RU	108350	9/2011
			RU	108741	9/2011
			TW	M404153	U1 5/2011
			TW	201325952	7/2013

(56)

References Cited

FOREIGN PATENT DOCUMENTS

TW 201325953 7/2013
 WO WO 81/03308 11/1981
 WO WO 91/06451 5/1991
 WO WO 92/06869 4/1992
 WO WO 97/12787 4/1997
 WO WO 98/01328 1/1998
 WO WO 98/01329 1/1998
 WO WO 98/50261 11/1998
 WO WO 98/51203 11/1998
 WO WO 98/51550 11/1998
 WO WO 99/08818 2/1999
 WO WO 99/15382 4/1999
 WO WO 99/56992 11/1999
 WO WO 00/05111 2/2000
 WO WO 00/06431 2/2000
 WO WO 00/21808 4/2000
 WO WO 00/21809 4/2000
 WO WO 00/21811 4/2000
 WO WO 00/38963 7/2000
 WO WO 00/38964 7/2000
 WO WO 00/53470 9/2000
 WO WO 0061409 10/2000
 WO WO 01/26942 4/2001
 WO WO 01/30618 5/2001
 WO WO 01/40034 6/2001
 WO WO 01/49537 7/2001
 WO WO 01/58732 8/2001
 WO WO 01/62559 8/2001
 WO WO 01/89890 11/2001
 WO WO 01/89891 11/2001
 WO WO 01/89892 11/2001
 WO WO 01/94166 12/2001
 WO WO 02/04168 1/2002
 WO WO 02/04266 1/2002
 WO WO 02/04267 1/2002
 WO WO 02/04268 1/2002
 WO WO 02/34590 5/2002
 WO WO 02/34596 5/2002
 WO WO 02/34597 5/2002
 WO WO 02/40328 5/2002
 WO WO 02/40329 5/2002
 WO WO 02/051677 7/2002
 WO WO 02/052917 7/2002
 WO WO 02/066301 8/2002
 WO WO 02/090155 11/2002
 WO WO 02/090156 11/2002
 WO WO 03/026938 4/2003
 WO WO 03/033316 4/2003
 WO WO 03/042017 5/2003
 WO WO 03/045746 6/2003
 WO WO 03/091078 11/2003
 WO WO 03/101794 12/2003
 WO WO 03/106233 12/2003
 WO WO 2004/002792 1/2004
 WO WO 2004/045927 6/2004
 WO WO 2004/045928 6/2004
 WO WO 2004/048163 6/2004
 WO WO 2004/056625 7/2004
 WO WO 2004/069617 8/2004
 WO WO 2004/076251 9/2004
 WO WO 2004/098962 11/2004
 WO WO 2004/098963 11/2004
 WO WO 2004/110833 12/2004
 WO WO 2005/025956 3/2005
 WO WO 2005/039944 5/2005
 WO WO 2005/054017 6/2005
 WO WO 2005/080160 9/2005
 WO WO 2005/082691 9/2005
 WO WO 2005/087560 9/2005
 WO WO 2005/092680 10/2005
 WO WO 2005/102801 11/2005
 WO WO 2005/115813 12/2005

WO WO 2005/123471 12/2005
 WO WO 2006/000393 1/2006
 WO WO 2006/013152 2/2006
 WO WO 2006/040259 4/2006
 WO WO 2006/048355 5/2006
 WO WO 2006/061284 6/2006
 WO WO 2006/069648 7/2006
 WO WO 2006/074995 7/2006
 WO WO 2006/079591 8/2006
 WO WO 2006/081893 8/2006
 WO WO 2006/106006 10/2006
 WO WO 2006/106109 10/2006
 WO WO 2006/114355 11/2006
 WO WO 2006/117081 11/2006
 WO WO 2006/117085 11/2006
 WO WO 2006/117308 11/2006
 WO WO 2007/009885 1/2007
 WO WO 2007/014389 2/2007
 WO WO 2007/014395 2/2007
 WO WO 2007/035288 3/2007
 WO WO 2007/042377 4/2007
 WO WO 2007/045549 4/2007
 WO WO 2007/071487 6/2007
 WO WO 2007/073974 7/2007
 WO WO 2007/102404 9/2007
 WO WO 2007/122095 11/2007
 WO WO 2007/128677 11/2007
 WO WO 2008/003633 1/2008
 WO WO 2008/043622 4/2008
 WO WO 2008/051483 5/2008
 WO WO 2008/076402 6/2008
 WO WO 2008/122453 10/2008
 WO WO 2008/124113 10/2008
 WO WO 2008/135308 11/2008
 WO WO 2009/000498 12/2008
 WO WO 2009/115494 9/2009
 WO WO 2009/121849 10/2009
 WO WO 2009/124792 10/2009
 WO WO 2009/132982 11/2009
 WO WO 2009/153097 12/2009
 WO WO 2009/155230 12/2009
 WO WO 2010/016000 2/2010
 WO WO 2010/028866 3/2010
 WO WO 2010/028918 3/2010
 WO WO 2010033646 3/2010
 WO WO 2010/034445 4/2010
 WO WO 2010/034447 4/2010
 WO WO 2010/035794 4/2010
 WO WO 2010/091757 8/2010
 WO WO 2010/098877 9/2010
 WO WO 2010/112579 10/2010
 WO WO 2010/121665 10/2010
 WO WO 2011/032753 3/2011
 WO WO 2011/032760 3/2011
 WO WO 2011/040743 4/2011
 WO WO 2011/060979 5/2011
 WO WO 2011/116995 9/2011
 WO WO 2011/120723 10/2011
 WO WO 2011/124404 10/2011
 WO WO 2011/131395 10/2011
 WO WO 2011/144400 11/2011
 WO WO 2011/157465 12/2011
 WO WO 2012/001175 1/2012
 WO WO 2012/014054 2/2012
 WO WO 2012/033363 3/2012

OTHER PUBLICATIONS

International Search Report mailed Sep. 19, 2012 for PCT/US2012/048617 filed Jul. 27, 2012.

International Search Report mailed Sep. 19, 2012 for PCT/US2012/048262 filed Jul. 26, 2012.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

FIG. 8





FIG. 9






FIG. 10




FIG. 11

FIG. 12

1

VORTEX DAMPING WIPER BLADE**CROSS REFERENCE TO RELATED APPLICATIONS**

This application claims the benefit of U.S. Provisional Application No. 61/477,908 filed Apr. 21, 2011, the disclosure of which is hereby incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

This invention relates to the field of windshield wiper blades, and in particular to the beam blade.

BACKGROUND

Typical wiper blades used on vehicles are plagued with numerous persistent drawbacks. Among these drawbacks are two common and interrelated drawbacks are of interest. The first such drawback is wiper blade separation from the surface of the windshield. The second such drawback is wind noise generated by the air moving over the wiper blade as a vehicle travels at speed.

One persistent cause of wiper blade separation from the windshield is the lack of sufficient downward force from the wiper blade onto the windshield. A major contributing factor to insufficient downward force involves wind lift. That is, wind passing over the windshield creates a "lifting" force which may cause the wiper blade to lose partial or complete contact with the surface of the windshield, and thus result in uneven or inconsistent clearing of water off the windshield. The wind lift problem has been known in the wiper field for decades, and many attempts have been made to resolve it. For example, see U.S. Pat. Nos. 3,056,991, 3,317,945, 3,879,793, 3,942,212, 6,292,974, 6,944,905, which are incorporated herein by reference in their entirety.

One common solution to the wind lift problem is to add a wind deflection structure, or spoiler, to the top of the wiper blade. On a beam blade, a spoiler is generally affixed to the top of the wiper blade, thereby substantially increasing the height and outer cross-section of the wiper blade overall, and increasing the need for an anti wind-lift structure. Moreover, for cost and ease of manufacture reasons, these spoilers have a uniform cross-sectional profile across the entire length, or substantially the entire length of the wiper blade structure. U.S. Pat. No. 6,944,905, for instance describes a uniformly shaped spoiler, except for the end sections, in which a wall and abrupt corner are used at the end of the wind deflection strip, slanting down to the end of the blade.

Another problem associated with wiper blades is that wind noise generated as a wiper blade is used while the vehicle travels at higher speeds. In general, undesirable wind noise from wiper blades originates in part from air vortices formed by wind contacting a wiper blade. In normal operation, as wind flows over a wiper blade, an air vortex forms behind the wiper blade, that is, on the leeward side of the wiper blade. Moreover, the size of the vortex is proportional to the height of the wiper blade, from its contact point with the windshield to the top of its cross-sectional profile. Thus, a wiper blade with a larger wind deflection structure generates a larger vortex, and therefore more noise.

Generally, wind noise is created as a wiper blade enters a slip stream of wind above the windshield. The wind noise created from wiper blades encountering the slip stream is distracting and makes for a less comfortable overall driving

2

experience. Reduction of such wind noise is therefore a constant concern associated with wiper blade design.

Wiper blade separation from the windshield is a primary concern in wiper blade design because of potential safety hazards that can arise out of poor wiping performance. However, a wiper blade designer should also attempt to minimize the amount of noise caused by the design of the wiper blade in order to allow for a more comfortable driving experience for the driver of the car on which the wiper blades are installed. Wiper blades currently used in the art do not adequately present a solution that addresses the wind lift problem while minimizing the amount of noise generated by the wiper blade.

BRIEF SUMMARY

The foregoing problems of prior wiper blades are resolved or at least substantially reduced and a technical advance is achieved in a low-profile wiper blade that reduces or eliminates wind-lift while damping wind noise. The present invention achieves this through a gradually decreasing-height cover attached to the surface of the beam of the beam blade.

In certain embodiments, the invention comprises a wiper blade having a beam with two ends, two longitudinal sides, a top side and a bottom side. The wiper blade further has a central bridge disposed on the top side of the beam, a wiper strip disposed on the bottom side of the beam and a cover having two longitudinal sides, two outer ends and a top surface. The cover may be disposed on the top side of the beam, and the top surface of the cover has a base portion having a height and a raised portion having a height, wherein the height of the raised portion is greater than the height of the base portion and the height of the raised portion gradually decreases as the raised portion approaches the outer ends of the cover.

Certain embodiments of the invention are directed to a wiper blade cover comprising two longitudinal sides, two outer ends and a top surface, wherein the cover is capable of being disposed on the top side of a beam. The top surface of the wiper blade cover may have a base portion having a height and a raised portion having a height, where the height of the raised portion is greater than the height of the base portion and the height of the raised portion gradually decreases as the raised portion approaches the outer ends of the cover.

Certain embodiments of the invention are directed to a wiper blade comprising a beam having two ends, a central bridge disposed on the beam, and a cover, wherein the cover has a spoiler that tapers from a highest point in the vicinity of the central bridge to a lowest point in the vicinity of the ends of the beam.

In some embodiments where the raised portion of the cover may optionally embody a wind deflection structure that gradually recedes along the length of the cover as it approaches the ends of the wiper blade, such that the tip of the wind deflection structure is either at or near the surface of the base of the cover at the ends of the wiper blade, or has completely receded into the base of the cover before reaching the end of the wiper blade.

In embodiments where the raised portion of the cover of the beam blade does not embody a spoiler, the cover the raised portion that gradually recedes along the length of the cover as it approaches the ends of the wiper blade such that the raised portion of the cover is at or near the surface of the base of the cover, at the ends of the wiper blade, or has completely receded into the base of the cover before reach-

ing the end of the wiper blade. In such embodiments, the raised portion of the cover is preferably curved in order to minimize the effect of the wind on that raised portion.

By gradually receding the top of the cover, whether it is a wind deflection structure or merely a raised portion, along the length of the cover as it approaches the ends of the wiper blade, the vortex formed behind the wiper blade relative to the direction of the oncoming wind is decreased along the length of the wiper blade, and approaching its ends. The decreasing profile of the cover reduces and/or dissipates the vortex, thereby reducing or eliminating the audible noise (to the driver of the vehicle) caused by the vortex.

It is notable that the portion(s) of the cover nearest the middle of the wiper blade need not be the "tallest" portions of the wiper blade. Also, the cover may be one piece, may be two pieces on either side of a connection device or mounting base attached at or near the middle of the beam, or may be made of multiple parts. In embodiments having two (or more) parts of the cover, there may be a cap, or caps, covering gaps in the cover. For instance, in an embodiment having two covers, one for each side of the wiper blade, there may be a cap which covers the inner ends of the two covers, and the connection device or mounting base.

Exemplary embodiments are attached hereto as examples of the invention, both with a wind deflection structure, and with a raised portion of the cover.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a perspective view of a first embodiment of a slim profile wiper blade of the present invention.

FIG. 2 illustrates a front view of a first embodiment of a slim profile wiper blade of the present invention.

FIG. 3 illustrates a bottom view of a first embodiment of a slim profile wiper blade of the present invention.

FIG. 4 illustrates a right end view of a first embodiment of a slim profile wiper blade of the present invention.

FIG. 5 illustrates a left end view of a first embodiment of a slim profile wiper blade of the present invention.

FIG. 6 illustrates a perspective view of a second embodiment of a slim profile wiper blade of the present invention.

FIG. 7 illustrates a right end view of a second embodiment of a slim profile wiper blade of the present invention.

FIG. 8 illustrates a front view of a second embodiment of a slim profile wiper blade of the present invention.

FIG. 9 illustrates a top view of a second embodiment of a slim profile wiper blade of the present invention.

FIG. 10 illustrates a bottom view of a second embodiment of a slim profile wiper blade of the present invention.

FIG. 11 illustrates a perspective view of a third embodiment of the invention.

FIG. 12 illustrates perspective view of a fourth embodiment of the invention.

As is apparent to persons of skill in the art FIGS. 1-12 depict the wiper blades as being flat for convenience and to show the relative relationships between the various parts. However, embodiments of the invention are preferably curved to better perform and contour to the shape of the spherical windshields found on motor vehicles. Accordingly, the scope of the invention is not intended to be limited to flat wiper blades and is intended to include curved embodiments within its scope.

DETAILED DESCRIPTION

The following detailed description and the appended drawings describe and illustrate exemplary embodiments of

the invention solely for the purpose of enabling one of ordinary skill in the relevant art to make and use the invention. As such, the detailed description and illustration of these embodiments are purely exemplary in nature and are in no way intended to limit the scope of the invention, or its protection, in any manner. The embodiments discussed below are described in sufficient detail to enable those skilled in the art to practice the subject matter disclosed herein. It is to be understood that the embodiments may be combined, or that other embodiments may be utilized, and that structural and logical variations may be made without departing from the scope of the subject matter disclosed. Accordingly, references to any particular embodiment are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features. It should also be understood that the drawings are not to scale and in certain instances details have been omitted, which are not necessary for an understanding of the present invention, such as conventional details of fabrication and assembly.

In certain embodiments, the invention comprises a wiper blade having a beam with two ends, two longitudinal sides, a top side and a bottom side. The wiper blade further has a central bridge disposed on the top side of the beam, a wiper strip disposed on the bottom side of the beam and a cover having two longitudinal sides, two outer ends and a top surface. The cover may be disposed on the top side of the beam, and the top surface of the cover has a base portion having a height and a raised portion having a height, wherein the height of the raised portion is greater than the height of the base portion and the height of the raised portion gradually decreases as the raised portion approaches the outer ends of the cover.

In certain embodiments of the invention, the wiper blade may further have a raised portion that forms a wind deflection structure having a generally triangular shape when viewed in cross section. In certain embodiments of the invention, the cover of the wiper blade may be symmetric in shape across a plane that is transverse to the two longitudinal sides of the cover. In certain embodiments of the invention the cover of the wiper blade may be symmetric in shape across a plane that extends vertically through a longitudinal axis of the cover.

In certain embodiments of the invention, the raised portion of the wiper blade may have an apex that merges with the base portion before the outer ends of the cover. In certain embodiments of the invention, the cover of the wiper blade may be provided with two claws that run along the two longitudinal sides of the cover, wherein the longitudinal sides of the beam are disposed in the two claws. In some such embodiments, the claws may end in the vicinity of the outer ends of the cover, and the outer ends of the cover may be provided with a structure that secures the ends of the beam.

In certain embodiments of the invention, the cover of the wiper blade may be a unitary structure and may be provided with a hole to accommodate the central bridge of the wiper blade. In other embodiments of the invention, the cover of the wiper blade may comprises two sections, where each section has an inner end and a gap is provided between the inner ends of the two sections to accommodate the central bridge. In some such embodiments, the wiper blade may have a cap that covers the gap and the inner ends of the two sections of the cover.

Certain embodiments of the invention are directed to a wiper blade cover comprising two longitudinal sides, two outer ends and a top surface, wherein the cover is capable of

5

being disposed on the top side of a beam. The top surface of the wiper blade cover may have a base portion having a height and a raised portion having a height, where the height of the raised portion is greater than the height of the base portion and the height of the raised portion gradually decreases as the raised portion approaches the outer ends of the cover.

In certain embodiments of the invention, the raised portion of the wiper blade cover forms a wind deflection structure having a generally triangular shape when viewed in cross-section. In certain embodiments of the invention the wiper blade cover is symmetric in shape across a plane that is transverse to the two longitudinal sides of the cover. In certain embodiments of the invention, the raised portion of the wiper blade cover may have an apex that merges with the base portion before the outer ends of the cover.

In certain embodiments of the invention, the wiper blade cover may be provided with two claws that run along the two longitudinal sides of the cover, wherein the claws are capable of receiving the longitudinal sides of a beam. In some such embodiments, the claws of the wiper blade cover may end in the vicinity of the outer ends of the cover, and the outer ends of the cover may be provided with a structure capable of securing the ends of the beam.

In certain embodiments of the invention, the wiper blade cover is a unitary structure and is provided with a hole to accommodate the central bridge of the wiper blade. In other embodiments of the invention, the wiper blade cover comprises two sections, each having an inner end, and a gap is provided between the inner ends of the two sections in order to accommodate a central bridge of a wiper blade. In some such embodiments, the wiper blade cover may further be provided with a cap that covers the gap and the inner ends of the two sections of the wiper blade cover.

Certain embodiments of the invention are directed to a wiper blade comprising a beam having two ends, a central bridge disposed on the beam, and a cover, wherein the cover has a spoiler that tapers from a highest point in the vicinity of the central bridge to a lowest point in the vicinity of the ends of the beam.

Referring to the drawings in general, an elongate, wiper blade **10** may be slender and includes a beam (or support element) **80**, a central bridge (or mounting base) **44**, a cover **22**, a front edge **32**, a rear edge **34**, opposing ends **26** having front edge **32** and rear edge **34** therebetween, a wiper strip **48** and either a tapered spoiler **60** or a tapered raised portion **61**. The wiper blade **10** may optionally further comprise a connector **14**. As best shown in FIG. 3, wiper blade **10** may have an outer edge or perimeter **56** formed by front edge **32**, left end **40**, rear edge **34**, and right end **36**. The front edge **32** and rear edge **34** may also be called the longitudinal sides of the wiper blade. The perimeter **56** is generally defined by a curvilinear cover **22**, having either a tapered spoiler **60** or a tapered raised portion **61**. The tapered spoiler **60** or tapered raised portion **61** constitute a highly effective means for damping air vortices. Connector **14**, which is removably attached to the central bridge **44**, secures the wiper blade **10** to a driver arm (not shown) that actuates the wiper blade **10**. As is well known in the art, different kinds of connectors may be used to connect the wiper blade **10** to different wiper arms, or multi-arm connectors can be used to connect to various types of arms. Additionally, the central bridge **44** may be designed to connect to a particular type (or types) of wiper arm(s), thereby making a connector **14** unnecessary.

FIGS. 1-5 depict a first embodiment of the wiper blade **10** having a cover **22** with a top surface **76** with a pedestal or base region that supports and defines the outer boundary of

6

the a raised portion that embodies a tapered spoiler **60**, having a generally triangular shape when viewed in cross-section (FIGS. 4 & 5). The tapered spoiler **60** provides a curvilinear outer surface **68**, best shown in FIG. 4. The tapered spoiler **60** provides a centrally elevated area most clearly defined at apex **64** (FIG. 4), which extends along axis **52** (FIG. 1). In use, the tapered spoiler **60** acts as a means for reducing wind vortices because it allows wind to pass over it with minimal or no noise effect. Specifically, the novel low-profile, longitudinally tapered design of tapered spoiler **60** provides minimized or negligible vortex at the leeward side of wiper blade **10**. The tapering of the tapered spoiler **60** is gradual, and tapering downwards towards the ends of the wiper blade **36**, **40**. Indeed, as shown in FIGS. 1 & 2, the height of the tapered spoiler **60** may recede into the height of the base portion of the top surface of the cover **22** in the vicinity of (either before the end of or at the end of) the outer ends of the cover such that the tapered spoiler **60** merges with the base portion. Alternatively, as shown in FIG. 12, the height of the tapered spoiler may still be greater than the height of the base portion of the top surface of the cover at the ends of the cover **22**.

The wiper blade **10** may also optionally further comprise a covering cap **18**, which covers the gaps between the cover and the central bridge **44**. As shown in FIGS. 1-5, the cover **22** may comprise two sections, each having an inner end in the vicinity of the central bridge **44**. As best seen in FIG. 3, the sections of the cover **22** thereby have a gap between their respective inner ends which accommodates the central bridge. As shown in FIG. 1, the covering cap **18** covers this gap and the inner ends of the cover sections, and is provided with a hole to accommodate the central bridge **44**. This covering cap may also be vertically extended to cover the connection area between wiper arm, the connector **14** (if one is used), and the central bridge **44** (not shown).

Alternatively, as shown in FIGS. 11 and 12, the cover may also be a single piece, shaped to cover the central bridge, thereby obviating the need for a covering cap **18**. In such embodiments, the cover **22** is provided with a hole which can accommodate the central bridge **44**. As shown in FIGS. 11 and 12, the portion of cover **22** surrounding the central bridge **44** may cover only the connection between the beam **80** and the central bridge **44**, leaving the connecting area between the central bridge **44**, wiper arm and connector **14** (if any) uncovered. Alternatively, the cover **22** may extend vertically to also cover the connection area between the wiper arm, connector **14** (if one is used) and the central bridge **44** (not shown).

As shown in FIGS. 1 and 11, the tapered spoiler **60** may be located in the center of the cover, or towards the rear edge of the cover **22**, and may be symmetric across the plane extending vertically through the axis **52**. Alternatively, as shown in FIG. 12, the apex **64** of the tapered spoiler **61** may be nearer to one longitudinal side (such as the rear edge **34**) than to the other. As shown in FIGS. 2, 11 and 12 the cover may also be symmetric across the plane that is transverse to the longitudinal sides and axis **52**.

FIGS. 6-10 depict a second preferred embodiment of the wiper blade **10** having an upper surface **76** with a pedestal or base region that supports and defines the outer boundary of the tapered raised portion **61**. As best illustrated in FIGS. 6 and 8, tapered raised portion **61** provides a gradual taper that extends nearly the entire length between right end **36** and left end **40**. As detailed in connection with the first preferred embodiment, the novel low-profile, slim design of tapered raised portion **61** provides minimized or negligible vortex at the leeward side of wiper blade **10**. Further, the

gradual taper of the tapered raised portion **61**, which is even less pronounced than the taper of the first preferred embodiment described above, provides exceptionally low drag and drastically limits vortex formation on the leeward edge. As best shown in FIGS. **8-10**, the second preferred embodiment of the wiper blade **10** includes partially blunted ends **36** and **40**. Because this second-preferred embodiment does not have a spoiler, or wind deflector, such embodiments preferably maintain a low profile. The distance from the bottom of the wiper strip to the highest point of the raised portion is preferably less than one inch, and is more preferably a half-inch or less.

As discussed above in connection with the first embodiment of the invention, in certain embodiments, the cover **22** may comprise two sections, each having inner ends in the vicinity of the central bridge **44** of the wiper blade, such that there is a gap between the inner ends of the cover sections which accommodates the central bridge **44**. In such embodiments the cover **22** may be provided with a covering cap **18** which covers that gap and the inner ends of the cover sections. The covering cap is provided with a hole to receive the central bridge, and may optionally be extended upwards to also cover the connection area including the central bridge **44**, connector **14** (if any) and the wiper arm. Alternatively, the cover **22** may be embodied as a unitary structure, obviating the need for a covering cap.

As also discussed above in connection with the first embodiment, the height of the tapered raised portion **61** may recede into the height of the base portion of the top surface of the cover **22** in the vicinity of (either before the end of or at the end of) the outer ends of the cover such that the tapered raised portion **61** merges with the base portion. Alternatively, the height of the tapered raised portion **61** may still be greater than the height of the base portion of the top surface of the cover at the ends of the cover **22**.

As shown in FIGS. **3** and **10**, the bottom of the beam **80** may receive and secure the wiper strip **48**. The beam **80** is attached to the central bridge **44** at joints **88**. These joints may be crimped or welded to the beam, shaped to fit notches in the beam or attached via any other method currently known in the art. It will also be apparent to one of skill in the art that the central bridge **44** is preferably in the middle of the beam **80**, but may be located anywhere along the length of the beam **80**.

The beam **80** is preferably made from a spring metal, and is generally rectangular, but may taper. The beam **80** may comprise a single strip, or may be two strips that are held together by the central bridge **44**, or other bridging devices (not shown) on the ends, or along the length of the beam **80**. If a single beam is used, it may be "U" or "O"-shaped, having a groove running longitudinally along the middle of the beam, such that a wiper strip **48** can be slid in between the groove between the sides of the "U" or "O". Alternatively, where the beam **80** may have no such groove, and the wiper strip may be secured to the bottom of the beam **80** by glue or clips, or any other methods currently known in the art for securing the wiper strip to the beam **80**.

Cover **22**, in turn is fitted or seated on and around the perimeter of beam **80**. The cover **22** may be fitted or seated to the ends of the beam **80** by means of detents, securing cavities **28**, claws, or other methods currently known in the art. As shown in FIGS. **3** and **10**, the cover **22** may be provided with claws which run along the longitudinal sides (i.e. front and rear edges **32**, **34** of the beam), and grip it along its length. The claws may run around the entire perimeter of the wiper blade (not shown), or as shown in FIGS. **3** & **10**, the claws may end in the vicinity of the outer

ends of the cover. Additionally, securing structures, such as detents or securing cavities (**28**) may be provided on the outer ends of the cover **22** which grip and secure the ends of the beam **80**. Optionally, cover **22** can be provided with an interior recess to receive an upper portion of wiper strip **48** and further secure the cover along its entire or a portion of its length. These and other methods of attaching a cover **22** to the surface of a beam **80** may be used and are considered within the scope of the invention. The cover **22** may be made of any suitable material, including natural or synthetic rubber or plastic or any other suitable polymeric material.

It is intended that the foregoing detailed description be regarded as illustrative rather than limiting, and that it be understood that it is the following claims, including all equivalents, that are intended to define the spirit and scope of this invention.

We claim:

1. A wiper blade comprising:

a beam having two ends, two longitudinal sides, a top side and a bottom side;
a central bridge disposed on the top side of the beam;
a wiper strip disposed on the bottom side of the beam;
a cover having two longitudinal sides, two outer ends and a top surface;
wherein:

the cover is disposed on the top side of the beam;
the top surface of the cover has a base portion having a height and a raised portion having a height wherein the height of the raised portion is greater than the height of the base portion;
the height of the raised portion gradually decreases as the raised portion approaches the outer ends of the cover; and
wherein the raised portion has an apex that merges with the base portion before the outer ends of the cover such that multiple cross-sections of the top surface of the cover have a substantially geometrically similar cross-sectional profile along a length of a longitudinal axis that is parallel to the two longitudinal sides of the cover until the apex merges with the base portion, and wherein the base portion has a substantially constant height.

2. The wiper blade of claim 1 wherein the raised portion forms a wind deflection structure having a generally triangular shape when viewed in cross section.

3. The wiper blade of claim 1 wherein the cover is symmetric in shape across a plane that is transverse to the two longitudinal sides of the cover.

4. The wiper blade of claim 1 wherein the cover is symmetric in shape across a plane that extends vertically through the longitudinal axis.

5. The wiper blade of claim 1 wherein the cover is provided with two claws that run along the two longitudinal sides of the cover, wherein the longitudinal sides of the beam are disposed in the two claws.

6. The wiper blade of claim 5 wherein the claws end in the vicinity of the outer ends of the cover, and wherein the outer ends of the cover are provided with a structure that secures the ends of the beam.

7. The wiper blade of claim 1 wherein the cover is a unitary structure and is provided with a hole to accommodate the central bridge of the wiper blade.

8. The wiper blade of claim 1 wherein the cover comprises two sections, each section having an inner end, wherein a gap is provided between the inner ends of the two sections to accommodate the central bridge.

9

9. The wiper blade of claim 8 wherein a cap is provided that covers the gap and the inner ends of the two sections.

10. A wiper blade cover comprising two longitudinal sides, two outer ends and a top surface;

wherein:

the cover is capable of being disposed on the top side of a beam;

the top surface of the cover has a base portion having a height and a raised portion having a height wherein the height of the raised portion is greater than the height of the base portion;

the height of the raised portion gradually decreases as the raised portion approaches the outer ends of the cover; and

wherein the raised portion has an apex that merges with the base portion before the outer ends of the cover such that multiple cross-sections of the top surface of the cover have a substantially geometrically similar cross-sectional profile along a length of a longitudinal axis that is parallel to the two longitudinal sides of the cover until the apex merges with the base portion, and wherein the base portion has a substantially constant height.

11. The wiper blade cover of claim 10 wherein the raised portion forms a wind deflection structure having a generally triangular shape when viewed in cross-section.

12. The wiper blade cover of claim 10 wherein the cover is symmetric in shape across a plane that is transverse to the two longitudinal sides of the cover.

13. The wiper blade cover of claim 10 wherein the cover is provided with two claws that run along the two longitudinal sides of the cover, wherein the claws are capable of receiving the longitudinal sides of a beam.

14. The wiper blade of claim 13 wherein the claws end in the vicinity of the outer ends of the cover, and wherein the outer ends of the cover are provided with a structure capable of securing the ends of the beam.

15. The wiper blade cover of claim 10 wherein the cover is a unitary structure and is provided with a hole to accommodate the central bridge of the wiper blade.

16. The wiper blade cover of claim 10 wherein the cover comprises two sections, each section having an inner end, wherein a gap is provided between the inner ends of the two sections to accommodate a central bridge of a wiper blade.

10

17. The wiper blade cover of claim 16 wherein the cover further comprises a cap that covers the gap and the inner ends of the two sections.

18. The wiper blade cover of claim 10, wherein the top surface of the cover has a similar cross-sectional profile along a longitudinal axis that is parallel to the two longitudinal sides of the wiper blade.

19. A wiper blade comprising:

a beam having two ends, two longitudinal sides, a top side and a bottom side;

a central bridge disposed on the top side of the beam;

a wiper strip disposed on the bottom side of the beam;

a cover having two longitudinal sides, two outer ends, a top surface, and two claws;

wherein:

the two claws run along the two longitudinal sides of the cover, and the longitudinal sides of the beam are disposed in the two claws;

the cover is disposed on the top side of the beam; the top surface of the cover has a base portion having a height and a raised portion having a height wherein the height of the raised portion is greater than the height of the base portion;

the height of the raised portion gradually decreases as the raised portion approaches the outer ends of the cover such that multiple cross-sections of the top surface of the cover having a substantially geometrically similar cross-sectional profile along a length of a longitudinal axis that is parallel to the two longitudinal sides of the cover until the raised portion merges with the base portion; and

wherein the claws end in the vicinity of, but at a distance from, the outer ends of the cover, and wherein the outer ends of the cover are provided with a structure that secures the ends of the beam such that the claws end before and are separate from the structure that secures the end of the beam.

20. The wiper blade of claim 19 wherein the raised portion has an apex that merges with the base portion before the outer ends of the cover such that the apex has a substantially constant shape, and wherein the base portion has a substantially constant height.

* * * * *