



US009462569B1

(12) **United States Patent**
Qu et al.

(10) **Patent No.:** **US 9,462,569 B1**
(45) **Date of Patent:** **Oct. 4, 2016**

(54) **DATA STORAGE SYSTEM MANAGEMENT**

(71) Applicants: **Qi Qu**, Shanghai (CN); **Scott E. Joyce**, Foxborough, MA (US); **Bruce R. Rabe**, Dedham, MA (US); **Xiaogang Wang**, Shanghai (CN)

(72) Inventors: **Qi Qu**, Shanghai (CN); **Scott E. Joyce**, Foxborough, MA (US); **Bruce R. Rabe**, Dedham, MA (US); **Xiaogang Wang**, Shanghai (CN)

(73) Assignee: **EMC Corporation**, Hopkinton, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 14 days.

(21) Appl. No.: **13/630,169**

(22) Filed: **Sep. 28, 2012**

(51) **Int. Cl.**
G06F 15/173 (2006.01)
H04W 64/00 (2009.01)
H04W 4/00 (2009.01)
H04L 29/08 (2006.01)

(52) **U.S. Cl.**
CPC **H04W 64/003** (2013.01); **H04L 67/24** (2013.01); **H04W 4/008** (2013.01)

(58) **Field of Classification Search**
CPC ... H04L 41/0213; H04L 29/06; H04L 41/22; H04L 41/12
USPC 709/223
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,565,676	B2 *	10/2013	Gormley et al.	455/41.1
8,768,765	B1 *	7/2014	Kato et al.	705/14.4
2007/0200712	A1 *	8/2007	Arneson et al.	340/572.8
2010/0261464	A1 *	10/2010	Deprun	455/418
2012/0185590	A1 *	7/2012	Kolin et al.	709/224
2012/0246074	A1 *	9/2012	Annamalai	G01S 1/68 705/44
2013/0098987	A1 *	4/2013	Jimenez Lamo	235/375
2014/0108084	A1 *	4/2014	Bargetzi et al.	705/7.19

OTHER PUBLICATIONS

NFC 2011: what's NFC and why do I care [Http://readwrite.com/#!/2011/02/25/nfc-in-2011-whats-nfc-and-why-do-i-care](http://readwrite.com/#!/2011/02/25/nfc-in-2011-whats-nfc-and-why-do-i-care).*

* cited by examiner


Primary Examiner — Tauqir Hussain

(74) *Attorney, Agent, or Firm* — Krishnendu Gupta; Jason A. Reyes

(57) **ABSTRACT**

There is disclosed a method and system for use in managing a data storage system. A management system stores information in connection with a data storage system. The information comprises a location of the data storage system. A near field communication link is established between a wireless mobile communications device and the management system in response to the wireless mobile communications device being positioned substantially adjacent the management system. The location of the data storage system is transmitted from the management system to the wireless mobile communications device over the near field communication link. The transmitted location of the data storage system is received in the wireless mobile communications device such that the wireless mobile communications device can assist in locating the data storage system.

6 Claims, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5




FIG. 6

DATA STORAGE SYSTEM MANAGEMENT

TECHNICAL FIELD

The invention relates to managing a data storage system. 5

BACKGROUND OF THE INVENTION

Computer systems may include different resources used by one or more host processors. Resources and host processors in a computer system may be interconnected by one or more communication connections. These resources may include, for example, data storage devices such as those included in the data storage systems manufactured by EMC Corporation. These data storage systems may be coupled to one or more servers or host processors and provide storage services to each host processor. Multiple data storage systems from one or more different vendors may be connected and may provide common data storage for one or more host processors in a computer system.

A host processor may perform a variety of data processing tasks and operations using the data storage system. For example, a host processor may perform basic system I/O operations in connection with data requests, such as data read and write operations.

Host processor systems may store and retrieve data using a storage device containing a plurality of host interface units, disk drives, and disk interface units. The host systems access the storage device through a plurality of channels provided therewith. Host systems provide data and access control information through the channels to the storage device and the storage device provides data to the host systems also through the channels. The host systems do not address the disk drives of the storage device directly, but rather, access what appears to the host systems as a plurality of logical disk units. The logical disk units may or may not correspond to the actual disk drives. Allowing multiple host systems to access the single storage device unit allows the host systems to share data in the device. In order to facilitate sharing of the data on the device, additional software on the data storage systems may also be used. In a common implementation, a Storage Area Network (SAN) is used to connect computing devices with a large number of storage devices. Management and modeling programs may be used to manage these complex computing environments, which may be include, or be included in a data center.

A data center refers to processing functionality for performing one or more prescribed processing tasks. For example, a provider may use a data center to implement any kind of network-accessible service. In some cases, the provider may use a specially designed computer room within a general purpose facility to implement the data center. For a particularly large-scale service, the provider may devote one or more separate facilities to implement the data center.

It will be appreciated that in recent time such data centers have grown substantially in size. It will be known that such modern data centers may comprise a plurality of data center equipment such as data storage systems. For example, the data center may comprise hundreds or thousands of discrete data storage systems. It will be understood that the task of managing such systems can be extremely arduous.

SUMMARY OF THE INVENTION

There is disclosed a method and system for use in managing a data storage system. A management system

stores information in connection with a data storage system. The information comprises a location of the data storage system. A near field communication link is established between a wireless mobile communications device and the management system in response to the wireless mobile communications device being positioned substantially adjacent the management system. The location of the data storage system is transmitted from the management system to the wireless mobile communications device over the near field communication link. The transmitted location of the data storage system is received in the wireless mobile communications device such that the wireless mobile communications device can assist in locating the data storage system.

Additionally, there is disclosed another method and system for use in managing a data storage system. A near field communication reader reads an identifier identifying a data storage system from a near field communication end point associated with the data storage system. The identifier is transmitted to a management system. The transmitted identifier is received in the management system. The identifier identifying the data storage system is stored in the management system.

BRIEF DESCRIPTION OF THE DRAWINGS

Features and advantages of the present invention will become more apparent from the following detailed description of exemplary embodiments thereof taken in conjunction with the accompanying drawings in which:

FIG. 1 illustrates an example of a data center that may be used with the techniques described herein;

FIG. 2 is a block diagrams of an example device that may be used with the techniques described herein;

FIG. 3A is a perspective diagram of a front of the example device of FIG. 2;

FIG. 3B is a perspective diagram of a back of the example device of FIG. 2;

FIGS. 4 to 6 are flowcharts of processing steps that may be performed in an embodiment in accordance with techniques described herein.

DETAILED DESCRIPTION

The invention can be implemented in numerous ways, including as a process, an apparatus, a system, a computer program embodied on a computer readable storage medium, and/or a processor, such as a processor configured to execute instructions stored on and/or provided by a memory coupled to the processor. In this specification, the implementations, or any other form that the invention may take, may be referred to as techniques. In general, the order of the steps of disclosed processes may be altered within the scope of the invention. Unless stated otherwise, a component such as a processor or a memory described as being configured to perform a task may be implemented as a general component that is temporarily configured to perform the task at a given time or a specific component that is manufactured to perform the task. As used herein, the term 'processor' refers to one or more devices, circuits, and/or processing cores configured to process data, such as computer program instructions.

Described below are techniques for use in managing a data storage system. It will be appreciated that a data center can comprise a plurality of data storage systems located in the data center. The vast size of some data centers means that finding a storage system accurately can be a problem. For

example, if an alert issues in connection with the storage system it will be necessary to locate the storage system in a timely manner to reduce the cost and the potential damage.

The techniques as described herein can enable the storage system to be located by using a wireless mobile communications device with near field communication capabilities to collect information from an asset management system over a near field communication link. The information can relate to the location of the data storage system. It will be understood that the asset management system can collect and store such information in connection with storage systems and provide the information to the mobile device. Once the user puts the mobile device near the portal of the asset management system, it can be activated to exchange information with the asset management system according to near field communication and the asset management system can provide the information to the device.

It will also be understood that in order to identify the storage system, the storage system can carry a near field communication endpoint which contains information such as a serial number which can identify the system. The information can be read using a near field communication reader.

Referring to FIG. 1, there is illustrated an example of an embodiment of a computer system that may be used in connection with performing the technique described herein. A data center **1100** may include zones **1110**, **1120**, **1130**, **1140**, and **1150** with each zone representing a grouping of storage component and/or a different type of data storage or processing. There is also illustrated an individual **1145** using a mobile computing device **1135**, for example, a wireless mobile communications device suitable for managing a data storage system **1155** in the data center **1100**.

Referring to FIG. 2, there is illustrated a block diagram of the device **1135** according to one example embodiment. The device **1135** may include a mobile phone, a smart phone, a laptop computer, a digital broadcast terminal, a personal digital assistant (PDA), a portable multimedia player (PMP), a navigation system and/or the like. The device **1135** may comprise a wireless communication unit **110**, an A/V (audio/video) input unit **120**, a user input unit **130**, a sensing unit **140**, an output unit **150** having a display **151**, a memory **160**, an interface unit **170**, a controller **180**, a power supply unit **190**, a locking set-up unit **195** and the like. The figure illustrates the device **1135** having various components, although all the illustrated components may not be a requirement. It will be appreciated that greater or fewer components may alternatively be implemented.

The wireless communication unit **110** may include one or more components that permit wireless communication between the device **1135** and a wireless communication system or network within which device **1135** is located. For example, the wireless communication unit **110** may include a broadcast receiving module **111**, a mobile communication module **112**, a wireless Internet module **113**, a short-range communication module **114**, a position determining module **115** and/or the like. The broadcast receiving module **111** may receive a broadcast signal and/or broadcast associated information from an external broadcast managing server via a broadcast channel, and the broadcast signal and/or broadcast associated information received by the broadcast receiving module **111** may be stored in a suitable device, such as the memory **160**. The mobile communication module **112** may transmit/receive wireless signals to/from one or more network entities (e.g., base station, external terminal, server, etc.). The wireless Internet module **113** may support Internet access for the device **1135**. This module may be internally or

externally coupled to the device **1135**. In this case, the wireless Internet technology can include WLAN (Wireless LAN) (Wi-Fi), Wibro (Wireless broadband), Wimax (World Interoperability for Microwave Access), HSDPA (High Speed Downlink Packet Access), etc. The short-range communication module **114** may facilitate near field communication (NFC). The position determining module **115** may identify or otherwise obtain the location or position of the device **1135**. This module may be a GPS module.

The audio/video (A/V) input unit **120** may provide audio or video signal inputs to the device **1135**. The A/V input unit **120** may include a camera **121** and a microphone **122**. The camera **121** may receive and process image frames of still pictures or videos that are obtained by an image sensor in a video call mode or a photograph mode. The processed image frames may be displayed on the display **151**. The image frames processed by the camera **121** may be stored in the memory **160** or may be externally transmitted via the wireless communication unit **110**. It will be appreciated that two or more cameras **121** may be provided to the device **1135** based on environment of usage. The microphone **122** may receive an external audio signal while the device **1135** is in a particular mode, such as phone call mode, a recording mode and/or a voice recognition mode. The audio signal may be processed and converted into electric audio data. The processed audio data may be transformed into a format transmittable to a mobile communication base station via the mobile communication module **112** in case of a call mode. The microphone **122** may include noise removing algorithms (or noise canceling algorithms) to remove or reduce noise generated in the course of receiving the external audio signal.

The user input unit **130** may generate input data responsive to user manipulation of an associated input device or devices. For example, the device may include a keypad, a dome switch, a touchpad (e.g., static pressure/capacitance), a jog wheel, a jog switch, and the like.

The sensing unit **140** may provide sensing signals for controlling operations of the device **1135** using status measurements of various aspects of the device **1135**. For example, the sensing unit **140** may detect an open/close status of the device **1135**, relative positioning of components (e.g., a display and a keypad) of the device **1135**, a position change of the device **1135** or a component of the device **1135**, a presence or an absence of user contact with the device **1135**, orientation or acceleration/deceleration of the device **1135**. For example, the device **1135** may be configured as a slide-type mobile terminal. The sensing unit **140** may sense whether a sliding portion of the device **1135** is open or closed. Other such examples may include the sensing unit **140** sensing presence or absence of power provided by the power supply **190**, presence or absence of a coupling or other connection between the interface unit **170** and an external device. The sensing unit **140** may include a proximity sensor **141** and a touch sensor **142**.

The output unit **150** may generate outputs perceptible to the senses such as sight, hearing, touch and the like. The output unit **150** may include the display **151**, an audio output module **152**, an alarm **153** and a haptic module **154**. The display **151** may visually display (i.e., output) information associated with the device **1135**. For example, if the device **1135** is operated in a phone call mode, the display **151** may provide a user interface (UI) or a graphical user interface (GUI) that includes information associated with placing, conducting, and/or terminating a phone call. If the device **1135** is in a video call mode or a photograph mode, the display **151** may additionally or alternatively display infor-

mation associated with these modes. The display **151** may be implemented using known display technologies including, for example, a liquid crystal display (LCD), a thin film transistor-liquid crystal display (TFT-LCD), an organic light-emitting diode display (OLED), a flexible display and a three-dimensional (3-D) display. The device **1135** may include one or more such displays. Some of the displays may be implemented in a transparent or optical transmissive type that can be called a transparent display. A transparent OLED (or TOLED) may be an example of the transparent display. The display **151** may also be implemented as the optical transmissive type. In this configuration, a user may see an object in rear of a terminal body via an area occupied by the display **151** of the terminal body. It will be appreciated that at least two displays **151** may be provided on the device **1135** based on the configuration of the device **1135**. For example, a plurality of displays may be arranged on a single face of the device **1135** by being spaced apart from each other or by being built in one body. A plurality of displays may be arranged on different faces of the device **1135**.

In a case where the display **151** and the touch sensor **142** for detecting a touch action are configured in a mutual layer structure (hereinafter "a touch screen"), the display **151** may be used as an input device as well as an output device. The touch sensor **142** may be configured as a touch film, a touch sheet, a touchpad and/or the like. The touch sensor **142** may convert a pressure applied to a specific portion of the display **151** or a variation of a capacitance generated from a specific portion of the display **151** to an electric input signal. The touch sensor **142** may detect a pressure of a touch as well as a touched position or size. A separate pressure sensor may detect pressure of the touch. If a touch input is provided to the touch sensor **142**, signal(s) corresponding to the touch may be transferred to a touch controller. The touch controller may process the signal(s) and then transfer the processed signal(s) to the controller **180**. The controller **180** may determine whether a prescribed portion of the display **151** is touched.

The proximity sensor **141** may also be provided to an internal area of the device **1135** enclosed by the touch screen and/or around the touch screen. The proximity sensor **141** may detect a presence or non-presence of an object approaching a prescribed detecting surface or an object existing around the proximity sensor **141** using an electromagnetic field strength or infrared ray without mechanical contact. The proximity sensor **141** may have longer durability than a contact type sensor and may also have a wider utility than the contact type sensor. The proximity sensor **141** may include one of a transmissive photoelectric sensor, a direct reflective photoelectric sensor, a mirror reflective photoelectric sensor, a radio frequency oscillation proximity sensor, an electrostatic capacity proximity sensor, a magnetic proximity sensor, an infrared proximity sensor and the like. If the touch screen includes the electrostatic capacity proximity sensor, the proximity of a pointer may be detected using a variation of electric field according to proximity of the pointer. The touch screen (i.e., touch sensor) may be classified as the proximity sensor **141**. In the following description, an action in which a pointer approaches without contacting the touch screen may be called a proximity touch. An action in which a pointer actually touches the touch screen may be called a contact touch. The meaning of the position on the touch screen proximity-touched by the pointer may define a position of the pointer that vertically opposes the touch screen when the pointer performs the proximity touch. The proximity sensor **141** may detect a proximity touch and a proximity touch pattern (e.g., a

proximity touch distance, a proximity touch duration, a proximity touch position, a proximity touch shift state, etc.). Information corresponding to the detected proximity touch action and the detected proximity touch pattern may be outputted to the touch screen.

The audio output module **152** may function in various modes including a call-receiving mode, a call-placing mode, a recording mode, a voice recognition mode, a broadcast reception mode and/or the like to output audio data that is received from the wireless communication unit **110** or is stored in the memory **160**. During operation, the audio output module **152** may output an audio signal relating to a particular function (e.g., a call received, a message received, etc.). The audio output module **152** may be implemented using one or more speakers, buzzers, other audio producing devices, and/or combinations thereof.

The alarm **153** may output a signal for announcing an occurrence of a particular event associated with the device **1135**. Events may include a call received event, a message received event and a touch input received event. The alarm **153** may output a signal for announcing the event occurrence by way of vibration as well as video or audio signal. The video or audio signal may be outputted via the display **151** or the audio output unit **152**. The display **151** or the audio output module **152** may be regarded as a part of the alarm **153**.

The haptic module **154** may generate various tactile effects that can be sensed by a user. Vibration may be a representative one of the tactile effects generated by the haptic module **154**. Strength and pattern of the vibration generated by the haptic module **154** may be controllable. For example, different vibrations may be outputted by being combined (or synthesized) together or may be outputted in sequence. The haptic module **154** may generate various tactile effects as well as vibrations. For example, the haptic module **154** may generate an effect attributed to the arrangement of pins vertically moving against a contact skin surface, an effect attributed to injection/suction power of air through an injection/suction hole, an effect attributed to a skim over a skin surface, an effect attributed to a contact with an electrode, an effect attributed to an electrostatic force, an effect attributed to representation of warm/cold sense using an endothermic or exothermic device and/or the like. The haptic module **154** may enable a user to sense a tactile effect through a muscle sense of a finger, an arm or the like as well as to transfer the tactile effect through a direct contact. At least two haptic modules **154** may be provided on the device **1135** based on a corresponding configuration type of the device **1135**.

The memory **160** may store programs for operating the controller **180**. The memory **160** may temporarily store input/output data such as phonebook data, message data, still image, and/or moving image. Data for various patterns of vibration and/or sound outputted in case of a touch input to the touch screen may be stored in the memory **160**. The memory **160** may be implemented using any type or combination of suitable volatile and non-volatile memories or storage devices including a hard disk, a random access memory (RAM), a static random access memory (SRAM), an electrically erasable programmable read-only memory (EEPROM), an erasable programmable read-only memory (EPROM), a programmable read-only memory (PROM), a read-only memory (ROM), a magnetic memory, a flash memory, a magnetic or optical disk, a multimedia card micro type memory, a card-type memory (e.g., SD memory, XD memory, etc.) and/or other similar memory or data storage device.

The interface unit **170** may couple the device **1135** with external devices. The interface unit **170** may receive data from the external devices or may be supplied with power and then transfer the data or power to respective elements of the device **1135** or enable data within the device **1135** to be transferred to the external devices. For example, when the device **1135** is connected to an external cradle, the interface unit **170** may become a passage for supplying the device **1135** with power from the cradle or a passage for delivering various command signals inputted from the cradle by a user to the device **1135**. The interface unit **170** may also be configured using a wired/wireless headset port, an external charger port, a wired/wireless data port, a memory card port, a port for coupling to a device having an identity module, audio input/output ports, video input/output ports, an ear-phone port and/or the like. The identity module may be a chip for storing various kinds of information for authenticating a use authority of the device **1135** and may include a User Identify Module (UIM), a Subscriber Identity Module (SIM), a Universal Subscriber Identity Module (USIM) and/or the like. A device having an identity module (hereinafter "identity device") may be manufactured as a smart card. The identity device may be connectable to the device **1135** via a relevant port.

The controller **180** may control overall operations of the device **1135**. For example, the controller **180** may perform control and processing associated with voice calls, data communications, video calls, etc. The controller **180** may include a multimedia module **181** that provides multimedia playback. The multimedia module **181** may be configured as part of the controller **180**, or may be implemented as a separate component. The controller **180** may have a time counting function. The controller **180** may also perform a pattern recognizing process for recognizing a writing input or a picture drawing input carried out on the touch screen as characters or images, respectively.

It will be appreciated that the power supply unit **190** may provide a power required by various components of the device **1135**. The power may be internal power, external power, and/or a combination thereof.

It will also be appreciated that embodiments may be implemented in a computer-readable medium using, for example, computer software, hardware, and/or some combination thereof. For hardware implementation, embodiments may be implemented using one or more applications of specific integrated circuits (ASICs), digital signal processors (DSPs), digital signal processing devices (DSPDs), programmable logic devices (PLDs), field programmable gate arrays (FPGAs), processors, controllers, micro-controllers, microprocessors, other electronic units designed to perform functions described herein, and/or a selective combination thereof. Embodiments may also be implemented by the controller **180**. For software implementation, embodiments may be implemented with separate software modules, such as procedures and functions, each of which may perform one or more of the functions and operations described herein. The software codes may be implemented with a software application written in any suitable programming language and may be stored in the memory **160**, and executed by a controller or a processor, such as the controller **180**.

Referring to FIG. 3A, there is illustrated a front view of a device **1135** according to an example embodiment. It will be appreciated that other embodiments, arrangements and configurations may also be provided. The device **1135** may have a bar type terminal body. Embodiments of the device **1135** may be implemented in a variety of other configura-

tions. Examples of such configurations may include a folder-type, a slide-type, a bar-type, a rotational-type, a swing-type and/or combinations thereof. The body may include a case (e.g., a casing, a housing, a cover) that form an exterior of the device. The case may be divided into a front case **101** and a rear case **102**. The various electric/electronic parts may be provided in a space between the front case **101** and the rear case **102**. The display **151**, the audio output unit **152**, the camera **121**, the user input unit **130** (including first and second manipulation units **131**, **132**), the microphone **122**, the interface unit **170** and the like may be provided on the device body. The display **151** may occupy most of a main face of the front case **101**. The audio output module **152** and the camera **121** may be provided at an area adjacent to one end portion of the display **151**, while the first manipulation unit **131** and the microphone **122** may be provided at another area adjacent to the other end portion of the display **151**. The second manipulation unit **132** and the interface unit **170** may be provided on lateral sides of the front and rear cases **101** and **102**.

The user input unit **130** may receive a command for controlling an operation of the device **1135**. The user input unit **130** may include the first and second manipulating units **131** and **132**. The first and second manipulating units **131** and **132** may be called a manipulating portion and may adopt any mechanism of a tactile manner that enables a user to perform a manipulation action. Content inputted by the first manipulating unit **131** or the second manipulating unit **132** may be diversely set. For example, a command such as a start, an end, a scroll and/or the like may be inputted to the first manipulating unit **131**. A command for a volume adjustment of sound outputted from the audio output unit **152**, a command for a switching to a touch recognizing mode of the display **151** and/or the like may be inputted to the second manipulating unit **132**.

Referring to FIG. 3B, there is illustrated a view of a backside of the device shown in FIG. 3A. It will be appreciated that other embodiments, arrangements and configurations may also be provided. A camera **121'** may be additionally provided on a backside of the device body, and more particularly on the rear case **102**. The camera **121'** may have a photographing direction that is substantially opposite to a photographing direction of the camera **121** and may have pixels differing from pixels of the camera **121**. For example, the camera **121** may have a lower number of pixels to capture and transmit a picture of a user face for a video call, while the camera **121'** may have a greater number of pixels for capturing a general subject for photography without transmitting the captured subject. Each of the cameras **121** and **121'** may be provided on the device body to be rotated and/or popped up. A flash **123** and a mirror **124** may be additionally provided adjacent to the camera **121'**. The flash **123** may project light toward a subject in case of photographing the subject using the camera **121'**. If a user attempts to take a picture of the user (i.e., self-photography) using the camera **121'**, the mirror **124** may enable the user to view a user face reflected by the mirror **124**. An additional audio output unit **152'** may be provided on a backside of the device body. The additional audio output unit **152'** may implement a stereo function together with the audio output unit **152** and may be used for implementation of a speakerphone mode in talking over the device **1135**. A broadcast signal receiving antenna (not shown) may be additionally provided at the lateral side of the device body as well as an antenna for communication or the like. The antenna may be considered as a portion of the broadcast receiving module **111** and/or may be retractably provided on the device body.

The power supply unit **190** for supplying a power to the device **1135** may be provided with respect to the device body. The power supply unit **190** may be built within the device body. Alternatively, the power supply unit **190** may be detachably connected to the device body. The figure also illustrates a touchpad **135** for detecting a touch that is additionally provided on the rear case **102**. The touchpad **135** may be configured as a light transmissive type. If the display **151** outputs visual information from both faces, the display **151** may also recognize visual information via the touchpad **135**. The information outputted from both of the faces may be controlled by the touchpad **135**.

Referring to FIG. 4, there is illustrated a technique **400** for use in managing a data storage system such as the data storage system **1155** located in the data center **1100** as illustrated in FIG. 1. The technique comprises storing information **410** in connection with a data storage system **1155** in a management system. For example, the management system may be a remote computing system suitable for storing information with respect to equipment in the data center **1100** such that a system administrator can centrally access the information. It will be understood that in this embodiment the information will comprise at least a location of the data storage system. The location of the data storage system can comprise the longitude and latitude of the data storage system in the data center. It will also be understood that the location can also include the position of the data storage system in a rack suitable for holding a plurality of data storage systems. For example, it will be known in the art that a data center can comprise a plurality of racks with each rack having a plurality of data storage systems. When there is a plurality of racks and storage systems, the location can include the location of the rack and the position of the storage system relative to the other storage systems in the rack. Additionally, it will be understood that the information can comprise a map for facilitating the location of the storage system. For example, the map can be the map of the data center **1100** uploaded to the management system.

The technique comprises establishing a near field communication link **420** between a wireless mobile communications device **1135** and the management system in response to the wireless mobile communications device **1135** being positioned substantially adjacent the management system. It will be appreciated that the mobile device **1135** as described herein comprises a module **114** for facilitating near field communication. This type of device can also be generally referred to as a near field communication enabled device, near field communication communicator, and the like. It will be understood that such a device **1135** is designed to communicate within a particular range or field of operation, for example, a few centimeters. By positioning the device **1135** substantially adjacent the management system, the device can establish a near field communication link with the management system for facilitating communication therebetween. For example, the user may request information from the management system relating to a specific storage system. The user can subsequently position the device **1135** adjacent the management system to establish a link such that an exchange can take place.

The technique comprises transmitting **430** the location of the data storage system from the management system to the wireless mobile communications device **1135** over the near field communication link. For example, the management system can provide the location to the device for enabling the user to locate the storage system. The management system can also provide a map such that the map can assist in directing the user to the location.

The technique also comprises receiving **440** the transmitted location of the data storage system in the wireless mobile communications device **1135** such that the wireless mobile communications device can assist in locating the data storage system.

Referring to FIG. 5, there is illustrated a technique **500** for use in managing a data storage system such as the data storage system **1155** located in the data center **1100** as illustrated in FIG. 1. It will be appreciated that the first step of storing information in connection with the data storage system as described in step **410** in FIG. 4 may at least in some embodiments be performed by the technique as described herein with respect to FIG. 5. The technique comprises reading **510** by a near field communication reader an identifier identifying a data storage system **1155** from a near field communication end point associated with the data storage system. It will be understood that the reader can be a stand-alone device or incorporated in another apparatus. Indeed, it will be understood that in this embodiment the device **1135** can also act as the reader using the module **114**. It will be understood that in this embodiment the near field communication end point is unique to the data storage system and contains a serial number for identifying the data storage system. The technique comprises transmitting **520** the identifier to a management system. For example, the device **1135** can transmit the identifier using the communications module **112**. As discussed above, the management system may be a remote computing system suitable for storing information relating to equipment located in the data center **1100**. Additionally, the technique comprises receiving **530** the transmitted identifier in the management system. Furthermore, the technique comprises storing **540** the identifier identifying the data storage system in the management system.

For example, the user may travel around the data center with a near field communication reader for reading the near field communication end point from each data storage system such that the identifier's can be stored centrally in a management system. It will be appreciated that the user may travel the data center with the device **1135** using the module **114** to read the respective end-points and communicate the identifier's using the mobile communications module **112** to the management system. The location of the respective storage systems may also be determined by the device **1135** as will be described below or determined separately such that the identifier and location can be recorded in the management system.

While the above technique describes the device **1135** reading the an identifier identifying the data storage system from a near field communication end point associated with the data storage system, it will be appreciated that the near field communication reader can in some embodiments be separate from the device **1135** and be a stand alone device.

Referring to FIG. 6, there is illustrated a technique **600** for use in managing a data storage system such as the data storage system **1155** located in the data center **1100** as illustrated in FIG. 1. It will also be appreciated that the first step of storing information in connection with the data storage system as described in step **410** in FIG. 4 may at least in some embodiments be performed by the technique as described herein with respect to FIG. 6. The technique as described herein comprises determining **610** a current location of a mobile device **1135** in response to the device being positioned local to the data storage system. For example, the mobile device may be positioned adjacent the data storage system such that the location of the device is substantially similar to the location of the data storage system. The mobile

11

device **1135** comprises a position determining module **115** for determining the current geographical location of the device. For example, the module may be a global positioning system (GPS) module with the capacity to determine the current longitude and latitude of the device. It will be understood that the current latitude and longitude of the device **1135** positioned local to the data storage system may be considered as the current latitude and longitude of the data storage system. It will also be understood that the module may have the capacity to determine the current altitude of the device.

The technique comprises reading **620** by a near field communication reader an identifier identifying a data storage system **1155** from a near field communication end point associated with the data storage system. It will be appreciated that in this embodiment the device **1135** incorporates a module **114** for reading the identifier from the near field communication end point associated with the data storage system by positioning the device substantially adjacent the end-points.

Furthermore, the technique comprises transmitting **630** the current location and identifier to the management system such that the information can be stored in the management system. For example, the technique may transmit the determined longitude and latitude of the device when positioned local to the data storage system and a serial number identifier identifying the data storage system. It will be appreciated that the device **1135** may transmit the location and the identifier in connection with the data storage system using the wireless communication unit **110**.

Additionally, the technique comprises receiving **640** the transmitted current location and the identifier in the management system. Furthermore, the technique comprises storing **650** the transmitted current location and the identifier in the management system.

While the invention has been disclosed in connection with preferred embodiments shown and described in detail, their modifications and improvements thereon will become readily apparent to those skilled in the art. Accordingly, the spirit and scope of the present invention should be limited only by the following claims.

What is claimed is:

1. A method, comprising:

storing, by a management system, information in connection with a plurality of data storage systems, wherein the information comprises a location and an identifier of respective data storage systems;

receiving, by the management system, an identifier identifying a data storage system, wherein the identifier is received from a mobile computing device over a near field communication (NFC) link when the mobile computing device is positioned adjacent the management system; and

transmitting, by the management system, the location information in connection with the data storage system to the mobile computing device in exchange for receiving

12

the identifier of the data storage system from the mobile computing device, wherein the location information is transmitted to the mobile computing device over a near field communication (NFC) link when the mobile computing device is positioned adjacent the management system, further wherein the location information comprises a map for locating the data storage system among the plurality of the data storage systems; wherein the management system is near field communication (NFC) enabled for enabling the identifier to be received and the location information to be transmitted when the device is positioned adjacent the management system.

2. The method as claimed in claim **1**, wherein the location information in connection with the data storage system comprises the longitude and latitude of the data storage system.

3. The method as claimed in claim **1**, wherein the location information in connection with the data storage system comprises the position of the data storage system in a rack suitable for holding a plurality of data storage systems.

4. A management system, comprising:

storage for storing information in connection with a plurality of data storage systems, wherein the information comprises a location and an identifier of respective data storage systems;

a receiver for receiving an identifier identifying a data storage system, wherein the identifier is received from a mobile computing device over a near field communication (NFC) link when the mobile computing device is positioned adjacent the management system; and

a transmitter for transmitting the location information in connection with the data storage system to the mobile computing device in exchange for receiving the identifier of the data storage system from the mobile computing device, wherein the location information is transmitted to the mobile computing device over a near field communication (NFC) link when the mobile computing device is positioned adjacent the management system, further wherein the location information comprises a map for locating the data storage system among the plurality of the data storage systems;

wherein the management system is near field communication (NFC) enabled for enabling the receiver to receive the identifier and the transmitter to transmit the location information when the device is positioned adjacent the management system.

5. The system as claimed in claim **4**, wherein the location information in connection with the data storage system comprises the longitude and latitude of the data storage system.

6. The system as claimed in claim **4**, wherein the location information in connection with the data storage system comprises the position of the data storage system in a rack suitable for holding a plurality of data storage systems.

* * * * *