



(12) **United States Patent**
Cune et al.

(10) **Patent No.:** **US 9,270,374 B2**
(45) **Date of Patent:** ***Feb. 23, 2016**

(54) **PROVIDING DIGITAL DATA SERVICES IN OPTICAL FIBER-BASED DISTRIBUTED RADIO FREQUENCY (RF) COMMUNICATIONS SYSTEMS, AND RELATED COMPONENTS AND METHODS**

(71) Applicant: **Corning Optical Communications LLC**, Hickory, NC (US)
(72) Inventors: **William Patrick Cune**, Charlotte, NC (US); **Michael Sauer**, Corning, NY (US); **Wolfgang Gottfried Tobias Schweiker**, Weyarn (DE)
(73) Assignee: **Corning Optical Communications LLC**, Hickory, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/711,306**
(22) Filed: **May 13, 2015**
(65) **Prior Publication Data**

US 2015/0249502 A1 Sep. 3, 2015
Related U.S. Application Data

(63) Continuation of application No. 13/785,603, filed on Mar. 5, 2013, now Pat. No. 9,042,732, which is a continuation of application No. 12/892,424, filed on Sep. 28, 2010, now abandoned.

(60) Provisional application No. 61/330,386, filed on May 2, 2010.

(51) **Int. Cl.**
H04B 10/2575 (2013.01)
H04J 14/02 (2006.01)

(52) **U.S. Cl.**
CPC **H04B 10/25752** (2013.01); **H04B 10/25753** (2013.01); **H04J 14/02** (2013.01); **H04J 14/0282** (2013.01); **H04J 14/0298** (2013.01)

(58) **Field of Classification Search**
CPC H04J 14/0282; H04J 10/2575; H04J 10/25753

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,365,865 A 12/1982 Stiles
4,867,527 A 9/1989 Dotti et al.
(Continued)

FOREIGN PATENT DOCUMENTS

AU 645192 B2 1/1994
AU 731180 B2 3/2001
(Continued)

OTHER PUBLICATIONS


Notification of Grant for Chinese patent application 201190000473.1 issued Aug. 28, 2013, 4 pages.
(Continued)

Primary Examiner — Nathan Curs
(74) *Attorney, Agent, or Firm* — C. Keith Montgomery, Esq.

(57) **ABSTRACT**

Optical fiber-based distributed communications systems that provide and support both RF communication services and digital data services are disclosed herein. The RF communication services and digital data services can be distributed over optical fiber to client devices, such as remote antenna units for example. In certain embodiments, digital data services can be distributed over optical fiber separate from optical fiber distributing RF communication services. In other embodiments, digital data services can be distributed over common optical fiber with RF communication services. For example, digital data services can be distributed over common optical fiber with RF communication services at different wavelengths through wavelength-division multiplexing (WDM) and/or at different frequencies through frequency-division multiplexing (FDM). Power distributed in the optical fiber-based distributed communications system to provide power to remote antenna units can also be accessed to provide power to digital data service components.

8 Claims, 15 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,889,977	A	12/1989	Haydon	5,880,863	A	3/1999	Rideout et al.
4,896,939	A	1/1990	O'Brien	5,881,200	A	3/1999	Burt
4,916,460	A	4/1990	Powell	5,883,882	A	3/1999	Schwartz
4,972,505	A	11/1990	Isberg	5,890,055	A	3/1999	Chu et al.
5,039,195	A	8/1991	Jenkins et al.	5,896,568	A	4/1999	Tseng et al.
5,042,086	A	8/1991	Cole et al.	5,903,834	A	5/1999	Wallstedt et al.
5,125,060	A	6/1992	Edmundson	5,910,776	A	6/1999	Black
5,189,718	A	2/1993	Barrett et al.	5,913,003	A	6/1999	Arroyo et al.
5,189,719	A	2/1993	Coleman et al.	5,917,636	A	6/1999	Wake et al.
5,206,655	A	4/1993	Caille et al.	5,930,682	A	7/1999	Schwartz et al.
5,210,812	A	5/1993	Nilsson et al.	5,936,754	A	8/1999	Ariyavisitakul et al.
5,260,957	A	11/1993	Hakimi et al.	5,943,372	A	8/1999	Gans et al.
5,263,108	A	11/1993	Kurokawa et al.	5,946,622	A	8/1999	Bojeryd
5,267,122	A	11/1993	Glover et al.	5,949,564	A	9/1999	Wake
5,268,971	A	12/1993	Nilsson et al.	5,959,531	A	9/1999	Gallagher, III et al.
5,280,472	A	1/1994	Gilhausen et al.	5,960,344	A	9/1999	Mahany
5,295,154	A	3/1994	Meier et al.	5,969,837	A	10/1999	Farber et al.
5,299,947	A	4/1994	Barnard	5,982,413	A	11/1999	Irie et al.
5,301,056	A	4/1994	O'Neill	5,983,070	A	11/1999	Georges et al.
5,339,058	A	8/1994	Lique	5,987,303	A	11/1999	Dutta et al.
5,339,184	A	8/1994	Tang	6,005,884	A	12/1999	Cook et al.
5,377,035	A	12/1994	Wang et al.	6,006,105	A	12/1999	Rostoker et al.
5,379,455	A	1/1995	Koschek	6,014,546	A	1/2000	Georges et al.
5,400,391	A	3/1995	Emura et al.	6,016,426	A	1/2000	Bodell
5,404,570	A	4/1995	Charas et al.	6,023,625	A	2/2000	Myers, Jr.
5,424,864	A	6/1995	Emura	6,046,992	A	4/2000	Meier et al.
5,428,636	A	6/1995	Meier	6,078,622	A	6/2000	Boytim et al.
5,444,564	A	8/1995	Newberg	6,088,381	A	7/2000	Myers, Jr.
5,457,557	A	10/1995	Zarem et al.	6,124,957	A	9/2000	Goel et al.
5,459,727	A	10/1995	Vannucci	6,127,917	A	10/2000	Tuttle
5,469,523	A	11/1995	Blew et al.	6,128,470	A	10/2000	Naidu et al.
5,499,241	A	3/1996	Thompson et al.	6,148,041	A	11/2000	Dent
5,504,746	A	4/1996	Meier	6,150,921	A	11/2000	Werb et al.
5,519,691	A	5/1996	Darcie et al.	6,157,810	A	12/2000	Georges et al.
5,543,000	A	8/1996	Lique	6,219,553	B1	4/2001	Panasik
5,544,161	A	8/1996	Bigham et al.	6,222,503	B1	4/2001	Gietema et al.
5,546,443	A	8/1996	Raith	6,223,021	B1	4/2001	Silvia et al.
5,553,064	A	9/1996	Paff et al.	6,232,870	B1	5/2001	Garber et al.
5,557,698	A	9/1996	Gareis et al.	6,236,789	B1	5/2001	Fitz
5,574,815	A	11/1996	Kneeland	6,240,274	B1	5/2001	Izadpanah
5,598,288	A	1/1997	Collar	6,268,946	B1	7/2001	Larkin et al.
5,603,080	A	2/1997	Kallander et al.	6,292,673	B1	9/2001	Maeda et al.
5,615,034	A	3/1997	Hori	6,301,240	B1	10/2001	Slabinski et al.
5,621,786	A	4/1997	Fischer et al.	6,314,163	B1	11/2001	Acampora
5,627,879	A	5/1997	Russell et al.	6,317,599	B1	11/2001	Rappaport et al.
5,640,678	A	6/1997	Ishikawa et al.	6,323,980	B1	11/2001	Bloom
5,642,405	A	6/1997	Fischer et al.	6,324,391	B1	11/2001	Bodell
5,644,622	A	7/1997	Russell et al.	6,330,244	B1	12/2001	Swartz et al.
5,648,961	A	7/1997	Ebihara	6,337,754	B1	1/2002	Imajo
5,651,081	A	7/1997	Blew et al.	6,353,406	B1	3/2002	Lanzl et al.
5,657,374	A	8/1997	Russell et al.	6,353,600	B1	3/2002	Schwartz et al.
5,668,562	A	9/1997	Cutrer et al.	6,356,374	B1	3/2002	Farhan
5,677,974	A	10/1997	Elms et al.	6,359,714	B1	3/2002	Imajo
5,682,256	A	10/1997	Motley et al.	6,373,611	B1	4/2002	Farhan et al.
5,684,799	A	11/1997	Bigham et al.	6,374,078	B1	4/2002	Williams et al.
5,689,355	A	11/1997	Okubo et al.	6,374,124	B1	4/2002	Slabinski
5,703,602	A	12/1997	Casebolt	6,374,311	B1	4/2002	Mahany et al.
5,726,984	A	3/1998	Kubler et al.	6,389,010	B1	5/2002	Kubler et al.
5,774,789	A	6/1998	van der Kaay et al.	6,392,770	B1	5/2002	Sasai et al.
5,790,536	A	8/1998	Mahany et al.	6,405,018	B1	6/2002	Reudink et al.
5,790,606	A	8/1998	Dent	6,405,058	B2	6/2002	Bobier
5,802,173	A	9/1998	Hamilton-Piercy et al.	6,405,308	B1	6/2002	Gupta et al.
5,802,473	A	9/1998	Rutledge et al.	6,438,301	B1	8/2002	Johnson et al.
5,805,983	A	9/1998	Naidu et al.	6,438,371	B1	8/2002	Fujise et al.
5,809,422	A	9/1998	Raleigh et al.	6,452,915	B1	9/2002	Jorgensen
5,812,296	A	9/1998	Tarusawa et al.	6,477,154	B1	11/2002	Cheong et al.
5,818,619	A	10/1998	Medved et al.	6,480,702	B1	11/2002	Sabat, Jr.
5,821,510	A	10/1998	Cohen et al.	6,486,907	B1	11/2002	Farber et al.
5,825,651	A	10/1998	Gupta et al.	6,496,290	B1	12/2002	Lee
5,825,829	A	10/1998	Borazjani et al.	6,501,768	B2	12/2002	Marin et al.
5,832,364	A	11/1998	Gustafson	6,501,942	B1	12/2002	Weissman et al.
5,838,474	A	11/1998	Stilling	6,501,965	B1	12/2002	Lucidarne
5,852,651	A	12/1998	Fischer et al.	6,504,636	B1	1/2003	Seto et al.
5,854,986	A	12/1998	Dorren et al.	6,512,478	B1	1/2003	Chien
5,867,485	A	2/1999	Chambers et al.	6,519,395	B1	2/2003	Bevan et al.
				6,523,177	B1	2/2003	Brown
				6,525,855	B1	2/2003	Westbrook et al.
				6,526,264	B2	2/2003	Sugar et al.
				6,549,772	B1	4/2003	Chavez et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,556,551	B1	4/2003	Schwartz	7,013,087	B2	3/2006	Suzuki et al.
6,560,441	B1	5/2003	Sabat, Jr. et al.	7,015,826	B1	3/2006	Chan et al.
6,577,794	B1	6/2003	Currie et al.	7,016,308	B1	3/2006	Gallagher
6,577,801	B2	6/2003	Broderick et al.	7,020,451	B2	3/2006	Sugar et al.
6,580,402	B2	6/2003	Navarro et al.	7,020,473	B2	3/2006	Splett
6,580,905	B1	6/2003	Naidu et al.	7,024,166	B2	4/2006	Wallace et al.
6,580,918	B1	6/2003	Leickel et al.	7,035,512	B2	4/2006	Van Bijsterveld
6,583,763	B2	6/2003	Judd	7,039,399	B2	5/2006	Fischer
6,594,496	B2	7/2003	Schwartz	7,047,028	B2	5/2006	Cagenius
6,597,325	B2	7/2003	Judd et al.	7,050,017	B2	5/2006	King et al.
6,606,430	B2	8/2003	Bartur et al.	7,053,838	B2	5/2006	Judd
6,615,074	B2	9/2003	Mickle et al.	7,054,513	B2	5/2006	Herz et al.
6,634,811	B1	10/2003	Gertel et al.	7,072,586	B2	7/2006	Aburakawa et al.
6,636,747	B2	10/2003	Harada et al.	7,082,320	B2	7/2006	Kattukaran et al.
6,640,103	B1	10/2003	Inman et al.	7,084,769	B2	8/2006	Bauer et al.
6,643,437	B1	11/2003	Park	7,092,710	B1	8/2006	Stoter et al.
6,652,158	B2	11/2003	Bartur et al.	7,093,985	B2	8/2006	Lord et al.
6,654,616	B1	11/2003	Pope, Jr. et al.	7,103,312	B2	9/2006	Judd et al.
6,657,535	B1	12/2003	Magbie et al.	7,106,931	B2	9/2006	Sutehall et al.
6,658,269	B1	12/2003	Golemon et al.	7,114,859	B1	10/2006	Tuohimaa et al.
6,670,930	B2	12/2003	Navarro	7,127,175	B2	10/2006	Mani et al.
6,675,294	B1	1/2004	Gupta et al.	7,127,176	B2	10/2006	Sasaki
6,687,437	B1	2/2004	Starnes et al.	7,133,697	B2	11/2006	Judd et al.
6,690,328	B2	2/2004	Judd	7,142,503	B1	11/2006	Grant et al.
6,697,603	B1	2/2004	Lovinggood et al.	7,142,535	B2	11/2006	Kubler et al.
6,704,298	B1	3/2004	Matsumiya et al.	7,160,032	B2	1/2007	Nagashima et al.
6,704,545	B1	3/2004	Wala	7,181,206	B2	2/2007	Pedersen
6,704,579	B2	3/2004	Woodhead et al.	7,199,443	B2	4/2007	Elsharawy
6,710,366	B1	3/2004	Lee et al.	7,200,305	B2	4/2007	Dion et al.
6,731,880	B2	5/2004	Westbrook et al.	7,200,391	B2	4/2007	Chung et al.
6,758,913	B1	7/2004	Tunney et al.	7,228,072	B2	6/2007	Mickelsson et al.
6,763,226	B1	7/2004	McZeal, Jr.	7,245,603	B1	7/2007	Lucidarme et al.
6,771,862	B2	8/2004	Karnik et al.	7,257,328	B2	8/2007	Levinson et al.
6,771,933	B1	8/2004	Eng et al.	7,263,293	B2	8/2007	Ommodt et al.
6,784,802	B1	8/2004	Stanescu	7,269,311	B2	9/2007	Kim et al.
6,785,558	B1	8/2004	Stratford et al.	7,286,843	B2	10/2007	Scheck
6,788,666	B1	9/2004	Linebarger et al.	7,286,854	B2	10/2007	Ferrato et al.
6,801,767	B1	10/2004	Schwartz et al.	7,295,119	B2	11/2007	Rappaport et al.
6,807,374	B1	10/2004	Imajo et al.	7,310,430	B1	12/2007	Mallya et al.
6,812,824	B1	11/2004	Goldinger et al.	7,313,415	B2	12/2007	Wake et al.
6,812,905	B2	11/2004	Thomas et al.	7,315,735	B2	1/2008	Graham
6,826,164	B2	11/2004	Mani et al.	7,324,730	B2	1/2008	Varkey et al.
6,826,165	B1	11/2004	Meier et al.	7,343,164	B2	3/2008	Kallstenius
6,826,337	B2	11/2004	Linnell	7,349,633	B2	3/2008	Lee et al.
6,831,901	B2	12/2004	Millar	7,359,408	B2	4/2008	Kim
6,842,433	B2	1/2005	West et al.	7,359,674	B2	4/2008	Markki et al.
6,847,856	B1	1/2005	Bohannon	7,366,150	B2	4/2008	Lee et al.
6,850,510	B2	2/2005	Kubler et al.	7,366,151	B2	4/2008	Kubler et al.
6,865,390	B2	3/2005	Goss et al.	7,369,526	B2	5/2008	Lechleider et al.
6,873,823	B2	3/2005	Hasarchi et al.	7,379,669	B2	5/2008	Kim
6,876,056	B2	4/2005	Tilmans et al.	7,392,029	B2	6/2008	Pronkine
6,876,852	B1	4/2005	Li et al.	7,394,883	B2	7/2008	Funakubo et al.
6,879,290	B1	4/2005	Toutain et al.	7,403,156	B2	7/2008	Coppi et al.
6,882,833	B2	4/2005	Nguyen	7,409,159	B2	8/2008	Izadpanah
6,883,710	B2	4/2005	Chung	7,412,224	B2	8/2008	Kotola et al.
6,885,846	B1	4/2005	Panasik et al.	7,424,228	B1	9/2008	Williams et al.
6,889,060	B2	5/2005	Fernando et al.	7,444,051	B2	10/2008	Tatat et al.
6,895,253	B1	5/2005	Carloni et al.	7,450,853	B2	11/2008	Kim et al.
6,909,399	B1	6/2005	Zegelin et al.	7,450,854	B2	11/2008	Lee et al.
6,915,058	B2	7/2005	Pons	7,451,365	B2	11/2008	Wang et al.
6,919,858	B2	7/2005	Rofougaran	7,457,646	B2	11/2008	Mahany et al.
6,920,330	B2	7/2005	Caronni et al.	7,460,507	B2	12/2008	Kubler et al.
6,924,997	B2	8/2005	Chen et al.	7,460,829	B2	12/2008	Utsumi et al.
6,930,987	B1	8/2005	Fukuda et al.	7,460,831	B2	12/2008	Hasarchi
6,931,183	B2	8/2005	Panak et al.	7,466,925	B2	12/2008	Iannelli
6,933,849	B2	8/2005	Sawyer	7,469,105	B2	12/2008	Wake et al.
6,961,312	B2	11/2005	Kubler et al.	7,477,597	B2	1/2009	Segel
6,963,289	B2	11/2005	Aljadeff et al.	7,483,504	B2	1/2009	Shapira et al.
6,963,552	B2	11/2005	Sabat, Jr. et al.	7,496,070	B2	2/2009	Vesuna
6,965,718	B2	11/2005	Koertel	7,496,384	B2	2/2009	Seto et al.
6,968,107	B2	11/2005	Belardi et al.	7,522,552	B2	4/2009	Fein et al.
6,970,652	B2	11/2005	Zhang et al.	7,542,452	B2	6/2009	Penumetsa
6,973,243	B2	12/2005	Koyasu et al.	7,548,695	B2	6/2009	Wake
6,974,262	B1	12/2005	Rickenbach	7,551,641	B2	6/2009	Pirzada et al.
7,006,465	B2	2/2006	Toshimitsu et al.	7,552,246	B2	6/2009	Mahany et al.
				7,557,758	B2	7/2009	Rofougaran
				7,580,384	B2	8/2009	Kubler et al.
				7,586,861	B2	9/2009	Kubler et al.
				7,590,354	B2	9/2009	Sauer et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,599,420 B2	10/2009	Forenza et al.	8,737,454 B2	5/2014	Wala et al.
7,606,594 B2	10/2009	Jesse et al.	8,743,718 B2	6/2014	Grenier et al.
7,627,250 B2	12/2009	George et al.	8,743,756 B2	6/2014	Uyehara et al.
7,630,690 B2	12/2009	Kaewell, Jr. et al.	8,837,659 B2	9/2014	Uyehara et al.
7,633,934 B2	12/2009	Kubler et al.	8,837,940 B2	9/2014	Smith et al.
7,646,743 B2	1/2010	Kubler et al.	8,929,288 B2	1/2015	Stewart et al.
7,646,777 B2	1/2010	Hicks, III et al.	9,042,732 B2*	5/2015	Cune et al. 398/96
7,653,397 B2	1/2010	Pernu et al.	2001/0036163 A1	11/2001	Sabat, Jr. et al.
7,668,153 B2	2/2010	Zavadsky	2001/0053011 A1	12/2001	Imajo
7,668,565 B2	2/2010	Ylänen et al.	2002/0003645 A1	1/2002	Kim et al.
7,684,709 B2	3/2010	Ray et al.	2002/0012336 A1	1/2002	Hughes et al.
7,688,811 B2	3/2010	Kubler et al.	2002/0012495 A1	1/2002	Sasai et al.
7,693,486 B2	4/2010	Kasslin et al.	2002/0031113 A1	3/2002	Dodds et al.
7,697,467 B2	4/2010	Kubler et al.	2002/0048071 A1	4/2002	Suzuki et al.
7,715,375 B2	5/2010	Kubler et al.	2002/0055371 A1	5/2002	Arnon et al.
7,715,466 B1	5/2010	Oh et al.	2002/0075906 A1	6/2002	Cole et al.
7,751,374 B2	7/2010	Donovan	2002/0090915 A1	7/2002	Komara et al.
7,751,838 B2	7/2010	Ramesh et al.	2002/0092347 A1	7/2002	Niekerk et al.
7,760,703 B2	7/2010	Kubler et al.	2002/0111149 A1	8/2002	Shoki
7,761,093 B2	7/2010	Sabat, Jr. et al.	2002/0111192 A1	8/2002	Thomas et al.
7,764,978 B1	7/2010	West	2002/0114038 A1	8/2002	Arnon et al.
7,768,951 B2	8/2010	Kubler et al.	2002/0123365 A1	9/2002	Thorson et al.
7,773,573 B2	8/2010	Chung et al.	2002/0126967 A1	9/2002	Panak et al.
7,778,603 B2	8/2010	Palin et al.	2002/0130778 A1	9/2002	Nicholson
7,783,263 B2	8/2010	Sperlich et al.	2002/0181668 A1	12/2002	Masoian et al.
7,809,012 B2	10/2010	Ruuska et al.	2002/0190845 A1	12/2002	Moore
7,817,958 B2	10/2010	Scheinert et al.	2003/0007214 A1	1/2003	Aburakawa et al.
7,817,969 B2	10/2010	Castaneda et al.	2003/0016418 A1	1/2003	Westbrook et al.
7,835,328 B2	11/2010	Stephens et al.	2003/0045284 A1	3/2003	Copley et al.
7,844,273 B2	11/2010	Scheinert	2003/0078052 A1	4/2003	Atias et al.
7,848,316 B2	12/2010	Kubler et al.	2003/0078074 A1	4/2003	Sesay et al.
7,848,731 B1	12/2010	Dianda et al.	2003/0141962 A1	7/2003	Barink
7,853,234 B2	12/2010	Afsahi	2003/0161637 A1	8/2003	Yamamoto et al.
7,870,321 B2	1/2011	Rofougaran	2003/0165287 A1	9/2003	Krill et al.
7,881,755 B1	2/2011	Mishra et al.	2003/0174099 A1	9/2003	Bauer et al.
7,894,423 B2	2/2011	Kubler et al.	2003/0209601 A1	11/2003	Chung
7,899,007 B2	3/2011	Kubler et al.	2004/0001719 A1	1/2004	Sasaki
7,907,972 B2	3/2011	Walton et al.	2004/0008114 A1	1/2004	Sawyer
7,912,043 B2	3/2011	Kubler et al.	2004/0017785 A1	1/2004	Zelst
7,916,706 B2	3/2011	Kubler et al.	2004/0037300 A1	2/2004	Lehr et al.
7,917,145 B2	3/2011	Mahany et al.	2004/0041714 A1	3/2004	Forster
7,920,553 B2	4/2011	Kubler et al.	2004/0043764 A1	3/2004	Bigham et al.
7,920,858 B2	4/2011	Sabat, Jr. et al.	2004/0047313 A1	3/2004	Rumpf et al.
7,924,783 B1	4/2011	Mahany et al.	2004/0078151 A1	4/2004	Aljadeff et al.
7,929,940 B1	4/2011	Dianda et al.	2004/0100930 A1	5/2004	Shapira et al.
7,936,713 B2	5/2011	Kubler et al.	2004/0106435 A1	6/2004	Bauman et al.
7,949,364 B2	5/2011	Kasslin et al.	2004/0110469 A1	6/2004	Judd et al.
7,957,777 B1	6/2011	Vu et al.	2004/0126068 A1	7/2004	Van Bijsterveld
7,962,042 B2	6/2011	Deas	2004/0146020 A1	7/2004	Kubler et al.
7,962,176 B2	6/2011	Li et al.	2004/0149736 A1	8/2004	Clothier
7,969,009 B2	6/2011	Chandrasekaran	2004/0151164 A1	8/2004	Kubler et al.
7,969,911 B2	6/2011	Mahany et al.	2004/0151503 A1	8/2004	Kashima et al.
7,990,925 B2	8/2011	Tinnakornsisuphap et al.	2004/0157623 A1	8/2004	Splett
7,996,020 B1	8/2011	Chhabra	2004/0160912 A1	8/2004	Kubler et al.
8,005,152 B2	8/2011	Wegener	2004/0160913 A1	8/2004	Kubler et al.
8,010,116 B2	8/2011	Scheinert	2004/0162115 A1	8/2004	Smith et al.
8,018,907 B2	9/2011	Kubler et al.	2004/0162116 A1	8/2004	Han et al.
8,036,308 B2	10/2011	Rofougaran	2004/0165573 A1	8/2004	Kubler et al.
8,082,353 B2	12/2011	Huber et al.	2004/0175173 A1	9/2004	Deas
8,086,192 B2	12/2011	Rofougaran et al.	2004/0198451 A1	10/2004	Varghese
8,135,102 B2	3/2012	Wiwel et al.	2004/0202257 A1	10/2004	Mehta et al.
8,155,525 B2	4/2012	Cox	2004/0203704 A1	10/2004	Ommodt et al.
8,213,401 B2	7/2012	Fischer et al.	2004/0203846 A1	10/2004	Caronni et al.
8,270,387 B2	9/2012	Cannon et al.	2004/0204109 A1	10/2004	Hoppenstein
8,290,483 B2	10/2012	Sabat, Jr. et al.	2004/0208526 A1	10/2004	Mibu
8,306,563 B2	11/2012	Zavadsky et al.	2004/0218873 A1	11/2004	Nagashima et al.
8,346,278 B2	1/2013	Wala et al.	2004/0230846 A1	11/2004	Mancey et al.
8,428,510 B2	4/2013	Stratford et al.	2004/0233877 A1	11/2004	Lee et al.
8,462,683 B2	6/2013	Uyehara et al.	2004/0258105 A1	12/2004	Spathas et al.
8,472,579 B2	6/2013	Uyehara et al.	2005/0052287 A1	3/2005	Whitesmith et al.
8,509,215 B2	8/2013	Stuart	2005/0058451 A1	3/2005	Ross
8,509,850 B2	8/2013	Zavadsky et al.	2005/0068179 A1	3/2005	Roesner
8,526,970 B2	9/2013	Wala et al.	2005/0076982 A1	4/2005	Metcalfe et al.
8,532,242 B2	9/2013	Fischer et al.	2005/0078006 A1	4/2005	Hutchins et al.
8,626,245 B2	1/2014	Zavadsky et al.	2005/0093679 A1	5/2005	Zai et al.
			2005/0099343 A1	5/2005	Asrani et al.
			2005/0116821 A1	6/2005	Wilsey et al.
			2005/0141545 A1	6/2005	Fein et al.
			2005/0143077 A1	6/2005	Charbonneau

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0147071	A1	7/2005	Karaoguz et al.	2008/0194226	A1	8/2008	Rivas et al.
2005/0148306	A1	7/2005	Hiddink	2008/0207253	A1	8/2008	Jaakkola et al.
2005/0159108	A1	7/2005	Fletcher et al.	2008/0212969	A1	9/2008	Fasshauer et al.
2005/0174236	A1	8/2005	Brookner	2008/0219670	A1	9/2008	Kim et al.
2005/0201761	A1	9/2005	Bartur et al.	2008/0232799	A1	9/2008	Kim
2005/0219050	A1	10/2005	Martin	2008/0247716	A1	10/2008	Thomas et al.
2005/0224585	A1	10/2005	Durrant et al.	2008/0253351	A1	10/2008	Pernu et al.
2005/0226625	A1*	10/2005	Wake et al. 398/115	2008/0253773	A1	10/2008	Zheng
2005/0232636	A1	10/2005	Durrant et al.	2008/0260388	A1	10/2008	Kim et al.
2005/0242188	A1	11/2005	Vesuna	2008/0261656	A1	10/2008	Bella et al.
2005/0252971	A1	11/2005	Howarth et al.	2008/0268833	A1	10/2008	Huang et al.
2005/0266797	A1	12/2005	Utsumi et al.	2008/0273844	A1	11/2008	Kewitsch
2005/0266854	A1	12/2005	Niiho et al.	2008/0279137	A1	11/2008	Pernu et al.
2005/0269930	A1	12/2005	Shimizu et al.	2008/0280569	A1	11/2008	Hazani et al.
2005/0271396	A1	12/2005	Iannelli	2008/0291830	A1	11/2008	Pernu et al.
2006/0002326	A1	1/2006	Vesuna	2008/0292322	A1	11/2008	Daghighian et al.
2006/0014548	A1	1/2006	Bolin et al.	2008/0298813	A1	12/2008	Song et al.
2006/0017633	A1	1/2006	Pronkine	2008/0304831	A1	12/2008	Miller, II et al.
2006/0045054	A1	3/2006	Utsumi et al.	2008/0310848	A1	12/2008	Yasuda et al.
2006/0053324	A1	3/2006	Giat et al.	2008/0311944	A1	12/2008	Hansen et al.
2006/0062579	A1	3/2006	Kim et al.	2009/0022304	A1	1/2009	Kubler et al.
2006/0079290	A1	4/2006	Seto et al.	2009/0028087	A1	1/2009	Nguyen et al.
2006/0094470	A1	5/2006	Wake et al.	2009/0028317	A1	1/2009	Ling et al.
2006/0104643	A1	5/2006	Lee et al.	2009/0041413	A1	2/2009	Hurley
2006/0159388	A1	7/2006	Kawase et al.	2009/0047023	A1	2/2009	Pescod et al.
2006/0182446	A1	8/2006	Kim et al.	2009/0059903	A1	3/2009	Kubler et al.
2006/0182449	A1	8/2006	Iannelli et al.	2009/0061796	A1	3/2009	Arkko et al.
2006/0189354	A1	8/2006	Lee et al.	2009/0061939	A1	3/2009	Andersson et al.
2006/0233506	A1	10/2006	Noonan et al.	2009/0073916	A1	3/2009	Zhang et al.
2006/0239630	A1	10/2006	Hase et al.	2009/0081985	A1	3/2009	Rofougaran et al.
2006/0274704	A1	12/2006	Desai et al.	2009/0086693	A1	4/2009	Kennedy
2007/0008939	A1	1/2007	Fischer	2009/0087181	A1*	4/2009	Gray 398/58
2007/0009266	A1	1/2007	Bothwell et al.	2009/0088072	A1	4/2009	Rofougaran et al.
2007/0058978	A1	3/2007	Lee et al.	2009/0092394	A1*	4/2009	Wei et al. 398/79
2007/0060045	A1	3/2007	Prautzsch	2009/0097855	A1	4/2009	Thelen et al.
2007/0060055	A1	3/2007	Desai et al.	2009/0135078	A1	5/2009	Lindmark et al.
2007/0071128	A1	3/2007	Meir et al.	2009/0149221	A1	6/2009	Liu et al.
2007/0076649	A1	4/2007	Lin et al.	2009/0154621	A1	6/2009	Shapira et al.
2007/0093273	A1	4/2007	Cai	2009/0169163	A1	7/2009	Abbott, III et al.
2007/0149250	A1	6/2007	Crozzoli et al.	2009/0175214	A1	7/2009	Sfar et al.
2007/0166042	A1	7/2007	Seeds et al.	2009/0218407	A1	9/2009	Rofougaran
2007/0208961	A1	9/2007	Ghoshal et al.	2009/0218657	A1	9/2009	Rofougaran
2007/0224954	A1	9/2007	Gopi	2009/0245084	A1	10/2009	Moffatt et al.
2007/0248358	A1	10/2007	Sauer	2009/0245153	A1	10/2009	Li et al.
2007/0253714	A1	11/2007	Seeds et al.	2009/0245221	A1	10/2009	Piipponen
2007/0257796	A1	11/2007	Easton et al.	2009/0252136	A1	10/2009	Mahany et al.
2007/0264009	A1	11/2007	Sabat, Jr. et al.	2009/0252204	A1	10/2009	Shatara et al.
2007/0274279	A1	11/2007	Wood et al.	2009/0252205	A1	10/2009	Rheinfelder et al.
2007/0286599	A1	12/2007	Sauer et al.	2009/0258652	A1	10/2009	Lambert et al.
2007/0297005	A1	12/2007	Montierth et al.	2009/0285147	A1	11/2009	Subasic et al.
2008/0007453	A1	1/2008	Vassilakis et al.	2009/0290632	A1	11/2009	Wegener
2008/0013909	A1	1/2008	Kostet et al.	2010/0002626	A1	1/2010	Schmidt et al.
2008/0013956	A1	1/2008	Ware et al.	2010/0002661	A1	1/2010	Schmidt et al.
2008/0013957	A1	1/2008	Akers et al.	2010/0027443	A1	2/2010	LoGalbo et al.
2008/0014948	A1	1/2008	Scheinert	2010/0054227	A1	3/2010	Hettstedt et al.
2008/0026765	A1	1/2008	Charbonneau	2010/0056200	A1	3/2010	Tolonen
2008/0031628	A1	2/2008	Dragas et al.	2010/0080154	A1	4/2010	Noh et al.
2008/0043714	A1	2/2008	Pernu	2010/0080182	A1	4/2010	Kubler et al.
2008/0056167	A1	3/2008	Kim et al.	2010/0087227	A1	4/2010	Francois et al.
2008/0058018	A1	3/2008	Scheinert	2010/0091475	A1	4/2010	Toms et al.
2008/0063387	A1	3/2008	Yahata et al.	2010/0118864	A1	5/2010	Kubler et al.
2008/0080863	A1	4/2008	Sauer et al.	2010/0127937	A1	5/2010	Chandrasekaran et al.
2008/0098203	A1	4/2008	Master et al.	2010/0134257	A1	6/2010	Puleston et al.
2008/0118014	A1	5/2008	Reunamaki et al.	2010/0144337	A1	6/2010	Dean
2008/0119198	A1	5/2008	Hettstedt et al.	2010/0148373	A1	6/2010	Chandrasekaran
2008/0124086	A1	5/2008	Matthews	2010/0156721	A1	6/2010	Alamouti et al.
2008/0124087	A1	5/2008	Hartmann et al.	2010/0177759	A1	7/2010	Fischer et al.
2008/0129634	A1	6/2008	Pera et al.	2010/0177760	A1	7/2010	Cannon et al.
2008/0134194	A1	6/2008	Liu	2010/0188998	A1	7/2010	Pernu et al.
2008/0145061	A1	6/2008	Lee et al.	2010/0189439	A1	7/2010	Novak et al.
2008/0150514	A1	6/2008	Codreanu et al.	2010/0190509	A1	7/2010	Davis
2008/0159226	A1	7/2008	He et al.	2010/0202326	A1	8/2010	Rofougaran et al.
2008/0159744	A1	7/2008	Soto et al.	2010/0202356	A1	8/2010	Fischer et al.
2008/0166094	A1	7/2008	Bookbinder et al.	2010/0208777	A1	8/2010	Ogaz
2008/0181282	A1	7/2008	Wala et al.	2010/0215028	A1	8/2010	Fischer
				2010/0225413	A1	9/2010	Rofougaran et al.
				2010/0225556	A1	9/2010	Rofougaran et al.
				2010/0225557	A1	9/2010	Rofougaran et al.
				2010/0232323	A1	9/2010	Kubler et al.

(56)

References Cited

FOREIGN PATENT DOCUMENTS

U.S. PATENT DOCUMENTS			FOREIGN PATENT DOCUMENTS		
			CA	2065090	C 2/1998
			CA	2242707	C 9/2002
			CN	1745560	A 3/2006
2010/0246558	A1	9/2010 Harel	CN	101151811	A 3/2008
2010/0255774	A1	10/2010 Kenington	CN	101496306	A 7/2009
2010/0258949	A1	10/2010 Henderson et al.	CN	101542928	A 9/2009
2010/0260063	A1	10/2010 Kubler et al.	DE	19705253	A1 8/1998
2010/0278530	A1	11/2010 Kummetz et al.	DE	20104862	U1 9/2001
2010/0290355	A1	11/2010 Roy et al.	DE	10249414	A1 5/2004
2010/0290787	A1	11/2010 Cox	EP	0391597	A2 10/1990
2010/0291949	A1	11/2010 Shapira et al.	EP	0461583	A1 12/1991
2010/0296458	A1	11/2010 Wala et al.	EP	0477952	A2 4/1992
2010/0296816	A1	11/2010 Larsen	EP	0477952	A3 4/1992
2010/0309049	A1	12/2010 Reunamäki et al.	EP	0714218	A1 5/1996
2010/0311472	A1	12/2010 Rofougaran et al.	EP	0687400	B1 11/1998
2010/0311480	A1	12/2010 Raines et al.	EP	0993124	A2 4/2000
2010/0329161	A1	12/2010 Ylanen et al.	EP	1056226	A2 11/2000
2010/0329166	A1	12/2010 Mahany et al.	EP	1173034	A1 1/2002
2011/0007724	A1	1/2011 Mahany et al.	EP	1202475	A2 5/2002
2011/0007733	A1	1/2011 Kubler et al.	EP	1227605	A2 7/2002
2011/0008042	A1	1/2011 Stewart	EP	1267447	A1 12/2002
2011/0021146	A1	1/2011 Pernu	EP	1347584	A2 9/2003
2011/0021224	A1	1/2011 Koskinen et al.	EP	1363352	A1 11/2003
2011/0045767	A1	2/2011 Rofougaran et al.	EP	1391897	A1 2/2004
2011/0055875	A1	3/2011 Zussman	EP	1443687	A1 8/2004
2011/0065450	A1	3/2011 Kazmi	EP	1455550	A2 9/2004
2011/0069668	A1	3/2011 Chion et al.	EP	1501206	A1 1/2005
2011/0071734	A1	3/2011 Van Wiemeersch et al.	EP	1503451	A1 2/2005
2011/0086614	A1	4/2011 Brisebois et al.	EP	1511203	A1 3/2005
2011/0116393	A1	5/2011 Hong et al.	EP	1530316	A1 5/2005
2011/0116572	A1	5/2011 Lee et al.	EP	1267447	B1 8/2006
2011/0126071	A1	5/2011 Han et al.	EP	1693974	A1 8/2006
2011/0141895	A1	6/2011 Zhang	EP	1742388	A1 1/2007
2011/0149879	A1	6/2011 Noriega et al.	EP	1173034	B1 7/2007
2011/0158298	A1	6/2011 Djadi et al.	EP	1954019	A1 8/2008
2011/0170577	A1	7/2011 Anvari	EP	1968250	A1 9/2008
2011/0170619	A1	7/2011 Anvari	EP	1357683	B1 5/2009
2011/0182230	A1	7/2011 Ohm et al.	EP	2110955	A1 10/2009
2011/0182255	A1	7/2011 Kim et al.	EP	2253980	A1 11/2010
2011/0194475	A1	8/2011 Kim et al.	EP	1570626	B1 11/2013
2011/0201368	A1	8/2011 Faccin et al.	GB	2323252	A 9/1998
2011/0204504	A1	8/2011 Henderson et al.	GB	2366131	A 2/2002
2011/0211439	A1	9/2011 Manpuria et al.	GB	2370170	A 6/2002
2011/0215901	A1	9/2011 Van Wiemeersch et al.	GB	2399963	A 9/2004
2011/0222415	A1	9/2011 Ramamurthi et al.	GB	2428149	A 1/2007
2011/0222434	A1	9/2011 Chen	JP	05260018	A 10/1993
2011/0222619	A1	9/2011 Ramamurthi et al.	JP	08181661	A 7/1996
2011/0223958	A1	9/2011 Chen et al.	JP	09083450	A 3/1997
2011/0223959	A1	9/2011 Chen	JP	09162810	A 6/1997
2011/0223960	A1	9/2011 Chen et al.	JP	09200840	A 7/1997
2011/0223961	A1	9/2011 Chen et al.	JP	11068675	A 3/1999
2011/0227795	A1	9/2011 Lopez et al.	JP	11088265	A 3/1999
2011/0236024	A1	9/2011 Mao	JP	2000152300	A 5/2000
2011/0237178	A1	9/2011 Seki et al.	JP	2000341744	A 12/2000
2011/0241881	A1	10/2011 Badinelli	JP	2002264617	A 9/2002
2011/0243201	A1	10/2011 Phillips et al.	JP	2003148653	A 5/2003
2011/0244887	A1	10/2011 Dupray et al.	JP	2003172827	A 6/2003
2011/0256878	A1	10/2011 Zhu et al.	JP	2004172734	A 6/2004
2011/0268033	A1	11/2011 Boldi et al.	JP	2004245963	A 9/2004
2011/0268452	A1	11/2011 Beamon et al.	JP	2004247090	A 9/2004
2011/0274021	A1	11/2011 He et al.	JP	2004264901	A 9/2004
2011/0281536	A1	11/2011 Lee et al.	JP	2004265624	A 9/2004
2013/0012195	A1	1/2013 Sabat, Jr. et al.	JP	2004317737	A 11/2004
2013/0150063	A1	6/2013 Berlin et al.	JP	2004349184	A 12/2004
2013/0188959	A1	7/2013 Cune et al.	JP	2005018175	A 1/2005
2013/0210490	A1	8/2013 Fischer et al.	JP	2005087135	A 4/2005
2013/0330086	A1	12/2013 Berlin et al.	JP	2005134125	A 5/2005
2014/0016583	A1	1/2014 Smith	JP	2007228603	A 9/2007
2014/0140225	A1	5/2014 Wala	JP	2008172597	A 7/2008
2014/0146797	A1	5/2014 Zavadsky et al.	KR	20040053467	A 6/2004
2014/0146905	A1	5/2014 Zavadsky et al.	WO	9603823	A1 2/1996
2014/0146906	A1	5/2014 Zavadsky et al.	WO	9935788	A2 7/1999
2014/0219140	A1	8/2014 Uyehara et al.	WO	0042721	A1 7/2000
			WO	0178434	A1 10/2001
			WO	0184760	A1 11/2001
			WO	0221183	A1 3/2002
			WO	0230141	A1 4/2002

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	02102102	A1	12/2002
WO	03024027	A1	3/2003
WO	03098175	A1	11/2003
WO	2004030154	A2	4/2004
WO	2004047472	A1	6/2004
WO	2004056019	A1	7/2004
WO	2004059934	A1	7/2004
WO	2004086795	A2	10/2004
WO	2004093471	A2	10/2004
WO	2005062505	A1	7/2005
WO	2005069203	A2	7/2005
WO	2005069203	A3	7/2005
WO	2005073897	A1	8/2005
WO	2005079386	A2	9/2005
WO	2005101701	A2	10/2005
WO	2005111959	A2	11/2005
WO	2005117337	A1	12/2005
WO	2006011778	A1	2/2006
WO	2006018592	A1	2/2006
WO	2006019392	A1	2/2006
WO	2006039941	A1	4/2006
WO	2006046088	A1	5/2006
WO	2006051262	A1	5/2006
WO	2006077569	A1	7/2006
WO	2006133609	A1	12/2006
WO	2006136811	A1	12/2006
WO	2007048427	A1	5/2007
WO	2007077451	A1	7/2007
WO	2007088561	A1	8/2007
WO	2007091026	A1	8/2007
WO	2008008249	A2	1/2008
WO	2008027213	A2	3/2008
WO	2008033298	A2	3/2008
WO	2008039830	A2	4/2008
WO	2009014710	A1	1/2009
WO	2009145789	A1	12/2009
WO	2010090999	A1	8/2010
WO	2011139937	A1	11/2011
WO	2011139939	A1	11/2011
WO	2011139942	A1	11/2011
WO	2012051227	A1	4/2012
WO	2012051230	A1	4/2012
WO	2013122915	A1	8/2013

OTHER PUBLICATIONS

International Search Report for PCT/US2011/034725 mailed Aug. 5, 2011, 4 pages.

Non-final Office Action for U.S. Appl. No. 12/892,424 mailed Nov. 5, 2012, 22 pages.

International Search Report and Written Opinion for PCT/US2011/034738 mailed Jul. 27, 2011, 13 pages.

International Search Report for PCT/US2011/047821 mailed Oct. 25, 2011, 4 pages.

International Preliminary Report on Patentability for PCT/US2011/047821 mailed Feb. 19, 2013, 10 pages.

Non-final Office Action for U.S. Appl. No. 13/025,719 mailed Sep. 11, 2013, 18 pages.

Parker et al., "Radio-over-fibre technologies arising from the Building the future Optical Network in Europe (BONE) project," IET Optoelectron., 2010, vol. 4, Issue 6, pp. 247-259.

Singh et al., "Distributed coordination with deaf neighbors: efficient medium access for 60 GHz mesh networks," IEEE INFOCOM 2010 proceedings, 9 pages.

Examination Report for European patent application 11754570.7 mailed Nov. 18, 2013, 7 pages.

Final Office Action for U.S. Appl. No. 13/025,719 mailed Dec. 31, 2013, 20 pages.

Advisory Action for U.S. Appl. No. 13/025,719 mailed Mar. 14, 2014, 6 pages.

Non-final Office Action for U.S. Appl. No. 13/785,603 mailed Dec. 23, 2013, 15 pages.

Final Office Action for U.S. Appl. No. 13/785,603 mailed Apr. 14, 2014, 17 pages.

Advisory Action for U.S. Appl. No. 13/785,603 mailed Jun. 30, 2014, 3 pages.

Non-final Office Action for U.S. Appl. No. 13/785,603 mailed Sep. 9, 2014, 10 pages.

Final Office Action for U.S. Appl. No. 13/785,603 mailed Dec. 4, 2014, 8 pages.

Non-final Office Action for U.S. Appl. No. 13/762,432 mailed Aug. 20, 2014, 4 pages.

Notice of Allowance for U.S. Appl. No. 13/762,432 mailed Dec. 24, 2014, 7 pages.

Chowdhury et al., "Multi-service Multi-carrier Broadband MIMO Distributed Antenna Systems for In-building Optical Wireless Access," Presented at the 2010 Conference on Optical Fiber Communication and National Fiber Optic Engineers Conference, Mar. 21-25, 2010, San Diego, California, IEEE, pp. 1-3.

International Search Report for PCT/US2011/055861 mailed Feb. 7, 2012, 4 pages.

International Preliminary Report on Patentability for PCT/US2011/055861 mailed Apr. 25, 2013, 9 pages.

International Search Report for PCT/US2011/055858 mailed Feb. 7, 2012, 4 pages.

International Preliminary Report on Patentability for PCT/US2011/055858 mailed Apr. 25, 2013, 8 pages.

International Search Report for PCT/US2011/034733 mailed Aug. 1, 2011, 5 pages.

International Preliminary Report on Patentability for PCT/US2011/034733 mailed Nov. 15, 2012, 8 pages.

First Office Action for Chinese patent application 201180024499.4 mailed Dec. 1, 2014, 13 pages.

Examination Report for European patent application 11754570.7 mailed Jan. 13, 2015, 5 pages.

Final Office Action for U.S. Appl. No. 13/967,426 mailed Apr. 29, 2015, 22 pages.

Cooper, A.J., "Fibre/Radio for the Provision of Cordless/Mobile Telephony Services in the Access Network," Electronics Letters, 1990, pp. 2054-2056, vol. 26, No. 24.

Bakaul, M., et al., "Efficient Multiplexing Scheme for Wavelength-Interleaved DWDM Millimeter-Wave Fiber-Radio Systems," IEEE Photonics Technology Letters, Dec. 2005, vol. 17, No. 12.

Huang, C., et al., "A WLAN-Used Helical Antenna Fully Integrated with the PCMCIA Carrier," IEEE Transactions on Antennas and Propagation, Dec. 2005, vol. 53, No. 12, pp. 4164-4168.

Gibson, B.C., et al., "Evanescence Field Analysis of Air-Silica Microstructure Waveguides," The 14th Annual Meeting of the IEEE Lasers and Electro-Optics Society, Jan. 7803-7104-4/01, Nov. 12-13, 2001, vol. 2, pp. 709-710.

International Search Report for PCT/US07/21041 mailed Mar. 7, 2008, 3 pages.

"ITU-T G.652, Telecommunication Standardization Sector of ITU, Series G: Transmission Systems and Media, Digital Systems and Networks, Transmission Media Characteristics—Optical Fibre Cables, Characteristics of a Single-Mode Optical Fiber and Cable," ITU-T Recommendation G.652, International Telecommunication Union, Jun. 2005, 20 pages.

"ITU-T G.657, Telecommunication Standardization Sector of ITU, Dec. 2006, Series G: Transmission Systems and Media, Digital Systems and Networks, Transmission Media and Optical Systems Characteristics—Optical Fibre Cables, Characteristics of a Bending Loss Insensitive Single Mode Optical Fibre and Cable for the Access Network," ITU-T Recommendation G.657, International Telecommunication Union, 19 pages.

Kojucharow, K., et al., "Millimeter-Wave Signal Properties Resulting from Electrooptical Upconversion," IEEE Transactions on Microwave Theory and Techniques, Oct. 2001, vol. 49, No. 10, pp. 1977-1985.

Monro, T.M., et al., "Holey Fibers with Random Cladding Distributions," Optics Letters, Feb. 15, 2000, vol. 25, No. 4, pp. 206-208.

Moreira, J.D., et al., "Diversity Techniques for OFDM Based WLAN Systems," The 13th IEEE International Symposium on Personal, Indoor and Mobile Radio Communications, Sep. 15-18, 2002, vol. 3, pp. 1008-1011.

(56)

References Cited

OTHER PUBLICATIONS

Niiho, T., et al., "Multi-Channel Wireless LAN Distributed Antenna System Based on Radio-Over-Fiber Techniques," The 17th Annual Meeting of the IEEE Lasers and Electro-Optics Society, Nov. 2004, vol. 1, pp. 57-58.

Paulraj, A.J., et al., "An Overview of MIMO Communications—A Key to Gigabit Wireless," Proceedings of the IEEE, Feb. 2004, vol. 92, No. 2, 34 pages.

Pickrell, G.R., et al., "Novel Techniques for the Fabrication of Hole Optical Fibers," Proceedings of SPIE, Oct. 28-Nov. 2, 2001, vol. 4578, 2002, pp. 271-282.

RFID Technology Overview, 11 pages.

Roh, W., et al., "MIMO Channel Capacity for the Distributed Antenna Systems," Proceedings of the 56th IEEE Vehicular Technology Conference, Sep. 2002, vol. 2, pp. 706-709.

Seto, I., et al., "Antenna-Selective Transmit Diversity Technique for OFDM-Based WLANs with Dual-Band Printed Antennas," 2005 IEEE Wireless Communications and Networking Conference, Mar. 13-17, 2005, vol. 1, pp. 51-56.

Shen, C., et al., "Comparison of Channel Capacity for MIMO-DAS versus MIMO-CAS," The 9th Asia-Pacific Conference on Communications, Sep. 21-24, 2003, vol. 1, pp. 113-118.

Wake, D. et al., "Passive Picocell: A New Concept in Wireless Network Infrastructure," Electronics Letters, Feb. 27, 1997, vol. 33, No. 5, pp. 404-406.

Winters, J., et al., "The Impact of Antenna Diversity on the Capacity of Wireless Communication Systems," IEEE Transactions on Communications, vol. 42, No. 2/3/4, Feb./Mar./Apr. 1994, pp. 1740-1751.

Opatic, D., "Radio over Fiber Technology for Wireless Access," Ericsson, Oct. 17, 2009, 6 pages.

"ADC Has 3rd Generation Services Covered at CeBIT 2001," Business Wire, Mar. 20, 2001, 3 pages.

"Andrew Unveils the InCell Fiber Optic Antenna System for In-Building Wireless Communications," Fiber Optics Weekly Update, Dec. 1, 2000, Information Gatekeepers Inc., pp. 3-4.

Arredondo, Albedo et al., "Techniques for Improving In-Building Radio Coverage Using Fiber-Fed Distributed Antenna Networks," IEEE 46th Vehicular Technology Conference, Atlanta, Georgia, Apr. 28-May 1, 1996, pp. 1540-1543, vol. 3.

Fitzmaurice, M. et al., "Distributed Antenna System for Mass Transit Communications," Vehicular Technology Conference, Boston, Massachusetts, Sep. 2000, IEEE, pp. 2011-2018.

Ghafouri-Shiraz, et al., "Radio on Fibre Communication Systems Based on Integrated Circuit-Antenna Modules," Microwave and Millimeter Wave Technology Proceedings, Beijing, China, Aug. 1998, IEEE, pp. 159-169.

Griffin, R.A. et al., "Radio-Over-Fiber Distribution Using an Optical Millimeter-Wave/DWDM Overlay," Optical Fiber Communication Conference, San Diego, California, Feb. 1999, IEEE, pp. 70-72.

Juntunen, J. et al., "Antenna Diversity Array Design for Mobile Communication Systems," Proceedings of the 2000 IEEE International Conference on Phased Array Systems and Technology, Dana Point, California, May 2000, IEEE, pp. 65-67.

Lee, D. et al., "Ricocheting Bluetooth," 2nd International Conference on Microwave and Millimeter Wave Technology Proceedings, Beijing, China, Sep. 2000, IEEE, pp. 432-435.

Lee, T., "A Digital Multiplexed Fiber Optic Transmission System for Analog Audio Signals," IEEE Western Canada Conference on Computer, Power, and Communications Systems in a Rural Environment, Regina, Saskatchewan, May 1991, pp. 146-149.

Schuh et al., "Hybrid Fibre Radio Access: A Network Operators Approach and Requirements," Proceedings of the 10th Microcoll Conference, Mar. 21-24, 1999, Budapest, Hungary, pp. 211-214.

Schweber, Bill, "Maintaining cellular connectivity indoors demands sophisticated design," EDN Network, Dec. 21, 2000, 2 pages, <http://www.edn.com/design/integrated-circuit-design/4362776/Maintaining-cellular-connectivity-indoors-demands-sophisticated-design>.

Margotte, B. et al., "Fibre Optic Distributed Antenna System for Cellular and PCN/PCS Indoor Coverage," Microwave Engineering Europe, Jun. 1998, 6 pages.

Matsunaka et al., "Point-to-multipoint Digital Local Distribution Radio System in the 21 GHz Band," KDD Technical Journal, Mar. 1991, No. 145, p. 43-54.

Translation of the First Office Action for Chinese patent application 201180039569.3 issued Jan. 16, 2015, 7 pages.

International Search Report for PCT/US2012/025337 mailed May 16, 2012, 4 pages.

Non-final Office Action for U.S. Appl. No. 13/025,719 mailed Mar. 31, 2015, 26 pages.

Non-final Office Action for U.S. Appl. No. 13/967,426 mailed Dec. 26, 2014, 15 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B




FIG. 12




FIG. 13




FIG. 14

1

**PROVIDING DIGITAL DATA SERVICES IN
OPTICAL FIBER-BASED DISTRIBUTED
RADIO FREQUENCY (RF)
COMMUNICATIONS SYSTEMS, AND
RELATED COMPONENTS AND METHODS**

PRIORITY APPLICATION

This application is a continuation of and claims priority to U.S. patent application Ser. No. 13/785,603 filed on Mar. 5, 2013, which is a continuation of and claims priority to U.S. patent application Ser. No. 12/892,424 filed on Sep. 28, 2010, which claims priority to U.S. Provisional Patent Application Ser. No. 61/330,386 filed on May 2, 2010, the contents of which are relied upon and incorporated herein by reference in their entireties.

RELATED APPLICATIONS

The present application is related to U.S. Provisional Patent Application No. 61/330,385 filed on May 2, 2010 entitled, "Power Distribution in Optical Fiber-based Distributed Communications Systems Providing Digital Data and Radio Frequency (RF) Communications Services, and Related Components and Methods," which is incorporated herein by reference in its entirety.

The present application is also related to U.S. Provisional Patent Application No. 61/330,383 filed on May 2, 2010 entitled, "Optical Fiber-based Distributed Communications Systems, and Related Components and Methods," which is incorporated herein by reference in its entirety.

BACKGROUND

1. Field of the Disclosure

The technology of the disclosure relates to optical fiber-based distributed communications systems for distributing radio frequency (RF) signals over optical fiber.

2. Technical Background

Wireless communication is rapidly growing, with ever-increasing demands for high-speed mobile data communication. As an example, so-called "wireless fidelity" or "WiFi" systems and wireless local area networks (WLANs) are being deployed in many different types of areas (e.g., coffee shops, airports, libraries, etc.). Distributed communications systems communicate with wireless devices called "clients," which must reside within the wireless range or "cell coverage area" in order to communicate with an access point device.

One approach to deploying a distributed communications system involves the use of radio frequency (RF) antenna coverage areas, also referred to as "antenna coverage areas." Antenna coverage areas can have a radius in the range from a few meters up to twenty meters as an example. Combining a number of access point devices creates an array of antenna coverage areas. Because the antenna coverage areas each cover small areas, there are typically only a few users (clients) per antenna coverage area. This allows for minimizing the amount of RF bandwidth shared among the wireless system users. It may be desirable to provide antenna coverage areas in a building or other facility to provide distributed communications system access to clients within the building or facility. However, it may be desirable to employ optical fiber to distribute communication signals. Benefits of optical fiber include increased bandwidth.

One type of distributed communications system for creating antenna coverage areas, called "Radio-over-Fiber" or "RoF," utilizes RF signals sent over optical fibers. Such sys-

2

tems can include a head-end station optically coupled to a plurality of remote antenna units that each provides antenna coverage areas. The remote antenna units can each include RF transceivers coupled to an antenna to transmit RF signals wirelessly, wherein the remote antenna units are coupled to the head-end station via optical fiber links. The RF transceivers in the remote antenna units are transparent to the RF signals. The remote antenna units convert incoming optical RF signals from an optical fiber downlink to electrical RF signals via optical-to-electrical (O/E) converters, which are then passed to the RF transceiver. The RF transceiver converts the electrical RF signals to electromagnetic signals via antennas coupled to the RF transceiver provided in the remote antenna units. The antennas also receive electromagnetic signals (i.e., electromagnetic radiation) from clients in the antenna coverage area and convert them to electrical RF signals (i.e., electrical RF signals in wire). The remote antenna units then convert the electrical RF signals to optical RF signals via electrical-to-optical (E/O) converters. The optical RF signals are then sent over an optical fiber uplink to the head-end station.

SUMMARY OF THE DETAILED DESCRIPTION

Embodiments disclosed in the detailed description include optical fiber-based distributed communications systems that provide and support both radio frequency (RF) communication services and digital data services. The RF communication services and digital data services can be distributed over optical fiber to client devices, such as remote antenna units for example. Digital data services can be distributed over optical fiber separate from optical fiber distributing RF communication services. Alternatively, digital data services can be distributed over common optical fiber with RF communication services. For example, digital data services can be distributed over common optical fiber with RF communication services at different wavelengths through wavelength-division multiplexing (WDM) and/or at different frequencies through frequency-division multiplexing (FDM). Power distributed in the optical fiber-based distributed communications system to provide power to remote antenna units can also be accessed to provide power to digital data service components.

In one embodiment, a distributed antenna system for distributing RF communications and digital data services (DDS) to at least one remote antenna unit (RAU) is provided. The distributed antenna system includes a head-end unit (HEU). The HEU is configured to receive at least one downlink electrical RF communications signal. The HEU is also configured to convert the at least one downlink electrical RF communications signal into at least one downlink optical RF communications signal to be communicated over at least one communications downlink to the at least one RAU. The HEU is also configured to receive at least one uplink optical RF communications signal over at least one communications uplink from the at least one RAU. The HEU is also configured to convert the at least one uplink optical RF communications signal into at least one uplink electrical RF communications signal. The distributed antenna system also includes a DDS controller. The DDS controller is configured to receive at least one downlink optical digital signal containing at least one DDS, and provide the at least one downlink optical digital signal over at least one second communications downlink to the at least one RAU.

In another embodiment, a method of distributing RF communications and DDS to at least one RAU in a distributed antenna system is provided. The method includes receiving at an HEU at least one downlink electrical RF communications

3

signal. The method also includes converting the at least one downlink electrical RF communications signal into at least one downlink optical RF communications signal to be communicated over at least one communications downlink to the at least one RAU. The method also includes receiving at the HEU at least one uplink optical RF communications signal over at least one communications uplink from the at least one RAU. The method also includes converting the at least one uplink optical RF communications signal into at least one uplink electrical RF communications signal. The method also includes receiving at a DDS controller at least one downlink optical digital signal containing at least one DDS, and providing the at least one downlink optical digital signal over at least one second communications downlink to the at least one RAU.

In another embodiment, an RAU for use in a distributed antenna system is provided. The RAU includes an optical-to-electrical (O-E) converter configured to convert received downlink optical RF communications signals to downlink electrical RF communications signals and provide the downlink electrical RF communications signals at least one first port. The RAU also includes an electrical-to-optical (E-O) converter configured to convert uplink electrical RF communications signals received from the at least one first port into uplink optical RF communications signals. The RAU also includes a DDS interface coupled to at least one second port. The DDS interface is configured to convert downlink optical digital signals into downlink electrical digital signals to provide to the at least one second port, and convert uplink electrical digital signals received from the at least one second port into uplink optical digital signals.

Additional features and advantages will be set forth in the detailed description which follows, and in part will be readily apparent to those skilled in the art from that description or recognized by practicing the embodiments as described herein, including the detailed description that follows, the claims, as well as the appended drawings.

It is to be understood that both the foregoing general description and the following detailed description present embodiments, and are intended to provide an overview or framework for understanding the nature and character of the disclosure. The accompanying drawings are included to provide a further understanding, and are incorporated into and constitute a part of this specification. The drawings illustrate various embodiments, and together with the description serve to explain the principles and operation of the concepts disclosed.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a schematic diagram of an exemplary optical fiber-based distributed communications system;

FIG. 2 is a more detailed schematic diagram of an exemplary head-end unit (HEU) and a remote antenna unit (RAU) that can be deployed in the optical fiber-based distributed communications system of FIG. 1;

FIG. 3 is a partially schematic cut-away diagram of an exemplary building infrastructure in which the optical fiber-based distributed communications system in FIG. 1 can be employed;

FIG. 4 is a schematic diagram of an exemplary embodiment of providing digital data services over downlink and uplink optical fibers separate from optical fibers providing radio frequency (RF) communication services to RAUs in an optical fiber-based distributed communications system;

FIG. 5 is a diagram of an exemplary head-end media converter (HMC) employed in the optical fiber-based distributed

4

communications system of FIG. 4 containing digital media converters (DMCs) configured to convert electrical digital signals to optical digital signals and vice versa;

FIG. 6 is a diagram of exemplary DMCs employed in the HMC of FIG. 5;

FIG. 7 is a schematic diagram of an exemplary building infrastructure in which digital data services and RF communication services are provided in an optical fiber-based distributed communications system;

FIG. 8 is a schematic diagram of an exemplary RAU that can be employed in an optical fiber-based distributed communications system providing exemplary digital data services and RF communication services;

FIG. 9 is a schematic diagram of another exemplary embodiment of providing digital data services over separate downlink and uplink optical fibers from RF communication services to RAUs in an optical fiber-based distributed communications system;

FIG. 10A is a schematic diagram of an exemplary embodiment of employing wavelength-division multiplexing (WDM) to multiplex digital data services and RF communication services at different wavelengths over downlink and uplink optical fibers in an optical fiber-based distributed communications system;

FIG. 10B is a schematic diagram of an exemplary embodiment of employing WDM to multiplex uplink and downlink communications for each channel over a common optical fiber;

FIG. 11 is a schematic diagram of another exemplary embodiment of employing WDM in a co-located HEU and HMC to multiplex digital data services and RF communication services at different wavelengths over common downlink optical fibers and common uplink optical fibers in an optical fiber-based distributed communications system;

FIG. 12 is a schematic diagram of another exemplary embodiment of employing WDM in a common housing HEU and MC to multiplex digital data services and RF communication services at different wavelengths over a common downlink optical fiber and a common uplink optical fiber in an optical fiber-based distributed communications system;

FIG. 13 is a schematic diagram of another exemplary embodiment of employing frequency-division multiplexing (FDM) to multiplex digital data services and RF communication services at different frequencies over downlink optical fibers and uplink optical fibers in an optical fiber-based distributed communications system; and

FIG. 14 is a schematic diagram of another exemplary embodiment of employing FDM and WDM to multiplex digital data services and RF communication services at different frequencies and at different wavelengths over downlink optical fibers and uplink optical fibers in an optical fiber-based distributed communications system.

DETAILED DESCRIPTION

Reference will now be made in detail to the embodiments, examples of which are illustrated in the accompanying drawings, in which some, but not all embodiments are shown. Indeed, the concepts may be embodied in many different forms and should not be construed as limiting herein; rather, these embodiments are provided so that this disclosure will satisfy applicable legal requirements. Whenever possible, like reference numbers will be used to refer to like components or parts.

Embodiments disclosed in the detailed description include optical fiber-based distributed communications systems that provide and support both radio frequency (RF) communica-

tion services and digital data services. The RF communication services and digital data services can be distributed over optical fiber to client devices, such as remote antenna units for example. For example, non-limiting examples of digital data services include Ethernet, WLAN, Worldwide Interoperability for Microwave Access (WiMax), Wireless Fidelity (WiFi), Digital Subscriber Line (DSL), and Long Term Evolution (LTE), etc. Digital data services can be distributed over optical fiber separate from optical fiber distributing RF communication services. Alternatively, digital data services can be distributed over common optical fiber with RF communication services. For example, digital data services can be distributed over common optical fiber with RF communication services at different wavelengths through wavelength-division multiplexing (WDM) and/or at different frequencies through frequency-division multiplexing (FDM). Power distributed in the optical fiber-based distributed communications system to provide power to remote antenna units can also be accessed to provide power to digital data service components.

In this regard, an exemplary optical fiber-based distributed communications system that provides RF communication services without providing digital data services is described with regard to FIGS. 1-3. Various embodiments of additionally providing digital data services in conjunction with RF communication services in optical fiber-based distributed communications systems starts at FIG. 4.

In this regard, FIG. 1 is a schematic diagram of an embodiment of an optical fiber-based distributed communications system. In this embodiment, the system is an optical fiber-based distributed communications system 10 that is configured to create one or more antenna coverage areas for establishing communications with wireless client devices located in the radio frequency (RF) range of the antenna coverage areas. The optical fiber-based distributed communications system 10 provides RF communications service (e.g., cellular services). In this embodiment, the optical fiber-based distributed communications system 10 includes a head-end unit (HEU) 12, one or more remote antenna units (RAUs) 14, and an optical fiber 16 that optically couples the HEU 12 to the RAU 14. The HEU 12 is configured to receive communications over downlink electrical RF signals 18D from a source or sources, such as a network or carrier as examples, and provide such communications to the RAU 14. The HEU 12 is also configured to return communications received from the RAU 14, via uplink electrical RF signals 18U, back to the source or sources. In this regard in this embodiment, the optical fiber 16 includes at least one downlink optical fiber 16D to carry signals communicated from the HEU 12 to the RAU 14 and at least one uplink optical fiber 16U to carry signals communicated from the RAU 14 back to the HEU 12.

The optical fiber-based distributed communications system 10 has an antenna coverage area 20 that can be substantially centered about the RAU 14. The antenna coverage area 20 of the RAU 14 forms an RF coverage area 21. The HEU 12 is adapted to perform or to facilitate any one of a number of Radio-over-Fiber (RoF) applications, such as radio frequency (RF) identification (RFID), wireless local-area network (WLAN) communication, or cellular phone service. Shown within the antenna coverage area 20 is a client device 24 in the form of a mobile device as an example, which may be a cellular telephone as an example. The client device 24 can be any device that is capable of receiving RF communication signals. The client device 24 includes an antenna 26 (e.g., a wireless card) adapted to receive and/or send electromagnetic RF signals.

With continuing reference to FIG. 1, to communicate the electrical RF signals over the downlink optical fiber 16D to

the RAU 14, to in turn be communicated to the client device 24 in the antenna coverage area 20 formed by the RAU 14, the HEU 12 includes an electrical-to-optical (E/O) converter 28. The E-O converter 28 converts the downlink electrical RF signals 18D to downlink optical RF signals 22D to be communicated over the downlink optical fiber 16D. The RAU 14 includes an optical-to-electrical (O/E) converter 30 to convert received downlink optical RF signals 22D back to electrical RF signals to be communicated wirelessly through an antenna 32 of the RAU 14 to client devices 24 located in the antenna coverage area 20.

Similarly, the antenna 32 is also configured to receive wireless RF communications from client devices 24 in the antenna coverage area 20. In this regard, the antenna 32 receives wireless RF communications from client devices 24 and communicates electrical RF signals representing the wireless RF communications to an E/O converter 34 in the RAU 14. The E-O converter 34 converts the electrical RF signals into uplink optical RF signals 22U to be communicated over the uplink optical fiber 16U. An O/E converter 36 provided in the HEU 12 converts the uplink optical RF signals 22U into uplink electrical RF signals, which can then be communicated as uplink electrical RF signals 18U back to a network or other source. The HEU 12 in this embodiment is not able to distinguish the location of the client devices 24 in this embodiment. The client device 24 could be in the range of any antenna coverage area 20 formed by an RAU 14.

FIG. 2 is a more detailed schematic diagram of the exemplary optical fiber-based distributed communications system of FIG. 1 that provides electrical RF service signals for a particular RF service or application. In an exemplary embodiment, the HEU 12 includes a service unit 37 that provides electrical RF service signals by passing (or conditioning and then passing) such signals from one or more outside networks 38 via a network link 39. In a particular example embodiment, this includes providing WLAN signal distribution as specified in the Institute of Electrical and Electronics Engineers (IEEE) 802.11 standard, i.e., in the frequency range from 2.4 to 2.5 GigaHertz (GHz) and from 5.0 to 6.0 GHz. Any other electrical RF signal frequencies are possible. In another exemplary embodiment, the service unit 37 provides electrical RF service signals by generating the signals directly. In another exemplary embodiment, the service unit 37 coordinates the delivery of the electrical RF service signals between client devices 24 within the antenna coverage area 20.

With continuing reference to FIG. 2, the service unit 37 is electrically coupled to the E-O converter 28 that receives the downlink electrical RF signals 18D from the service unit 37 and converts them to corresponding downlink optical RF signals 22D. In an exemplary embodiment, the E-O converter 28 includes a laser suitable for delivering sufficient dynamic range for the RoF applications described herein, and optionally includes a laser driver/amplifier electrically coupled to the laser. Examples of suitable lasers for the E-O converter 28 include, but are not limited to, laser diodes, distributed feedback (DFB) lasers, Fabry-Perot (FP) lasers, and vertical cavity surface emitting lasers (VCSELs).

With continuing reference to FIG. 2, the HEU 12 also includes the O-E converter 36, which is electrically coupled to the service unit 37. The O-E converter 36 receives the uplink optical RF signals 22U and converts them to corresponding uplink electrical RF signals 18U. In an example embodiment, the O-E converter 36 is a photodetector, or a photodetector electrically coupled to a linear amplifier. The E-O converter 28 and the O-E converter 36 constitute a "converter pair" 35, as illustrated in FIG. 2.

In accordance with an exemplary embodiment, the service unit **37** in the HEU **12** can include an RF signal modulator/demodulator unit **40** for modulating/demodulating the downlink electrical RF signals **18D** and the uplink electrical RF signals **18U**, respectively. The service unit **37** can include a digital signal processing unit (“digital signal processor”) **42** for providing to the RF signal modulator/demodulator unit **40** an electrical signal that is modulated onto an RF carrier to generate a desired downlink electrical RF signal **18D**. The digital signal processor **42** is also configured to process a demodulation signal provided by the demodulation of the uplink electrical RF signal **18U** by the RF signal modulator/demodulator unit **40**. The HEU **12** can also include an optional central processing unit (CPU) **44** for processing data and otherwise performing logic and computing operations, and a memory unit **46** for storing data, such as data to be transmitted over a WLAN or other network for example.

With continuing reference to FIG. 2, the RAU **14** also includes a converter pair **48** comprising the O-E converter **30** and the E-O converter **34**. The O-E converter **30** converts the received downlink optical RF signals **22D** from the HEU **12** back into downlink electrical RF signals **50D**. The E-O converter **34** converts uplink electrical RF signals **50U** received from the client device **24** into the uplink optical RF signals **22U** to be communicated to the HEU **12**. The O-E converter **30** and the E-O converter **34** are electrically coupled to the antenna **32** via an RF signal-directing element **52**, such as a circulator for example. The RF signal-directing element **52** serves to direct the downlink electrical RF signals **50D** and the uplink electrical RF signals **50U**, as discussed below. In accordance with an exemplary embodiment, the antenna **32** can include one or more patch antennas, such as disclosed in U.S. patent application Ser. No. 11/504,999, filed Aug. 16, 2006 entitled “Radio-over-Fiber Transponder With A Dual-Band Patch Antenna System,” and U.S. patent application Ser. No. 11/451,553, filed Jun. 12, 2006 entitled “Centralized Optical Fiber-Based Wireless Picocellular Systems and Methods,” both of which are incorporated herein by reference in their entireties.

With continuing reference to FIG. 2, the optical fiber-based distributed communications system **10** also includes a power supply **54** that generates an electrical power signal **56**. The power supply **54** is electrically coupled to the HEU **12** for powering the power-consuming elements therein. In an exemplary embodiment, an electrical power line **58** runs through the HEU **12** and over to the RAU **14** to power the O-E converter **30** and the E-O converter **34** in the converter pair **48**, the optional RF signal-directing element **52** (unless the RF signal-directing element **52** is a passive device such as a circulator for example), and any other power-consuming elements provided. In an exemplary embodiment, the electrical power line **58** includes two wires **60** and **62** that carry a single voltage and that are electrically coupled to a DC power converter **64** at the RAU **14**. The DC power converter **64** is electrically coupled to the O-E converter **30** and the E-O converter **34** in the converter pair **48**, and changes the voltage or levels of the electrical power signal **56** to the power level(s) required by the power-consuming components in the RAU **14**. In an exemplary embodiment, the DC power converter **64** is either a DC/DC power converter or an AC/DC power converter, depending on the type of electrical power signal **56** carried by the electrical power line **58**. In another example embodiment, the electrical power line **58** (dashed line) runs directly from the power supply **54** to the RAU **14** rather than from or through the HEU **12**. In another example embodiment, the electrical power line **58** includes more than two wires and carries multiple voltages.

To provide further exemplary illustration of how an optical fiber-based distributed communications system can be deployed indoors, FIG. 3 is provided. FIG. 3 is a partially schematic cut-away diagram of a building infrastructure **70** employing an optical fiber-based distributed communications system. The system may be the optical fiber-based distributed communications system **10** of FIGS. 1 and 2. The building infrastructure **70** generally represents any type of building in which the optical fiber-based distributed communications system **10** can be deployed. As previously discussed with regard to FIGS. 1 and 2, the optical fiber-based distributed communications system **10** incorporates the HEU **12** to provide various types of communication services to coverage areas within the building infrastructure **70**, as an example. For example, as discussed in more detail below, the optical fiber-based distributed communications system **10** in this embodiment is configured to receive wireless RF signals and convert the RF signals into RoF signals to be communicated over the optical fiber **16** to multiple RAUs **14**. The optical fiber-based distributed communications system **10** in this embodiment can be, for example, an indoor distributed antenna system (IDAS) to provide wireless service inside the building infrastructure **70**. These wireless signals can include cellular service, wireless services such as RFID tracking, Wireless Fidelity (WiFi), local area network (LAN), WLAN, and combinations thereof, as examples.

With continuing reference to FIG. 3, the building infrastructure **70** in this embodiment includes a first (ground) floor **72**, a second floor **74**, and a third floor **76**. The floors **72**, **74**, **76** are serviced by the HEU **12** through a main distribution frame **78** to provide antenna coverage areas **80** in the building infrastructure **70**. Only the ceilings of the floors **72**, **74**, **76** are shown in FIG. 3 for simplicity of illustration. In the example embodiment, a main cable **82** has a number of different sections that facilitate the placement of a large number of RAUs **14** in the building infrastructure **70**. Each RAU **14** in turn services its own coverage area in the antenna coverage areas **80**. The main cable **82** can include, for example, a riser cable **84** that carries all of the downlink and uplink optical fibers **16D**, **16U** to and from the HEU **12**. The riser cable **84** may be routed through an interconnect unit (ICU) **85**. The ICU **85** may be provided as part of or separate from the power supply **54** in FIG. 2. The ICU **85** may also be configured to provide power to the RAUs **14** via the electrical power line **58**, as illustrated in FIG. 2 and discussed above, provided inside an array cable **87** and distributed with the downlink and uplink optical fibers **16D**, **16U** to the RAUs **14**. The main cable **82** can include one or more multi-cable (MC) connectors adapted to connect select downlink and uplink optical fibers **16D**, **16U**, along with an electrical power line, to a number of optical fiber cables **86**.

The main cable **82** enables multiple optical fiber cables **86** to be distributed throughout the building infrastructure **70** (e.g., fixed to the ceilings or other support surfaces of each floor **72**, **74**, **76**) to provide the antenna coverage areas **80** for the first, second and third floors **72**, **74** and **76**. In an example embodiment, the HEU **12** is located within the building infrastructure **70** (e.g., in a closet or control room), while in another example embodiment the HEU **12** may be located outside of the building infrastructure **70** at a remote location. A base transceiver station (BTS) **88**, which may be provided by a second party such as a cellular service provider, is connected to the HEU **12**, and can be co-located or located remotely from the HEU **12**. A BTS is any station or source that provides an input signal to the HEU **12** and can receive a return signal from the HEU **12**. In a typical cellular system, for example, a plurality of BTSs are deployed at a plurality of

remote locations to provide wireless telephone coverage. Each BTS serves a corresponding cell and when a mobile station enters the cell, the BTS communicates with the mobile station. Each BTS can include at least one radio transceiver for enabling communication with one or more subscriber units operating within the associated cell.

The optical fiber-based distributed communications system **10** in FIGS. **1-3** and described above provides point-to-point communications between the HEU **12** and the RAU **14**. Each RAU **14** communicates with the HEU **12** over a distinct downlink and uplink optical fiber pair to provide the point-to-point communications. Whenever an RAU **14** is installed in the optical fiber-based distributed communications system **10**, the RAU **14** is connected to a distinct downlink and uplink optical fiber pair connected to the HEU **12**. The downlink and uplink optical fibers may be provided in the optical fiber **16**. Multiple downlink and uplink optical fiber pairs can be provided in a fiber optic cable to service multiple RAUs **14** from a common fiber optic cable. For example, with reference to FIG. **3**, RAUs **14** installed on a given floor **72**, **74**, or **76** may be serviced from the same optical fiber **16**. In this regard, the optical fiber **16** may have multiple nodes where distinct downlink and uplink optical fiber pairs can be connected to a given RAU **14**.

It may be desirable to provide both digital data services and RF communication services for client devices. For example, it may be desirable to provide digital data services and RF communication services in the building infrastructure **70** to client devices located therein. Wired and wireless devices may be located in the building infrastructure **70** that are configured to access digital data services. Examples of digital data services include, but are not limited to, Ethernet, WLAN, WiMax, WiFi, DSL, and LTE, etc. Ethernet standards could be supported, including but not limited to 100 Megabits per second (Mbps) (i.e., fast Ethernet) or Gigabit (Gb) Ethernet, or ten Gigabit (10 G) Ethernet. Example of digital data devices include, but are not limited to, wired and wireless servers, wireless access points (WAPs), gateways, desktop computers, hubs, switches, remote radio heads (RRHs), baseband units (BBUs), and femtocells. A separate digital data services network can be provided to provide digital data services to digital data devices.

In this regard, embodiments disclosed herein provide optical fiber-based distributed communications systems that support both RF communication services and digital data services. The RF communication services and digital data services can be distributed over optical fiber to client devices, such as remote antenna units for example. Digital data services can be distributed over optical fiber separate from the optical fiber distributing RF communication services. Alternatively, digital data services can be both distributed over common optical fiber with RF communication services in an optical fiber-based distributed communications system. For example, digital data services can be distributed over common optical fiber with RF communication services at different wavelengths through wavelength-division multiplexing (WDM) and/or at different frequencies through frequency-division multiplexing (FDM).

FIG. **4** is a schematic diagram of an exemplary embodiment of providing digital data services over separate downlink and uplink optical fibers from radio frequency (RF) communication services to RAUs in an optical fiber-based distributed communications system **90**. The optical fiber-based distributed communications system **90** includes some optical communication components provided in the optical fiber-based distributed communications system **10** of FIGS. **1-3**. These common components are illustrated in FIG. **4** with

common element numbers with FIGS. **1-3**. As illustrated in FIG. **4**, the HEU **12** is provided. The HEU **12** receives the downlink electrical RF signals **18D** from the BTS **88**. As previously discussed, the HEU **12** converts the downlink electrical RF signals **18D** to downlink optical RF signals **22D** to be distributed to the RAUs **14**. The HEU **12** is also configured to convert the uplink optical RF signals **22U** received from the RAUs **14** into uplink electrical RF signals **18U** to be provided to the BTS **88** and on to a network **93** connected to the BTS **88**. A patch panel **92** may be provided to receive the downlink and uplink optical fibers **16D**, **16U** configured to carry the downlink and uplink optical RF signals **22D**, **22U**. The downlink and uplink optical fibers **16D**, **16U** may be bundled together in one or more riser cables **84** and provided to one or more ICU **85**, as previously discussed and illustrated in FIG. **3**.

To provide digital data services in the optical fiber-based distributed communications system **90** in this embodiment, a digital data service controller (also referred to as “DDS controller”) in the form of a head-end media converter (HMC) **94** in this example is provided. The DDS controller **94** can include only a media converter for provision media conversion functionality or can include additional functionality to facilitate digital data services. A DDS controller is a controller configured to provide digital data services over a communications link, interface, or other communications channel or line, which may be either wired, wireless, or a combination of both. FIG. **5** illustrates an example of the HMC **94**. The HMC **94** includes a housing **95** configured to house digital media converters (DMCs) **97** to interface to a digital data services switch **96** to support and provide digital data services. For example, the digital data services switch **96** could be an Ethernet switch. The digital data services switch **96** may be configured to provide Gigabit (Gb) Ethernet digital data service as an example. The DMCs **97** are configured to convert electrical digital signals to optical digital signals, and vice versa. The DMCs **97** may be configured for plug and play installation (i.e., installation and operability without user configuration required) into the HMC **94**. FIG. **6** illustrates an exemplary DMC **97** that can be disposed in the housing **95** of the HMC **94**. For example, the DMC **97** may include Ethernet input connectors or adapters (e.g., RJ-45) and optical fiber output connectors or adapters (e.g., LC, SC, ST, MTP).

With reference to FIG. **4**, the HMC **94** (via the DMCs **97**) in this embodiment is configured to convert downlink electrical digital signals (or downlink electrical digital data services signals) **98D** over digital line cables **99** from the digital data services switch **96** into downlink optical digital signals (or downlink optical digital data services signals) **100D** that can be communicated over downlink optical fiber **102D** to RAUs **14**. The HMC **94** (via the DMCs **97**) is also configured to receive uplink optical digital signals **100U** from the RAUs **14** via the uplink optical fiber **102U** and convert the uplink optical digital signals **100U** into uplink electrical digital signals **98U** to be communicated to the digital data services switch **96**. In this manner, the digital data services can be provided over optical fiber as part of the optical fiber-based distributed communications system **90** to provide digital data services in addition to RF communication services. Client devices located at the RAUs **94** can access these digital data services and/or RF communication services depending on their configuration. For example, FIG. **7** illustrates the building infrastructure **70** of FIG. **3**, but with illustrative examples of digital data services and digital client devices that can be provided to client devices in addition to RF communication services in the optical fiber-based distributed communications system **90**. As illustrated in FIG. **7**, exemplary digital

data services include WLAN **106**, femtocells **108**, gateways **110**, baseband units (BBU) **112**, remote radio heads (RRH) **114**, and servers **116**.

With reference back to FIG. 4, in this embodiment, the downlink and uplink optical fibers **102D**, **102U** are provided in a fiber optic cable **104** that is interfaced to the ICU **85**. The ICU **85** provides a common point in which the downlink and uplink optical fibers **102D**, **102U** carrying digital optical signals can be bundled with the downlink and uplink optical fibers **16U**, **16D** carrying RF optical signals. One or more of the fiber optic cables **104**, also referenced herein as array cables **104**, can be provided containing the downlink and uplink optical fibers **16D**, **16U** for RF communication services and downlink and uplink optical fibers **102D**, **102U** for digital data services to be routed and provided to the RAUs **14**. Any combination of services or types of optical fibers can be provided in the array cable **104**. For example, the array cable **104** may include single mode and/or multi-mode optical fibers for RF communication services and/or digital data services.

Examples of ICUs that may be provided in the optical fiber-based distributed communications system **90** to distribute both downlink and uplink optical fibers **16D**, **16U** for RF communication services and downlink and uplink optical fibers **102D**, **102U** for digital data services are described in U.S. patent application Ser. No. 12/466,514 filed on May 15, 2009 and entitled "Power Distribution Devices, Systems, and Methods For Radio-Over-Fiber (RoF) Distributed Communication," incorporated herein by reference in its entirety, and U.S. Provisional Patent Application Ser. No. 61/330,385, filed on May 2, 2010 and entitled "Power Distribution in Optical Fiber-based Distributed Communication Systems Providing Digital Data and Radio-Frequency (RF) Communication Services, and Related Components and Methods," both of which are incorporated herein by reference in their entireties.

With continuing reference to FIG. 4, some RAUs **14** can be connected to access points (APs) **118** or other devices supporting digital data services. APs **118** are illustrated, but the APs **118** could be any other device supporting digital data services. In the example of APs, the APs **118** provide access to the digital data services provided by the digital data services switch **96**. This is because the downlink and uplink optical fibers **102D**, **102U** carrying downlink and uplink optical digital signals **100D**, **100U** converted from downlink and uplink electrical digital signals **98D**, **98U** from the digital data services switch **96** are provided to the APs **118** via the array cables **104** and RAUs **14**. Digital data client devices can access the APs **118** to access digital data services provided through the digital data services switch **96**.

Digital data service clients, such as APs, require power to operate and to receive digital data services. By providing digital data services as part of an optical fiber-based distributed communications system, power distributed to the RAUs in the optical fiber-based distributed communications system can also be used to provide access to power for digital data service clients. This may be a convenient method of providing power to digital data service clients as opposed to providing separate power sources for digital data service clients. For example, power distributed to the RAUs **14** in FIG. 4 by or through the ICU **85** can also be used to provide power to the APs **118** located at RAUs **14** in the optical fiber-based distributed communications system **90**. In this regard, the ICUs **85** may be configured to provide power for both RAUs **14** and the APs **118**. A power supply may be located within the ICU **85**, but could also be located outside of the ICU **85** and provided over an electrical power line **120**, as illustrated in

FIG. 4. The ICU **85** may receive either alternating current (AC) or direct current (DC) power. The ICU **85** may receive 110 Volts (V) to 240V AC or DC power. The ICU **85** can be configured to produce any voltage and power level desired. The power level is based on the number of RAUs **14** and the expected loads to be supported by the RAUs **14** and any digital devices connected to the RAUs **14** in FIG. 4. It may further be desired to provide additional power management features in the ICU **85**. For example, one or more voltage protection circuits may be provided.

FIG. 8 is a schematic diagram of exemplary internal components in the RAU **14** of FIG. 4 to further illustrate how the downlink and uplink optical fibers **16D**, **16U** for RF communications, the downlink and uplink optical fibers **102D**, **102U** for digital data services, and electrical power are provided to the RAU **14** and can be distributed therein. As illustrated in FIG. 8, the array cable **104** is illustrated that contains the downlink and uplink optical fibers **16D**, **16U** for RF communications, the downlink and uplink optical fibers **102D**, **102U** for digital data services, and the electrical power line **58** (see also, FIG. 2) carrying power from the ICU **85**. As previously discussed in regard to FIG. 2, the electrical power line **58** may comprise two wires **60**, **62**, which may be copper lines for example.

The downlink and uplink optical fibers **16D**, **16U** for RF communications, the downlink and uplink optical fibers **102D**, **102U** for digital data services, and the electrical power line **58** come into a housing **124** of the RAU **14**. The downlink and uplink optical fibers **16D**, **16U** for RF communications are routed to the O-E converter **30** and E-O converter **34**, respectively, and to the antenna **32**, as also illustrated in FIG. 2 and previously discussed. The downlink and uplink optical fibers **102D**, **102U** for digital data services are routed to a digital data services interface **126** provided as part of the RAU **14** to provide access to digital data services via a port **128**, which will be described in more detail below. The electrical power line **58** carries power that is configured to provide power to the O-E converter **30** and E-O converter **34** and to the digital data services interface **126**. In this regard, the electrical power line **58** is coupled to a voltage controller **130** that regulates and provides the correct voltage to the O-E converter **30** and E-O converter **34** and to the digital data services interface **126** and other circuitry in the RAU **14**.

In this embodiment, the digital data services interface **126** is configured to convert downlink optical digital signals **100D** on the downlink optical fiber **102D** into downlink electrical digital signals **132D** that can be accessed via the port **128**. The digital data services interface **126** is also configured to convert uplink electrical digital signals **132U** received through the port **128** into uplink optical digital signals **100U** to be provided back to the HMC **94** (see FIG. 4). In this regard, a media converter **134** is provided in the digital data services interface **126** to provide these conversions. The media converter **134** contains an O-E digital converter **136** to convert downlink optical digital signals **100D** on the downlink optical fiber **102D** into downlink electrical digital signals **132D**. The media converter **134** also contains an E-O digital converter **138** to convert uplink electrical digital signals **132U** received through the port **128** into uplink optical digital signals **100U** to be provided back to the HMC **94**. In this regard, power from the electrical power line **58** is provided to the digital data services interface **126** to provide power to the O-E digital converter **136** and E-O digital converter **138**.

Because electrical power is provided to the RAU **14** and the digital data services interface **126**, this also provides an opportunity to provide power for digital devices connected to the RAU **14** via the port **128**. In this regard, a power interface

13

140 is also provided in the digital data services interface 126, as illustrated in FIG. 8. The power interface 140 is configured to receive power from the electrical power line 58 via the voltage controller 130 and to also make power accessible through the port 128. In this manner, if a client device contains a compatible connector to connect to the port 128, not only will digital data services be accessible, but power from the electrical power line 58 can also be accessed through the same port 128. Alternatively, the power interface 140 could be coupled to a separate port from the port 128 for digital data services.

For example, if the digital data services are provided over Ethernet, the power interface 140 could be provided as a Power-over-Ethernet (PoE) interface. The port 128 could be configured to receive a RJ-45 Ethernet connector compatible with PoE as an example. In this manner, an Ethernet connector connected into the port 128 would be able to access both Ethernet digital data services to and from the downlink and uplink optical fibers 102D, 102U to the HMC 94 as well as access power distributed by the ICU 85 over the array cable 104 provided by the electrical power line 58.

Further, the HEU 12 could include low level control and management of the media converter 134 using communication supported by the HEU 12. For example, the media converter 134 could report functionality data (e.g., power on, reception of optical digital data, etc.) to the HEU 12 over the uplink optical fiber 16U that carries communication services. The RAU 14 can include a microprocessor that communicates with the media converter 134 to receive this data and communicate this data over the uplink optical fiber 16U to the HEU 12.

Other configurations are possible to provide digital data services in an optical fiber-based distributed communications system. For example, FIG. 9 is a schematic diagram of another exemplary embodiment of providing digital data services in an optical fiber-based distributed communications system configured to provide RF communication services. In this regard, FIG. 9 provides an optical fiber-based distributed communications system 150. The optical fiber-based distributed communications system 150 may be similar to and include common components provided in the optical fiber-based distributed communications system 90 in FIG. 4. In this embodiment, instead of the HMC 94 being provided separate from the HEU 12, the HMC 94 is co-located with the HEU 12. The downlink and uplink optical fibers 102D, 102U for providing digital data services from the digital data services switch 96 are also connected to the patch panel 92. The downlink and uplink optical fibers 16D, 16U for RF communications and the downlink and uplink optical fibers 102D, 102U for digital data services are then routed to the ICU 85, similar to FIG. 2.

The downlink and uplink optical fibers 16D, 16U for RF communications, and the downlink and uplink optical fibers 102D, 102U for digital data services, may be provided in a common fiber optic cable or provided in separate fiber optic cables. Further, as illustrated in FIG. 9, standalone media converters (MCs) 141 may be provided separately from the RAUs 14 in lieu of being integrated with RAUs 14, as illustrated in FIG. 4. The stand alone MCs 141 can be configured to contain the same components as provided in the digital data services interface 126 in FIG. 8, including the media converter 134. The APs 118 may also each include antennas 152 to provide wireless digital data services in lieu of or in addition to wired services through the port 128 through the RAUs 14.

FIG. 10A is a schematic diagram of another exemplary embodiment of providing digital data services in an optical

14

fiber-based distributed communications system. In this regard, FIG. 10A provides an optical fiber-based distributed communications system 160. The optical fiber-based distributed communications system 160 may be similar to and include common components provided in the optical fiber-based distributed communications systems 90, 150 in FIGS. 4 and 9.

In this embodiment, as illustrated in FIG. 10A, wavelength-division multiplexing (WDM) is employed to multiplex digital data services and RF communication services together at different wavelengths over downlink and uplink optical fibers 162D(1-N), 162U(1-N) in the optical fiber-based distributed communications system 160. "1-N" downlink and uplink optical fiber pairs are provided to the ICU 85 to be distributed to the RAUs 14 and stand alone MCs 141. Multiplexing could be used to further reduce the cost for the digital data services overlay. By using WDM, digital data signals are transmitted on the same optical fibers as the RF communication signals, but on different wavelengths. Separate media conversion and WDM filters at the transmit locations and at the receive locations (e.g., HMC 96 and RAUs 14) would be employed to receive signals at the desired wavelength.

The HMC 94 and HEU 12 are co-located in the optical fiber-based distributed communications system 160 in FIG. 10A. A plurality of wavelength-division multiplexers 164(1)-164(N) are provided that each multiplex the downlink optical RF signal(s) 22D for RF communications and the downlink optical digital signal(s) 100D for digital data services together on a common downlink optical fiber(s) 162D(1-N). Similarly, a plurality of wavelength-division de-multiplexers 168(1)-168(N) (e.g., wavelength filters) are provided that each de-multiplex the uplink optical RF signal(s) 22U from the uplink optical digital signal(s) 100U from a common uplink optical fiber(s) 162U(1-N) to provide the uplink optical RF signals 22U to the HEU 12 and the uplink optical digital signal 100U to the HMC 94. Wavelength-division de-multiplexing (WDD) and WDM are also employed in the RAUs 14 to de-multiplex multiplexed downlink optical RF signals 22D and downlink optical digital signals 100D on the common downlink optical fibers 162D(1-N) and to multiplex uplink optical RF signals 22U and uplink optical digital signals 100U on the common uplink optical fibers 162U(1-N).

FIG. 10B is a schematic diagram of another exemplary embodiment of providing digital data services in an optical fiber-based distributed communications system 160'. The optical fiber-based distributed communications system 160' in FIG. 10B is the same as the optical fiber-based distributed communications system 160 in FIG. 10A, except that WDM is employed to multiplex uplink and downlink communication services at different wavelengths over common optical fiber that includes both downlink and uplink optical fibers 162D(1-N), 162U(1-N).

FIG. 11 is a schematic diagram of another exemplary embodiment of providing digital data services in an optical fiber-based distributed communications system. As illustrated in FIG. 11, an optical fiber-based distributed communications system 170 is provided that can also deliver digital data services. Instead of wavelength-division multiplexing the downlink optical RF signal(s) 22D for RF communications with the downlink optical digital signal(s) 100D for digital data services together on a common downlink optical fiber(s) 162D(1-N) as provided in FIG. 10A, a wavelength-division multiplexer 172 is provided. The wavelength-division multiplexer 172 multiplexes all downlink optical RF signals 22D with all downlink optical digital signal 100D to a single downlink optical fiber 174D. Similarly, a wavelength-

15

division de-multiplexer **176** is provided to de-multiplex all uplink optical RF signals **22U** from all uplink optical digital signals **100U** from the common uplink optical fiber **174U** at the desired wavelength. A wavelength-division de-multiplexer **175** and a wavelength-division multiplexer **177** are also employed in the ICU **85** to de-multiplex wavelength-division multiplexed downlink optical RF signals **22D** and uplink optical digital signals **100U** on the common downlink optical fiber **174D**, and to wavelength-division multiplex uplink optical RF signals **22U** and uplink optical digital signals **100U** on the common uplink optical fiber **174U**, respectively.

Alternatively, WDD and WDM could also be employed in the RAUs **14** to de-multiplex wavelength-division multiplexed downlink optical RF signals **22D** and downlink optical digital signals **100D** on the common downlink optical fiber **174D**, and to wavelength-division multiplex uplink optical RF signals **22U** and uplink optical digital signals **100U** on the common uplink optical fiber **174U**. In this alternative embodiment, de-multiplexing at the RAUs **14** could be done where a common WDM signal would be distributed from RAU **14** to RAU **14** in a daisy-chain configuration. Alternatively, optical splitters could be employed at break-out points in the fiber optic cable **104**.

FIG. **12** is a schematic diagram of another exemplary embodiment of providing digital data services in an optical fiber-based distributed communications system. As illustrated in FIG. **12**, an optical fiber-based distributed communications system **180** is provided that can also deliver digital data services. The optical fiber-based distributed communications system **180** is the same as the optical fiber-based distributed communications system **170** in FIG. **11**, except that the HEU **12** and HMC **94** are provided in a common housing **182** that also houses the wavelength-division multiplexer **172** and wavelength-division de-multiplexer **176**. Alternatively, a plurality of wavelength-division multiplexers and plurality of wavelength-division de-multiplexers like provided in FIG. **10A** (**164(1-N)**) and **168(1-N)**) can be provided in the common housing **182**.

FIG. **13** is a schematic diagram of another exemplary embodiment of an optical fiber-based distributed communications system providing digital data services. As illustrated in FIG. **13**, an optical fiber-based distributed communications system **190** is provided. In this embodiment, frequency-division multiplexing (FDM) is employed to multiplex digital data services and RF communication services at different frequencies over downlink optical fibers and uplink optical fibers. One advantage of employing FDM is that E-O converters would be used simultaneously for converting RF communication signals and digital data signals into respective optical signals. Therefore, additional media converters for converting electrical digital signals to optical digital signals can be avoided to reduce complexity and save costs. For example, fast Ethernet (e.g., 100 Megabits/second (Mbs)) could be transmitted below the cellular spectrum (e.g., below 700 MHz). More than one (1) channel could be transmitted simultaneously in this frequency range.

In this regard, the HEU **12** and HEC **94** are both disposed in the common housing **182**, as illustrated in FIG. **13**. A plurality of frequency-division multiplexers **192(1-N)** are provided in the common housing **182** and are each configured to multiplex the downlink electrical digital signal(s) **98D** with the downlink electrical RF signal(s) **18D** at different frequencies prior to optical conversion. In this manner, after optical conversion, a common optical fiber downlink **194D(1-N)** can carry frequency-division multiplexed downlink optical RF signal **22D** and downlink optical digital signal **102D** on the

16

same downlink optical fiber **194D(1-N)**. Similarly, a plurality of frequency-division de-multiplexers **196(1-N)** are provided in the common housing **182** to de-multiplex an uplink optical RF signal **22U** and an uplink optical digital signal **100U** on an uplink optical fiber **194U(1-N)**. Frequency-division de-multiplexing (FDD) and FDM are also employed in the RAUs **14**. FDD is employed in the RAU **14** to de-multiplex frequency multiplexed downlink electrical RF signals **18D** and downlink electrical digital signals **98D** after being converted from optical signals from the common downlink optical fiber **174D** to electrical signals. FDM is also provided in the RAU **14** to frequency multiplex uplink electrical signals in the RAU **14** before being converted to uplink optical RF signals **22U** and uplink optical digital signals **100U** provided on the common uplink optical fiber **174U**.

FIG. **14** is a schematic diagram of another exemplary embodiment of an optical fiber-based distributed communications system that employs both WDM and FDM. In this regard, FIG. **14** illustrates an optical fiber-based distributed communications system **200**. The optical fiber-based distributed communications system **200** employs the WDM and WDD of the optical fiber-based distributed communications system **180** of FIG. **12** combined with FDM and FDD of the optical fiber-based distributed communications system **190** of FIG. **13**. The wavelength-division multiplexed and frequency-division multiplexed downlink signals are provided over downlink optical fiber **202D**. The wavelength-division multiplexed and frequency-division multiplexed uplink signals are provided over uplink optical fiber **202U**.

Options and alternatives can be provided for the above-described embodiments. A digital data services interface provided in an RAU or stand alone MC could include more than one digital data services port. For example, referring to FIG. **14** as an example, a switch **203**, such as an Ethernet switch for example, may be disposed in the RAUs **14** to provide RAUs **14** that can support more than one digital data services port. An HMC could have an integrated Ethernet switch so that, for example, several APs could be attached via cables (e.g., Cat 5/6/7 cables) in a star architecture. The Ethernet channel could be used for control, management, and/or communication purposes for an optical fiber-based distributed communications system as well as the Ethernet media conversion layer. The HMC could be either single channel or multi-channel (e.g., twelve (12) channel) solutions. The multi-channel solution may be cheaper per channel than a single channel solution. Further, uplink and downlink electrical digital signals can be provided over mediums other than optical fiber, including electrical conducting wire and/or wireless communications, as examples.

Frequency up conversions or down conversions may be employed when providing FDM if RF communication signals have frequencies too close to the frequencies of the digital data signals to avoid interference. While digital baseband transmission of a baseband digital data signals below the spectrum of the RF communication signals can be considered, intermodulation distortion on the RF communication signals may be generated. Another approach is to up convert the digital data signals above the frequencies of the RF communication signals and also use, for example, a constant envelope modulation format for digital data signal modulation. Frequency Shift Keying (FSK) and Minimum Shift Keying (MSK) modulation are suitable examples for such modulation formats. Further, in the case of FDM for digital data services, higher-level modulation formats can be considered to transmit high data rates (e.g., one (1) Gb, or ten (10) Gb) over the same optical fiber as the RF communication signals.

Multiple solutions using single-carrier (with e.g., 8-FSK or 16-QAM as examples) or multi-carrier (OFDM) are conceivable.

Further, as used herein, it is intended that terms “fiber optic cables” and/or “optical fibers” include all types of single mode and multi-mode light waveguides, including one or more optical fibers that may be upcoated, colored, buffered, ribbonized and/or have other organizing or protective structure in a cable such as one or more tubes, strength members, jackets or the like. The optical fibers disclosed herein can be single mode or multi-mode optical fibers. Likewise, other types of suitable optical fibers include bend-insensitive optical fibers, or any other expedient of a medium for transmitting light signals. An example of a bend-insensitive, or bend resistant, optical fiber is ClearCurve® Multimode fiber commercially available from Corning Incorporated. Suitable fibers of this type are disclosed, for example, in U.S. Patent Application Publication Nos. 2008/0166094 and 2009/0169163, the disclosures of which are incorporated herein by reference in their entireties.

Many modifications and other embodiments of the embodiments set forth herein will come to mind to one skilled in the art to which the embodiments pertain having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the description and claims are not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. It is intended that the embodiments cover the modifications and variations of the embodiments provided they come within the scope of the appended claims and their equivalents. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of imitation.

We claim:

1. A distributed antenna system for distributing radio frequency (RF) communications and digital data services (DDS) to at least one remote antenna unit (RAU), comprising:

a head-end unit (HEU) configured to:

receive at least one downlink electrical RF communications signal;

convert the at least one downlink electrical RF communications signal into at least one downlink optical RF communications signal to be communicated over at least one communications downlink to the at least one RAU;

receive at least one uplink optical RF communications signal over at least one communications uplink from the at least one RAU; and

convert the at least one uplink optical RF communications signal into at least one uplink electrical RF communications signal;

a DDS controller configured to:

receive at least one downlink signal containing at least one DDS;

convert the at least one downlink signal containing at least one DDS to at least one downlink optical digital signal containing at least one DDS;

provide the at least one downlink optical digital signal containing at least one DDS over at least one second communications downlink to the at least one RAU;

receive at least one uplink optical digital signal over at least one second communications uplink from the at least one RAU;

convert the at least one uplink optical digital signal to at least one uplink electrical digital signal; and

at least one RAU, wherein each RAU of the at least one RAU comprises:

an optical-to-electrical (O/E) converter configured to convert received downlink optical RF communications signals to downlink electrical RF communications signals and provide the downlink electrical RF communications signals to at least one first port;

an electrical-to-optical (E/O) converter configured to convert uplink electrical RF communications signals received from the at least one first port to uplink optical RF communications signals; and

a DDS interface coupled to at least one second port and configured to:

convert downlink optical digital signals into downlink electrical digital signals to provide to the at least one second port; and

convert uplink electrical digital signals received from the at least one second port into uplink optical digital signals; and

at least one device supporting digital data services and connected to at least one RAU via the at least one second port, and

wherein the DDS interface further comprises a power interface configured to receive electrical power and provide the electrical power to the at least one second port, the electrical power configured to power the at least one device supporting digital data services and connected to the at least one RAU.

2. The distributed antenna system of claim 1, wherein the at least one RAU comprises a plurality of remote antenna units.

3. The distributed antenna system of claim 1, wherein the at least one communications downlink and the at least one communications uplink are the same optical fiber.

4. The distributed antenna system of claim 1, wherein the at least one communications downlink and the at least one communications uplink comprise separate, different optical fibers.

5. A distributed antenna system for distributing radio frequency (RF) communications and digital data services (DDS) to at least one remote antenna unit (RAU) comprising:

a head-end unit (HEU) configured to:

receive at least one downlink electrical RF communications signal;

convert the at least one downlink electrical RF communications signal into at least one downlink optical RF communications signal to be communicated over at least one communications downlink to the at least one RAU;

receive at least one uplink optical RF communications signal over at least one communications uplink from the at least one RAU; and

convert the at least one uplink optical RF communications signal into at least one uplink electrical RF communications signal;

a DDS controller configured to:

receive at least one downlink signal containing at least one DDS;

convert the at least one downlink signal containing at least one DDS to at least one downlink optical digital signal containing at least one DDS;

provide the at least one downlink optical digital signal containing at least one DDS over at least one second communications downlink to the at least one RAU;

receive at least one uplink optical digital signal over at least one second communications uplink from the at least one RAU;

convert the at least one uplink optical digital signal to at least one uplink electrical digital signal; and

19

at least one RAU, wherein each RAU of the at least one RAU comprises:

- an optical-to-electrical (O/E) converter configured to convert received downlink optical RF communications signals to downlink electrical RF communications signals and provide the downlink electrical RF communications signals to at least one first port;
- an electrical-to-optical (E/O) converter configured to convert uplink electrical RF communications signals received from the at least one first port to uplink optical RF communications signals; and
- a DDS interface coupled to at least one second port and configured to:
 - convert downlink optical digital signals into downlink electrical digital signals to provide to the at least one second port; and
 - convert uplink electrical digital signals received from the at least one second port into uplink optical digital signals; and

20

a media converter associated with the at least one RAU and configured to report functionality data to the HEU over the at least one second communications uplink to the HEU, and wherein the HEU is configured to provide control and management of the media converter based on the functionality data.

- 6. The distributed antenna system of claim 5, wherein the at least one RAU comprises a plurality of remote antenna units.
- 7. The distributed antenna system of claim 5, wherein the at least one communications downlink and the at least one communications uplink are the same optical fiber.
- 8. The distributed antenna system of claim 5, wherein the at least one communications downlink and the at least one communications uplink comprise separate, different optical fibers.

* * * * *