



US009240877B2

(12) **United States Patent**
Gorokhov et al.

(10) **Patent No.:** **US 9,240,877 B2**
(45) **Date of Patent:** **Jan. 19, 2016**

(54) **SEGMENT SENSITIVE SCHEDULING**

(75) Inventors: **Alexei Y. Gorokhov**, San Diego, CA (US); **Tingfang Ji**, San Diego, CA (US)

(73) Assignee: **QUALCOMM Incorporated**, San Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 555 days.

(21) Appl. No.: **12/372,954**

(22) Filed: **Feb. 18, 2009**

(65) **Prior Publication Data**

US 2009/0201872 A1 Aug. 13, 2009

Related U.S. Application Data

(62) Division of application No. 11/260,924, filed on Oct. 27, 2005.

(60) Provisional application No. 60/710,461, filed on Aug. 22, 2005.

(51) **Int. Cl.**

H04W 4/00 (2009.01)
H04L 12/26 (2006.01)
H04Q 11/02 (2006.01)
H04L 5/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **H04L 5/006** (2013.01); **H04L 5/0044** (2013.01); **H04L 5/1438** (2013.01); **H04L 1/0002** (2013.01); **H04L 1/0009** (2013.01); **H04L 1/0026** (2013.01); **H04L 1/1812** (2013.01); **H04L 5/0007** (2013.01); **H04L 5/0048** (2013.01); **H04L 5/0057** (2013.01); **H04L 5/0064** (2013.01); **H04L 25/0398** (2013.01)

(58) **Field of Classification Search**

None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,393,276 A 7/1983 Steele et al.
4,554,668 A 11/1985 Deman et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2348137 11/2001
CA 2477536 9/2003

(Continued)

OTHER PUBLICATIONS

3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Physical Layer Aspects for Evolved UTRA (Release 7), 3GPP TR 25.814 v0.3.1 (Nov. 2005).


(Continued)

Primary Examiner — Chirag Shah
Assistant Examiner — Srinivasa Reddivalam

(57) **ABSTRACT**

Systems and methods of scheduling sub-carriers in an OFDMA system in which a scheduler takes into account channel conditions experienced by the communication devices to optimize channel conditions. The scheduler can partition a set of sub-carriers spanning an operating bandwidth into a plurality of segments. The segments can include a plurality of global segments that each includes a distinct non-contiguous subset of the sub-carriers spanning substantially the entire operating bandwidth. One or more of the global segments can be further partitioned into a plurality of local segments that each has a bandwidth that is less than a channel coherence bandwidth. The scheduler determines channel characteristics experienced by each communication device via reporting or channel estimation, and allocates one or more segments to communication links for each device according to the channel characteristics.

18 Claims, 5 Drawing Sheets



(51)	Int. Cl.							
	<i>H04L 5/14</i>	(2006.01)		6,154,484	A	11/2000	Lee et al.	
	<i>H04L 1/00</i>	(2006.01)		6,169,910	B1	1/2001	Tamil et al.	
	<i>H04L 1/18</i>	(2006.01)		6,172,993	B1	1/2001	Kim et al.	
	<i>H04L 25/03</i>	(2006.01)		6,175,550	B1	1/2001	van Nee et al.	
				6,175,650	B1	1/2001	Sindhu et al.	
				6,176,550	B1	1/2001	Lamart et al.	
				6,198,775	B1	3/2001	Khayrallah et al.	
(56)	References Cited			6,215,983	B1	4/2001	Dogan et al.	
	U.S. PATENT DOCUMENTS			6,226,280	B1	5/2001	Roark et al.	
	4,747,137	A	5/1988	Matsunaga				
	4,783,779	A	11/1988	Takahata et al.				
	4,783,780	A	11/1988	Alexis				
	4,975,952	A	12/1990	Mabey et al.				
	5,008,900	A	4/1991	Critchlow et al.				
	5,115,248	A	5/1992	Roederer et al.				
	5,268,694	A	12/1993	Jan et al.				
	5,282,222	A	1/1994	Fattouche et al.				
	5,363,408	A	11/1994	Paik et al.				
	5,371,761	A	12/1994	Daffara et al.				
	5,384,810	A	1/1995	Amrany et al.				
	5,406,551	A	4/1995	Saito et al.				
	5,410,538	A	4/1995	Roche et al.				
	5,455,839	A	10/1995	Eyuboglu et al.				
	5,465,253	A	11/1995	Rahnema				
	5,491,727	A	2/1996	Petit et al.				
	5,513,379	A	4/1996	Benveniste et al.				
	5,539,748	A	7/1996	Raith				
	5,548,582	A	8/1996	Brajal et al.				
	5,553,069	A	9/1996	Ueno et al.				
	5,583,869	A	12/1996	Grube et al.				
	5,594,738	A	1/1997	Crisler et al.				
	5,604,744	A	2/1997	Anderson et al.				
	5,612,978	A	3/1997	Blanchard et al.				
	5,625,876	A	4/1997	Gilhousen et al.				
	5,684,491	A	11/1997	Newman et al.				
	5,726,978	A	3/1998	Frodigh et al.				
	5,732,113	A	3/1998	Schmidl et al.				
	5,745,487	A	4/1998	Hamaki				
	5,768,276	A	6/1998	Diachina et al.				
	5,790,537	A	8/1998	Yoon et al.				
	5,812,938	A	9/1998	Gilhousen et al.				
	5,815,488	A	9/1998	Williams et al.				
	5,822,368	A	10/1998	Wang et al.				
	5,828,650	A	10/1998	Malkamaki et al.				
	5,838,268	A	11/1998	Frenkel et al.				
	5,867,478	A	2/1999	Baum et al.				
	5,870,393	A	2/1999	Yano et al.				
	5,887,023	A	3/1999	Mabuchi et al.				
	5,907,585	A	5/1999	Suzuki et al.				
	5,920,571	A	7/1999	Houck et al.				
	5,926,470	A	7/1999	Tiedemann, Jr.				
	5,933,421	A	8/1999	Alamouti et al.				
	5,949,814	A	9/1999	Odenwalder et al.				
	5,953,325	A	9/1999	Willars et al.				
	5,955,992	A	9/1999	Shattil et al.				
	5,956,642	A	9/1999	Larsson et al.				
	5,995,992	A	11/1999	Eckard et al.				
	5,999,826	A	12/1999	Whinnett				
	6,002,942	A	12/1999	Park et al.				
	6,016,123	A	1/2000	Barton et al.				
	6,038,150	A	3/2000	Yee et al.				
	6,038,263	A	3/2000	Kotzin et al.				
	6,038,450	A	3/2000	Brink et al.				
	6,052,364	A	4/2000	Chalmers et al.				
	6,061,337	A	5/2000	Light et al.				
	6,067,315	A	5/2000	Sandin				
	6,075,350	A	6/2000	Peng et al.				
	6,075,797	A	6/2000	Thomas				
	6,076,114	A	6/2000	Wesley				
	6,088,345	A	7/2000	Sakoda et al.				
	6,088,592	A	7/2000	Doner et al.				
	6,108,323	A	8/2000	Gray et al.				
	6,108,550	A	8/2000	Wiorek et al.				
	6,112,094	A	8/2000	Dent et al.				
	6,128,776	A	10/2000	Kang et al.				
	6,138,037	A	10/2000	Jaamies				
	6,141,317	A	10/2000	Marchok et al.				
				6,154,484	A	11/2000	Lee et al.	
				6,169,910	B1	1/2001	Tamil et al.	
				6,172,993	B1	1/2001	Kim et al.	
				6,175,550	B1	1/2001	van Nee et al.	
				6,175,650	B1	1/2001	Sindhu et al.	
				6,176,550	B1	1/2001	Lamart et al.	
				6,198,775	B1	3/2001	Khayrallah et al.	
				6,215,983	B1	4/2001	Dogan et al.	
				6,226,280	B1	5/2001	Roark et al.	
				6,232,918	B1	5/2001	Wax et al.	
				6,240,129	B1	5/2001	Reusens et al.	
				6,249,683	B1	6/2001	Lundby et al.	
				6,256,478	B1	7/2001	Allen et al.	
				6,271,946	B1	8/2001	Chang et al.	
				6,272,122	B1	8/2001	Wee et al.	
				6,310,704	B1	10/2001	Dogan et al.	
				6,317,435	B1	11/2001	Tiedemann, Jr. et al.	
				6,335,922	B1	1/2002	Tiedemann, Jr. et al.	
				6,337,659	B1	1/2002	Kim	
				6,337,983	B1	1/2002	Bonta et al.	
				6,353,637	B1	3/2002	Mansour et al.	
				6,363,060	B1	3/2002	Sarkar	
				6,374,115	B1	4/2002	Barnes et al.	
				6,377,539	B1	4/2002	Kang et al.	
				6,377,809	B1	4/2002	Rezaifar et al.	
				6,388,998	B1	5/2002	Kasturia et al.	
				6,393,008	B1	5/2002	Cheng et al.	
				6,393,012	B1	5/2002	Pankaj	
				6,401,062	B1	6/2002	Murashima	
				6,438,369	B1	8/2002	Huang et al.	
				6,449,246	B1	9/2002	Barton et al.	
				6,466,800	B1	10/2002	Sydon et al.	
				6,473,467	B1	10/2002	Wallace et al.	
				6,477,317	B1	11/2002	Itokawa	
				6,478,422	B1	11/2002	Hansen	
				6,483,820	B1	11/2002	Davidson et al.	
				6,487,243	B1	11/2002	Hwang et al.	
				6,496,790	B1	12/2002	Kathavate et al.	
				6,501,810	B1	12/2002	Karim et al.	
				6,507,601	B2	1/2003	Parsa et al.	
				6,519,462	B1	2/2003	Lu et al.	
				6,529,525	B1	3/2003	Pecen et al.	
				6,535,666	B1	3/2003	Dogan et al.	
				6,539,008	B1	3/2003	Ahn et al.	
				6,539,213	B1	3/2003	Richards et al.	
				6,542,485	B1	4/2003	Mujtaba	
				6,542,743	B1	4/2003	Soliman	
				6,563,806	B1	5/2003	Yano et al.	
				6,563,881	B1	5/2003	Sakoda et al.	
				6,577,739	B1	6/2003	Hurtig et al.	
				6,584,140	B1	6/2003	Lee et al.	
				6,590,881	B1	7/2003	Wallace et al.	
				6,597,746	B1	7/2003	Amrany et al.	
				6,601,206	B1	7/2003	Marvasti	
				6,614,857	B1	9/2003	Buehrer et al.	
				6,625,172	B2	9/2003	Odenwalder et al.	
				6,636,568	B2	10/2003	Kadous et al.	
				6,654,339	B1	11/2003	Bohnke et al.	
				6,654,431	B1	11/2003	Barton et al.	
				6,657,949	B1	12/2003	Jones, IV et al.	
				6,658,258	B1	12/2003	Chen et al.	
				6,674,787	B1	1/2004	Dick et al.	
				6,674,810	B1	1/2004	Cheng et al.	
				6,675,012	B2	1/2004	Gray et al.	
				6,678,318	B1	1/2004	Lai et al.	
				6,690,951	B1	2/2004	Cuffaro et al.	
				6,693,952	B1	2/2004	Chuah et al.	
				6,701,165	B1	3/2004	Ho et al.	
				6,704,571	B1	3/2004	Moon	
				6,711,400	B1	3/2004	Aura	
				6,717,908	B2	4/2004	Zehavi et al.	
				6,721,568	B1	4/2004	Gustavsson et al.	
				6,724,719	B1	4/2004	Tong et al.	
				6,731,602	B1	5/2004	Watanabe et al.	
				6,735,244	B1	5/2004	Hasegawa et al.	
				6,744,743	B2	6/2004	Walton et al.	
				6,748,220	B1	6/2004	Chow et al.	
				6,751,444	B1	6/2004	Meiyappan et al.	
				6,751,456	B2	6/2004	Bilgic	

(56)

References Cited

U.S. PATENT DOCUMENTS

6,754,511	B1	6/2004	Halford et al.	7,072,315	B1	7/2006	Liu et al.
6,763,009	B1	7/2004	Bedekar et al.	7,079,867	B2	7/2006	Chun
6,765,969	B1	7/2004	Vook et al.	7,085,574	B2	8/2006	Gaal et al.
6,776,165	B2	8/2004	Jin	7,095,708	B1	8/2006	Alamouti et al.
6,776,765	B2	8/2004	Soukup et al.	7,095,709	B2	8/2006	Walton et al.
6,778,513	B2	8/2004	Kasapi et al.	7,099,299	B2	8/2006	Liang et al.
6,785,341	B2	8/2004	Walton et al.	7,099,630	B2	8/2006	Brunner et al.
6,798,736	B1	9/2004	Black et al.	7,103,384	B2	9/2006	Chun
6,799,043	B2	9/2004	Tiedemann, Jr. et al.	7,106,319	B2	9/2006	Ishiyama
6,802,035	B2	10/2004	Catreux et al.	7,113,808	B2	9/2006	Hwang et al.
6,804,307	B1	10/2004	Popovic	7,120,134	B2	10/2006	Tiedemann, Jr. et al.
6,813,284	B2	11/2004	Vayanos et al.	7,120,395	B2	10/2006	Tong et al.
6,821,535	B2	11/2004	Nurmi et al.	7,126,928	B2	10/2006	Tiedemann, Jr. et al.
6,828,293	B1	12/2004	Hazenkamp et al.	7,131,086	B2	10/2006	Yamasaki et al.
6,829,293	B2	12/2004	Jones et al.	7,133,460	B2	11/2006	Bae et al.
6,831,943	B1	12/2004	Dabak et al.	7,139,328	B2	11/2006	Thomas et al.
6,842,487	B1	1/2005	Larsson	7,142,864	B2	11/2006	Laroia et al.
6,850,481	B2	2/2005	Wu et al.	7,145,940	B2	12/2006	Gore et al.
6,850,509	B2	2/2005	Lee et al.	7,145,959	B2	12/2006	Harel et al.
6,862,271	B2	3/2005	Medvedev et al.	7,149,199	B2	12/2006	Sung et al.
6,870,808	B1	3/2005	Liu et al.	7,149,238	B2	12/2006	Agee et al.
6,870,826	B1	3/2005	Ishizu et al.	7,151,761	B1	12/2006	Palenius
6,904,097	B2	6/2005	Agami et al.	7,151,936	B2	12/2006	Wager et al.
6,904,283	B2*	6/2005	Li et al. 455/450	7,154,936	B2	12/2006	Bjerke et al.
6,904,550	B2	6/2005	Sibecas et al.	7,155,236	B2	12/2006	Chen et al.
6,907,020	B2	6/2005	Periyalwar et al.	7,157,351	B2	1/2007	Cheng et al.
6,907,269	B2	6/2005	Yamaguchi et al.	7,161,971	B2	1/2007	Tiedemann, Jr. et al.
6,909,707	B2	6/2005	Rotstein et al.	7,164,649	B2	1/2007	Walton et al.
6,909,797	B2	6/2005	Romsdahl et al.	7,164,696	B2	1/2007	Sano et al.
6,917,602	B2	7/2005	Toskala et al.	7,167,916	B2	1/2007	Willen et al.
6,917,821	B2	7/2005	Kadous et al.	7,170,937	B2	1/2007	Zhou
6,927,728	B2	8/2005	Vook et al.	7,177,297	B2	2/2007	Agrawal et al.
6,928,047	B1	8/2005	Xia et al.	7,177,351	B2	2/2007	Kadous
6,934,266	B2	8/2005	Dulin et al.	7,180,627	B2	2/2007	Moylan et al.
6,934,275	B1	8/2005	Love et al.	7,181,170	B2	2/2007	Love et al.
6,934,340	B1	8/2005	Dollard	7,184,426	B2	2/2007	Padovani et al.
6,940,842	B2	9/2005	Proctor, Jr.	7,188,300	B2	3/2007	Eriksson et al.
6,940,845	B2	9/2005	Benveniste	7,197,282	B2	3/2007	Dent et al.
6,954,448	B2	10/2005	Farley et al.	7,200,177	B2	4/2007	Miyoshi et al.
6,954,481	B1	10/2005	Laroia et al.	7,209,712	B2	4/2007	Holtzman
6,954,622	B2	10/2005	Nelson et al.	7,215,979	B2	5/2007	Nakagawa et al.
6,961,364	B1	11/2005	Laroia et al.	7,230,942	B2	6/2007	Laroia et al.
6,963,543	B2	11/2005	Diep et al.	7,233,634	B1	6/2007	Hassell Sweatman et al.
6,970,682	B2	11/2005	Crilly, Jr. et al.	7,236,747	B1	6/2007	Meacham et al.
6,975,868	B2	12/2005	Joshi et al.	7,242,722	B2	7/2007	Krauss et al.
6,980,540	B1	12/2005	Laroia et al.	7,243,150	B2	7/2007	Sher et al.
6,985,434	B2	1/2006	Wu et al.	7,248,559	B2	7/2007	Ma et al.
6,985,453	B2	1/2006	Lundby et al.	7,248,841	B2	7/2007	Agee et al.
6,985,466	B1	1/2006	Yun et al.	7,254,158	B2	8/2007	Agrawal
6,985,498	B2	1/2006	Laroia et al.	7,257,167	B2	8/2007	Lau
6,987,746	B1	1/2006	Song	7,257,406	B2	8/2007	Ji et al.
6,993,342	B2	1/2006	Kuchibhotla et al.	7,257,423	B2	8/2007	Iochi et al.
7,002,900	B2	2/2006	Walton et al.	7,260,153	B2	8/2007	Nissani et al.
7,006,529	B2	2/2006	Alastalo et al.	7,280,467	B2	10/2007	Smee et al.
7,006,557	B2	2/2006	Subrahmanya et al.	7,289,570	B2	10/2007	Schmidl et al.
7,006,848	B2	2/2006	Ling et al.	7,289,585	B2	10/2007	Sandhu et al.
7,009,500	B2	3/2006	Rao et al.	7,290,195	B2	10/2007	Guo et al.
7,010,048	B1	3/2006	Shattil et al.	7,292,651	B2	11/2007	Li
7,013,143	B2	3/2006	Love et al.	7,292,863	B2	11/2007	Chen et al.
7,016,318	B2	3/2006	Pankaj et al.	7,295,509	B2	11/2007	Laroia et al.
7,016,319	B2	3/2006	Baum et al.	7,313,086	B2	12/2007	Aizawa et al.
7,016,425	B1	3/2006	Kraiem et al.	7,313,126	B2	12/2007	Yun et al.
7,020,110	B2	3/2006	Walton et al.	7,313,174	B2	12/2007	Alard et al.
7,023,880	B2	4/2006	El-Maleh et al.	7,313,407	B2	12/2007	Shapira et al.
7,039,356	B2	5/2006	Nguyen	7,327,812	B2	2/2008	Auer et al.
7,039,370	B2	5/2006	Laroia et al.	7,330,701	B2	2/2008	Mukkavilli et al.
7,042,856	B2	5/2006	Walton et al.	7,336,727	B2	2/2008	Mukkavilli et al.
7,042,857	B2	5/2006	Krishnan et al.	7,349,371	B2	3/2008	Schein et al.
7,047,006	B2	5/2006	Classon et al.	7,349,667	B2	3/2008	Magee et al.
7,050,402	B2	5/2006	Schmidl et al.	7,356,000	B2	4/2008	Oprescu-Surcobe et al.
7,050,405	B2	5/2006	Attar et al.	7,356,005	B2	4/2008	Derryberry et al.
7,050,759	B2	5/2006	Gaal et al.	7,356,073	B2	4/2008	Heikkila
7,054,301	B1	5/2006	Sousa et al.	7,359,327	B2	4/2008	Oshiba
7,061,898	B2	6/2006	Hashem et al.	7,363,055	B2	4/2008	Castrogiovanni et al.
7,069,009	B2	6/2006	Li et al.	7,366,223	B1	4/2008	Chen et al.
				7,366,253	B2	4/2008	Kim et al.
				7,366,520	B2	4/2008	Haustein et al.
				7,369,531	B2	5/2008	Cho et al.
				7,372,911	B1	5/2008	Lindskog et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,372,912 B2	5/2008	Seo et al.	2001/0055297 A1	12/2001	Benveniste et al.
7,379,489 B2	5/2008	Zuniga et al.	2002/0000948 A1	1/2002	Chun et al.
7,382,764 B2	6/2008	Uehaere	2002/0015405 A1	2/2002	Sepponen et al.
7,392,014 B2	6/2008	Baker et al.	2002/0018157 A1	2/2002	Zhang et al.
7,394,865 B2	7/2008	Borran et al.	2002/0039912 A1	4/2002	Yamaguchi et al.
7,403,745 B2	7/2008	Dominique et al.	2002/0044524 A1	4/2002	Laroia et al.
7,403,748 B1	7/2008	Keskitalo et al.	2002/0058525 A1	5/2002	Kasapi et al.
7,406,119 B2	7/2008	Yamano et al.	2002/0061742 A1	5/2002	Lapaille et al.
7,406,336 B2	7/2008	Astely et al.	2002/0077152 A1	6/2002	Johnson et al.
7,411,898 B2	8/2008	Erllich et al.	2002/0085521 A1	7/2002	Tripathi et al.
7,412,212 B2	8/2008	Hottinen et al.	2002/0090004 A1	7/2002	Rinchiuso
7,418,043 B2	8/2008	Shattil et al.	2002/0090024 A1	7/2002	Tan
7,418,246 B2	8/2008	Kim et al.	2002/0101839 A1	8/2002	Farley et al.
7,423,991 B2	9/2008	Cho et al.	2002/0122381 A1	9/2002	Wu et al.
7,426,426 B2	9/2008	Van Baren et al.	2002/0122403 A1	9/2002	Hashem et al.
7,428,426 B2	9/2008	Kiran et al.	2002/0128035 A1	9/2002	Jokinen et al.
7,433,661 B2	10/2008	Kogiantis et al.	2002/0147953 A1	10/2002	Catreux et al.
7,437,164 B2	10/2008	Agrawal et al.	2002/0159422 A1	10/2002	Li et al.
7,443,835 B2	10/2008	Lakshmi Narayanan et al.	2002/0160769 A1	10/2002	Gray et al.
7,447,270 B1	11/2008	Hottinen et al.	2002/0160781 A1	10/2002	Bark et al.
7,450,532 B2	11/2008	Chae et al.	2002/0168946 A1	11/2002	Aizawa et al.
7,450,548 B2	11/2008	Haustein et al.	2002/0172293 A1	11/2002	Kuchi et al.
7,460,466 B2	12/2008	Lee et al.	2002/0176398 A1	11/2002	Nidda
7,463,698 B2	12/2008	Fujii et al.	2002/0181571 A1	12/2002	Yamano et al.
7,468,943 B2	12/2008	Gu et al.	2002/0193146 A1	12/2002	Wallace et al.
7,469,011 B2	12/2008	Lin et al.	2003/0002464 A1	1/2003	Rezaifar et al.
7,471,963 B2	12/2008	Kim et al.	2003/0020651 A1	1/2003	Crilly, Jr. et al.
7,483,408 B2	1/2009	Bevan et al.	2003/0027579 A1	2/2003	Sydon
7,483,719 B2	1/2009	Kim et al.	2003/0035491 A1	2/2003	Walton et al.
7,486,408 B2	2/2009	Van Der Schaar et al.	2003/0036359 A1	2/2003	Dent et al.
7,486,735 B2	2/2009	Dubuc et al.	2003/0040283 A1	2/2003	Kawai et al.
7,492,788 B2	2/2009	Zhang et al.	2003/0043732 A1	3/2003	Walton et al.
7,499,393 B2	3/2009	Ozluturk et al.	2003/0043764 A1	3/2003	Kim et al.
7,508,748 B2	3/2009	Kadous	2003/0063579 A1	4/2003	Lee
7,508,842 B2	3/2009	Baum et al.	2003/0068983 A1	4/2003	Kim et al.
7,512,096 B2	3/2009	Kuzminskiy et al.	2003/0072254 A1	4/2003	Ma et al.
7,545,867 B1	6/2009	Lou et al.	2003/0072255 A1	4/2003	Ma et al.
7,548,506 B2	6/2009	Ma et al.	2003/0072280 A1	4/2003	McFarland et al.
7,551,546 B2*	6/2009	Ma et al. 370/208	2003/0072395 A1	4/2003	Jia et al.
7,551,564 B2	6/2009	Mattina	2003/0073409 A1	4/2003	Nobukiyo et al.
7,558,293 B2	7/2009	Choi et al.	2003/0073464 A1	4/2003	Giannakis et al.
7,567,621 B2	7/2009	Sampath et al.	2003/0076890 A1	4/2003	Hochwald et al.
7,573,900 B2	8/2009	Kim et al.	2003/0086371 A1	5/2003	Walton et al.
7,599,327 B2	10/2009	Zhuang	2003/0086393 A1	5/2003	Vasudevan et al.
7,616,955 B2	11/2009	Kim et al.	2003/0096579 A1	5/2003	Ito et al.
7,627,051 B2	12/2009	Shen et al.	2003/0103520 A1	6/2003	Chen et al.
7,664,061 B2	2/2010	Hottinen	2003/0109266 A1	6/2003	Rafiah et al.
7,676,007 B1	3/2010	Choi et al.	2003/0112745 A1	6/2003	Zhuang et al.
7,684,507 B2	3/2010	Levy	2003/0123414 A1	7/2003	Tong et al.
7,724,777 B2	5/2010	Sutivong et al.	2003/0125040 A1	7/2003	Walton et al.
7,768,979 B2	8/2010	Sutivong et al.	2003/0128658 A1	7/2003	Walton et al.
7,899,497 B2	3/2011	Kish et al.	2003/0133426 A1	7/2003	Schein et al.
7,916,624 B2	3/2011	Laroia et al.	2003/0142648 A1	7/2003	Semper
7,924,699 B2	4/2011	Laroia et al.	2003/0142729 A1	7/2003	Subrahmanya et al.
7,990,843 B2	8/2011	Laroia et al.	2003/0147371 A1	8/2003	Choi et al.
7,990,844 B2	8/2011	Laroia et al.	2003/0161281 A1	8/2003	Dulin et al.
8,014,271 B2	9/2011	Laroia et al.	2003/0161282 A1	8/2003	Medvedev et al.
8,045,512 B2	10/2011	Khandekar et al.	2003/0165189 A1	9/2003	Kadous et al.
8,095,141 B2	1/2012	Teague	2003/0181170 A1	9/2003	Sim
8,098,568 B2	1/2012	Laroia et al.	2003/0185310 A1	10/2003	Ketchum et al.
8,098,569 B2	1/2012	Laroia et al.	2003/0190897 A1	10/2003	Lei et al.
8,199,634 B2	6/2012	Laroia et al.	2003/0193915 A1	10/2003	Lee et al.
8,218,425 B2	7/2012	Laroia et al.	2003/0202491 A1	10/2003	Tiedemann, Jr. et al.
8,223,627 B2	7/2012	Laroia et al.	2003/0202560 A1	10/2003	Tiedemann, Jr. et al.
8,462,859 B2	6/2013	Sampath et al.	2003/0216156 A1	11/2003	Chun et al.
8,477,684 B2	7/2013	Khandekar et al.	2003/0228850 A1	12/2003	Hwang
8,582,509 B2	11/2013	Khandekar et al.	2003/0235255 A1	12/2003	Ketchum et al.
8,582,548 B2	11/2013	Gore et al.	2003/0236080 A1	12/2003	Kadous et al.
8,599,945 B2	12/2013	Sampath	2004/0001429 A1	1/2004	Ma et al.
2001/0021650 A1	9/2001	Bilgic et al.	2004/0001460 A1	1/2004	Bevan et al.
2001/0024427 A1	9/2001	Suzuki	2004/0002364 A1	1/2004	Trikkonen et al.
2001/0030948 A1	10/2001	Tiedemann, Jr.	2004/0009783 A1	1/2004	Miyoshi et al.
2001/0047424 A1	11/2001	Alastalo et al.	2004/0010623 A1	1/2004	Sher et al.
2001/0053140 A1	12/2001	Choi et al.	2004/0015692 A1	1/2004	Green et al.
2001/0055294 A1	12/2001	Motoyoshi	2004/0017785 A1	1/2004	Zelst et al.
			2004/0032443 A1	2/2004	Moylan et al.
			2004/0042558 A1	3/2004	Hwang et al.
			2004/0048609 A1	3/2004	Kosaka
			2004/0048630 A1	3/2004	Shapira et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2004/0054999	A1	3/2004	Willen et al.	2005/0025093	A1	2/2005	Yun et al.
2004/0057394	A1	3/2004	Holtzman et al.	2005/0030886	A1	2/2005	Wu et al.
2004/0058687	A1	3/2004	Kim et al.	2005/0030964	A1	2/2005	Tiedemann, Jr. et al.
2004/0066754	A1	4/2004	Hottinen et al.	2005/0034079	A1	2/2005	Gunasekar et al.
2004/0066761	A1	4/2004	Giannakis et al.	2005/0041611	A1	2/2005	Sandhu et al.
2004/0066772	A1	4/2004	Moon et al.	2005/0041618	A1	2/2005	Wei et al.
2004/0067756	A1	4/2004	Wager et al.	2005/0041750	A1	2/2005	Lau et al.
2004/0072565	A1	4/2004	Nobukiyo et al.	2005/0041775	A1	2/2005	Batzinger et al.
2004/0076185	A1	4/2004	Kim et al.	2005/0044206	A1	2/2005	Johansson et al.
2004/0077345	A1	4/2004	Turner et al.	2005/0047517	A1	3/2005	Georgios et al.
2004/0077379	A1	4/2004	Smith et al.	2005/0052991	A1	3/2005	Kadous
2004/0081073	A1	4/2004	Walton et al.	2005/0053081	A1	3/2005	Andersson et al.
2004/0087325	A1	5/2004	Cheng et al.	2005/0053151	A1	3/2005	Lin et al.
2004/0095907	A1	5/2004	Agee et al.	2005/0063298	A1	3/2005	Ling et al.
2004/0097215	A1	5/2004	Abe et al.	2005/0068921	A1	3/2005	Liu
2004/0097240	A1	5/2004	Chen et al.	2005/0073976	A1	4/2005	Fujii
2004/0098505	A1	5/2004	Clemmensen et al.	2005/0084000	A1	4/2005	Krauss et al.
2004/0105489	A1	6/2004	Kim et al.	2005/0085195	A1	4/2005	Tong et al.
2004/0114618	A1	6/2004	Tong et al.	2005/0085236	A1	4/2005	Gerlach et al.
2004/0120411	A1	6/2004	Walton et al.	2005/0111397	A1	5/2005	Attar et al.
2004/0125792	A1	7/2004	Bradbury et al.	2005/0113100	A1	5/2005	Oprescu-Surcobe et al.
2004/0128605	A1	7/2004	Sibecas et al.	2005/0122898	A1	6/2005	Jang et al.
2004/0131007	A1	7/2004	Smee et al.	2005/0128683	A1	6/2005	Watanabe et al.
2004/0131008	A1	7/2004	Zuniga et al.	2005/0128983	A1	6/2005	Kim et al.
2004/0131038	A1	7/2004	Kim et al.	2005/0135324	A1	6/2005	Kim et al.
2004/0131110	A1	7/2004	Alard et al.	2005/0135498	A1	6/2005	Yee
2004/0136344	A1	7/2004	Kim et al.	2005/0141624	A1	6/2005	Lakshmiipathi et al.
2004/0136349	A1*	7/2004	Walton et al. 370/338	2005/0147024	A1	7/2005	Jung et al.
2004/0156328	A1	8/2004	Walton et al.	2005/0147025	A1	7/2005	Auer et al.
2004/0160914	A1	8/2004	Sarkar et al.	2005/0152484	A1	7/2005	Sandhu et al.
2004/0160933	A1	8/2004	Odenwalder et al.	2005/0157807	A1	7/2005	Shim et al.
2004/0162083	A1	8/2004	Chen et al.	2005/0159162	A1	7/2005	Park
2004/0165564	A1	8/2004	Kim et al.	2005/0164709	A1	7/2005	Balasuubramanian et al.
2004/0166867	A1	8/2004	Hawe et al.	2005/0165949	A1	7/2005	Teague
2004/0166887	A1	8/2004	Laroia et al.	2005/0174981	A1	8/2005	Heath et al.
2004/0170152	A1	9/2004	Nagao et al.	2005/0175070	A1	8/2005	Grob et al.
2004/0170157	A1	9/2004	Kim et al.	2005/0180311	A1	8/2005	Wang et al.
2004/0171384	A1	9/2004	Holma et al.	2005/0180313	A1*	8/2005	Kim et al. 370/208
2004/0171385	A1	9/2004	Hausestein et al.	2005/0181799	A1	8/2005	Laroia et al.
2004/0178954	A1	9/2004	Vook et al.	2005/0192011	A1	9/2005	Hong et al.
2004/0179480	A1	9/2004	Attar et al.	2005/0195733	A1	9/2005	Walton et al.
2004/0179494	A1	9/2004	Attar et al.	2005/0195852	A1	9/2005	Vayanos et al.
2004/0179506	A1	9/2004	Padovani et al.	2005/0195886	A1	9/2005	Lampinen et al.
2004/0179627	A1	9/2004	Ketchum et al.	2005/0201296	A1	9/2005	Vannithamby et al.
2004/0181569	A1	9/2004	Attar et al.	2005/0204247	A1	9/2005	Guo et al.
2004/0185792	A1	9/2004	Alexiou et al.	2005/0207367	A1	9/2005	Onggosanusi et al.
2004/0190640	A1	9/2004	Dubuc et al.	2005/0215196	A1	9/2005	Krishnan et al.
2004/0202257	A1	10/2004	Mehta et al.	2005/0215251	A1	9/2005	Krishnan et al.
2004/0208138	A1	10/2004	Hayashi et al.	2005/0226204	A1	10/2005	Uehara et al.
2004/0218520	A1	11/2004	Aizawa et al.	2005/0239465	A1	10/2005	Lee et al.
2004/0219819	A1	11/2004	Di Mascio et al.	2005/0243791	A1	11/2005	Park et al.
2004/0219919	A1	11/2004	Whinnett et al.	2005/0246548	A1	11/2005	Laitinen
2004/0224711	A1	11/2004	Panchal et al.	2005/0249266	A1	11/2005	Brown et al.
2004/0228267	A1	11/2004	Agrawal et al.	2005/0254416	A1	11/2005	Laroia et al.
2004/0228313	A1	11/2004	Cheng et al.	2005/0254467	A1	11/2005	Li et al.
2004/0229615	A1	11/2004	Agrawal et al.	2005/0254477	A1	11/2005	Lee et al.
2004/0240419	A1	12/2004	Abrishamkar et al.	2005/0254556	A1	11/2005	Fujii et al.
2004/0240572	A1	12/2004	Brutel et al.	2005/0259005	A1	11/2005	Chiang et al.
2004/0248604	A1	12/2004	Vaidyanathan et al.	2005/0259723	A1	11/2005	Blanchard et al.
2004/0252529	A1	12/2004	Huber et al.	2005/0259757	A1	11/2005	Wu et al.
2004/0252629	A1	12/2004	Hasegawa et al.	2005/0265220	A1	12/2005	Erlich et al.
2004/0252655	A1	12/2004	Lim et al.	2005/0265293	A1	12/2005	Ro et al.
2004/0252662	A1	12/2004	Cho	2005/0265470	A1	12/2005	Kishigami et al.
2004/0257979	A1	12/2004	Ro et al.	2005/0271012	A1	12/2005	Agrawal et al.
2004/0264507	A1	12/2004	Cho et al.	2005/0276347	A1	12/2005	Mujtaba et al.
2004/0264585	A1	12/2004	Borran et al.	2005/0276348	A1	12/2005	Vandenameele
2004/0264593	A1	12/2004	Shim et al.	2005/0277423	A1	12/2005	Sandhu et al.
2005/0002412	A1	1/2005	Sagfors et al.	2005/0281029	A1	12/2005	Inamoto et al.
2005/0002440	A1	1/2005	Alamouti et al.	2005/0281290	A1	12/2005	Khandekar et al.
2005/0002467	A1	1/2005	Seo et al.	2005/0282500	A1	12/2005	Wang et al.
2005/0002468	A1	1/2005	Walton et al.	2005/0286408	A1	12/2005	Jin et al.
2005/0003782	A1	1/2005	Wintzell	2005/0289256	A1	12/2005	Cudak et al.
2005/0008091	A1	1/2005	Boutros et al.	2006/0002451	A1	1/2006	Fukuta et al.
2005/0009486	A1	1/2005	Al-Dhahir et al.	2006/0013285	A1	1/2006	Kobayashi et al.
2005/0013263	A1	1/2005	Kim et al.	2006/0018336	A1	1/2006	Sutivong et al.
				2006/0018347	A1	1/2006	Agrawal
				2006/0018397	A1	1/2006	Sampath et al.
				2006/0026344	A1	2/2006	Sun Hsu et al.
				2006/0029289	A1	2/2006	Yamaguchi et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0034164	A1	2/2006	Ozluturk et al.	2007/0060178	A1	3/2007	Gorokhov et al.
2006/0034173	A1	2/2006	Teague et al.	2007/0064669	A1	3/2007	Classon et al.
2006/0039332	A1	2/2006	Kotzin	2007/0070952	A1	3/2007	Yoon et al.
2006/0039344	A1	2/2006	Khan	2007/0071147	A1	3/2007	Sampath et al.
2006/0039500	A1	2/2006	Yun et al.	2007/0097853	A1	5/2007	Khandekar et al.
2006/0040655	A1	2/2006	Kim et al.	2007/0097889	A1	5/2007	Wang et al.
2006/0045003	A1	3/2006	Choi et al.	2007/0097897	A1	5/2007	Teague et al.
2006/0050770	A1	3/2006	Wallace et al.	2007/0097908	A1	5/2007	Khandekar et al.
2006/0056340	A1	3/2006	Hottinen et al.	2007/0097909	A1	5/2007	Khandekar et al.
2006/0057958	A1	3/2006	Ngo et al.	2007/0097910	A1	5/2007	Ji et al.
2006/0067421	A1	3/2006	Walton et al.	2007/0097922	A1	5/2007	Parekh et al.
2006/0078075	A1	4/2006	Stamoulis et al.	2007/0097927	A1	5/2007	Gorokhov et al.
2006/0083159	A1	4/2006	Laroia et al.	2007/0097942	A1	5/2007	Gorokhov et al.
2006/0083183	A1	4/2006	Teague et al.	2007/0097981	A1	5/2007	Papasakellariou et al.
2006/0089104	A1	4/2006	Kaikkonen et al.	2007/0098050	A1	5/2007	Khandekar et al.
2006/0092054	A1	5/2006	Li et al.	2007/0098120	A1	5/2007	Wang
2006/0093065	A1	5/2006	Thomas et al.	2007/0099666	A1	5/2007	Astely et al.
2006/0104333	A1	5/2006	Rainbolt et al.	2007/0110172	A1	5/2007	Faulkner et al.
2006/0104381	A1	5/2006	Menon et al.	2007/0115795	A1	5/2007	Gore et al.
2006/0107171	A1	5/2006	Skraparlis	2007/0149194	A1	6/2007	Das et al.
2006/0109814	A1	5/2006	Kuzminskiy et al.	2007/0149228	A1	6/2007	Das
2006/0111054	A1	5/2006	Pan et al.	2007/0159969	A1	7/2007	Das et al.
2006/0111148	A1	5/2006	Mukkavilli et al.	2007/0160115	A1	7/2007	Palanki et al.
2006/0114858	A1	6/2006	Walton et al.	2007/0165738	A1	7/2007	Barriac et al.
2006/0120469	A1	6/2006	Maltsev et al.	2007/0177631	A1	8/2007	Popovic et al.
2006/0120471	A1	6/2006	Learned et al.	2007/0177681	A1	8/2007	Choi et al.
2006/0126491	A1	6/2006	Ro et al.	2007/0183303	A1	8/2007	Pi et al.
2006/0133269	A1	6/2006	Prakash et al.	2007/0183386	A1	8/2007	Muharemovic et al.
2006/0133455	A1	6/2006	Agrawal et al.	2007/0207812	A1	9/2007	Borran et al.
2006/0133521	A1	6/2006	Sampath et al.	2007/0211616	A1	9/2007	Khandekar et al.
2006/0140289	A1	6/2006	Mandyam et al.	2007/0211667	A1	9/2007	Agrawal et al.
2006/0153239	A1	7/2006	Julian et al.	2007/0230324	A1	10/2007	Li et al.
2006/0155534	A1	7/2006	Lin et al.	2007/0242653	A1	10/2007	Yang et al.
2006/0156199	A1	7/2006	Palanki et al.	2007/0263743	A1	11/2007	Lee et al.
2006/0172704	A1	8/2006	Nishio et al.	2007/0280336	A1	12/2007	Zhang et al.
2006/0189321	A1	8/2006	Oh et al.	2007/0281702	A1	12/2007	Lim et al.
2006/0203708	A1	9/2006	Sampath et al.	2008/0039129	A1	2/2008	Li et al.
2006/0203794	A1	9/2006	Sampath et al.	2008/0063099	A1	3/2008	Laroia et al.
2006/0203891	A1	9/2006	Sampath et al.	2008/0095223	A1	4/2008	Tong et al.
2006/0203932	A1	9/2006	Palanki et al.	2008/0095262	A1	4/2008	Ho et al.
2006/0209670	A1	9/2006	Gorokhov et al.	2008/0151829	A1	6/2008	Khandekar et al.
2006/0209732	A1	9/2006	Gorokhov et al.	2008/0181139	A1	7/2008	Rangarajan et al.
2006/0209754	A1	9/2006	Ji et al.	2008/0214222	A1	9/2008	Atarashi et al.
2006/0209764	A1	9/2006	Kim et al.	2008/0253279	A1	10/2008	Ma et al.
2006/0209973	A1	9/2006	Gorokhov et al.	2008/0267157	A1	10/2008	Lee et al.
2006/0215777	A1	9/2006	Krishnamoorthi	2008/0299983	A1	12/2008	Kwak et al.
2006/0218459	A1	9/2006	Hedberg	2009/0003466	A1	1/2009	Taherzadehboroujeni et al.
2006/0223449	A1	10/2006	Sampath et al.	2009/0010351	A1	1/2009	Laroia et al.
2006/0233124	A1	10/2006	Palanki et al.	2009/0022098	A1	1/2009	Novak et al.
2006/0233131	A1	10/2006	Gore et al.	2009/0041150	A1	2/2009	Tsai et al.
2006/0233222	A1	10/2006	Reial et al.	2009/0110103	A1	4/2009	Maltsev et al.
2006/0262754	A1	11/2006	Andersson et al.	2009/0129501	A1	5/2009	Mehta et al.
2006/0270427	A1	11/2006	Shida et al.	2009/0180459	A1	7/2009	Orlik et al.
2006/0274836	A1	12/2006	Sampath et al.	2009/0197646	A1	8/2009	Tamura et al.
2006/0280114	A1	12/2006	Osseiran et al.	2009/0201826	A1	8/2009	Gorokhov et al.
2006/0285485	A1	12/2006	Agrawal et al.	2009/0213750	A1	8/2009	Gorokhov et al.
2006/0285515	A1	12/2006	Julian et al.	2009/0213950	A1	8/2009	Gorokhov et al.
2006/0286974	A1	12/2006	Gore et al.	2009/0262641	A1	10/2009	Laroia et al.
2006/0286982	A1	12/2006	Prakash et al.	2009/0262699	A1	10/2009	Wengertter et al.
2006/0286995	A1	12/2006	Onggosanusi et al.	2009/0285163	A1	11/2009	Zhang et al.
2006/0291371	A1	12/2006	Sutivong et al.	2009/0287977	A1	11/2009	Chang et al.
2006/0292989	A1	12/2006	Gerlach et al.	2010/0002570	A9	1/2010	Walton et al.
2007/0004430	A1	1/2007	Hyun et al.	2010/0135242	A1	6/2010	Nam et al.
2007/0005749	A1	1/2007	Sampath	2010/0220800	A1	9/2010	Erell et al.
2007/0009011	A1	1/2007	Coulson et al.	2010/0232384	A1	9/2010	Farajidana et al.
2007/0019596	A1	1/2007	Barriac et al.	2010/0238902	A1	9/2010	Ji et al.
2007/0025345	A1	2/2007	Bachl et al.	2010/0254263	A1	10/2010	Chen et al.
2007/0041311	A1	2/2007	Baum et al.	2011/0064070	A1	3/2011	Gore et al.
2007/0041404	A1	2/2007	Palanki et al.	2011/0235733	A1	9/2011	Laroia et al.
2007/0041457	A1	2/2007	Kadous et al.	2011/0235745	A1	9/2011	Laroia et al.
2007/0047485	A1	3/2007	Gorokhov et al.	2011/0235746	A1	9/2011	Laroia et al.
2007/0047495	A1	3/2007	Ji et al.	2011/0235747	A1	9/2011	Laroia et al.
2007/0049218	A1	3/2007	Gorokhov et al.	2011/0255518	A9	10/2011	Agrawal et al.
2007/0053282	A1	3/2007	Tong et al.	2011/0306291	A1	12/2011	Ma et al.
2007/0053383	A1	3/2007	Choi et al.	2012/0002623	A1	1/2012	Khandekar et al.
				2012/0063441	A1	3/2012	Palanki
				2012/0120925	A1	5/2012	Kadous et al.
				2012/0140798	A1	6/2012	Kadous et al.
				2012/0140838	A1	6/2012	Kadous et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0016678 A1 1/2013 Laroia et al.
 2013/0208681 A1 8/2013 Gore et al.
 2013/0287138 A1 10/2013 Ma et al.
 2013/0315200 A1 11/2013 Gorokhov et al.
 2014/0247898 A1 9/2014 Laroia et al.
 2014/0376518 A1 12/2014 Palanki et al.

FOREIGN PATENT DOCUMENTS

CA 2540688 5/2005
 CA 2577369 3/2006
 CL 14001993 12/1994
 CL 8461997 1/1998
 CL 9531997 1/1998
 CL 27102004 8/2005
 CL 22892004 9/2005
 CL 30862004 10/2005
 CL 29932005 5/2006
 CL 29012006 10/2006
 CL 29022006 10/2006
 CL 29032006 10/2006
 CL 29042006 10/2006
 CL 29062006 10/2006
 CL 29082006 10/2006
 CL 15202006 12/2006
 CL 22032006 2/2007
 CL 15212006 3/2007
 CL 14922006 4/2007
 CL 14892006 5/2007
 CL 14902006 5/2007
 CL 46151 12/2009
 CL 29072006 1/2010
 CN 1252919 5/2000
 CN 1267437 9/2000
 CN 1267437 A 9/2000
 CN 1284795 2/2001
 CN 1296682 5/2001
 CN 1344451 4/2002
 CN 1346221 4/2002
 CN 1383631 12/2002
 CN 1386344 12/2002
 CN 1402916 A 3/2003
 CN 1424835 6/2003
 CN 1467938 A 1/2004
 CN 1487755 A 4/2004
 CN 1520220 8/2004
 CN 1525678 9/2004
 CN 1636346 7/2005
 CN 1642051 A 7/2005
 CN 1642335 A 7/2005
 CN 1647436 7/2005
 DE 19800653 A1 7/1999
 DE 19800953 7/1999
 DE 19957288 5/2001
 DE 10240138 8/2003
 DE 10254384 6/2004
 EP 0488976 6/1992
 EP 0568291 A2 11/1993
 EP 0740431 A1 10/1996
 EP 0786889 A1 7/1997
 EP 0805576 A2 11/1997
 EP 0807989 A1 11/1997
 EP 0844796 5/1998
 EP 0981222 A2 2/2000
 EP 1001570 A2 5/2000
 EP 1047209 A1 10/2000
 EP 1061687 12/2000
 EP 1091516 A1 4/2001
 EP 1093241 A1 4/2001
 EP 1148673 A2 10/2001
 EP 1172983 A2 1/2002
 EP 1180907 A2 2/2002
 EP 1187506 A1 3/2002
 EP 1204217 5/2002

EP 1255369 11/2002
 EP 1267513 12/2002
 EP 1074099 B1 2/2003
 EP 1286490 2/2003
 EP 1335504 A2 8/2003
 EP 1351538 A1 10/2003
 EP 1376920 1/2004
 EP 1392073 A1 2/2004
 EP 1434365 A2 6/2004
 EP 1441469 A2 7/2004
 EP 1445873 A2 8/2004
 EP 1465449 A1 10/2004
 EP 1478204 A2 11/2004
 EP 1507421 2/2005
 EP 1513356 A2 3/2005
 EP 1531575 A2 5/2005
 EP 1533950 5/2005
 EP 1538863 6/2005
 EP 1542488 A1 6/2005
 EP 1601149 A2 11/2005
 EP 1643669 A1 4/2006
 EP 1898542 A1 3/2008
 EP 1941693 7/2011
 FR 2584884 1/1987
 GB 2279540 A 1/1995
 GB 2348776 10/2000
 GB 2412541 A 9/2005
 IL 167573 2/2011
 IL 201872 5/2012
 JP H04111544 A 4/1992
 JP 04301931 A 10/1992
 JP H0746248 A 2/1995
 JP 7336323 A 12/1995
 JP 8116329 A 5/1996
 JP 08288927 11/1996
 JP 9008725 A 1/1997
 JP H09501548 A 2/1997
 JP 9131342 5/1997
 JP 9182148 A 7/1997
 JP 09214404 8/1997
 JP 9284200 A 10/1997
 JP 10117162 5/1998
 JP H10210000 A 8/1998
 JP 10322304 12/1998
 JP H11168453 A 6/1999
 JP 11191756 A 7/1999
 JP 11196109 7/1999
 JP 11508417 T 7/1999
 JP 11239155 A 8/1999
 JP 11298954 10/1999
 JP 11331927 A 11/1999
 JP 2000022618 A 1/2000
 JP 2000102065 A 4/2000
 JP 2000184425 6/2000
 JP 2000511750 A 9/2000
 JP 2000332724 A 11/2000
 JP 2001016644 A2 1/2001
 JP 2001045573 A 2/2001
 JP 2001057545 A 2/2001
 JP 2001156732 A 6/2001
 JP 2001238269 8/2001
 JP 2001245355 A 9/2001
 JP 2001249802 A 9/2001
 JP 2001285927 A 10/2001
 JP 2001521698 A 11/2001
 JP 2001526012 12/2001
 JP 2002026790 1/2002
 JP 2002111556 A 4/2002
 JP 2002515203 T 5/2002
 JP 2002290148 A 10/2002
 JP 2002534925 A 10/2002
 JP 2002534941 10/2002
 JP 2002538696 A 11/2002
 JP 200318054 1/2003
 JP 2003032218 1/2003
 JP 2003500909 1/2003
 JP 200369472 3/2003
 JP 20030101515 4/2003
 JP 2003169367 A 6/2003

(56) References Cited					
FOREIGN PATENT DOCUMENTS					
JP	2003174426	6/2003	RU	2141168	11/1999
JP	2003199173 A	7/2003	RU	2141706 C1	11/1999
JP	2003520523	7/2003	RU	2159007 C2	11/2000
JP	2003235072 A	8/2003	RU	2162275 C2	1/2001
JP	2003249907 A	9/2003	RU	2183387 C2	6/2002
JP	2003292667 A	10/2003	RU	2192094 C1	10/2002
JP	2003318857 A	11/2003	RU	2197778 C2	1/2003
JP	2003347985 A	12/2003	RU	2201033 C2	3/2003
JP	2003348047	12/2003	RU	2207723 C1	6/2003
JP	2003536308 A	12/2003	RU	2208913	7/2003
JP	2004007643 A	1/2004	RU	2210866 C2	8/2003
JP	2004023716	1/2004	RU	2216101 C2	11/2003
JP	2004048716	2/2004	RU	2216103 C2	11/2003
JP	200472457	3/2004	RU	2216105 C2	11/2003
JP	2004072157 A	3/2004	RU	2225080 C2	2/2004
JP	2004096142	3/2004	RU	2235429	8/2004
JP	2004507151 A	3/2004	RU	2235432 C2	8/2004
JP	2004507950 A	3/2004	RU	2237379 C2	9/2004
JP	2004153676	5/2004	RU	2238611 C1	10/2004
JP	2004158901 A	6/2004	RU	2242091 C2	12/2004
JP	2004162388 A	6/2004	RU	2003125268	2/2005
JP	2004201296 A	7/2004	RU	2285388	3/2005
JP	2004215022 A	7/2004	RU	2250564	4/2005
JP	20040194262 A	7/2004	RU	2257008	7/2005
JP	2004221972	8/2004	RU	2267224	12/2005
JP	2004266818	9/2004	RU	2005129079	2/2006
JP	2004529524 T	9/2004	RU	2285338 C2	10/2006
JP	2004297276 A	10/2004	RU	2285351 C2	10/2006
JP	2004297370 A	10/2004	RU	2292655	1/2007
JP	2004297756	10/2004	RU	2335864 C2	10/2008
JP	2004534456	11/2004	RU	2349043 C2	3/2009
JP	2004535106 A	11/2004	SU	1320883	6/1987
JP	2005006337	1/2005	TW	508960 B	11/2002
JP	2005020530 A	1/2005	TW	510132	11/2002
JP	2005502218 T	1/2005	TW	200302642	8/2003
JP	2005506757	3/2005	TW	200401572	1/2004
JP	2005110130 A	4/2005	TW	1232040	5/2005
JP	2005130491 A	5/2005	TW	248266	1/2006
JP	2005167502 A	6/2005	TW	200718128	5/2007
JP	2005197772	7/2005	WO	WO9408432	4/1994
JP	2005203961	7/2005	WO	WO-9521494 A1	8/1995
JP	2005521327	7/2005	WO	WO9613920 A1	5/1996
JP	2005521358	7/2005	WO	WO9701256	1/1997
JP	2005236678 A	9/2005	WO	WO9737456 A2	10/1997
JP	2006505172	2/2006	WO	WO-9746033 A2	12/1997
JP	2006505230 A	2/2006	WO	WO9800946	1/1998
JP	2006506860 A	2/2006	WO	WO-9814026 A1	4/1998
JP	2006211537 A	8/2006	WO	WO9837706 A2	8/1998
JP	2006518173 A	8/2006	WO	WO9848581 A1	10/1998
JP	2006524930 A	11/2006	WO	WO9853561	11/1998
JP	2007500486 A	1/2007	WO	WO9854919 A2	12/1998
JP	2007503790	2/2007	WO	WO-9941871 A1	8/1999
JP	2007519281	7/2007	WO	WO-9944313 A1	9/1999
JP	2007520309 A	7/2007	WO	WO-9944383 A1	9/1999
JP	2007525043 T	8/2007	WO	WO-9952250 A1	10/1999
JP	2007527127	9/2007	WO	WO9953713 A2	10/1999
JP	2008505587 A	2/2008	WO	WO-9959265 A1	11/1999
JP	2008535398	8/2008	WO	WO9960729 A1	11/1999
JP	4188372 B2	11/2008	WO	0004728	1/2000
JP	2008546314	12/2008	WO	WO0002397	1/2000
JP	4694628	6/2011	WO	WO0033503 A1	6/2000
KR	0150275 B1	11/1998	WO	0051389 A1	8/2000
KR	20000060428	10/2000	WO	WO0070897	11/2000
KR	100291476 B1	3/2001	WO	WO0101596	1/2001
KR	20010056333	4/2001	WO	WO0117125 A1	3/2001
KR	20010087715 A	9/2001	WO	WO0126269	4/2001
KR	20030007965	1/2003	WO	WO-0139523 A2	5/2001
KR	20030035969 A	5/2003	WO	WO0145300	6/2001
KR	20040063057	7/2004	WO	WO0148989	7/2001
KR	200471652	8/2004	WO	WO-0158054 A1	8/2001
KR	20040103441 A	12/2004	WO	WO-0160106 A1	8/2001
KR	20050061559	6/2005	WO	0165637 A2	9/2001
KR	20050063826 A	6/2005	WO	WO0169814 A1	9/2001
KR	100606099	7/2006	WO	0182544	11/2001
RU	95121152	12/1997	WO	WO0182543	11/2001
			WO	WO-0189112 A1	11/2001
			WO	0195427 A2	12/2001
			WO	WO0193505	12/2001
			WO	WO-0204936 A1	1/2002

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO0207375	A1	1/2002	WO	WO2004095730	A1	11/2004
WO	0215432	A1	2/2002	WO	WO2004095851		11/2004
WO	WO0215616	A2	2/2002	WO	WO2004095854		11/2004
WO	WO0219746		3/2002	WO	WO2004098072		11/2004
WO	WO-0231991	A2	4/2002	WO	WO2004098222		11/2004
WO	WO-0233848	A2	4/2002	WO	WO2004102815		11/2004
WO	0245293	A2	6/2002	WO	WO2004102816	A2	11/2004
WO	WO0245456	A1	6/2002	WO	2004114564	A1	12/2004
WO	WO0249305		6/2002	WO	2004114615	A1	12/2004
WO	WO0249306		6/2002	WO	WO2004105272	A1	12/2004
WO	WO0249385	A2	6/2002	WO	WO2004114549		12/2004
WO	WO02060138		8/2002	WO	WO2005002253	A1	1/2005
WO	WO02065675		8/2002	WO	2005011163	A1	2/2005
WO	WO02082689	A2	10/2002	WO	2005018270		2/2005
WO	WO02082743		10/2002	WO	WO-2005015795	A1	2/2005
WO	WO02089434	A1	11/2002	WO	WO-2005015797	A1	2/2005
WO	WO02093782	A1	11/2002	WO	WO2005015810		2/2005
WO	WO02093819		11/2002	WO	WO2005015941		2/2005
WO	WO02100027	A1	12/2002	WO	WO2005020488	A1	3/2005
WO	WO03001596		1/2003	WO	WO2005020490		3/2005
WO	WO03001761	A1	1/2003	WO	WO2005022811		3/2005
WO	WO-03001981	A2	1/2003	WO	WO2005025110	A2	3/2005
WO	WO-03003617	A2	1/2003	WO	WO2005032004	A1	4/2005
WO	WO03019819		3/2003	WO	2005043780	A1	5/2005
WO	WO03030414		4/2003	WO	WO2005043855		5/2005
WO	WO03034644	A1	4/2003	WO	WO2005046080		5/2005
WO	WO03043262		5/2003	WO	2005055465	A1	6/2005
WO	WO03043369		5/2003	WO	WO2005055484	A1	6/2005
WO	03049409	A2	6/2003	WO	WO2005055527		6/2005
WO	WO03058871	A1	7/2003	WO	WO2005060192	A1	6/2005
WO	03069816	A2	8/2003	WO	WO2005065062		7/2005
WO	WO03067783		8/2003	WO	WO-2005069538	A1	7/2005
WO	WO03069832	A1	8/2003	WO	WO2005074184		8/2005
WO	WO03073646		9/2003	WO	2005086440	A1	9/2005
WO	WO03075479		9/2003	WO	WO2005096538		10/2005
WO	WO03085876		10/2003	WO	WO2005122628		12/2005
WO	WO03088538	A1	10/2003	WO	2006007292	A2	1/2006
WO	WO03094384		11/2003	WO	WO2006019710		2/2006
WO	WO03103331		12/2003	WO	WO2006026344		3/2006
WO	WO04002047	A1	12/2003	WO	WO2006044487		4/2006
WO	WO2004004370		1/2004	WO	2006062356	A1	6/2006
WO	WO2004008671	A1	1/2004	WO	2006069301		6/2006
WO	WO-2004008681	A1	1/2004	WO	WO2006069300		6/2006
WO	WO2004015912		2/2004	WO	WO2006069397		6/2006
WO	WO2004016007		2/2004	WO	WO2006077696		7/2006
WO	WO2004021605	A1	3/2004	WO	WO-2006096784	A1	9/2006
WO	WO2004023834	A1	3/2004	WO	WO-2006099349	A1	9/2006
WO	2004028037	A1	4/2004	WO	WO-2006099545	A1	9/2006
WO	WO-2004030238	A1	4/2004	WO	WO-2006099577	A1	9/2006
WO	WO-2004032443	A1	4/2004	WO	WO-2006127544	A2	11/2006
WO	2004038984	A2	5/2004	WO	WO2006134032		12/2006
WO	WO2004004827		5/2004	WO	WO2006138196		12/2006
WO	WO2004038954		5/2004	WO	WO2006138573		12/2006
WO	WO-2004038972	A1	5/2004	WO	WO2006138581	A2	12/2006
WO	WO-2004038988	A2	5/2004	WO	2007022430	A2	2/2007
WO	WO-2004040690	A2	5/2004	WO	WO2007024934		3/2007
WO	WO2004047354		6/2004	WO	WO-2007024935	A2	3/2007
WO	WO2004049618	A1	6/2004	WO	WO2007025160		3/2007
WO	WO-2004051872	A2	6/2004	WO	WO-2007051159	A2	5/2007
WO	2004056022	A2	7/2004				
WO	WO2004062255		7/2004				
WO	WO2004064294		7/2004				
WO	WO2004064295		7/2004				
WO	WO2004068721	A2	8/2004				
WO	WO-2004073276	A1	8/2004				
WO	WO2005066520		8/2004				
WO	WO2004075023		9/2004				
WO	WO2004075442		9/2004				
WO	WO2004075448		9/2004				
WO	WO2004075468		9/2004				
WO	WO2004075596		9/2004				
WO	WO2004077850	A2	9/2004				
WO	WO2004084509		9/2004				
WO	WO-2004086706	A1	10/2004				
WO	WO2004086711		10/2004				

OTHER PUBLICATIONS

B. Sklar: "The process of thus correcting the channel-induced distortion is called equalization", Digital Communications, PTR Prentice Hall, Upper Saddle River, New Jersey, 1998, Formatting and Baseband Transmission, Chap. 2, Section 2.11.2, pp. 104-105.

Bahai, Saltzberg: "System Architecture," Multi-Carrier Digital Communications, Kluwer Academic, New York, NY, XP-002199501, 1999, pp. 17-21.

Bingham: "Other Types of MCM," ADSL, VDSL, and Multicarrier Modulation, John Wiley & Sons, New York, XP-002199502, 2000, pp. 111-113.

Carl R. Nassar, Balasubramaniam Natarajan and Steve Shattil: Introduction of Carrier Interference to Spread Spectrum Multiple Access, Apr. 1999, IEEE, pp. 1-5.

Chennakeshu, et al. "A Comparison of Diversity Schemes for a Mixed-Mode Slow Frequency-Hopped Cellular System," IEEE, 1993, pp. 1749-1753.

(56)

References Cited

OTHER PUBLICATIONS

- Chennakeshu, et al. "Capacity Analysis of a TDMA-Based Slow-Frequency-Hopped Cellular System," IEEE Transaction on Vehicular Technology, vol. 45., No. 3 Aug. 1996, pp. 531-542.
- Chiani, et al. "Outage Evaluation for Slow Frequency-Hopping Mobile Radio Systems" IEEE Transactions on Communications, vol. 47, No. 12, pp. 1865-1874, Dec. 1999.
- Choi, et al., "Design of the Optimum Pilot Pattern for Channel Estimation of OFDM Systems," Global Telecommunications Conference, IEEE Communications Society, Globecom, Dallas, Texas (2004), p. 3661-3665.
- Czylwik: "Comparison Between Adaptive OFDM and Single Carrier Modulation with Frequency Domain Equalization," IEEE 47th Vehicular Technology Conference, vol. 2, May 4-7, 1997, pp. 865-869.
- Das, et al. "On the Reverse Link Interference Structure for Next Generation Cellular Systems," European Microwave Conference, Oct. 11, 2004, pp. 3068-3072.
- Dinis, et al., "A Multiple Access Scheme for the Uplink of Broadband Wireless Systems," IEEE Global Telecommunications Conference, 2004, GLOBECOM '04, vol. 6, Nov. 29-Dec. 3, 2004, pp. 3808-3812.
- Fuchs, et al., "A Novel Tree-Based Scheduling Algorithm for the Downlink of Multi-User MIMO Systems with ZF Beamforming," IEEE International Conference on Acoustics, Speech, and Signal Processing, 2005, Proceedings, Philadelphia, PA, pp. 1121-1124.
- Hermann Rohling et al., : "Performance Comparison of Different Multiple Access Schemes for the Downlink of an OFDM Communication System", Vehicular Technology Conference, 1997, 47th IEEE, vol. 3, May 4-7, 1997, pp. 1365-1369.
- Hill, et al., "Cyclic Shifting and Time Inversion of Partial Transmit Sequences to Reduce the Peak-to-Average Power Ratio in OFDM," IEEE International Symposium on Personal, Indoor and Mobile Radio Communications, vol. 2, Sep. 18, 2000, Piscataway, NJ, pp. 1256-1259.
- J.S. Chow and J.M. Cioffi: "A cost-effective maximum likelihood receiver for multicarrier systems", Proc. IEEE Int. Conf. on Comm., pp. 948-952, Jun. 1992.
- Je, et al. "A Novel Multiple Access Scheme for Uplink Cellular Systems," IEEE Vehicular Technology Conference, Sep. 26, 2004 pp. 984-988.
- John B. Groe, Lawrence E. Larson, "CDMA Mobile Radio Design" Sep. 26, 2001, Artech House, Norwood, MA02062 580530, XP002397967, pp. 157-159.
- Kaleh: "Channel Equalization for Block Transmission Systems," IEEE Journal on Selected Areas in Communications, vol. 13, No. 1, Jan. 1995, pp. 110-121.
- Kappes, J.M., and Sayegh, S.I., "Programmable Demultiplexer/Demodulator Processor," COMSAT Laboratories, IEEE, 1990, pp. 230-234.
- Karsten Bruninghaus et al., : "Multi-Carrier Spread Spectrum and It's relationship to Single-Carrier Transmission", Vehicular technology Conference, 1998, VTC 98, 48th IEEE, vol. 3, May 18-21, 1998, pp. 2329-2332.
- Keller, et al.: "Adaptive Multicarrier Modulation: A Convenient Framework for Time-Frequency Processing in Wireless Communications," Proceedings of the IEEE, vol. 88, No. 5, May 2000, pp. 611-640.
- Kim, et al. "Performance of TDMA System With SFH and 2-Bit Differentially Detected GMSK Over Rayleigh Fading Channel," IEEE Vehicular Technology Conference, Apr. 28, 1996, pp. 789-793.
- Kishiyama Y et al: "Investigation of Optimum Pilot Channel Structure for VSF-OFCDM Broadband Wireless Access in Forward Link", IEEE Vehicular Technology Conference, New York, NY, US, vol. 4, Apr. 22, 2003, pp. 139-144.
- Kostic, et al. "Dynamic Frequency Hopping in Wireless Cellular Systems-Simulations of Full-Replacement and Reduced-Overhead Methods," IEEE Vehicular Technology Conference, May 16, 1999, pp. 914-918.
- Kostic, et al. "Fundamentals of Dynamic Frequency Hopping in Cellular Systems," IEEE Journal on Selected Areas in Communications, vol. 19, No. 11, Nov. 2001, pp. 2254-2266.
- Lacroix, et al.: "A Study of OFDM Parameters for High Data Rate Radio LAN's," 2000 IEEE 51st Vehicular Technology Conference Proceedings, vol. 2, May 15-18, 2000, pp. 1075-1079.
- Leon, et al., "Cyclic Delay Diversity for Single Carrier-Cyclic Prefix Systems," Conference Record of the Thirty-Ninth Asilomar Conference on Signals, Systems and Computers. Oct. 28, 2005, Piscataway, NJ, pp. 519-523.
- Lott: "Comparison of Frequency and Time Domain Differential Modulation in an OFDM System for Wireless ATM," 1999 IEEE 49th Vehicular Technology Conference, vol. 2, Jul. 1999, pp. 877-883.
- Mignone, et al.: "CD3-OFDM: A New Channel Estimation Method to Improve the Spectrum Efficiency in Digital Terrestrial Television Systems," International Broadcasting Convention, Sep. 14-18, 1995 Conference Publication No. 413, IEE 1995, pp. 122-128.
- Naofal Al-Dhahir: "A Bandwidth-Optimized Reduced-Complexity Equalized Multicarrier Transceiver", IEEE Transactions on Communications, vol. 45, No. 8, Aug. 1997.
- Naofal Al-Dhahir: "Optimum Finite-Length Equalization for Multicarrier Transceivers", IEEE Trans. on Comm., pp. 56-64, Jan. 1996.
- Nassar, Carl R., et al., "High-Performance MC-CDMA via Carrier-Interferometry Codes", IEEE Transactions on Vehicular Technology, vol. 50, No. 6, Nov. 2001.
- NTT DoCoMo, et al.: "Orthogonal Common Pilot Channel and Scrambling Code in Evolved UTRA Downlink," 3GPP TSG RAN WG1 #42 on LTE, pp. 1-8 (Aug.-Sep. 2005).
- Sari, et al., "Transmission Techniques for Digital Terrestrial TV Broadcasting," IEEE Communications Magazine, Feb. 1995, pp. 100-109.
- Schnell, et al., "Application of IFDMA to Mobile Radio Transmission," IEEE 1998 International Conference on Universal Personal Communications, vol. 2, Oct. 5-9, 1998, pp. 1267-1272.
- Schnell, et al., "A Promising New Wideband Multiple-Access Scheme for Future Mobile Communications Systems," European Transactions on Telecommunications, Wiley & Sons, Chichester, GB, vol. 10, No. 4, Jul. 1999, pp. 417-427.
- Shattil, et al., "Array Control Systems for Multicarrier Protocols Using a Frequency-Shifted Feedback Cavity", IEEE, 1999.
- Sklar: "Formatting and Baseband Transmission", Chapter 2, pp. 54, 104-106.
- Siimane Djidel; "High Speed, 3-Dimensional, Telecentric Imaging," 14 Optics Express No. 18 (Sep. 4, 2006).
- Sorger U. et al., : "Interleave FMDA—a new spread-spectrum multiple-access scheme", IEEE Int. Conference on Atlanta, GA, USA Jun. 7-11, 1998, XP010284733.
- Tellado, "Multicarrier Modulation with Low Par," Kluwer Academic, Dordrecht, NL, XP-002199500, 2000, pp. 6-11 and 55-60.
- Tellambura, "Use of m-sequences for OFDM Peak-to-Average Power Ratio Reduction," Electronics Letters, vol. 33, No. 15, Jul. 17, 1997, pp. 1300-1301.
- TIA/EIA/IS-2000 "Standards for CDMA2000 Spread Spectrum Systems" Version 1.0 Jul. 1999.
- TIA/EIA/IS-95 "Mobile Station-Base Station Compatibility Standard for Dual-Mode Wideband Spread Spectrum Cellular System" Jul. 1993.
- Torrieri, "Cellular Frequency-Hopping CDMA Systems," IEEE Vehicular Technology Conference, May 16, 1999, pp. 919-925.
- W. Neil Charman et al; "Can we measure wave aberration in patients with diffractive IOLs?" Journal of Cataract & Refractive Surgery No. 11 p. 1997 (Nov. 2007).
- Xiaodong, et al., "M-Sequences for OFDM Peak-to-Average Power Ratio Reduction and Error Correction," Electronics Letters, vol. 33, Issue 7, Mar. 27, 1997, pp. 554-555.
- Zekri, et al., "DMT Signals with Low Peak-to-Average Power Ratio," Proceedings, IEEE International Symposium on Computers and Communications, 1999, Jul. 6-8, 1999, pp. 362-368.
- Digital cellular telecommunications system (Phase 2+); Mobile radio interface layer 3 specification (GSM 04.08 version 7.7.1 Release 1998); ETSI EN 300 940 V7.7.7 (Oct. 2000), pp. 1,2,91-93.

(56)

References Cited

OTHER PUBLICATIONS

- Favre et al.: "Self-Adaptive Transmission Procedure" IBM Technical Disclosure Bulletin, IBM Corporation, Sep. 1976, vol. 19, No. 4, pp. 1283-1284, New York, New York.
- Groe, et al., "CDMA Mobile Radio Design," Sep. 26, 2001, Artech House, Norwood, MA 02062, pp. 257-259.
- Laroya, R. et al.: "An integrated approach based on cross-layer optimization—Designing a mobile broadband wireless access network" IEEE Signal Processing Magazine, IEEE Service Center, Piscataway, NJ, US, vol. 21, No. 5, Sep. 2004, pp. 20-28, XP01118149.
- Lau, et al., "On the Design of MIMO Block-Fading Channels with Feedback-Link Capacity Constraint," IEEE Transactions on Communications, IEEE Service Center, Piscataway, NJ, US, v. 52, No. 1, Jan. 2004, pp. 62-70, XP001189908.
- Lettieri et al.: "Adaptive frame length control for improving wireless link throughput, range, and energy efficiency", INFOCOM 98, 17th Annual Joint Conference of the IEEE Computer and Communications Societies, Mar. 29-Apr. 2, 1998, pp. 564-571, vol. 2, IEEE San Francisco, CA, New York, New York.
- Molisch, et al., MIMO systems with antenna selection, IEEE Microwave Magazine, URL: <http://ieeexplore.ieee.org/iel5/6668/28677/01284943.pdf>, Retrieved on Dec. 8, 2006, pp. 46-56 (2004).
- Tomcik, J.: "QFDD Technology Overview Presentation," IEEE 802.20 Working Group on Mobile Broadband Wireless Access, Slides/pp. 1-73, Nov. 15, 2005.
- Tomcik, J.; "MBFDD and MBTDD Wideband Mode: Technology Overview," IEEE 802.20 Working Group Mobile Broadband Wireless Access, Jan. 2006, pp. 1-109, XP002429968.
- Toufik I et al., "Channel allocation algorithms for multi-carrier systems", Vehicular Technology Conference, 2004. VTC2004-Fall. 2004 IEEE 60th Los Angeles, CA, USA Sep. 26-29, 2004, pp. 1129-1133, XP010786798, ISBN: 07-7803-8521-7.
- TIA-1121.001 "Physical Layer for Ultra Mobile Broadband (UMB) Air Interface Specification," 3GPP2 C.S0084-001-0, Version 2.0 (Aug. 2007).
- TIA-1121.002 "Medium Access Control Layer for Ultra Mobile Broadband (UMB) Air Interface Specification," 3GPP2 C.S0084-002-0, Version 2.0 (Aug. 2007).
- International Preliminary Report on Patentability—PCT/US06/032901, The International Bureau of WIPO, Geneva, Switzerland—Feb. 26, 2008.
- International Search Report—PCT/US06/032901—International Search Authority—European Patent Office, Mar. 23, 2007.
- Written Opinion—PCT/US06/032901—International Search Authority—European Patent Office, Mar. 23, 2007.
- Das, Arnab, et al. "Adaptive, asynchronous incremental redundancy (A-IR) with fixed transmission time intervals TTI for HSDPA," IEEE, pp. 10-83-1087.
- Wang et al., "Improving performance of multi-user OFDM systems using bit-wise interleaver" Electronics Letters IEE Stevenage, GB, vol. 37, No. 19, Sep. 13, 2001, pp. 1173-1174 XP006017222.
- Yun et al., "Performance of an LDPC-Coded Frequency-Hopping QFDMA System Based on Resource Allocation in the Uplink" Vehicular Technology -Conference 2004. VTO 2004-Spring, 2004 IEEE 59th Milan, Italy May 17-19, 2004, Piscataway, NJ, USA, vol. 4, pp. 1925-1928. XP010766497.
- 3GPP TS 33.220 V.1.1.0 XX,XX, "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Generic Authentication Architecture (GAA); Generic Bootstrapping Architecture (Release 6)" Feb. 9, 2004, pp. 1-17, figure 4, XP002996023.
- Blum, R. et al.: "On Optimum MIMO with Antenna Selection," IEEE International Conference on Communications: Conference Proceedings, vol. 1, Apr. 28, 2002, pp. 386-390.
- Catreux, S. et al.: "Simulation results for an interference-limited multiple input multiple output cellular system," Global Telecommunications Conference, 2000. GLOBECOM '00. IEEE. Dec. 1, 2000, vol. 2, pp. 1094-1096, <http://ieeexplore.ieee.org/iel5/7153/19260/00891306.pdf?tp=&isnumber=19260&arnumber=8913063&punumber=7153>.
- Chung, S. et al.: "Low complexity algorithm for rate and power quantization in extended V-BLAST" VTC Fall 2001. IEEE 54th. Vehicular Technology Conference Proceedings. Atlantic City, NJ, Oct. 7-11, 2001, vol. 1 of 4, pp. 910-914, Conf. 54.
- Dierks, et al., "The TLS Protocol", Version 1.0, Network Working Group, Request for Comments 2246, pp. 1-80 (Jan. 1999).
- El Gamal, H. et al.: "Universal Space-Time Coding," IEEE Transactions on Information Theory, vol. 49, Issue 5, pp. 1097-1119, XP011074756, ISSN: 0018-9448, May 2003.
- Guo, K. Et al.: "Providing end-to-end QoS for multimedia applications in 3G wireless networks," Proceedings vol. 5242, SPIE ITCOM 2003 Conf. Internet Multimedia Management Systems IV, Nov. 26, 2003, pp. 1-14, DOI: 10.1117/12.514061.
- Hochwald, B. et al., "Achieving near-capacity on a multiple-antenna channel," IEEE Transactions on Communications, IEEE Service Center, Piscataway, New Jersey, vol. 51, No. 3, pp. 389-399 (2003).
- Kiessling, M. et al., "Short-term and long-term diagonalization of correlated MIMO channels with adaptive modulation" IEEE International Symposium on Personal, Indoor and Mobile Radio Communications, vol. 2, Sep. 15, 2002, pp. 593-597.
- Kousa, M. et al.: "Adaptive Binary Coding for Diversity Communication Systems" IEEE International Conference on Personal Wireless Communications Proceedings, pp. 80-84, XP000992269, (1997).
- Maniatis, I. et al., "Pilots for joint channel estimation in multi-user OFDM mobile radio systems," 2002 IEEE Seventh International Symposium on Spread Spectrum Techniques and Applications, Prague, Czech Republic, Sep. 2, 2002, pp. 44-48, XP010615562.
- Nokia, "Uplink Considerations for UTRA LTE", 3GPP TSG RAN WG1#40bis Beijing, CN R1-050251, 3GPP, Apr. 4, 2005, pp. 1-9.
- NTT DoCoMo, "Downlink Multiple Access Scheme for Evolved UTRA", 3GPP R1-050249, 3GPP, Apr. 4, 2005, pp. 1-8.
- Prasad, N. et al.: "Analysis of Decision Feedback Detection for MIMO Rayleigh Fading Channels and Optimum Allocation of Transmitter Powers and QAM Constellations," pp. 1-10, 39th Annual Conference on Comm. Control and Comput., Monticello, IL Oct. 2001.
- Qualcomm Europe: "Description and link simulations for OFDMA based E-UTRA uplink" 3GPP Draft; R1-051100, 3RD Generation Partnership Project (3GPP), Mobile Competence Centre; Sophia-Antipolis Cedex, France, vol. RAN WG1, no. San Diego, USA; 20051004, Oct. 4, 2005, pp. 1-10, XP050100715.
- S. Nishimura et al., "Downlink Nullforming by a Receiving Antenna Selection for a MIMO/SDMA Channel", Technical Search Report of Electric Information Communication Academic Conference, Feb. 28, 2002, vol. 101, No. 683, pp. 17-22, RCS 2001-286.
- Sumii, Kenji et al.: "A Study on Computational Complexity Reduction of Iterative Decoding for Turbo-coded MIMO-SDM Using Sphere Decoding," Technical Report of IEICE. RCS, Nov. 9, 2010, vol. 104, No. 675, pp. 43-48.
- Tomcik, T.: "QTDD Performance Report 2," IEEE C802.20-05/88, IEEE 802.20 Working Group on Mobile Broadband Wireless Access, <<http://iee802.org/20/>>, pp. 1-56, XP002386798 (Nov. 15, 2005).
- Translation of Office Action in Chinese Application 2006800295980 corresponding to U.S. Appl. No. 11/260,895, citing CN1346221 and CN1383631 dated Feb. 16, 2011.
- Translation of Office Action in Korean application 10-2007-7031029 corresponding to U.S. Appl. No. 11/260,931, citing US20030202491 and KR20040063057 dated Jan. 28, 2011.
- Translation of Office Action in Chinese application 200680040236.1 corresponding to U.S. Appl. No. 11/261,065, citing US20040048609 and CN1402916 dated Feb. 18, 2011.
- Translation of Office Action in Chinese application 200680048832A corresponding to U.S. Appl. No. 11/261,158, citing CN1132474 dated Dec. 31, 2010.
- Translation of Office Action in Japanese Application 2008-514880 corresponding to U.S. Appl. No. 11/445,377, citing JP2007519281 and JP2006505172 dated Nov. 9, 2010.
- Translation of Office Action in Japanese application 2008-528103 corresponding to U.S. Appl. No. 11/260,924, citing JP2005502218, JP2004534456, JP2003348047, JP2003199173, JP2004529524, JP11508417, JP2001238269, JP2005130491 and JP2003500909 dated Feb. 8, 2011.

(56)

References Cited

OTHER PUBLICATIONS

- Translation of Office Action in Japanese Application 2008-529216 corresponding to U.S. Appl. No. 11/261,159, citing GB2348776, WO2004098222, WO2005065062 and WO2004102815. Dated Jan. 11, 2011.
- Translation of Office Action in Japanese application 2008-538181 corresponding to U.S. Appl. No. 11/511,735, citing WO04064295, JP2002515203, JP8288927, JP7336323 and JP200157545 dated Jan. 25, 2011.
- Widdup, B. et al., "A highly-parallel VLSI architecture for a list sphere detector," IEEE International Conference, Paris, France, vol. 5, pp. 2720-2725 (2004).
- Wiesel, A. et al.: "Efficient implementation of sphere demodulation" Signal Processing Advances in Wireless Communications 2003. SPAWC 2003. 4th IEEE Workshop on Rome, Italy Jun. 15-18, 2003, Piscataway, NJ, USA, IEEE, US, pp. 36-40, XP010713463.
- Yongmei Dai.; Sumei Sun; Zhongding Lei; Yuan Li.: "A List Sphere Decoder based turbo receiver for groupwise space time trellis coded (GSTTC) systems," 2004 IEEE 59th Vehicular Technology Conference, vol. 2, pp. 804-808, May 17, 2004, doi: 10.1109/VETECS.2004.1388940.
- B. Sklar: "The process of thus correcting the channel-induced distortion is called equalization", Digital Communications, PTR Prentice Hall, Upper Saddle River, New Jersey, 1998, Formatting and Baseband Transmission, Chap. 2, Section 2.11.2, pp. 104-106.
- Taiwan Search Report—TW095129021—TIPO—May 24, 2011.
- Translation of Office Action in Japan application 2008-538193 corresponding to U.S. Appl. No. 11/261,065, citing JP11196109, JP10322304 and JP09008725 dated Mar. 8, 2011.
- Translation of Office Action in Canadian application 2625987 corresponding to U.S. Appl. No. 11/261,065, citing CA2557369 dated Apr. 12, 2011.
- Translation of Office Action in Chinese application 200680048265.2 corresponding to U.S. Appl. No. 11/260,931, citing US6904097, WO2004095851, CN1344451 dated Jan. 26, 2011.
- Voltz, P. J., "Characterization of the optimum transmitter correlation matrix for MIMO with antenna subset selection", IEEE Transactions on Communications, vol. 51, No. 11, pp. 1779-1782, (Nov. 1, 2003).
- Alcatel-Lucent, et al., "Dedicated Reference Signals for Precoding in E-UTRA Downlink" 3GPP Draft; R1-071718, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre; 650, Route Des Lucioles; F-06921 Sophia-Antipolis Cedex; France, vol. RAN WG1, no. St. Julian; 20070403, Apr. 3, 2007, XP050105640 [retrieved on Apr. 3, 2007].
- Bengtsson, M. et al., "A Generalization of Weighted Subspace Fitting to Full-Rank Models", IEEE Transactions on Signal Processing, IEEE Service Center, New York, NY, US, vol. 49, No. 5, pp. 1002-1012, May 1, 2001.
- Dammann, A. et al., "Beamforming in Combination with Space-Time Diversity for Broadband OFDM Systems", ICC 2002. 2002 IEEE International Conference on Communications. Apr. 28-May 2, 2002, pp. 165-171, XP010589479.
- Ken Murakami et al., "Status Toward Standardization at IEEE 802.3ah and items on the construction of GE-PON system," Technical Report of the Institute of Electronics, Information and Communication Engineers, Jun. 13, 2003, vol. 103, No. 124, pp. 1-6, IN2003-24.
- Physical Channels and Multiplexing in Evolved UTRA Downlink TSG-RAN Working Group 1 Meeting, XX, XX, vol. RI-050590, Jun. 20, 2005, pp. 1-24, XP003006923 the whole document.
- Siemens, "Evolved UTRA uplink scheduling and frequency reuse" [online], 3GPP TSG-WG1 #41 R1-050476, Internet <URL:http://www.3gpp.org/ftp/tsg_ran/WG1_R1/TSGR1_41/Docs/R1-050476.zip>, May 9, 2005.
- Viswanath, P. et al., "Opportunistic Beamforming Using Dumb Antennas" IEEE Transactions on Information Theory, IEEE USA, vol. 48, No. 6, Jun. 2002, pp. 1277-1294, XP002314708 ISSN: 0018-9448 abstract right-hand column, paragraph 1.
- Yatawatta, S. et al., "Energy Efficient Channel Estimation in MIMO Systems", 2005 IEEE International Conference on Acoustics, Speech, and Signal Processing, Mar. 18-23, 2005, Philadelphia, vol. 4, pp. 317-320, Mar. 18, 2005.
- European Search Report—EP10184156—Search Authority—Munich—Jun. 14, 2012.
- Miorandi D., et al., "Analysis of master-slave protocols for real-time industrial communications over IEEE 802.11 WLANs" Industrial Informatics, 2004. Indin '04, 2nd IEEE International Conference on Berlin, Germany Jun. 24-26, 2004. Piscataway, NJ, USA IEEE, Jun. 24, 2004, pp. 143-148, XP010782619, ISBN 0789385136, Para 3, point B.
- Anonymous: "3GPP TS 36.211 V8.0.0; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical channels and modulation (Release 8)" 3rd Generation Partnership Project; Technical Specification Group Radio Access Network, [Online] 2007, XP002520076 Retrieved from the Internet: URL:http://www.3gpp.org/ftp/Specs/html-info/36211.htm> [retrieved on Sep. 27, 2007] Section 5.
- Jim Tomcik, QFDD and QTDD: Technology Overview, IEEE 802.20 Working Group on Mobile Broadband Wireless Access, Oct. 28, 2005, pp. 48-50, URL, HTTP://www.IEEE802.Org/20/Contribs/C802.20-05-68.Zip.
- Nokia: "Compact signalling of multi-code allocation for HSDPA", version 2, 3GPP R1-02-0018, Jan. 11, 2002.
- Sethi M, et al., "Code Reuse DS-CDMA—A Space Time Approach", Proceedings of the 2002 IEEE International Conference on Acoustics, Speech, and Signal Processing (ICASSP), pp: 2297-2300, May 13-17, 2002.
- Samsung: "Uplink Transmission and Multiplexing for EUTRA", 3GPP DRAFT; R1-050605 UL Multiplexing, Jun. 16, 2005, XP050111420.
- Bhushan N., "UHDR Overview", C30-20060522-037, Denver, CO, May 22, 2006, pp. 1-115.
- Tachikawa (Editor); "W-CDMA Mobile Communication Systems," John Wiley & Sons Ltd., Japan, Maruzen: pp. 82-213, Jun. 25, 2001.
- Tomcik J., "QFDD and QTDD: Proposed Draft Air Interface Specification," IEEE C802.20-05/69, IEEE 802.20 Working Group on Mobile Broadband Wireless Access, Oct. 28, 2005, P.1-6,1-7,1-16,6-65,7-11,7-33,7-37-7-55,9-21,9-22,9-24-9-32.
- Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); Mobile Station (MS)-Base Station System (BSS) interface; Radio Link Control/Medium Access Control (RLC/MAC) protocol (GSM 04.60 version 8.4.1 Release 1999), 3GPP Standard; ETSI EN 301 349, 3rd Generation Partnership Project (3GPP), Mobile Competence Centre; 650, Route Des Lucioles; F-06921 Sophia-Antipolis Cedex; France, No. V8.4.1, Oct. 1, 2000, pp. 1-243, XP050358534.
- LG Electronics: "PAPR comparison of uplink MA schemes", 3GPP TSG RAN WG1 Meeting #41, R1-050475, May 9-13, 2005, pp. 6.
- Motorola: "Uplink Numerology and Frame Structure", 3GPP TAG RAN1 #41 Meeting R1-050397, 10 pages, May 13, 2005.
- Samsung Electronics Co. Ltd.; "Uplink Multiple Access and Multiplexing for Evolved UTRA", R1-050439, May 3, 2005, pp. 1-22, XP55018616, Retrieved from the Internet: URL:http://www.3gpp.org/ftp/tsg_ran/WG1_R1/TSGR1/Docs/ [retrieved on Feb. 7, 2012].
- Institute for Infocomm Research et al., "Intra-Node B Macro Diversity based on Cyclic Delay Transmissions", 3GPP TSG RAN WG1 #42 on LTE, R1-050795, Aug. 29-Sep. 2, 2005, pp. 1-5.
- Sommer D., et al., "Coherent OFDM transmission at 60 GHz", Vehicular Technology Conference, 1999, VTC 1999—Fall, IEEE VTS 50th Amsterdam, Netherlands Sep. 19-22, 1999, Piscataway, NJ, USA, IEEE, US, vol. 3, Sep. 19, 1999, pp. 1545-1549, XP010353233, Doi: 10.1109/Vetecf.1999.801553, ISBN: 978-0-7803-5435-7.
- Zhang H., "A new space-time-frequency MIMO-OFDM scheme with cyclic delay diversity", Frontiers of Mobile and Wireless Communication, 2004. Proceedings of the IEEE 6th Circuits and Systems Symposium on vol. 2, Jun. 2, 2004, pp. 647 to 650.

* cited by examiner




FIG. 1

200




FIG. 2

300




FIG. 3

400




FIG. 4




FIG. 5

SEGMENT SENSITIVE SCHEDULING

CLAIM OF PRIORITY UNDER 35 U.S.C. §120

The present application for patent is a divisional of patent application Ser. No. 11/260,924 entitled "CHANNEL SENSITIVE SCHEDULING" filed Oct. 27, 2005, pending, and assigned to the assignee hereof and hereby expressly incorporated by reference herein, and claims priority to Provisional Application No. 60/710,461 entitled "CHANNEL SENSITIVE SCHEDULING" filed Aug. 22, 2005.

REFERENCE TO CO-PENDING APPLICATIONS FOR PATENT

The present application for patent is related to the following co-pending U.S. patent application:

"Shared Signaling Channel" having patent application Ser. No. 11/261,158, filed concurrently herewith on Oct. 27, 2005, assigned to the assignee hereof, and expressly incorporated by reference herein.

BACKGROUND OF THE INVENTION

1. Field of the Disclosure

The disclosure relates to the field of wireless communications. More particularly, the disclosure relates to scheduling of resources in a wireless communication system.

2. Description of Related Art

Communication devices operating in wireless communication systems can be affected by drastic changes in the channel conditions experienced by communication device. The channel conditions can be affected by extraneous interferers and can be affected by changes in the physical relationship and terrain separating a wireless transmitter from a receiver.

It is known that a wireless signal originating at the transmitter is attenuated by the physical distance to the receiver. Additionally, it is known that multipath signals from the transmitter to the receiver can result in fading of the channel.

A wireless communication system can compensate for attenuation by increasing transmit power or by increasing modulation or coding gain associated with the transmit signal. A wireless communication system may partially compensate for multipath fading by implementing a broadband signal that allows the receiver to separately identify multipath signals.

A wireless communication system implementing frequency division multiplexing can operate over a relatively wide frequency band. The operating band may be sufficiently wide that distinct communication devices operating at the same location but at different operating frequencies may experience substantially different channel conditions and channel fading. Additionally, each communication device may not operate with a sufficiently broad band signal to allow the device to compensate for multipath fades.

It is desirable to have the ability to communicate in a frequency division multiplex communication system with multiple communication devices in a manner that compensates for, or otherwise substantially eliminates the effects of frequency selective channel conditions.

BRIEF SUMMARY OF THE INVENTION

Systems and methods of scheduling sub-carriers in an OFDMA system are disclosed, in which a scheduler takes into account channel conditions experienced by the commu-

nication devices to optimize channel conditions. The scheduler can partition a set of sub-carriers spanning an operating bandwidth into a plurality of segments. The segments can include a plurality of global segments that each includes a distinct non-contiguous subset of the sub-carriers spanning substantially the entire operating bandwidth. One or more of the global segments can be further partitioned into a plurality of local segments that each has a bandwidth that is less than a channel, carrier, or coherence bandwidth. The scheduler determines channel characteristics experienced by each communication device via reporting or channel estimation, and allocates one or more segments to communication links for each device according to the segment characteristics.

The disclosure includes a method of segment sensitive scheduling in an Orthogonal Frequency Division Multiple Access (OFDMA) communication system including a plurality of sub-carriers spanning an operating frequency band. The method includes partitioning the operating frequency band into a plurality of segments, determining a segment preference indicative of a preferred segment based upon channel characteristics experienced by a receiver, and assigning a subset of sub-carriers within the preferred segment to a particular communication link associated with the segment preference.

The disclosure includes a method of segment sensitive scheduling that includes partitioning the operating frequency band into a plurality of segments, determining user data constraints, assigning sub-carriers from a global segment having a non-contiguous subset of sub-carriers spanning a substantial fraction of the operating band if the user data constraints include a data bandwidth requirement greater than a coherent bandwidth of a carrier, segment, or the like determining, if the data bandwidth requirement is not greater than the coherent bandwidth of a carrier, segment or the like, a segment preference indicative of a preferred local segment based upon channel characteristics experienced by a receiver, the preferred local segment selected from a plurality of local segments, each of the plurality of local segments having a bandwidth less than the coherent bandwidth, and assigning a subset of sub-carriers within the preferred local segment to a communication link associated with the segment preference.

The disclosure includes an apparatus for segment sensitive scheduling. The apparatus includes a receiver module configured to receive a pilot signal, a channel estimator coupled to the receiver and configured to determine a channel estimate corresponding to each of a plurality of segments spanning the operating frequency band based on the pilot signal, each of the segments having a bandwidth less than a coherent bandwidth, a signal mapper configured to map serial data symbols to a subset of the plurality of sub-carriers in the OFDMA communication system, and a resource scheduler coupled to the channel estimator and configured to determine a first preferred segment based on the channel estimates, select the subset of the plurality of sub-carriers from within the first preferred segment, and further configured to control the signal mapper to map the data symbols to the subset of the plurality of sub-carriers.

The disclosure includes an apparatus for segment sensitive scheduling that includes a receiver module configured to receive a reverse link pilot signal and at least one channel characteristic reporting message, and a scheduler coupled to the receiver module and configured to determine, based on the reverse link pilot signal, a channel characteristic corresponding to each of a plurality of segments spanning the operating frequency band, each of the segments having a bandwidth less than a coherent bandwidth, the scheduler configured to determine a reverse link assignment based on the channel charac-

teristics and further configured to determine a forward link resource assignment based on the at least one channel characteristic reporting message.

The disclosure includes an apparatus for segment sensitive scheduling that includes means for determining a segment preference indicative of a preferred segment from a plurality of segments substantially spanning the operating band based upon channel characteristics experienced by a receiver, and means for assigning a subset of sub-carriers within the preferred segment to a particular communication link associated with the segment preference.

The disclosure includes a method of reporting segment characteristics. The method includes receiving a pilot signal, determining a segment characteristic corresponding to each of a plurality of segments spanning the operating band, each segment having a bandwidth less than a coherent bandwidth, determining a preferred segment from the plurality of segments, comparing the channel characteristic corresponding to the preferred segment to a reporting threshold, and generating a reporting message based on the preferred segment if the channel characteristic corresponding to the preferred segment exceeds the reporting threshold.

BRIEF DESCRIPTION OF THE DRAWINGS

The features, objects, and advantages of embodiments of the disclosure will become more apparent from the detailed description set forth below when taken in conjunction with the drawings, in which like elements bear like reference numerals.

FIG. 1 is a simplified functional block diagram of an embodiment of a communication system having segment sensitive scheduling.

FIG. 2 is a simplified functional block diagram of an embodiment of a transmitter with segment sensitive scheduling.

FIG. 3 is a simplified functional block diagram of an embodiment of a receiver in a system implementing segment sensitive scheduling.

FIG. 4 is a simplified flowchart of an embodiment of a method of segment sensitive scheduling.

FIG. 5 is a simplified flowchart of an embodiment of a method of segment characteristic reporting in a system implementing segment sensitive scheduling.

DETAILED DESCRIPTION OF THE INVENTION

Segment sensitive scheduling of sub-carrier resources in an Orthogonal Frequency Division Multiple Access (OFDMA) communication system provides for a form of multi-user frequency diversity. A segment sensitive scheduler operates to schedule communication links with communication devices on available sub-carriers in the OFDMA system having maximum gain.

Frequency selectivity is a common characteristic of broadband wireless communication systems. Users with the same average channel strength may have quite different channel strength at particular frequency tones. The interference a user observes is in general also frequency selective. Hence, it would be desirable for users to communicate over the frequency tones with high signal level or low interference level depending on user data requirements and information resources of the system. The segment sensitive scheduling schemes discussed herein implement scheduling frequency tones, such as sub-carriers in an OFDMA system, based on the user frequency or channel characteristics under overhead and latency constraints.

One set of beneficiaries of segment sensitive scheduling include users with low signal to noise ratio (SNR), limited assignment size and low mobility. According to information theory, SNR improvement translates into capacity gain through a logarithmic function, hence, the capacity gain is larger if the SNR is low. In practical systems, the capacity of high SNR users may also be limited by the capacity of the highest order modulation and coding scheme that saturates at certain SNR, which diminishes the improvements due to further improvement in SNR. High data rate users require transmission of signals over a large fraction of the total bandwidth, which reduces the potential gain of scheduled transmission over average segment SNR. The scheduling and transmission delay can make it difficult to schedule high mobility users on their preferred tones based on past channel observations. Fortunately, many users in a wide area network satisfy the SNR, assignment size, and mobility requirements to benefit from segment sensitive scheduling.

A scheduler in an OFDMA system can be configured to schedule forward link communications from a base station to a user terminal, reverse link communications from a user terminal to a base station, or a combination of forward link and reverse link communications. A scheduler can perform forward link scheduling independent of reverse link scheduling. In other embodiments, the scheduler can relate forward link scheduling to reverse link scheduling.

The scheduler operates to schedule channel resources based, at least in part, on channel characteristics experienced by the communication devices. In one embodiment, the scheduler can determine the channel characteristics based on one or more channel quality indicator (CQI) included in one or more reporting messages communicated from a communication device to the scheduler. In another embodiment, the scheduler can be configured to determine the channel characteristics through channel estimation. In another embodiment, the scheduler can determine the channel characteristics using a combination of reporting messages and channel estimation.

FIG. 1 is a simplified functional block diagram of an embodiment of a wireless communication system **100** configured to schedule resources based on channel characteristics. The system **100** includes one or more fixed elements that can be in communication with a user terminal **110**. Although the description of the system **100** of FIG. 1 generally describes a wireless telephone system or a wireless data communication system, the system **100** is not limited to implementation as a wireless telephone system or a wireless data communication system nor is the system **100** limited to having the particular elements shown in FIG. 1.

The user terminal **110** can be, for example, a wireless telephone configured to operate according to one or more communication standards. The user terminal **110** can be a portable unit, a mobile unit, or, a stationary unit. The user terminal **110** may also be referred to as a mobile unit, a mobile terminal, a mobile station, user equipment, a portable, a phone, and the like. Although only a single user terminal **110** is shown in FIG. 1, it is understood that a typical wireless communication system **100** has the ability to communicate with multiple user terminals **110**.

The user terminal **110** typically communicates with one or more base stations **120a** or **120b**, here depicted as sectorized cellular towers. Other embodiments of the system **100** may include access points in place of the base stations **120a** and **120b**. In such a system **100** embodiment, the BSC **130** and MSC **140** may be omitted and may be replaced with one or more switches, hubs, or routers.

As used herein, a base station may be a fixed station used for communicating with the terminals and may also be referred to as, and include some or all the functionality of, an access point, a Node B, or some other terminology. An access terminal may also be referred to as, and include some or all the functionality of, a user equipment (UE), a wireless communication device, terminal, a mobile station or some other terminology.

The user terminal **110** will typically communicate with the base station, for example **120b**, that provides the strongest signal strength at a receiver within the user terminal **110**. Each of the base stations **120a** and **120b** can include a scheduler configured to assign and schedule the segment resources. The one or more base stations **120a-120b** can be configured to schedule the channel resources used in the forward link, reverse link, or both links.

Each of the base stations **120a** and **120b** can be coupled to a Base Station Controller (BSC) **140** that routes the communication signals to and from the appropriate base stations **120a** and **120b**. The BSC **140** is coupled to a Mobile Switching Center (MSC) **150** that can be configured to operate as an interface between the user terminal **110** and a Public Switched Telephone Network (PSTN) **150**. In another embodiment, the system **100** can implement a Packet Data Serving Node (PDSN) in place or in addition to the PSTN **150**. The PDSN can operate to interface a packet switched network, such as network **160**, with the wireless portion of the system **100**.

The MSC **150** can also be configured to operate as an interface between the user terminal **110** and a network **160**. The network **160** can be, for example, a Local Area Network (LAN) or a Wide Area Network (WAN). In one embodiment, the network **160** includes the Internet. Therefore, the MSC **150** is coupled to the PSTN **150** and network **160**. The MSC **150** can also be configured to coordinate inter-system hand-offs with other communication systems (not shown).

The wireless communication system **100** can be configured as an OFDMA system with communications in both the forward link and reverse link utilizing OFDM communications. The term forward link refers to the communication link from the base stations **120a** or **120b** to the user terminal **110**, and the term reverse link refers to the communication link from the user terminal **110** to the base stations **120a** or **120b**. Both the base stations **120a** and **120b** and the user terminal **110** may allocate resources for channel and interference estimation. For example, both the base stations **120a** and **120b** and the user terminal **110** may broadcast pilot signals that are used by the corresponding receivers for channel and interference estimation.

The wireless communication system **100** can include a set of sub-carriers that span an operating bandwidth of the OFDMA system. Typically, the sub-carriers are equally spaced. The wireless communication system **100** may allocate one or more sub-carriers as guard bands, and the system **100** may not utilize the sub-carriers within the guard bands for communications with the user terminal **110**.

In one embodiment, the wireless communication system **100** can include 2048 sub-carriers spanning an operating frequency band of 20 MHz. A guard band having a bandwidth substantially equal to the bandwidth occupied by six sub-carriers can be allocated on each end of the operating band. Therefore, in this embodiment, over 2000 sub-carriers are available for allocation to communications with the user terminal **110**.

The wireless communication system **100** can be configured to partition the operating band into a plurality of operating segments, each of which can include at least one sub-carrier.

The wireless communication system **100** can partition the forward link and reverse links to be identical. Alternatively, the forward link and reverse link segment definitions can be distinct.

The segments can each have a distinct set of sub-carriers such that no sub-carrier is allocated to more than one segment. In another embodiment, segments may have overlapping sub-carrier assignments. The segments can be contiguous frequency bands within the operating band or can be non-contiguous bands within the operating band. In one embodiment, each segment can span at least 16 sub-carriers or a multiple of 16 sub-carriers, although not all of the sub-carriers may be allocated to the same segment. Additionally, the segments may not be equally sized, and segments nearer the edge of the operating band may be smaller than segments closer to the center of the operating band.

In one embodiment, the wireless communication system **100** can be configured to partition a plurality of global segments, where each global segment has a bandwidth that spans a substantial fraction of the total operating band. Each of the global segments typically includes a non-contiguous subset of the total set of sub-carriers. In one embodiment, two global segments may be defined, with odd sub-carriers allocated to a first global segment and even sub-carriers allocated to a second global segment. In another embodiment, three global segments can be defined, with each global segment assigned every third sub-carrier in the operating band. Of course, the global segments do not need to have equally spaced sub-carriers, and do not need to span substantially the entire operating band. For example, two global segments can be defined that span one-half of the operating band, with sub-carriers in the half of the operating band alternately assigned to the global segments. Various other segment partitions may be defined, and the disclosure is not limited to any particular segment partition.

The wireless communication system **100** can also be configured to partition the operating band into one or more local segments. In one embodiment, each of the local segments can include a contiguous subset of all of the sub-carriers in the operating band. In another embodiment, at least one local segment can include a non-contiguous subset of sub-carriers. In one embodiment, each of the sub-carriers in the local segment can be within a coherent bandwidth of any other sub-carrier assigned to the same local segment. The coherent bandwidth corresponds to the bandwidth in which no substantial frequency selective fading occurs relative to another frequency within the band. For example, an embodiment can partition the operating band into multiple segments each having a bandwidth of approximately 1.25 MHz.

For example, the International Telecommunication Union (ITU) defines a channel model designated the Ped-B channel. This channel model has a coherent bandwidth on the order of hundreds of kilohertz. Thus, a local segment can have a bandwidth that is less than the coherent bandwidth of the Ped-B channel model. With such a local segment constraint, the resource assignments within any particular local segment are relatively frequency non-selective. That is, a channel estimate within one local segment can be valid for any combination of sub-carriers within the local segment. For example, a wireless communication system **100** with an operating bandwidth of 20 MHz can partition the band into local segments of approximately 1.25 MHz each.

In one embodiment, the operating band can be partitioned into a predetermined number of local segments, each having substantially equal number of contiguous sub-carriers. In another embodiment, the wireless communication system **100** can include both global and local segments. For example,

the wireless communication system **100** can define two global segments, with sub-carriers alternately assigned to each of the global segments. The wireless communication system **100** can select one of the global segments and can further partition the selected global segment into a plurality of local segments.

The wireless communication system **100** can include one more schedulers that are configured to allocate sub-carrier resource assignments to the various communication links within the system. For example, the wireless communication system **100** can include one or more schedulers at each of the base stations **120a** and **120b**. In one embodiment, each of the base stations **120a** and **120b** can include a first scheduler configured to schedule forward link sub-carrier assignments within the coverage area and a second scheduler configured to schedule reverse link sub-carrier assignments within the coverage area. Because each individual user terminal **110** typically has no knowledge regarding the sub-carrier assignments of other user terminals **110** within a particular coverage area, it may be advantageous for the wireless communication system **100** to implement a centralized reverse link scheduler for each coverage area located at the base stations **120a** and **120b**.

The scheduler can be configured to determine a resource assignment, including sub-carriers and corresponding segments, based in part on the channel characteristics experienced by the communication device. For example, the forward link scheduler can be configured to assign sub-carriers and segments based on the channel characteristics experienced by the base-station, for example **120a**, when communicating with a particular user terminal **110**. Similarly, the reverse link scheduler can be configured to adding sub-carriers and segments to each user terminal **110** based in part on the channel characteristics experienced by the reverse link signal.

The schedulers can determine the channel characteristics on the forward and reverse links based on channel analysis, channel characteristic reporting, or a combination of channel analysis and reporting. The schedulers can be configured to assign the sub-carriers and segments to a communication link that exhibit the greatest signal level or that have the lowest interference. The scheduler can determine the number of sub-carriers assigned to a particular communication link based on a variety of factors, including the bandwidth of the signal communicated. The scheduler can also take into account other scheduling criteria, such as fairness, signal latency constraints, and other criteria, when assigning segments and sub-carriers to a communication link.

The wireless communication system **100** can maintain some level of interference diversity between the various communication channels by implementing frequency hopping. A communication link, such as a forward link signal transmitted by a base station **120a** or **120b**, or a reverse link signal transmitted by a user terminal **110**, can be configured to frequency hop across a plurality of sub-carriers based on an initial sub-carrier assignment and a predetermined frequency hopping algorithm. The wireless communication system **100** can implement a frequency hopping algorithm that enforces frequency hopping within the assigned segments. Therefore, a forward link signal that is assigned a subset of carriers within a segment will perform frequency hopping within the segment in order to provide some level of interference diversity.

The wireless communication system **100** can be configured to Frequency Division Duplex (FDD) the forward and reverse links. In a FDD embodiment, the forward link is frequency offset from the reverse link. Therefore, forward link sub-carriers are frequency offset from the reverse link sub-carriers. Typically, the frequency offset is fixed, such that the

forward link channels are separated from the reverse link sub-carriers by a predetermined frequency offset. The forward link and reverse link may communicate simultaneously, or concurrently, using FDD. In an FDD system, channel estimates determined for the forward or reverse link signals are typically not accurate channel estimates for the complementary FDD reverse or forward link channels. Thus, in FDD systems, channel characteristic reporting may be used to communicate channel characteristics to the appropriate scheduler.

In another embodiment, the wireless communication system **100** can be configured to Time Division Duplex (TDD) the forward and reverse links. In such an embodiment, the forward link and reverse links can share the same sub-carriers, and the wireless communication system **100** can alternate between forward and reverse link communications over predetermined time intervals. In TDD, the allocated frequency channels are identical between the forward and reverse links, but the times allocated to the forward and reverse links are distinct. A channel estimate performed on a forward or reverse link channel is typically accurate for the complementary reverse or forward link channel because of reciprocity.

The base stations **120a** and **120b**, and the user terminal **110** can be configured to broadcast a pilot signal for purposes of channel and interference estimation. The pilot signal can include broadband pilots such as a plurality of CDMA waveforms or a collection of narrow band pilots that span the overall spectrum. The broadband pilots could also be a collection of narrow band pilots staggered in time and frequency.

In one embodiment, the pilot signal can include a number of tones selected from the OFDM frequency set. For example, the pilot signal can be formed from uniformly spaced tones selected from the OFDM frequency set. The uniformly spaced configuration may be referred to as a staggered pilot signal.

The scheduler in the base station, **120a** or **120b**, can determine the channel characteristics in each of the segments based on the pilot signals. The recipient of the pilot signal, for example the user terminal **110** in the forward link direction, can determine an estimate of the channel and interference based on the received pilot signal. Additionally, the user terminal **110** can determine an estimate of the signal quality of the received signal, such as by determining a received signal to noise ratio (SNR). The signal quality of the received signal can be quantified as a channel quality indicator (CQI) value, which can be determined, in part based on the estimated channel and interference. In a wireless communication system **100** implementing multiple operating segments, the user terminal **110** can determine a channel and interference estimate corresponding to each of the operating segments and determine one or more CQI values based on the various channel and interference estimates.

The user terminal **110** can report a CQI value back to the base station, for example **120a**, and a scheduler in the base station **120a** can compare the CQI value for each of the operating segments to determine the segment(s) to allocate to the user terminal **110**. The user terminal **110** can report the CQI directly in a reporting message or can generate a reporting message that includes data and information derived from the CQI value. For example, the user terminal **110** can be configured to determine the segment having the greatest CQI value and report the CQI value and identity of the corresponding segment. As will be discussed in greater detail below, the user terminal **110** can be configured to report the CQI value or related reporting message regularly, on an assigned basis, or on a probabilistically determined basis.

The wireless communication system **100** can implement a retransmission process, such as a Hybrid Automatic Repeat Request (HARQ) algorithm. In such a system, a transmitter may send an initial transmission at a first data rate and may send a subsequent retransmissions due to unsuccessful receipt at lower rates. HARQ incremental redundancy retransmission schemes can improve system performance in terms of providing early termination gain and robustness. However, improvements attributable to segment sensitive scheduling can be reduced if the scheduled transmission is based on out-dated information, which may occur in HARQ systems. If the segments and sub-carriers are not reallocated for retransmissions of an HARQ protocol, the segment which has high SNR at the time of the first transmission may get faded and results in a loss in performance.

Thus, in one embodiment, the wireless communication system **100** can be configured to re-determine the channel characteristics and can re-schedule sub-carrier and segments assigned to a particular communication link for HARQ retransmissions. Alternatively, the probability of channel fade occurring in the duration of the longest retransmission duration of a HARQ protocol, and the probability of a HARQ re-transmission occurring during channel fade may be sufficiently low. In such a situation, the wireless communication system may not reschedule sub-carriers and segments for HARQ retransmissions and may allow the communication link to experience a slight degradation if a channel fade should occur during the HARQ retransmissions.

FIG. 2 is a simplified functional block diagram of an embodiment of an OFDMA transmitter **200** such as can be incorporated within a base station of the wireless communication system of FIG. 1. The following discussion describes an embodiment in which the transmitter **200** is implemented in a base station of a wireless communication system configured for OFDMA communications. The transmitter **200** is configured to transmit one or more OFDMA signals to one or more user terminals. The transmitter **200** includes a data buffer **210** configured to store data destined for one or more receivers. The data buffer **210** can be configured, for example, to hold the data destined for each of the user terminals in a coverage area supported by the corresponding base station.

The data can be, for example, raw unencoded data or encoded data. Typically, the data stored in the data buffer **210** is unencoded, and is coupled to an encoder **212** where it is encoded according to a desired encoding rate. The encoder **212** can include encoding for error detection and Forward Error Correction (FEC). The data in the data buffer **210** can be encoded according to one or more encoding algorithms. Each of the encoding algorithms and resultant coding rates can be associated with a particular data format of a multiple format Hybrid Automatic Repeat Request (HARQ) system. The encoding can include, but is not limited to, convolutional coding, block coding, interleaving, direct sequence spreading, cyclic redundancy coding, and the like, or some other coding.

A wireless communication system implementing a HARQ algorithm can be configured to retransmit prior data that was not successfully decoded. The HARQ algorithm can be configured to provide a maximum number of retransmissions, and each of the retransmissions can occur at a lower rate. In other embodiments, the HARQ algorithm can be configured to transmit some of the retransmissions at the same rate.

The encoded data to be transmitted is coupled to a serial to parallel converter and signal mapper **214** that is configured to convert a serial data stream from the encoder **212** to a plurality of data streams in parallel. The scheduler **230** determines the number of sub-carriers, the identity of the sub-carriers, and

the corresponding frequency segments for each user terminal. The scheduler **230** provides the resource allocation information to the signal mapper **214**. The number of carriers allocated to any particular user terminal may be a subset of all available carriers. Therefore, the signal mapper **214** maps data destined for a particular user terminal to those parallel data streams corresponding to the data carriers allocated to that user terminal by the scheduler **230**.

The output of the serial to parallel converter/signal mapper **214** is coupled to a pilot module **220** that is configured to allocate a predetermined portion of the sub-carriers to a pilot signal. In one embodiment, the pilot signal can include a plurality of equally spaced sub-carriers spanning substantially the entire operating band. The pilot module **220** can be configured to modulate each of the carriers of the OFDMA system with a corresponding data or pilot signal.

The output of the pilot module **220** is coupled to an Inverse Fast Fourier Transform (IFFT) module **222**. The IFFT module **222** is configured to transform the OFDMA carriers to corresponding time domain symbols. Of course, a Fast Fourier Transform (FFT) implementation is not a requirement, and a Discrete Fourier Transform (DFT) or some other type of transform can be used to generate the time domain symbols. The output of the IFFT module **222** is coupled to a parallel to serial converter **224** that is configured to convert the parallel time domain symbols to a serial stream.

The serial OFDMA symbol stream is coupled from the parallel to serial converter **224** to a transceiver **240**. In the embodiment shown in FIG. 2, the transceiver **240** is a base station transceiver configured to transmit the forward link signals and receive reverse link signals.

The transceiver **240** includes a forward link transmitter module **244** that is configured to convert the serial symbol stream to an analog signal at an appropriate frequency for broadcast to user terminals via an antenna **246**. The transceiver **240** can also include a reverse link receiver module **242** that is coupled to the antenna **246** and is configured to receive the signals transmitted by one or more remote user terminals.

The scheduler **230** can be configured to receive reverse link signals, including the reverse link pilot signals and channel characteristic reporting messages, and determine the segments and sub-carriers to assign to the communication links for each of the user terminals. As described earlier, the scheduler **230** can use the reverse link pilot signals to determine the reverse link resource allocation. Additionally, the scheduler **230** can use the reverse link pilot signals to determine forward link resource allocation for TDD systems in which OFDMA system uses the same bandwidth for the forward and reverse links. In the embodiment shown in FIG. 2, the scheduler **230** can be used to schedule both forward and reverse link resources. In other embodiments, a separate scheduler can be used for the forward and reverse links.

The reverse link receiver module **242** can couple the reverse pilot signals to a channel estimator **232**, shown in this embodiment as part of the scheduler **230**. Of course, the channel estimator **232** is not limited to implementation within the scheduler **230** and may be implemented in some other module, such as the reverse link receiver **242**. The channel estimator **232** can determine, for each of the user terminals broadcasting a reverse pilot signal, which segment has the highest signal power or highest Signal to Noise Ratio (SNR). Additionally, the channel estimator **232** can determine which of the segments has the lowest interference level.

High bandwidth communication links that are assigned to the global segments may not experience a significant improvement when the sub-carrier assignments over a resource allocation scheme that allocates resources based on

highest average channel strength. Thus, in one embodiment, the channel estimator **232** determines the channel characteristics for each local segment and does not determine the channel characteristics for the global segments. Alternatively, the channel estimator **232** can be configured to determine an average channel strength for the global segments.

The channel estimator **232** can communicate the channel characteristic information to the resource scheduler **234** that operates to schedule the sub-carriers to the appropriate forward links based on the channel characteristic information. The resource scheduler **234** can also include reverse link scheduling messages on one or more overhead channels in the OFDMA system.

In one embodiment, the wireless communication system can implement an assignment algorithm that minimizes the overhead associated with resource assignments. The assignment method can be referred to as "sticky assignment." The assignment algorithm may alternatively be referred to as persistent assignment or enduring assignment. In sticky assignment a user's assignment does not expire unless an explicit de-assignment message is received. An assignment message to other users that include a user's current resource ID is considered as a de-assignment message of the corresponding resource of this user. A user is assigned certain segment corresponding to a particular frequency band based upon favorable channel characteristics. This user will keep receiving or sending information over sub-carriers within the segment until a new assignment is received. Given limited scheduling overhead of N simultaneous messages, the system can potentially simultaneously schedule M users, where M is much greater than N.

Once resources are allocated to a particular communication link, the communication link can continue with that assignment. However, the sub-carrier assignments are not necessarily static. For example, the resource scheduler **234** can implement a channel tree that is a logical map of the available resources. The resources scheduler **234** can be configured to assign resources based on the logical structure of the channel tree. The resource scheduler **234** or some other module, such as the frequency hopping module **238**, can map the logical resource assignment from the channel tree to a physical assignment that corresponds to physical sub-carriers of the OFDM system.

The channel tree can be organized in a branch structure with multiple branches. The branches eventually terminate in a lowest level of the tree, referred to as a leaf node or a base node. Every branch node in the channel tree can be assigned an identifying node index. Additionally, each leaf node or base node can be assigned a node index. Typically, the number of leaf nodes can correspond to the number of physical sub-carriers available in the OFDM system.

Every node includes a corresponding node index, and higher level branch nodes can be used to identify all of the nodes underneath the branch node in the channel tree. Thus, assigning a particular branch node to a particular communication link assigns all of the leaf nodes appearing underneath the particular branch node to that communication link.

Although each node of the channel tree, including each leaf node or base node, can be arbitrarily mapped to any physical resource, it may be advantageous to provide some mapping constraints on the channel tree. For example, the leaf nodes can be divided into groups, where each group of leaf nodes corresponds approximately to the number of sub-carriers within a segment. Thus, some of the leaf nodes can be divided into a group that corresponds to a global segment, while other leaf nodes can be divided into a group that corresponds to a local segment.

The branch nodes can thus be organized according to the grouping of the leaf nodes, and assigning a branch node corresponds to assigning all of the resources in nodes appearing underneath the branch node. It may be advantageous to have two distinct channel trees, one corresponding to resources assigned to global segments and another channel tree corresponding to the resources assigned to local segments.

If the resource scheduler **234** assigns a branch node sufficiently deep in the channel tree to a particular communication link based on the channel characteristics, the channel tree can be constrained such that all of the lower nodes underneath the branch node will be assigned to the same segment. This channel tree organization can simplify the mapping of the logical nodes to the physical resources.

The resource scheduler **234** or the frequency hopping module **238** can map the logical channel tree assignments to physical sub-carrier assignments. Therefore, the logical node assignments can remain stable while the physical sub-carriers mapped to the nodes can vary.

A frequency hopping module **238** can be configured to improve interference diversity by implementing frequency hopping within the assigned segment. The frequency hopper module **238** can, for example, implement a pseudorandom frequency hopping scheme for each assigned sub-carrier. The receiver can be configured to utilize the same frequency hopping algorithm to determine which sub-carriers are assigned to its corresponding link. For example, the frequency hopping module **238** can implement a frequency hopping algorithm that results in the same logical nodes being mapped to different physical sub-carriers at different instances.

The scheduler **230** can include a CQI receiver **236** configured to receive and process channel characteristic reporting messages generated by the user terminals and transmitted on the reverse link. Such reporting messages may be used to schedule the forward link assignments in FDD systems, or systems in which the reverse pilots do not sufficiently represent the forward link resources.

The manner and information included in the reporting messages are described in further detail below in relation to the description of the receiver embodiment. For the purposes of resource assignment, it is sufficient to describe the reporting messages as including some measure of channel characteristics, channel quality, segment preference, or some other indication that can be related to a segment preference.

The CQI receiver **236** is configured to receive the reporting messages and determine, based at least in part on the reporting messages, if the present resource allocation should be sustained or if the sub-carrier or segment allocations should be modified. The CQI receiver **236** can communicate the assignment information to the resource scheduler **234** that is configured to control the signal mapper **214** to implement the sub-carrier and segment assignments. The resource scheduler **234** can also report any new sub-carrier or segment assignments to the corresponding receiver. For example, the resource scheduler **234** can be configured to generate a control message that is communicated to the appropriate receiver using an overhead channel.

FIG. 3 is a simplified functional block diagram of an embodiment of a receiver **300**. The receiver **300** can be, for example, part of a user terminal **110** shown in FIG. 1. The following discussion describes a receiver **300** implemented within a user terminal of an OFDMA wireless communication system using reporting messages for the determination of the forward link assignments.

The receiver **300** can include an antenna **356** coupled to a transceiver **350** configured to communicate over a wireless

channel with the transmitter **200** shown in FIG. 2. The transceiver **350** can include a forward link receiver module **352** configured to receive the forward link wireless signals, via the antenna **356**, and generate a serial baseband symbol stream.

The output of the receiver module **352** of the transceiver **350** is coupled to a serial to parallel converter **360** configured to convert the serial symbol stream to a plurality of parallel streams corresponding to the number of carriers in the OFDMA system.

The output of the serial to parallel converter **360** is coupled to a Fast Fourier Transform (FFT) module **362**. The FFT module **362** is configured to transform the time domain symbols to the frequency domain counterpart.

The output of the FFT module **362** is coupled to a channel estimator **364** that is configured to determine a channel and interference estimate based in part on the forward link pilot signals. A carrier allocation module **380**, alternatively referred to as a resource allocation module, can determine the sub-carriers assigned to the data and the sub-carriers assigned to the forward link pilot signals. The carrier allocation module **380** can determine the sub-carrier and segment assignments based in part on any assignment messages received. The carrier allocation module **380** can, for example, implement a frequency hopping algorithm to determine the current carrier assignment based on a past assignment. The carrier allocation module **380** is coupled to the channel estimator **364** and informs the channel estimator **364** of the sub-carrier and segment assignment.

The channel estimator **364** determines a channel and interference estimate based on the forward link pilot signals. The channel estimator **364** can be configured to estimate the channel and interference for each of the segments of the OFDMA system. The channel estimator **364** can determine an estimate using a least squares method, a maximum likelihood estimate, a combination of least squares and maximum likelihood estimate, and the like, or some other process of channel and interference estimation.

The output of the channel estimator **364** including the frequency domain transform of the received symbols and the channel and interference estimates is coupled to a demodulator **370**. The carrier allocation module **380** can also inform the demodulator **370** of the sub-carrier frequencies allocated to data transmission. The demodulator **370** is configured to demodulate the received data carriers based in part on the channel and interference estimate. In some instances, the demodulator **370** may be unable to demodulate the received signals. As noted earlier, the demodulator **370** may be unsuccessful because the channel quality is inadequate and cannot support the transmitted rate of the data, or because degradation attributable to inadequate channel and interference estimation is sufficiently severe to result in decoding error.

If the demodulator **370** is unsuccessful, it can generate an indication of the inability to demodulate the received signals. The demodulator **370** can also provide an unsuccessful demodulation indication to the transmitter module **354** in the transceiver **350** for transmission back to the base station.

If the demodulator **370** is successful, the received data is dropped, and there is no need to couple any data to memory. If the demodulator **370** is successful, the demodulator **370** can be configured to couple the demodulated data to a parallel to serial converter **372** that is configured to convert the parallel demodulated data to a serial data stream. The output of the parallel to serial converter **372** is coupled to a data buffer **374** for further processing.

A channel quality indicator (CQI) module **390** can also be coupled to the channel estimator **364** and can use the values of pilot power, channel estimate, and interference estimate to

determine a value of the CQI for each of the segments. In one embodiment, the CQI value is based in part on the SNR. The CQI module **390** couples the CQI value to the transmitter module **354**, which can be configured to transmit the value to the base station using, for example, an overhead channel, control channel, or traffic channel.

The wireless communication system can implement a channel characteristic reporting scheme that is configured to minimize the amount of reporting messages that need to be communicated to the base stations. The wireless communication system can implement channel reporting schemes that require a user terminal to provide reporting messages on a periodic basis, an assigned basis, a probabilistically determined basis, or some other basis or combination of bases.

If the wireless communication system implements a periodic reporting scheme, the period can correspond to a predetermined time. The predetermined time can be based on a symbol timing, and can be based on a frame of symbols or multiple frames of symbols.

The CQI module **390** can be configured to report the CQI or an index of the segment corresponding to the best frame, if the reporting period spans multiple frames. In other embodiments, the CQI module **390** can be configured to average the CQI values over multiple frames and report the CQI or index of the segment having the best averaged CQI. In another embodiment, the CQI module **390** can be configured to report the CQI or index of the segments exhibiting improving CQI values. The CQI module **390** is not limited to any particular reporting criteria, and may use some other criteria for determining which segment or segments to report, and the information included with the reporting message.

If the feedback channel capacity and link budget are not limited in a system, each user terminal could transmit an array of CQI reporting messages for all frequency segments. In such a brute force reporting scheme, each user terminal reports every CQI value corresponding to every segment. However, this creates an enormous amount of unnecessary information.

To improve the amount of overhead used for reporting CQI, the wireless communication system can implement a reporting scheme where user terminals measure the forward link pilots and feedback the identity of the preferred frequency segment(s). In one embodiment, the user terminals determine a predetermined number of preferred segments and can report the identity of the predetermined number of segments to the scheduler in one or more reporting messages. The predetermined number can be a fixed number or can be varied, for example, based on a control message transmitted by the scheduler or a communication bandwidth desired by the user terminal.

The user terminal can generate reporting messages that report a CQI for as few as one preferred segment or CQI values for as many as all of the segments. In some embodiments, the number of segments identified in a reporting message can depend on a bandwidth occupied or desired in the communication link to the user terminal. For example, a user terminal having a communication bandwidth that is less than a bandwidth of a segment may report as few as one segment CQI value or a segment identity. A second user terminal having a communication bandwidth that is greater than the bandwidth of a single segment may report CQI values or segment identities for at least the number of segments needed to support the communication bandwidth.

In other embodiments, the wireless communication system may define more than one local segment size, or multiple local segments can be aggregated to form a larger segment. In such an embodiment, the user terminal can report a desired

preferred segment of any size, and the segment size is not limited to a single segment size. In one embodiment, the user terminal can store a codebook with multiple segment sizes. The user terminal can determine a CQI value for each cluster or segment size defined in the codebook. The user terminal can report N of the best segment sizes based upon some predefined criteria, which may be part of the communication session or negotiated on a periodic basis.

The format of the reporting messages may be predetermined such that the user terminal reports the identities of the one or more segments in order of decreasing preference. Of course, other reporting message formats may be used. For example, the user terminal may report a CQI value and corresponding segment identity for each reported segment that is identified as a preferred segment.

The scheduler can use the reporting messages and other scheduling criteria to determine the tones or sub-carriers that are assigned to each of the user terminals. The wireless communication system can thus use the reporting messages to maintain communication links between base stations and user terminals over the segments that opportunistically provide advantageous performance.

In an embodiment of a reporting scheme implementing an efficient channel preference feedback algorithm, a user terminal can generate a reporting message using $\log_2 L$ bits to indicate the segment with the best channel quality, where there are: L segments in the system. The user terminal transmits only the CQI of the best segment or only a segment index corresponding to the best segment in the feedback reporting message. The user terminal does not need to report L-1 CQI values corresponding to segments with lesser CQI values.

The CQI module 390 can further reduce the feedback rate by implementing thresholding logic in best segment reporting. Given a long term average channel quality in SNR, the CQI module 390 can compare the SNR corresponding to the best segment against the average SNR and choose not to report the CQI corresponding to the best segment unless it is a predetermined value, Δ , above the average. For example, the CQI module 390 can generate the reporting message if the CQI corresponding to the best segment is Δ dB above the average.

Thus, the CQI module 390 can have the opportunity to transmit a reporting message on a periodic basis or on an assigned basis and may selectively not transmit the reporting message based on the thresholding logic. For example, the CQI module 390 may be allowed to transmit a reporting message in a predetermined time slot that occurs each reporting interval, which can be, for example 15 ms. Alternatively, the CQI module 390 can be assigned a reporting time based on a round robin allocation of reporting slots to each of the user terminals in a base station coverage area. The CQI module 390 can implement thresholding logic to further reduce the instances of reporting messages regardless of the underlying reporting timing. In other embodiments, the CQI module 390 can be configured to generate and transmit a reporting message when the thresholding logic is satisfied.

This thresholding mechanism can provide a manner for a scheduler to balance the segment sensitive scheduling gain and reverse link feedback capacity. A scheduler in the wireless communication system can broadcast or multicast the desired threshold level, Δ , to user terminals based on reverse link feedback channel loading. High thresholds would lead to less reporting and low thresholds would lead to more reporting.

Alternatively, the scheduler can broadcast or multicast a desired reporting rate directly for example, the scheduler in the base station can transmit a desired percentage of time a

user terminal is allowed to report the best segment. Each CQI module 390 in a user terminal can translate the desired reporting rate into a Δ dB threshold based on historical channel characteristic statistics maintained by the user terminal. For example, the CQI module 390 can collect the CQI values determines for each of the segments and can generate a distribution of the CQI values over time. The CQI module 390 can, for example, generate a Cumulative Distribution Function (CDF) based on the historical values. The CQI module 390 can then determine a threshold based on the desired reporting percentage and the CDF. For example, a reporting rate of 0.3 can correspond to a 70% CDF quantile and $\Delta=5$ dB reporting threshold. The CDF maintained by each CQI module 390 can be distinct, because they are established based on the channel characteristics experienced by the user terminal. Furthermore, the CDF may change over time, as the channel characteristics experienced by the user terminal change, for example, due to mobility or changes in the multipaths in the environment.

If HARQ is deployed in a system, the CQI module 390 can be configured to include the average CQI across all frequency segment the feedback reporting message. Although the conservative CQI will lead to the scheduling of low spectral efficiency transmission, early termination of HARQ is likely to retain a substantial fraction of the achievable capacity gain given reasonable HARQ granularity. This approach also improve the robustness of segment sensitive scheduling in the cases when the scheduled segment is not the best one and may possibly be a poor selection, because of, for example, channel decorrelation between channel measurement time and the actual transmission time, measurement mismatch, or some other factors.

FIG. 4 is a simplified flowchart of an embodiment of a method 400 of segment sensitive scheduling. The method 400 can be performed, for example, by the scheduler in an OFDMA wireless communication system, such as a scheduler in a base station shown in the system of FIG. 1. For example, the scheduler shown in the base station transmitter of FIG. 2 can be configured to perform the method 400. The scheduler can perform the method 400 for each of the users. For example, the scheduler can perform the method for each of the forward link and reverse links established between a base station and user terminals in the base station coverage area.

The method 400 begins at block 402 where the scheduler partitions the operating band into a plurality of segments. The wireless communication system can define the segments, and the segments can include one or more global segments and one or more local segments. The global segments can include a subset of the sub-carriers of the OFDMA system that span substantially a large fraction of the operating band. The global segments typically are assigned non-contiguous frequency spans comprising one or more sub-carriers. The local segments can be contiguous or non-contiguous bands that include one or more sub-carriers. The local segments typically have a bandwidth that is less than a coherent bandwidth of the wireless channel. In some cases the segments may be pre-partitioned in a predetermined manner and known to both the base station and mobile station. As such, this functionality may be omitted.

The scheduler need not perform any actual physical partitioning of the operating band, but may instead, merely account for the various segments and the sub-carriers associated with each segment. The scheduler typically associates each sub-carrier with only one segment, and each segment includes a distinct subset of sub-carriers.

17

The scheduler proceeds to block **410** and determines user data constraints. Such user data constraints can include data latency constraints, bandwidth constraints, and other constraints that may be associated with particular users or communication links. The scheduler can be configured to attempt to satisfy substantially all data constraints when scheduling the segment.

After receiving the data constraints, the scheduler proceeds to decision block **420** to determine if the channel for a particular user requires high bandwidth. In the context of the scheduler, the term high bandwidth refers to a user that requires a resource assignment that exceeds the bandwidth of a predetermined number of local segments. The predetermined number of local segments can be, for example, one, or can be some other number greater than one. High data rate users can require transmission of signals over a large fraction of the total bandwidth, which reduces the potential gain of scheduled transmission over average channel SNR.

If the user requires high bandwidth, the scheduler proceeds to block **430** and assigns the user to a global segment and assigns sub-carriers from the assigned global segment. The scheduler then proceeds from block **430** back to block **410**.

If, at decision block **420** the scheduler determines that the user does not require high bandwidth, the scheduler proceeds to block **440** and determines a segment preference for the user and communication link. The scheduler can determine a segment preference based on channel analysis, channel characteristic reporting messages, or a combination of analysis and reporting messages.

In one embodiment, the scheduler can determine a channel estimate for each local segment in the operating band based on a pilot signal transmitted by the user terminal. The scheduler can compare all of the channel estimates to determine the segment preference as the segment that has the best channel characteristics. For example, the scheduler can determine, based in part on the channel estimates, which of the segments has the highest SNR.

In another embodiment, the scheduler can receive reporting messages from some or all of the user terminals. The reporting messages can include a segment preference or can include channel characteristics that the scheduler can use to determine a segment preference.

After determining the segment preference for a particular user, the scheduler proceeds to decision block **450** to determine whether the segment preference differs from a previous segment preference for that same user.

If the scheduler determines that the segment preference has changed, the scheduler proceeds to block **460** and assigns a segment and sub-carriers from the segment to the communication link. In the forward link direction, the scheduler can assign a channel by controlling a signal mapper to map the data signal for the user terminal to the appropriate sub-carriers in the preferred segment. In the reverse link direction, the scheduler can generate a segment assignment message that identifies the segment and sub-carriers assigned to that user terminal. After segment assignment, the scheduler proceeds back to block **410**.

The wireless communication system can implement sticky or persistent assignments. The user terminal can use the same assignment until it receives a de-assignment message. In one embodiment, the de-assignment message can be an assignment message to a distinct user terminal for a sub-carrier for which the user terminal is assigned.

If, at decision block **450**, the scheduler determines that the segment preference has not changed, the scheduler proceeds to block **470**. At block **470**, the scheduler can provide some form of interference diversity by implementing frequency

18

hopping. The scheduler can be configured to enforce frequency hopping within the assigned segment in order to maintain the advantages of segment sensitive scheduling. After enforcing the frequency hopping on the assigned sub-carriers, the scheduler proceeds back to block **410**.

FIG. **5** is a simplified flowchart of an embodiment of a method **500** of channel characteristic reporting in a system implementing segment sensitive scheduling. As noted above, the scheduler can utilize reporting messages as part of the segment sensitive scheduling process. The manner in which reporting messages are generated and transmitted to the scheduler can affect the amount of overhead required to support reporting messages. The reporting method **500** can be performed, for example, by a user terminal of the wireless communication system of FIG. **1** to assist in scheduling of forward link OFDMA channels.

The method **500** begins at block **510** where the user terminal receives the forward link pilot signals. The user terminal proceeds to block **520** and determines channel characteristics for each of the predetermined local segments in the operating band. The user terminal can, for example, determine the signal level, interference level, SNR over the segment, or some other channel characteristic for each local segment. The user terminal can also determine channel characteristics, such as an average channel strength or average SNR for each of the global segments.

The user terminal proceeds to block **530** and determines a preferred segment from the various segments. A high bandwidth user may prefer a global segment to any local segment merely due to the ability of the global segment to satisfy the bandwidth requirements. If there are multiple global segments, the user terminal can determine a global segment having the greatest average SNR as the preferred segment.

Alternatively, fit the user terminal is assigned to a local segment or capable of assignment to a local segment, the user terminal determines which of the segments is the preferred segment. The user terminal can, for example, select the local segment that corresponds to the highest SNR or channel power. In another embodiment, the user terminal may select the segment having the least interference. In another embodiment, the user terminal can select a preferred segment based on a variety of factors.

After determining the segment preference, the user terminal proceeds to decision block **540** to determine whether a reporting constraint is satisfied. The user terminal can include a number of reporting constraints and may generate and transmit a reporting message only when a predetermined number of constraints are satisfied. The user terminal can limit the reporting messages using the reporting constraints in order to minimize the amount of reporting overhead communicated to the scheduler.

For example, the user terminal can limit reporting to messages that report SNR values greater than a predetermined threshold above an average channel SNR. The predetermined threshold can be static or can be communicated from the scheduler. Additionally, the user terminal can be limited to only reporting segment preferences that are distinct from the segment in which the user terminal is presently operating.

If the user terminal does not satisfy the reporting constraints, the user terminal returns to block **510** and does not generate a reporting message. Alternatively, if at decision block **540** the user terminal determines that the reporting constraints have been satisfied, the user terminal proceeds to block **550** and generates a reporting message.

The user terminal can, for example, generate a reporting message that identifies the preferred segment or a plurality of preferred segments. The user terminal can, for example,

report an index corresponding to the preferred segment. The user terminal may also include in the reporting message other channel characteristics, such as an average CQI over all segments.

After generating the reporting message, the user terminal proceeds to block 560 and transmits the reporting message to the scheduler. For example, the user terminal can transmit the reporting message or messages to a base station on a reverse link overhead channel. The user terminal returns to block 510 to repeat the channel analysis and reporting method 500.

Methods and apparatus for segment sensitive scheduling have been described. An OFDMA wireless communication system can implement segment sensitive scheduling to improve the performance of the communication links. The wireless system can partition the operating band into a number of segments, including global segments and local segments. A scheduler in the system can be configured to assign a segment and sub-carriers within the segment to each communication link based on channel characteristics. The channel characteristics can be determined at the scheduler using channel analysis or can be determined at the receiver and fed back to the scheduler in one or more reporting messages.

Reporting constraints can be imposed on the reporting messages to limit the overhead needed to support the reporting messages. The reporting constraints can limit the amount of information reported and can limit the instances of reporting messages. For example, the reporting messages can be limited to reporting a CQI value or segment index for a segment preference. The reporting messages can be limited to reporting on a predetermined periodic basis or an assigned basis such as in round robin reporting where each user terminal in a base station coverage area reports one time before any user terminal transmits an updated reporting message. The reporting messages can also be limited to a probabilistic basis, where reporting is limited based on a probability that the user terminal will experience a preferred segment that is substantially better than an average channel characteristic.

The wireless communication system can improve the overall system performance by utilizing segment sensitive scheduling.

The various illustrative logical blocks, modules, and circuits described in connection with the embodiments disclosed herein may be implemented or performed with a general purpose processor, a digital signal processor (DSP), a Reduced Instruction Set Computer (RISC) processor, an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor may be a microprocessor, but in the alternative, the processor may be any processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices, for example, a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

The steps of a method, process, or algorithm described in connection with the embodiments disclosed herein may be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two.

A software module may reside in RAM memory, flash memory, non-volatile memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or any other form of storage medium known in the art. An exemplary storage medium is coupled to the processor such the processor can read information from,

and write information to, the storage medium. In the alternative, the storage medium may be integral to the processor. Further, the various methods may be performed in the order shown in the embodiments or may be performed using a modified order of steps. Additionally, one or more process or method steps may be omitted or one or more process or method steps may be added to the methods and processes. An additional step, block, or action may be added in the beginning, end, or intervening existing elements of the methods and processes.

The above description of the disclosed embodiments is provided to enable any person of ordinary skill in the art to make or use the disclosure. Various modifications to these embodiments will be readily apparent to those of ordinary skill in the art, and the generic principles defined herein may be applied to other embodiments without departing from the spirit or scope of the disclosure. Thus, the disclosure is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent with the principles and novel features disclosed herein.

What is claimed is:

1. An apparatus for channel sensitive scheduling in a communication system including a plurality of sub-carriers spanning an operating frequency band, the apparatus comprising:
 - a channel estimator executably configured to determine a channel estimate corresponding to each of a plurality of segments spanning the operating frequency band based on pilot signals, each of the plurality of segments having a bandwidth less than a total bandwidth;
 - a signal mapper executably configured to map data symbols to a subset of the plurality of sub-carriers in the communication system;
 - a scheduler coupled to the channel estimator and executably configured to determine a first preferred segment based on the channel estimates and user data constraints of data to be transmitted, determine a number of sub-carriers assigned to the subset of the plurality of sub-carriers based on one or more signal conditions, select the subset of the plurality of sub-carriers from within the first preferred segment, and further executably configured to control the signal mapper to map the data symbols to the subset of the plurality of sub-carriers; and
 - a Channel Quality Indicator (CQI) receiver coupled to a receiver module and executably configured to process channel characteristic reporting messages received by the receiver module to determine a second preferred segment and further configured to generate a resource assignment message based on the channel characteristic reporting messages.
2. The apparatus of claim 1, wherein the receiver module is executably configured to receive reverse link pilot signals and wherein the scheduler is executably configured to select the subset of the plurality of sub-carriers for a forward link transmission based on the reverse link pilot signals.
3. The apparatus of claim 1, wherein the pilot signals comprise reverse link pilot signals and the scheduler is executably configured to generate a reverse link resource assignment message for transmission to a user terminal based on the channel estimates.
4. The apparatus of claim 1, wherein the scheduler is executably configured to select the first preferred segment as a segment having a largest signal to noise ratio determined from the pilot signals.
5. The apparatus of claim 1, further comprising a frequency hopper module executably configured to enforce a frequency hopping scheme within the first preferred segment.

21

6. A method for channel sensitive scheduling in a communication system including a plurality of sub-carriers spanning an operating frequency band, the method comprising:

determining a channel estimate corresponding to each of a plurality of segments spanning the operating frequency band based on pilot signals, each of the plurality of segments having a bandwidth less than a total bandwidth;

mapping data symbols to a subset of the plurality of sub-carriers in the communication system;

determining a first preferred segment based on the channel estimates and user data constraints of data to be transmitted;

determining a number of sub-carriers assigned to the subset of the plurality of subcarriers based on one or more signal conditions;

selecting the subset of the plurality of sub-carriers from within the first preferred segment; mapping the data symbols to the subset of the plurality of sub-carriers;

and processing channel characteristic reporting messages received by a Channel Quality Indicator (CQI) receiver coupled to a receiver module to determine a second preferred segment and further comprising generating a resource assignment message based on the channel characteristic reporting messages.

7. The method of claim 6, further comprising receiving reverse link pilot signals and selecting the subset of the plurality of sub-carriers for a forward link transmission based on the reverse link pilot signals.

8. The method of claim 6, wherein the pilot signals comprise reverse link pilot signals and generating a reverse link resource assignment message for transmission to a user terminal based on the channel estimates.

9. The method of claim 6, further comprising selecting the first preferred segment as a segment having a largest signal to noise ratio determined from the pilot signals.

10. The method of claim 6, further comprising enforcing a frequency hopping scheme within the first preferred segment.

11. A non-transitory computer-readable tangible medium including computer-executable instructions for executing a method for channel sensitive scheduling in a communication system including a plurality of sub-carriers spanning an operating frequency band, the method comprising:

determining a channel estimate corresponding to each of a plurality of segments spanning the operating frequency band based on pilot signals, each of the plurality of segments having a bandwidth less than a total bandwidth;

mapping data symbols to a subset of the plurality of sub-carriers in the communication system;

determining a first preferred segment based on the channel estimates and user data constraints of data to be transmitted;

determining a number of sub-carriers assigned to the subset of the plurality of sub-carriers based on one or more signal conditions;

selecting the subset of the plurality of sub-carriers from within the first preferred segment;

mapping the data symbols to the subset of the plurality of sub-carriers; and

22

processing channel characteristic reporting messages received by a Channel Quality Indicator (CQI) receiver coupled to a receiver module to determine a second preferred segment and further comprising generating a resource assignment message based on the channel characteristic reporting messages.

12. The non-transitory computer-readable tangible medium of claim 11, the method further comprising receiving reverse link pilot signals and selecting the subset of the plurality of sub-carriers for a forward link transmission based on the reverse link pilot signals.

13. The non-transitory computer-readable tangible medium of claim 11, wherein the pilot signals comprise reverse link pilot signals and the method further comprising generating a reverse link resource assignment message for transmission to a user terminal based on the channel estimates.

14. The non-transitory computer-readable tangible medium of claim 11, the method further comprising selecting the first preferred segment as a segment having a largest signal to noise ratio determined from the pilot signals.

15. The non-transitory computer-readable tangible medium of claim 11, the method further comprising enforcing a frequency hopping scheme within the first preferred segment.

16. An apparatus for channel sensitive scheduling in a communication system including a plurality of sub-carriers spanning an operating frequency band, the apparatus comprising:

means for determining a channel estimate corresponding to each of a plurality of segments spanning the operating frequency band based on pilot signals, each of the plurality of segments having a bandwidth less than a total bandwidth;

means for mapping data symbols to a subset of the plurality of sub-carriers in the communication system;

means for determining a first preferred segment based on the channel estimates and user data constraints of data to be transmitted;

means for determining a number of sub-carriers assigned to the subset of the plurality of sub-carriers based on one or more signal conditions;

means for selecting the subset of the plurality of sub-carriers from within the first preferred segment;

means for mapping the data symbols to the subset of the plurality of sub-carriers; and

means for processing channel characteristic reporting messages received by a Channel Quality Indicator (CQI) receiver coupled to a receiver module to determine a second preferred segment and further comprising means for generating a resource assignment message based on the channel characteristic reporting messages.

17. The apparatus of claim 16, further comprising means for receiving reverse link pilot signals and means for selecting the subset of the plurality of sub-carriers for a forward link transmission based on the reverse link pilot signals.

18. The apparatus of claim 16, wherein the pilot signals comprise reverse link pilot signals and the apparatus further comprises a means for generating a reverse link resource assignment message for transmission to a user terminal based on the channel estimates.

* * * * *