US009302381B2

(12) **United States Patent**
Kondou et al.

(10) **Patent No.: US 9,302,381 B2**
(45) **Date of Patent: Apr. 5, 2016**

(54) **DRIVING TOOL WITH REACTION ABSORBING MECHANISM**

(75) Inventors: **Yoshihiko Kondou**, Tokyo (JP); **Kouji Kubo**, Tokyo (JP)

(73) Assignee: **MAX CO., LTD.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 755 days.

(21) Appl. No.: **13/369,484**

(22) Filed: **Feb. 9, 2012**

(65) **Prior Publication Data**

US 2012/0211540 A1 Aug. 23, 2012

(30) **Foreign Application Priority Data**

Feb. 18, 2011 (JP) 2011-033582
Jan. 18, 2012 (JP) 2012-008039

(51) **Int. Cl.**
B25C 1/00 (2006.01)
B25C 1/06 (2006.01)

(52) **U.S. Cl.**
CPC . ***B25C 1/00*** (2013.01); ***B25C 1/008*** (2013.01); ***B25C 1/06*** (2013.01)

(58) **Field of Classification Search**
CPC B25C 1/06; B25C 1/00; B25C 5/00; B25C 5/10
USPC 227/140
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,610,505	A *	10/1971	Males et al.	227/127
4,630,687	A *	12/1986	Dummermuth	173/131
7,410,085	B2 *	8/2008	Wolf et al.	227/131
7,513,407	B1 *	4/2009	Chang	227/132
8,561,869	B2 *	10/2013	Towfighi	227/130
2008/0121404	A1 *	5/2008	Spasov et al.	173/202
2008/0237294	A1 *	10/2008	Tanimoto et al.	227/129
2008/0296339	A1 *	12/2008	Fielitz et al.	227/107
2009/0078734	A1	3/2009	Chang	
2010/0001032	A1 *	1/2010	Miescher et al.	227/8

FOREIGN PATENT DOCUMENTS

CN	2649269	Y	10/2004
CN	101274425	A	10/2008
EP	1 980 369	A2	10/2008
JP	U-S57-38777		3/1982
JP	62-5888	Y2	2/1987
JP	9-295283		11/1997
JP	A-2010-228084		10/2010

* cited by examiner

Primary Examiner — Andrew M Tecco
Assistant Examiner — Praachi M Pathak
(74) *Attorney, Agent, or Firm* — Drinker Biddle & Reath LLP

(57) **ABSTRACT**

A driving tool is provided with a driver for driving out a fastener from a nozzle, a balancer, and a balancer biasing member for biasing the balancer in a direction away from the nozzle. The balancer moves in the direction away from the nozzle by a biasing force of the balancer biasing member when the driver moves toward the nozzle.

9 Claims, 21 Drawing Sheets



FIG. 1



FIG. 2(a)



FIG. 2(b)



FIG. 3(a)



FIG. 3(b)



FIG. 4(a)



FIG. 4(b)



FIG. 5



FIG. 6



FIG. 7



FIG. 8



FIG. 9



FIG. 10(a)



FIG. 10(b)



FIG. 11



FIG. 12



FIG. 13



FIG. 14(a)



FIG. 14(b)



FIG. 15



FIG. 16



FIG. 17



FIG. 18



FIG. 19(a)



FIG. 19(b)



FIG. 20(c)



FIG. 20(a)



FIG. 20(b)



FIG. 21



DRIVING TOOL WITH REACTION ABSORBING MECHANISM

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a driving tool.

2. Related Art

As types of driving tools, for example, a type in which a tool is driven by a compressed air, and a type in which a tool is driven by a spring force are known.

JP-A-09-295283 discloses a spring drive type nailing machine which can sequentially drive out nails stored in a magazine using a plunger normally biased downward by a spring and a driver fixed to the plunger.

In the above type driving tool, in the case that a nose portion of the driving tool is separated from a driven workpiece due to a reaction on driving, a nail cannot be sufficiently driven or a driven mark caused by the driver off the nail can be left on the workpiece.

To prevent such reaction, the nose portion of the driving tool must be strongly pressed against the workpiece. However, when the nose portion is strongly pressed against the workpiece, the nose portion can damage the workpiece and also can cause an operator to get tired.

SUMMARY OF THE INVENTION

One or more embodiments and modifications thereof of the invention provide a driving tool having a mechanism for absorbing a reaction on driving in order to provide a sufficient driving force with a small pressing force against a workpiece.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** is a section view of a driving tool.

FIGS. **2**(*a*) and **2**(*b*) are external views of a plunger unit.

FIGS. **3**(*a*) and **3**(*b*) are external views of a plunger.

FIG. **4**(*a*) is a section view of the plunger unit taken along **4**A-**4**A line shown in FIG. **4**(*b*). FIG. **4**(*b*) is a side view of the plunger unit.

FIG. **5** is a section view of the plunger unit taken along **5**-**5** line shown in FIG. **4**(*b*).

FIG. **6** is an explanatory view to show how the plunger is pushed up by a drive mechanism.

FIG. **7** is a section view of the plunger unit, showing a state where the plunger exists at its bottom dead center position.

FIG. **8** is a section view of the plunger unit, showing a state where the plunger exists at its top dead center position.

FIG. **9** is a section view of the plunger unit, showing a state where the plunger is moving from the top dead center position to the bottom dead center position.

FIG. **10**(*a*) is a partially enlarged section view of the plunger unit near to a pulley, showing a state where the plunger is moving from the top dead center position to the bottom dead center position. FIG. **10**(*b*) is a (partially omitted) section view taken along the **10**B-**10**B line shown in FIG. **10**(*a*).

FIG. **11** is a section view of the plunger unit, showing a state just after the plunger has reached the bottom dead center position from the top dead center position.

FIG. **12** is an explanatory view to show the equilibrium of forces when the plunger exists at its top dead center position.

FIG. **13** is an explanatory view to show a reaction amount in a state where the plunger is moving from the top dead center position to the bottom dead center position.

FIG. **14**(*a*) is a section view taken along **14**A-**14**A line shown in FIG. **14**(*b*). FIG. **14**(*b*) is a side view of a plunger unit including a vibration isolator, according to a first modification of the embodiment.

FIG. **15** shows a second modification of the embodiment, showing a driving tool with a balancer disposed outside its housing.

FIG. **16** shows a third modification of the embodiment. Specifically, it is a section view of a plunger unit including a tensile spring as a balancer biasing member.

FIG. **17** shows a fourth modification of the embodiment. Specifically, it is a section view of a plunger unit including a magnetic spring as a balancer biasing member.

FIG. **18** shows a fifth modification of the embodiment. Specifically, it is a section view of a plunger unit with a balancer disposed outside its pipe.

FIG. **19**(*a*) is a side section view of a plunger unit including a balancer guide having a different shape according to a sixth modification of the embodiment. FIG. **19**(*b*) is a section view thereof taken along the **19**B-**19**B line shown in FIG. **19**(*a*).

FIGS. **20**(*a*) to **20**(*c*) shows a seventh modification of the embodiment. Specifically, FIG. **20**(*a*) is a front view of a plunger unit with a plunger guide disposed only one side of a pipe. FIG. **20**(*b*) is a section view thereof when viewed from above. FIG. **20**(*c*) is a section view thereof when viewed from side.

FIG. **21** shows a fifth modification of the embodiment, where a driving tool using a flywheel is employed.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Description will be given below of an embodiment and modifications thereof with reference to the accompanying drawings.

The embodiment and the modifications described herein are not intended to limit the invention but only to exemplify the invention, and all features or combinations of the features of the embodiment and the modifications are not always essential to the invention.

A driving tool **10** according to the embodiment is a spring drive type nailing machine for carrying out its driving operation using a spring force, while it strikes out a nail as a fastener. The driving tool **10**, as shown in FIG. **1**, includes, within its housing **11**, a plunger unit **30** connected to a driver **31** for driving out the nail, a drive mechanism **20** for actuating the plunger unit **30**, a magazine **12** storing therein connected nails (connected staples) to be driven out by the driver **31**, and so on.

The magazine **12** includes a nose portion **15** formed in its front end portion, while the leading one of the connected nails stored in the magazine **12** is supplied to the nose portion **15** by a supply device (not shown). The leading nail supplied to the nose portion **15** is driven out from a nozzle **16** formed in the leading end of the nose portion **15**. The driver **31** of this embodiment is formed as part of the plunger unit **30** and, when the plunger unit **30** is operated, the driver **31** is caused to slide toward the nozzle **16** to thereby drive out the nail supplied to the nose portion **15** from the nozzle **16**.

The plunger unit **30** is structured in an elongated bar-like unit such that, as shown in FIG. **2**(*a*) and FIG. **2**(*b*), two plunger guides **34** are fixed respectively to the two sides of a cylindrical pipe **35** functioning as a balancer guide A plunger **32** is slidably mounted on the outer surface of the pipe **35**, while a plunger biasing member **33** for normally biasing the plunger **32** toward the nozzle **16** is also mounted on the outer surface thereof.

Here, the plunger guide **34** is used to guide the sliding movement of the plunger **32** and, as shown in FIGS. **4**(*a*) to **5**, it has a rail portion **34***a* formed in its inside facing the pipe **35** and extending in its longitudinal direction.

The plunger unit **30** is fixed within the housing **11** such that the longitudinal direction of the pipe **35** can be parallel to the nail drive-out direction and the driver **31** can become most distant from the grip **13** (in other words, the pipe **35** can be situated nearer to the grip **13** than the driver **31**).

The plunger **32** includes in its side portion a driver connecting portion **32***b* for connecting the driver **31** thereto. The driver **31** is connected to this driver connecting portion **32***b* and thus it is able to slide to the sliding movement of the plunger **32**.

The plunger **32**, as shown in FIGS. **3**(*a*) and **3**(*b*), has a pipe hole **32***e* which is opened up in its center and through which the pipe **35** can be penetrated. On the wall portions of both sides of the pipe hole **32***e*, there are provided guide rollers **32***a*. Each guide roller **32***a*, as shown in FIG. **4**(*a*), slides within the rail portion **34***a* of the plunger guide **34**. The plunger **32**, due to provision of the pipe hole **32***e* and guide rollers **32***a*, can be guided to slide along the pipe **35** and plunger guide **34**.

The plunger **32** has first and second engaging portions **32***c* and **32***d* for engagement with the drive mechanism **20** which, as shown in FIGS. **3**(*a*) and **3**(*b*), are respectively provided on and projected from its side portion. These first and second engaging portions **32***c* and **32***d* are disposed on the opposite side (on the drive mechanism **20** side) to the side where the driver connecting portion **32***b* is disposed. Here, the first and second engaging portions **32***c* and **32***d* are disposed respectively at mutually different height positions (positions with respect to the nozzle **16**). That is, as shown in FIG. **3**(*b*), the first engaging portion **32***c* is disposed at a position nearer to the nozzle **16** than the second engaging portion **32***d*. Thus, the first and second engaging portions **32***c* and **32***d* are disposed alternately with respect to the sliding direction of the plunger **32**.

The drive mechanism **20** for pushing up the plunger **32** against the biasing force of the plunger biasing member **33**, as shown in FIG. **6**, includes multiple gears. The multiple gears can be rotated by the driving force of a motor **17**. The motor **17** can be operated when a trigger **14** is operated and its operation will continue until a micro switch (not shown) detects that the plunger **32** has moved to a given position.

Here, within the driving tool **10**, there is provided a control apparatus (not shown) including a CPU, a RAM and the like, while the control apparatus controls the driving of the motor **17** according to input signals from the trigger **14** and micro switch.

The drive mechanism **20** rotates the gears in engagement with the plunger **32**, thereby pushing up the plunger **32**. And, when the engagement of the gears with the plunger **32** is removed, the plunger **32** is caused to move due to the biasing force of the plunger biasing member **33**, whereby the driver **31** connected to the plunger **32** is slid toward the nozzle **16** for driving out the nail.

Specifically, in the drive mechanism **20**, as shown in (a) of FIG. **6**, on a torque gear plate **21** fixed to the housing **11**, there are pivotally supported first and second torque gears **22** and **23** in such a manner that they can be rotated respectively. Here, the first and second torque gears **22** and **23** are arranged side by side along the sliding direction of the plunger **32**, while the first torque gear **22** is disposed nearer to the nozzle **16** than the second torque gear **23**. Thus, the plunger **32** is engaged sequentially with the first and second torque gears **22** and **23** in this order to be thereby lifted up gradually.

(b) of FIG. **6** shows a state where the plunger **32** exists at its bottom dead center position (a state where the driving-out of the nail by the driver **31** is completed). When the first and second torque gears **22** and **23** are rotated from this state, the torque roller **22***a* of the first torque gear **22** is engaged with the first engaging portion **32***c* of the plunger **32**.

As shown in (c) of FIG. **6**, the plunger **32** is lifted up by the first torque gear **22** with the above engagement maintained. When the first torque gear **22** is rotated up to a position where the torque roller **22***a* comes to its upper-most position, the engagement between the torque roller **22***a* and first engaging portion **32***c* is removed. At the then time, before the engagement between the torque roller **22***a* and first engaging portion **32***c* is removed, the torque roller **23***a* of the second torque gear **23** is engaged with the second engaging portion **32***d* of the plunger **32**.

As shown in (d) of FIG. **6**, with the above engagement maintained, the plunger **32** is lifted up by the second torque gear **23** and is thereby moved up to its top dead center position.

After then, as shown in (e) of FIG. **6**, when the second torque gear **23** is further rotated up to a position where the torque roller **23***a* comes to its upper-most position, the engagement between the torque roller **23***a* and second engaging portion **32***d* is removed. Thus, since the plunger **32** is biased by the plunger biasing member **33**, it is moved down to its bottom dead center position shown in (b) of FIG. **6**. Consequently, the driver **31** connected to the plunger **32** is caused to slide toward the nozzle **16** for driving out the nail.

Here, in this embodiment, the plunger **32** normally waits at its top dead center position shown in (d) of FIG. **6**. When the trigger **14** is operated, the drive mechanism **20** is operated to move the plunger **32** sequentially through the states respectively shown in (e) to (b) and (b) to (c) of FIG. **6** and, after then, the plunger **32** waits again at the top dead center position shown in (d) of FIG. **6**.

That is, when the trigger **14** is operated, on receiving this operation signal, the control apparatus starts to drive the motor **17**. Thus, when the gear is rotated to a position shown in (e) of FIG. **6**, the nail driving operation is carried out. And, also after completion of the nail driving operation, the control apparatus drives the motor on. Consequently, when the plunger **32** moves up to the top dead center position shown in (d) of FIG. **6**, the above-mentioned micro switch is depressed by the plunger **32**. On receiving the signal of the micro switch, the control apparatus controls the motor **17** to stop its driving operation.

Here, the plunger unit **30** of this embodiment includes a reaction absorbing mechanism for absorbing the reaction to be generated in the above nail driving operation.

The reaction absorbing mechanism, as shown in FIG. **5**, includes a balancer **36** disposed slidably within the pipe **35** and a balancer biasing member **37** for biasing the balancer **36** in the direction away from the nozzle **16**.

The balancer **36** is a cylindrical metal member formed to follow the inside diameter of the pipe **35** and can slide inside the pipe **35**. Here, as described above, since the pipe **35** is disposed parallel to the nail drive-out direction, the balancer **36** to slide within this pipe **35** is formed to slide parallel to the driver **31**.

The balancer biasing member **37** is a spring mechanism constituted of a compression spring which is disposed within the pipe **35** and can be operated there. The balancer biasing member **37** is disposed nearer to the nozzle **16** than the balancer **36** and biases the balancer **36** in the direction away from the nozzle **16**.

Here, in this embodiment, the pipe **35** is formed to have a cylindrical shape with its outer surface closed. However, instead, the pipe **35** may also be formed such that it includes a slit or an opening in its outer surface, or it may be formed to have a prism shape or other shapes.

The balancer **36** is connected to the plunger **32** through a string-shaped wire **39** and thus, when the plunger **32** moves, it can be moved in linking with the plunger **32**. Specifically, since the direction of a force to be applied to the wire **39** by a pulley **40** provided as a direction changing portion is changed about 180°, when the plunger **32** is pushed up by the drive mechanism **20** and the driver **31** is thereby slid in the direction away from the nozzle **16**, the balancer **36** is pulled and moved by the wire **39** in the direction of the nozzle **16**. Thus, the balancer biasing member **37** is compressed to thereby store a spring force therein.

When the plunger **32** is released from the drive mechanism **20** and the driver **31** is thereby slid toward the nozzle **16** to carry out a nail driving operation, the pull by the wire **39** is removed. Therefore, the balancer **36** is biased and moved by the balancer biasing member **37** in the direction away from the nozzle **16**.

The reaction absorption in this embodiment is carried out by the reaction due to the bias of the balancer biasing member **37**. Now, description will be given below specifically of the mechanism of the reaction absorption with reference to the operation of the plunger unit **30**.

FIG. **7** shows the plunger unit **30** with the plunger **32** at the bottom dead center position. In this state, the plunger **32** is biased by a plunger biasing member **33** toward the nozzle **16** and is pressed against a rubber-made bumper **41**. Also, the balancer **36** is biased by the balancer biasing member **37** in the direction away from the nozzle **16** and is pressed against a rubber-made balancer stopper **38**. In this case, the wire **39** is pulled almost with no loosening.

FIG. **8** shows a state where the plunger **32** is pushed up by the drive mechanism **20** and exists at its top dead center position. In this state, the plunger is pushed up in the direction away from the nozzle **16** against the biasing force of the plunger biasing member **33**. Also, as the plunger **32** is pushed up, the wire **39** is pulled and the balancer **36** connected to the other end of the wire **39** is pulled toward the nozzle **16** against the biasing force of the balancer biasing member **37**.

In this state, as shown in FIG. **12**, the housing **11** receives the biasing forces of the plunger biasing member **33** and balancer biasing member **37**, while the forces balance with each other.

In the state of FIG. **8**, when the engagement between the plunger **32** and drive mechanism **20** is removed, as shown in FIG. **9**, the biasing force of the plunger biasing member **33** allows the plunger **32** to start to move toward the nozzle **16**. Thus, since the wire **39** pulling the balancer **36** is loosened, the balancer **36** is free and the biasing force of the balancer biasing member **37** allows the balancer **36** to start to move in the direction away from the nozzle **16**.

In this case, as shown in FIG. **13**, the biasing reaction P**1** of the plunger biasing member and driving reaction P**2** generate the reaction on driving which provides a force to part the driving tool **10** away from the workpiece.

However, in the driving tool **10** of this embodiment, due to the biasing reaction P**3** of the balancer biasing member, there is applied a force to press the driving tool **10** against the workpiece. That is, since the balancer biasing member **37** biases the balancer **36** in the direction away from the nozzle **16**, on the opposite side to the balancer **36**, there is generated a reaction in a portion for receiving the balancer biasing member **37**. That is, there is generated a force to press the workpiece against the housing **11** of the driving tool **10**.

Therefore, the biasing reaction P**1** of the plunger biasing member and driving reaction P**2** cancel the biasing reaction P**3** of the balancer biasing member, thereby reducing the reaction on driving. Here, a reaction, which cannot be cancelled by the biasing reaction P**3** of the balancer biasing member, is to be cancelled by a pressing load P**4** given by an operator (a mechanical weight can also be added thereto).

The loosening of the wire **39** in the driving operation is provided because the moving speed of the plunger **32** is set faster than the moving speed of the balancer **36**. That is, by adjusting the difference between the biasing forces of the plunger biasing member **33** and balance biasing member **37** or the weights or sliding resistances of the plunger **32** and balancer **36**, the moving speed of the plunger **32** is set faster than the moving speed of the balancer **36**. Therefore, the wire **39** can be loosened due to the difference between these speeds.

The wire **39**, as shown in FIG. **10**(*a*), is loosenably looped on a pulley **40** and is guided using a space S formed by the housing **11**. Therefore, since, even when the loosened wire **39** comes off the pulley **40**, it is guided by the space S, it is prevented from being caught by other portions.

FIG. **11** shows a state just after the plunger **32** moves further from the state of FIG. **9** and reaches the bumper **41** (just after the nail driving operation is ended). As shown in FIG. **11**, just after the plunger **32** reaches the bumper **41**, the balancer **36** has not reached the balancer stopper **38** but it is caused to move on due to the biasing force of the balancer biasing member **37**. That is, since the moving speed of the plunger **32** is set faster than the moving speed of the balancer **36**, after the plunger **32** reaches the bumper **41**, the balancer **36** reaches the balancer stopper **38**. When the balancer **36** reaches the balancer stopper **38**, the plunger unit **30** returns to the state of FIG. **7**.

In this embodiment, since there is set a time lag between the stop timing of the plunger **32** and the stop timing of the balancer **36** in this manner, the impact absorption by the balancer **36** and balancer biasing member **37** (generation of the biasing reaction P**3** of the balancer biasing member) is allowed to continue until the completion of the nail driving operation. Also, although a force is applied in the reaction direction due to impacts caused by the balancer **36** colliding with the balancer stopper **38**, the generating timing of this reaction is set after completion of the nail driving operation.

In accordance with the above embodiment, a driving tool may include: a driver **31** provided to be slidable toward a nozzle **16** formed in a leading end of the tool **10** and adapted to drive out a fastener from the nozzle **16**; a balancer **36** provided to be slidable with respect to a housing **11** of the tool **10**; and a balancer biasing member **37** adapted to bias the balancer **36** in a direction away from the nozzle **16**. The balancer **36** may be adapted to move in the direction away from the nozzle **16** by a biasing force of the balancer biasing member **37**, in accordance with a sliding movement of the driver **31** toward the nozzle **16**.

According to this structure, in the driving time, although there is applied a force to the driving tool **10** in a direction away from the workpiece, at the same time, due to the biasing reaction of the balancer biasing member **37** applied to the balancer **36**, there is applied a force in a direction to press the driving tool **10** against the workpiece. That is, "the force applied to the driving tool **10** in the direction away from the workpiece" and "the force applied in the direction to press the driving tool **10** against the workpiece" cancel each other, thereby being able to absorb the reaction on driving. There-

fore, since a sufficient driving force can be obtained with a small pressing force against the workpiece, the fatigue of an operation can be reduced. Also, it is hard to raise a problem that the driver **31** can be caused to come off the nail due to the reaction and thus can damage the workpiece.

The balancer biasing member **37** may include a spring mechanism which is adapted to accumulate the biasing force when the driver **31** moves in the direction away from the nozzle **16**.

According to this structure, the spring force thereof can generate the "force pressing the tool toward the workpiece".

The balancer **36** may be structured to be pulled toward the nozzle **16** through a string-shaped member **39** when the driver **31** moves in the direction away from the nozzle **16**.

According to this structure, it is possible to physically link the balancer **36** with the driver **31** and thus operate the balancer **36** to the driving operation.

The balancer **36** may slide parallel to the driver **31**.

According to this structure, since "the force applied in the direction away from the workpiece" and "the pressing force applied toward the workpiece" are parallel and opposite in direction, the reaction on driving can be absorbed highly efficiently.

The driving tool may further include: a plunger **32** to which the driver **31** is connected; a plunger biasing member **33** adapted to bias the plunger **32** toward the nozzle **16**; a drive mechanism **20** adapted to drive the plunger **32** in the direction away from the nozzle **16** against a biasing force of the plunger biasing member **33** and to release the plunger **32** located in a position away from the nozzle **16** so that the driver **31** moves toward the nozzle **16** by the biasing force of the plunger biasing member **33** and drives the fastener; a string-shaped member **39** that connects the balancer **36** and the plunger **32** to each other; and a direction changing portion **40** adapted to change a direction of a force applied to the string-shaped member **39**. The balancer **36** may be adapted to be pulled by the string-shaped member **39** and to move toward the nozzle **16** in accordance with a movement of the plunger **32** in the direction away from the nozzle **16**, and the balancer **36** may be also adapted to move in the direction away from the nozzle **16** by the biasing force of the balancer biasing member **37** in accordance with a movement of the plunger **32** toward the nozzle **16** when the plunger **32** is released.

According to this structure, the absorbing mechanism can absorb such reaction effectively.

The string-shaped member **39** (wire **39**) may be loosenably looped on the direction changing portion **40** (pulley **40**).

According to this structure, the balancer **36** will not be pulled by the plunger **32**. Therefore, due to the loosened wire **39**, the balancer **36** is released from the plunger **32** (wire **39**) and is thereby allowed to operate independently. Thus, the balancer **36** can be biased by the biasing force of the balancer biasing member **37** without being obstructed by the plunger **32** (wire **39**). The reaction to this biasing force generates a force to press the driving tool **10** toward the workpiece to thereby be able to absorb the reaction on driving.

The balancer **36** may be provided so as to be slidable within a pipe **35** (balancer guide **35**, cylindrical member **35**) which is provided parallel to the nail drive-out direction. On both sides of the pipe **35**, there may be provided plunger guides **34** respectively for guiding the sliding movement of the plunger **32**.

According to this structure, since the balancer **36** can be disposed inside the pipe **35** and the plunger **32** can be disposed outside the pipe **35**, the plunger unit **30** with a reaction absorbing mechanism can be made compact, its manufacturing cost can be reduced and the size of a product can also be reduced.

The plunger unit **30** may be fixed within the housing **11** in such a manner that the driver **31** is most distant from the grip **13**. That is, the balancer **36** may be disposed nearer to the grip **13** than the driver **31**.

According to this structure, since the driver **31** can be situated as near as possible to the counter-grip-**13** side, it is not necessary to provide an extra projection on the counter-grip-**13** side. No provision of a projection on the counter-grip-**13** side makes it possible to use the nose portion **15** as near as possible to the wall surface. Therefore, for example, the plunger unit **30** can be applied to a finishing driving tool which is required to be able to drive a nail into an edge.

The balancer **36** may be adapted to continue its movement, even after the nail driving operation by the driver **31** is completed.

According to this structure, since the ending timing of the reaction absorption by the balancer **36** can be set later than the completion of the nail driving operation by the driver **31**, the reaction absorbing mechanism can be positively operated up to the completion of the nail driving operation.

As shown in FIG. **14**, when fixing the plunger unit **30** to the housing **11**, a vibration isolator **50** may also be interposed between the plunger unit **30** and housing **11**. The vibration isolator **50** may be made of resilient material such as rubber or urethane.

Specifically, as shown in FIGS. **14**(*a*) and **14**(*b*), the vibration isolator **50** can be provided, for example, between the plunger guides **34** and housing **11** or on a contact portion between the plunger unit **30** and the housing **11** at an opposite side of the nozzle **16**.

Provision of such vibration isolator **50** can restrict the vibrations of the plunger unit **30** in operation (such as the vibrations of the plunger biasing member **33** and balancer biasing member **37**, vibrations to be generated due to the sliding movements of the plunger **32** and balancer **36**, and vibrations to be generated due to the collision of the plunger **32** and bumper **41**). Thus, noises to be generated when driving a nail can be reduced.

Here, in the above embodiment, although description has been given of an example using a spring drive type nailing machine to be driven by a spring force, the invention is not limited to this but it can also be applied a tool to be driven by other drive source such as compressed air, electricity or the like.

In the above embodiment, although the compression spring is used as the balancer biasing member **37**, this is not limitative but a tensile spring may also be used. And, other biasing means than the spring may also be used provided that it can generate a reaction. For example, an elastic member other than a spring may be used, electric or magnetic means may be used, or biasing means using hydraulic pressure or the like may be used.

In the above embodiment, although the balancer **36** is structured to slide parallel to the driver **31**, this is not limitative but it may also be structured to slide with a certain angle relative to the sliding direction of the driver **31**.

In the above embodiment, although the moving speed of the plunger **32** is set faster than the moving speed of the balancer **36**, this is not limitative. The moving speed of the plunger **32** and the moving speed of the balancer **36** may also be set equal, or the moving speed of the plunger **32** may be set slower than the moving speed of the balancer **36**.

In the above embodiment, although, in the driving operation, the plunger **32** and balancer **36** start to move simulta-

neously, this is not limitative. For example, by loosening the wire **39** in a state where the plunger **32** exists at its top dead center position, the movement of the balancer **36** can be set later than the movement of the plunger **32**.

In the above embodiment, although the balancer **36** and plunger **32** are connected by the wire **39**, this is not limitative. For example, the balancer **36** and plunger **32** may also be connected by a belt.

In the above embodiment, although the plunger unit **30** is disposed within the housing **11**, this is not limitative. For example, as shown in FIG. **15**, the balancer **36** may also be disposed outside the housing **11**. Also, the whole plunger unit **30** may be disposed outside the housing **11**. In this case, the whole plunger unit **30** may also be covered with other case than the housing **11**.

In the above embodiment, although the compression spring is used as the balancer biasing member **37**, this is not limitative. For example, as shown in FIG. **16**, a tensile spring may also be used as the balancer biasing member **37**. Also, as shown in FIG. **17**, a magnetic spring (a member in which two mutually repelling magnets are disposed opposed to each other) may also be used as the balancer biasing member **37**.

In the above embodiment, although the wire **39** is used as the string-shaped member, this is not limitative. For example, a belt, a strip cloth, a string or a cord may also be used.

In the above embodiment, although the balancer **36** is structured to slide inside the pipe **35**, this is not limitative. For example, as shown in FIG. **18**, the balancer **36** may also be structured to slide outside the pipe **35**. In this case, as the drive mechanism **20**, there may be provided, for example, such a plunger hoisting mechanism **42** as shown in FIG. **18**. That is, by operating the plunger hoisting mechanism **42** using a motor, a plunger hoisting wire **43** may be hoisted to thereby push up the plunger **32** against the biasing force of the plunger biasing member **33**.

In the above embodiment, although the cylindrical pipe **35** is used as a balancer guide for guiding the balancer **36**, this is not limitative. For example, as shown in FIG. **19**, there may also be used a balancer guide **35** shaped to be able to guide the balancer **36** while sandwiching it from both sides at two or more points.

Here, in the example of FIG. **19**, although the balancer guide **35** has a substantially arc-like shape following the outer periphery of the balancer **36**, the range containing the sandwiching contact points may be reduced in size and thus the balancer may have a rectangular shape instead of the arc-like shape.

In the above embodiment, although the pulley **40** is used as the direction changing portion, this is not limitative. For example, a string-shaped member may be simply slid along the edge portion of a given member, whereby such edge portion may be used as the direction changing portion.

In the above embodiment, although the plunger guides **34** for guiding the sliding movement of the plunger **32** are disposed on both sides of the cylindrical portion (pipe **35**), this is not limitative. For example, as shown in FIG. **20**, a plunger guide **34** for guiding the sliding movement of the plunger **32** may also be disposed on only one side of the cylindrical portion (pipe **35**). Or, as many as possible plunger guides may be provided on the periphery of the cylindrical portion (pipe **35**) to thereby enhance the guide performance.

As shown in FIG. **21**, a flywheel mechanism may also be used to absorb the reaction. That is, as shown in FIG. **21**, there is provided a flywheel **44** which rotates in a clockwise direction in the vicinity of the central portion of the main body of the driving tool **10**. And, as shown in FIG. **21**, when, simultaneously with the driving operation, the flywheel **44** is rotated in a direction where its front side (driver **31** side) is raised, due to the reaction thereof, the main body of the driving tool **10** receives a rotation force in the opposite direction (a direction where its front side is lowered). Therefore, this rotation force and the reaction on driving cancel the floating force of the main body of the driving tool **10**, thereby being able to reduce the reaction on driving.

The flywheel **44** may be adapted to rotate such that the rotational movement of the flywheel **44** is independent from the straight-going movement of the driver **31**. In contrast, the flywheel **44** may be rotated in linking with the driver **31**. For example, using a rack belt or a wire, the straight-going movement of the driver **31** may be converted to the rotational movement of the flywheel **44**, whereby the flywheel **44** may be rotated in linking with the driving operation of the driver **31**. Also, as the rotation center of the flywheel **44** becomes nearer to the center of gravity of the main body of the driving tool **10**, the flywheel rotates nearer around the center of gravity, thereby being able to absorb the reaction more effectively. Therefore, preferably, the rotation center of the flywheel **44** may be set as near as possible to the center of gravity of the main body of the driving tool **10**.

DESCRIPTION OF REFERENCE NUMERALS AND SIGNS

10: Driving tool
11: Housing
12: Magazine
13: Grip
14: Trigger
15: Nose portion
16: Nozzle
17: Motor
20: Drive mechanism
21: Torque gear plate
22: First torque gear
22*a*: Torque roller
23: Second torque gear
23*a*: Torque roller
30: Plunger unit
31: Driver
32: Plunger
32*a*: Guide roller
32*b*: Driver connecting portion
32*c*: First engaging portion
32*d*: Second engaging portion
32*e*: Pipe hole
33: Plunger biasing member
34: Plunger guide
34*a*: Rail portion
35: Pipe (balancer guide)
36: Balancer
37: Balancer biasing member
38: Balancer stopper
39: Wire (string-shaped member)
40: Pulley (direction changing portion)
41: Bumper
42: Plunger hoisting mechanism
43: Plunger hoisting wire
44: Flywheel
50: Vibration isolator
S: Space
P1: Biasing reaction of plunger biasing member
P2: Driving reaction
P3: Biasing reaction of balancer biasing member
P4: Operator's pressing load

What is claimed is:

1. A driving tool comprising:

a driver provided to be slidable toward a nozzle formed in a leading end of the tool and adapted to drive out a fastener from the nozzle;

a plunger adapted to be connected with the driver;

a plunger biasing member adapted to bias the plunger toward the nozzle;

a balancer provided to be slidable toward the nozzle;

a balancer biasing member adapted to bias the balancer in a direction away from the nozzle;

a drive mechanism adapted to drive the plunger in the direction away from the nozzle against a biasing force of the plunger biasing member and to release the plunger located in a position away from the nozzle so that the driver moves toward the nozzle by the biasing force of the plunger biasing member and drives the fastener;

a string-shaped member that connects the balancer and the plunger to each other; and

a direction changing portion adapted to change a direction of a force applied to the string-shaped member,

wherein the balancer is adapted to be pulled by the string-shaped member in a state of tension, and to move toward the nozzle when the plunger moves in the direction away from the nozzle, and

the balancer is also adapted to move in the direction away from the nozzle by the biasing force of the balancer biasing member when the plunger is released and moves toward the nozzle, and the string-shaped member is in a relaxed state, and

wherein the balancer biasing member is connected by the string-shaped member in the relaxed state with the plunger biasing member when the plunger is released and the plunger moves toward the nozzle.

2. The driving tool according to claim 1, wherein the balancer biasing member comprises a spring mechanism which is adapted to accumulate the biasing force when the driver moves in the direction away from the nozzle.

3. The driving tool according to claim 1, wherein the balancer is adapted to slide substantially parallel to the driver.

4. The driving tool according to claim 1, wherein the balancer is provided to be slidable along a balancer guide provided substantially parallel to the fastener drive-out direction.

5. The driving tool according to claim 1, wherein the string-shaped member is loosenably looped on the direction changing portion.

6. The driving tool according to claim 5, wherein when the string-shaped member is loosened, the balancer is released from the plunger and is thereby allowed to operate independently.

7. The driving tool according to claim 1, wherein a plunger guide is provided on the cylindrical portion, and the plunger is slidably guided by the plunger guide.

8. The driving tool according to claim 1, wherein a first distance between the balancer and a grip is less than a second distance between the balancer and the driver.

9. The driving tool according to claim 1, wherein the balancer is adapted to continue its movement even after a completion of a fastener driving operation by the driver.

* * * * *