



US009315981B2

(12) **United States Patent**
Anastasio et al.

(10) **Patent No.:** **US 9,315,981 B2**
(45) **Date of Patent:** **Apr. 19, 2016**

(54) **SEPARATOR MODULE FOR A
STORMWATER GULLY CHAMBER**

5,849,181 A *	12/1998	Monteith	210/170.03
6,062,767 A *	5/2000	Kizhnerman et al.	210/170.03
6,068,765 A *	5/2000	Monteith	210/170.03
6,149,803 A *	11/2000	DiLoreto et al.	210/170.03
6,254,770 B1 *	7/2001	Remon	210/163
6,264,835 B1 *	7/2001	Pank	210/170.03
6,743,354 B1 *	6/2004	Evans et al.	210/170.03
7,314,549 B2 *	1/2008	Swift	210/170.03
7,344,636 B2	3/2008	Faram et al.	
7,922,916 B1 *	4/2011	Witt	210/170.03
2004/0188357 A1	9/2004	Moore	
2011/0278237 A1 *	11/2011	McInnis	210/163

(71) Applicant: **Hydro International plc**, Clevedon (GB)

(72) Inventors: **Andrew Scott Anastasio**, Portland, ME (US); **Anthony Tadek Leslie Kolanko**, Bristol (GB); **Kevin John McKee**, Scarborough, ME (US); **Andrew Steven Kane**, North Somerset (GB); **David Andrew Scott**, Portland, ME (US)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Hydro International PLC**, Clevedon (GB)

WO WO97/41316 11/1997

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 165 days.

OTHER PUBLICATIONS

Search Report and Written Opinion for PCT/GB2014/052279 (mailed Nov. 11, 2014).

(21) Appl. No.: **13/967,078**

* cited by examiner

(22) Filed: **Aug. 14, 2013**

Primary Examiner — Christopher Upton

(65) **Prior Publication Data**

(74) *Attorney, Agent, or Firm* — Klarquist Sparkman, LLP

US 2015/0048014 A1 Feb. 19, 2015

(51) **Int. Cl.**
E03F 5/14 (2006.01)
E03F 5/04 (2006.01)

(57) **ABSTRACT**

(52) **U.S. Cl.**
CPC **E03F 5/04** (2013.01); **E03F 5/0403** (2013.01); **E03F 5/14** (2013.01)

A separator module for a stormwater gully chamber is disclosed, the separator module comprising: a partition arrangement which, in use, divides the chamber into an upper region and a lower region, the partition arrangement comprising: an inlet chute having an opening which, in use, provides an inlet to the lower region from the upper region; an outlet chute having an opening which, in use, provides an outlet from the lower region to the upper region; and a weir separating the outlet chute from the inlet chute; wherein at least a portion of the partition arrangement is flexible so as to allow an external diameter of the partition arrangement to be adjusted to fit different sized chambers.


(58) **Field of Classification Search**
CPC E03F 5/04; E03F 5/0403; E03F 5/0404; E03F 5/041; E03F 5/14
USPC 210/170.03, 232, 254, 532.1
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,405,539 A *	4/1995	Schneider	210/170.03
5,753,115 A *	5/1998	Monteith	210/170.03

11 Claims, 7 Drawing Sheets






FIG. 1

PRIOR ART




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

1

SEPARATOR MODULE FOR A STORMWATER GULLY CHAMBER

BACKGROUND

This invention relates to a separator module for a stormwater gully chamber.

Conventional gullies under roadways and other paved areas comprise a chamber having inlet and outlet pipes which open into the chamber at a position above the bottom of the chamber. There may also be a top inlet, which provides access to the interior of the chamber through a grating provided at the roadway surface, for example in a gutter. In use, solids entering the chamber, whether from the inlet pipe or through the grating, collect under gravity in the base of the chamber and can be extracted at intervals by means of a suction pipe introduced into the chamber after removing the grating. Such gullies have a low separation efficiency. Furthermore, in the event of heavy storm flows, collected solids in the base of the chamber, and solids floating on the surface tend to be stirred up, and can pass into the outlet pipe.

A hydrodynamic vortex separator may be used to improve the separation efficiency of the gully. Such separators are suitable for removing sediment, litter and oil from surface water runoff.

FIG. 1 shows an example of a hydrodynamic vortex separator used in a stormwater gully, as disclosed in U.S. Pat. No. 7,344,636. The separator comprises an inlet compartment 3 and an outlet compartment 5 installed within a chamber 7. The inlet compartment 3 is connected to an inlet duct and the outlet compartment 5 is connected to an outlet duct. The inlet compartment 3 and the outlet compartment 5 are offset from one another around the circumference of the chamber 7 and are fluidically connected by a bypass duct 9.

An opening 11 is provided at the bottom of the inlet compartment 3 which serves as an inlet to the interior of the gully chamber 7. The inlet opening 11 is oriented so that inflowing liquid creates a circulating flow within the chamber 7 which assists in causing any solids within the incoming flow to accumulate and fall to the bottom of the chamber 7 or rise to the fluid surface depending upon their density. Similarly, the outlet compartment 5 has an opening which serves as an outlet from the interior of the chamber 7. The outlet opening is oriented so that outflowing liquid passes through the outlet opening in a direction opposite that of the circulating flow. The relative orientations of the inlet and outlet openings means that, even under conditions of heavy flow, solids will be swept past the outlet opening rather than leave the chamber.

A weir is provided between the inlet compartment 3 and the bypass duct 9 so that, in periods of heavy flow, only some of the flow entering the inlet compartment 3 will pass through the inlet opening 11, and the remainder will pass over the weir and through the bypass duct 9 directly to the outlet compartment 5.

Although the bypass duct 9 may be cut to an appropriate length so that the inlet and outlet compartments 3, 5 align with the inlet and outlet ducts, the bypass duct 9 must be made available in different radii of curvature to conform to chambers having different diameters. Further, the size, number and position of the ducts is restricted somewhat by this arrangement.

In addition, the inlet and outlet compartments 3, 5 and the bypass duct 9 limit the bypass capacity of the separator.

2

It is therefore desired to provide a separator module which addresses or alleviates some or all of these issues.

SUMMARY

5

In accordance with an aspect of the invention, there is provided a separator module for a stormwater gully chamber, the separator module comprising: a partition arrangement which, in use, divides the chamber into an upper region and a lower region, the partition arrangement comprising: an inlet chute having an opening which, in use, provides an inlet to the lower region from the upper region; an outlet chute having an opening which, in use, provides an outlet from the lower region to the upper region; and a weir separating the outlet chute from the inlet chute. At least a portion of the partition arrangement is flexible so as to allow an external diameter of the partition arrangement to be adjusted to fit different sized chambers.

The separator module may be particularly beneficial in the US and UK markets, where chambers are sized based on metric and imperial measurements respectively. The flexible nature of the partition arrangement may also provide an improved seal against the chamber.

The partition arrangement may comprise a partition plate and a separate ledger component which, in use, connects to an inner wall of the chamber. The ledger component supports the partition plate within the chamber such that the partition plate does not directly contact the chamber, the ledger component defining the external diameter of the partition arrangement. The ledger component comprises a discontinuous flexible annular ring having a gap which allows the ledger component to expand or contract so as to alter the external diameter of the partition arrangement.

The ledger component may be resiliently deformed when inserted into the chamber.

The partition plate and the ledger component may comprise complementary structures which interlock with one another. The complementary structures can fix the relative orientations of the partition plate and the ledger component. The complementary structures may, in particular, be formed by the weir plates described below.

The partition arrangement may comprise a partition plate and separate inlet and outlet chute components forming the inlet and outlet chutes respectively, the partition plate having first and second openings for receiving the inlet and outlet chute components and an axially extending central standpipe portion disposed between the first and second openings. The central portion comprises first and second slots extending axially from the first and second openings. The width of the first and second slots and thus the width of the first and second openings is adjustable so as to alter the external diameter of the partition arrangement.

The inlet and outlet chute components may each comprise a backing plate which is received within the central standpipe portion, the backing plates covering the first and second slots. The backing plates may therefore seal against the slots to prevent water from passing through them.

The inlet and outlet chute components may each comprise a pair of circumferentially extending flanges which abut the partition plate. The circumferentially extending flanges allow the width of the first and second openings to be adjusted and abut with the partition plate over the full range of movement.

The central standpipe portion may comprise a bypass port, a top edge of which is positioned at or below a top edge of the weir. As the top edge of the bypass port is positioned at or below the top edge of the weirs, any accumulated floatable material in the upper region is able to pass into the lower

65

3

region before the water level reaches the upper edge of the weir and so does not pass to the outlet chute.

The partition arrangement may further comprise an annular bypass channel fluidically coupling the inlet chute and the outlet chute via the weir. The annular bypass channel may be formed between the central standpipe portion and the surrounding wall of the chamber. The annular nature of the bypass channel maximizes its length and so increases the bypass capacity of the module. The bypass channel may prevent washout of material captured in the lower region during heavy flow conditions.

The annular bypass channel may be open at its top so as to avoid placing any limitation on the bypass capacity of the module. The head room over the weir is thus limited only by the height of the chamber.

The annular bypass channel may be inclined from the inlet chute to the outlet chute. This may prevent material from accumulating on the surface of the partition plate.

The annular bypass channel may be inclined at an angle of 30 to 40 degrees from horizontal.

The weir may comprise a pair of weir plates disposed either side of the outlet chute. Locating the weir plates either side of the outlet chute allows an inlet duct into the chamber to be located at any position about the remainder of the circumference. Accordingly, the separator module can be installed in a wide variety of chambers with different inlet and outlet duct configurations. Moreover, the separator module can support a plurality of inlet ducts and/or inlet ducts of a larger diameter.

The separator module may be installed in a chamber to form a separator.

BRIEF DESCRIPTION OF DRAWINGS

For a better understanding of the present invention, and to show more clearly how it may be carried into effect, reference will now be made, by way of example, to the accompanying drawings, in which:

FIG. 1 is a sectional view of a prior art separator;

FIG. 2 is a top perspective view of a separator in which a separator module according to an embodiment of the invention is installed in a gully chamber;

FIG. 3 is a perspective view of the separator module of FIG. 2 alone;

FIG. 4 is another perspective view of the separator module;

FIG. 5 is a perspective view of a ledger component of the separator module;

FIG. 6 is an exploded view of a separator module according to another embodiment of the invention; and

FIG. 7 shows the separator module of FIG. 6 assembled.

DETAILED DESCRIPTION

FIG. 2 shows a separator which comprises a gully chamber 2 having a cylindrical surrounding wall 4 and top and bottom end walls (not shown for clarity). An inlet duct 6 and an outlet duct 8 open into the surrounding wall 4. An inlet may also be provided in the top wall in a region which is close to the surrounding wall 4 and at a circumferential position which is near to the inlet duct 6. Such an inlet may be positioned in a roadway passing over the separator and covered by a grating.

A separator module 10 according to an embodiment of the invention is installed in the gully chamber 2. As shown in FIGS. 3 and 4, the separator module 10 comprises a partition arrangement having a partition plate 12 and a separate ledger component 14.

4

The partition plate 12 divides the chamber 2 into an upper region above the partition plate 12 and a lower region below the partition plate 12.

The partition plate 12 comprises an inlet chute 16 and an outlet chute 18. The inlet chute 16 comprises an opening 20 which provides an inlet to the lower region from the upper region. Similarly, the outlet chute 18 comprises an opening (not shown) which provides an outlet from the lower region to the upper region.

The inlet chute 16 has an arcuate shape which is contoured to conform to the curvature of the inner surface of the surrounding wall 4. The inlet opening 20 is situated close to the internal surface of the surrounding wall 4, and is oriented to direct incoming flow tangentially of the chamber 2. That is, it lies in a plane extending radially with respect to the central axis of the chamber 2.

Likewise, the outlet chute 18 has an arcuate shape which is contoured to conform to the curvature of the inner surface of the surrounding wall 4. The outlet opening is situated close to the internal surface of the surrounding wall 4. The outlet opening is oriented in the same direction as the inlet opening 20 with respect to the circumferential direction around the central axis of the chamber 2.

The inlet chute 16 and outlet chute 18 are positioned in the partition plate 12 so that they are diametrically opposed from one another, with a central standpipe portion 24 disposed therebetween. The central standpipe portion 24 provides access to the lower region of the chamber 2 to allow the chamber 2 to be cleaned out using a standard vacuum tanker, for example. The central standpipe portion 24 also allows air to escape from the lower region as the latter fills with liquid. The central standpipe portion 24 may be cut to suit the headroom available within the chamber 2. The central standpipe portion 24 may be closed at its upper end, for example, by a removable cover.

The partition plate 12 comprises an annular bypass channel 26 defined between the central standpipe portion 24 and the inner surface of the surrounding wall 4. The annular bypass channel 26 fluidically couples the inlet chute 16 and the outlet chute 18 in the upper region.

The inlet chute 16 and the outlet chute 18 are arranged so that the exit from the outlet chute 18 in the upper region of the chamber is located above the entrance to the inlet chute 16. Accordingly, the annular bypass channel 26 is angled and slopes upwards from the inlet chute 16 to the outlet chute 18. The annular bypass channel 26 is inclined at an angle of between 30 and 40 degrees from horizontal.

The annular bypass channel 26 projects upwards either side of the outlet chute 18 to form a pair of weirs 28 which extend radially from the central standpipe portion 24. As shown in FIG. 2, positioning the weirs 28 either side of the outlet chute 18 allows the inlet duct 6 to be disposed at any position about the remainder of the surrounding wall 4. Indeed, this arrangement allows a plurality of inlet ducts and/or larger inlet ducts to be used.

The central standpipe portion 24 is provided with a bypass port 30 which opens into lower region. The top edge of the bypass port is positioned at or below the top edge of the weirs 28. The bypass port 30 may allow air to escape from the lower region where the upper end of the central standpipe portion 24 is closed and sealed.

Referring now to FIG. 5, the ledger component 14 comprises an annular ring which is configured to be affixed to the inner surface of the surrounding wall 4. The ledger component 14 is designed to support the partition plate 12 within the chamber 2 such that the partition plate 12 does not directly contact the inner surface of the surrounding wall 4.

5

Accordingly, the ledger component **14** is shaped to conform to the profile of the underside of the partition plate **12**. Notably, the ledger component **14** comprises an inlet recess **32** which corresponds to the inlet chute **16** and an outlet recess **34** which corresponds to the outlet chute **18**. Between the inlet recess **32** and the outlet recess **34**, the ledger component **14** is inclined at the angle of the annular bypass channel **26**. The ledger component **14** further comprises a pair of projections **35** which correspond to the weirs **28**.

The ledger component **14** has a gap **36** positioned midway across the outlet recess **34**. Together with the flexibility of the material used to form the ledger component **14**, this discontinuity allows the ledger component **14** to contract so as to reduce its external diameter.

The complementary features of the partition plate **12** and the ledger component **14** interlock the two components so as to prevent rotation of the partition plate **12** relative to the ledger component **14**. There is, however, sufficient laxity between the complementary features so as to permit the ledger component **14** to contract by closing the gap **36**.

To install the separator module **10**, the ledger component **14** is inserted into the chamber **2**. Depending on the diameter of the surrounding wall **4**, the ledger component **14** may need to be deformed from its rest position to correspond to the inner diameter of the surrounding wall **4** by closing the gap **36**. The ledger component **14** is then affixed to the surrounding wall **4** before locating the partition plate **12** thereon.

The gap may also allow the ledger component **14** to expand so as to increase its external diameter.

In use, under low or moderate flow, incoming water flows into the chamber **2** from the inlet duct **6** and enters the inlet chute **16** either directly or having been directed to the inlet chute **16** by the angled annular bypass channel **26**. The water passes through the inlet chute **16** and enters the lower region via the inlet opening **20**. The flow enters the lower region in a tangential direction and so circulates around the lower region. The flow from the inlet opening **20** will also induce a circulating flow in the water accumulated in the lower region of the chamber **2**. This relatively low-energy circulating flow will assist in causing any solids within the incoming flow to accumulate and fall to the bottom of the chamber **2** or rise to the fluid surface depending upon their density. Furthermore, by sweeping past the outlet opening of the outlet chute **18**, solids will be less likely to enter the outlet chute **18**. The outlet chute **18**, and consequently the outlet duct **8**, will thus receive substantially clean water.

If the incoming flow rate from the inlet duct **6** increases to a rate above that which can pass through the inlet opening **20**, the level in the upper region will rise.

Eventually, it will reach the level of the upper edge of the weirs **28**, and will overflow into the outlet chute **18** and the outlet duct **8**. Much of the solids material entering the upper region through the inlet duct **6** will pass through the inlet chute **16** and emerge from the inlet opening **20**, and so, as before, will tend to fall to the bottom of the chamber **2** or rise to the fluid surface. Nevertheless, under heavy flow conditions, some solid material will pass, with the water, over the weirs **28** into the outlet chute **18**, and thence to the outlet duct **8**. However, since the main flow within the chamber **2** does not receive the surplus flow passing over the weirs **28**, there is less likelihood that the high flow throughput will stir up solids from the bottom of the chamber **2** or from the fluid surface and cause them to enter the outlet chute **18**. Moreover, since the top edge of the bypass port **30** in the central standpipe portion **24** is positioned at or below the top edge of the weirs **28**, any accumulated floatable material in the upper region is able to

6

pass into the lower region before the water level reaches the upper edge of the weirs **28** and so does not pass over the weirs **28** to the outlet duct **8**.

The inclined annular bypass channel **26** prevents material from accumulating on the surface of the partition plate **12**. Initial tests have shown that an inclined annular bypass channel provides approximately a 80 to 90% reduction in accumulated solids on the floor of the bypass channel **26**, compared to the equivalent level channel.

FIGS. **6** and **7** show a separator module **110** according to another embodiment of the invention. Although not shown, the separator module **110** may be installed in the chamber **2** described in relation to the previous embodiment.

The separator module **110** comprises a partition arrangement having a partition plate **112**. The partition plate **112** divides the chamber **2** into an upper region above the partition plate **112** and a lower region below the partition plate **112**.

The partition arrangement further comprises an inlet chute **116** and an outlet chute **118** which are formed as separate components from the partition plate **112**.

The inlet chute **116** comprises an opening **120** which provides an inlet to the lower region from the upper region. Similarly, the outlet chute **118** comprises an opening (not shown) which provides an outlet from the lower region to the upper region.

The inlet chute **116** has an arcuate shape which is contoured to conform to the curvature of the inner surface of the surrounding wall **4**. The inlet opening **120** is situated close to the internal surface of the surrounding wall **4**, and is oriented to direct incoming flow tangentially of the chamber **2**. That is, it lies in a plane extending radially with respect to the central axis **X** of the chamber **2**.

Likewise, the outlet chute **118** has an arcuate shape which is contoured to conform to the curvature of the inner surface of the surrounding wall **4**. The outlet opening is situated close to the internal surface of the surrounding wall **4**. The outlet opening is oriented in the same direction as the inlet opening **120** with respect to the circumferential direction around the central axis **X** of the chamber **2**.

The inlet and outlet chutes components each further comprise a backing plate **138** and first and second circumferential flanges **140a**, **140b**, which will be described in more detail below.

The partition plate **112** comprises an inlet recess **142** and an outlet recess (not shown) which are diametrically opposed from one another with a central standpipe portion **124** disposed therebetween. The inlet and outlet recesses are configured to receive the inlet and outlet chute components, respectively.

A keyhole slot **146** opens at the centre of each of the inlet and outlet recesses and extends partway up the central standpipe portion **124**. As per the inlet and outlet recesses, the keyhole slots **146** are diametrically opposed from one another and so divide the partition plate **112** into two halves which are joined to one another by the central standpipe portion **124** above the keyhole slots **146**.

As shown in FIG. **7**, the inlet and outlet chute components are received by the inlet and outlet recesses of the partition plate **112** so that the inlet and outlet chutes **116**, **118** are positioned centrally in the inlet and outlet recesses. The inlet and outlet chute components are received from below the partition plate **112**, with the backing plates **138** being inserted into the interior of the central standpipe portion **124** so that they cover the keyhole slots **146** formed in the central standpipe portion **124**. The circumferential flanges **140a**, **140b** abut with and seal against the underside of the partition plate **112**. The partition plate **112** comprises an annular bypass channel

126 defined between the central standpipe portion **124** and the inner surface of the surrounding wall **4**. The annular bypass channel **126** fluidically couples the inlet chute **116** and the outlet chute **118** in the upper region.

The annular bypass channel **126** projects upwards either side of the outlet chute **118** to form a pair of weirs **128** which extend radially from the central standpipe portion **124**. As described previously with respect to the separator module **10**, positioning the weirs **128** either side of the outlet chute **118** allows the inlet duct **6** to be disposed at any position about the remainder of the surrounding wall **4**. Indeed, this arrangement allows a plurality of inlet ducts and/or larger inlet ducts to be used.

Although not shown, the annular bypass channel **126** may be inclined as per the annular bypass channel **26** of the previous embodiment.

The partition plate **112** may comprise a number of tabs **144** which can be used to affix the separator module **110** to the surrounding wall **4** of the chamber **2**. If the (at rest) external diameter of the partition plate **112** is smaller than the internal diameter of the surrounding wall **4**, the keyhole slots **146** allow the two halves of the partition plate **112** to be played apart in order to increase the external diameter of the partition plate **112** to conform to the diameter of the surrounding wall **4**.

The connection of the tabs **144** to the surrounding wall **4** may maintain the two halves of the partition plate in this expanded position. Alternatively, the introduction or connection of the inlet and outlet chute components in or to the inlet and outlet recesses may maintain the partition plate **112** in the expanded position.

The backing plates **138** are of sufficient size so that they cover the keyhole slots **146** even when the partition plate **112** is in the expanded position.

To a lesser extent, the keyhole slots **146** may also allow the two halves of the partition plate **112** to be compressed together in order to decrease the external diameter of the partition plate **112**.

As described above, both the separator module **10** and the separator module **110** have mechanisms by which the external diameter of the module can be adjusted so as to conform to chambers having different diameters. This is particularly important where such modules are supplied to both the UK and US markets, with chambers being typically sized based on metric and imperial measurements respectively. The arrangements also provide an improved seal between the precast chamber and the components of the separator module.

The invention claimed is:

1. A separator module for a stormwater gully chamber, the separator module comprising:

a partition arrangement which, in use, divides the chamber into an upper region and a lower region, the partition arrangement comprising:

an inlet chute having an opening which, in use, provides an inlet to the lower region from the upper region;

an outlet chute having an opening which, in use, provides an outlet from the lower region to the upper region; and

a weir separating the outlet chute from the inlet chute; wherein at least a portion of the partition arrangement is flexible so as to allow an external diameter of the partition arrangement to be adjusted to fit different sized chambers;

wherein the partition arrangement comprises a partition plate and a separate ledger component which, in use, connects to an inner wall of the chamber;

wherein the ledger component supports the partition plate within the chamber such that the partition plate does not directly contact the chamber, the ledger component defining an external diameter of the partition arrangement; and

wherein the ledger component comprises a discontinuous flexible annular ring having a gap which allows the ledger component to expand or contract so as to alter the external diameter of the partition arrangement.

2. A separator module as claimed in claim **1**, wherein the partition plate and the ledger component comprise complementary structures which interlock with one another.

3. A separator module as claimed in claim **1**, wherein the partition arrangement further comprises an annular bypass channel fluidically coupling the inlet chute and the outlet chute via the weir.

4. A separator module as claimed in claim **3**, wherein the annular bypass channel is inclined from the inlet chute to the outlet chute.

5. A separator module as claimed in claim **4**, wherein the annular bypass channel is inclined at an angle of about 30 to about 40 degrees from horizontal.

6. A separator module as claimed in claim **1**, wherein the weir comprises a pair of weir plates disposed either side of the outlet chute.

7. A separator comprising a separator module as claimed in claim **1**, installed in the stormwater gully chamber.

8. A separator module for a stormwater gully chamber, the separator module comprising:

a partition arrangement which, in use, divides the chamber into an upper region and a lower region, the partition arrangement comprising:

an inlet chute having an opening which, in use, provides an inlet to the lower region from the upper region;

an outlet chute having an opening which, in use, provides an outlet from the lower region to the upper region; and

a weir separating the outlet chute from the inlet chute;

wherein at least a portion of the partition arrangement is flexible so as to allow an external diameter of the partition arrangement to be adjusted to fit different sized chambers;

wherein the partition arrangement comprises a partition plate and separate inlet and outlet chute components forming the inlet and outlet chutes respectively, the partition plate having first and second openings for receiving the inlet and outlet chute components and an axially extending central standpipe portion disposed between the first and second openings;

wherein the central portion comprises first and second slots extending axially from the first and second openings; and

wherein the width of the first and second slots and thus the width of the first and second openings is adjustable so as to alter the external diameter of the partition arrangement.

9. A separator module as claimed in claim **8**, wherein the inlet and outlet chute components each comprise a backing plate which is received within the central standpipe portion, the backing plates covering the first and second slots.

10. A separator module as claimed in claim **8**, wherein the inlet and outlet chute components each comprise a pair of circumferentially extending flanges which abut the partition plate.

11. A separator module as claimed in claim 8, wherein the central standpipe portion comprises a bypass port, wherein a top edge of the bypass port is positioned at or below a top edge of the weir.

* * * * *