

(12) **United States Patent**
Hu et al.

(10) **Patent No.:** **US 9,271,181 B2**
(45) **Date of Patent:** ***Feb. 23, 2016**

(54) **ARCHITECTURAL MODEL FOR LTE (LONG TERM EVOLUTION) EPC (EVOLVED PACKET CORE) DEPLOYMENT**

(2013.01); **H04W 88/16** (2013.01); **H04W 40/00** (2013.01); **H04W 92/02** (2013.01)

(71) Applicant: **AT&T Mobility II LLC**, Atlanta, GA (US)

(58) **Field of Classification Search**
None
See application file for complete search history.

(72) Inventors: **Qingmin James Hu**, Sammamish, WA (US); **Douglas Eng**, Sammamish, WA (US)

(56) **References Cited**

(73) Assignee: **AT&T MOBILITY II LLC**, Atlanta, GA (US)

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

2010/0054222	A1*	3/2010	Rune	370/338
2010/0124223	A1*	5/2010	Gibbs et al.	370/389
2010/0220656	A1*	9/2010	Ramankutty et al.	370/328
2010/0278111	A1	11/2010	Kashima et al.	
2010/0309881	A1	12/2010	Kim et al.	
2011/0122824	A1	5/2011	Muhanna et al.	

(Continued)

OTHER PUBLICATIONS

(21) Appl. No.: **14/590,856**

Office Action dated Nov. 23, 2011 for U.S. Appl. No. 12/402,239, 23 pages.
Office Action dated Sep. 12, 2012 for U.S. Appl. No. 12/402,239, 26 pages.
Office Action dated Dec. 18, 2012 for U.S. Appl. No. 12/402,239, 31 pages.

(22) Filed: **Jan. 6, 2015**

(65) **Prior Publication Data**

(Continued)

US 2015/0138980 A1 May 21, 2015

Primary Examiner — Chirag Shah

Assistant Examiner — Srinivasa Reddivalam

Related U.S. Application Data

(74) *Attorney, Agent, or Firm* — Amin, Turocy & Watson, LLP

(63) Continuation of application No. 14/033,050, filed on Sep. 20, 2013, now Pat. No. 8,964,647, which is a continuation of application No. 12/402,239, filed on Mar. 11, 2009, now Pat. No. 8,565,150.

(57) **ABSTRACT**

(51) **Int. Cl.**


H04W 4/00 (2009.01)
H04B 7/00 (2006.01)
H04W 28/02 (2009.01)
H04W 88/16 (2009.01)
H04L 12/853 (2013.01)
H04W 40/00 (2009.01)
H04W 92/02 (2009.01)

A new deployment model enables a seamless migration to LTE (long term evolution)/EPC (Evolved packet core). In addition, an intelligent edge gateway (IEG) supports future distributed architecture and a converged network for service providers. Specifically, the model supports existing data services (e.g. UMTS) and the delivery of LTE services does not affect the existing data services. Moreover, a distributed architecture is employed, such that, local traffic is optimally routed at the edge and backhaul is minimized. The system can also provide support for enhanced Femto cell 3GPP access to a home network.

(52) **U.S. Cl.**

CPC **H04W 28/0247** (2013.01); **H04L 47/2416**

18 Claims, 11 Drawing Sheets



(56)

References Cited

OTHER PUBLICATIONS

U.S. PATENT DOCUMENTS

2011/0128907 A1 6/2011 Kvernvik
2012/0269161 A1* 10/2012 Chin et al. 370/330
2012/0269162 A1 10/2012 Vesterinen et al.

Notice of Allowance dated Oct. 7, 2014 for U.S. Appl. No. 14/033,050, 37 pages.

* cited by examiner




FIG. 1A




FIG. 1B

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

600




FIG. 6

700




FIG. 7

800




FIG. 8

900




FIG. 9

1000




FIG. 10




FIG. 11

ARCHITECTURAL MODEL FOR LTE (LONG TERM EVOLUTION) EPC (EVOLVED PACKET CORE) DEPLOYMENT

RELATED APPLICATIONS

This application is a continuation of, and claims the benefit of priority to each of, U.S. patent application Ser. No. 14/033,050 entitled "A NEW ARCHITECTURAL MODEL FOR LTE (LONG TERM EVOLUTION) EPC (EVOLVED PACKET CORE) DEPLOYMENT," filed Sep. 20, 2013, which is a continuation of, and claims the benefit of priority to, U.S. patent application Ser. No. 12/402,239 entitled "A NEW ARCHITECTURAL MODEL FOR LTE (LONG TERM EVOLUTION) EPC (EVOLVED PACKET CORE) DEPLOYMENT," filed Mar. 11, 2009 (now U.S. Pat. No. 8,565,150, issued Oct. 22, 2013). The entireties of the each of the above noted applications are incorporated by reference herein.

TECHNICAL FIELD

The subject disclosure relates to wireless communications and, more particularly, to an architectural model, which provides a phased evolution path that enables migration to Evolved packet core (EPC) architecture and beyond.

BACKGROUND

Mobile data communications is evolving quickly because of global communication networks and devices such as the Internet, intranets, laptops, PDAs (personal digital assistants) and increased requirements of workforce mobility. Third generation mobile system (3G) technologies (e.g., UMTS-Universal Mobile Telecommunications System) are considered enhancements to GSM (Global System for Mobile telecommunications) cellular standards.

3GPP (Third generation partnership project) standards define an EPC (evolved packet core) that supports packet-switched traffic only. One of the main advantages of EPC is that interfaces are based on IP protocols and thus all services can be delivered through packet connections (e.g., data, voice, media, etc.). Mobile operators can employ a single-packet network for all services by utilizing the EPC. With the LTE (long term evolution) and EPC standards near completion, mobile operators are gearing up to deploy the new 3GPP standard architecture. Although the new standard EPC architecture offers many advantages, there are still many gaps in between the new architecture and the conventional deployed systems (e.g. 3G radio access networks). Furthermore, the migration path has to be carefully planned to maximize the investment yet provide seamless evolution of the mobile core network.

The core mobile data network has seen its traffic demand increase dramatically in the past few years and is expected to grow even faster. Various challenges are faced in designing a packet core network. Some of these challenges include, managing the evolution of the packet core without impact to existing data services, considering the need to separate user plane traffic and control traffic, migration from a centralized deployed architecture to a more distributed architecture and/or migration of network intelligence to the edge. In addition, deployment of EPC systems has increased cost and management complexity.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A-1B illustrate high-level system diagrams depicting example system architectures for an EPC (evolved packet core) in accordance with an aspect of the subject disclosure.

FIG. 2 illustrates an example network architecture for migration towards an EPS, in accordance with an aspect of the disclosure.

FIG. 3 illustrates an example system that depicts a co-existing architecture (none roaming) with a combined S-GW (serving gateway) and PDN-GW (packet data network gateway) at the core, according to an aspect of the subject specification.

FIG. 4 illustrates an example hybrid architecture that can be employed for migrating to LTE/EPC standards, according to an aspect of the specification.

FIG. 5 illustrates an example long term evolution mobile core architecture that can meet the long term need of a converged network and that supports integrated telecommunication services in accordance with an aspect to the subject system.

FIG. 6 illustrates an example high level system that depicts an intelligent edge gateway (IEG), according to an aspect of the subject disclosure.

FIG. 7 illustrates an example methodology that facilitates migration towards a LTE/EPC with minimal impact on existing services in accordance with an aspect of the subject disclosure.

FIG. 8 illustrates an example methodology that can be employed at an initial phase to establish LTE services during migration to EPC, according to an aspect of the subject specification.

FIG. 9 illustrates an example methodology that can optimize routing at the edge and provide locally managed services, according to an aspect of the subject disclosure.

FIG. 10 illustrates an example methodology that facilitates separating signaling and user data path, such that, signaling elements are centralized and user path elements are distributed at the edge.

FIG. 11 illustrates a block diagram of a computer operable to execute the disclosed migration and/or long term evolution architectures.

DETAILED DESCRIPTION

The claimed subject matter is now described with reference to the drawings, wherein like reference numerals are used to refer to like elements throughout. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the claimed subject matter. It may be evident, however, that the claimed subject matter may be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form in order to facilitate describing the claimed subject matter.

As used in this application, the terms "component," "module," "system", "interface", or the like are generally intended to refer to a computer-related entity, either hardware, a combination of hardware and software, software, or software in execution. For example, a component may be, but is not limited to being, a process running on a processor, a processor, an object, an executable, a thread of execution, a program, and/or a computer. By way of illustration, both an application running on a controller and the controller can be a component. One or more components may reside within a process and/or thread of execution and a component may be localized on one computer and/or distributed between two or more computers. As another example, an interface can include I/O components as well as associated processor, application, and/or API components.

Furthermore, the claimed subject matter may be implemented as a method, apparatus, or article of manufacture

using standard programming and/or engineering techniques to produce software, firmware, hardware, or any combination thereof to control a computer to implement the disclosed subject matter. The term "article of manufacture" as used herein is intended to encompass a computer program accessible from any computer-readable device, carrier, or media. For example, computer readable media can include but are not limited to magnetic storage devices (e.g., hard disk, floppy disk, magnetic strips . . .), optical disks (e.g., compact disk (CD), digital versatile disk (DVD) . . .), smart cards, and flash memory devices (e.g., card, stick, key drive . . .). Additionally it should be appreciated that a carrier wave can be employed to carry computer-readable electronic data such as those used in transmitting and receiving electronic mail or in accessing a network such as the Internet or a local area network (LAN). Of course, those skilled in the art will recognize many modifications may be made to this configuration without departing from the scope or spirit of the claimed subject matter.

Moreover, the word "exemplary" is used herein to mean serving as an example, instance, or illustration. Any aspect or design described herein as "exemplary" is not necessarily to be construed as preferred or advantageous over other aspects or designs. Rather, use of the word exemplary is intended to present concepts in a concrete fashion. As used in this application, the term "or" is intended to mean an inclusive "or" rather than an exclusive "or". That is, unless specified otherwise, or clear from context, "X employs A or B" is intended to mean any of the natural inclusive permutations. That is, if X employs A; X employs B; or X employs both A and B, then "X employs A or B" is satisfied under any of the foregoing instances. In addition, the articles "a" and "an" as used in this application and the appended claims should generally be construed to mean "one or more" unless specified otherwise or clear from context to be directed to a singular form.

Moreover, terms like "user equipment," "mobile station," "mobile," subscriber station," "access terminal," "terminal," "handset," and similar terminology, refer to a wireless device utilized by a subscriber or user of a wireless communication service to receive or convey data, control, voice, video, sound, gaming, or substantially any data-stream or signaling-stream. The foregoing terms are utilized interchangeably in the subject specification and related drawings. Likewise, the term "Node B," employed herein can additionally denote an "access point," "base station," "evolved Node B," "home Node B (HNB)," and the like, and refers to a wireless network component or appliance that serves and receives data, control, voice, video, sound, gaming, or substantially any data-stream or signaling-stream from a set of subscriber stations. Data and signaling streams can be packetized or frame-based flows.

Furthermore, the terms "user," "subscriber," "operator," "customer," "consumer," and the like are employed interchangeably throughout the subject specification, unless context warrants particular distinction(s) among the terms. It should be appreciated that such terms can refer to human entities or automated components supported through artificial intelligence (e.g., a capacity to make inference based on complex mathematical formalisms) which can provide simulated vision, sound recognition and so forth. In addition, the terms "wireless network" and "network" are used interchangeably in the subject application, when context wherein the term is utilized warrants distinction for clarity purposes such distinction is made explicit. Further, the terms "existing services" and "existing architecture" used herein can include 2G/3G services and architectures respectively.

With telecommunication networks evolving in the direction of IP (Internet Protocol)-based services and traffic mov-

ing towards an all IP environment, the migration of network intelligence towards the "edge" of the networks via IP addressing capabilities is having a significant impact on operators' ability to manage and control their networks in terms of providing intelligent, integrated services. Systems and/or methods are presented herein that can provide a phased evolution path for a service provider to migrate existing deployment architecture to the new EPC (Evolved Packet Core) architecture and can provide a clear path to solve issues associated therewith. In addition, a network architecture model is provided, which is intelligently distributed yet provides some central management capability. It can be appreciated that the EPC standards can be the technical specification defined by the 3rd Generation Partnership Project's (3GPP's) Technical Specification Group Services and System Aspects entitled "Architecture enhancements for non-3GPP accesses, Release 8" and identified as "3GPP TS 23.402 V8.4.1 (2009-01)", which is incorporated herein by reference in its entirety.

SAE (System Architecture Evolution)/EPC is defined by 3GPP in Release 8 as a new core network with a flatter all-IP architecture, that can be utilized to enable a higher-data-rate, lower-latency packet-optimized system that supports multiple radio-access technologies. The SAE/EPC supports most any services (including voice) in a packet-switched domain. Specifically, the SAE/EPC can support the EUTRAN (Evolved UMTS Terrestrial Radio Access Network), which utilizes an OFDMA (orthogonal frequency division multiple access) based air interface as defined by the 3GPP standards. Moreover, the complete packet system consisting of the EUTRAN and the EPC is called the Evolved Packet System (EPS). The combination of LTE and SAE provides an all-IP, packet only wideband OFDMA system that can improve performance by providing higher data rates, improved spectral efficiency and reduced latency.

In one aspect, the EPS architecture can include only two nodes in the user plane, namely, a base station and a core network Gateway (GW). Typically, a node that performs control-plane functionality (MME-Mobility Management Entity) can be separated from a node that performs bearer-plane functionality (GW), with a well-defined open interface between them (S11), and by using the optional interface S5 the Gateway (GW) can be split into two separate nodes. Thus, throughput traffic and control signal processing can be independently scaled. FIGS. 1-4 provide an example network architecture that optimizes topological locations of nodes within the network in order to optimize the network in different aspects.

The systems and methods disclosed herein, in one aspect thereof, can facilitate realistic phased architectural evolution of a deployed network (e.g. 3G radio access network). The system facilitates reduced latency and higher data performance through a flatter all-IP architecture and provides support for both LTE radio-access networks and interworking 3G radio-access networks. In one aspect, a PDN-GW (Packet Data Network Gateway) is deployed at a core, for example, a NDC (National Data Center) and an S-GW (Serving Gateway) is deployed at an edge, for example a RDC (Regional Data Center), in a manner such that existing services, for example, provided by 3G radio-access networks are not affected.

According to another aspect, a network architecture is provided wherein a PDN-GW and S-GW can be deployed together at the core (e.g. NDC) during an initial migration deployment. Moreover, deploying the S-GW at the core can reduce costs and management complexity of the system. Fur-

ther, the existing services, for example, provided by 3G radio-access networks can be delivered with zero or minimal impact.

In accordance with another aspect, a hybrid architecture is utilized for migrating to LTE/EPC standards, wherein an edge PDN-GW and S-GW are deployed together at an edge and a core PDN-GW is deployed at the core. Specifically, the edge PDN-GW and core PDN-GW are deployed in a hierarchical manner. The deployment provides a faster response time for real time traffic and local management and/or routing of services at the edge.

Yet another aspect of the disclosed subject matter relates to a long term evolution mobile core architecture that can meet the long term need of a converged network and that is inline with long term 3GPP standardization. Specifically, the architecture is distributed, such that, control plane elements are less distributed and user plane elements are distributed at an edge. More specifically, an intelligent edge gateway (IEG) is deployed at the edge. In one example, the IEG can intelligently route traffic at the edge, such that response time and performance is improved.

An additional aspect of the subject disclosure relates to a method that facilitates migration towards a LTE/EPC with minimal impact on existing services. In one example, a PDN-GW can be utilized at the core and an S-GW can be utilized at the edge. In another example, a PDN-GW and an S-GW can be utilized together at the core and can provide centralized management. In yet another example, a PDN-GW can be utilized at the core, along with, a PDN-GW and an S-GW that can be utilized together at the edge. LTE services can be established by employing the PDN-GW(s) and S-GW, without affecting the existing (e.g. UMTS) services. Further, in one aspect, control plane elements can be less distributed and user plane elements can be distributed at the edge. Specifically, an IEG that supports mobility and distributed architecture can be utilized at the edge. Moreover, LTE services can be established by employing the somewhat centralized control plane elements, distributed user plane elements and the IEG without affecting existing (e.g. UMTS) services.

Referring initially to FIGS. 1A-1B, there illustrated are high-level system diagrams depicting example system architectures **100**, **102** for EPC in accordance with an aspect of the subject disclosure. The systems **100**, **102** can provide various advantages of EPC, such as, but not limited to, reduced latency and higher data performance through a flatter all-IP architecture and provides support for both LTE radio-access networks and interworking with 3G radio-access networks. Moreover, the systems **100**, **102** can provide optimization for all services provided via IP.

FIG. 1A illustrates system **100** that can deploy a PDN-GW (Packet Data Network Gateway) **104** in a core **106**, for example a central management center, such as, but not limited to a NDC (National Data Center) with S-GW (Serving Gateway) **108** deployed at an edge **110**, such as but not limited to, a RDC (Regional Data Center). The deployment illustrated in FIG. 1A provides minimum impact on existing services (e.g. UMTS services) and is cost effective. In addition, since the S-GW **108** is deployed at the edge, backhaul from an eNodeB (not shown) is substantially reduced.

As shown in FIG. 1A, the main components of EPC, for example, as defined by the 3GPP standards, include a PDN-GW **104** and S-GW **108**. Typically, the S-GW **108** can terminate the interface towards EUTRAN. For each UE (user equipment) associated with the EPS, at a given point of time, a single S-GW **108** can be employed. The S-GW **108** can be employed for routing and/or forwarding of user data packets and can operate as a local Mobility Anchor point for inter-

eNodeB handover. Further, the S-GW **108** can perform 3GPP Anchor function that provides mobility anchoring for inter-3GPP mobility (terminating S4 and relaying the traffic between 2G/3G system and PDN-GW **104**). For idle state UEs associated with the S-GW **108**, the S-GW **108** can terminate a DL (downlink) data path and trigger paging when DL data arrives for the UE by utilizing downlink packet buffering and initiation of network triggered service request procedure. Furthermore, the S-GW **108** can manage and/or store UE contexts, e.g. parameters of the IP bearer service, network internal routing information. Additionally, the S-GW **108** can perform replication of the user traffic in case of lawful interception.

The PDN-GW **104** is the node that terminates the SGi interface towards the PDN. If a UE is accessing multiple PDNs, there can be more than one PDN GW for that UE. The PDN-GW provides connectivity to the UE to external packet data networks by being the point of exit and entry of traffic for the UE. In one aspect, the PDN-GW **104** can be employed as a mobility anchor for mobility between 3GPP access systems and non-3GPP access systems, such as but not limited to, such as WiMAX and 3GPP2 (CDMA 1x and EvDO). The PDN-GW **104** can perform policy enforcement, per-user based packet filtering (e.g. by deep packet inspection), charging support, lawful interception, UE IP address allocation and/or packet screening. According to one embodiment, the PDN-GW **104** can be deployed in the core **106**, such that, the connectivity and/or services between the UE and external packet data networks are managed within a central location.

FIG. 1B, illustrates an alternate network architecture **102** wherein both PDN-GW **104** and S-GW **108** can be deployed together at core **106** during initial deployment. By deploying the S-GW-**108** at a central location, such as, the core **106** (as opposed to edge **110** in FIG. 1A), costs and complexity can be further reduced. However, a long backhaul from eNodeB (not shown) to S-GW **108** can be encountered. The deployment options illustrated in FIG. 1A and FIG. 1B can be modeled based on a cost and impact analysis and synch up with an SGSN team. It can be appreciated that architectures **100** and **102** can deploy components defined in the EPC standards along with currently employed components (not shown) by the 3G radio access networks such that existing services (e.g. 3G) are not affected.

FIG. 2 illustrates an example network architecture for migration towards an EPS, in accordance with an aspect of the disclosure. System **200** can be employed to deploy EPS functionality without affecting 3G services and/or 3G architecture. The 3G architecture can be based on the 3GPP (Third Generation Partnership Project) Release 99 specification. However, it is to be understood that the subject disclosure can be applied to any UMTS telecommunications architecture, including by way of example, Release 5 (R5) and, R5 and Release 6 (R6) 3GPP standards. Further, it can be appreciated that the S-GW **108** and PDN-GW **104** can include functionality, as more fully described herein, for example, with regard to systems **100**, **102**.

Typically, a UMTS network includes three interacting domains; a user equipment (UE) domain (not shown), a UMTS Terrestrial Radio Access Network (UTRAN) domain (not shown), and a core network (CN) domain, for example, **200**. The UTRAN domain is also referred to as the access network domain and the CN is referred to as the core network domain, the both of which comprise an infrastructure domain. The Core Network can include packet-switched elements include a serving GPRS (General packet radio service) support node (SGSN) **202** and gateway GPRS support node (GGSN)/Policy and charging enforcement function (PCEF)

204. Some network elements such as an EIR (equipment identity register), HLR (home location register), VLR (visitor location register) and AuC (authentication center) (not shown) can also be utilized.

A function of the system **200** is to provide switching, routing and transit for user traffic. The system **200** also contains databases and network management functions. The system **200** has several interfaces that can be configured and dimensioned. An Iu-PS (packet-switched) reference point interfaces an RNC (radio network controller) (not shown) of the access network to the SGSN entity **202** for data from/to the SGSN **202**. A Gn interface is provided between the SGSN **202** and the GGSN/PCEF **204**. PCEF (Policy and charging enforcement function) is typically disposed in GGSN/PCEF **204** and can receive Policy and charging rules (PCR) **212** via the Gx interface. Further, Subscriber Policy Repository (SPR) **214** can be access via Sp interface. The GGSN/PCEF **204** can be coupled to an offline charging system (OFCS) and/or online charging system (OCS) **210**, through Gz and Gy interfaces respectively. A Gi Interface can be located between the GGSN/PCEF **204** and an external PDN (Public Data Network). Further, the SGSN **202** can connect to an HSS (Home subscriber server) **206** via a Gr interface. The HSS **206** is a master user database that supports the network entities that actually handle calls and can contain subscription-related information (user profiles), perform authentication and authorization of a user, and provide information about the user's physical location.

In addition to the conventional UMTS network, system **200** can include EPS components, such as, an MME (Mobility management entity) **208**, S-GW **108** and PDN-GW **104**. According to an aspect, the MME **208** and S-GW **108** can be deployed at an edge, for example, regional data center **110** and the PDN-GW **104** can be deployed in the national data center **106**. Typically, the MME **208** can manage mobility, UE (User Equipment) identities and security parameters. The MME **208** can be employed for idle mode UE tracking and paging procedure including retransmissions, bearer activation and/or deactivation process and can also be responsible for choosing the S-GW **108** for a UE at the initial attach and at time of intra-LTE handover involving Core Network (CN) node relocation. The MME **208** can interact with the HSS **206** by employing an S6a interface. Moreover, the S6a interface enables transfer of subscription and authentication data for authenticating and/or authorizing user access to the evolved system (AAA interface) between MME **208** and HSS **206**.

The MME **208** can check the authorization of a UE and enforce UE roaming restrictions. Further, the MME **208** can be a termination point in the network **200** for ciphering/integrity protection for NAS (Non-Access Stratum) signaling and can facilitate security key management. Lawful interception of signaling can also be supported by the MME **208**. According to an aspect, the MME **208** can provide control plane function for mobility between LTE and 2G/3G access networks with the S3 interface terminating at the MME **208** from the SGSN **202**. Specifically, the S3 interface enables user and bearer information exchange for inter 3GPP access network mobility in idle and/or active state and is based on the GTP protocol and the Gn interface as defined between SGSNs.

According to yet another aspect, the MME **208** can connect to the S-GW **108** located at the edge **110** via S11 interface. The S-GW **108** can employ an S1-U interface that provides a per bearer user plane tunneling between the Evolved UTRAN (not shown) and S-GW **108**. The S1-U interface can contain support for path switching during handover between eNodeBs and can be based on the GTP-U protocol that is also used

for Iu user plane in the Rel-7 architecture. In one aspect, the S-GW **108** communicates with the PDN-GW **104** in the core **106** by utilizing an S5 interface that provides user plane tunneling and tunnel management for the PDN connectivity.

The SGSN **202** can interface with the PDN-GW **104** by employing a Gn interface. Further, the PDN-GW **104** employs a SGi interface to connect with a packet data network. In an example, the packet data network can be an operator external public or private packet data network or an intra operator packet data network, e.g. for provision of IMS services. The SGi interface corresponds to Gi and Wi interfaces and can support most any 3GPP or non-3GPP access. According to an aspect, the services controlled by the PDN-GW **104** and/or GGSN/PCEF **204** can be centrally managed by utilizing the deployment in FIG. 2. In one example, the system **200** can be deployed as an initial architecture during migration to a 3GPP standard architecture.

Referring now to FIG. 3, there illustrated is an example system **300** that depicts a co-existing architecture (none roaming) with combined S-GW **108** and PDN-GW **104** at the core, according to an aspect of the subject specification. In particular, both PDN-GW **104** and S-GW **108** can be deployed together at the core **106**, such that, a minimum impact is made on existing (e.g. UMTS) services. It can be appreciated that the S-GW **108**, PDN-GW **104**, SGSN **202**, GGSN/PCEF **204**, HSS **206**, MME **208**, OCS/OFCS **210**, PCR **212**, and SPR **214** can include functionality, as more fully described herein, for example, with regard to systems **100**, **102** and **200**.

According to an aspect, deploying the S-GW **108** along with the PDN-GW **104** at the core **106** can substantially reduce costs. The system **300** can support an existing 3G deployment model and can provide support for service continuity. Further, system **300** can leverage policy and charging control mechanisms efficiency and can provide for a smooth build up for LTE traffic and transition. However, since S-GW **108** and PDN-GW **104** are in the core **106**, latency for real time services can increase. Additionally or alternately, local traffic routing cannot be supported at the edge **110** (e.g. RDC). It can be appreciated that the system **300** can be deployed as an initial architecture during migration to a 3GPP standard architecture.

Referring now to FIG. 4, there illustrated is an example hybrid architecture that can be employed for migrating to LTE EPC standards, according to an aspect of the specification. It can be appreciated that the S-GW **108**, PDN-GW **104**, SGSN **202**, GGSN/PCEF **204**, HSS **206**, MME **208**, OCS/OFCS **210**, PCR **212**, and SPR **214** can include functionality, as more fully described herein, for example, with regard to systems **100**, **102**, **200** and **300**. System **400** can be deployed as an intermediate architecture during migration to 3GPP architecture that can provide a flexible deployment based on mid-term business need and traffic projections.

According to an embodiment, system **400** deploys a PDN-GW **402** with S-GW **108** at the edge **110** (e.g. in RDC) and a PDN-GW **104** at the core **106** (e.g. NDC) in a hierarchical manner. It can be appreciated that the functionality of the edge PDN-GW **402** is substantially similar to the core PDN-GW **104** as described with respect to systems **100**, **102**, **200** and **300**. The edge and core PDN-GW **402**, **104** can enable a flexible deployment architecture that can support increasing LTE traffic. Moreover, simultaneous IP connections can be made to the multiple PDN-GWs (**402**, **104**) offered by the EPC and LTE traffic can be increased. Depending on traffic projections and transition model, the split of local and cen-

tralized traffic can change over time. As an example, for data, the split can start with 80% central and 20% local (opposite for voice traffic).

The system **400** provides a shortened latency for real time traffic since the edge PDN-GW **402** can facilitate local management and/or routing of services. Further, according to an aspect, the edge PDN-GW **402** can provide optimized traffic routing at the edge and increased support for local breakout at the edge. The architecture depicted in FIG. **4** can provide flexible deployment, for example, can support overlay VoIP (Voice over IP) services. Furthermore, system **400** can provide flexible policy and charging support and default bearers at the edge PDN-GW **402**.

In one aspect, the edge PDN-GW **402** can be connected to the SGSN **202** by a Gn interface and can employ a Gx interface to access the PCR **212**. Moreover, services can create a data path from UE (to eNodeB) through regional S-GW **108**, which is tunneled to PDN-GW **104** at core **106**. Accordingly, existing services through SGSN **202** are not impacted and can be delivered as usual. Specifically, the PDN-GW **402** can facilitate optimal local routing of traffic and/or services at the edge, thus, reduce latency and improve performance. In one example, the deployment of system **400** can be flexible and can be scaled based on traffic. The additional PDN-GW **402** increases management complexity and/or costs, however can improve performance and reduce latency without affecting existing services. Further, the additional PDN-GW **402** can increase backhaul requirements and can employ intelligence to split traffics (e.g. edge policy functions).

FIG. **5** illustrates an example long term evolution mobile core architecture that can meet the long term need of a converged network that supports integrated telecommunication services in accordance with an aspect to the subject system. System **500** provides a distributed architecture that can facilitate routing of traffic and/or services at the edge. It can be appreciated that the S-GW **108**, SGSN **202**, HSS **206**, MME **208**, OCS/OFCS **210**, PCR **212**, and SPR **214** can include functionality, as more fully described herein, for example, with regard to systems **100**, **102**, **200**, **300** and **400**.

Typically, the EPS architecture, as defined by standards set by 3GPP, can include two nodes in the user plane, a base station and a core network gateway (GW). An MME **208** node that performs control-plane functionality can be employed and can be separated from a node that performs bearer-plane functionality (e.g. S-GW **108**), with a well defined open interface between them (S11). Further, an S5 interface can be utilized can be to split the Gateway (GW) into two separate nodes (e.g. S-GW **108** and IEG **502**) to enable independent scaling and growth of throughput traffic and control signal processing. According to an embodiment, system **500** employs a distributed architecture, such that, databases (e.g., HSS **206**, PCR **212**, SPR **214**, etc.) are deployed in the core **106** and all gateways (e.g. SGSN **202**, S-GW **108**, IEG **502**, etc) are deployed at edge **110**.

System **500** can employ an intelligent edge gateway (IEG) **502** at the edge **110** (e.g. RDC) that can adhere to the 3GPP standards. Specifically, control plane elements can be centralized (e.g. at core **106**) and user plane elements can be distributed at an edge **110**. Additionally, user plane elements can be policy enabled and an integrated access gateway (e.g. IEG **502**) can be utilized. According to an embodiment, the IEG **502** can interface with the SGSN **202** over a Gn interface. Further, the IEG **502** can access databases in the core **106** (e.g. NDC), such as, but not limited to, the PCR **212** via the Gx interface and can be coupled to the OFCS and/or OCS **210** at the core **106**, through Gz and Gy interfaces respectively.

The IEG **502** can be composite edge gateway that is policy enabled and can be deployed in a very flexible fashion that can support a converged network architecture. In one aspect, the IEG **502** can intelligently route traffic at the edge, such that backhaul to the core **106** is avoided, latency is reduced and performance is improved. System **500** illustrates a truly distributed architecture that can be inline with long term 3GPP standardization wherein the IEG **502** can perform optimized routing at the edge **110**. Moreover, system **500** can provide enhanced support for local breakout and can allow traffic to be kept local at the edge and thus provide shortened latency. Further, the distributed architecture of system **500** can separate signaling and user data path, with centralized signaling elements and distributed user path elements. Specifically, the system **500** supports existing data services (e.g. UMTS services) and does not have a negative affect the existing data services. In one example, the system **500** can support enhanced Femto cell 3GPP access to a home network (not shown). In one example, various AI (artificial intelligence)-based schemes can be employed for carrying out various aspects, for example, local traffic routing can be facilitated via an automatic classifier system and process. A classifier is a function that maps an input attribute vector, $x=(x_1, x_2, x_3, x_4, x_n)$, to a confidence that the input belongs to a class, that is, $f(x)=confidence(class)$. Such classification can employ a probabilistic and/or statistical-based analysis (e.g. factoring into the analysis utilities and costs) to prognose or infer an action that a user desires to be automatically performed. A support vector machine (SVM) is an example of a classifier that can be employed. Other directed and undirected model classification approaches include, e.g., naïve Bayes, Bayesian networks, decision trees, neural networks, fuzzy logic models, and probabilistic classification models providing different patterns of independence can be employed. Classification as used herein also is inclusive of statistical regression that is utilized to develop models of priority.

As will be readily appreciated from the subject specification, the subject disclosure can employ classifiers that are explicitly trained (e.g. via a generic training data) as well as implicitly trained (e.g. via observing user behavior, receiving extrinsic information). For example, SVM's are configured via a learning or training phase within a classifier constructor and feature selection module. Thus, the classifier(s) can be used to automatically learn and perform a number of functions, including but not limited to determining according to a predetermined criteria routing of data traffic at the edge.

Referring now to FIG. **6**, there illustrated is an example high level system **600** that depicts an intelligent edge gateway IEG **502**, according to an aspect of the subject disclosure. In one aspect, the IEG **502** can be an evolved data gateway that is a composite of edge functions that support mobility and distributed architecture (e.g. system **500**), which can be supported in a converged network. Further, the IEG **502** can be policy enabled and can be deployed in a flexible fashion that can support a converged network architecture. The IEG **502** can facilitate intelligent routing of local traffic and thus reduce latency. In addition, the IEG **502** can be deployed at the edge and optimize routing at the edge and provide increased support for local breakout.

According to an aspect, the IEG **502** can be deployed at the edge (e.g. RDC) and can include a GGSN component **602** that can facilitate interworking between a GPRS network and the external packet switched network. As an example, the IEG **502** can employ the GGSN component **602** to route data from a packet switched network to the SGSN serving a mobile user, and route mobile-originated packets from the SGSN to the packet switched network. Additionally, the GGSN compo-

nent **602** can keep a record of active mobile users and an SGSN that the mobile users are attached to, and can allocate IP addresses to mobile users. Further, GGSN component **602** can also facilitate billing. It can be appreciated that the GGSN component **602** can include functionality provided by a

The IEG **502** can also include a PCEF component **604** that can handle most any PEP (Policy Enforcement Point) functions. Further, an S-GW **608** and a PDN-GW with LMA (local mobility anchor) **610** can also be included within the IEG **502**. It can be appreciated that the S-GW **608** can be substantially similar to S-GW **108** in FIG. **4** and can include functionality thereof. Similarly, PDN-GW with LMA **610** can be substantially similar to PDN-GW **402** in FIG. **4** and include functionality thereof. Additionally, PDN-GW with LMA **610** can maintain a collection of host routes and associated forwarding information for mobile nodes within a localized mobility management domain under its control. Specifically, the PDN-GW with LMA **610** can employ a protocol to manage IP node mobility within the localized mobility management domain. Routing of mobile node data traffic can be anchored at the PDN-GW with LMA **610** as the mobile node moves around within the localized mobility management domain.

Additionally, an ePDG component **612** can also be included in the IEG **502**. According to an aspect, the ePDG component **612** can include functionality of a PDG (packet data gateway) according to 3GPP TS 23.234 that specifies inter-working between 3GPP systems and WLAN. Moreover, ePDG component **612** can authenticate the users and control the traffic for untrusted network access. In particular, the ePDG component **612** can provide functionality to deliver voice and data services over the untrusted Internet and WiFi networks to femtocells and dual-mode handsets.

An Access SBC (session border controller) component **614** can be employed that provides with support for delivering real-time interactive IP-based voice, video and multimedia sessions in critical areas, such as, but not limited to, security, service reach maximization, SLA assurance, revenue and cost optimization, and regulatory compliance. The Access SBC component **614** can satisfy requirements at a border where subscribers access the IMS (IP Multimedia Subsystem) core. Further, a Proxy-Call Session Control Function (P-CSCF) component **616** can be utilized as a SIP (Session Initiation Protocol) signaling contact point, the outbound/inbound “proxy,” for subscribers within IMS as defined by 3GPP. Typically, the P-CSCF component **616** can facilitate forwarding SIP registration messages from the subscriber’s endpoint, the User Equipment (UE), in a visited network to the Interrogating-CSCF (I-CSCF) and subsequent call set-up requests and responses to the Serving-CSCF (S-CSCF). Further, the P-CSCF component **616** can maintain the mapping between logical subscriber SIP URI (uniform resource identifier) address and physical UE IP address and a security association, for both authentication and confidentiality, with the UE using IPsec for example. Furthermore, emergency call (E911) local routing within the visited network, accounting, session timers and admission control can also be supported by the P-CSCF component **616**.

FIGS. **7-10** illustrate methodologies and/or flow diagrams in accordance with the disclosed subject matter. For simplicity of explanation, the methodologies are depicted and described as a series of acts. It is to be understood and appreciated that the subject disclosure is not limited by the acts illustrated and/or by the order of acts, for example acts can occur in various orders and/or concurrently, and with other acts not presented and described herein. Furthermore, not all

illustrated acts may be required to implement the methodologies in accordance with the disclosed subject matter. In addition, those skilled in the art will understand and appreciate that the methodologies could alternatively be represented as a series of interrelated states via a state diagram or events. Additionally, it should be further appreciated that the methodologies disclosed hereinafter and throughout this specification are capable of being stored on an article of manufacture to facilitate transporting and transferring such methodologies to computers. The term article of manufacture, as used herein, is intended to encompass a computer program accessible from any computer-readable device, carrier, or media.

Referring now to FIG. **7**, there illustrated is an example methodology **700** that facilitates migration towards a LTE/EPC with minimal impact on existing (2G/3G) services in accordance with an aspect of the subject disclosure. At **702**, a PDN-GW can be utilized at the core, e.g. NDC and provide centralized management. At **704**, an S-GW can be utilized at the edge, e.g. RDC and provide local management at the edge. Further, at **706**, LTE services can be established by employing the PDN-GW and S-GW, without affecting the existing (e.g. UMTS) services.

FIG. **8** illustrates an example methodology **800** that can be employed at an initial phase to establish LTE services during migration to EPC, according to an aspect of the subject specification. At **802**, a PDN-GW and an S-GW can be utilized together at the core and can provide centralized management. At **804**, LTE services can be established and/or delivered by employing the PDN-GW and S-GW, without affecting the existing (e.g. UMTS) services.

FIG. **9** illustrates an example methodology **900** that can optimize routing at the edge and provide locally managed services, according to an aspect of the subject disclosure. At **902**, a PDN-GW can be utilized at the core, e.g. NDC, and provide centrally managed services. At **904**, a PDN-GW and an S-GW can be utilized together at the edge, for example, RDC and can provide locally managed services. In one example, the core PDN-GW and edge PDN-GW can be utilized in a hierarchical manner. The edge PDN-GW can facilitate local traffic routing and minimize backhaul to the core. At **906**, LTE services can be established and/or delivered by employing the PDN-GWs and S-GW, without affecting the existing (e.g. UMTS) services.

Referring to FIG. **10**, there illustrated is an example methodology **1000** that facilitates separating signaling and user data path, such that, signaling elements are centralized and user path elements are distributed at the edge. At **1002**, centralized control plane elements can be utilized, for example databases, such as, but not limited to HSS, PCR, OCS/OFCS, etc. At **1004**, distributed user plane elements are utilized including an IEG. Moreover, the IEG is composite of edge functions, which can be supported in a converged network, that support mobility and distributed architecture. At **1006**, LTE services can be established and/or delivered by employing the centralized control plane elements and the IEG without affecting existing (e.g. UMTS) services.

Referring now to FIG. **11**, there is illustrated a block diagram of a computer operable to execute the disclosed architectures. In order to provide additional context for various aspects of the subject specification, FIG. **11** and the following discussion are intended to provide a brief, general description of a suitable computing environment **1100** in which the various aspects of the specification can be implemented. While the specification has been described above in the general context of computer-executable instructions that may run on one or more computers, those skilled in the art will recognize

13

that the specification also can be implemented in combination with other program modules and/or as a combination of hardware and software.

Generally, program modules include routines, programs, components, data structures, etc., that perform particular tasks or implement particular abstract data types. Moreover, those skilled in the art will appreciate that the inventive methods can be practiced with other computer system configurations, including single-processor or multiprocessor computer systems, minicomputers, mainframe computers, as well as personal computers, hand-held computing devices, micro-processor-based or programmable consumer electronics, and the like, each of which can be operatively coupled to one or more associated devices.

The illustrated aspects of the specification may also be practiced in distributed computing environments where certain tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules can be located in both local and remote memory storage devices.

A computer typically includes a variety of computer-readable media. Computer-readable media can be any available media that can be accessed by the computer and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer-readable media can comprise computer storage media and communication media. Computer storage media includes volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information such as computer-readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disk (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by the computer.

Communication media typically embodies computer-readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier wave or other transport mechanism, and includes any information delivery media. The term "modulated data signal" means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media. Combinations of the any of the above should also be included within the scope of computer-readable media.

With reference again to FIG. 11, the example environment 1100 for implementing various aspects of the specification includes a computer 1102, the computer 1102 including a processing unit 1104, a system memory 1106 and a system bus 1108. The system bus 1108 couples system components including, but not limited to, the system memory 1106 to the processing unit 1104. The processing unit 1104 can be any of various commercially available processors. Dual microprocessors and other multi-processor architectures may also be employed as the processing unit 1104.

The system bus 1108 can be any of several types of bus structure that may further interconnect to a memory bus (with or without a memory controller), a peripheral bus, and a local bus using any of a variety of commercially available bus architectures. The system memory 1106 includes read-only memory (ROM) 1110 and random access memory (RAM)

14

1112. A basic input/output system (BIOS) is stored in a non-volatile memory 1110 such as ROM, EPROM, EEPROM, which BIOS contains the basic routines that help to transfer information between elements within the computer 1102, such as during start-up. The RAM 1112 can also include a high-speed RAM such as static RAM for caching data.

The computer 1102 further includes an internal hard disk drive (HDD) 1114 (e.g., EIDE, SATA), which internal hard disk drive 1114 may also be configured for external use in a suitable chassis (not shown), a magnetic floppy disk drive (FDD) 1116, (e.g., to read from or write to a removable diskette 1118) and an optical disk drive 1120, (e.g., reading a CD-ROM disk 1122 or, to read from or write to other high capacity optical media such as the DVD). The hard disk drive 1114, magnetic disk drive 1116 and optical disk drive 1120 can be connected to the system bus 1108 by a hard disk drive interface 1124, a magnetic disk drive interface 1126 and an optical drive interface 1128, respectively. The interface 1124 for external drive implementations includes at least one or both of Universal Serial Bus (USB) and IEEE 1394 interface technologies. Other external drive connection technologies are within contemplation of the subject specification.

The drives and their associated computer-readable media provide nonvolatile storage of data, data structures, computer-executable instructions, and so forth. For the computer 1102, the drives and media accommodate the storage of any data in a suitable digital format. Although the description of computer-readable media above refers to a HDD, a removable magnetic diskette, and a removable optical media such as a CD or DVD, it should be appreciated by those skilled in the art that other types of media which are readable by a computer, such as zip drives, magnetic cassettes, flash memory cards, cartridges, and the like, may also be used in the example operating environment, and further, that any such media may contain computer-executable instructions for performing the methods of the specification.

A number of program modules can be stored in the drives and RAM 1112, including an operating system 1130, one or more application programs 1132, other program modules 1134 and program data 1136. All or portions of the operating system, applications, modules, and/or data can also be cached in the RAM 1112. It is appreciated that the specification can be implemented with various commercially available operating systems or combinations of operating systems.

A user can enter commands and information into the computer 1102 through one or more wired/wireless input devices, e.g., a keyboard 1138 and a pointing device, such as a mouse 1140. Other input devices (not shown) may include a microphone, an IR remote control, a joystick, a game pad, a stylus pen, touch screen, or the like. These and other input devices are often connected to the processing unit 1104 through an input device interface 1142 that is coupled to the system bus 1108, but can be connected by other interfaces, such as a parallel port, an IEEE 1394 serial port, a game port, a USB port, an IR interface, etc.

A monitor 1144 or other type of display device is also connected to the system bus 1108 via an interface, such as a video adapter 1146. In addition to the monitor 1144, a computer typically includes other peripheral output devices (not shown), such as speakers, printers, etc.

The computer 1102 may operate in a networked environment using logical connections via wired and/or wireless communications to one or more remote computers, such as a remote computer(s) 1148. The remote computer(s) 1148 can be a workstation, a server computer, a router, a personal computer, portable computer, microprocessor-based entertainment appliance, a peer device or other common network

15

node, and typically includes many or all of the elements described relative to the computer **1102**, although, for purposes of brevity, only a memory/storage device **1150** is illustrated. The logical connections depicted include wired/wireless connectivity to a local area network (LAN) **1152** and/or larger networks, e.g., a wide area network (WAN) **1154**. Such LAN and WAN networking environments are commonplace in offices and companies, and facilitate enterprise-wide computer networks, such as intranets, all of which may connect to a global communications network, e.g., the Internet.

When used in a LAN networking environment, the computer **1102** is connected to the local network **1152** through a wired and/or wireless communication network interface or adapter **1156**. The adapter **1156** may facilitate wired or wireless communication to the LAN **1152**, which may also include a wireless access point disposed thereon for communicating with the wireless adapter **1156**.

When used in a WAN networking environment, the computer **1102** can include a modem **1158**, or is connected to a communications server on the WAN **1154**, or has other means for establishing communications over the WAN **1154**, such as by way of the Internet. The modem **1158**, which can be internal or external and a wired or wireless device, is connected to the system bus **1108** via the serial port interface **1142**. In a networked environment, program modules depicted relative to the computer **1102**, or portions thereof, can be stored in the remote memory/storage device **1150**. It will be appreciated that the network connections shown are example and other means of establishing a communications link between the computers can be used.

The computer **1102** is operable to communicate with any wireless devices or entities operatively disposed in wireless communication, e.g., a printer, scanner, desktop and/or portable computer, portable data assistant, communications satellite, any piece of equipment or location associated with a wirelessly detectable tag (e.g., a kiosk, news stand, restroom), and telephone. This includes at least Wi-Fi and Bluetooth™ wireless technologies. Thus, the communication can be a predefined structure as with a conventional network or simply an ad hoc communication between at least two devices.

Wi-Fi, or Wireless Fidelity, allows connection to the Internet from a couch at home, a bed in a hotel room, or a conference room at work, without wires. Wi-Fi is a wireless technology similar to that used in a cell phone that enables such devices, e.g., computers, to send and receive data indoors and out; anywhere within the range of a base station. Wi-Fi networks use radio technologies called IEEE 802.11 (a, b, g, etc.) to provide secure, reliable, fast wireless connectivity. A Wi-Fi network can be used to connect computers to each other, to the Internet, and to wired networks (which use IEEE 802.3 or Ethernet). Wi-Fi networks operate in the unlicensed 2.4 and 5 GHz radio bands, at an 11 Mbps (802.11a) or 54 Mbps (802.11b) data rate, for example, or with products that contain both bands (dual band), so the networks can provide real-world performance similar to the basic 10BaseT wired Ethernet networks used in many offices.

It is to be noted that aspects, features, or advantages of the subject disclosure described in the subject specification can be exploited in substantially any wireless communication technology. For instance, 4G, Enhanced GPRS, 3GPP LTE, 3GPP2 UMB, 3GPP UMTS, HSPA, or Zigbee. Additionally, substantially all aspects of the subject disclosure as disclosed in the subject specification can be exploited in legacy telecommunication technologies.

What has been described above includes examples of the present specification. It is, of course, not possible to describe every conceivable combination of components or methodolo-

16

gies for purposes of describing the present specification, but one of ordinary skill in the art may recognize that many further combinations and permutations of the present specification are possible. Accordingly, the present specification is intended to embrace all such alterations, modifications and variations that fall within the spirit and scope of the appended claims. Furthermore, to the extent that the term “includes” is used in either the detailed description or the claims, such term is intended to be inclusive in a manner similar to the term “comprising” as “comprising” is interpreted when employed as a transitional word in a claim.

What is claimed is:

1. A system, comprising:

a processor; and

a memory that stores executable instructions that, when executed by the processor, facilitate performance of operations, comprising:

accessing communication data associated with a user equipment, wherein the communication data is received by a serving support node device of a first communication network;

based on time-dependent traffic projection data and first percentage data associated with the time-dependent traffic projection data, determining a first portion of the communication data that is to be directed to a first packet data network gateway device of a hierarchically defined second communication network;

based on the time-dependent traffic projection data and second percentage data associated with the time-dependent traffic projection data, determining a second portion of the communication data that is to be directed to a second packet data network gateway device of the hierarchically defined second communication network; and in response to determining that that an expiration criterion has been satisfied, updating the first percentage data to facilitate a reduction in the first portion of the communication data, and updating the second percentage data to facilitate an increase in the second portion of the communication data.

2. The system of claim **1**, wherein

the second portion of the communication data is determined in accordance with the second percentage data associated with the time-dependent traffic projection data.

3. The system of claim **1**, wherein the second packet data network gateway device is deployed at a regional data center device.

4. The system of claim **3**, wherein the second portion of the communication data is associated with a service managed by the regional data center device.

5. The system of claim **1**, wherein the second portion of the communication data is associated with a voice over Internet protocol service.

6. The system of claim **1**, wherein the first packet data network gateway device is deployed at a national data center device.

7. The system of claim **6**, wherein the first portion of the communication data is associated with a service managed by the national data center device.

8. The system of claim **1**, wherein the determining the first portion of the communication data comprises determining the first portion of the communication data based on defined policy data.

9. The system of claim **1**, wherein the determining the first portion of the communication data comprises determining the first portion of the communication data based on traffic data.

17

10. The system of claim 1, wherein the first portion of the communication data is associated with a service that is determined to satisfy a defined latency criterion.

11. The system of claim 1, wherein the time-dependent traffic projection data is associated with transition model data.

12. The system of claim 1, wherein the first percentage data is associated with transition model data.

13. A method, comprising:

receiving, by a serving support node device of a first communication network and comprising a processor, communication data from a user equipment;

based on time-dependent traffic projection data, selecting, by the serving support node device, a first portion of the communication data that is to be transmitted via a first packet data network gateway device of a hierarchically defined second communication network, wherein the selecting comprises selecting the first portion of the communication data based on first percentage data associated with the time-dependent traffic projection data;

based on the time-dependent traffic projection data, selecting, by the serving support node device, a second portion of the communication data that is to be transmitted via a second packet data network gateway device of the hierarchically defined second communication network, wherein the selecting the second portion of the communication data comprises selecting the second portion of the communication data based on second percentage data associated with the time-dependent traffic projection data;

in response to determining that that an expiration criterion has been satisfied and based on modifying the first percentage data, decreasing, by the serving support node device, the first portion of the communication data that is to be transmitted via the packet data network gateway device; and

in response to the determining that that the expiration criterion has been satisfied and based on modifying the second percentage data, increasing, by the serving support node device, the second portion of the communication data.

14. The method of claim 13, further comprising:

in response to determining that authentication data has been received from a data store of the hierarchically defined second communication network, facilitating, by

18

the serving support node device, a transmission of the second portion of the communication data via the second packet data network gateway device.

15. The method of claim 13, wherein the selecting comprises selecting the second portion of the communication data that is associated with a voice over Internet protocol service.

16. The method of claim 13, wherein the decreasing comprises decreasing the first portion of the communication data based on traffic data.

17. A computer readable storage device comprising executable instructions that, in response to execution, cause a device comprising a processor to perform operations, comprising:

selecting a first portion of communication data in accordance with a first fractional value associated with time-dependent traffic projection data, wherein the communication data has been transmitted to a serving support node device of a first communication network and wherein the first portion of the communication data is to be directed to a first packet data network gateway device of a hierarchically defined second communication network;

based on the time-dependent traffic projection data, selecting a second portion of the communication data in accordance with a second fractional value associated with the time-dependent traffic projection data, wherein the second portion of the communication data is to be transmitted to a second packet data network gateway device of the hierarchically defined second communication network; and

in response to determining that that an expiration criterion associated with the time-dependent traffic projection data has been satisfied, updating the first fractional value to facilitate a decrease in the first portion of the communication data, and updating the second fractional value to facilitate an increase in the second portion of the communication data.

18. The computer readable storage device of claim 17, wherein the determining that the expiration criterion has been satisfied comprises determining that a defined time period has expired.

* * * * *