



US009162586B2

(12) **United States Patent**
Tang

(10) **Patent No.:** **US 9,162,586 B2**
(45) **Date of Patent:** **Oct. 20, 2015**

(54) **CONTROL SYSTEM FOR AN ALL-WHEEL DRIVE ELECTRIC VEHICLE**

2540/12 (2013.01); B60W 2710/083 (2013.01);
Y02T 10/642 (2013.01); Y02T 10/7275 (2013.01)

(71) Applicant: **Tesla Motors, Inc.**, Palo Alto, CA (US)

(58) **Field of Classification Search**

(72) Inventor: **Yifan Tang**, Los Altos, CA (US)

CPC B60L 15/2036; B60L 15/20; B60L 2240/423; B60L 2260/28; B60W 10/08; B60W 2710/083; Y02T 10/7275; Y02T 10/642

(73) Assignee: **Tesla Motors, Inc.**, Palo Alto, CA (US)

See application file for complete search history.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(56) **References Cited**

U.S. PATENT DOCUMENTS

(21) Appl. No.: **14/281,679**

4,589,511 A 5/1986 Leiber
5,148,883 A 9/1992 Tanaka et al.

(22) Filed: **May 19, 2014**

(Continued)

(65) **Prior Publication Data**

FOREIGN PATENT DOCUMENTS

US 2014/0257613 A1 Sep. 11, 2014

JP 3706565 10/2005

Primary Examiner — Michael J Zanelli

Related U.S. Application Data

(74) Attorney, Agent, or Firm — J. Richard Soderberg

(60) Continuation of application No. 13/866,214, filed on Apr. 19, 2013, now Pat. No. 8,761,985, and a division of application No. 12/782,413, filed on May 18, 2010, now Pat. No. 8,453,770, and a continuation-in-part of application No. 12/380,427, filed on Feb. 26, 2009, now Pat. No. 7,739,005, and a continuation-in-part of application No. 12/322,218, filed on Jan. 29, 2009, now abandoned.

(57) **ABSTRACT**

Electric vehicles and, more particularly, a control system for an all-wheel drive electric vehicle. An electric vehicle drive system comprises: first and second electric motors; a torque split unit configured to receive first input that includes at least a total torque request for the first and second electric motors, and respective first and second maximum torques for the first and second electric motors, the torque split unit configured to process the first input without taking into account wheel slip, and to generate at least respective first and second torque requests for the first and second electric motors; and a traction and stability control unit configured to receive second input that includes at least the first and second torque requests, the total torque request, a computed vehicle speed, and respective first and second slip errors relating to the first and second electric motors, the traction and stability control unit configured to process the second input and to generate respective first and second torque commands for the first and second electric motors.


(51) **Int. Cl.**

B60L 15/20 (2006.01)
B60W 10/08 (2006.01)
B60K 1/02 (2006.01)
B60K 1/00 (2006.01)

(52) **U.S. Cl.**

CPC **B60L 15/20** (2013.01); **B60L 15/2036** (2013.01); **B60W 10/08** (2013.01); **B60K 1/02** (2013.01); **B60K 2001/001** (2013.01); **B60L 2240/24** (2013.01); **B60L 2240/423** (2013.01); **B60L 2240/486** (2013.01); **B60W 2520/28** (2013.01); **B60W 2540/10** (2013.01); **B60W**

22 Claims, 17 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,419,624 A 5/1995 Adler et al.
5,465,806 A 11/1995 Higasa et al.
5,508,924 A 4/1996 Yamashita
5,549,172 A 8/1996 Mutoh et al.
5,804,935 A 9/1998 Radev
6,909,959 B2 6/2005 Hallowell
7,033,406 B2 4/2006 Weir et al.

2002/0147539 A1 10/2002 Strothmann
2004/0104699 A1 6/2004 Nishikawa et al.
2004/0222771 A1 11/2004 Iwata et al.
2006/0016630 A1 1/2006 Yang
2006/0185915 A1 8/2006 Kaneko
2007/0038340 A1 2/2007 Sekiguchi et al.
2007/0284159 A1 12/2007 Takami et al.
2008/0032162 A1 2/2008 Hirakata
2008/0251246 A1 10/2008 Ohkuma et al.
2008/0276825 A1 11/2008 King et al.
2010/0194318 A1 8/2010 Aso




FIG. 1




FIG. 2




FIG. 3





FIG. 4

FIG. 6







FIG. 7







FIG. 9

FIG. 10






FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19

1

CONTROL SYSTEM FOR AN ALL-WHEEL DRIVE ELECTRIC VEHICLE

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. application Ser. No. 13/866,214, filed Apr. 19, 2013, which is a divisional of U.S. application Ser. No. 12/782,413, now U.S. Pat. No. 8,453,770, which is a continuation-in-part of U.S. application Ser. No. 12/322,218, filed Jan. 29, 2009, and is a continuation-in-part of U.S. application Ser. No. 12/380,427, now U.S. Pat. No. 7,739,005, the contents of each of which are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates generally to electric vehicles and, more particularly, to a control system for an all-wheel drive electric vehicle.

BACKGROUND OF THE INVENTION

The advantages of using an all-wheel drive system in a vehicle are well known. In general, an all-wheel drive system improves traction, and thus safety, by allowing power to be sent to all four wheels, rather than just the front two or the rear two. Thus when traction is lost in one or more wheels, for example due to wet or icy road conditions, the drive system can increase the torque to the axle/wheels with traction.

A variety of control systems have been developed to detect tire slippage, i.e., wheel spin, and to redirect the available torque to the remaining wheels. These control systems range from simple hydraulic and mechanical systems to relatively sophisticated electronic control systems. For example, U.S. Pat. No. 4,589,511 describes a traction control system that uses wheel spin sensors to detect the spinning of a wheel or wheels, and an electronically controlled wheel braking system to prevent wheel spinning.

Many of the current traction control systems, while providing efficient traction control in a conventional vehicle utilizing a combustion engine drive train, are unsatisfactory for a hybrid or all-electric vehicle due to differences in vehicle weight and weight distribution, and more importantly differences in drive train torque and power capabilities. Accordingly, what is needed is a traction control system designed to meet the needs of such alternative fuel vehicles in general, and all-electric vehicles in particular. The present invention provides such a system.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates the basic elements of a dual electric motor drive system for use with the present invention;

FIG. 2 graphically illustrates the torque curves for exemplary primary and assist motors;

FIG. 3 graphically illustrates the power curves for exemplary primary and assist motors;

FIG. 4 illustrates the basic elements of a control system for a dual electric motor drive system in accordance with the invention;

FIG. 5 illustrates the basic elements of a control system for a dual electric motor drive system similar to that shown in FIG. 4, with the exception that each motor/power control module is coupled to a separate ESS;

FIG. 6 illustrates the basic elements of the system controller shown in FIG. 4;

2

FIG. 7 illustrates the algorithm used to calculate the optimal torque split between the two drive trains, without taking into account wheel slip errors;

FIG. 8 illustrates the algorithm used to generate the look-up table utilized by the optimal torque split unit;

FIG. 9 illustrates a block diagram of the traction and stability control unit shown in FIG. 6;

FIG. 10 illustrates the basic elements of the system controller shown in FIG. 5;

FIG. 11 illustrates the basic elements of a control system for an EV utilizing a single primary motor coupled to one axle, and dual assist motors coupled to the second axle;

FIG. 12 illustrates the basic elements of the system controller shown in FIG. 11;

FIG. 13 illustrates the algorithm used to calculate the optimal torque split between the three drive motors, without taking into account wheel slip errors;

FIG. 14 illustrates a block diagram of the traction and stability control unit shown in FIG. 12;

FIG. 15 illustrates the basic elements of a control system for an EV utilizing a single electric motor coupled to one axle;

FIG. 16 illustrates the basic elements of the system controller shown in FIG. 15;

FIG. 17 illustrates the algorithm used to calculate the optimal torque request without taking into account wheel slip errors;

FIG. 18 illustrates the algorithm used to generate the look-up table utilized by the torque control unit; and

FIG. 19 illustrates a block diagram of the traction control unit shown in FIG. 16.

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

In the following text, the terms “electric vehicle” and “EV” may be used interchangeably and refer to an all-electric vehicle. Similarly, the terms “hybrid”, “hybrid electric vehicle” and “HEV” may be used interchangeably and refer to a vehicle that uses dual propulsion systems, one of which is an electric motor and the other of which is a combustion engine. Similarly, the terms “all-wheel-drive” and “AWD” may be used interchangeably and refer to a vehicle drive system in which every wheel, or every set of wheels sharing the same axle or axis, is provided with a separate motor. Similarly, the terms “battery”, “cell”, and “battery cell” may be used interchangeably and refer to any of a variety of different rechargeable cell chemistries and configurations including, but not limited to, lithium ion (e.g., lithium iron phosphate, lithium cobalt oxide, other lithium metal oxides, etc.), lithium ion polymer, nickel metal hydride, nickel cadmium, nickel hydrogen, nickel zinc, silver zinc, or other battery type/configuration. The term “battery pack” as used herein refers to multiple individual batteries contained within a single piece or multi-piece housing, the individual batteries electrically interconnected to achieve the desired voltage and current capacity for a particular application. The terms “energy storage system” and “ESS” may be used interchangeably and refer to an electrical energy storage system that has the capability to be charged and discharged such as a battery, battery pack, capacitor or supercapacitor. Lastly, identical element symbols used on multiple figures refer to the same component, or components of equal functionality.

FIG. 1 illustrates the basic elements of a dual electric motor drive system 100 for use with the control system of the invention. As shown, each axle is coupled to an independent power source, specifically rear axle 101 is coupled to an electric motor 103 via a transmission/differential assembly 105, and

3

front axle **107** is coupled to an electric motor **109** via a transmission/differential assembly **111**. It should be understood that the present invention is not limited to a specific type/configuration of transmission or a specific type/configuration of differential. For example, although a single speed transmission is preferred, either or both transmissions can use a multi-speed transmission. Similarly, the differentials used with the present invention can be configured as open, locked or limited slip, although preferably an open or limited slip differential is used.

In the simplified illustration of FIG. 1, a single ESS/power control module **113** is shown coupled to both motors **103/109**. It should be understood, however, that the present invention is not limited to a specific ESS/power control module configuration. Exemplary configurations that are applicable to the present invention are described in detail in co-pending U.S. patent application Ser. No. 12/322,218, filed Jan. 29, 2009, the disclosure of which is incorporated herein for any and all purposes.

In a preferred embodiment of the invention, one of the two motors is the primary drive motor, e.g., motor **103**, while the second motor, e.g., motor **109**, is relegated to the role of an assisting motor. Preferably both motors **103** and **109** are AC induction motors. Additionally, in a preferred embodiment assist motor **109** is designed to have a relatively flat torque curve over a wide range of speeds, and therefore is capable of augmenting the output of primary motor **103** at high speeds, specifically in the range in which the torque of primary motor **103** is dropping off. FIGS. 2 and 3 illustrate torque and power curves, respectively, of exemplary motors. In particular, curves **201** and **301** represent the torque and power curves, respectively, of an exemplary primary motor; curves **203** and **303** represent the torque and power curves, respectively, of an exemplary assist motor; and curves **205** and **305** represent the torque and power curves, respectively, of the combination of the exemplary primary and assist motors.

It will be understood that the gear ratios of transmission/differential elements **105** and **111** may be the same, or different, from one another. If they are the same, FIGS. 2 and 3 show the motor speeds of both motors. If they are different, FIGS. 2 and 3 show the motor speed of the primary motor, with the motor speed of the secondary motor converted based on a gear ratio conversion factor. FIGS. 2 and 3 illustrate that in at least one configuration, the maximum amount of assist torque can be substantially constant throughout the motor speed, and hence vehicle speed, range of operation (FIG. 2), and as a result the maximum amount of assist power increases as a function of motor speed (FIG. 3). This preferred configuration applies to both the motoring and regenerating modes of operation. One benefit of this approach is that it can be used to compensate for torque fall-off at higher speeds, a characteristic typical of electric motors with limited operating voltage. Another benefit of significantly increasing the high speed capabilities of a vehicle in accordance with the preferred embodiment of the invention is improved vehicle performance, specifically in the areas of top speed, high speed acceleration, and hill climbing abilities. Lastly, by utilizing a dual drive approach, in some configurations a lower total motor weight can be achieved than is possible with a single motor sized to provide similar peak power capabilities.

As previously noted, the curves shown in FIGS. 2 and 3 assume the use of AC inductions motors even though the use of a specific motor or motor configuration is not a requirement of the invention. Curve **201** illustrates a characteristic common of many such electric motors, i.e., exhibiting a relatively flat peak torque at low speeds that then drops off at higher speeds. As used herein, a motor's "base speed" is defined as

4

the speed at which the torque drops to 95% of the flat peak torque and will continue to drop after the base speed up to the top speed under constant power source limits. Therefore, for curve **201**, this knee point occurs at a point **207** on the curve, leading to a base speed of approximately 7200 rpm. As used herein, a motor's "drive system base speed" is equivalent to the motor's base speed after gearing, i.e., the motor base speed divided by the transmission gear ratio. As described above and illustrated in FIGS. 2 and 3, preferably assist motor **109** is designed to provide a much higher drive system base speed than the drive system base speed of primary motor **103**; more preferably assist motor **109** is designed to provide at least a 50% higher drive system base speed than the drive system base speed of primary motor **103**.

The basic configuration illustrated in FIG. 1 provides a number of advantages over a single drive EV. First, the dual motor configuration provides superior traction control as power is coupled to both axles, therefore providing power to at least one wheel per axle. It will be appreciated that additional traction control can be achieved if one or both differentials utilize a limited slip or locking configuration, thereby coupling power to the remaining wheel or wheels. Second, by coupling each axle to an independent power source, vehicle traction, and therefore stability, can be dramatically improved since the torque supplied to the front wheel(s) versus the rear wheel(s) can be varied depending upon the specific situation. For example, while making a turn it may be advantageous to gradually increase the torque supplied to the front wheel(s) versus the rear wheel(s). Similarly, in icy road conditions, it may be desirable to increase the torque supplied to the front wheel(s). Third, by utilizing a dual motor configuration, regenerative braking can be used with respect to both sets of wheels, thus providing enhanced braking as well as improved battery charging capabilities. Fourth, assuming an assist motor with a relatively flat torque curve, in addition to providing additional power at all speeds, the assist motor provides greatly enhanced performance at high speeds when the primary motor starts losing torque.

As previously noted, the use of a dual drive configuration offers a number of advantages over a single drive configuration. The present invention expands upon these advantages by providing a torque and traction control system that is capable of rapidly and efficiently splitting the torque between the two drive systems. As a consequence, wheel slippage is minimized and vehicle traction and stability is greatly improved in a variety of operating conditions. These improvements are evident in both cornering and straight-line traction, and in wheel slip control.

FIG. 4 illustrates the basic configuration of a preferred embodiment of the invention. As shown, primary motor **103** is connected to the ESS **401** via the primary power control module **403**. Similarly, assist motor **109** is connected to ESS **401** via a secondary power control module **405**. Primary and secondary power control modules **403** and **405** each include a DC to AC inverter. The power control modules **403/405** are used to insure that the power delivered to motors **103/109** or the regenerated power recovered from motors **103/109** have the desired voltage, current, waveform, etc. As such, power control modules **403/405** may be comprised of passive power devices (e.g., transient filtering capacitors and/or inductors), active power devices (e.g., semiconductor and/or electromechanical switching devices, circuit protection devices, etc.), sensing devices (e.g., voltage, current, and/or power flow sensors, etc.), logic control devices, communication devices, etc.

Although FIG. 4 shows a single ESS, as previously noted other configurations can be used with the invention, for

example ones in which each motor is connected to a separate ESS. Alternate ESS and power control configurations are described in detail in co-pending U.S. patent application Ser. No. 12/322,218, filed Jan. 29, 2009, the disclosure of which is incorporated herein for any and all purposes.

In accordance with the invention, system **400** includes a torque and traction controller **407** that determines the power, i.e., voltage, current, and waveform, that each of the power control modules supplies to their respective motors, and thus the torque and power that each motor applies to the wheel or wheels to which it is coupled. In order to calculate the appropriate power to be supplied to each motor, and thus the torque/power to be supplied to the individual wheels, torque and traction controller **407** is coupled to, and receives data from, a variety of sensors throughout the vehicle. In general, these sensors can be divided into four groups; those used to monitor vehicle performance, those used to monitor the drive system, those used to monitor the condition and performance of the ESS and the power control electronics, and those used to monitor user input. A description of exemplary sensors for each group of sensors follows.

Vehicle Performance Sensors—The sensors within this group monitor the on-going performance of the vehicle by monitoring wheel spin, and thus tire slippage. Preferably a wheel spin sensor is coupled to each wheel, i.e., sensors **409-412**.

Drive System Sensors—The sensors within this group monitor the performance of the primary and assist motors. Preferably coupled to the primary motor is a temperature sensor **413** and a motor speed sensor **415**, and coupled to the assist motor is a temperature sensor **417** and a motor speed sensor **419**.

ESS and Power Control Electronics Sensors—The sensors within this group monitor the condition of the ESS and power control modules. Preferably coupled to ESS **401** is a temperature sensor **421**, a voltage sensor **423** and a current sensor **425**. Preferably coupled to primary power control module **403** is a temperature sensor **427**. Preferably coupled to secondary power control module **405** is a temperature sensor **429**.

User Input Sensors—The sensors within this group monitor user input. Exemplary sensors in this group include a brake sensor **431**, an accelerator sensor **433**, and a steering sensor **435**. These sensors can be coupled to the corresponding pedals and/or steering wheel, coupled to the corresponding linkage, or otherwise coupled to the vehicle drive systems such that braking, accelerator and steering data is obtained. The system may also include a gear selection sensor **437** if the vehicle includes a multi-gear transmission, as opposed to a single speed transmission. The system may also include a mode selection sensor **439** if the vehicle allows the user to select from multiple operating modes, e.g., high efficiency mode, high performance mode, etc.

Although the primary sensors used by torque and traction controller **407** are shown in FIG. **4** and described above, it will be appreciated that the invention can use other sensors to provide additional information that can be used to determine the optimal torque split between the primary and assist drive system. For example, by monitoring the ambient temperature and/or monitoring humidity/rainfall, the system can adapt for inclement weather, i.e., wet and slippery conditions or potential icy conditions. Similarly, by monitoring vehicle incline, the system can adapt for steep hill climbing or descending conditions.

As previously noted, the present invention is not limited to vehicle systems in which both drive trains are coupled to a single ESS. For example, FIG. **5** illustrates a torque and traction control system similar to that shown in FIG. **4**, with

the exception that each motor/power control module is coupled to a separate ESS. Specifically, primary motor **103** and primary power control module **403** are coupled to ESS **501** while assist motor **109** and secondary power control module **405** are coupled to ESS **503**. In this embodiment primary motor ESS **501** includes temperature, voltage and current sensors **505-507**, respectively, and assist motor ESS **503** includes temperature, voltage and current sensors **509-511**, respectively. If desired, the ESS **501** can be coupled to ESS **503**, for example using a bi-directional DC/DC converter (not shown) as described in detail in co-pending U.S. patent application Ser. No. 12/322,218, filed Jan. 29, 2009, the disclosure of which is incorporated herein for any and all purposes.

FIG. **6** provides a more detailed schematic of torque and traction controller **407**. As shown, data from the brake sensor **431**, accelerator sensor **433**, gear selection sensor **437** (if the vehicle has multiple gears) and mode selection sensor **439** (if the vehicle includes multiple modes) are input into the vehicle torque command generation unit **601**. The computed vehicle speed, referred to herein as “C_vs_{speed}”, is also input into the vehicle torque command generation unit **601**. C_vs_{speed} is computed by the traction command generation unit **609**. The output of unit **601** is a total torque requirement request, referred to herein as “C_torque”. C_torque is the torque required from the combined drive trains.

The maximum torque available from the primary and assist motors, referred to herein as “C_max_{torque1}” and “C_max_{torque2}”, are calculated by the primary torque limiting unit **603** and the assist torque limiting unit **605**, respectively. The inputs to the primary torque limiting unit **603** are the data from primary motor temperature sensor **413**, primary motor speed sensor **415**, and primary power control module temperature sensor **427**. The inputs to the assist torque limiting unit **605** are the data from assist motor temperature sensor **417**, assist motor speed sensor **419**, and secondary power control module temperature sensor **429**. Assuming a single ESS configuration, for example as shown in FIG. **4**, ESS data input to both units **603** and **605** are the ESS temperature data from sensor **421** as well as the ESS voltage and current data from sensors **423** and **425**, respectively. If the drive trains use separate ESS systems as illustrated in FIG. **5**, then the ESS data input into unit **603** is from sensors **505-507** and the data input into unit **605** is from sensors **509-511**.

The torque required from the combined drive trains calculated by unit **601**, and the maximum available torque for the primary and assist motors, calculated by units **603** and **605** respectively, are input into the optimal torque split unit **607** as is the computed vehicle speed. Unit **607** optimizes the torque split between the two drive trains without taking into account wheel slip, thus splitting the desired combined torque, i.e., C_torque, into an optimal primary motor torque request and an optimal assist motor torque request, the split based solely on achieving maximum operating efficiency within the limits of the available torque for each motor.

The system of the invention uses a simple continuously running algorithm to determine the optimal torque split, as illustrated in FIG. **7**. As shown, initially C_torque, C_vs_{speed}, C_max_{torque1} and C_max_{torque2} are read (step **701**). Next, temporary values for the torque for primary motor **103** (C_tem_{torque1}) and for assist motor **109** (C_tem_{torque2}) are determined, as well as values for the motor flux for primary motor **103** (C_flux₁) and for assist motor **109** (C_flux₂). (Step **703**). This step is performed by interpolating data from a look-up table, described in further detail below, that contains optimal torque (i.e., T₁ and T₂) and optimal flux values (i.e., F_{1opt} and F_{2opt}) based on vehicle speed and total

requested torque. The temporary torque values set in step 703, based on the look-up table, are then compared to the maximum available torque values (step 705) calculated by the primary torque limiting unit and the assist torque limiting unit. If the temporary torque values are less than the maximum available torque values, then the temporary torque values are output as C_torque1e (primary motor) and C_torque2e (assist motor); if the temporary torque values are greater than the maximum available torque values, then the maximum available torque values are output as C_torque1e and C_torque2e. (Steps 707 and 709). The flux command values for the primary motor, i.e., C_flux1, and the assist motor, i.e., C_flux2, are also output in step 709.

FIG. 8 illustrates the preferred algorithm used to generate the three-dimensional look-up table utilized by the optimal torque split unit 607. In step 801, a first loop is initiated in which vehicle speed, W, is stepped through from a minimum value, Wmin, to a maximum value, Wmax, in steps of Wstep. In step 803, a second loop is initiated in which total vehicle torque, T, is stepped through from a minimum value, Tmin, to a maximum value, Tmax, in steps of Tstep. In step 805, a third loop is initiated in which the torque of the primary motor, T1, is stepped through from a minimum value, T1min, to a maximum value in steps of T1step. The maximum value in step 805 is the smaller of T1max and T.

In the next series of steps, steps 807-809, the optimum flux value, F1opt, for the primary motor is determined for each value of T1. Initially, for a given value of T1 the primary motor flux F1 is stepped through from a minimum value, F1min, to a maximum value, F1max, in steps of F1step. Then for each value of T1 and F1, a value for primary motor input power, P1, is calculated. Next, F1opt is determined, based on achieving the minimum input power, P1min.

In the next series of steps, steps 811-814, the optimum flux value, F2opt, for the assist motor is determined for each value of T1. Initially for a given value of T1, the corresponding value for the torque of the assist motor, T2, is determined, where T2 is equal to T minus T1. Then the assist motor flux F2 is stepped through from a minimum value, F2min, to a maximum value, F2max, in steps of F2step. Next, the value for the assist motor input power, P2, is calculated for each value of T2 and F2. Lastly, F2opt is determined, based on achieving the minimum input power, P2min.

In step 815 a minimum total motor input power, Pmin, is calculated, where Pmin is equal to P1min plus P2min. Next, the smallest Pmin is found for the value of T1 for this particular iteration of the T1 loop. (Step 817) Lastly, for the smallest Pmin and the current T and W, values for T1, T2, F1opt and F2opt are output. (Step 819)

The traction control command generation unit 609 provides several functions. As input, data from each wheel spin sensor, i.e., sensors 409-412, is feed into unit 609. Additionally, data from primary motor speed sensor 415, assist motor speed sensor 419, and steering sensor 435 are input into the traction control command generation unit. Using this data, unit 609 calculates vehicle speed, C_vspeed, which is input into the vehicle torque command generation unit 601 as previously noted. Unit 609 also uses the motor speed data to provide error checking.

A primary function of unit 609 is to calculate wheel slip ratios for each wheel, the wheel slip ratio being the difference between the wheel speed and the vehicle speed, divided by the greater of the wheel speed and the vehicle speed. After calculating the wheel slip ratio for each wheel as a function of vehicle speed, a wheel slip ratio for each axle is calculated. The wheel slip ratio for an axle must take into account that different wheels on the same axle may experience different

degrees of slip, and thus exhibit different slip ratios. For a limited slip differential, and in most other cases as well, preferably the higher of the two wheel slip ratios for a given axle is taken as the wheel slip ratio for that particular axle.

In order to determine if the wheel slip ratio for a given axle is greater than desired, the wheel slip ratio must be compared to a target wheel slip ratio contained within a lookup table. The lookup table provides target wheel slip ratios as a function of speed and steering angle. The lookup table can be based on well known target ratios or, as is preferred, based on test data obtained for that particular vehicle and vehicle configuration. For each axle, the difference between the computed wheel slip ratio and the target wheel slip ratio yields the computed slip error, referred to herein as "C_sliperror1" for the wheel slip ratio error of the primary-driven axle 101 and "C_sliperror2" for the wheel slip ratio error of the assist-driven axle 107. To prevent control chatter, preferably hysteresis is incorporated into the comparator used in this calculation by means of a dead band, i.e., neutral zone. In addition to controlling chatter, the hysteresis band also allows for a small amount of additional wheel slippage, which may compensate for vehicle weight dynamic distribution and improve acceleration and deceleration performance.

The computed slip errors, C_sliperror1 and C_sliperror2, along with the values for the optimized torque split, C_torque1e and C_torque2e, and the total requested torque, C_torque, are input into the first stage of the traction and stability control unit 611. Details of unit 611 are shown in FIG. 9. As shown, the first stage independently minimizes the wheel slip ratio errors using a feedback control system, for example using a lead-lag controller, sliding-mode controller, PID controller or other linear or non-linear controller type. Preferably PID controllers are used for the compensators 901/902 in the first stage feedback control system. In the second stage of unit 611, motor speed fast disturbances are independently minimized using high pass filters 903/904 and compensators (preferably PID controllers) 905/906. Motor speed fast disturbances can be caused, for example, by sudden large reductions of load torque on the motor shaft during an excessive wheel slip event, or by sudden large additions of load torque on the motor shaft from one or two stuck wheels.

Between the first and second stages is a transient torque boost feedforward control circuit, referred to in the figure as dynamic boost, which adds an amount of torque to each axle. The amount of added torque is proportional to the difference between the driver torque request after the first stage of traction control and the combined torque command, C_torque. The proportional constants K1 and K2 may be tuned to be different between the two axles. The feedforward torques enhance the vehicle performance, vehicle response to driver request and drivability without compromising traction control and vehicle stability. The feedforward torques are zero when the torque request is fully met, with zero effective wheel slip ratio errors and with the maximum torque limits not in effect. During a wheel slip event that causes a torque reduction on an axle, an effect of the feedforward control is to increase the torque command to the other axle that has a better tire-to-road grip. The feedforward control also adds a torque command to the axle experiencing wheel slip, but due to the relatively smaller gain in the feedforward path, the wheel slip ratio error feedback loop still dominates and will minimize the wheel slip ratio error.

After the second stage of traction control, torque limiters 907/908 independently limit the torque commands issuing from the second stage based on C_maxtorque1 and C_maxtorque2. The output of the torque limiters 907/908 are torque commands C_torque1 and C_torque2. The torque commands

from the limiters and the flux commands, C_flux1 and C_flux2, from the optimal torque split unit 607 are input into control modules 403 and 405 as shown in FIG. 6. Power control modules 403 and 405 can use any of a variety of motor control techniques, e.g., scalar control, vector control, and direct torque control. Vector control allows fast and decoupled control of torque and flux. In at least one preferred embodiment of the invention, the control modules utilize a pulse width modulator (PWM) control circuit.

In some instances the torque and flux motor control commands may be subject to further limitation, specifically due to component overheating and/or ESS power limitations. Such command limits may be applied by an additional limiter circuit within the torque and traction controller 407, or within the power control modules as illustrated in FIG. 6. In general, such limiters monitor the temperatures of the motors via sensors 413/417, the temperatures of the power electronics via sensors 427/429, and the temperature, voltage and current of ESS 401 via sensors 421/423/425. If multiple ESS systems are used, as previously described, then the temperature, voltage and current of each ESS system are taken as inputs to the limiters. In at least one embodiment using a single ESS system, if the ESS temperature is above a threshold temperature, then the commands to the motors are proportionally reduced. If the temperature of a particular power control module or a particular motor is above its preset temperature threshold, then the control commands sent to that particular motor are reduced. Preferably in such an instance the control commands sent to the non-affected motor are sufficiently increased to insure that the total requested torque, C_torque, is met. The limiters may rely on a look-up table that provides preset command reductions as a function of the amount that a monitored temperature is above its respective preset temperature threshold.

In accordance with at least one preferred embodiment, the torque and traction controller 407 uses multiple processing frequencies, the specific frequency depending upon the function of the unit in question. For example, a dual frequency approach can be used in which a relatively low frequency is applied in order to optimize the performance of the two drive systems based on general operating conditions, while a second, higher frequency is applied in order to quickly respond to rapidly developing transient conditions, e.g., wheel slippage. In this preferred approach, low frequency cycling is applied to the torque command generation unit 601, the torque limiting units 603/605, the optimal torque split unit 607 and the various temperature, voltage, current, and speed sensors. Preferably the low frequency is selected to be within the range of 100 Hz to 2 kHz, more preferably in the range of 500 Hz to 1.5 kHz, and even more preferably set at approximately 1 kHz. High frequency cycling is applied to the traction and stability control unit 611, control modules 403/405 and the wheel slip sensors, and is preferably at a frequency of about 10 to 30 times that of the low frequency, and more preferably at a frequency of approximately 20 kHz. As the traction control command generation unit 609 monitors wheel slippage and generates the slip errors for each axle, preferably it operates at the high cycle frequency although in at least one embodiment, it operates at an intermediate rate, e.g., 5-10 kHz.

As previously noted, the present control system can be used with an EV that utilizes a single ESS for both drives, or one which utilizes an ESS per drive. The system and methodology is basically the same as previously described in detail, except that the temperature, current and voltage of each ESS must be monitored and taken into account. Thus, for example, the control system shown in FIG. 6 would be modi-

fied as shown in FIG. 10. Specifically, the temperature, current and voltage of the primary ESS 501 would be sensed with sensors 505-507 and input into the primary torque limiting unit 603 and the primary control module 403; and the temperature, current and voltage of the secondary ESS 503 would be sensed with sensors 509-511 and input into the assist torque limiting unit 605 and the assist control module 405.

The inventor also envisions using the torque and traction control system of the invention with an EV that includes a primary drive train and a secondary drive train with dual assist motors. Such a system can utilize either a single ESS system similar to that of FIG. 4, or dual ESS systems similar to that of FIG. 5. Suitable alternate ESS and power control configurations are described in detail in co-pending U.S. patent application Ser. No. 12/322,218, filed Jan. 29, 2009, the disclosure of which is incorporated herein for any and all purposes. System 1100 shown in FIG. 11 is intended to illustrate one such configuration.

System 1100 is based on the configuration shown in FIG. 4, with single assist motor 109 being replaced with dual assist motors 1101 and 1103. Preferably assist motors 1101 and 1103 are coupled to split axles 1105 and 1107 via gear assemblies 1109 and 1111. In these embodiments, motors 1101 and 1103 are coupled to ESS 401 via first and second assist power control modules 1113 and 1115, respectively, thereby providing independent torque control over motors 1101 and 1103. System 1100 includes a torque and traction controller 1117 that performs the same functions, and operates in a similar manner, to previously described torque and traction controller 407. In system 1100, however, torque controller 1117 must control two separate assist motors 1101 and 1103 via dual assist power control modules 1113 and 1115, rather than a single assist motor via a single power control module. Additionally, torque controller 1117 monitors the temperature of both motors 1101 and 1103 via temperature sensors 1119/1121, respectively; monitors the motor speed of both motors 1101 and 1103 via motor speed sensors 1123/1125, respectively; and monitors the temperature of both assist power control modules via temperature sensors 1127/1129, respectively.

In the preferred embodiment of the dual assist drive configuration, assist motors 1101 and 1103 use identical motors. This configuration is preferred since the two assist driven wheels are on the same axis and under most driving conditions, will experience a similar range of wheel slippage. Under these conditions it is desirable for both assist motors to apply a similar amount of torque to their respective wheels. Accordingly, using identical assist motors simplifies system design.

Torque and traction control system 1117 operates in a manner quite similar to that described above relative to control system 407, with a few important differences. FIG. 12 is a schematic of controller 1117. Vehicle torque command generation unit 601 functions as previously described, as does primary torque limiting unit 603. In this configuration, however, there are two assist torque limiting units 1201 and 1203, each having as inputs data from their respective temperature and motor speed sensors as well as the temperature data from their respective control modules 1113 and 1115. The output from units 1201 and 1203 are the maximum available torque for the right and left assist motors, i.e., C_maxtorque2r and C_maxtorque2l. Although in general these values will be the same, it will be appreciated that under some circumstances the temperature of a particular assist motor and/or a particular assist power control module may be higher than that of the other assist drive, potentially resulting in different maximum available torque values.

11

Optimal torque split unit **1205** splits the desired combined torque, i.e., C_torque , into three components without taking into account wheel slip. As shown in FIG. **13**, the algorithm previously described in relation to FIG. **7** undergoes minor modifications in order to output the three torque components. Initially C_torque , C_vspeed , $C_maxtorque1$, $C_maxtorque2r$ and $C_maxtorque2l$ are read (step **1301**). Next, temporary values for the torque for primary motor **103** ($C_temptorque1$) and for assist motors **1101** and **1103**, combined ($C_temptorque2$) are determined, as well as values for the motor flux for primary motor **103** (C_flux1) and for assist motors **1101** and **1103**, combined (C_flux2). (Step **1303**). This step is performed by interpolating data from the look-up table, described previously relative to FIG. **8**, that contains optimal torque (i.e., $T1$ and $T2$) and optimal flux values (i.e., $F1opt$ and $F2opt$) based on vehicle speed and total requested torque. Note that the values are only divided into two sets, i.e., one set for the front axle and one set for the rear axle. Next, the set of values for the front axle, assuming the dual assist motors are coupled to the front axle, are divided in half such that half of the torque is applied to each assist motor, and the same flux is applied to each assist motor. (Step **1305**). The temporary torque values set in steps **1303** and **1305** are then compared to the maximum available torque values (step **1307**) calculated by the primary torque limiting unit and the two assist torque limiting units. If the temporary torque values are less than the maximum available torque values, then the temporary torque values are output as $C_torque1e$ (primary motor), $C_torque2er$ (1^{st} assist motor) and $C_torque2el$ (2^{nd} assist motor); if the temporary torque values are greater than the maximum available torque values, then the maximum available torque values are output as $C_torque1e$, $C_torque2er$ and $C_torque2el$. (Steps **1309** and **1311**). The flux values for the primary motor, i.e., C_flux1 , and the assist motors, i.e., C_flux2r and C_flux2l , are also output in step **1311**.

Traction control command generation unit **1207** operates in a manner similar to that of unit **609**, except that it computes and outputs three slip errors, i.e., $C_sliperror1$, $C_sliperror2r$ and $C_sliperror2l$. As in the previous embodiment, the unit calculates wheel slip ratios for each wheel. For the axle coupled to a single motor, i.e., primary motor **103**, a wheel slip ratio for the axle is calculated, preferably using the higher of the two wheel slip ratios for that particular axle. For the split axle, two wheel slip ratios are used, one per wheel. The three wheel slip ratios are then compared to target wheel slip ratios contained within a lookup table, the lookup table providing target wheel slip ratios as a function of speed and steering angle. For each axle or half-axle, the difference between the computed wheel slip ratio and the target wheel slip ratio yields the computed slip error, referred to herein as " $C_sliperror1$ " for the wheel slip ratio error of the primary-driven axle **101**, " $C_sliperror2r$ " for the wheel slip ratio error of the right wheel of first assist-driven axle **1105**, and " $C_sliperror2l$ " for the wheel slip ratio error of the left wheel of second assist-driven axle **1107**.

As illustrated in FIG. **14**, the computed slip errors along with the values for the optimized torque split and the total requested torque are input into the first stage of the traction and stability control unit **1209**. The first stage independently minimizes the wheel slip ratio errors using a feedback control system, for example using lead-lag compensators or a PID controllers **1401/1402/1403** as shown. In the second stage of unit **1209**, motor speed fast disturbances are independently minimized using high pass filters **1405/1406/1407** and compensators (preferably PID controllers) **1409/1410/1411**. As in the previous embodiment, between the first and second stages

12

is a transient torque boost feedforward control circuit which adds an amount of torque to each drive motor. After the second stage of traction control, torque limiters **1413/1414/1415** independently limit the torque commands issuing from the second stage based on $C_maxtorque1$, $C_maxtorque2r$ and $C_maxtorque2l$. The output of the torque limiters **1413/1414/1415** are torque commands $C_torque1$, $C_torque2l$ and $C_torque2r$.

The torque commands from the limiters, i.e., $C_torque1$, $C_torque2r$ and $C_torque2l$, and the flux commands from the optimal torque split unit **1205**, i.e., C_flux1 , C_flux2r and C_flux2l , are input into control modules **403**, **1113** and **1115**. As previously described, the power control modules can use any of a variety of motor control techniques. Preferably torque and traction controller **1117** uses multiple processing frequencies as previously described relative to controller **407**.

Although multiple drive systems are required in order to gain all of the benefits of the present invention, the inventor has found that with certain modifications, even a single drive system as described below can achieve improved performance via improved efficiency and more effective traction control. An exemplary configuration of a single drive EV **1500** is shown in FIG. **15**. EV **1500** is basically the same as EV **400** with the removal of the assist drive system and associated components. FIG. **16** illustrates a schematic of controller **1501**.

Vehicle torque command generation unit **601** functions as previously described, outputting a torque requirement request, i.e., C_torque , while traction control command generation unit outputs the computed vehicle speed, i.e., C_vspeed . Torque limiting unit **603** calculates the maximum available torque based on monitored data from motor **103**, power control module **403** and ESS **401**.

Optimal torque control unit **1601** determines an optimal torque, $C_torquee$, based on the torque request, C_torque , the vehicle speed, C_vspeed , and the maximum available torque, $C_maxtorque$, without taking into account wheel slip. In order to make this calculation, both the algorithm described relative to FIG. **7** and the look-up table algorithm described relative to FIG. **8** are simplified as shown in corresponding FIGS. **17** and **18**.

In the first step shown in FIG. **17**, C_torque , C_vspeed and $C_maxtorque$ are read. (Step **1701**). Next, temporary values for the torque, $C_temptorque$, and for the flux, C_flux , are determined (step **1703**) by interpolating data from a look-up table. The temporary torque value set in step **1703** is then compared to (step **1705**), and limited by (step **1707**), the maximum available torque value calculated by torque limiting unit **603**, before being output as $C_torquee$ (step **1709**). The flux value for the motor, i.e., C_flux , is also output in step **1709**.

The algorithm used to generate the look-up table used in step **1703** is illustrated in FIG. **18**. As shown, the approach is similar to that illustrated in FIG. **8**, except that it has been simplified due to the elimination of the assist drive system. In step **1801**, a first loop is initiated in which vehicle speed, W , is stepped through from a minimum value, $Wmin$, to a maximum value, $Wmax$, in steps of $Wstep$. In step **1803**, a second loop is initiated in which total vehicle torque, T , is stepped through from a minimum value, $Tmin$, to a maximum value, $Tmax$, in steps of $Tstep$. In the next series of steps, steps **1805-1807**, the optimum flux value, $Fopt$, is determined. Initially, for a given value of T the motor flux F is stepped through from a minimum value, $Fmin$, to a maximum value, $Fmax$, in steps of $Fstep$ (step **1805**). Then for each value of T and F , a value for motor input power, P , is calculated (step **1806**). Next, $Fopt$ is determined, based on achieving the mini-

13

mum input power, P_{min} (step 1807). In the last step, values for F_{opt} are output as a function of T and W (step 1809).

Traction control command generation unit 1603 operates in a manner similar to that of unit 609, except that it computes a single slip error, $C_{sliperror}$. In this embodiment, unit 1603 calculates wheel slip ratios for each wheel of driven axle 101. The wheel slip ratio for this axle is then calculated, preferably using the higher of the two wheel slip ratios. The wheel slip ratio is then compared to a target wheel slip ratio contained within a lookup table, the lookup table providing target wheel slip ratios as a function of speed and steering angle. The difference between the computed wheel slip ratio and the target wheel slip ratio yields the computed slip error, referred to herein as " $C_{sliperror}$ ".

As illustrated in FIG. 19, the computed slip error and the optimized torque are input into the first stage of the traction control unit 1605. The first stage independently minimizes the wheel slip ratio error using a feedback control system, for example using a lead-lag compensator, a PID controller 1901, or other controller type. In the second stage of unit 1605, motor speed fast disturbances are independently minimized using a high pass filter 1903 and a compensator (preferably a PID controller) 1905. Preferably, controllers 1901 and 1905 have different bandwidths and dynamic responses. For example, the bandwidth of the first stage loop is preferably lower than that of the second stage. In at least one embodiment, the sampling frequency of both loops is the same. High pass filter 1903 is designed to remove dc and certain low frequency components of the input motor speed. After the second stage of traction control, a torque limiter 1907 limits the torque command issuing from the second stage based on $C_{maxtorque}$. The output of torque limiter 1907 is torque command $C_{torque1}$.

The torque command from the limiter, i.e., $C_{torque1}$, and the flux command from the optimal torque unit 1601, i.e., C_{flux} , are input into control module 403. As previously described, the power control module can use any of a variety of motor control techniques. Preferably torque and traction controller 1501 uses multiple processing frequencies as previously described relative to controller 407.

As will be understood by those familiar with the art, the present invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. Accordingly, the disclosures and descriptions herein are intended to be illustrative, but not limiting, of the scope of the invention which is set forth in the following claims.

What is claimed is:

1. An electric vehicle drive system comprising:
 - a first and second electric motors;
 - a torque split unit configured to receive first input that includes at least a total torque request for the first and second electric motors, and respective first and second maximum torques for the first and second electric motors, the torque split unit configured to process the first input without taking into account wheel slip, and to generate at least respective first and second torque requests for the first and second electric motors; and
 - a traction and stability control unit configured to receive second input that includes at least the first and second torque requests, the total torque request, and respective first and second slip errors relating to the first and second electric motors, the traction and stability control unit configured to process the second input and to generate respective first and second torque commands for the first and second electric motors.
2. The electric vehicle drive system of claim 1, further comprising a traction control command generation unit

14

coupled to the torque split unit and to the traction and stability control unit, the traction control command generation unit configured to generate at least a computed vehicle speed.

3. The electric vehicle drive system of claim 2, wherein the traction control command generation unit is configured to also generate the first and second slip errors.

4. The electric vehicle drive system of claim 1, further comprising respective first and second torque limiting units for the first and second electric motors, the first and second torque limiting units configured to generate the respective first and second maximum torques.

5. The electric vehicle drive system of claim 1, further comprising a lookup table that contains at least optimal torque values based on vehicle speed and total requested torque, wherein the torque split unit is configured to use the lookup table in generating the first and second torque requests.

6. The electric vehicle drive system of claim 1, wherein the torque split unit is configured to generate the first and second torque requests to implement a maximum operating efficiency while complying with the first and second maximum torques.

7. The electric vehicle drive system of claim 1, wherein the traction and stability control unit comprises multiple stages, in which a first stage minimizes the first and second slip errors.

8. The electric vehicle drive system of claim 7, wherein the traction and stability control unit further comprises a second stage in which motor speed disturbances are minimized.

9. The electric vehicle drive system of claim 8, wherein the traction and stability control unit further comprises a control circuit between the first and second stages, the control circuit configured to add an amount of torque to each of the first and second torque requests, the amount of torque proportional to a difference between the first or second torque request and the total torque request.

10. The electric vehicle drive system of claim 8, wherein the traction and stability control unit further comprises a torque limit stage that limits torque commands generated by the second stage, the torque limit stage limiting the torque commands based on the first and second maximum torques.

11. The electric vehicle drive system of claim 1, wherein the torque split unit and the traction and stability control unit are configured to operate at different frequencies than each other.

12. The electric vehicle drive system of claim 11, wherein the traction and stability control unit is configured to have a first operating frequency that is a specific factor higher than a second operating frequency of the torque split unit.

13. A method comprising:

- receiving first input that includes at least a total torque request for first and second electric motors of an electric vehicle, and respective first and second maximum torques for the first and second electric motors;
- generating, based on the first input and without taking into account wheel slip, at least respective first and second torque requests for the first and second electric motors;
- receiving second input that includes at least respective first and second slip errors relating to the first and second electric motors;
- generating, based on the second input, respective first and second torque commands for the first and second electric motors; and
- applying the respective first and second torque commands for the first and second electric motors.

14. The method of claim 13, further comprising calculating wheel slip ratios for wheels associated with the first and

15

second electric motors, wherein generating the first and second slip errors comprises determining differences between the wheel slip ratios and target wheel slip ratios.

15. The method of claim **13**, wherein generating the first and second torque requests comprises using a lookup table containing at least optimal torque values based on vehicle speed and total requested torque.

16. The method of claim **15**, further comprising generating the lookup table, the lookup table generated by looping through vehicle speed values between minimum and maximum vehicle speeds, looping through total vehicle torque values between minimum and maximum vehicle torques, and looping through first motor torque values between minimum and maximum first motor torque torques.

17. The method of claim **13**, further comprising minimizing the first and second slip errors.

18. The method of claim **17**, further comprising minimizing motor speed disturbances after minimizing the first and second slip errors.

16

19. The method of claim **18**, further comprising, after minimizing the motor speed disturbances, adding an amount of torque to each of the first and second torque requests, the amount of torque proportional to a difference between the first or second torque request and the total torque request.

20. The method of claim **18**, further comprising limiting, based on the first and second maximum torques, torque commands generated in minimizing the motor speed disturbances.

21. The method of claim **13**, further comprising setting a first operating frequency for generating the first and second torque commands to be a specific factor higher than a second operating frequency of generating the first and second torque requests.

22. The method of claim **13**, further comprising limiting the first and second torque commands based on a power limitation of an energy storage system for the first and second electric motors.

* * * * *