



US009092686B2

(12) **United States Patent**
Wang

(10) **Patent No.:** **US 9,092,686 B2**
(45) **Date of Patent:** ***Jul. 28, 2015**

(54) **LOW POWER MULTI-CORE DECODER SYSTEM AND METHOD**

(56) **References Cited**

- (71) Applicant: **Hand Held Products, Inc.**, Fort Mill, SC (US)
- (72) Inventor: **Ynjiun P. Wang**, Cupertino, CA (US)
- (73) Assignee: **Hand Held Products, Inc.**, Fort Mill, SC (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 4 days.

This patent is subject to a terminal disclaimer.

U.S. PATENT DOCUMENTS

| | | |
|-------------|--------|-----------------|
| 3,582,884 A | 6/1971 | Shepard |
| 3,663,762 A | 5/1972 | Joel, Jr. |
| 3,684,868 A | 8/1972 | Christie et al. |
| 3,723,970 A | 3/1973 | Stoller |
| 3,906,166 A | 9/1975 | Cooper et al. |
| 4,004,237 A | 1/1977 | Kratzer |
| 4,041,391 A | 8/1977 | Deerkoski |
| 4,097,847 A | 6/1978 | Forsen et al. |
| 4,114,155 A | 9/1978 | Raab |
| 4,164,628 A | 8/1979 | Ward et al. |
| 4,210,802 A | 7/1980 | Sakai et al. |
| 4,291,410 A | 9/1981 | Caples et al. |
| 4,315,245 A | 2/1982 | Nakahara et al. |
| 4,435,822 A | 3/1984 | Spencer et al. |

(Continued)

(21) Appl. No.: **13/932,634**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Jul. 1, 2013**

EP 2309418 A1 4/2011

(65) **Prior Publication Data**

US 2014/0008439 A1 Jan. 9, 2014

OTHER PUBLICATIONS

EPO, European Search Report from corresponding EP Application EP 10 182186 (EP2309418), dated Jan. 11, 2011 (3 pages).

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 12/571,911, filed on Oct. 1, 2009, now Pat. No. 8,587,595.

Primary Examiner — Joni Richer

(74) *Attorney, Agent, or Firm* — Additon, Higgins & Pendleton, P.A.

- (51) **Int. Cl.**
G06F 15/80 (2006.01)
G06K 7/10 (2006.01)
G06K 7/14 (2006.01)

(57) **ABSTRACT**


A portable data terminal including a multi-core processor having at least a first core and a second core, at least one illumination assembly and at least one imaging assembly and data storage means configured to store a plurality of program instructions, the program instructions including at least one one-dimensional decoder and at least one two-dimensional decoder.

- (52) **U.S. Cl.**
CPC **G06K 7/1404** (2013.01); **G06K 7/1093** (2013.01); **G06K 7/10722** (2013.01)

- (58) **Field of Classification Search**
USPC 345/501, 502, 505, 530, 554, 557;
235/462.01, 462.09, 462.1, 462.11;
718/105

See application file for complete search history.

20 Claims, 5 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

| | | | | | | | |
|-----------|---|---------|----------------------|-----------|---|---------|----------------------|
| 4,445,118 | A | 4/1984 | Taylor et al. | 5,430,286 | A | 7/1995 | Hammond, Jr. et al. |
| 4,488,678 | A | 12/1984 | Hara et al. | 5,430,472 | A | 7/1995 | Curry |
| 4,488,679 | A | 12/1984 | Bockholt et al. | 5,446,271 | A | 8/1995 | Cherry et al. |
| 4,500,776 | A | 2/1985 | Laser | 5,461,425 | A | 10/1995 | Fowler et al. |
| 4,538,060 | A | 8/1985 | Sakai et al. | 5,463,214 | A | 10/1995 | Longacre, Jr. et al. |
| 4,542,528 | A | 9/1985 | Sanner et al. | 5,471,515 | A | 11/1995 | Fossum et al. |
| 4,561,089 | A | 12/1985 | Rouse et al. | 5,471,592 | A | 11/1995 | Gove et al. |
| 4,570,057 | A | 2/1986 | Chadima, Jr. et al. | 5,477,042 | A | 12/1995 | Wang |
| 4,610,359 | A | 9/1986 | Muller et al. | 5,478,997 | A | 12/1995 | Bridgelall et al. |
| 4,628,532 | A | 12/1986 | Stone et al. | 5,478,999 | A | 12/1995 | Figarella et al. |
| 4,636,624 | A | 1/1987 | Ishida et al. | 5,479,515 | A | 12/1995 | Longacre, Jr. |
| 4,639,932 | A | 1/1987 | Schiff | 5,481,098 | A | 1/1996 | Davis et al. |
| 4,644,523 | A | 2/1987 | Horwitz | 5,487,115 | A | 1/1996 | Surka |
| 4,646,353 | A | 2/1987 | Tenge et al. | 5,489,769 | A | 2/1996 | Kubo et al. |
| 4,653,076 | A | 3/1987 | Jerrim et al. | 5,502,297 | A | 3/1996 | Sherman |
| 4,686,363 | A | 8/1987 | Schoon | 5,504,524 | A | 4/1996 | Lu et al. |
| 4,690,530 | A | 9/1987 | Fujino et al. | 5,512,739 | A | 4/1996 | Chandler et al. |
| 4,710,817 | A | 12/1987 | Ando et al. | 5,517,018 | A | 5/1996 | Zheng et al. |
| 4,785,463 | A | 11/1988 | Janc et al. | 5,521,366 | A | 5/1996 | Wang et al. |
| 4,791,446 | A | 12/1988 | Ishida et al. | 5,524,068 | A | 6/1996 | Kacandes et al. |
| 4,794,239 | A | 12/1988 | Allais | 5,537,431 | A | 7/1996 | Chen et al. |
| 4,807,256 | A | 2/1989 | Holmes et al. | 5,545,886 | A | 8/1996 | Metlitsky et al. |
| 4,818,856 | A | 4/1989 | Matsushima et al. | 5,565,669 | A | 10/1996 | Liu |
| 4,825,058 | A | 4/1989 | Poland | 5,567,934 | A | 10/1996 | Zheng et al. |
| 4,841,544 | A | 6/1989 | Nuytkens | 5,569,901 | A | 10/1996 | Bridgelall et al. |
| 4,874,936 | A | 10/1989 | Chandler et al. | 5,572,006 | A | 11/1996 | Wang et al. |
| 4,877,949 | A | 10/1989 | Danielson et al. | 5,585,616 | A | 12/1996 | Roxby et al. |
| 4,896,029 | A | 1/1990 | Chandler et al. | 5,591,955 | A | 1/1997 | Laser |
| 4,901,073 | A | 2/1990 | Kibrick | 5,591,956 | A | 1/1997 | Longacre, Jr. et al. |
| 4,908,500 | A | 3/1990 | Baumberger et al. | 5,598,007 | A | 1/1997 | Bunce et al. |
| 4,942,474 | A | 7/1990 | Akimoto et al. | 5,600,119 | A | 2/1997 | Dvorkis et al. |
| 4,998,010 | A | 3/1991 | Chandler et al. | 5,610,387 | A | 3/1997 | Bard et al. |
| 5,001,560 | A | 3/1991 | Ericsson | 5,612,524 | A | 3/1997 | Sant' Anselmo et al. |
| 5,019,699 | A | 5/1991 | Koenck | 5,621,203 | A | 4/1997 | Swartz et al. |
| 5,113,445 | A | 5/1992 | Wang | 5,637,849 | A | 6/1997 | Wang et al. |
| 5,138,140 | A | 8/1992 | Siemiatkowski et al. | 5,638,465 | A | 6/1997 | Sano et al. |
| 5,153,418 | A | 10/1992 | Batterman et al. | 5,640,202 | A | 6/1997 | Kondo et al. |
| 5,153,421 | A | 10/1992 | Tandon et al. | 5,663,549 | A | 9/1997 | Katz et al. |
| 5,155,343 | A | 10/1992 | Chandler et al. | 5,665,959 | A | 9/1997 | Fossum et al. |
| 5,159,340 | A | 10/1992 | Smith | 5,666,167 | A | 9/1997 | Tufts |
| 5,189,292 | A | 2/1993 | Batterman et al. | 5,668,803 | A | 9/1997 | Tymes et al. |
| 5,212,777 | A | 5/1993 | Gove et al. | 5,672,858 | A | 9/1997 | Li et al. |
| 5,223,701 | A | 6/1993 | Batterman et al. | 5,698,833 | A | 12/1997 | Skinger |
| 5,227,614 | A | 7/1993 | Danielson et al. | 5,699,447 | A | 12/1997 | Alumot et al. |
| 5,235,167 | A | 8/1993 | Dvorkis et al. | 5,702,059 | A | 12/1997 | Chu et al. |
| 5,237,163 | A | 8/1993 | Collins et al. | 5,703,349 | A | 12/1997 | Meyerson et al. |
| 5,245,695 | A | 9/1993 | Basehore | 5,710,417 | A | 1/1998 | Joseph et al. |
| 5,262,871 | A | 11/1993 | Wilder et al. | 5,723,823 | A | 3/1998 | Bell |
| 5,272,323 | A | 12/1993 | Martino | 5,723,853 | A | 3/1998 | Longacre, Jr. et al. |
| 5,276,842 | A | 1/1994 | Sugita | 5,723,868 | A | 3/1998 | Hammond, Jr. et al. |
| 5,278,397 | A | 1/1994 | Barkan et al. | 5,726,435 | A | 3/1998 | Hara et al. |
| 5,286,960 | A | 2/1994 | Longacre, Jr. et al. | 5,739,518 | A | 4/1998 | Wang |
| 5,294,783 | A | 3/1994 | Hammond, Jr. et al. | 5,756,981 | A | 5/1998 | Roustaei et al. |
| 5,304,786 | A | 4/1994 | Pavlidis et al. | 5,763,864 | A | 6/1998 | O'Hagan et al. |
| 5,304,787 | A | 4/1994 | Wang | 5,773,806 | A | 6/1998 | Longacre, Jr. |
| 5,311,001 | A | 5/1994 | Joseph et al. | 5,773,810 | A | 6/1998 | Hussey et al. |
| 5,313,533 | A | 5/1994 | Scott | 5,774,357 | A | 6/1998 | Hoffberg et al. |
| 5,319,185 | A | 6/1994 | Obata et al. | 5,780,832 | A | 7/1998 | Watanabe et al. |
| 5,327,441 | A | 7/1994 | Kawazoe et al. | 5,780,834 | A | 7/1998 | Havens et al. |
| 5,331,176 | A | 7/1994 | Sant' Anselmo et al. | 5,783,811 | A | 7/1998 | Feng et al. |
| 5,343,028 | A | 8/1994 | Figarella et al. | 5,784,102 | A | 7/1998 | Hussey et al. |
| 5,345,266 | A | 9/1994 | Denyer et al. | 5,811,774 | A | 9/1998 | Ju et al. |
| 5,354,977 | A | 10/1994 | Roustaei | 5,811,784 | A | 9/1998 | Tausch et al. |
| 5,378,881 | A | 1/1995 | Adachi et al. | 5,814,801 | A | 9/1998 | Wang et al. |
| 5,378,883 | A | 1/1995 | Batterman et al. | 5,814,803 | A | 9/1998 | Olmstead et al. |
| 5,392,447 | A | 2/1995 | Schlack et al. | 5,815,200 | A | 9/1998 | Ju et al. |
| 5,396,054 | A | 3/1995 | Krichever et al. | 5,818,028 | A | 10/1998 | Meyerson et al. |
| 5,399,852 | A | 3/1995 | Zheng et al. | 5,818,528 | A | 10/1998 | Roth et al. |
| 5,401,949 | A | 3/1995 | Ziemacki et al. | 5,825,006 | A | 10/1998 | Longacre, Jr. et al. |
| 5,412,197 | A | 5/1995 | Smith | 5,831,254 | A | 11/1998 | Karpen et al. |
| 5,414,251 | A | 5/1995 | Durbin | 5,831,674 | A | 11/1998 | Ju et al. |
| 5,418,862 | A | 5/1995 | Zheng et al. | 5,841,121 | A | 11/1998 | Koenck |
| 5,420,409 | A | 5/1995 | Longacre, Jr. et al. | 5,841,126 | A | 11/1998 | Fossum et al. |
| 5,422,470 | A | 6/1995 | Kubo et al. | 5,867,594 | A | 2/1999 | Cymbalski |
| 5,428,211 | A | 6/1995 | Zheng et al. | 5,867,595 | A | 2/1999 | Cymbalski |
| | | | | 5,875,108 | A | 2/1999 | Hoffberg et al. |
| | | | | 5,877,487 | A | 3/1999 | Tani et al. |
| | | | | 5,900,613 | A | 5/1999 | Koziol et al. |
| | | | | 5,914,476 | A | 6/1999 | Gerst, III et al. |

(56)

References Cited

U.S. PATENT DOCUMENTS

| | | | | | | | |
|-----------|----|---------|----------------------|--------------|----|---------|------------------------|
| 5,917,171 | A | 6/1999 | Sasai et al. | 6,661,521 | B1 | 12/2003 | Stern |
| 5,917,945 | A | 6/1999 | Cymbalski | 6,665,012 | B1 | 12/2003 | Yang et al. |
| 5,920,477 | A | 7/1999 | Hoffberg et al. | 6,666,377 | B1 | 12/2003 | Harris |
| 5,926,214 | A | 7/1999 | Denyer et al. | 6,672,511 | B1 | 1/2004 | Shellhammer |
| 5,929,418 | A | 7/1999 | Ehrhart et al. | 6,678,412 | B1 | 1/2004 | Shigekusa et al. |
| 5,932,862 | A | 8/1999 | Hussey et al. | 6,685,095 | B2 | 2/2004 | Roustaei et al. |
| 5,942,741 | A | 8/1999 | Longacre, Jr. et al. | 6,698,656 | B2 | 3/2004 | Parker et al. |
| 5,949,052 | A | 9/1999 | Longacre, Jr. et al. | 6,714,239 | B2 | 3/2004 | Guidash |
| 5,949,054 | A | 9/1999 | Karpen et al. | 6,714,665 | B1 | 3/2004 | Hanna et al. |
| 5,949,056 | A | 9/1999 | White | 6,722,569 | B2 | 4/2004 | Ehrhart et al. |
| 5,962,838 | A | 10/1999 | Tamburrini | 6,729,546 | B2 | 5/2004 | Roustaei |
| 5,965,863 | A | 10/1999 | Parker et al. | 6,732,929 | B2 | 5/2004 | Good et al. |
| 5,979,763 | A | 11/1999 | Wang et al. | 6,732,930 | B2 | 5/2004 | Massieu et al. |
| 5,979,768 | A | 11/1999 | Koenck | 6,736,321 | B2 | 5/2004 | Tsikos et al. |
| 5,984,186 | A | 11/1999 | Tafoya | 6,739,511 | B2 | 5/2004 | Tsikos et al. |
| 5,986,297 | A | 11/1999 | Guidash et al. | 6,742,707 | B1 | 6/2004 | Tsikos et al. |
| 6,003,008 | A | 12/1999 | Postrel et al. | 6,814,290 | B2 | 11/2004 | Longacre |
| 6,012,640 | A | 1/2000 | Liu | 6,832,729 | B1 | 12/2004 | Perry et al. |
| 6,017,496 | A | 1/2000 | Nova et al. | 6,834,806 | B2 | 12/2004 | Benedetti et al. |
| 6,019,286 | A | 2/2000 | Li et al. | 6,837,432 | B2 | 1/2005 | Tsikos et al. |
| 6,053,407 | A | 4/2000 | Wang et al. | 6,854,649 | B2 | 2/2005 | Worner et al. |
| 6,064,763 | A | 5/2000 | Maltsev | 6,857,570 | B2 | 2/2005 | Tsikos et al. |
| 6,070,800 | A | 6/2000 | Fujita et al. | 6,858,159 | B2 | 2/2005 | Lyons |
| 6,082,619 | A | 7/2000 | Ma et al. | 6,860,428 | B1 | 3/2005 | Dowling et al. |
| 6,082,621 | A | 7/2000 | Chan et al. | 6,863,216 | B2 | 3/2005 | Tsikos et al. |
| 6,094,739 | A | 7/2000 | Miller et al. | 6,877,665 | B2 | 4/2005 | Challa et al. |
| 6,119,179 | A | 9/2000 | Whitridge et al. | 6,982,800 | B1 | 1/2006 | Cavill et al. |
| 6,123,264 | A | 9/2000 | Li et al. | 7,014,416 | B2 | 3/2006 | Lund |
| 6,129,278 | A | 10/2000 | Wang et al. | 7,055,747 | B2 | 6/2006 | Havens et al. |
| 6,144,453 | A | 11/2000 | Hallerman et al. | 7,059,525 | B2 | 6/2006 | Longacre et al. |
| 6,152,368 | A | 11/2000 | Olmstead et al. | 7,077,317 | B2 | 7/2006 | Longacre, Jr. et al. |
| 6,155,491 | A | 12/2000 | Dueker et al. | 7,077,321 | B2 | 7/2006 | Longacre, Jr. et al. |
| 6,161,760 | A | 12/2000 | Marrs et al. | 7,080,786 | B2 | 7/2006 | Longacre, Jr. et al. |
| 6,170,749 | B1 | 1/2001 | Goren et al. | 7,086,596 | B2 | 8/2006 | Meier et al. |
| 6,173,894 | B1 | 1/2001 | Olmstead et al. | 7,090,132 | B2 | 8/2006 | Havens et al. |
| 6,176,428 | B1 | 1/2001 | Joseph et al. | 7,093,147 | B2 | 8/2006 | Farkas et al. |
| 6,176,429 | B1 | 1/2001 | Reddersen et al. | 7,097,102 | B2 | 8/2006 | Patel et al. |
| 6,179,208 | B1 | 1/2001 | Feng | D528,146 | S | 9/2006 | Fitch |
| 6,186,404 | B1 | 2/2001 | Ehrhart et al. | 7,104,456 | B2 | 9/2006 | Parker et al. |
| 6,215,992 | B1 | 4/2001 | Howell et al. | 7,261,238 | B1 | 8/2007 | Carlson et al. |
| 6,219,182 | B1 | 4/2001 | McKinley | 7,270,273 | B2 | 9/2007 | Barber et al. |
| 6,230,975 | B1 | 5/2001 | Colley et al. | 7,349,285 | B2 | 3/2008 | Balasubramanian et al. |
| 6,264,105 | B1 | 7/2001 | Longacre, Jr. et al. | 7,540,424 | B2 | 6/2009 | Knowles et al. |
| 6,276,605 | B1 | 8/2001 | Olmstead et al. | 7,571,284 | B1 | 8/2009 | Olson et al. |
| 6,311,895 | B1 | 11/2001 | Olmstead et al. | 7,596,705 | B2 | 9/2009 | Kim |
| 6,315,204 | B1 | 11/2001 | Knighton et al. | 7,694,158 | B2 | 4/2010 | Melpignano et al. |
| 6,329,139 | B1 | 12/2001 | Nova et al. | 7,740,176 | B2 | 6/2010 | Wang et al. |
| 6,347,163 | B2 | 2/2002 | Roustaei | 7,852,519 | B2 | 12/2010 | Meier et al. |
| 6,360,948 | B1 | 3/2002 | Yang et al. | 7,984,854 | B2 | 7/2011 | Nadabar |
| 6,371,373 | B1 | 4/2002 | Ma et al. | 7,984,855 | B2 | 7/2011 | Wang |
| 6,385,352 | B1 | 5/2002 | Roustaei | 8,321,693 | B2 | 11/2012 | Melpignano et al. |
| 6,398,112 | B1 | 6/2002 | Li et al. | 8,587,595 | B2 | 11/2013 | Wang |
| 6,429,934 | B1 | 8/2002 | Dunn et al. | 8,726,048 | B2 | 5/2014 | Naveh et al. |
| 6,443,360 | B1 | 9/2002 | Marchi et al. | 2002/0035715 | A1 | 3/2002 | Hatakeyama |
| 6,462,842 | B1 | 10/2002 | Hamilton | 2002/0039099 | A1 | 4/2002 | Harper |
| 6,486,911 | B1 | 11/2002 | Denyer et al. | 2002/0039197 | A1 | 4/2002 | Hikichi |
| 6,491,223 | B1 | 12/2002 | Longacre, Jr. et al. | 2002/0039457 | A1 | 4/2002 | Helms et al. |
| 6,493,029 | B1 | 12/2002 | Denyer et al. | 2002/0135683 | A1 | 9/2002 | Tamama et al. |
| 6,505,778 | B1 | 1/2003 | Reddersen et al. | 2002/0145043 | A1 | 10/2002 | Challa et al. |
| 6,508,404 | B2 | 1/2003 | Hecht | 2002/0158127 | A1 | 10/2002 | Hori et al. |
| 6,512,218 | B1 | 1/2003 | Canini et al. | 2003/0042311 | A1 | 3/2003 | Longacre et al. |
| 6,525,827 | B2 | 2/2003 | Liu | 2003/0062418 | A1 | 4/2003 | Barber et al. |
| 6,547,139 | B1 | 4/2003 | Havens et al. | 2003/0085282 | A1 | 5/2003 | Parker et al. |
| 6,547,142 | B1 | 4/2003 | Goren et al. | 2003/0136843 | A1 | 7/2003 | Ralph et al. |
| 6,552,323 | B2 | 4/2003 | Guidash et al. | 2003/0146283 | A1 | 8/2003 | Longacre et al. |
| 6,552,746 | B1 | 4/2003 | Yang et al. | 2003/0218067 | A1 | 11/2003 | Parker et al. |
| 6,565,003 | B1 | 5/2003 | Ma | 2004/0004128 | A1 | 1/2004 | Pettinelli et al. |
| 6,575,367 | B1 | 6/2003 | Longacre, Jr. | 2004/0094627 | A1 | 5/2004 | Parker et al. |
| 6,578,766 | B1 | 6/2003 | Parker et al. | 2004/0195332 | A1 | 10/2004 | Barber et al. |
| 6,585,159 | B1 | 7/2003 | Meier et al. | 2004/0206821 | A1 | 10/2004 | Longacre et al. |
| 6,598,797 | B2 | 7/2003 | Lee | 2004/0256464 | A1 | 12/2004 | Longacre et al. |
| 6,606,171 | B1 | 8/2003 | Renk et al. | 2004/0256465 | A1 | 12/2004 | Longacre |
| 6,634,558 | B1 | 10/2003 | Patel et al. | 2004/0262392 | A1 | 12/2004 | Longacre et al. |
| 6,637,658 | B2 | 10/2003 | Barber et al. | 2004/0262394 | A1 | 12/2004 | Longacre et al. |
| 6,655,595 | B1 | 12/2003 | Longacre, Jr. et al. | 2004/0262395 | A1 | 12/2004 | Longacre et al. |
| | | | | 2004/0262396 | A1 | 12/2004 | Longacre et al. |
| | | | | 2004/0262399 | A1 | 12/2004 | Longacre et al. |
| | | | | 2005/0056699 | A1 | 3/2005 | Meier et al. |
| | | | | 2005/0103851 | A1 | 5/2005 | Zhu et al. |

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0161511 A1 7/2005 Parker et al.
2006/0026447 A1 2/2006 Naveh et al.
2006/0054704 A1 3/2006 Fitch et al.
2006/0097054 A1 5/2006 Biss et al.
2006/0126129 A1 6/2006 Barber et al.
2006/0175413 A1 8/2006 Longacre, Jr. et al.
2006/0255150 A1 11/2006 Longacre, Jr.
2006/0259799 A1 11/2006 Melpignano et al.
2006/0282692 A1 12/2006 Oh
2006/0283954 A1 12/2006 Ralph et al.

2006/0288243 A1 12/2006 Kim
2007/0070673 A1 3/2007 Borkar et al.
2007/0140574 A1 6/2007 Yamaguchi et al.
2007/0285698 A1 12/2007 Wang et al.
2008/0011855 A1 1/2008 Nadabar
2010/0078477 A1 4/2010 Wang et al.
2010/0108769 A1 5/2010 Wang et al.
2010/0161939 A1 6/2010 Melpignano et al.
2010/0289915 A1 11/2010 Wang

OTHER PUBLICATIONS

Chinese Office Action (Second) issued Nov. 3, 2014, in application 201010537775.4, Original with English Translation provided, 23 pages.




Fig. 1A




Fig. 1B




Fig. 2A




Fig. 2B




FIG. 3




FIG. 4




FIG. 5

1

LOW POWER MULTI-CORE DECODER SYSTEM AND METHOD

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 12/571,911 filed Oct. 1, 2009 entitled, "Low Power Multi-Core Decoder System and Method." The above application is incorporated herein by reference in its entirety.

TECHNICAL FIELD

The present invention relates to portable data terminals and more particularly, to portable data terminals configured to capture an image and decode any bar code contained in the image.

BACKGROUND INFORMATION

Portable data terminals (PDTs) such as laser indicia reading devices, optical indicia reading devices, barcode scanners and barcode readers, for example, typically read data represented by printed indicia such as symbols, symbology, and bar codes, for example. One type of symbol is an array of rectangular bars and spaces that are arranged in a specific way to represent elements of data in machine readable form. Optical indicia reading devices typically transmit light onto a symbol and receive light scattered and/or reflected back from a bar code symbol or indicia. The received light is interpreted by an image processor to extract the data represented by the symbol. Laser indicia reading devices typically utilize transmitted laser light. One-dimensional (1D) optical bar code readers are characterized by reading data that is encoded along a single axis, in the widths of bars and spaces, so that such symbols can be read from a single scan along that axis, provided that the symbol is imaged with a sufficiently high resolution.

In order to allow the encoding of larger amounts of data in a single bar code symbol, a number of one-dimensional (1D) stacked bar code symbologies have been developed which partition encoded data into multiple rows, each including a respective 1D bar code pattern, all or most all of which must be scanned and decoded, then linked together to form a complete message. Scanning still requires relatively higher resolution in one dimension only, but multiple linear scans are needed to read the whole symbol.

A class of bar code symbologies known as two-dimensional (2D) matrix symbologies have been developed which offer orientation-free scanning and greater data densities and capacities than 1D symbologies. 2D matrix codes encode data as dark or light data elements within a regular polygonal matrix, accompanied by graphical finder, orientation and reference structures.

Conventionally, a PDT includes a central processor which directly controls the operations of the various electrical components housed within the PDT. For example, the central processor controls detection of keypad entries, display features, wireless communication functions, trigger detection, and bar code read and decode functionality. More specifically, the central processor typically communicates with an illumination assembly configured to illuminate a target, such as a bar code, and an imaging assembly configured to receive an image of the target and generate an electric output signal indicative of the data optically encoded therein.

The output signal is generally representative of the pixel data transmitted by an image sensor of the imaging assembly.

2

Because the pixel data may not be high enough quality for the processor to reliably decode the bar code in the image, PDTs generally successively capture images, or image frames, until a reliable decode is complete. Further, where the bar codes being decoded vary from 1D and 2D symbologies, the PDT generally sequentially executes decode algorithms for the multiple symbologies. This process can be time-intensive because the processor must wait for the pixel data to be stored in memory before it can access the data in order to execute a decode algorithm and then must further wait for a decode algorithm to complete before a second decode algorithm can execute. Further, in many settings such as warehouses, shopping centers, shipping centers, and numerous others, PDTs are used to decode bar codes in serial fashion such that a faster decode operation generally increases throughput.

Attempts have been made to increase decode speed particularly by multi-threading. Multi-threading, or hyper-threading, allows multiple threads to use a single processing unit by providing processor cycles to one thread when another thread incurs a latency such as a cache miss, for example, which would cause the processor to incur several cycles of idle time while off-chip memory is accessed. Using multi-threading, the central processor idle time is minimized but not substantially parallelized. Further, context switching between threads can significantly increase overhead, as the state of one process/thread is saved while another is loaded, further minimizing any efficiency gain.

Accordingly, there remains a need in the art for a PDT system architecture that will allow for faster, substantially parallel, bar code decoding operations.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is disclosed with reference to the accompanying drawings, wherein:

FIG. 1A is a plan view of an exemplary PDT and FIG. 1B is a side perspective view of an exemplary PDT.

FIG. 2A is a block schematic diagram of an exemplary PDT according to the present invention.

FIG. 2B is a block schematic diagram of an exemplary PDT according to the present invention.

FIG. 3 is a block schematic diagram of an exemplary multi-core processor according to the present invention.

FIG. 4 is a block schematic diagram of an exemplary dual port memory module according to the present invention.

FIG. 5 is a block schematic diagram of an exemplary multi-core processor according to the present invention.

It will be appreciated that for purposes of clarity and where deemed appropriate, reference numerals have been repeated in the figures to indicate corresponding features.

DETAILED DESCRIPTION

Referring to FIGS. 1A and 1B, two exemplary PDTs 100 for reading/scanning printed indicia are shown. The PDT housing can be shaped so as to fit comfortably into a human hand using a handle portion 104 and can include a finger actuable scan/capture or trigger button 101 as well as a keypad 102 for inputting data and commands, power button, and antenna for facilitating communication with a local or remote host processor, for example. The PDT also includes a display 103, such as an LCD or OLED display, for example, for displaying information to the user. If the display 103 is a touch screen, a stylus (not shown) may also be included to facilitate interaction with the touch screen. An aperture in the housing is included such that the illumination 108 and imaging optics 109 have substantially unobstructed access to the

target **114**. The PDT can also include a power port for receiving a power supply as well as one or more communication ports for facilitating wired or wireless communication with a network interface **134**. Although the present invention is described with respect to a PDT, the invention can be utilized in any bar code scanner, mobile device, mobile computer, or personal data assistant, for example.

Referring to FIGS. 2A and 2B, there is shown a block schematic diagram of the basic structures that together comprise a PDT **105** according to the present invention. The PDT **105** includes an illumination assembly **108** for illuminating a target **114**, such as a bar code, and an imaging assembly **109** for receiving an image of the target **114** and generating an electric output signal indicative of the pixel data optically encoded therein. The illumination assembly **108** includes at least one light source **112** together with illumination optics **110**, such as one or more reflectors, for directing light from the light source in the direction of the target **114**. The light source **112** can include at least one LED configured to emit light in the near-infrared range and/or at least one LED configured to emit light in the visible range. The imaging assembly **102** includes a 2D image sensor **106**, such as a CCD, CMOS, NMOS, PMOS, CID, or CMD solid state image sensor, along with imaging optics **107** for receiving and focusing an image of the target **114** onto the image sensor **106**.

Still referring to FIGS. 2A and 2B, the PDT **105** further includes a processing architecture **115** which controls the operation of the PDT **105** by implementing program instructions it retrieves from the data storage means **122**. More specifically, the processing architecture **115** is configured to receive, output and process data, including image/pixel data, operate the imaging **109** and illumination **108** assemblies, and communicate with a system bus **138** among other operations. Further, the processing architecture **115** may be configured to control the illumination of the light source **112**, the timing of the image sensor **106**, analog-to-digital conversion, transmission and reception of data to and from a processor of a remote computer **136** external to the reader through a network interface **134**, such as an RS-232, RS-485, USB, Ethernet, Wi-Fi, Bluetooth™, IrDA and Zigbee interface, control a user input interface to manage user interaction with a scan/trigger button **101** and/or keypad **102**, and control an output device **103**, such as an LCD or an OLED display, through the display interface **132**. The processing architecture **115** includes at least one multi-core processor **116** as described in detail below with respect to FIGS. 3 and 5 but optionally can include an additional processor(s) or microprocessor(s) such as VLSI or ASIC integrated circuit microprocessor(s). In one embodiment shown in FIG. 2A the data storage means **122a** includes at least one dual port memory module **160**, such as RAM for example, described in detail below with respect to FIG. 4 but optionally can include additional memory modules such as local, network-accessible, removable and/or non-removable memory, such as RAM, ROM, and/or flash. In another embodiment shown in FIG. 2B, the data storage means **122b** includes at least one single port memory module **163**, such as RAM for example, in communication with a direct memory access (DMA) controller **161** as described further below. The data storage means **122** is shown as including applications **125**, such as an operating system for example, a 1D decoder **127**, and a 2D decoder **129**. The decoders **127** and **129** include program instructions that, when executed by the multi-core processor **116**, retrieve image pixel data and decode any bar code contained in the image as is known in the art. Although the decoders **127** and **129** are shown as separate from the dual port memory **160** in FIG. 2A, in another embodiment the

decoder **127** and **129** program instructions are stored in the dual port memory **160**. The PDT **105** also includes one or more power supplies **128**, such as one or more batteries and/or circuitry for receiving an alternating current, and a user input interface **130** for receiving data from a user input device **102**, such as a keyboard, keypad, and/or touch screen. The PDT **105** structures shown in FIG. 2 are preferably supported on one or more printed circuit boards (not shown).

Referring to FIG. 3, a multi-core processor **116** according to the present invention is shown as a dual-core processor **116a** having a first core **140** and a second core **142**. The cores can also share one cache, or in a multilevel cache architecture, each utilize its own respective cache (e.g. L1) and share another cache (e.g. L2) or any combination thereof. In the embodiment shown in FIG. 3, a first level of cache **144** is shown as having instruction and data caches for each core **140**, **142** and a second level of cache **146** is shown as being shared among both cores **140** and **142**. The cores **140** and **142** can be integrated on the same integrated circuit die or they can be integrated onto multiple dies in the same integrated circuit package as is known in the art. Further, the processor **116** can also include one or more independent or shared bus interfaces such as a shared bus interface **148** for communication with a system bus and/or the data storage means **122**. Each core **140** and **142** has its own processing unit and is capable of issuing instructions transmitted through the bus interface to a bus as well as simultaneously performing operations.

Referring to one embodiment shown in FIGS. 2A and 4, dual port memory **160** is shown as including a first port **162** and a second port **164**. At least a portion of the dual port memory, identified as frame buffer **166** in FIG. 4, is configured to store image frame data as received from the image sensor. Dual port memory, such as the dual port memory described by U.S. Pat. No. 5,276,842 to Sugita, incorporated herein by reference, is preferably configured to be accessed by two cores simultaneously on the same clock. Contention issues are preferably handled by arbitration system or arbitration logic as is known in the art and as one exemplary implementation of an arbitration system is also described in the '842 patent. Dual port memory can also be implemented with a single port memory core as taught by Balasubramanian et al. in U.S. Pat. No. 7,349,285, incorporated herein by reference, whereby access requests are processed on both the high and low logic states of the memory clock cycle.

In an exemplary operation, the processing architecture **115** retrieves program instructions from data storage means **122a**, over system bus **138**, which the architecture implements to control the illumination assembly **108** to focus light on a target **114** containing a bar code and imaging assembly **109** to receive the reflected light. The image sensor **106** then transmits output signals, representative of pixel data of the captured image, to the first port **162** of the dual port memory **164** where it is stored in a frame buffer **166**. Each of the first core **140** and the second core **142** can then access the frame buffer **166** and retrieve the pixel data. To allow for parallel decoding, the first core **140** can be configured to execute the program instructions of the 1D decoder and the second core **142** can be configured to execute the program instructions of the 2D decoder. Accordingly, whether the image contains a 1D or 2D bar code, decoding can occur at substantially the same time decreasing the time required for a successful decode. Further, image pixel/frame data can be stored in the dual port memory **160** on the same clock cycle as image pixel/frame data is being retrieved by the first core **140** and/or the second core **142**. PDT **105** can be configured to continuously image the target **114** and store the pixel data, or each frame, in the frame buffer and the cores **140** and **142** can continually process the

5

image frame data, in parallel, until a successful decode event occurs. Upon successful decode, the decoded data is optionally transmitted to the data storage means **122** where it can be accessed, for example, by an application **125**.

In another embodiment, the first core is configured to execute 1D decoder **127** program instructions as well as image quality filter program instructions stored in data storage means **122**. When executed by the first core **140**, the image quality filter program instructions analyze, in real time, the pixel data/each frame retrieved by the core from the frame buffer for quality with respect to contrast, for example. The frame can then be assigned an image quality score which can be factored into a decode algorithm's decision with respect to selecting the highest image quality score frame available in the frame buffer. Further, the image quality filter program instructions can be configured to interrupt an existing decode **127** process which is decoding a frame/image with a low image quality score should a frame/image with a higher image quality score be captured.

In yet another embodiment, the first core **140** is configured to execute image quality filter program instructions, or any other program instructions related to image processing, for example, stored in data storage means **122** and the second core **142** is configured to execute 1D decoder **127** program instructions as well as 2D decoder program instructions **129**.

Referring to FIG. 5, another embodiment is shown wherein the multi-core processor is a quad-core processor further including a third core and a fourth core as well as a first cache level **178**, a second shared cache level **180** and a bus interface **182**. A quad-core processor **116b** generally refers to four processing units or cores **170**, **172**, **174** and **176** manufactured on the same integrated circuit. In this embodiment, the third core **174** can be configured to execute the program instructions of the image quality filter and the fourth core **176** can execute program instructions related to communication with the network interface **134**. Accordingly, the user does not have to wait to pull the trigger or press the scan button again until the first or second core has executed communication routines to transmit the decode results, for example through the network interface **134** to a remote computer **136**, because the fourth core **176** can handle communication with the network interface **134** in parallel with the first and/or second core causing the PDT **105** to capture a new image and begin a new process of decoding any bar code contained in the image.

Referring to FIG. 2B, although the invention has thus far been described as including a dual port memory module, in another embodiment the data storage means **122b** includes a single port memory **163** configured to store a frame buffer. In this embodiment, preferably a DMA controller **161** is included as being in communication with the imaging assembly **109**, the processing architecture **115** and the data storage means **122b**. The DMA controller **161** can off-load the processor by transferring pixel data from the image sensor **106** directly to the single port memory **163** without involving the processing architecture **115** including the multi-core processor **116**. Accordingly, processor cycles that otherwise would be used to manage a frame buffer can instead be used to run decode **127**, **129** algorithms and/or otherwise as described above.

While the present invention substantially reduces the time required for a successful decode, it can also effectively manage the system clock and/or the power supplied to each core to reduce overall power consumption. Particularly in PDTs that are mostly powered by battery, power consumption is a concern because the greater the power dissipated, the faster the remaining battery life is reduced. Accordingly, and as shown in FIGS. 3 and 5, a clock management module/logic

6

150 configured to dynamically vary the clock speed received by each respective core based on the workload/utilization of each core and/or a power management module/logic **150** configured to dynamically vary the voltage received by at least a portion of each core can be utilized to manage resources consumed by the multi-core processor **116b**. One method of power management is described in U.S. patent application Ser. No. 11/238,489 to Borkar et al., incorporated herein by reference, as including voltage regulators to supply power to each core or a part of a core depending on a number of factors including activity, core temperature, transient current consumption, and reliability. Another method of power management has been described by Kim in U.S. patent application Ser. No. 11/424,080, incorporated herein by reference, which includes modulating the mode of the processor to single core or multi-core depending on a number of factors including whether the PDT is connected to AC or battery power, remaining battery level, available memory, and memory usage. One exemplary clock management module is disclosed by Naveh et al. in U.S. patent application Ser. No. 10/899,674, incorporated herein by reference, wherein the clock management module utilizes independent clock throttle settings for each core, independent clock throttle of various functional blocks of one or more core's internal architecture such as reorder buffers and reservation station tables, for example, and scaling the clock frequency of the bus that the multi-core processor uses to communicate with system components.

While the principles of the invention have been described herein, it is to be understood by those skilled in the art that this description is made only by way of example and not as a limitation as to the scope of the invention. Other embodiments are contemplated within the scope of the present invention in addition to the exemplary embodiments shown and described herein. Modifications and substitutions by one of ordinary skill in the art are considered to be within the scope of the present invention, which is not to be limited except by the following claims.

What is claimed is:

1. A portable data terminal, comprising:

a multi-core processor having at least a first core and a second core, the multi-core processor receiving image data on a first clock cycle;

at least one illumination assembly and at least one imaging assembly; and

data storage means configured to store a plurality of program instructions, the program instructions including at least one one-dimensional decoder and at least one two-dimensional decoder, the decoders running in parallel on the first clock cycle, and

wherein the program instructions stored in the data storage means further includes an image quality filter.

2. The portable data terminal of claim 1 wherein the data storage means further includes including at least one multi-port memory module having at least a first port and a second port, the at least one multi-port memory module being configured to receive output signals from the imaging assembly and communicate with the multi-core processor.

3. The portable data terminal of claim 1 further including a power supply, at least one system bus, a network interface, a display interface, and a user input interface.

4. The portable data terminal of claim 1 further including at least one management module selected from the group consisting of a clock management module configured to dynamically vary the clock speed received by each respective core based on the workload of each core and a power management

module configured to dynamically vary the voltage received by at least a portion of each core.

5. The portable data terminal of claim 1 wherein the first core of the multi-core processor executes the one-dimensional decoder and the second core executes the two-dimensional decoder.

6. The portable data terminal of claim 1 wherein the first core of the multi-core processor executes the image quality filter and the second core of the multi-core processor communicates with the network interface.

7. The portable data terminal of claim 1, wherein the image quality filter is configured with filter program instructions that analyze pixel data retrieved by the multi-core processor and assign an image quality score to the pixel data.

8. The portable data terminal of claim 1, wherein the multi-core processor comprises a frame buffer receiving the image data from the imaging assembly and the image quality filter assigns a score to each frame of data in the buffer.

9. The portable data terminal of claim 1, wherein the image quality filter is processed in the first core.

10. The portable data terminal of claim 9, wherein the second core processes the decoders.

11. A portable data terminal, comprising:

a multi-core processor having at least a first core and a second core;

at least one illumination assembly and at least one imaging assembly;

a dual port memory receiving output signals from the imaging assembly on a first clock cycle and the multi-core processor retrieving image data from the dual port memory on the first clock cycle;

data storage means configured to store a plurality of program instructions, the program instructions including at least one one-dimensional decoder and at least one two-dimensional decoder; and

wherein the first core of the multi-core processor executes the one-dimensional decoder and the second core executes the two-dimensional decoder, and

wherein the one-dimensional decoder and two-dimensional decoder run in parallel and on the first clock cycle.

12. The portable data terminal of claim 11, comprising a first level of cache and a second level of cache, the first level including an instruction cache and a data cache for each core and the second level being shared among all the cores.

13. The portable data terminal of claim 11, wherein the multi-core processor comprises a third core and a fourth core, wherein the program instructions stored in the data storage means comprises an image quality filter and wherein the third core of the multi-core processor executes the image quality

filter and the fourth core of the multi-core processor communicates with the network interface.

14. The portable data terminal of claim 11, comprising a direct memory access controller in communication with the imaging assembly, multi-core processor and data storage means and wherein the data storage means comprises at least one single port memory module.

15. A portable data terminal, comprising:

a multi-core processor having at least a first core and a second core;

at least one illumination assembly and at least one imaging assembly;

a dual port memory receiving output signals from the imaging assembly on a first clock cycle and the multi-core processor retrieving image data from the dual port memory on the first clock cycle;

data storage means configured to store a plurality of program instructions, the program instructions including at least one one-dimensional decoder and at least one two-dimensional decoder; and

wherein the one-dimensional decoder and two-dimensional decoder run in parallel and on the first clock cycle.

16. The portable data terminal of claim 15, comprising a power supply, at least one system bus, a network interface, a display interface, a system bus, and a user input interface.

17. The portable data terminal of claim 15, wherein the imaging assembly comprises imaging optics and an image sensor and the illumination assembly comprises illumination optics and at least one light source.

18. The portable data terminal of claim 15, comprising at least one management module selected from the group consisting of a clock management module configured to dynamically vary the clock speed received by each respective core based on the workload of each core and a power management module configured to dynamically vary the voltage received by at least a portion of each core.

19. The portable data terminal of claim 15, wherein a first port of the memory is configured to receive at least one output signal from the imaging assembly, the output signals representing pixel data transmitted by the image sensor, and a second port of the memory is configured to communicate with the multi-core processor.

20. The portable data terminal of claim 15, wherein the multi-core processor comprises a third core and a fourth core, wherein the program instructions stored in the data storage means comprises an image quality filter and wherein the third core of the multi-core processor executes the image quality filter and the fourth core of the multi-core processor communicates with the network interface.

* * * * *