



US009256487B1

(12) **United States Patent**
Varnica et al.

(10) **Patent No.:** **US 9,256,487 B1**
(45) **Date of Patent:** ***Feb. 9, 2016**

(54) **OPTIMIZING ERROR FLOOR PERFORMANCE OF FINITE-PRECISION LAYERED DECODERS OF LOW-DENSITY PARITY-CHECK (LDPC) CODES**

(58) **Field of Classification Search**
CPC H03M 13/1102; H03M 13/1114; H03M 13/1131
See application file for complete search history.

(71) Applicant: **Marvell International Ltd.**, Hamilton (BM)

(56) **References Cited**

(72) Inventors: **Nedeljko Varnica**, San Jose, CA (US);
Gregory Burd, San Jose, CA (US);
Kiran Gunnam, Milpitas, CA (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Marvell International Ltd.**, Hamilton (BM)

8,291,292	B1	10/2012	Varnica et al.	
2003/0229843	A1 *	12/2003	Yu et al.	714/794
2004/0034827	A1 *	2/2004	Shen et al.	714/758
2004/0268205	A1 *	12/2004	Stolpman	714/758
2005/0078765	A1 *	4/2005	Jeong et al.	375/267
2005/0193320	A1 *	9/2005	Varnica et al.	714/800
2005/0210367	A1 *	9/2005	Ashikhmin et al.	714/801
2005/0229087	A1 *	10/2005	Kim et al.	714/800
2006/0107193	A1 *	5/2006	Park et al.	714/801

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(Continued)

OTHER PUBLICATIONS

Gunnam et al., "Iterative LDPC Solutions for Turbo Equalization," Jul. 2006.

(21) Appl. No.: **14/283,718**

(Continued)

(22) Filed: **May 21, 2014**

Primary Examiner — M. Mujtaba K Chaudry

Related U.S. Application Data

(57) **ABSTRACT**

(60) Continuation of application No. 13/610,438, filed on Sep. 11, 2012, now Pat. No. 8,769,382, which is a division of application No. 12/350,052, filed on Jan. 7, 2009, now Pat. No. 8,291,292.


Systems and methods are provided for selecting precisions during iterative decoding with a low-density parity check (LDPC) decoder in order to maximize LDPC code's performance in the error floor region. The selection of the precision of the messages may be done in such a way as to avoid catastrophic errors and to minimize the number of near-code-word errors during the decoding process. Another system and method to avoid catastrophic errors in the layered (serial) LDPC decoder is provided. Lastly, a system and method that select precisions and provide circuitry that optimizes the exchange of information between a soft-input, soft-output (SISO) channel detector and an error correction code (ECC) decoder for channels with memory is provided.

(60) Provisional application No. 61/019,946, filed on Jan. 9, 2008.

(51) **Int. Cl.**
H03M 13/00 (2006.01)
G06F 11/07 (2006.01)
H03M 13/11 (2006.01)

18 Claims, 15 Drawing Sheets

(52) **U.S. Cl.**
CPC **G06F 11/073** (2013.01); **H03M 13/1102** (2013.01); **H03M 13/1114** (2013.01)



(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0276156 A1 11/2008 Gunnam et al.
2008/0301521 A1 12/2008 Gunnam et al.

OTHER PUBLICATIONS

Gunnam et al., "Value-Reuse Properties of Min-Sum for GF(q)," Texas A&M Note, report dated Oct. 2006. Available for unrestricted access since Jul. 2008. Published around Aug. 2010.

Gunnam et al., excerpt "Word Length Analysis for LDPC Decoders," Texas A&M University Technical Note Draft, 2006.

Kavcic, Aleksander et al. "Binary Intersymbol Interference Channels: Gallager Codes, Density Evolution and Code Performance Bounds," IEEE Transactions on Information Theory, pp. 100-118, (Feb. 2002).

Luby, Michael G. et al. "Improved Low-Density Parity-Check Codes Using Irregular Graphs," IEEE Transactions on Information Theory, vol. 47, No. 2, pp. 585-598, (Feb. 2001).

Mackay, David J.C. et al. "Weaknesses of Margulis and Ramanujan-Margulis Low-Density Parity-Check Codes," Electronic Notes in Theoretical Computer Science, vol. 74, (2003).

Mansour, Mohammad M. et al. "A 640-Mb/s 2048-Bit Programmable LDPC Decoder Chip," IEEE Journal of Solid-State Circuits, vol. 41, No. 3, pp. 684-698, (Mar. 2006).

Richardson, Thomas J. et al. "The Capacity of Low-Density Parity-Check Codes Under Message-Passing Decoding," IEEE Transactions on Information Theory, vol. 47, No. 2, pp. 599-618, (Feb. 2001).

Richardson, Thomas J. et al. "Design of Capacity-Approaching Irregular Low-Density Parity-Check Codes," IEEE Transactions on Information Theory, vol. 47, No. 2, pp. 619-637, (Feb. 2001).

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7




FIG. 8

900




FIG. 9




FIG. 10

1100




FIG. 11




FIG. 12A




FIG. 12B




FIG. 12C

**OPTIMIZING ERROR FLOOR
PERFORMANCE OF FINITE-PRECISION
LAYERED DECODERS OF LOW-DENSITY
PARITY-CHECK (LDPC) CODES**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a continuation of pending U.S. patent application Ser. No. 13/610,438, filed Sep. 11, 2012, which is a divisional of U.S. patent application Ser. No. 12/350,052 (now U.S. Pat. No. 8,291,292), filed Jan. 7, 2009, which claims the benefit under 35 U.S.C. §119(e) of U.S. Provisional Application No. 61/019,946, filed Jan. 9, 2008, each of which is hereby incorporated by reference herein in its entirety.

BACKGROUND OF THE DISCLOSURE

This disclosure relates generally to data decoding, and more particularly to optimizing error floor performance of finite-precision layered decoders of low-density parity check (LDPC) codes.

With the continuing demand for high-reliability transmission of information in digital communication and storage systems, and with the rapid increase in available computational power, various coding and decoding techniques have been investigated and applied to increase the performance of these systems. One such coding technique, low-density parity check (LDPC) coding, was first proposed in the 1960s, but was not generally used until the 1990s when researchers began to investigate iterative coding and decoding techniques.

LDPC codes are among the few known error control coding techniques capable of transmitting information at a rate close to the Shannon limit or channel-capacity. LDPC codes may be used in the transmission of information on media, or channels, with or without memory. LDPC coding techniques are generally iterative in nature, and may be represented by many different types of parity check matrices. The structure of an LDPC code's parity check matrix may be, for example, random, cyclic, or quasi-cyclic. LDPC codes defined by quasi-cyclic parity check matrices are particularly common and computationally efficient. These codes are known as quasi-cyclic low density parity check (QC-LDPC) codes.

As used herein, "finite precision" refers to a property of an object that signifies that the object either may contain information that may be represented by a finite set of symbols or that the object may perform computations on information represented by a finite set of symbols.

An iterative decoder for use with channels without memory may include an error correcting code (ECC) decoder. In performing decoding, the information from the channel may be passed to the ECC decoder for use in the decoding operation. An iterative decoder for use with channels with memory may include a soft-input soft-output (SISO) channel detector in addition to the ECC decoder. An iterative decoder may alternate between use of a SISO channel detector and ECC decoder to decode data. The information from an iteration of the SISO channel detector may be passed to the ECC decoder for use in the next ECC decoding iteration, and vice versa. Through this iterative process, data reliability is improved.

An iterative decoder may decode LDPC codes using an iterative message passing algorithm, such as a min-sum decoding algorithm. Such algorithms may decode a received codeword using an iterative process, in which each iteration includes two update steps. In the first update step, messages

may be passed from some (or all) check nodes to some (or all) variable nodes, and in the second update step, messages may be passed from some (or all) variable nodes to some (or all) check nodes. The update steps may be scheduled in a serial (layered) or flooding fashion. A layered update schedule may provide similar performance with half the number of iterations as compared to a flooding decoding schedule. Details about a layered decoder can be found in the following reference "A 640-Mb/s 2048-Bit Programmable LDPC Decoder Chip", in IEEE Journal of Solid State Circuits, March 2006. An iterative decoder which uses a layered update schedule for the message passing algorithm may be referred to as a layered iterative decoder.

The performance capability of a coding scheme, such as a LDPC coding scheme, is often described by the code's performance curve. The performance curve is a plot of signal-to-noise ratios (SNR) vs. Bit Error Rate (BER), or Sector Error Rate (SER). The performance curve of LDPC codes generally includes two regions: a waterfall region and an error floor region (see FIG. 6). In the waterfall region, the code's BER or equivalently, SER, decreases rapidly with improvements in SNR. However, in the high SNR operating region, the BER/SER plateaus to an error floor, meaning that further improvements in channel condition would not lead to significantly lower BER/SER.

Messages that are passed in the message passing algorithm, used by the iterative decoder, may be of a finite precision. If the messages passed have insufficient precision or precision that is not optimized, the iterative decoder may have the drawback of producing two types of errors that results in higher error floors, which is highly undesirable. These two types of errors are: 1) near-codeword failures and 2) catastrophic errors also known as propagating errors of propagating failures. Near-codeword failures in iterative decoders that do not use properly selected or optimized message precisions may occur more frequently than they would in iterative decoders that use properly selected or optimized message precisions. Details about near-codeword failures can be found in "Weaknesses of Margulis and Ramanujan-Margulis Low-Density Parity-Check Codes" in Electronic Notes in Theoretical Computer Science 2003. Catastrophic errors may lead to increased BER/SER at high SNR values. Moreover, an increased BER/SER at high SNR values may lead to degraded application performance and/or a lowered data transmission rate.

Many communication channels utilizing iterative encoders and iterative decoders operate in the error floor region of the performance curve of the LDPC code. Due to the fact that error floors tend to be very low, e.g. in some instances the error floor is observed at SER= 10^{-9} , at SER= 10^{-12} , or lower, it might not be feasible to reliably simulate error floor performance of a LDPC code. As a consequence, simulations in the waterfall region are typically relied upon to carry out performance/complexity studies for implementations of iterative decoders using messages. It is important to note, however, that neither the effects of near-codeword failures nor the effects of catastrophic errors are likely to be observed in the waterfall region of the performance curve of a LDPC code. Therefore, iterative decoders that are configured based on the performance curve of the LDPC code in the waterfall region (i.e. BER/SER performance at lower SNRs) may use precisions that may not be appropriate or sufficient for the error floor region of the performance curve of the LDPC code. This can lead to suboptimal implementations of an iterative decoder for LDPC codes.

Iterative decoders which use a message passing algorithm with optimized message precisions (or with a modified

decoding update rule) may avoid a high probability for near-codeword failures and may produce fewer catastrophic errors. This may lead to decreased BER/SER at various SNR values. Therefore, it would be desirable to provide layered iterative decoders which use a message passing algorithm with optimized message precisions based on the error floor region of the performance curve of a LDPC code. The increased decoding performance in the error floor region of these types of decoders may lead to improved application performance and/or larger data transmission rates.

SUMMARY OF THE DISCLOSURE

Accordingly, systems and methods are disclosed that provide optimizations in the precision of a-posteriori P type messages computed by the variable nodes and the precision of the Q type messages that are passed from the variable nodes to the check nodes in the message passing algorithm used by the iterative decoder for LDPC codes. Selecting precisions according to this disclosure may provide optimized performance of iterative decoders in the error floor region of the performance curve of a LDPC code.

Embodiments are provided to avoid catastrophic (propagating) errors in the layered iterative decoder. For example, P and/or Q type messages in the layered iterative decoder may be “frozen” as soon as those messages reach their saturation values. As another example, finite precisions for messages in the message passing algorithm used by the iterative decoder may be selected to avoid the catastrophic errors altogether.

Embodiments are also provided for selecting the precision and the maximum magnitudes of the messages passed from a soft-input, soft-output (SISO) channel detector (e.g. a SOVA detector) to the LDPC decoder and from LDPC decoder to SISO channel detector in the detector-decoder combination for channels with memory.

An encoder, in accordance with some embodiments, may encode user information (such as holographic page data or magnetic recording data) using a LDPC code and send this to a modulator to transmit on a channel. The channel may or may not have memory. After transmission on the channel, a demodulator may demodulate the information received from the channel. The received signal (received vector) from the demodulator may contain errors due to channel noise. The signal may then be processed by an iterative decoder.

A finite precision for Q type messages (i.e. the messages sent from variable nodes to check nodes) or P type messages (i.e. the a-posteriori probabilities of variable nodes) may be selected. The precisions may be selected based at least in part on channel type (e.g. channels with memory or channels without memory). The precisions may also be selected based at least in part on the performance of the LDPC code. For example, assuming that the precision of R type messages (i.e. the messages from sent from check nodes to variable nodes) may be given or already selected (e.g. based on the hardware complexity limitations), selecting a different precision of the Q type and/or P type messages may be done in order to preferably optimize the performance of an LDPC code in the error floor region of its performance curve. The layered iterative decoder may then use the message passing algorithm with the selected finite precisions for check nodes and variable nodes messages to process the received vector.

In some embodiments, such as in channels without memory, the precision of R type messages, P_R , may be first selected or optimized, and then the precision of the computed a-priori LLRs (P_{LLR}) may be selected. In order to substantially eliminate catastrophic (propagating) errors, the precision of P type messages may be set to: $P_P = \text{ceil}(\log_2(\text{cw} \cdot 2^{P_R} +$

$2^{P_{LLR}})$, where cw is the largest column weight in the LDPC parity check matrix. Moreover, if the message passing algorithm update steps are scheduled so that Q type messages are stored in memory, the precision of Q type messages may be set to: $P_Q = \text{ceil}(\log_2((\text{cw}-1) \cdot 2^{P_R} + 2^{P_{LLR}}))$. Selecting the precisions of messages in this way may ideally avoid catastrophic errors. It may also reduce the occurrence of near-codeword failures, which may be a dominating factor in the performance of a LDPC code in the error floor region.

In some embodiments, such as in channels with memory, a precision for P type and Q type messages, P_P and P_Q respectively, may be chosen together with the precision of the LLRs received from a channel detector (i.e. S type messages with precisions P_S), and/or together with the precision of output messages from the ECC decoder back to the channel detector (i.e. Le type messages). For iterative decoders used in channels with memory, the precision of S type messages (P_S) may be reduced, if desired. There may be a gain or loss in the performance of the LDPC code due to this reduction. Reducing P_S may, however, mitigate the effects of improper LLRs (such as defect LLRs, for example) that may be produced by a channel detector (e.g. due to defects present in the received vector).

For example, the precision of R type messages may first be selected or optimized; the precision of Le type messages may be set to $P_{Le} = P_R + \text{ceil}(\log_2(\text{cw}))$, and the precision of S type messages, P_S , may be set. For example, this precision may be set so that $P_S \leq P_{Le}$. Then, the precision of P type messages may be set to: $P_P = \text{ceil}(\log_2(\text{cw} \cdot 2^{P_R} + 2^{P_S}))$ and the precision of Q type messages may be set to: $P_Q = \text{ceil}(\log_2((\text{cw}-1) \cdot 2^{P_R} + 2^{P_S}))$. Setting precisions in this way may ideally avoid catastrophic errors are avoided altogether. This may also reduce the occurrence of some near-codeword failures, which may dominate the LDPC code performance in the error floor region.

In another embodiment, the precisions of messages sent between a SISO channel detector and an ECC decoder may be selected and appropriately quantized. More specifically, the range of Le type messages going from the output of the ECC decoder and the input of the SISO channel detector may be confined. Also, the range of LS_{ext} messages going from the SISO channel detector to the ECC decoder may be confined. Depending on implementation, a message that is passed by the ECC decoder to the SISO detector may be either a P type or a LS_{ext} message. However, a message sent from the SISO channel detector to the ECC decoder may be labeled as an extrinsic message, LS_{ext} (a LS_{ext} message may contain new information produced by the SISO channel detector).

Yet another embodiment relates to a layered iterative decoder that “freezes” any P type (and/or Q type) message (i.e. stops the message from changing value) as soon as that message becomes saturated (i.e. there are insufficient bits to hold the information in the message) in the layered iterative decoder. This may result in reducing or entirely eliminating catastrophic (propagating) errors in the layered decoder. P type and/or Q type messages may be set to smaller precisions (P_P and P_Q , respectively). For example, P_P may be set so that $P_P < \text{ceil}(\log_2(\text{cw} \cdot 2^{P_R} + 2^{P_S}))$, and P_Q may be set so that $P_Q < \text{ceil}(\log_2((\text{cw}-1) \cdot 2^{P_R} + 2^{P_S}))$. More specifically, the precisions for P type messages may be set as $P_P = \text{ceil}(\log_2(\text{cw} \cdot 2^{P_R} + 2^{P_S})) - 1$ or $P_P = \text{ceil}(\log_2(\text{cw} \cdot 2^{P_R} + 2^{P_S})) - 2$. Setting the precisions of the P type messages in this manner may avoid catastrophic errors if it is possible to freeze the P type messages. However, using reduced precisions, and not freezing the P type messages, may not avoid catastrophic errors.

BRIEF DESCRIPTION OF THE FIGURES

The above and other aspects and advantages of the invention will be apparent upon consideration of the following

detailed description, taken in conjunction with the accompanying drawings, in which like reference characters refer to like parts throughout, and in which:

FIG. 1 shows an illustrative block diagram of an error-correcting communication/storage system in accordance with some embodiments;

FIG. 2A shows an illustrative example of the properties of a codeword in accordance with some embodiments;

FIG. 2B shows an illustrative example of a quasi-cyclic parity check matrix in accordance with some embodiments;

FIG. 3A shows a simplified block diagram of an iterative decoder used for decoding a codeword in channels without memory in accordance with some embodiments;

FIG. 3B shows a simplified block diagram of an iterative decoder used for decoding a codeword in channels with memory in accordance with some embodiments;

FIG. 4 shows a graphical illustration of a parity check matrix and a message passing algorithm corresponding to the parity check matrix in accordance with some embodiments;

FIG. 5A shows a graphical illustration of update rules for variable nodes in the message passing algorithm in accordance with some embodiments;

FIG. 5B shows a graphical illustration of update rules for check nodes in the message passing algorithm in accordance with some embodiments;

FIG. 6 shows an illustrative graph of regions of error at various signal to noise ratios in accordance with some embodiments;

FIG. 7 shows a graphical illustration of the scheduling of update steps of the iterative layered message passing algorithm in accordance with some embodiments;

FIG. 8 shows a simplified block diagram of a serial (layered) decoder processing unit used in an iterative in accordance with some embodiments;

FIG. 9 shows a flowchart of an embodiment of a process for choosing the optimal precision of P and/or Q type messages within the iterative decoder used by the message passing algorithm for decoding a codeword in channels without memory in accordance with some embodiments;

FIG. 10 shows a simplified block diagram of an iterative decoder used for decoding a codeword in channels with memory and precisions of various messages passed within the iterative decoder used by the message passing algorithm in accordance with some embodiments;

FIG. 11 shows a flowchart of an embodiment of a process for choosing the optimal precision of P or Q type messages within the iterative decoder used by the message passing algorithm for decoding a codeword in channels with memory in accordance with some embodiments;

FIG. 12A shows a flowchart of a process for “freezing” a P type message, if it becomes saturated in accordance with some embodiments;

FIG. 12B shows a flowchart of a process for “freezing” a Q type message, if it becomes saturated in accordance with some embodiments; and

FIG. 12C shows a simplified block diagram of serial (layered) decoder processing unit 1220 used in an iterative decoder with additional “message freezing” hardware in accordance with some embodiments.

DETAILED DESCRIPTION OF THE DISCLOSURE

Systems and methods are provided for optimizing performance of layered decoders of low-density parity check (LDPC) codes. In applications or devices where information may be altered by interference signals or other phenomena,

error correction codes, such as LDPC codes, may provide a measured way to protect information against such interference. As used herein, “information” and “data” refer to any unit or aggregate of energy or signals that contain some meaning or usefulness. Encoding may generally refer to the process of generating data in a manner that facilitates subsequent detection and/or correction of errors in the data, while decoding may generally refer to the counterpart process of detecting and/or correcting the errors. The elements of a coding system that perform encoding and decoding are likewise referred to as encoders and decoders, respectively.

FIG. 1 shows an illustrative communication or data storage system 100 that utilizes error correction codes for achieving reliable communication or storage in accordance with some embodiments. User information 102 is encoded through encoder 104. User information 102, often referred to as the message information or a message vector, may be grouped into units of k symbols, where each symbol may be binary, ternary, quaternary, or any other suitable type of data. However, for simplicity, embodiments of the present invention will be described in terms of binary bits. In the process of encoding user information 102, different codes may be used by encoder 104 to achieve different results.

As shown in FIG. 1, encoder 104 may encode user information 102 using a low density parity check (LDPC) code. The result of encoding user information 102 is codeword 106, also denoted as c. Codeword 106 may be of a predetermined length, which may be referred to as n, where $n \geq k$.

In one implementation, codeword 106 is passed to a modulator 108. Modulator 108 prepares codeword 106 for transmission on channel 110. Modulator 108 may use phase-shift keying, frequency-shift keying, quadrature amplitude modulation, or any suitable modulation technique to modulate codeword 106 into one or more information-carrying signals. Channel 110 may represent media through which the information-carrying signals travel. Channel 110 may be an asymmetric or symmetric channel. Channel 110 may have memory or may not have memory. For example, channel 110 may represent a wired or wireless medium in a communication system, or an electrical (e.g., RAM, ROM), magnetic (e.g., a hard disk), or optical (e.g., CD, DVD or holographic) storage medium in which the information-carrying signals may be stored.

Due to interference signals and other types of noise and phenomena, channel 110 may corrupt the waveform transmitted by modulator 108. Thus, the waveform received by demodulator 112, received waveform 111, may be different from the originally transmitted signal waveform. Received waveform 111 may be demodulated with demodulator 112. Demodulator 112 may demodulate received waveform 111 with filters, multiplication by periodic functions, or any suitable demodulation technique corresponding to the type of modulation used in modulator 108. The result of demodulation is received vector 114, which may contain errors due to channel corruption.

Received vector 114 may then be processed by iterative decoder 116. Iterative decoder 116 may be used to correct or detect errors in received vector 114. Iterative decoder 116 may use an iterative message passing algorithm to correct or detect errors in received vector 114. The iterative message passing algorithm may use, for example, a error correction code (ECC) decoder. The iterative message passing decoding algorithm may use, for example, a SISO channel detector and an ECC decoder. When utilizing such an iterative algorithm, iterative decoder 116 may perform several iterations of the algorithm until the output of iterative decoder 116 converges to a valid codeword. In some instances, the output of iterative

decoder **116** may fail to converge to a valid codeword. Decoder failure may be caused by a variety of reasons. Because the output of iterative decoder **116** may never converge to a valid codeword in certain situations, iterative decoder **116** may be equipped with a maximum iteration limit, which may be any suitable predetermined number. When iterative decoder **116** reaches the maximum iteration limit, iterative decoder **116** may automatically terminate operation and move on to the next received vector **114**. However, if the output of iterative decoder **116** successfully converges to a valid codeword, iterative decoder **116** may then output decoded information **118**.

FIG. 2A shows an illustrative example of the properties of codeword **106** of FIG. 1 in accordance with some embodiments. The LDPC codes processed by encoder **104** of FIG. 1 and iterative decoder **116** of FIG. 1 are conventionally represented by mathematical vector models. In particular, an LDPC code may be described by its parity check matrix **H**. Equation **210** illustrates parity check matrix **212**. Parity check matrix **212** may be of size $[r \times n]$, corresponding to codewords of length n and syndromes of length r . Codewords may be, for example, n -length codeword **106** or n -length received vector **114** of FIG. 1. Syndrome length r may satisfy the inequality $r \geq n - k$ and where k is the length of the information being encoded (e.g., length of user information **102** of FIG. 1). When parity check matrix **212** is multiplied by codeword **214**, the result is zero-vector **216**, which is a vector of size $[r \times 1]$ where all elements equal zero. Parity check matrix **212** has a maximum column weight (cw) defined to be the maximum of the set of the number of nonzero entries in each column of parity check matrix **212**. Parity check matrix **212** is not unique, and may be chosen, for example, to be computationally convenient and/or to decrease the number of errors of the ECC decoder used by the message passing algorithm in iterative decoder **116** of FIG. 1. As discussed in relation to FIG. 1, codeword **214** may be decoded in iterative decoder **116** of FIG. 1 to produce decoded information **118** of FIG. 1.

FIG. 2B shows an illustrative example of quasi-cyclic parity check matrix **220** in accordance with some embodiments. In hardware implementations of low-density parity check codes, it may be desirable for storage and processing to have quasi-cyclic code representations. A quasi-cyclic code representation is defined by the characteristic that the parity check matrix for that particular code is quasi-cyclic. A quasi-cyclic matrix is made up of circular submatrices known as circulants. Circulant **222** is one such matrix. Circulant **222** is a square matrix—i.e. circulant **222** has the same number of rows as columns. This number is commonly referred to as the circulant size S_c . In addition, circulants have the property that for any given positive integer $M < S_c$, any row/column of the circulant matrix may be cyclically shifted by M positions to obtain another row or column. It may be computationally beneficial to represent circulants so that they have the property that the cyclic shift of any row or column by $M=1$ yields the adjacent row or column. Circulant **222** may be one of many circulants of the same size that comprise the quasi-cyclic parity check matrix **220**.

If a quasi-cyclic representation of parity check matrix is used, then the implementation of LDPC encoder **104** of FIG. 1 and the ECC decoder, used by the message passing algorithm in iterative decoder **116** of FIG. 1, may be significantly simplified. One reason for this is that parity check matrix **212** of FIG. 2A may be much easier to store, since only the first row of each circulant matrix needs to be stored in order to generate the entire circulant. Another reason for this is that the storage of the messages used in LDPC decoders may be made compact and that the parallelization in encoder/decoder may

be achievable with simple shifting operations since adjacent rows (or adjacent columns) corresponding to the same circulant are simple cyclic shifts of each other.

FIG. 3A shows a simplified block diagram of an iterative decoder that may be used for decoding a codeword in channels without memory in accordance with some embodiments. An iterative decoder for use with channels without memory may include ECC decoder **312**. Received vector **114** from channel **110** of FIG. 1 may be passed as channel input **314** to ECC decoder **312** for use in the decoding operation. ECC decoder **312** may calculate a log-likelihood-ratio (LLR) message (also known as soft information). For example, ECC decoder **312** may compute the LLR message using the equation

$$LLR(b_i) = \log \left(\frac{P(b_i = 0)}{P(b_i = 1)} \right)$$

for each i , where b_i may represent the i^{th} bit in received vector **114** of FIG. 1. ECC decoder **312** may use the computed LLR messages in the message passing algorithm, which will be discussed further below. ECC decoder **312** may then output LLRs **316** based on the output of the message passing algorithm.

FIG. 3B shows a simplified block diagram of an iterative decoder used for decoding a codeword in channels with memory in accordance with some embodiments. An iterative decoder for use with channels with memory may include soft-input soft-output (SISO) channel detector **322**, and ECC decoder **326**. In performing iterative decoding, an iterative decoder may alternate between use of SISO channel detector **322** and ECC decoder **326**. The information from an iteration of SISO channel detector **322** may be passed to the ECC decoder **326** for use in the next ECC decoding iteration, and vice versa. Through this iterative process, data reliability may be improved.

In each iteration of the process, received vector **114** from channel **110** of FIG. 1 may be passed as channel input **321** to SISO channel detector **322**. SISO channel detector **322** may then use a soft output Viterbi algorithm (SOVA) or a Bahle, Cocke, Jelinek, and Reviv (BCJR) algorithm and channel input **321** to produce detector output LLRs **324** (also referred to as S type messages, or more generally, soft information). Detector output LLRs **324** may then be passed as input to ECC decoder **326** for use in the decoding operation. ECC decoder **326** may use detector output LLRs **324** to compute ECC decoder **326** output LLRs **328** (also referred to as L type messages). ECC decoder **326** output LLRs **328** may be passed as input LLRs **329** to SISO channel detector **322**.

FIG. 4 shows graphical illustration **400** of a parity check matrix and a message passing algorithm corresponding to the parity check matrix in accordance with some embodiments. An LDPC code may be graphically represented by a Tanner graph, a bipartite graph showing the relationship between a LDPC code's codeword bits and syndrome bits. The advantages of using a Tanner graph of a LDPC code may include access to efficient graph-based message passing algorithms for decoding. There are two types of nodes shown in Tanner graphs **403** and **404**. Variable nodes **401** represent each position in codeword **106** and are denoted by circles. Thus, there may be n variable nodes. Variable nodes may also be referred to as symbol or bit nodes. Check nodes **405** represent each syndrome (parity check equation) of the LDPC code. For example, there may be $n-k$ check nodes. Check nodes are denoted by squares.

Tanner graphs **403** and **404** correspond to parity check matrix **402**. The check nodes and variable nodes of Tanner graphs **403** and **404** may correspond to the rows and columns of parity check matrix **402**, respectively. The undirected edges connecting check nodes with variable nodes may correspond to the locations of the non-zero entries of parity check matrix **402**. In other words, parity check matrix **402** may be the adjacency matrix of Tanner graphs **403** and **404**. For example, the 1 at the (1,1) location and the 0 at the (1,2) location of parity check matrix **402** may indicate that there is an edge between check node S_1 and variable node V_1 , and that there is no edge between check node S_1 and variable node V_2 , respectively. Therefore, if there are d_v "1"s in a given column of parity check matrix **402**, then there are d_v edges emanating from the variable node corresponding to that column. Equivalently, the variable node corresponding to that column may have a degree of d_v . Similarly, if there are d_c "1"s in some given row of parity check matrix **402**, then there may be d_c edges emanating from the check node corresponding to that row. Equivalently, the check node corresponding to that row may have a degree of d_c .

The check nodes (e.g. check nodes **405**) of a Tanner graph may either be satisfied or unsatisfied, where a satisfied node has a binary value of 0 and an unsatisfied node has a binary value of 1. A check node may be satisfied (i.e., equal to 0), if the values of the variable nodes connected to the check node sum to an even number. In other words, the value of each check node may be equal to the sum modulo two of the value of the variable nodes to which it is connected. For example, check node S_2 of Tanner graphs **403** and **404** may be satisfied if the values of variable nodes V_2 , V_5 , and V_8 SUM to an even number. Furthermore, when a check node is unsatisfied, at least one of the variable nodes connected to it may be in error. Thus, the value of the check nodes (or equivalently, the value of the syndrome produced by parity check matrix **402**) may provide a parity check on each codeword received by a LDPC decoder (i.e., iterative decoder **116** of FIG. 1), thereby providing error correction capability to communication or data storage system **100** of FIG. 1.

Tanner graphs **403** and **404** may be used to illustrate an iterative two-step decoding algorithm known as message passing algorithm **406** employed by, for example, iterative decoder **116** of FIG. 1. The message passing algorithm may perform several rounds (or iterations) of message updates in accordance with the structure of the Tanner graph associated with the parity check matrix of the LDPC codes to be decoded.

In a layered decoder, one layer of message passing decoding (i.e. each iteration **412** of message passing algorithm **406**) may include processing several check nodes. For example, in processing the first layer, some of the check nodes **405** (for example, check nodes S_1 and S_2) may request that some of variable nodes **401**, to which they are connected, send their current messages to these check nodes. Check nodes S_1 and S_2 may then perform update **408** by carrying out computations based on the messages that they receive and a set of update rules, which will be discussed further below. Then, check nodes S_1 and S_2 may send their current messages to the variable nodes to which they are connected. The variable nodes connected to check nodes S_1 and S_2 (i.e. variable nodes V_1, V_4, V_7 and nodes V_2, V_5 and V_8) may then perform update **410** by carrying out computations based on the messages that they receive and a set of update rules, which will be discussed further below.

Then, for example, in processing the second layer, some of the check nodes **405** (for example, check nodes S_3 and S_4) may request that the variable nodes connected to these check

nodes send their current messages to these check nodes. Check nodes S_3 and S_4 may then perform update **408** by carrying out computations based on the messages that they receive and a set of update rules, which will be discussed further below. Then, check nodes S_3 and S_4 may send their current messages to the variable nodes to which they are connected. Variable nodes connected to check nodes S_3 and S_4 (i.e. nodes V_3, V_6, V_9 and nodes V_1, V_6 and V_8) may then perform update **410** by carrying out computations based on the messages that they receive and a set of update rules, which will be discussed further below. The same process may be repeated for check nodes S_5 and S_6 .

Iteration **412** may be repeated until either the codeword has been decoded or until a threshold number of iterations has been reached. The messages that are sent during each step of each iteration of message passing algorithm **406** may depend on the update rules and the scheduling of the update steps, which will be discussed further below. The messages may correspond to log-likelihood-ratio values.

FIG. 5A shows graphical illustration **510** of update rules for variable nodes in message passing algorithm **406** of FIG. 4 in accordance with some embodiments. For decoders operating in channels without memory, prior to the first iteration of message passing algorithm **406**, each of the variable nodes **401** of FIG. 4 may compute LLR message **512** based on information from received vector **114** in FIG. 1. For decoders operating in channels with memory, prior to the first iteration of message passing algorithm **406**, each of the variable nodes **401** of FIG. 4 may compute LLR message **512** based on information received from SISO channel detector **322** of FIG. 3B.

Each of variable nodes **401** of FIG. 4 may have d_v edges emanating from it in Tanner graphs **403** and **404** of FIG. 4. Each of these edges may connect a variable node to a check node in Tanner graphs **403** and **404** of FIG. 4. For each iteration of the message passing algorithm **406** of FIG. 4, each variable node may receive d_v messages **514** each from a different check node to which it is connected. Each of messages **514** sent from the check nodes to the variable nodes may be labeled as a R type message. For example, these messages are labeled R_1 through R_{d_v} in graphical illustration **510**.

In the layered iterative decoder, in the first layer, some number of check nodes may be processed and the corresponding neighboring variable nodes are updated. Then in the next layer, the next set of check nodes may be processed and the corresponding variable nodes may be updated. Each layer may be processed in this manner.

There may be several ways to perform (schedule) message update steps in the layered decoder. For example, using initial LLR messages **512**, and each of the R type messages **514**, each of the variable nodes **401** of FIG. 4 may compute Q type message **513** (also known as a bit-to-check message) based on the equation:

$$Q = LLR + \sum_{j=1}^{d_v-1} R_j.$$

This Q type message may be sent to the check nodes to which the variable node is connected. Similarly, message update steps may be performed to compute P type message **515** (also known as an a-posteriori probability (APP) message). Using initial LLR message **512** and each of the R type messages **514**, each of the variable nodes **401** of FIG. 4 may compute a P type message **515** based on the equation:

$$P = LLR + \sum_{j=1}^{d_v} R_j,$$

In addition, each of the variable nodes **401** of FIG. **4** may also compute an extrinsic (LLR_{EXT}) message based on the equations:

$$LLR_{APP}(v) = LLR + \sum_{j=1}^{d_v} R_j$$

and $LLR_{EXT}(v) = LLR_{APP}(v) - LLR$. The scheduling of update steps will be discussed further below.

FIG. **5B** shows graphical illustrations **520** of update rules for check nodes in message passing algorithm **406** of FIG. **4** in accordance with some embodiments. Each of the check nodes **405** of FIG. **4** may have d_c edges emanating from it in Tanner graphs **403** and **404** of FIG. **4**. Each of these edges may connect a check node to a variable node in Tanner graphs **403** and **404** of FIG. **4**. For each iteration of the message passing algorithm **406** of FIG. **4**, each check node may receive d_c messages **524** each from a different variable node to which it is connected. Messages sent from the variable nodes to the check nodes may be labeled as Q type messages. Depending on the scheduling of the update steps, either Q type messages may be stored in the iterative decoder's memory or P type messages may be stored in the iterative decoder's memory.

Each of the check nodes **405** of FIG. **4** may compute R type message **522**, using a min approximation. Using each of the Q type messages **524**, each of the check nodes **405** of FIG. **4** may compute R type messages **522** based on the equations

$$\tanh\left(\frac{R}{2}\right) = \prod_{k=1}^{d_c-1} \tanh\left(\frac{Q_k}{2}\right)$$

which may be approximated using min approximation

$$R \approx \min(Q_1, \dots, Q_{d_c-1}) \prod_{k=1}^{d_c-1} \text{sign}(Q_k).$$

The Q_k messages (i.e. a number k of Q type messages) may be read directly from the memory of the iterative decoder or may be reconstructed. The Q_k messages may be reconstructed from the P_k messages (i.e. a number k of P type messages) and the previous R type messages that may be read from the memory of the iterative decoder. These newly computed R messages may be sent to each of the variable nodes to which the check node is connected.

FIG. **6** shows an illustrative graph of regions of error at various signal-to-noise-ratios (SNRs) in accordance with some embodiments. As mentioned previously, the performance capability of LDPC codes, as described by a mapping of BER/SER to SNR, generally comprises two regions of operation: the waterfall region and the error floor region. FIG. **6** shows an exemplary LDPC performance curve **600** with waterfall region **602** and error floor region **604**. In error floor region **604**, the BER/SER of the LDPC code disadvantageously asymptotes to a lower limit. Because the normal

operating conditions for a communication/storage channel may be in error floor region **604**, lowering the error floor may improve the performance of the LDPC code in terms of BER/SER. Appropriately selecting the precision of messages sent during the use of message passing algorithm **406** of FIG. **4** may lower the error floor. Therefore, appropriately selecting the precision of messages sent during the use of message passing algorithm **406** of FIG. **4** may improve the performance of the LDPC code in terms of BER/SER.

FIG. **7** shows graphical illustration **710** of the scheduling of update steps of message passing algorithm **406** of FIG. **4** in accordance with some embodiments. In illustration **710**, variable node **716** is denoted by a circle. In illustration **710** check node **712** and check node **714** are denoted by squares.

For example, during one part of one iteration of message passing algorithm **406** of FIG. **4**, check node **712** may update and send R type message R_{new} (of precision P_R) to variable node **716**. Check node **712** may use the min approximation, as discussed above, to compute R_{new} . Variable node **716** has access to the previous Q type message (of precision P_Q) that it had sent to check node **712**, in the current iteration, prior to check node **712** updating. Variable node **716** also has access to the previous R type message, R_{old} (of precision P_R), sent to it by check node **714** in the previous iteration. After check node **712** has updated, in the current iteration, variable node **716** may compute $Q := Q + R_{new} - R_{old}$ and send this Q type message to check node **714**. In one of the subsequent iterations of message passing algorithm **406** of FIG. **4**, check node **714** may use this Q type message, the Q type messages received from other variable nodes to which it is connected, and the min approximation, discussed above, to compute a R type message R_{new} (of precision P_R) to be sent to variable node **716**. Check node **714** may compute R type messages for all other variable nodes to which it is connected, in a similar way.

Each variable node may also update its P type message. For example, after check node **712** has updated, in the current iteration, variable node **716** may compute the a-posteriori probability message $P := P - R_{old} + R_{new}$ (also discussed in FIG. **8**). This update may be performed as follows: Variable node **716** may have access to the previous R type message, R_{old} (of precision P_R), computed and sent to it by check node **714** in the previous update. Check node **712** may update and send R type message R_{new} (of precision P_R) to variable node **716**. Check node **712** may use the min approximation, as discussed above, to compute R_{new} from the Q type message reconstructed using $P - R_{old}$ (where R_{old} is the previous R type message received from variable node **716**). After check node **712** has updated, variable node **716** may compute $P := Q + R_{new}$ and store this P type message (see FIG. **8**). In one of the subsequent layers of iterative decoding, check node **714** then may use this P type message, the P type messages received from other variable nodes (to which it is connected), and the corresponding R_{old} messages, to reconstruct the Q type messages using $P - R_{old}$. Check node **714** may then use the min approximation, discussed above, to compute a R type message R_{new} (of precision P_R) to be sent to variable node **716**. Similarly, check node **714** may compute R type messages for all other variable nodes to which it is connected.

FIG. **8** shows a simplified block diagram of serial (layered) decoder processing unit **800** used in iterative decoder **116** of FIG. **1** in accordance with some embodiments. Processing unit **800** may be used to implement each layer of each iteration of the layered update steps in message passing algorithm **406** of FIG. **4**. Processing unit **800** may include memory **804** to store P type messages, cyclic shifter **810** which may be used to cyclically shift the bits of the P type messages, adder

812 and subtractor **806**, cyclic shifter **822** which may be used to cyclically shift the bits output from adder **812**, check node processing unit **818** (also known as check node unit (CNU) **818**), and memory **820** to store R type messages. The ECC decoder used by message passing algorithm **406** of FIG. **4** may include a plurality of check node units (CNUs), for example, one check node unit (CNU) per check node in the Tanner graph associated with the LDPC code being used. For example, if one layer of the ECC decoder includes S_c check nodes, then S_c such CNUs are needed. In some embodiments, processing unit **800** may be used to implement the process described in FIG. **7**. For example, processing unit **800** may be used to implement the operation given by the equation $P:=P+R_{new}-R_{old}$. A similar processing unit may be used to implement the operation $Q:=Q+R_{new}-R_{old}$.

The a-priori message in FIG. **8** refers to (LLR) messages produced from the output of the channel or the output of a SISO channel detector (e.g. SISO channel detector **322** of FIG. **3B**). In some embodiments, memory **804** may initially store the LLR messages derived from, for example, the output of channel **110** of FIG. **1**. In other embodiments, memory **804** may initially store the LLR messages derived from SISO channel detector, for example, the SISO extrinsic messages (LS_{ext} message in FIG. **10**). Each P type and/or Q type message corresponds to a particular variable node in the Tanner graph associated with the LDPC code being used. The LLR messages are read initially from memory **804**. The output of memory **804** may be input to cyclic shifter **810**, which may shift the bits contained in the output of memory **804** appropriately according to a quasi-cyclic LDPC parity check matrix (e.g. matrix **220** of FIG. **2B**) associated with the LDPC code being used in message passing algorithm **406** of FIG. **4**. Cyclic shifter **810** may then output the shifted bits to subtractor **806**.

Subtractor **806** may also have input R_{old} , which, as described in FIG. **7**, represents the R type message previously computed by the check node in the previous update. For each variable node connected to this the check node represented by CNU **818**, subtractor **806** may initially calculate and output $Q:=LLR$ upon the first iteration of message passing algorithm **406** of FIG. **4** and $Q:=P-R_{old}$ upon each subsequent iteration. The output of subtractor **806** may be input to check node processing unit **818** (CNU **818**). CNU **818** may then compute and output R type message R_{new} using as input the Q type messages from subtractor **816** and the min approximation, as discussed above and in FIG. **7**. CNU **818** may then output the computed R_{new} message as input to adder **812**. Adder **812** may also have as input the Q type messages from subtractor **816**. Adder **812** may then calculate and output the value of R_{new} added to the output of subtractor **806** into the input cyclic shifter **822**. Cyclic shifter **822** may shift the bits of its input appropriately according to the quasi-cyclic parity check matrix (e.g. matrix **220** of FIG. **2B**) being used in message passing algorithm **406** of FIG. **4** and output the result to the input of memory **804**.

One cause of catastrophic errors in layered iterative decoders with insufficient precision of P type and/or Q type messages may relate to a “swing” in R type messages. During an update of an R type message in layered iterative decoder (e.g. within processing unit **800**), the computed difference of R type messages, $(R_{new}-R_{old})$, also referred to as a “swing” in R type messages, may represent a significant portion of (or even exceed) the magnitude of a P type message (which may have already been truncated). Furthermore, the P type message and $(R_{new}-R_{old})$ may have opposite signs. For decoders with sufficient precision, however, the difference of R type messages, $(R_{new}-R_{old})$, may actually be a small portion of the magnitude

of the P type message. This may mean that in layered iterative decoders with insufficient precision for the P type message, the result of computing $P-R_{old}+R_{new}$ may be significantly different than the result of computing $P-R_{old}+R_{new}$ in layered iterative decoders that do not impose any limitation on the precision of intermediate messages. Similarly, in layered iterative decoders with insufficient precision for a Q type message, the result of $Q-R_{old}+R_{new}$ may be significantly different than the results of computing $Q-R_{old}+R_{new}$ in layered iterative decoders with larger or sufficient precisions for the Q type message.

In other words, a problem in layered iterative decoders with insufficient precision of P type and/or Q type messages is that some P type or Q type messages may become saturated. Furthermore this problem may be complicated by the event of having a large “swing” in the difference of R type messages, $(R_{new}-R_{old})$, while having opposite signs between the “swing” in the difference of R type messages and the P type (or Q type) message. Catastrophic errors may occur when this problem occurs on several nodes at substantially the same. Catastrophic errors may propagate through the iterative decoder. These errors may be eliminated via proper selection of the finite precisions of the P type or Q type messages, P_P or P_Q , or by a message “freezing” method, described below.

FIG. **9** shows a flowchart of a process for choosing the optimal precision of P type and/or Q type messages within iterative decoder **116** of FIG. **1** used by message passing algorithm **406** of FIG. **4** for decoding a codeword in channels without memory in accordance with some embodiments. Process **900** includes steps **902** and **910**. In certain embodiments, process **900** is designed to select or optimize the precision of the messages by iterative decoder **116**. For example, process **900** may select or optimize the precision of P type and/or Q type messages given that the precision of R type or LLR messages are already selected (or already optimized).

At step **902**, the precision of R type messages (P_R) may be selected or optimized. Furthermore, at step **902**, the precision of LLR messages (P_{LLR}) may be selected.

At step **910**, the precision of P type messages (P_P) may be set to a bit value. Specifically, the values of P_R , P_{LLR} , and the maximum column weight, cw , of the parity check matrix associated with the LDPC code may be used to determine the value of P_P . This may be done using equation $P_P=\text{ceil}(\log_2((cw \cdot 2^{P_R} + 2^{P_{LLR}})))$, which may be simplified to $P_P=P_R+\text{ceil}(\log_2(cw+1))$ if P_R is equal to P_{LLR} . The selected precisions may be used in every iteration of iterative decoder **116** of FIG. **1**. With this selection, the catastrophic errors may be substantially eliminated.

At step **910**, the precision of Q type messages (P_Q) may also be set. Specifically, the values of P_R , P_{LLR} , and the maximum column weight, cw , of the parity check matrix associated with the LDPC code may be used to determine the value of P_Q . This may be done using equation $P_Q=\text{ceil}(\log_2((cw-1) \cdot 2^{P_R} + 2^{P_{LLR}}))$, which may be simplified to $P_Q=P_R+\text{ceil}(\log_2(cw))$ if P_R is equal to P_{LLR} . With this selection, the catastrophic (propagation) errors may be substantially eliminated.

FIG. **10** shows a simplified block diagram of iterative decoder **1000** used for decoding a codeword in channels with memory and precisions of various messages passed within iterative decoder **1000** used by message passing algorithm **406** of FIG. **4** in accordance with some embodiments. Iterative decoder **1000** includes SISO channel detector **1004**, circuitry **1050**, and ECC decoder **1005**. In performing iterative decoding, iterative decoder **1000** may alternate between the use of SISO channel detector **1004**, and ECC decoder **1005**.

Similar to iterative decoder **320**, messages from an iteration of SISO channel detector **1004** may be passed to the ECC decoder **1005** for use in the next ECC decoding iteration, and vice versa. However, the precision of the messages sent from SISO channel detector **1004** may be quantized by circuitry **1050** prior to them being input to ECC decoder **1005**. Similarly, the precision of the messages sent from ECC decoder **1005** may be quantized prior to them being input to SISO channel detector **1004**.

The quantization of SISO a-priori information may be related to the implementation of SISO channel detector **1004**. The a-priori message may have a precision P_S bits. For example, this a-priori message may have the same precision as the R type messages in the iterative decoder for LDPC codes, i.e., $P_S=P_R$. SISO channel detector **1004** may produce the a-posteriori SISO message LS_{app} which may be the sum of a-priori information received from ECC decoder **1005** and new extrinsic information LS_{ext} derived by SISO channel detector **1004**. Although the information passed from SISO channel detector **1004** to ECC decoder **1005** may be a LS_{ext} message, in some embodiments it may be advantageous to pass a LS_{app} message instead. The LS_{app} message may be computed based on the equation

$$LS_{app} = LS_{ext} + \sum_{j=1}^{d_v} R_j.$$

Due to the way in which the LS_{app} message is computed, it may become important to confine the range of the LS_{ext} message to be within the range of the LS_{app} message and to set the range to a predetermined value. If this is not done, then as iterations of message passing algorithm **406** of FIG. **4** progress, the range of the LS_{ext} message may occupy increasingly large portion of the LS_{app} message range. Initially, the P type message in ECC decoder **1005** may take a quantized version of the value of LS_{app} . If, however, there is no quantization, the initial P type message in the ECC decoder may be set as $P=LS_{app}$.

The range of the LS_{ext} message may be allowed to occupy a very large portion of the range of the LS_{app} message. Then, given that there may be a saturation of P type messages that may take place during the update of P type messages within ECC decoder **1005** (i.e. $P=(P-R_{old})+R_{new}$), new information from ECC decoder may not be captured by the P type message. This, however, may result in the sub-optimal performance of SISO channel detector **1004**. To remedy the situation, SISO channel detector **1004** may confine the range of the LS_{ext} message to be within the range of the LS_{app} message and to a predetermined level using circuitry **1050**. This may be accomplished by reconstructing the LS_{ext} message from the LS_{app} message using the equation $LS_{ext}=LS_{app}-Le$, quantizing (clipping) the LS_{ext} message to the desired range, and then obtaining a new, quantized, value for the LS_{app} message using the equation $P=\text{quantized}(LS_{ext})+Le$. These operations may be implemented using the adder, subtractor, clippers, and delay unit in circuitry **1050**. This operation assures that information derived by SISO channel detector **1004**, as well as information derived by ECC decoder **1005** are properly represented by the P type messages.

FIG. **11** shows a flowchart of a process for choosing the optimal precision of P or Q type messages within the iterative decoder **116** of FIG. **1** used by message passing algorithm **406** for decoding a codeword in channels with memory in accordance with some embodiments. Process **1100** includes steps

1101, **1102**, and **1110**. In certain embodiments, process **1100** may be designed to select or optimize the precision of the messages computed or passed by iterative decoder **116** of FIG. **1**. For example, process **1100** may select or optimize the precision of P type messages and/or Q type messages by setting, selecting or optimizing the precision of R type messages, S type messages, and/or Le type messages.

At step **1101**, the precision of R type messages (P_R) may be selected or optimized. In this step, the precision of Le type messages (P_{Le}) may be computed using the equation $P_{Le}=P_R+\text{ceil}(\log_2(cw))$. In step **1102**, the precision of S type messages (P_S) may be selected or optimized such that $P_S \leq P_{Le}$.

At step **1110**, the precision of P type messages (P_P) may be set. Specifically, the values of P_R , P_S , and the maximum column weight, cw, of the parity check matrix associated with the LDPC code may be used to determine the value of P_P . This may be done using equation $P_P=\text{ceil}(\log_2(cw \cdot 2^{P_R} + 2^{P_S}))$, which may be simplified to $P_P=P_R \text{ceil}(\log_2(cw+1))$ if P_R is equal to P_S .

At step **1110**, the precision of Q type messages (P_Q) may also be set. Specifically, the values of P_R , P_S , and the maximum column weight, cw, of the parity check matrix associated with the LDPC code may be used to determine the value of P_Q . This may be done using equation $P_Q=\text{ceil}(\log_2((cw-1) \cdot 2^{P_R} + 2^{P_S}))$, which may be simplified to $P_Q=P_R+\text{ceil}(\log_2(cw))$ if P_R is equal to P_S . The selected precisions may be used in every iteration of iterative decoder **116** of FIG. **1**.

Setting the precision of messages in iterative decoder **116** of FIG. **1** to an appropriate value helps to avoid catastrophic errors in the decoding operation and may reduce the occurrence of near-codeword failures, thus reducing the error floor of the LDPC code's performance curve.

FIG. **12A** shows a flowchart of a process for "freezing" a P type message if it becomes saturated in accordance with some embodiments. Process **1200** involves steps **1201**, **1202**, **1203**, and **1204**. At the beginning of decoding, for each variable node, step **1201** may be executed. At step **1201**, freeze_flag (v) may be set to zero. Next, step **1202** may be executed. At step **1202**, process **1200** may wait for the value for the P type message to be updated (e.g. by the update steps in message passing algorithm **406** of FIG. **4** within processing unit **800** of FIG. **8**). Next, at step **1203**, it is determined if the value of the P type message is greater than 2^{P_P} or if the value of the P type message is less than -2^{P_P} . This step determines if the magnitude (absolute value) of the P type message is greater than the 2^{P_P} bit precision allotted to the P type messages (i.e. the P type message has been saturated/clipped). Next, at step **1204**, if the value of the P type message is greater than 2^{P_P} or if the value of the P type message is less than -2^{P_P} , the freeze_flag(v) may be set to one. Otherwise, step **1202** may be executed.

FIG. **12B** shows a flowchart of a process for "freezing" a Q type message, if it becomes saturated in accordance with some embodiments. Process **1210** involves steps **1211**, **1212**, **1213**, and **1214**. At the beginning of decoding, for each variable node, step **1211** may be executed. At step **1211**, freeze_flag(v) may be set to zero. Next, step **1212** may be executed. At step **1212**, process **1210** may wait for the value for the Q type message to be updated (e.g. by the update steps in message passing algorithm **406** of FIG. **4** within processing unit **800** of FIG. **8**). Next, at step **1213**, it is determined if the value of the Q type message is greater than 2^{P_Q} or if the value of the Q type message is less than -2^{P_Q} . This step determines if the magnitude (absolute value) of the Q type message is greater than the 2^{P_Q} bit precision allotted to the Q type messages (i.e. the Q type message has been saturated/clipped). Next, at step **1214**, if the value of the Q type message is

17

greater than 2^{P_Q} or if the value of the Q type message is less than -2^{P_Q} , the freeze_flag(v) may be set to one. Otherwise, step 1212 may be executed.

FIG. 12C shows a simplified block diagram of serial (layered) decoder processing unit 1220 used in iterative decoder 116 of FIG. 1 with additional “message freezing” hardware in accordance with some embodiments. Processing unit 1220 may be used to implement each layer of each iteration of a check node unit (CNU) update steps in the layered message passing algorithm 406 of FIG. 4. As with processing unit 800 of FIG. 8, processing unit 1220 may include memory 1254 to store P type messages, cyclic shifter 1260 which may be used to cyclically shift the bits of the P type messages, adder 1262 and subtractor 1256, cyclic shifter 1272 which may be used to cyclically shift the bits output from adder 1262, check node processing unit 1268 (CNU 1268), and memory 1270 to store R type messages. These elements may be substantially similar to memory 804 of FIG. 8, cyclic shifter 810 of FIG. 8, adder 812 of FIG. 8 and subtractor 806 of FIG. 8, cyclic shifter 822 of FIG. 8, check node processing unit 818 of FIG. 8 (CNU 818 of FIG. 8), and memory 820 of FIG. 8. However, processing unit 1220 may also include circuit block 1221, selector 1222, circuit block 1223, and selector 1224. This additional hardware may allow for the “freezing” of a P type or Q type message, if either becomes saturated. This “message freezing approach” may be used for channels with or without memory.

Circuit block 1221 may include hardware to implement process 1200 of FIG. 12A. Selector 1222 may have as input, the output of free_flag(v) from circuit block 1221 for each variable node. Selector 1222 may also have as input the output of cyclic shifter 1272 and the value $\pm 2^{P_P}$. If, free_flag(v)=1 in circuit block 1221, then selector 1222 may select the value $\pm 2^{P_P}$ to output to memory 1254 for the current variable node and for the current iteration of message passing algorithm 406 of FIG. 4 as well as for each subsequent iteration. Therefore, if free_flag(v)=1 for a particular variable node, the decoded value (i.e. the hard decision) on this node may be frozen and no updates may be performed on the P type messages for this variable node. If, free_flag(v)=0 in circuit block 1221, then selector 1222 may output the output of cyclic shifter 1272 to memory 1222 for the current iteration. The sign of $\pm 2^{P_P}$ output to memory 1254 by selector 1222 may be the same as the sign of the current value of the P type message.

Circuit block 1223 may include hardware to implement process 1210 of FIG. 12B. Selector 1224 may have as input, the output of free_flag(v) from circuit block 1223 for each variable node. Selector 1222 may also have as input the output of subtractor 1256 and the value $\pm 2^{P_Q}$. If, free_flag(v)=1 in circuit block 1223, then selector 1224 may select the value $\pm 2^{P_Q}$ to output to CNU array 1268 for the current variable node and for the current iteration of message passing algorithm 406 of FIG. 4 as well as for each subsequent iteration. Therefore, if free_flag(v)=1 for a particular variable node, the decoded value (i.e. the hard decision) on this node may be “frozen” and no updates may be performed on the Q type messages for this variable node. If, free_flag(v)=0 in circuit block 1223, then selector 1224 may output the output of subtractor 1256 to CNU array 1268 for the current iteration. The sign of $\pm 2^{P_Q}$ output to CNU array 1268 by selector 1224 may be the same as the sign of the current value of the P type message.

The ability to “freeze” P type or Q type messages may be useful in situations when the precisions of these messages are not set sufficiently high. For example, the ability to “freeze” the value of a P type message may be useful if the precision of the P type message is chosen to be $P_P < \text{ceil}(\log_2(\text{cw} \cdot 2^{P_R} +$

18

$2^{P_{LLR}})$. Otherwise, if $P_P \geq (\log_2(\text{cw} \cdot 2^{P_R} + 2^{P_{LLR}}))$, then the P type messages may have sufficient precision and the clipping (saturation) of the P type messages may not occur. Similarly, the ability to “freeze” the value of a Q type message may be useful if the precision of the Q type message is chosen to be $P_Q < \text{ceil}(\log_2(\text{cw} \cdot 2^{P_R} + 2^{P_{LLR}}))$. Otherwise, if $P_Q \geq (\log_2(\text{cw} \cdot 2^{P_R} + 2^{P_{LLR}}))$, then the Q type messages may have sufficient precision and the clipping (saturation) of Q type messages may not occur.

What is claimed is:

1. A system comprising:

memory circuitry configured to store check node messages and variable node messages; and

processing circuitry configured to:

update a variable node message of stored variable node messages; and

determine if the variable node message is saturated based on a precision of the variable node message.

2. The system of claim 1, wherein the processing circuitry is further configured to update the variable node message by processing the variable node message based on the check node messages.

3. The system of claim 1, wherein the processing circuitry is further configured to determine if the variable node message is saturated based on determining if the variable node message is greater than 2 raised to a precision of the variable node message or if the variable node message is less than the negative of 2 raised to a precision of the variable node message.

4. The system of claim 1, wherein the processing circuitry is further configured to at least determine if the variable node message is saturated based on determining if $P > 2^{P_P}$ or if $P < -2^{P_P}$, wherein P denotes a magnitude of a P type message and 2^{P_P} denotes bit precision allotted to the P type message.

5. The system of claim 1, wherein the processing circuitry is further configured to at least determine if the variable node message is saturated based on determining if $Q > 2^{P_Q}$ or if $Q < -2^{P_Q}$, wherein Q denotes a magnitude of a Q type message and 2^{P_Q} denotes bit precision allotted to the Q type message.

6. The system of claim 1, further comprising a plurality of selectors wherein if the variable node message is saturated:

the processing circuitry is configured to generate an indication that the variable node message is saturated, and the selectors are configured to stop future updating of the variable node message.

7. The system of claim 6, wherein each selector of the plurality of selectors is further configured to set the variable node message to a maximum possible value for the variable node message.

8. The system of claim 6, wherein each selector of the plurality of selectors is further configured to set the variable node message to a minimum possible value for the variable node message.

9. The system of claim 1, wherein the variable node message of the stored variable node messages is used to decode information within one of a wireless communication medium, an electrical storage medium, and a magnetic storage medium.

10. A method comprising:

storing check node messages and variable node messages using memory circuitry;

updating a variable node message of stored variable node messages based on stored check node messages; and

determining if the variable node message is saturated based on a precision of the variable node message.

19

11. The method of claim 10, further comprising updating the variable node message by processing the variable node message based on the check node messages.

12. The method of claim 10, further comprising determining if the variable node message is saturated based on determining if the variable node message is greater than 2 raised to a precision of the variable node message or if the variable node message is less than the negative of 2 raised to a precision of the variable node message.

13. The method of claim 10, further comprising determining if the variable node message is saturated based on determining if $P > 2^{P_p}$ or if $P < -2^{P_p} - 2^{P_p}$, wherein P denotes a magnitude of a P type message and 2^{P_p} denotes bit precision allotted to the P type message.

14. The method of claim 10, further comprising determining if the variable node message is saturated based on determining if $Q > 2^{P_q}$ or if $Q < -2^{P_q}$, wherein Q denotes a magnitude of a Q type message and 2^{P_q} denotes bit precision allotted to the Q type message.

20

15. The method of claim 10, further comprising if the variable node message is saturated:

- generating an indication that the variable node message is saturated; and
- stopping future updating of the variable node message.

16. The method of claim 15, further comprising setting the variable node message to a maximum possible value for the variable node message.

17. The method of claim 15, further comprising setting the variable node message to a minimum possible value for the variable node message.

18. The method of claim 15, wherein the variable node message of the stored variable node messages is used to decode information within one of a wireless communication medium, an electrical storage medium, and a magnetic storage medium.

* * * * *