



US009314588B2

(12) **United States Patent**
Groves et al.

(10) **Patent No.:** **US 9,314,588 B2**
(45) **Date of Patent:** **Apr. 19, 2016**

(54) **SYSTEMS AND METHODS FOR VARIABLE INJECTION FLOW**

USPC 606/20, 21, 22, 23
See application file for complete search history.

(75) Inventors: **Regina E. Groves**, Dellwood, MN (US);
Jean-Pierre Lalonde, Candiac (CA);
Timothy G. Laske, Shoreview, MN (US);
Claudia Lueckge, L'Île-Bizard (CA);
Dan Wittenberger, L'Île-Bizard (CA);
Ramin Sabbaghe-Kermani, Laval (CA);
Mahmoud Kabir Seraj, Apex, NC (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,903,871 A 9/1975 Chisum et al. 128/2 T
3,938,514 A 2/1976 Boucher 128/232

(Continued)

FOREIGN PATENT DOCUMENTS

DE 4331198 A1 3/1994
EP 0455478 A1 11/1991

(Continued)

OTHER PUBLICATIONS

EPO, PCT/US2012/060761, Feb. 1, 2013 Invitation to Pay Additional Fees and Partial International Search Report, pp. 1-8.

(Continued)

(73) Assignee: **Medtronic CryoCath LP**, Toronto, Ontario (CA)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 688 days.

(21) Appl. No.: **13/300,931**

(22) Filed: **Nov. 21, 2011**

(65) **Prior Publication Data**

US 2013/0110099 A1 May 2, 2013

Related U.S. Application Data

(60) Provisional application No. 61/552,527, filed on Oct. 28, 2011.

(51) **Int. Cl.**

A61B 18/02 (2006.01)
A61M 25/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61M 25/007** (2013.01); **A61B 18/02** (2013.01); **A61B 18/0218** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC A61B 18/02; A61B 18/0262; A61B 18/0212; A61M 25/007; A61M 25/0029; A61M 39/28

Primary Examiner — Theodore Stigell


Assistant Examiner — Michael Carey

(74) *Attorney, Agent, or Firm* — Christopher & Weisberg, P.A.

(57) **ABSTRACT**

Systems and methods for controllably variable fluid flow are disclosed that provide the ability to modify the effective cross-sectional area of the fluid delivery conduit available for fluid flow. Accordingly, selective control of these configurations allows fluid flow to be regulated as desired while the fluid delivery pressure remains the same. Additional configurations provided herein allow for the selective manipulation of a footprint or therapeutic pattern achievable with the medical device during a single procedure, negating the need for the removal and insertion of multiple devices to achieve the same variations in treatment geometry or characteristics.

16 Claims, 10 Drawing Sheets



(51) **Int. Cl.**
A61M 39/28 (2006.01)
A61M 39/22 (2006.01)
A61M 25/01 (2006.01)
A61B 18/00 (2006.01)

(52) **U.S. Cl.**
 CPC *A61M 25/0029* (2013.01); *A61M 39/22* (2013.01); *A61M 39/28* (2013.01); *A61B 2018/0022* (2013.01); *A61B 2018/00202* (2013.01); *A61B 2018/0212* (2013.01); *A61B 2018/0262* (2013.01); *A61B 2018/0268* (2013.01); *A61M 2025/0025* (2013.01); *A61M 2025/0079* (2013.01); *A61M 2025/0175* (2013.01); *Y10T 137/0318* (2015.04)

(56) **References Cited**
 U.S. PATENT DOCUMENTS

4,029,099	A	6/1977	Fifield	128/295
4,176,662	A	12/1979	Frazer	128/6
4,202,336	A	5/1980	van Gerven	
4,375,220	A	3/1983	Matvias	128/804
4,411,656	A	10/1983	Cornett, III	604/212
4,509,370	A	4/1985	Hirschfeld	73/705
4,620,769	A	11/1986	Tsuno	350/96.26
4,660,571	A	4/1987	Hess et al.	128/784
4,664,120	A	5/1987	Hess	128/642
4,686,996	A	8/1987	Ulbrich	128/642
4,690,155	A	9/1987	Hess	128/786
4,699,147	A	10/1987	Chilson et al.	128/642
4,704,104	A	11/1987	Christensen	604/205
4,709,698	A	12/1987	Johnston et al.	128/303.12
4,725,267	A	2/1988	Vaillancourt	604/192
4,754,752	A	7/1988	Ginsburg et al.	128/303.12
4,776,349	A	10/1988	Nashef et al.	128/786
4,787,882	A	11/1988	Claren	604/4
4,813,425	A	3/1989	Malis	128/642
4,823,790	A	4/1989	Alperovich et al.	
4,850,351	A	7/1989	Herman et al.	
4,945,912	A	8/1990	Langberg	128/642
4,946,440	A	8/1990	Hall	604/95
4,979,948	A	12/1990	Geddes et al.	606/33
4,998,933	A	3/1991	Eggers et al.	606/41
5,007,437	A	4/1991	Sterzer	428/786
5,010,894	A	4/1991	Edhag	128/785
5,015,240	A	5/1991	Soproni et al.	604/192
5,078,713	A	1/1992	Varney	606/23
5,100,388	A	3/1992	Behl et al.	604/113
5,139,496	A	8/1992	Hed	606/23
5,147,355	A	9/1992	Friedman et al.	606/23
5,168,880	A	12/1992	Sogawa et al.	
5,205,298	A	4/1993	Hurst	128/844
5,224,943	A	7/1993	Goddard	606/20
5,228,442	A	7/1993	Imran	128/642
5,231,995	A	8/1993	Desai	128/784
5,281,213	A	1/1994	Milder et al.	606/15
5,281,215	A	1/1994	Milder	606/20
5,293,869	A	3/1994	Edwards et al.	128/642
5,314,408	A	5/1994	Salmon et al.	604/22
5,327,881	A	7/1994	Greene	128/11
5,334,181	A	8/1994	Rubinsky et al.	606/22
5,342,295	A	8/1994	Imran	604/43
5,363,882	A	11/1994	Chikama	138/118
5,364,353	A	11/1994	Corfitsen et al.	604/95
5,380,307	A *	1/1995	Chee et al.	604/264
5,403,309	A	4/1995	Coleman et al.	606/20
5,409,469	A	4/1995	Schaerf	604/282
5,423,807	A	6/1995	Milder	606/20
5,452,582	A	9/1995	Longsworth	62/51.2
5,466,222	A	11/1995	Ressemann et al.	604/96
5,487,385	A	1/1996	Avitall	128/642
5,520,682	A	5/1996	Baust et al.	606/24
5,545,200	A	8/1996	West et al.	607/122
5,569,161	A	10/1996	Ebling et al.	600/121
5,575,773	A	11/1996	Song et al.	604/110
5,624,392	A	4/1997	Saab	604/43
5,669,870	A	9/1997	Elist	600/40
5,766,192	A	6/1998	Zacca	
5,769,702	A	6/1998	Hanson	454/63
5,792,105	A	8/1998	Lin et al.	604/96
5,792,118	A	8/1998	Kurth et al.	
5,797,879	A	8/1998	DeCampli	
5,800,482	A	9/1998	Pomeranz et al.	607/101
5,810,802	A	9/1998	Panescu et al.	606/31
5,876,324	A	3/1999	Trouchine	600/38
5,957,963	A	9/1999	Dobak, III	607/104
6,001,117	A	12/1999	Huxel et al.	606/191
6,004,269	A	12/1999	Crowley et al.	
6,033,426	A	3/2000	Kaji	606/213
6,096,068	A	8/2000	Dobak, III et al.	607/105
6,106,518	A	8/2000	Wittenberger et al.	606/23
6,149,677	A	11/2000	Dobak, III	607/106
6,162,171	A	12/2000	Ng et al.	600/141
6,190,348	B1	2/2001	Tiemann et al.	604/15
6,224,624	B1	5/2001	Lasheras et al.	607/105
6,235,019	B1	5/2001	Lehmann et al.	606/22
6,238,371	B1	5/2001	Himbert et al.	604/187
6,238,428	B1	5/2001	Werneth et al.	607/105
6,245,095	B1	6/2001	Dobak, III et al.	607/105
6,248,089	B1	6/2001	Porat	604/17
6,248,096	B1	6/2001	Dwork et al.	604/349
6,251,130	B1	6/2001	Dobak, III et al.	607/105
6,254,626	B1	7/2001	Dobak, III et al.	607/105
6,270,482	B1	8/2001	Rosoff et al.	604/200
6,270,488	B1	8/2001	Johnson et al.	604/403
6,283,294	B1	9/2001	Thorball et al.	206/438
6,312,452	B1	11/2001	Dobak, III et al.	607/105
6,315,761	B1	11/2001	Shcherbina et al.	604/216
6,319,235	B1	11/2001	Yoshino	604/216
6,319,248	B1	11/2001	Nahon	606/22
7,041,080	B2	5/2006	Dion	
7,282,041	B2 *	10/2007	Igarashi	A61M 25/003 604/43
2001/0001830	A1	5/2001	Dobak, III et al.	607/105
2001/0001831	A1	5/2001	Dobak, III et al.	607/105
2001/0002442	A1	5/2001	Dobak, III et al.	607/105
2001/0011184	A1	8/2001	Dobak, III et al.	607/105
2001/0011185	A1	8/2001	Dobak, III et al.	607/105
2001/0016763	A1	8/2001	Lasheras et al.	607/105
2001/0021865	A1	9/2001	Dobak, III et al.	607/105
2001/0021866	A1	9/2001	Dobak, III et al.	607/105
2001/0029394	A1	10/2001	Dobak, III et al.	607/105
2001/0047138	A1	11/2001	Kokate et al.	
2002/0062122	A1 *	5/2002	Lehmann	A61B 18/02 606/23
2002/0193751	A1	12/2002	Theeuwes et al.	
2005/0027246	A1	2/2005	Dion	
2009/0112156	A1 *	4/2009	Rush	A61M 5/14216 604/67
2009/0234345	A1 *	9/2009	Hon	A61B 18/02 606/21
2011/0184398	A1	7/2011	Desrochers	

FOREIGN PATENT DOCUMENTS

EP	0810003	A2	12/1997
GB	002163655	A	3/1986
JP	402095364	A	4/1990
JP	405293077	A	11/1993
WO	9407549	A1	4/1994
WO	9817187	A	4/1998
WO	2004009171	A1	1/2004

OTHER PUBLICATIONS

EPO, PCT/US2012/060761, Apr. 10, 2013 International Search Report, pp. 1-7.
 EPO, PCT/US2012/060761, Apr. 10, 2013 Written Opinion of the International Searching Authority, pp. 1-12.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5








FIG. 6






FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22

1

SYSTEMS AND METHODS FOR VARIABLE INJECTION FLOW

CROSS-REFERENCE TO RELATED APPLICATION

This application is related to and claims priority to U.S. Provisional Application Ser. No. 61/552,527, filed Oct. 28, 2011, entitled SYSTEMS AND METHODS FOR VARIABLE INJECTION FLOW, the entirety of which is incorporated herein by reference.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

n/a

FIELD OF THE INVENTION

The present invention relates to systems and methods of use thereof for controlled fluid delivery in medical devices to provide safe and effective treatment.

BACKGROUND OF THE INVENTION

Minimally invasive devices, such as catheters, are often employed for medical procedures, including those involving mapping, ablation, dilation, and the like. For example, a thermal diagnostic or treatment procedure may involve permanently and/or temporarily exchanging thermal energy with a targeted tissue region, such as creating a series of inter-connecting or otherwise substantially continuous lesions in order to electrically isolate tissue believed to be the source of an arrhythmia. An example of a thermal mechanism for diagnosis and treatment is a cryogenic device that uses the energy transfer derived from thermodynamic changes occurring in the flow of a cryogen therethrough to create a net transfer of heat flow from the target tissue to the device. The quality and magnitude of heat transfer is regulated in large part by the device configuration and control of the cryogen flow regime within the device.

Structurally, cooling can be achieved through injection of high pressure refrigerant through an orifice. Upon injection from the orifice, a refrigerant may undergo two primary thermodynamic changes: (i) expanding to low pressure and temperature through positive Joule-Thomson throttling, and (ii) undergoing a phase change from liquid to vapor, thereby absorbing heat of vaporization. The resultant flow of low temperature refrigerant through the device acts to absorb heat from the target tissue and thereby cool the tissue to the desired temperature.

The efficacy of a thermal exchange procedure may be substantially affected by the fluid flow through the device as well as the thermal conductivity between a device and the tissue site. To provide shorter treatment durations and increased efficacy for the particular treatment provided, it is desirable to optimize the heat transfer between the specific tissue to be treated and the cryogenic element or device. Such optimization may include providing accurate and precise fluid delivery through a selected device to achieve the desired thermal affect in the physiological location being treated. Such physiological locations often include numerous environmental factors that can constantly change, resulting in fluctuating thermal conditions arising between the tissue and the device. For example, blood or other body fluids passing through the vicinity of the thermal device can reduce the quality of thermal exchange with the targeted tissue, which

2

can then necessitate additional "cooling power" or refrigerant flow in the case of cryogenic treatments in order to complete the desired treatment.

Accordingly, it is desirable to provide systems and methods of use thereof that provide accurate and precise control over fluid delivery to and through such devices in order to optimize the efficacy of the device in a physiological environment.

SUMMARY OF THE INVENTION

The present invention advantageously provides systems and methods of use thereof that provide accurate and precise control over fluid delivery to and through such devices in order to optimize the efficacy of the device in a physiological environment. In particular, a medical device is provided, including a catheter body defining a distal portion; a fluid delivery conduit defining an outlet in the distal portion of the catheter body, an elongate member movably disposed within at least a portion of the fluid delivery conduit to selectively obstruct a portion of the fluid delivery conduit to modulate fluid flow through the outlet. The medical device may define a fluid exhaust lumen within the catheter body, the fluid delivery conduit may define a tapered diameter, and/or the elongate member may be longitudinally movable with respect to the tapered diameter. The elongate member may include a plug movably positionable about the outlet, where the plug may include a tapered cross-section and/or be substantially spherical. The elongate member may be constructed from a shape memory material that transitions in response to a thermal and/or electrical load. The fluid delivery conduit may define a plurality of outlets in the distal portion, and the elongate member may be movable to selectively obstruct the plurality of outlets. The medical device may include a cryogenic fluid source in fluid communication with at least one of the fluid delivery conduit or elongate member.

A method of regulating fluid flow through a catheter is provided, including delivering a fluid to a fluid delivery conduit disposed within a portion of the catheter; and moving a rod within a portion of the fluid delivery conduit to at least partially obstruct a portion of the fluid delivery conduit to regulate fluid flowing therethrough. The fluid delivery conduit may define a tapered section, and moving the rod may include moving the rod with respect to the tapered section.

A medical device is provided, including a catheter body defining a distal portion; a fluid delivery conduit defining an outlet in the distal portion of the catheter body, and a deformation element within the catheter body, the deformation element controllably movable to deform a portion of the fluid delivery conduit. The deformation element may be movable substantially perpendicularly to the fluid delivery conduit to depress a portion of the fluid delivery conduit and/or may be rotatable about the fluid delivery conduit to depress a portion of the fluid delivery conduit.

A method of regulating fluid flow through a catheter is disclosed, including delivering a fluid to a first conduit disposed within a portion of the catheter; and mechanically deforming a portion of the first conduit to controllably regulate fluid flowing therethrough.

A method of controlling fluid delivery in a medical device is provided, including movably positioning a fluid delivery conduit within a delivery manifold in the medical device, the fluid delivery conduit defining a first plurality of openings and the delivery manifold defining a second plurality of openings; introducing a fluid into the fluid delivery conduit; moving the fluid delivery conduit to a first position where the first plurality of openings is substantially aligned with the second plu-

3

rality of openings to direct fluid through the first and second plurality of openings; and moving the fluid delivery conduit to a second position where the second plurality of openings are substantially obstructed by the fluid delivery conduit, and at least one of the plurality of first openings is positioned outside the manifold such that fluid is directed through the at least one of the plurality of first openings. The second plurality of openings may be asymmetrically disposed about a longitudinal axis of the manifold, the fluid may include a cryogenic fluid, and/or the medical device may include a thermally-transmissive region proximate the delivery manifold, such as a balloon or an electrode.

A medical device is disclosed, including an elongate body defining a distal portion; and a unitary distal insert coupled to the distal portion, the distal insert defining: a first lumen extending therethrough, a second lumen coaxial with the first lumen, and a plurality of openings in fluid communication with the second lumen. The unitary distal insert may define a collar and the medical device may include one or more steering elements coupled to the collar. The medical device may include a thermally-transmissive region substantially enclosing the distal insert and/or a rod movably positionable with a portion of the first lumen.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the present invention, and the attendant advantages and features thereof, will be more readily understood by reference to the following detailed description when considered in conjunction with the accompanying drawings wherein:

FIG. 1 is an illustration of an example of a medical device and control unit of a medical system constructed in accordance with the principles of the present disclosure;

FIG. 2 is a cross-sectional view of a distal portion of the medical device of FIG. 1;

FIG. 3 is a perspective view of the distal portion shown in FIGS. 1-2;

FIG. 4 is another example of a distal portion of the medical device shown in FIG. 1;

FIG. 5 is another cross-sectional view of a distal portion of the medical device of FIG. 1 or 4;

FIG. 6 is an illustration of an example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 7 is an illustration of another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 8 is an illustration of yet another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 9 is an illustration of still another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 10 is an illustration of another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 11 is an illustration of yet another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 12 is an illustration of still another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 13 is an illustration of another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

4

FIG. 14 is an illustration of still another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 15 is an illustration of yet another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 16 is an illustration of another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 17 is an illustration of still another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 18 is an illustration of yet another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 19 is an illustration of another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 20 is an illustration of another example of a fluid delivery tube configuration for a medical device in accordance with the principles of the present disclosure;

FIG. 21 is an illustration of another example of a medical device in accordance with the principles of the present disclosure; and

FIG. 22 is an illustration of another example of a medical device in accordance with the principles of the present disclosure.

DETAILED DESCRIPTION OF THE INVENTION

The present invention advantageously provides systems and methods of use thereof that provide accurate and precise control over fluid delivery to and through such devices in order to optimize the efficacy of the device in a physiological environment. Referring now to the drawing figures in which like reference designations refer to like elements, an embodiment of a medical system constructed in accordance with principles of the present invention is shown in FIG. 1 and generally designated as "10." The system 10 generally includes a medical device 12 that may be coupled to a control unit 14. The medical device 12 may generally include one or more treatment regions for energetic or other therapeutic interaction between the medical device 12 and a treatment site. The treatment region(s) may deliver, for example, cryogenic therapy, radiofrequency energy, or other energetic transfer with a tissue area in proximity to the treatment region (s), including cardiac tissue.

Continuing to refer to FIG. 1, the medical device 12 may include an elongate body 16 passable through a patient's vasculature and/or proximate to a tissue region for diagnosis or treatment, such as a catheter, sheath, or intravascular introducer. The elongate body 16 may define a proximal portion 18 and a distal portion 20, and may further include one or more lumens disposed within the elongate body 16 thereby providing mechanical, electrical, and/or fluid communication between the proximal portion of the elongate body 16 and the distal portion of the elongate body 16, as discussed in more detail below.

The medical device 12 may further include a fluid delivery conduit 22 traversing at least a portion of the elongate body 16 and distal portion 20. The delivery conduit 22 may be coupled to or otherwise extend from the proximal portion 18 of the elongate body 16. The fluid delivery conduit 22 may be flexible, constructed from a shape memory material (such as Nitinol), and/or include other controllably deformable materials that allow the fluid delivery conduit 22 to be manipulated for selective fluid flow control as described herein. The fluid

5

delivery conduit **22** may define a lumen therein for the passage or delivery of a fluid from the proximal portion of the elongate body **16** and/or the control unit **14** to the distal portion **20** and/or treatment region of the medical device **12**. The fluid delivery conduit **22** may further include one or more apertures or openings therein providing dispersion or directed ejection of fluid from the lumen to an environment exterior to the fluid delivery conduit **22**.

The elongate body **16** may also define or otherwise include an exhaust lumen **24** in fluid communication with the distal portion **20**, proximal portion **18**, and/or control unit **14** to facilitate circulation or removal of fluid within the medical device **12**. A guide wire lumen may also be disposed or otherwise included in the elongate body **16**.

Now referring to FIGS. 1-3, the medical device **12** may include a distal insert **26** coupled to the elongate body **16**, where the distal insert **26** provides multiple anchoring or connection points for steering mechanisms, electrical signal wires, and/or fluid dispersion and removal features. For example, the distal insert **26** may include a unitary body having a proximal segment **28** engageable with the elongate body **16**. The proximal segment **28** may define a plurality of ridges or angled teeth **30** aiding in securing or anchoring the distal insert **26** within a portion of the elongate body **16**. The distal insert **26** may also define a collar **32** adjacent the proximal segment **28**, the collar **32** having a larger diameter than the proximal segment **28** such that the collar **32** can be sealed to the elongate body **16**. As shown in FIG. 2, the collar **32** may further define one or more anchoring points **34** for a temperature sensor, steering wire, and/or electrical signal wire. The distal insert **26** may further include or define a distal segment **36** on an opposite side of the collar **32**, where the distal segment **26** defines a fluid dispersion channel **38** and a fluid exhaust channel **40** in fluid communication with the fluid delivery conduit **22** and exhaust lumen **24**, respectively. For example, the fluid dispersion channel **38** may extend longitudinally through the distal segment **36** and open at an aperture **42** at a distal direction at a tip or distal-most face of the insert **26**. The fluid exhaust channel **40** may include one or more openings **44** on an exterior surface and/or transverse to the fluid dispersion channel **38** located proximal to the aperture **42** and/or in proximity to the collar **32**.

The medical device **12** may further include a thermally-transmissive region **46** at the distal portion **20** that provides for energy exchange between the medical device **10** and targeted tissue region. The thermally-transmissive region **46** may include, for example, a thermally- and/or electrically-conductive shell (as shown in FIGS. 1 and 3) that substantially surrounds the distal segment **36** of the distal insert **26**. The shell may be coupled to the collar **32** and/or elongate body **16** to provide a fluid-tight seal. The shell may also be in communication with the control unit **14** to send and/or receive diagnostic or therapeutic signals or energy to and from a targeted tissue region. The communication may be established or facilitated by one or more wires anchored to the collar **32** of the distal insert **26**, for example.

Referring now to FIG. 4, the thermally-transmissive region **46** may include an expandable element or balloon at the distal portion **20** of the elongate body **16**. The expandable element may be coupled to a portion of the elongate body **16** and/or the distal insert **26**. The expandable element may further be coupled to a distal tip **48** that may be attached to one or more steering elements (not shown) to allow manipulation of the expandable element. The distal tip **48** may also define a guide wire lumen therethrough. The expandable element defines an interior chamber or region that contains coolant or fluid dispersed from the fluid delivery conduit **22**, and may be in fluid

6

communication with the exhaust lumen **24** for the removal of dispersed coolant from the interior of the expandable element. The expandable element may further include one or more material layers providing for puncture resistance, radio-opacity, or the like.

Referring now to FIGS. 5-19, a number of exemplary configurations for accurately and precisely manipulating fluid flow through the fluid delivery conduit of the medical device are shown. These configurations may be used, for example, in proximity to a distal portion **20** and/or a thermally-transmissive region **46** of the medical device **12** to achieve desirable therapeutic or diagnostic effects, which may include varying degrees of thermal interaction with an adjacent tissue region. For example, as shown in FIGS. 5-7, the medical device **12** may include a secondary elongate body or rod **50** positioned within a portion of the fluid delivery conduit **22** and/or the fluid dispersion channel **38** of the distal insert **26**. The rod **50** may be selectively and controllably movable to obstruct or restrict a portion of the diameter of the fluid delivery conduit **22** or fluid dispersion channel **38** to thus modulate fluid flowing therethrough. Alternatively, the rod **50** may be constructed from a shape memory alloy that predictably lengthens and shortens in response to a designated thermal or electrical load. Accordingly, the elongate body **50** may be controllably manipulated into a desired length or width within the fluid delivery conduit **22** through the application or removal of a thermal or electrical load. The thermal or electrical load may be controllable and/or otherwise provided at a proximal portion of the medical device **12** and/or from the control unit **14**.

As shown in FIGS. 6-7, the fluid delivery conduit **22** or fluid dispersion channel **38** may define a tapered diameter or stepped decrease in diameter in proximity to where the rod **50** is positioned or slidably movable to further facilitate changes in fluid flow rate and/or volume due to movement of the rod **50** within the lumen.

Now referring to FIGS. 8-10, a plug **52** may be movably disposed within a portion of the fluid delivery conduit **22** to selectively obstruct a portion of an outlet **54** of the fluid delivery conduit. The plug **52** may include a number of geometric variations to achieve the desired modulation of fluid flow through the delivery conduit **22**. For example, as shown in FIG. 8, the plug **52** may have a substantially rectangular shape oriented transversely to a longitudinal axis of the fluid delivery conduit **22**. The plug **52** may also have a trapezoidal or angled shape to provide progressively increased or decreased fluid flow depending on the position of the plug **52**, as shown in FIG. 9. FIG. 10 illustrates a variation of the plug **52** having a substantially rounded or spherical shape, as well as an outward flaring of the distal opening **54** in the fluid delivery conduit **22**.

Turning to FIGS. 11-12, the medical device may include a mechanism or component(s) providing selective deformation or externally-actuated restriction of a length of the fluid delivery conduit **22** to modify the fluid flow characteristics therethrough. For example, as shown in FIG. 11, a deformation element **56** may be movably positioned within a portion of the medical device **12**, and further operable to apply a depressible force onto an exterior surface of the fluid delivery conduit **22** to kink or otherwise decrease the passable area, and thus fluid flow capacity, through the affected segment of the fluid delivery conduit **22**. The deformation element **56** may include a sufficiently-rigid protrusion that is controllably movable within the medical device **12** along a substantially linear path transverse to the fluid delivery conduit **22** through the use of one or more steering or actuator wires or transmission linkages (not shown) accessible to a user at a handle or proximal

end **18** of the device **12**. As shown in FIG. **12**, the deformation element **56** may include a rotatable component that contacts the fluid delivery conduit **22** at two locations in opposite directions to restrict or kink a portion of the conduit to affect fluid flow therethrough to a desired degree.

Fluid flow may further be controlled through the implementation of one or more rotational components disposed within or about the fluid flow path through the delivery conduit. For example, referring to FIG. **13**, the fluid delivery conduit **22** of the medical device **12** may include a semi-circular or rounded flange **58** disposed on a distal end thereof and circumscribing a portion of a fluid outlet **60** of the delivery conduit **22**. The fluid delivery conduit **22** and the flange **58** may be rotatable within the elongate body **16**, and the fluid outlet **60** may be off-center with respect to a central longitudinal axis of the elongate body **16** of the medical device **12**. A stopper **62** may be at least partially disposed within the elongate body **16** such that rotation of the fluid delivery conduit **22** about the fixed stopper **62** increases or decreases the percentage of the fluid outlet **60** that is unobstructed by the stopper **62**, thus modulating the fluid flowing therethrough. The rotation of the fluid delivery conduit **22** may be controlled at a proximal portion of the medical device **12**, as described in more detail below, while the flange **58** aids in securing the relative position of the fluid outlet **60** with respect to the stopper **62** and/or wall of the elongate body **16**. Turning now to FIG. **14**, the medical device may include a pivotable or rotatable valve **64** disposed within a portion of the fluid delivery conduit. The valve **64** may be selectively opened or closed to a desired degree to permit or obstruct fluid flowing through the delivery conduit.

A rate or volume of fluid flowing through the medical device **12** may further be controlled through selective opening or closing of all or part of a plurality of openings or fluid dispersion points within the medical device **12** or selectively control the amount, direction, location, size, and/or other characteristics of the dispersion area. In thermal treatment procedures, such fluid control provides the ability to directly control the resulting location, size, and other characteristics of the tissue treatment pattern. For example referring to FIGS. **15-16**, the fluid delivery conduit **22** may define a plurality of fluid openings or outlets **66**, which may be positioned adjacent to the thermally-transmissive region **46** of the medical device **12**. An elongate body or rod **68** may be slidably positioned within the delivery conduit **22** to selectively obstruct one or more of the outlets **66**. For example, in FIG. **15**, the rod **68** may be sufficiently dimensioned or sized to obstruct all of the outlets in a first position, while being movable proximally to a second position to uncover or otherwise allow fluid to flow out of a one or more of the outlets **66**, thus increasing fluid flow. In FIG. **16**, for example, the elongate body or rod **68** may have a distal plug **70** sized or dimensioned to only obstruct, at most, a portion of the fluid outlets **66**. In this example, the distal plug **70** may be selectively moved to provide spatial control over the fluid dispersion out of the fluid delivery conduit, e.g., either more-proximally or more-distally. The plurality of fluid outlets **66** may include one or more spaced subsets of outlets having a predetermined separation distance between them to achieve a desired spatial separation between the selectable locations for dispersion, and thus the resulting thermal characteristics for treatment or diagnosis.

One or more of the fluid outlets **66** may also include a directional taper or angular orientation, as shown in FIG. **17**, such that selective obstruction of the fluid outlets **66** provides directional control over the resulting fluid dispersion. Such directional control may be implemented for example, when

the thermally-transmissive region includes a balloon, and it is desirable to focus thermal exchange on a proximal portion of the balloon (for example, when directing treatment or diagnosis towards a pulmonary vein or other proximally-located tissue) or a distal portion of the balloon (for example, when directing treatment or diagnosis towards a septal wall or other distally-positioned tissue region). The directional dispersion may also be implemented with other thermally-transmissive regions, such as elongated, linear segments and other geometric configurations, for example.

Aside from and/or in addition to providing selective fluid dispersion in a proximal-distal range, the medical device may also provide selective radial or rotational dispersion of the fluid either separately or in combination with the proximal-distal range to provide a variety of longitudinally and radially controllable dispersion patterns. For example, referring to FIG. **18**, the fluid delivery conduit **22** may include a dispersion manifold **72** along a length thereof, such as adjacent to the thermally-transmissive region of the device **12**. The dispersion manifold **72** may define a plurality of openings **74** positioned around its circumference at different radial or angular positions. A rotational selector element **76** may be rotatably movable with respect to the dispersion manifold **72** to selectively disperse fluid from the fluid delivery conduit **22** out of a selected portion of the plurality of openings **74**. The rotational selector element **76** may include, for example, a sleeve having one or more openings at one or more select radial positions such that when the openings in the rotational selector element **76** are aligned with a subset of the openings in the dispersion manifold **72**, fluid is directed outward in one or more specific, selected radial directions. Though the rotational selector **76** is illustrated in FIG. **18** as being positioned within the dispersion manifold **72**, it is contemplated the rotational selector **76** may also be on the exterior of the dispersion manifold **72** and achieve the same selective dispersion when the openings are aligned. The rotational selector element **76** may be actuated or otherwise controlled with one or more wires, rods or the like extending through the medical device **12** and accessible to a user.

Turning now to FIG. **19**, the medical device may provide for selective fluid dispersion to create either a smaller-area, focal or "spot"-type lesion, or a more elongated thermal treatment pattern. For example, the medical device may include a first thermally-transmissive segment **78** having a first geometric configuration and a second thermally-transmissive segment **80** having a second geometric configuration. The two regions may be spaced apart or substantially adjacent to one another. In a particular example, the first thermally-transmissive segment **78** may include a distal tip providing a "spot"-type footprint or contact area, while the second thermally-transmissive segment **80** may include an elongated segment providing a linear or curvilinear footprint or contact area. The fluid delivery conduit **22** may again include a dispersion manifold **82**, which extends along a length of the second thermally-transmissive segment **80** and defines one or more fluid outlets **84** longitudinally and/or rotationally spaced from one another. The device **12** may include a dispersion selector **86** movably coupled to the manifold **82** to selectively disperse fluid either towards the first thermally-transmissive segment **78** or the second thermally-transmissive segment **80**. For example, the dispersion selector **86** may define a sleeve or secondary manifold slidably and/or rotationally movable with respect to the dispersion manifold **82**. The dispersion selector **86** may define one or more primary openings **88** that are alignable with one or more of the fluid outlets **84** of the dispersion manifold **82** when in a first position, thus directing fluid flow towards the second thermally-

transmissive segment **80**. The dispersion selector **86** may further define one or more secondary openings **90** that are positionable to disperse fluid towards the first thermally-transmissive segment **78** when in a second position. The second position may also include a misalignment between the primary openings **88** and the fluid outlets **84** of the manifold **82** such that fluid is prevented from being dispersed towards the second thermally-transmissive segment **80**. The secondary opening(s) **90** may be positioned on a distal end or region of the dispersion selector **86** that extends out of the manifold **82** in the second position, while being contained within the manifold **82** when the selector **86** is in the first position. There may be a seal or gasket (not shown) between the selector **86** and the manifold **82** allowing telescoping movement while restricting fluid flow to one or more of the outlets rather than between a gap or opening between the manifold **82** and the selector **86** themselves, for example.

As shown in FIGS. **16-19**, one or more of the components described above, e.g., the manifold **72,82** or selectors **76,86**, may have at least one radiopaque marker **92** to aid in identifying and manipulating a position and/or alignment of the fluid delivery components to achieve a desired rotational and/or longitudinal position and associated fluid flow or dispersion characteristics. FIG. **20** illustrates an additional example of a radiopaque marker **92** that is angularly positioned asymmetrically on a dispersion tube (which may include any of the manifolds or components described herein) to selectively direct fluid flow to one or more regions of the thermally transmissive region **46**, which in this example includes a balloon or expandable element.

Turning now to FIGS. **21-22**, examples of the medical device **12** are shown providing selective and/or movable thermal insulation about at least a portion of the thermally transmissive region **46** to provide a desired treatment or diagnosis pattern. For example, the medical device **12** may include one or more insulators **93** movably coupled to the thermally transmissive region **46** that prevent or significantly reduce energy exchange with the thermally transmissive region **46** and the surrounding environment or targeted tissue, while controllably exposing other portions of the region **46** to interact, diagnose, and/or treat a tissue region. The insulators **93** may be oriented and movable in a proximal-to-distal direction, as shown in FIG. **21**, or the insulators **93** may be oriented and movable around a radial circumference of the thermally transmissive region, as shown in FIG. **22**. The insulators may be constructed from a thermally-insulating material that is sufficiently conformable or flexible to facilitate coupling to the thermally transmissive region and/or other portions of the medical device, such as the elongate body **16**. The controllable movement of the insulators may be accomplished through the use of one or more pull wires or other actuation elements (not shown), and may be further facilitated by one or more joints, hinges, or the like providing a range of movement about the thermally-transmissive region.

Returning again to FIG. **1**, the medical device **12** may include a handle **94** coupled to the proximal portion of the elongate body **16**. The handle **94** can include circuitry for identification and/or use in controlling of the medical device **12** or another component of the system. For example, the handle **94** may include one or more pressure or flow rate sensors **96** to monitor the fluid pressure and/or flow rate within the medical device **12**. Additionally, the handle **94** may be provided with a fitting **98** for receiving a guide wire that may be passed into a guide wire lumen. The handle **94** may also include connectors **100** that are matable directly to a fluid supply/exhaust and control unit **14** or indirectly by way of one or more umbilicals. The handle **94** may further include blood

detection circuitry in fluid and/or optical communication with the injection, exhaust and/or interstitial lumens. The handle **94** may also include a pressure relief valve in fluid communication with the fluid delivery conduit **22** and/or exhaust lumen **24** to automatically open under a predetermined threshold value in the event that value is exceeded.

The handle **94** may also include one or more actuation or control features that allow a user to control, deflect, steer, or otherwise manipulate a distal portion of the medical device from the proximal portion of the medical device. For example, the handle **94** may include one or more components such as a lever or knob **102** for manipulating the elongate body **16** and/or additional components of the medical device **12**, such as the selectors, manifolds, or other fluid flow components described herein. Movement or operation of these components may be triggered or performed mechanically, electro-mechanically, and/or in conjunction with one or more sensors described herein to provide a variety of predetermined configurations and/or fluid flow sequences or patterns. For example, a pull wire **104** with a proximal end and a distal end may have its distal end anchored to the elongate body **16** at or near the distal portion **20**, such as the distal insert **26**. The proximal end of the pull wire **94** may be anchored to an element such as a cam in communication with and responsive to the lever **102**.

The medical device **12** may include an actuator element **106** that is movably coupled to the proximal portion of the elongate body **16** and/or the handle **94**. The actuator element **106** may further be coupled to a proximal portion of the fluid delivery conduit **22**, rod **50, 68**, and/or selectors **76,86** such that manipulating the actuator element **106** in a longitudinal direction causes longitudinal manipulation of the attached component. The actuator element **106** may include a thumb-slide, a push-button, a rotating lever, or other mechanical structure for providing a movable coupling to the elongate body **16** and/or the handle **94**. Moreover, the actuator element **106** may be movably coupled to the handle **44** such that the actuator element is movable into individual, distinct positions, and is able to be releasably secured in any one of the distinct positions.

The medical device **12** may include one or more rotational control elements **108** that are rotatably coupled to the proximal portion of the elongate body **16** and/or the handle **44**. The rotational control element(s) **58** may further be coupled to the proximal and/or distal ends of the fluid delivery conduit **22**, rod **50,68**, selectors **76,86**, or other fluid flow control elements described herein such that rotating the rotational control element **108** about a longitudinal axis of the handle **44** and/or elongate body **16** results in similar rotation of the attached component(s) at the distal portion of the medical device **12**. The rotational control element **108** may include a knob, dial, or other mechanical structure for providing a rotatable coupling to the elongate body **16** and/or the handle **94**. Moreover, the rotational control element **108** may be rotatably coupled to the handle **94** and/or elongate body **16** such that the rotational control element is movable into individual, distinct positions, and is able to be releasably secured in any one of the distinct positions.

The system **10** may further include one or more sensors to monitor the operating parameters throughout the system, including for example, pressure, temperature, flow rates, volume, or the like in the control unit **14** and/or the medical device **12**, in addition to monitoring, recording or otherwise conveying measurements or conditions within the medical device **12** or the ambient environment at the distal portion of the medical device **12**. The sensor(s) may be in communication with the control unit **14** for initiating or triggering one or

11

more alerts or therapeutic delivery modifications during operation of the medical device **12**. One or more valves, controllers, or the other components described herein may be in communication with the sensor(s) to provide for the automated and/or controlled dispersion or circulation of fluid through the lumens/fluid paths of the medical device **12**. Such valves, controllers, or the like may be located in a portion of the medical device **12** and/or in the control unit **14**.

In an exemplary system, a fluid supply **110** including a coolant, cryogenic refrigerant, or the like, an exhaust or scavenging system (not shown) for recovering or venting expended fluid for re-use or disposal, as well as various control mechanisms for the medical system may be housed in the control unit **14**. In addition to providing an exhaust function for the catheter fluid supply, the control unit **14** may also include pumps, valves, controllers or the like to recover and/or re-circulate fluid delivered to the handle, the elongate body, and/or the fluid pathways of the medical device **12**. A vacuum pump **112** in the control unit **14** may create a low-pressure environment in one or more conduits within the medical device **12** so that fluid is drawn into the conduit(s)/lumen(s) of the elongate body **16**, away from the distal portion and towards the proximal portion of the elongate body **16**. The control unit **14** may include one or more controllers, processors, and/or software modules containing instructions or algorithms to provide for the automated operation and performance of the features, sequences, or procedures described herein.

Several of the above configurations and methods of use thereof provide the ability to modify the effective cross-sectional area of the fluid delivery conduit available for fluid flow. Accordingly, selective control of these configurations allows fluid flow to be regulated as desired while the fluid delivery pressure remains the same. Additional configurations provided herein allow for the selective manipulation of a footprint or therapeutic pattern achievable with the medical device during a single procedure, negating the need for the removal and insertion of multiple devices to achieve the same variations in treatment geometry or characteristics. Moreover, while the medical device **12** may be in fluid communication with a cryogenic fluid source to cryogenically treat selected tissue, it is also contemplated that the medical device **12** may alternatively or additionally include one or more electrically conductive portions or electrodes thereon coupled to a radiofrequency generator or power source of the control unit **14** as a treatment or diagnostic mechanism.

It will be appreciated by persons skilled in the art that the present invention is not limited to what has been particularly shown and described herein above. In addition, unless mention was made above to the contrary, it should be noted that all of the accompanying drawings are not to scale. Of note, the system components have been represented where appropriate by conventional symbols in the drawings, showing only those specific details that are pertinent to understanding the embodiments of the present invention so as not to obscure the disclosure with details that will be readily apparent to those of ordinary skill in the art having the benefit of the description herein. Moreover, while certain embodiments or figures described herein may illustrate features not expressly indicated on other figures or embodiments, it is understood that the features and components of the system and devices disclosed herein are not necessarily exclusive of each other and may be included in a variety of different combinations or configurations without departing from the scope and spirit of the invention. A variety of modifications and variations are

12

possible in light of the above teachings without departing from the scope and spirit of the invention, which is limited only by the following claims.

What is claimed is:

1. A medical device, comprising:

a catheter body defining a distal portion having a thermally transmissive region, the thermally transmissive region defining a chamber;

a fluid delivery conduit located entirely within the catheter body and defining an outlet in fluid communication with the chamber of the thermally transmissive region;

a solid elongate member slidably disposed within at least a portion of the fluid delivery conduit, advancing and retracting the solid elongate member selectively obstructing and un-obstructing a portion of the fluid delivery conduit to modulate fluid flow through the outlet.

2. The medical device of claim **1**, further defining a fluid exhaust lumen within the catheter body.

3. The medical device of claim **1**, wherein the fluid delivery conduit defines a tapered diameter, and the elongate member is longitudinally movable with respect to the tapered diameter.

4. The medical device of claim **1**, wherein the elongate member includes a plug movably positionable about the outlet.

5. The medical device of claim **4**, wherein the plug has a tapered cross-section.

6. The medical device of claim **4**, wherein the plug is substantially spherical.

7. The medical device of claim **1**, wherein the elongate member is constructed from a shape memory material.

8. The medical device of claim **7**, wherein the shape memory material transitions in response to a thermal load.

9. The medical device of claim **7**, wherein the shape memory material transitions in response to an electrical load.

10. The medical device of claim **1**, wherein the fluid delivery conduit defines a plurality of outlet apertures in the distal portion, and the elongate member is movable to selectively obstruct one or more of the plurality of outlet apertures.

11. The medical device of claim **1**, further comprising a cryogenic fluid source in fluid communication with at least one of the fluid delivery conduit or elongate member.

12. A method of regulating fluid flow through a catheter, comprising:

delivering a fluid to a fluid delivery conduit entirely disposed within a portion of the catheter, the catheter including a thermally transmissive region in fluid communication with the fluid delivery conduit; and

moving a solid rod within a portion of the fluid delivery conduit to at least partially obstruct a portion of the fluid delivery conduit to regulate fluid flowing through the fluid delivery conduit within the catheter.

13. The method of claim **12**, wherein the fluid delivery conduit defines a tapered section, and moving the rod includes moving the rod with respect to the tapered section.

14. A medical device, comprising:

an elongate body defining a distal end, a fluid delivery conduit, a fluid exhaust conduit, and a thermally transmissive region at the distal end; and

a unitary distal insert partially disposed within the thermally transmissive region and coupled to the distal end of the elongate body, the distal insert defining:

a first lumen extending through the unitary distal insert and being in fluid communication with the fluid delivery conduit,

a second lumen extending through the unitary distal insert and being coaxial with the first lumen and being in fluid communication with the fluid exhaust conduit, and

a plurality of openings within the thermally transmissive region in fluid communication with the second lumen. 5

15. The medical device of claim **14**, wherein the unitary distal insert defines a collar and the medical device includes a steering element coupled to the collar.

16. The medical device of claim **14**, further comprising a rod movably positionable with a portion of the first lumen. 10

* * * * *